

# Networking Commands for DevOps

**1.ping** - To check the reachability of a host on an Internet Protocol (IP) network.

```
root@ip-172-31-84-148:/home/ubuntu# ping google.com
PING google.com (142.251.111.139) 56(84) bytes of data:
64 bytes from bk-in-fl39.1e100.net (142.251.111.139): icmp_seq=1 ttl=58 time=1.67 ms
64 bytes from bk-in-fl39.1e100.net (142.251.111.139): icmp_seq=2 ttl=58 time=1.66 ms
64 bytes from bk-in-fl39.1e100.net (142.251.111.139): icmp_seq=3 ttl=58 time=1.70 ms
64 bytes from bk-in-fl39.1e100.net (142.251.111.139): icmp_seq=4 ttl=58 time=1.79 ms
64 bytes from bk-in-fl39.1e100.net (142.251.111.139): icmp_seq=5 ttl=58 time=1.73 ms
64 bytes from bk-in-fl39.1e100.net (142.251.111.139): icmp_seq=6 ttl=58 time=1.69 ms
64 bytes from bk-in-fl39.1e100.net (142.251.111.139): icmp_seq=7 ttl=58 time=1.72 ms
64 bytes from bk-in-fl39.1e100.net (142.251.111.139): icmp_seq=8 ttl=58 time=1.73 ms
64 bytes from bk-in-fl39.1e100.net (142.251.111.139): icmp_seq=9 ttl=58 time=1.74 ms
```

**2. netstat** - To display active network connections, routing tables, interface statistics, masquerade connections, and multicast memberships.

```
root@ip-172-31-84-148:/home/ubuntu# netstat
Active Internet connections (w/o servers)
Proto Recv-Q Send-Q Local Address           Foreign Address         State
tcp        0      272 ip-172-31-84-148.ec:ssh ec2-18-206-107-29:13145 ESTABLISHED
tcp        0      0 ip-172-31-84-148.:58832 ec2-18-232-150-247:http TIME_WAIT
```

**3. ifconfig** - To display the configuration of network interfaces.

```
root@ip-172-31-84-148:/home/ubuntu# ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 9001
    inet 172.31.84.148 netmask 255.255.240.0 broadcast 172.31.95.255
    inet6 fe80::1087:e6ff:fe78:eee7 prefixlen 64 scopeid 0x20<link>
    ether 12:87:e6:78:ee:e7 txqueuelen 1000 (Ethernet)
    RX packets 1892 bytes 708653 (708.6 KB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 1690 bytes 232442 (232.4 KB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 258 bytes 27049 (27.0 KB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 258 bytes 27049 (27.0 KB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

**4. traceroute** - To display the route and measure transit delays of packets across an Internet Protocol network

```
root@ip-172-31-84-148:/home/ubuntu# traceroute google.com
traceroute to google.com (142.251.111.139), 64 hops max
 1  3.236.63.255  0.670ms  8.231ms  8.921ms
 2  240.3.20.98  0.442ms  0.366ms  0.326ms
 3  100.66.36.74  3.134ms  8.139ms  8.241ms
 4  240.0.236.7  0.900ms  0.835ms  0.777ms
 5  100.100.36.104  4.867ms  1.190ms  1.420ms
 6  242.2.213.199  0.970ms  1.027ms  0.935ms
 7  99.83.65.1  1.251ms  1.186ms  1.218ms
 8  100.66.52.140  0.871ms  8.230ms  8.100ms
 9  142.251.49.187  2.091ms  2.083ms  2.118ms
10  172.253.71.206  3.337ms  3.101ms  3.112ms
11  142.251.67.255  2.813ms  2.712ms  2.819ms
12  242.2.213.195  7.521ms  0.997ms  1.019ms
13  142.251.68.23  3.505ms  3.188ms  3.171ms
```

**5. mtr** - The mtr command is typically used to combine the functionalities of the ping and traceroute commands.

```
My traceroute  [v0.95]
ip-172-31-84-148 (172.31.84.148) -> youtube.com (172.253.122.91)
Keys: Help  Display mode  Restart statistics  Order of fields  quit
2024-02-16T03:50:04+0000

Host
1. (waiting for reply)
2. (waiting for reply)
3. (waiting for reply)
4. 241.0.5.11
5. 240.0.236.4
6. 100.100.34.98
7. 99.83.115.173
8. 108.170.240.97
9. 108.170.240.112
10. 216.239.48.95
11. 142.250.215.195
12. 172.253.79.84
13. 172.253.67.65
14. (waiting for reply)
15. (waiting for reply)
16. (waiting for reply)
17. (waiting for reply)
18. (waiting for reply)
19. (waiting for reply)
20. (waiting for reply)21. (waiting for reply)22. (waiting for reply)23. bh-in-f91.1e100.net

Packets
Loss% Snt Last Avg Best Wrst StDev
0.0% 17 0.5 0.5 0.4 0.5 0.0
0.0% 17 1.7 0.8 0.6 1.7 0.2
0.0% 16 0.7 2.3 0.6 12.3 3.3
0.0% 16 1.4 1.3 1.2 1.4 0.1
0.0% 16 2.5 2.1 1.6 2.9 0.4
0.0% 16 1.2 1.5 0.9 5.6 1.2
0.0% 16 1.9 2.0 1.7 2.4 0.2
0.0% 16 3.1 3.0 2.1 4.6 0.7
0.0% 16 6.7 4.0 1.6 17.8 4.9
0.0% 16 2.7 2.7 2.6 3.1 0.1
```

**6. telnet** - The telnet command can be used in one line to establish a connection to a specific host and port

```
root@ip-172-31-84-148:/home/ubuntu# telnet google.com 443
Trying 172.253.63.138...
Connected to google.com.
Escape character is '^]'.

```

**7. iwconfig**- The iwconfig command is typically used to configure wireless network interfaces on Linux systems.

```
root@ip-172-31-84-148:/home/ubuntu# iwconfig
lo          no wireless extensions.

eth0       no wireless extensions.
```

**8. dig** - To query DNS name servers for information about host addresses, mail exchanges, name servers, and related information.

```
root@ip-172-31-84-148:/home/ubuntu# dig google.com

; <<>> DiG 9.18.18-0ubuntu0.22.04.1-Ubuntu <<>> google.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 43929
;; flags: qr rd ra; QUERY: 1, ANSWER: 6, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 65494
;; QUESTION SECTION:
;google.com.                IN      A

;; ANSWER SECTION:
google.com.                83      IN      A      172.253.63.139
google.com.                83      IN      A      172.253.63.100
google.com.                83      IN      A      172.253.63.102
google.com.                83      IN      A      172.253.63.113
google.com.                83      IN      A      172.253.63.101
google.com.                83      IN      A      172.253.63.138

;; Query time: 4 msec
;; SERVER: 127.0.0.53#53(127.0.0.53) (UDP)
;; WHEN: Fri Feb 16 03:54:52 UTC 2024
;; MSG SIZE rcvd: 135
```

**9. whois** - The whois command is used to retrieve information about registered domain names, IP addresses, and autonomous system numbers.

```
The Registry database contains ONLY .COM, .NET, .EDU domains and Registrars.
Domain Name: google.com
Registry Domain ID: 2138514 DOMAIN_COM-VRSN
Registrar WHOIS Server: whois.markmonitor.com
Registrar URL: http://www.markmonitor.com
Updated Date: 2019-09-09T15:39:04+0000
Creation Date: 1997-09-15T07:00:00+0000
Registrar Registration Expiration Date: 2028-09-13T07:00:00+0000
Registrar: MarkMonitor, Inc.
Registrar IANA ID: 292
Registrar Abuse Contact Email: abusecomplaints@markmonitor.com
Registrar Abuse Contact Phone: +1.2086851750
Domain Status: clientUpdateProhibited (https://www.icann.org/epp#clientUpdateProhibited)
Domain Status: clientTransferProhibited (https://www.icann.org/epp#clientTransferProhibited)
Domain Status: clientDeleteProhibited (https://www.icann.org/epp#clientDeleteProhibited)
Domain Status: serverUpdateProhibited (https://www.icann.org/epp#serverUpdateProhibited)
Domain Status: serverTransferProhibited (https://www.icann.org/epp#serverTransferProhibited)
Domain Status: serverDeleteProhibited (https://www.icann.org/epp#serverDeleteProhibited)
Registrant Organization: Google LLC
Registrant State/Province: CA
Registrant Country: US
Registrant Email: Select Request Email Form at https://domains.markmonitor.com/whois/google.com
Admin Organization: Google LLC
Admin State/Province: CA
```

**10. wget** - The wget command is used for downloading files from the internet.

```
root@ip-172-31-84-148:/home/ubuntu# wget http://ftp.gnu.org/gnu/wget/wget2-2.0.0.tar.gz
--2024-02-16 04:08:24-- http://ftp.gnu.org/gnu/wget/wget2-2.0.0.tar.gz
Resolving ftp.gnu.org (ftp.gnu.org)... 209.51.188.20, 2001:470:142:3::b
Connecting to ftp.gnu.org (ftp.gnu.org)|209.51.188.20|80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 3565643 (3.4M) [application/x-gzip]
Saving to: 'wget2-2.0.0.tar.gz.3'

wget2-2.0.0.tar.gz.3      100%[=====] 3.40M 18.2MB/s  in 0.2s

2024-02-16 04:08:24 (18.2 MB/s) - 'wget2-2.0.0.tar.gz.3' saved [3565643/3565643]
```

**11. route** - The route command is used to view and manipulate the IP routing table in a Unix-like operating system. Here's an example of using the route command in one line to display the routing table:

```
root@ip-172-31-84-148:/home/ubuntu# route
Kernel IP routing table
Destination      Gateway          Genmask         Flags Metric Ref    Use Iface
default          ip-172-31-80-1. 0.0.0.0         UG    100    0      0 eth0
ip-172-31-0-2.e ip-172-31-80-1. 255.255.255.255 UGH    100    0      0 eth0
172.31.80.0      0.0.0.0         255.255.240.0   U    100    0      0 eth0
ip-172-31-80-1. 0.0.0.0         255.255.255.255 UH    100    0      0 eth0
```

**12. curl** - The curl command is used to transfer data to or from a server, typically using HTTP or HTTPS protocols.

```
root@ip-172-31-84-148:/home/ubuntu# curl -L https://dummy.restapiexample.com/api/v1/employees | jq
% Total    % Received % Xferd  Average Speed   Time    Time     Current
Dload  Upload   Total   Spent    Left     Speed
100 2561    0 2561    0    6482    0 --:--:-- --:--:-- --:--:-- 6500
{
  "status": "success",
  "data": [
    {
      "id": 1,
      "employee_name": "Tiger Nixon",
      "employee_salary": 320800,
      "employee_age": 61,
      "profile_image": ""
    },
    {
      "id": 2,
      "employee_name": "Garrett Winters",
      "employee_salary": 170750,
      "employee_age": 63,
      "profile_image": ""
    },
    {
      "id": 3,
      "employee_name": "Ashton Cox",
      "employee_salary": 86000,
      "employee_age": 66,
      "profile_image": ""
    },
    {
      "id": 4,
      "employee_name": "Cedric Kelly",
      "employee_salary": 433060,

```

**13. nmap** - The nmap is a powerful network scanning tool used for discovering hosts and services on a computer network.

```
Starting Nmap 7.80 ( https://nmap.org ) at 2024-02-16 04:10 UTC
Initiating Ping Scan at 04:10
Scanning google.com (172.253.63.101) [4 ports]
Completed Ping Scan at 04:10, 0.01s elapsed (1 total hosts)
Initiating Parallel DNS resolution of 1 host. at 04:10
Completed Parallel DNS resolution of 1 host. at 04:10, 0.00s elapsed
Initiating SYN Stealth Scan at 04:10
Scanning google.com (172.253.63.101) [1000 ports]
Discovered open port 443/tcp on 172.253.63.101
Discovered open port 80/tcp on 172.253.63.101
Completed SYN Stealth Scan at 04:10, 4.84s elapsed (1000 total ports)
Nmap scan report for google.com (172.253.63.101)
Host is up (0.0013s latency).
Other addresses for google.com (not scanned): 172.253.63.102 172.253.63.113 172.253.63.138 172.253.63.139 172.253.63.100 2607:f8b0:4004:cld::71 2607:f8b0:4004:cld::8b
2607:f8b0:4004:cld::64 2607:f8b0:4004:cld::e5
rDNS record for 172.253.63.101: bi-in-f101.lel00.net
Not shown: 998 filtered ports
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https
Read data files from: /usr/bin/./share/nmap
Nmap done: 1 IP address (1 host up) scanned in 4.94 seconds
Raw packets sent: 2004 (88.152KB) | Rcvd: 5 (220B)
```

**Thank you  
so much!**

**MRADUL  
SINGH**

DevOps Engineer

**CLICK HERE  
TO FOLLOW ME**