



195 lines (132 loc) · 3.6 KB

Implementation-of-filter

Aim:

To implement filters for smoothing and sharpening the images in the spatial domain.

Software Required:

Anaconda - Python 3.7

Algorithm:

Step1

Import the required libraries.

Step2

Convert the image from BGR to RGB.

Step3

Apply the required filters for the image separately.

Step4

Plot the original and filtered image by using matplotlib.pyplot.

Step5

End the program.

Program:

Developed By : NARESH M
Register Number: 212223220064



1. Smoothing Filters

i) Using Averaging Filter

```
import cv2
import matplotlib.pyplot as plt
import numpy as np
image1=cv2.imread("rome.jpg")
image2=cv2.cvtColor(image1,cv2.COLOR_BGR2RGB)
kernel=np.ones((11,11),np.float32)/169
image3=cv2.filter2D(image2,-1,kernel)
plt.figure(figsize=(9,9))
plt.subplot(1,2,1)
plt.imshow(image2)
plt.title("Original Image")
plt.axis("off")
plt.subplot(1,2,2)
plt.imshow(image3)
plt.title("Average Filter Image")
plt.axis("off")
plt.show()
```



ii) Using Weighted Averaging Filter

```
kernel1=np.array([[1,2,1],[2,4,2],[1,2,1]])/16
image3=cv2.filter2D(image2,-1,kernel1)
plt.figure(figsize=(9,9))
plt.subplot(1,2,1)
plt.imshow(image2)
plt.title("Original Image")
plt.axis("off")
plt.subplot(1,2,2)
plt.imshow(image3)
plt.title("Weighted Average Filter Image")
plt.axis("off")
plt.show()
```



iii) Using Gaussian Filter

```
gaussian_blur=cv2.GaussianBlur(image2,(33,33),0,0)
plt.figure(figsize=(9,9))
plt.subplot(1,2,1)
plt.imshow(image2)
plt.title("Original Image")
plt.axis("off")
plt.subplot(1,2,2)
plt.imshow(gaussian_blur)
plt.title("Gaussian Blur")
plt.axis("off")
plt.show()
```



iv) Using Median Filter

```
median=cv2.medianBlur(image2,13)
plt.figure(figsize=(9,9))
plt.subplot(1,2,1)
plt.imshow(image2)
plt.title("Original Image")
plt.axis("off")
plt.subplot(1,2,2)
plt.imshow(median)
plt.title("Median Blur")
plt.axis("off")
plt.show()
```



2. Sharpening Filters

i) Using Laplacian Kernel

```
kernel2=np.array([[ -1, -1, -1],[ 2, -2, 1],[ 2, 1, -1]])
image3=cv2.filter2D(image2,-1,kernel2)
plt.figure(figsize=(9,9))
plt.subplot(1,2,1)
plt.imshow(image2)
plt.title("Original Image")
plt.axis("off")
plt.subplot(1,2,2)
plt.imshow(image3)
plt.title("Laplacian Kernel")
plt.axis("off")
```



```
plt.show()
```

ii) Using Laplacian Operator


```
laplacian=cv2.Laplacian(image2,cv2.CV_64F)
plt.figure(figsize=(9,9))
plt.subplot(1,2,1)
plt.imshow(image2)
plt.title("Original Image")
plt.axis("off")
plt.subplot(1,2,2)
plt.imshow(laplacian)
plt.title("Laplacian Operator")
plt.axis("off")
plt.show()
```




OUTPUT:

1. Smoothing Filters

i) Using Averaging Filter



ii) Using Weighted Averaging Filter



iii) Using Gaussian Filter

Original Image



Gaussian Blur



iv) Using Median Filter

Original Image



Median Blur




2. Sharpening Filters

i) Using Laplacian Kernel

Original Image



Laplacian Kernel




ii) Using Laplacian Operator

Original Image



Laplacian Operator



Result:

Thus the filters are designed for smoothing and sharpening the images in the spatial domain.



main ▾

Implementation-of-filter / README.md

↑ Top

Preview

Code

Blame

Raw

