String based Programming

Q1

What will be the result of:

System.out.println(10+20+”30”+”40”);

Important
Don’t leave it..!!

String based Programming

Q2

How many objects are created in:

String s1=new String("abc");

Important
Don't leave it..!!

String based Programming

Q3

What will be output:

```
String s1=null;
System.out.println(s1.length());
```

Important
Don't leave it..!!

String based Programming

Q4

What will be output:

```
String s1="null";
System.out.println(s1.length());
```

Important
Don't leave it..!!

String based Programming

Q5

What will be output:

```
String s1="";
System.out.println(s1.length());
```

Important
Don't leave it..!!

String based Programming

Q6

What will be output:

```
String s1=null;
System.out.println(s1+"test");
```

Important
Don't leave it..!!

String based Programming

Q7

What will be output:

```
String s1=null;
String s2=null;
System.out.println(s1==s2);
```

Important
Don't leave it..!!

String based Programming

Q8

What will be output:

```
String s1=null;
String s2=null;
System.out.println(s1.equals(s2));
```

Important
Don't leave it..!!

String based Programming

Q9

What will be output:

```
String s1="abc";
String s2=null;
System.out.println(s1.equals(s2));
```

Important
Don't leave it..!!

String based Programming

Q10

What will be output:

```
String s1=null;
String s2="abc";
System.out.println(s1.equals(s2));
```

Important
Don't leave it..!!

String based Programming

Q11

What will be output:

```
String s = "java";
s.concat("rocks");
System.out.println(s);
```

Important
Don't leave it..!!

String based Programming

Q12

What will be output:

```
String s1="abc";
String s2="a"+"bc";
System.out.println(s1==s2);
```

Important
Don't leave it..!!

String based Programming

Q13

What will be output:

```
String s1="abc";
String s2="ab";
System.out.println(s1==s2+"c");
```

Important
Don't leave it..!!

String based Programming

Q14

What will be output:

```
String s1="abc";
String s2="ab";
String s3="c";
System.out.println(s1==s2+s3);
```

Important
Don't leave it..!!

String based Programming

Q15

What will be output:

```
String s1="abc";
String s2="ab";
String s3="c";
String s4=s2+s3;
System.out.println(s1==s4);
```

Important
Don't leave it..!!

String based Programming

Q16

What will be output:

```
String s1 = "x";
String s2 = s1 + "y";
String s3 = "x" + "y";
System.out.println(s2 == s3);
```

Important
Don't leave it..!!

String based Programming

Q17

What will be output:

```
String s1 = "Java";
String s2 = "8";
String s3 = s1 + s2;
System.out.println(s3 == "Java8");
```

Important
Don't leave it..!!

String based Programming

Q18

What will be output:

```
String s1 = "Java";
String s2 = "8";
String s3 = (s1 + s2).intern();
System.out.println(s3 == "Java8");
```

Important
Don't leave it..!!

String based Programming

Q19

What will be output:

```
String s = "HelloWorld";
String sub = s.substring(5);
System.out.println(sub);
```

Important
Don't leave it..!!

String based Programming

Q20

What will be output:

```
String s1 = "HelloWorld";
String s2 = s1.substring(0, 5);
String s3 = "Hello";
System.out.println(s2 == s3);
```

Important
Don't leave it..!!

String based Programming

Q21

What will be output:

```
String s1 = "HelloWorld";
String s2 = s1.substring(0, 5).intern();
String s3 = "Hello";
System.out.println(s2 == s3);
```

Important
Don't leave it..!!

String based Programming

Q22

What will be output:

```
String s = "hello";
System.out.println(s.equals(null));
```

Important
Don't leave it..!!

String based Programming

Q23

What will be output:

```
String s = null;
System.out.println(s.equals("test"));
```

Important
Don't leave it..!!

String based Programming

Q24

What will be output:

```
String s1 = new String("hello");
String s2 = s1.intern();
String s3 = "hello";
System.out.println(s2 == s3);
```

Important
Don't leave it..!!

String based Programming

Q25

What will be output:

```
String s = "banana";
s.replace('a', 'b');
System.out.println(s);
```

Important
Don't leave it..!!

String based Programming

Q26

What will be output:

```
String s = null;
System.out.println(String.valueOf(s));
```

Important
Don't leave it..!!

String based Programming

Q27

What will be output:

```
StringBuilder sb = new StringBuilder("abc");
String s = sb.toString();
System.out.println(s == "abc");
```

Important
Don't leave it..!!

String based Programming

Q28

What will be output:

```
String s1 = "abc";
String s2 = s1.toUpperCase();
String s3 = s2.toLowerCase();
System.out.println(s1 == s3);
```

Important
Don't leave it..!!

String based Programming

Q29

What will be output:

```
String s = new String(null);
System.out.println(s);
```

Important
Don't leave it..!!

String based Programming

Q30

What will be output:

```
System.out.println(null == null);
```

Important
Don't leave it..!!

String based Programming

Q31

What will be output:

```
String s1=null;
String s2=null;
System.out.println(s1==s2);
```

Important
Don't leave it..!!

String based Programming

Q32

What will be output:

```
System.out.println(String.join("-", "a", "b", "c"));
```

Important
Don't leave it..!!

String based Programming

Q33

What will be output:

```
String s1 = "abc";
String s2 = new String("abc");
System.out.println(s1.hashCode() == s2.hashCode());
```

Important
Don't leave it..!!

String based Programming

Q34

What will be output:

```
public class Test {
    public static void main(String[] args) {
        String s = "abc";
        change(s);
        System.out.println(s);
    }
    static void change(String s) {
        s = "xyz";
    }
}
```

Important
Don't leave it..!!

String based Programming

Q35

What will be output:

```
public class Test {
    public static void main(String[] args) {
        StringBuilder s = new StringBuilder("abc");
        change(s);
        System.out.println(s);
    }
    static void change(StringBuilder s) {
        s.append("xyz");
    }
}
```

Important
Don't leave it..!!

String based Programming

Q36

What will be output:

```
String s = String.format("Value is: %d", 100);
System.out.println(s);
```

Important
Don't leave it..!!

String based Programming

Q37

What will be output:

```
StringBuilder sb1 = new StringBuilder("hello");
StringBuilder sb2 = new StringBuilder("hello");
System.out.println(sb1.equals(sb2));
```

Important
Don't leave it..!!

String based Programming

Q38

What will be output:

```
StringBuffer sb1 = new StringBuffer("abc");
StringBuffer sb2 = new StringBuffer("abc");
System.out.println(sb1.equals(sb2));
```

Important
Don't leave it..!!

String based Programming

Q39

Which of the following is **most efficient** for string concatenation?

Options:

A) String s = "Java" + " " + "Programming";

B)StringBuilder sb = new StringBuilder(); sb.append("Java").append(" ").append("Programming");

C)StringBuffer sb = new StringBuffer(); sb.append("Java").append(" ").append("Programming");

D) Both B and C

String based Programming

Q40

What will be output:

```
void modify(String s) {
    s = "new";
}
String s = "old";
modify(s);
System.out.println(s);
```

Important
Don't leave it..!!

String based Programming

Q41

What will be output:

```
String s = "abc";
System.out.println(new StringBuilder(s).reverse());
```

Important
Don't leave it..!!

String based Programming

Q42

What will be output:

```
StringBuilder sb = new StringBuilder("Java");
sb.append("123").append("ABC");
System.out.println(sb);
```

Important
Don't leave it..!!

String based Programming

Q43

What will be output:

```
StringBuilder sb = new StringBuilder("Hello");
System.out.println(sb.capacity());
```

Important
Don't leave it..!!

String based Programming

Q44

What will be output:

```
StringBuilder sb = new StringBuilder();
Sb.append("Hello");
System.out.println(sb.capacity());
```

Important
Don't leave it..!!

String based Programming

Q45

What will be output:

```
StringBuilder sb = new StringBuilder();
sb.append(null);
System.out.println(sb);
```

Important
Don't leave it..!!

String based Programming

Q46

What will be output:

```
StringBuffer sb = new StringBuffer("JavaIsFun");
sb.delete(4, 6);
System.out.println(sb);
```

Important
Don't leave it..!!

String based Programming

Q47

What will be output:

```
StringBuilder sb = null;
sb.append("abc");
System.out.println(sb);
```

Important
Don't leave it..!!

String based Programming

Q48

What will be output:

```
StringBuffer sb = new StringBuffer("Java");
sb.setCharAt(2, 'X');
System.out.println(sb);
```

Important
Don't leave it..!!

String based Programming

Q49

For which class equal(Object) method is not overridden?

a)String

b)StringBuilder

c)StringBuffer

d)Both b and c

Important
Don't leave it..!!