Programiz C++ Online Compiler | Programiz PRO

main.cpp | Share | Run | Output | Clear

```cpp
#include <stdio.h>
#include <stdlib.h>

struct Node {
    int data;
    struct Node *next;
};

int main() {
    struct Node *head, *first, *second;

    head = (struct Node*)malloc(sizeof(struct Node));
    first = (struct Node*)malloc(sizeof(struct Node));
    second = (struct Node*)malloc(sizeof(struct Node));

    head->data = 60;
    head->next = first;

    first->data = 75;
    first->next = second;

    second->data = 90;
    second->next = NULL;


    struct Node *newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = 10;
```

```
10->60->75->90->NULL

=== Code Execution Successful ===
```

Programiz C++ Online Compiler | Programiz PRO

main.cpp | Share | Run | Output | Clear

```cpp
    second = (struct Node*)malloc(sizeof(struct Node));

    head->data = 60;
    head->next = first;

    first->data = 75;
    first->next = second;

    second->data = 90;
    second->next = NULL;


    struct Node *newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = 10;
    newNode->next = head;
    head = newNode;

    struct Node *temp = head;
    while (temp != NULL) {
        printf("%d->", temp->data);
        temp = temp->next;
    }
    printf("NULL");

    return 0;
}
```

```
10->60->75->90->NULL

=== Code Execution Successful ===
```