

## STRAIGHT BILL OF LADING-SHORT FORM

BILL OF LADING NO. 1487848

ORIGINAL - NOT NEGOTIABLE

RECEIVED, subject to the classifications and tariffs in effect on the date of the issue of this Bill of Lading

FROM: NUCOR STEEL - ARKANSAS  
AT: 7301 EAST COUNTY ROAD 142  
BLYTHEVILLE, AR 72315

TELEPHONE: 870/762-2100  
DATE: 12/23/25  
Load Req # 1570225

Subject to Section 7 of the terms and conditions of this bill of lading, if the shipment is to be delivered to a consignee without recourse, on the condition, the consignee shall sign the following statement:  
The carrier may refuse to make delivery of this shipment without payment of freight and other lawful charges.

Per NUCOR

If charges are to be prepaid, rate of freight, etc., to be prepaid.

Prepaid

The property described below, in apparent good order, except as noted (conditions and condition of contents of packages, weight, marks, etc.), and declared as indicated below, which kind and value the shipper hereby declares, is being shipped by the carrier named herein, to the destination named herein, and the carrier is not responsible for any loss or damage to the property during transit, except as specifically agreed to in writing by the shipper and carrier.

Shipper hereby certifies that he is familiar with all the terms and conditions of this bill of lading, including those on the back hereof, and the said terms and conditions are hereby agreed to by the shipper and accepted for itself and its assigns.

## SHIP TO:

NUCOR BUILDING SYSTEMS-TEXAS  
NUCOR BUILDING SYSTE  
600 APACHE TRAIL  
TERRELL, TX 75160

## SOLD TO:

NUCOR BLDG SYSTEMS TEXAS  
600 APACHE TRAIL

TERRELL, TX 75160  
UNITED STATES

ROUTE: PRESTON

CAR OR

TICKET #

CARRIER: PRESTON RICHEY TRUCKING

VEHICLE NO: 31

1570225

| COIL NUMBER                                                                                                                                                                                                                                                                                                                                                                                         | CUST ORDER NO | DESCRIPTION                                                | LENGTH         | WEIGHT   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------------------------------------------------|----------------|----------|
| 2115023.1000 TX-0013183                                                                                                                                                                                                                                                                                                                                                                             |               | .0940 MIN X 14.0600 MIN Ord H503160-1                      | 2833.000       |          |
| Heat: 2157562                                                                                                                                                                                                                                                                                                                                                                                       | 156832        | HRO A1011SSG55<.10 /Mill Part CP099BK1406                  | 13406.00       |          |
| 2115023.2000 TX-0013183                                                                                                                                                                                                                                                                                                                                                                             |               | .0940 MIN X 14.0600 MIN Ord H503160-1                      | 2833.000       |          |
| Heat: 2157562                                                                                                                                                                                                                                                                                                                                                                                       | 156833        | HRO A1011SSG55<.10 /Mill Part CP099BK1406                  | 13406.00       |          |
| 2115023.3000 TX-0013183                                                                                                                                                                                                                                                                                                                                                                             |               | .0940 MIN X 14.0600 MIN Ord H503160-1                      | 2833.000       |          |
| Heat: 2157562                                                                                                                                                                                                                                                                                                                                                                                       | 156834        | HRO A1011SSG55<.10 /Mill Part CP099BK1406                  | 13406.00       |          |
| Melted and Manufactured In the USA.                                                                                                                                                                                                                                                                                                                                                                 |               |                                                            | Charged Weight | 40218.00 |
| Heat                                                                                                                                                                                                                                                                                                                                                                                                | C             | Mn P S Si Cu Ni Cr Mo Sn Al V Nb N                         |                |          |
| 2157562                                                                                                                                                                                                                                                                                                                                                                                             | .230          | .99 .009 .0014 .02 .09 .03 .04 .01 .005 .04 .004 .000 .007 |                |          |
|                                                                                                                                                                                                                                                                                                                                                                                                     | Ti: .002      | B: .000 Ca: .003                                           |                |          |
| <p>RECEIVING HOURS----7AM TO 2PM MONDAY THROUGH FRIDAY<br/>CM LOADS MUST BE TARPED!!!!!!<br/>TO MAKE APPTS EMAIL NBGTX.RECEIVING@NUCOR.ONMICROSOFT.COM<br/>APPOINTMENTS ARE REQUIRED FOR DELIVERY<br/>SHEETED MATERIAL MUST BE LOADED FOR FORK SIDE UNLOADING<br/>COILS THAT LOAD OUTSIDE DO NOT TARP<br/>*****<br/>TRUCKS ARE TO BE TURNED<br/>OFF AND KEYS TURNED IN<br/>TO AN NBGTX RECEIVER</p> |               |                                                            |                |          |
| SPECIAL INSTRUCTIONS                                                                                                                                                                                                                                                                                                                                                                                |               |                                                            |                |          |

NUCOR STEEL - ARKANSAS  
P.O. BOX 30  
ARMOREL, ARKANSAS 72310

SHIPPER'S  
SIGNATURE:

DBAKER

Carrier acknowledges receipt of the property described above in good order and condition.

PER  
CARRIER'S  
SIGNATURE:

SHIPPING

Permanent post office address of shipper

REVISION 09-7-05-23

FRM-001-SHIP

BLSC110A

|                                                                                                           |                  |                                                                               |                                  |                                                                                   |               |                        |            |             |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
|-----------------------------------------------------------------------------------------------------------|------------------|-------------------------------------------------------------------------------|----------------------------------|-----------------------------------------------------------------------------------|---------------|------------------------|------------|-------------|-------|---------|-----|----|-----|----|-----|----|-----|---|------|----|------|----|------|---|------|----|------|----|------|
| NUCOR STEEL - ARKANSAS                                                                                    |                  | METALLURGICAL TEST                                                            |                                  | Total Wgt: 40,218 LBS                                                             |               | Date Printed: 12/23/25 |            | Page 1 of 1 |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
| A Division of Nucor Corp<br>7301 East County Road 142<br>Blytheville, AR 72315<br>Telephone: 870/762-2100 |                  | Sold To:<br>NUCOR BLDG SYSTEMS TEXAS<br>600 APACHE TRAIL<br>TERRELL, TX 75160 |                                  | Ship To:<br>NUCOR BUILDING SYSTEMS-TEXAS<br>600 APACHE TRAIL<br>TERRELL, TX 75160 |               |                        |            |             |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
| Order/Line                                                                                                | H503160-1        | Product                                                                       | HOT ROLL OUTSIDE PROCESS         |                                                                                   | B/L #         | 1487846                | Ship Date  | 12/23/25    |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
| P/O Number                                                                                                | TX-0012183       | Dimensions                                                                    | .0940 MIN X 14.3600 MIN (INCHES) |                                                                                   |               |                        | Vehicle #  | 31          |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
| Description                                                                                               | A1011-25 SS GR35 |                                                                               |                                  |                                                                                   |               |                        | Ticket #   | 1570225     |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
|                                                                                                           |                  |                                                                               |                                  |                                                                                   |               |                        | Issue Date | 12/18/25    |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
| With the following modifications: Customer Part Number CP099BK1406                                        |                  |                                                                               |                                  |                                                                                   |               |                        |            |             |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
| Heat                                                                                                      | 2157562          | Coil ID                                                                       | 2115023.1000                     | 2115023.2000                                                                      | 2115023.3000  |                        |            |             |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
|                                                                                                           |                  |                                                                               | 13,406.00 Lbs                    | 13,406.00 Lbs                                                                     | 13,406.00 Lbs |                        |            |             |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
| Heat                                                                                                      | 2157562          | C                                                                             | .23                              | Mn                                                                                | .99           | P                      | .009       | S           | .0014 | Si      | .02 | Cr | .04 | Ni | .03 | Al | .04 | V | .004 | Nb | .000 | Ti | .002 | B | .000 | Ca | .003 | Sb | .001 |
| Coil                                                                                                      | Test             | Val UOM                                                                       | Test                             | Val UOM                                                                           | Test          | Val UOM                | Test       | Val UOM     | Test  | Val UOM |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
| 2115023.1000                                                                                              | L YIELD          | 66.0 KSI                                                                      | L TENSILE                        | 88.9 KSI                                                                          | L ELONG       | 22 %                   |            |             |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
| 2115023.2000                                                                                              | L YIELD          | 66.0 KSI                                                                      | L TENSILE                        | 88.9 KSI                                                                          | L ELONG       | 22 %                   |            |             |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |
| 2115023.3000                                                                                              | L YIELD          | 66.0 KSI                                                                      | L TENSILE                        | 88.9 KSI                                                                          | L ELONG       | 22 %                   |            |             |       |         |     |    |     |    |     |    |     |   |      |    |      |    |      |   |      |    |      |    |      |

All goods are sold subject to the description, specifications and terms and conditions set forth on the face and reverse side, or otherwise provided with. Nucor Steel is order acknowledgement.

Tensile specimens are tested in accordance with ASTM A-370 specification; standard rectangular test configuration (Figure 3) with 2 inch gauge length and a 0.25 offset yield method. Steel is aluminum killed and produced to a fine grain practice.

This material has been produced in compliance with the chemistry and established rolling practices of the ordered specification. If material is ordered to a chemistry only, testing is not performed by producer.

Materials certified to most current revision of ASTM specifications.

We hereby certify the above is correct as contained in the records of the corporation.

100% MELTED AND ROLLED IN THE U.S.

Andrew Nix  
Hot Mill Metallurgist

Rev. 12/13/13

FRM-014-RM

# PURCHASE ORDER



PO Number: TX-0013183

Date: 10/23/2025

**This Purchase Order Number must appear on all Packages, Invoices and Packing Slips.**

Nucor Building Systems Texas  
600 Apache Trail  
Terrell, TX 75160  
USA

PH: Sales Tax Exempt  
No.:

Vendor: V000160  
NUCOR HICKMAN  
PO BOX 30  
ARMOREL, AR 72310  
USA

Vendor  
Contact:  
PH:

FAX:

Ship To: Nucor Building Systems  
600 Apache Trail  
Terrell, TX 75160  
USA

Job ID:  
Job Name:

Deliveries to NBGTx are by appointment only

Phone: (972) 210-4941

Email: nbgtx.receiving@nucor.onmicrosoft.com

Hours: Monday - Friday from 6:00am - 2:00pm CST

**\*\*MUST BE MELTED AND MANUFACTURED IN USA\*\***

Application: Structural Steel Buildings

ASTM A1011-18a SS Grade 55, No Oil, Slit Edge

Dimensional Tolerances per ASTM A568

Minimum Yield Strength (Fy) = 55 ksi / Minimum Tensile Strength (Fu) = 70 ksi

Coil Widths to be -0" + 1/8"

Minimum Coil I.D. = 19" / Maximum Coil I.D. = 21" / Maximum Coil O.D. = 68"

Maximum (Banded) Coil Weight = 44,000#

Loading Instructions: Coils are to be loaded with the eye to the side, slit coils banded together

Freight: Prepaid & Add

| Buyer:            | Payment Terms: | Delivery Terms: | Shipping Method: | Cash discount |
|-------------------|----------------|-----------------|------------------|---------------|
| Christina Roberts | Net30          |                 |                  |               |

| L/N | Item Number | Description                                                       | Req. Date  | U/M | Ordered   | Unit Price | Ext. Price |
|-----|-------------|-------------------------------------------------------------------|------------|-----|-----------|------------|------------|
| 1   | CP099BK1406 | .099" (.094" min)<br>x 14.0625" Black Coil<br><br>Account: 130001 | 12/13/2025 | LBS | 41,000.00 | 0.44120    | 18,089.20  |
| 2   | CP099BK2044 | .099" (.094" min)<br>x 20.4375" Black Coil                        | 12/13/2025 | LBS | 38,000.00 | 0.47790    | 18,160.20  |

# PURCHASE ORDER

| L/N             | Item Number | Description                                        | Req. Date  | U/M | Ordered   | Unit Price | Ext. Price |
|-----------------|-------------|----------------------------------------------------|------------|-----|-----------|------------|------------|
| Account: 130001 |             |                                                    |            |     |           |            |            |
| 3               | CP105BK1675 | .105" (.100" min-.107" max)<br>x 16.75" Black Coil | 12/13/2025 | LBS | 40,000.00 | 0.44860    | 17,944.00  |
| Account: 130001 |             |                                                    |            |     |           |            |            |
| 4               | CP120BK1675 | .120" (.114" min)<br>x 16.75" Black Coil           | 12/13/2025 | LBS | 42,000.00 | 0.44860    | 18,841.20  |
| Account: 130001 |             |                                                    |            |     |           |            |            |
| 5               | CP120BK2044 | .120" (.114" min)<br>x 20.4375" Black Coil         | 12/13/2025 | LBS | 42,000.00 | 0.47790    | 20,071.80  |
| Account: 130001 |             |                                                    |            |     |           |            |            |

Shipper to ensure all products are properly packaged, loaded and blocked to prevent any movement or shifting during transit and unloading. Delivering driver is responsible for safely removing straps, tie-down, etc. and following all Division safety rules and procedures.



Authorized Signature

|                    |           |
|--------------------|-----------|
| Order Total (USD): | 93,106.40 |
|--------------------|-----------|

By acceptance and acknowledgement of this order, vendor agrees to furnish materials and/or services in accordance with all terms and conditions provided.

W  
C  
P  
D  
E  
G  
S  
T  
N  
S  
G  
O  
U  
P

COL INSPECTOR SHEET

DATE: 12-29-25

[illegible]

CONFIDENTIAL

|       | I.D. |      | O.D. |         | Width |        | Weight |
|-------|------|------|------|---------|-------|--------|--------|
|       | min. | max. | max. | max.    | max.  | (lb)   |        |
| Wall  | 19"  | 21"  | 70"  | 60 7/8" |       | 40,000 |        |
| Pin   | 19"  | 30"  | 70"  | 60 7/8" |       | 40,000 |        |
| Web   | 25"  | 30"  | 70"  | 60 7/8" |       | 40,000 |        |
| Panel | 19"  | 21"  | 65"  | 48"     |       | 20,000 |        |

Notes: If 1.25 coefficients than 1.9 the coefficient and 1.9 must be marked

USE FOR MED ONLY DO NOT REUSE

Figure 1 shows a vertical sequence of 15 diagrams illustrating the stages of a cell cycle. The diagrams are arranged in a column, with the cell at the top and the two daughter cells at the bottom. The stages are labeled with numbers 1 through 15, and some are labeled with the names of the stages: Prophase, Metaphase, Anaphase, and Telophase. The diagrams show the progression from a single cell to two daughter cells, with the nucleus and chromosomes visible in each stage.

REV. LIZ ROSEN

2020

| Design | Painted |       | Galv.   |       |
|--------|---------|-------|---------|-------|
|        | coating | min   | coating | min   |
| 28 ga. | C40     | .0164 | AZ55    | .0160 |
| 26 ga. | G90/C60 | .0197 | AZ50    | .0184 |
| 26 ga. | G30     | .0198 | —       | —     |
| 26 ga. | AZ50    | .0199 | —       | —     |
| 24 ga. | G90     | .0141 | AZ55    | .0229 |
| 24 ga. | AZ50    | .0242 | —       | —     |
| 24 ga. | AZ55    | .0244 | —       | —     |
| 22 ga. | AZ55    | .0302 | AZ55    | .0287 |

SECRET

| Design | min. | max. |
|--------|------|------|
| .054   | .051 | .055 |
| .060   | .057 | .064 |
| .067   | .064 | .071 |
| .071   | .067 | .074 |
| .075   | .071 | .078 |
| .076   | .072 | .078 |
| .086   | .082 | .088 |
| .089   | .085 | .092 |
| .098   | .093 | .099 |
| .099   | .094 | .102 |
| .105   | .100 | .107 |
| .120   | .114 | .121 |

| Design | min. | max. |
|--------|------|------|
| 1.25*  | .417 | .433 |
| .134   | .126 | .142 |
| .140   | .142 | .158 |
| .164   | .156 | .172 |
| .115   | .167 | .183 |
| .188   | .178 | .198 |
| .200   | .190 | .210 |
| .220   | .211 | .230 |
| .225   | .216 | .234 |
| .250   | .240 | .280 |
| .275   | .265 | .305 |
| .313   | .303 | .343 |
| .375   | .365 | .405 |
| .500   | .490 | .530 |