


Variant-calling Workflow

Markus Mayrhofer

What is a workflow





Today:

- Basic variant calling workflow for one sample
- Extend to multiple samples

Tomorrow:

- GATK's Best practices



Example: Basic workflow, one sample

HG00097_1.fastq

HG00097_2.fastq

FASTQ files

Alignment

HG00097.bam

BAM files

VariantCalling

HG00097.vcf

VCF files




Workflow conventions



1. Create a new output file in each process
2. Don't overwrite the input file
3. Use informative file names
4. Include information of the process + sample
5. Correct name extension e.g. .bam, .vcf, ...

GATK's best practices workflow for germline short variant discovery



Basic Variant Calling in one sample

Alignment



HG00097_1.fastq

HG00097_2.fastq

FASTQ files

BWA mem

HG00097.bam

BAM files

HaplotypeCaller

HG00097.vcf

VCF files




The reference genome

A reference genome is a haploid nucleic acid sequence which represents a species genome.

The first draft of the human genome contained 150,000 gaps.

GRCh37: 250 gaps

We will work with GRCh37 in the lab.



Keep track of the reference version!



The reference genome sequence is used as input in many bioinformatics applications for NGS data:

- mapping
- variant calling
- annotation

You must keep track of which version of the reference genome your data was mapped to.

The same version must be used in all downstream analyses.

AACAGGTATATCTTCCCCGCTAGCTAGCTAGCTA**GCTAGCTAGCTAGCTACCCT**CTTCCTTAGGGACTGTAC
GCTAGCTAGCTAGCTACCCT

Burrows-Wheeler Aligner



<http://bio-bwa.sourceforge.net>

Burrows-Wheeler Aligner

[Home](#)

Introduction

BWA is a software package for mapping low-divergent sequences against a large reference genome, such as the human genome. It consists of three algorithms: BWA-backtrack, BWA-SW and BWA-MEM. The first algorithm is designed for Illumina sequence reads up to 100bp, while the rest two for longer sequences ranging from 70bp to 1Mbp. BWA-MEM and BWA-SW share similar features: long-read support and split alignment, but BWA-MEM, which is the generally recommended for high-quality queries as it is faster and more accurate. BWA-MEM also has better performance than BWA-backtrack for 70-100bp reads.

FAQ

How can I cite BWA?

The short read alignment component (bwa-short) has been published in:
Li H. and Durbin R. (2009) Fast and accurate short read alignment with Burrows-Wheeler Transform. Bioinformatics, 25:1754-60. [PMID: 19451168]

If you use BWA-SW, please cite:

Li H. and Durbin R. (2010) Fast and accurate long-read alignment with Burrows-Wheeler Transform. Bioinformatics, Epub. [PMID: 20111653]

(See also Errata below for a minor correction to the formulae in the above papers.)


There are three algorithms, which one should I choose?

For 70bp or longer Illumina, 454, Ion Torrent and Sanger reads, contigs and BAC sequences, BWA-MEM is usually the preferred algorithm. For short sequences, BWA-backtrack may be better. BWA-SW may be better for longer sequences.

BWA:

[SF project page](#)

Burrows-Wheeler transform of reference genome



Output from mapping - Sam format



HEADER SECTION

```
@HD VN:1.6SO:coordinate
@SQ SN:2 LN:243199373
@PG ID:bwaPN:bwaVN:0.7.17-r1188 CL:bwa mem -t 1 human_g1k_v37_chr2.fasta HG00097_1.fq HG00097_2.fq
@PG ID:samtools PN:samtools PP:bwaVN:1.10 CL:samtools sort
@PG ID:samtools.1 PN:samtools PP:samtools VN:1.10 CL:samtools view -H HG00097.bam
```

ALIGNMENT SECTION

Read_001	99	2	3843448	0	101M	=	3843625	278	TTTGGTTCCATATGAACTTT	0F<BFB<FFFBFBFFFBFB
Read_001	147	2	3843625	0	101M	=	3843448	-278	TTATTTTCATTGAGCAGTGGT	FBBI7IIFIB<BBBB<BBFF
Read_002	163	2	4210055	0	101M	=	4210377	423	TGGTACCAAAACAGAGATAT	0IIFBFFFIIIFIFIFFBFB
Read_003	99	2	4210066	0	101M	=	4210317	352	CAGAGATATAGATCAATGGA	0IIFFFIFFFIFIFIIIIIF

Read name
(usually more
complicated)

Reference sequence name

Start position

Sequence

Quality

Convert to Bam



Bam file is a binary representation of the Sam file



- Most large files we work with, such as the reference genome (**.fasta**) and the aligned reads (**.bam**) need an index
- The index is a small file
- Allows efficient access to the large file
- Different indices for different file types
- BWA index = Burrows-Wheeler transform of reference genome (**several files**)



Variant calling

HG00097_1.fastq

HG00097_2.fastq

FASTQ files

BWA mem

HG00097.bam

BAM files

HaplotypeCaller


HG00097.vcf

VCF files





Genetic variation



Genetic variation = differences in DNA among individuals of the same species

Alignment



Detecting variants in reads



Reference:

...GTGCGTAGACTGCTAGATCGAAGA...

Sample:

...GTGCGTAGACTG**A**TAGATCGAAGA...

...GTGCGTAGACTG**A**TAGATCGAAGA...

...GTGCGTAGACTGCTAGATCGAAGA...

...GTGCGTAGACTGCTAGATCGAAGA...

...GTGCGTAGACTG**A**TAGATCGAAGA...

...GTGCGTAGACTG**A**TAGATCGAAGA...

...GTGCGTAGACTGCTAGATCGAAGA...

...GTGCGTAGACTG**A**TAGATCGAAGA...

...GTGCGTAGACTGCTAGATCGAAGA...

...GTGCGTAGACTG**A**TAGATCGAAGA...

Reference- and alternative alleles



TGGGCTTTTCCAACAGGTATATCTTCCCCGCTAGCTCGCTAGCTACTTCAAATTCCT


Reference allele AGCTCGCTA

Alternative allele AGCTAGCTA

Reference allele = the allele in the reference genome

Alternative allele = the allele NOT in the reference genome

Variant Call Format (VCF)



Variant Call Format (VCF)



```
##fileformat=VCFv4.2
##FILTER=<ID=LowQual,Description="Low quality">
##FORMAT=<ID=AD,Number=R,Type=Integer,Description="Allelic depths for the ref and alt alleles in the order listed">
##FORMAT=<ID=DP,Number=1,Type=Integer,Description="Approximate read depth (reads with MQ=255 or with bad mates are filtered)">
##FORMAT=<ID=GT,Number=1,Type=String,Description="Genotype">
##INFO=<ID=AC,Number=A,Type=Integer,Description="Allele count in genotypes, for each ALT allele, in the same order as listed">
##INFO=<ID=AF,Number=A,Type=Float,Description="Allele Frequency, for each ALT allele, in the same order as listed">
##INFO=<ID=AN,Number=1,Type=Integer,Description="Total number of alleles in called genotypes">
##contig=<ID=2,length=243199373>
##source=HaplotypeCaller
#CHROM  POS      ID      REF      ALT      QUAL      FILTER      INFO      FORMAT      HG00097
2       136220992  .       G        GT       30.64     .          AC=1;AF=0.500;AN=2  GT:AD:DP    0/1:3,2:5
2       136226814  .       GAC      G        44.60     .          AC=1;AF=0.500;AN=2  GT:AD:DP    0/1:4,2:6
2       136234279  .       C        T        102.60    .          AC=1;AF=0.500;AN=2  GT:AD:DP    0/1:3,4:7
2       136234284  .       C        T        102.60    .          AC=1;AF=0.500;AN=2  GT:AD:DP    0/1:3,4:7
2       136263277  .       T        A        148.60    .          AC=1;AF=0.500;AN=2  GT:AD:DP    0/1:8,5:13
...
...
```



Basic workflow, one sample

HG00097_1.fastq

HG00097_2.fastq

FASTQ files

Alignment

HG00097.bam

BAM files

VariantCalling

HG00097.vcf

VCF files



Variant Call Format (VCF)




```
##fileformat=VCFv4.2
##FILTER=<ID=LowQual,Description="Low quality">
##FORMAT=<ID=AD,Number=R,Type=Integer,Description="Allelic depths for the ref and alt alleles in the order listed">
##FORMAT=<ID=DP,Number=1,Type=Integer,Description="Approximate read depth (reads with MQ=255 or with bad mates are filtered)">
##FORMAT=<ID=GT,Number=1,Type=String,Description="Genotype">
##INFO=<ID=AC,Number=A,Type=Integer,Description="Allele count in genotypes, for each ALT allele, in the same order as listed">
##INFO=<ID=AF,Number=A,Type=Float,Description="Allele Frequency, for each ALT allele, in the same order as listed">
##INFO=<ID=AN,Number=1,Type=Integer,Description="Total number of alleles in called genotypes">
##contig=<ID=2,length=243199373>
##source=HaplotypeCaller
#CHROM  POS      ID      REF      ALT      QUAL      FILTER      INFO      FORMAT      HG00097
2       136220992  .       G        GT       30.64     .          AC=1;AF=0.500;AN=2  GT:AD:DP    0/1:3,2:5
2       136226814  .       GAC      G        44.60     .          AC=1;AF=0.500;AN=2  GT:AD:DP    0/1:4,2:6
2       136234279  .       C        T        102.60    .          AC=1;AF=0.500;AN=2  GT:AD:DP    0/1:3,4:7
2       136234284  .       C        T        102.60    .          AC=1;AF=0.500;AN=2  GT:AD:DP    0/1:3,4:7
2       136263277  .       T        A        148.60    .          AC=1;AF=0.500;AN=2  GT:AD:DP    0/1:8,5:13
...
...
```


Basic variant calling in cohort






Basic variant calling in cohort




GVCF Files are valid VCFs with extra information



- GVCF has records for all sites, whether there is a variant call there or not.
- The records include an accurate estimation of how confident we are in the determination that the sites are homozygous-reference or not.
- Adjacent non-variant sites merged into blocks



Basic variant calling in cohort



Variant Call Format (VCF)



```
##fileformat=VCFv4.2
##ALT=<ID=NON_REF,Description="Represents any possible alternative allele at this location">
##FILTER=<ID=LowQual,Description="Low quality">
##FORMAT=<ID=AD,Number=R,Type=Integer,Description="Allelic depths for the ref and alt alleles in the order listed">
##FORMAT=<ID=DP,Number=1,Type=Integer,Description="Approximate read depth (reads with MQ=255 or with bad mates are filtered)">
##FORMAT=<ID=GT,Number=1,Type=String,Description="Genotype">
##INFO=<ID=AC,Number=A,Type=Integer,Description="Allele count in genotypes, for each ALT allele, in the same order as listed">
##INFO=<ID=AF,Number=A,Type=Float,Description="Allele Frequency, for each ALT allele, in the same order as listed">
##INFO=<ID=AN,Number=1,Type=Integer,Description="Total number of alleles in called genotypes">
##contig=<ID=2,length=243199373>
##source=CombineGVCFs
##source=GenotypeGVCFs
##source=HaplotypeCaller
```

#CHROM	POS	ID	REF	ALT	QUAL	FILTER	INFO	FORMAT	HG00097	HG00100	HG00101
2	136045826	.	G	A	167.26	.	AC=1;AF=0.167;AN=6	GT:AD:DP	0/0:8,0:8	0/0:13,0:13	0/1:1,5:6
2	136046443	.	CGT	C	129.27	.	AC=3;AF=0.500;AN=6	GT:AD:DP	0/0:8,0:8	0/1:3,1:4	1/1:0,4:4
2	136047387	.	T	C	186.27	.	AC=1;AF=0.167;AN=6	GT:AD:DP	0/0:6,0:6	0/0:16,0:16	0/1:4,6:10
2	136048649	.	C	G	127.26	.	AC=1;AF=0.167;AN=6	GT:AD:DP	0/0:13,0:13	0/0:9,0:9	0/1:1,4:5
2	136052318	.	C	T	107.26	.	AC=1;AF=0.167;AN=6	GT:AD:DP	0/0:7,0:7	0/0:13,0:13	0/1:3,3:6

Today's lab



1000 Genomes data



- Low coverage WGS data
- 3 samples
- Small region on chromosome 2

About the samples:

<https://www.internationalgenome.org/data-portal/sample>

The Lactase enzyme





Figure 2. Lactose digestion in the intestine.

- All mammals produce lactase as infants
- Some human produce lactase in adulthood
- Genetic variation upstream of the *LCT* gene cause the lactase persistent phenotype (lactose tolerance)

The Lactase enzyme



Part 1:

Variant calling in one sample

Basic variant calling in one sample



HG00097_1.fastq

HG00097_2.fastq

FASTQ files

BWA mem

HG00097.bam

BAM files

HaplotypeCaller

HG00097.vcf

VCF files




Part 2:

Variant calling in cohort



Joint variant calling workflow



Workflow conventions



1. Create a new output file in each process
2. Don't overwrite the input file
3. Use informative file names
4. Include information of the process + sample
5. Correct name extension e.g. .bam, .vcf, ...

Part 3:

Follow GATK best practices for short variant discovery



[User Guide](#)[Tool Index](#)[Blog](#)[Forum](#)[DRAGEN-GATK](#)[Events](#)[Download GATK4](#)[Sign in](#)

Genome Analysis Toolkit

Variant Discovery in High-Throughput Sequencing Data




Developed in the Data Sciences Platform at the [Broad Institute](#), the toolkit offers a wide variety of tools with a primary focus on variant discovery and genotyping. Its powerful processing engine and high-performance computing features make it capable of taking on projects of any size. [Learn more](#)

Find answers to your questions. Stay up to date on the latest topics. Ask questions and help others.


**Getting Started**
Best practices, tutorials, and other info to get you started

**Technical Documentation**
Algorithms, glossary, and other detailed resources

**Announcements**
Blog and events

**Tool Index**
Purpose, usage and options for each tool

**Forum**
Ask our team for help and report issues

**GATK Showcase on Terra**
Check out these fully configured workspaces


**DRAGEN-GATK**
Learn more about DRAGEN-GATK

**Download latest version of GATK**
The GATK package download includes all released GATK tools


**Run on Cloud**

**Run on HPC**

GATK's best practices workflow for germline short variant discovery




Mark Duplicates



Duplicate reads



- PCR duplicates - library preparation
- Optical duplicates - sequencing
- Don't add unique information
- Gives false allelic ratios of variants
- Should be removed/marked





Need Help?

Search our documentation

MarkDuplicates



[GATK](#) / [Tool Index](#) / 4.0.1.1

MarkDuplicates (Picard)

[Follow](#)



GATK Team


10 months ago · Updated

Identifies duplicate reads.

This tool locates and tags duplicate reads in a BAM or SAM file, where duplicate reads are defined as originating from a single fragment of DNA. Duplicates can arise during sample preparation e.g. library construction using PCR. See also [EstimateLibraryComplexity](#) for additional notes on PCR duplication artifacts. Duplicate reads can also result from a single amplification cluster, incorrectly detected as multiple clusters by the optical sensor of the sequencing instrument. These duplication artifacts are referred to as optical duplicates.

```
gatk --java-options -Xmx7g MarkDuplicates \  
  -I input.bam \  
  -O marked_duplicates.bam \  
  -M marked_dup_metrics.txt
```

Base Quality Score Recalibration (BQSR)





- During base calling, the sequencer estimates a quality score for each base. This is the quality scores present in the fastq files.
- Systematic (non-random) errors in the base quality score estimation can occur.
 - due to the physics or chemistry of the sequencing reaction
 - manufacturing flaws in the equipment
 - etc
- Can cause bias in variant calling
- **Base Quality Score Recalibration** helps to calibrate the scores so that they correspond to the real per-base sequencing error rate (phred scores)


[User Guide](#)
[Tool Index](#)
[Blog](#)
[Forum](#)
[DRAGEN-GATK](#)
[Events](#)

Need Help?

Search our documentation



[GATK](#) / [Technical Documentation](#) / [Algorithms](#)

Base Quality Score Recalibration (BQSR)

[Follow](#)


GATK Team

5 days ago · Updated

BQSR stands for Base Quality Score Recalibration. In a nutshell, it is a data pre-processing step that detects systematic errors made by the sequencing machine when it estimates the accuracy of each base call.

*Note that this **base** recalibration process (BQSR) should not be confused with **variant** recalibration (VQSR), which is a sophisticated filtering technique applied on the variant callset produced in a later step. The developers who named these methods wish to apologize sincerely to anyone, especially Spanish-speaking users, who get tripped up by the similarity of these names.*

Contents

1. Overview
2. Base recalibration procedure details
3. Important factors for successful recalibration
4. Examples of pre- and post-recalibration metrics
5. Recalibration report

Articles in

ActiveRe
(Haploty

Evaluatir
and varia
Mutect2)


Local re-
determin
Mutect2)

Allele-sp
germline

Variant C

Evaluatir
variant c:

Filter variants




<https://software.broadinstitute.org/gatk/best-practices/>
Germline short variant discovery (SNPs + Indels)




- Remove low quality variants
- Variant quality score recalibration (VQSR):
 - For large data sets (>1 WGS or >30WES samples)
 - GATK has a machine learning algorithm that can be trained to recognise "likely false" variants
 - **We do recommend to use VQSR when possible!**
- Hard filters:
 - For smaller data sets
 - Hard filters on information in the VCF file
 - For example: Flag variants with "QD < 2" and "MQ < 40.0"
 - GATK discussion on hard filters:
<https://gatkforums.broadinstitute.org/gatk/discussion/2806/howto-apply-hard-filters-to-a-call-set>

Part 3:



More details and links to GATK for each step is found in the lab instructions.

GATK's best practises



First look at video
about this linked from
schedule!

Questions?






User GuideTool IndexBlogForumDRAGEN-GATKEventsDownload GATK4Sign in


Genome Analysis Toolkit

Variant Discovery in High-Throughput Sequencing Data




Developed in the Data Sciences Platform at the [Broad Institute](#), the toolkit offers a wide variety of tools with a primary focus on variant discovery and genotyping. Its powerful processing engine and high-performance computing features make it capable of taking on projects of any size. [Learn more](#)

Find answers to your questions. Stay up to date on the latest topics. Ask questions and help others.




Getting Started

Best practices, tutorials, and other info to get you started




Technical Documentation

Algorithms, glossary, and other detailed resources




Announcements

Blog and events




Tool Index

Purpose, usage and options for each tool




Forum

Ask our team for help and report issues




GATK Showcase on Terra

Check out these fully configured workspaces




DRAGEN-GATK

Learn more about DRAGEN-GATK




Download latest version of GATK

The GATK package download includes all released GATK tools



Run on Cloud



Run on HPC

Read groups



- Link *sample id*, *library prep*, *flowcell* and *sequencing run* to the reads.
- Good for error tracking!
- Often needed for variant calling
- Detailed description at <https://gatkforums.broadinstitute.org/gatk/discussion/6472/read-groups>

RGID = *combination of the sample id and run id*

RGLB = Library prep

RGPL = Platform (for us ILLUMINA)

RGPU = Run identifier *usually barcode of flowcell*

RGSM = Sample name