

HPC Introduction

High-performance computing

2026-03-02

Martin Dahlö
martin.dahlo@nbis.se

Enabler for Life Sciences

What is PDC, what it provides

Projects at PDC

How to access PDC

Jobs and queuing systems

How to use the resources of PDC

Parallelldatorcentrum

<http://www.pdc.kth.se>

1 computer cluster, **Dardel**

Parallelldatorcentrum

<http://www.pdc.kth.se>

1 computer cluster, **Dardel**

- 1 278 nodes
 - 128 cores each, 163 584 in total
 - 256 GB RAM, also 512, 1024, 2048

Parallelldatorcentrum

<http://www.pdc.kth.se>

1 computer cluster, **Dardel**

- 1 278 nodes
 - 128 cores each, 163 584 in total
 - 256 GB RAM, also 512, 1024, 2048
- 18 PB fast parallel storage

Parallelldatorcentrum

<http://www.pdc.kth.se>

1 computer cluster, **Dardel**

- 1 278 nodes
 - 128 cores each, 163 584 in total
 - 256 GB RAM, also 512, 1024, 2048
- 18 PB fast parallel storage
- Bioinformatics **software**


The basic structure of supercomputer



Login nodes

node = computer

The basic structure of supercomputer




Calculation nodes




Login nodes

node = computer

The basic structure of supercomputer



Calculation nodes



Storage




Login nodes

node = computer

The basic structure of a supercomputer

Parallel computing
Not one super fast



The basic structure of a supercomputer

Parallel computing
Not one super fast



What is PDC, what it provides

Projects at PDC

How to access PDC

Jobs and queuing systems

How to use the resources of PDC

PDC provides its resources via


projects

PDC provides its resources via

projects

compute
(core-hours/month)

storage
(GB)



Two separate projects:

NAISS compute:

cluster **Dardel**

2000 - 100 000+ core-hours/month

512 GB storage

NAISS Storage:

storage system **Klemming**

1 - 100+ TB storage

Projects



[Start](#)
[Rounds](#)
[Resources](#)
[Support](#)
[Login](#)

Your are not logged in.

[Start](#) / [Rounds](#)

Rounds

Resources are made available through rounds, in which projects proposals are made. First, you need to select the type of round to use:

Compute Rounds

Access to ~~general~~ resources for high performance computing.

[Go to Compute Rounds](#)

Storage Rounds

Access to storage resources at centres and nation-wide.

[Go to Storage Rounds](#)

LUMI Rounds

Access to the Swedish part of the LUMI high performance computing and storage resources.

[Go to LUMI Rounds](#)

AI/ML

Access to resources specifically for AI and Machine Learning.

[Go to AI/ML Rounds](#)

NAISS SENS

Access to HPC resources specifically for analyzing sensitive data.

[Go to NAISS SENS](#)

Swedish Science Cloud

Access to NAISS cloud resources.

[Go to Swedish Science Cloud](#)

You can also view all rounds (including closed and decided).

<https://supr.naiss.se/round/>

Projects



[Start](#)
[Rounds](#)
[Resources](#)
[Support](#)
[Login](#)

Your are not logged in.

[Start](#) / [Rounds](#) / [Compute Rounds](#)

Compute Rounds

HPC resources are made available through compute rounds. There are three different sizes of NAISS allocated rounds, as well as local rounds at centres. Select the size of round to use:

NAISS Small Compute

Up to 10 000 core-hours/month.
Continuous evaluation of proposals during the year. To apply, you must be a scientist in Swedish academia, at least at the level of PhD student.

[Go to NAISS Small Compute](#)

NAISS Medium Compute

Monthly evaluation of proposals during the year. To apply, you must be a scientist in Swedish academia, at least at the level of assistant professor.

[Go to NAISS Medium Compute](#)

NAISS Large Compute

Evaluation of proposals twice a year with a peer-review procedure. To apply, you must be a scientist in Swedish academia, at least at the level of assistant professor.

[Go to NAISS Large Compute](#)

Centre Local Compute

Local resources that are not allocated via NAISS. Conditions are described per round.

[Go to Centre Local Compute](#)

<https://supr.naiss.se/round/>

Projects



[Start](#)
[Rounds](#)
[Resources](#)
[Support](#)
[Login](#)

Your are not logged in.

[Start](#) / [Rounds](#) / [NAISS Small Compute 2024](#)

NAISS Small Compute 2024

Open for Proposals

To apply, you must be a scientist in Swedish academia, at least at the level of PhD student.

Deadlines and Decisions

Proposals are processed weekly. Note that staff will be on vacation during the summer and proposals submitted in July will be processed at a reduced pace.

This round is open for proposals until 2025-01-01 00:00.

[Create New Proposal for NAISS Small Compute 2024](#)

Resources

Resource	Centre	Upper		Unit	Note
		Limit	Available		
▶ Alvis	C3SE	1 000	80 000	GPU-h/month	The Alvis resource is dedicated for AI/ML research.
▶ Tetralith	NSC	10	1 500	x 1000 core-h/month	
▶ Dardel	PDC	10	1 720	x 1000 core-h/month	
▶ Dardel-GPU	PDC	200	6 160	GPU-h/month	
▶ Rackham	UPPMAX	10	1 500	x 1000 core-h/month	Restrictive policy for NEW projects on Rackham.

Click ▶ above to show more information about the resource.

<https://supr.naiss.se/round/>

What is PDC what it provides

Projects at PDC

How to access PDC

Jobs and queuing systems

How to use the resources of PDC

SSH to Dardel

```
ssh -Y your_username@dardel.pdc.kth.se
```

Requires setting up either SSH keys or Kerberos

<https://support.pdc.kth.se/doc/basics/quickstart/>

SSH to Dardel

```
ssh -Y your_username@dardel.pdc.kth.se
```

Requires setting up either **SSH keys** or Kerberos

<https://support.pdc.kth.se/doc/basics/quickstart/>

SSH to Dardel

```
user@computer ~ $ ssh -Y username@dardel.pdc.kth.se  
Last login: Mon Nov 11 10:19:30 2024 from icm-42-29.bmc.uu.se
```

```
--== Welcome to Dardel! ==--
```


```
username@login1 ~ $
```





Local
computer



Login
nodes



Computation
nodes



Login nodes

use them to access PDC,
never use them to run **jobs**

Calculation nodes

do your work here - testing and running,
not accessible directly,
SLURM (queueing system) gives you access

What is PDC, what it provides

Projects at PDC

How to access PDC

Jobs and queuing systems

How to use the resources of PDC

Job (computing)

From Wikipedia, the free encyclopedia

For other uses, see [Job \(Unix\)](#) and [Job stream](#).

In [computing](#), a **job** is a unit of work or unit of execution (that performs said work). A component of a job (as a unit of work) is called a [task](#) or a *step* (if sequential, as in a [job stream](#)). As a unit of execution, a job may be concretely identified with a single [process](#), which may in turn have subprocesses ([child processes](#); the process corresponding to the job being the [parent process](#)) which perform the tasks or steps that comprise the work of the job; or with a [process group](#); or with an abstract reference to a process or process group, as in [Unix job control](#).

Read/open files

Do something with the data


Print/save output

Queue System


More users than nodes
Need for a queue




More users than nodes
Need for a queue



More users than nodes
Need for a queue



More users than nodes
Need for a queue



workload manager

job queue

batch queue

job scheduler

SLURM (Simple Linux Utility for Resource Management)

free and open source

What is PDC, what it provides

Projects at PDC

How to access PDC

Jobs and queuing systems

How to use the resources of PDC

1) Ask for resource and run jobs manually

For testing, possibly small jobs, specific programs needing user input while running

2) Write a script and submit it to SLURM

Submits an automated job to the job queue, runs when it's your turn

1) Ask for resource and run jobs manually

book a node/core



ssh to the node



run programs

1) Ask for resource and run jobs manually

```
salloc -A naiss2099-99-999 -p shared -c 1 -t 00:05:00
```

salloc - command

mandatory job parameters:

- A** - project ID (who “pays”)
- p** - partition
- c** - number of cores
- t** - time

```
salloc -A naiss2099-99-999 -p shared -c 1 -t 00:05:00
```

-A example course project naiss2099-99-999
you have to be a member


```
salloc -A naiss2099-99-999 -p shared -c 1 -t 00:05:00
```

-A example course project naiss2099-99-999
you have to be a member

-p shared = parts of 1 node 1 node = 128 cores)
main = whole nodes 1 hour walltime = 128 core-hours

```
salloc -A naiss2099-99-999 -p shared -c 1 -t 00:05:00
```

-A example course project naiss2099-99-999
you have to be a member

-p shared = parts of 1 node 1 node = 128 cores)
main = whole nodes 1 hour walltime = 128 core-hours

-c number of cores (default value = 1)

```
salloc -A naiss2099-99-999 -p shared -c 1 -t 00:05:00
```

-A example course project naiss2099-99-999
you have to be a member

-p shared = parts of 1 node 1 node = 128 cores)
main = whole nodes 1 hour walltime = 128 core-hours

-c number of cores (default value = 1)

-t format - hh:mm:ss
or - dd-hh:mm:ss
default value= 7-00:00:00

jobs killed when time limit reaches - always overestimate ~ 50%

Information about your jobs

```
squeue -u <user>
```

```
username@login1 ~ $ squeue -u username
```

JOBID	PARTITION	NAME	USER	ST	TIME	NODES	NODELIST(REASON)
5236781	shared	interact	username	R	20:41	1	nid002582

```
username@login1 ~ $
```

SSH to a calculation node (from a login node)

```
ssh -Y <node_name>
```

```
username@login1 ~ $ salloc -A naiss2099-99-999 -t 01:00:00 -p shared -c 1
```

```
username@login1 ~ $ salloc -A naiss2099-99-999 -t 01:00:00 -p shared -c 1
salloc: Pending job allocation 5236781
salloc: job 5236781 queued and waiting for resources
salloc: job 5236781 has been allocated resources
salloc: Granted job allocation 5236781
salloc: Nodes nid002582 are ready for job
username@login1 ~ $
```

```
username@login1 ~ $ salloc -A naiss2099-99-999 -t 01:00:00 -p shared -c 1
salloc: Pending job allocation 5236781
salloc: job 5236781 queued and waiting for resources
salloc: job 5236781 has been allocated resources
salloc: Granted job allocation 5236781
salloc: Nodes nid002582 are ready for job
username@login1 ~ $ squeue -u username
```



```
username@login1 ~ $ salloc -A naiss2099-99-999 -t 01:00:00 -p shared -c 1
salloc: Pending job allocation 5236781
salloc: job 5236781 queued and waiting for resources
salloc: job 5236781 has been allocated resources
salloc: Granted job allocation 5236781
salloc: Nodes nid002582 are ready for job
username@login1 ~ $ squeue -u username
```

JOBID	PARTITION	NAME	USER	ST	TIME	NODES	NODELIST (REASON)
5236781	shared	interact	username	R	0:10	1	nid002582

```
username@login1 ~ $
```

```
username@login1 ~ $ salloc -A naiss2099-99-999 -t 01:00:00 -p shared -c 1
salloc: Pending job allocation 5236781
salloc: job 5236781 queued and waiting for resources
salloc: job 5236781 has been allocated resources
salloc: Granted job allocation 5236781
salloc: Nodes nid002582 are ready for job
username@login1 ~ $ squeue -u username
```

JOBID	PARTITION	NAME	USER	ST	TIME	NODES	NODELIST (REASON)
5236781	shared	interact	username	R	0:10	1	nid002582

```
username@login1 ~ $ ssh -Y nid002582
```


```
username@login1 ~ $ salloc -A naiss2099-99-999 -t 01:00:00 -p shared -c 1
salloc: Pending job allocation 5236781
salloc: job 5236781 queued and waiting for resources
salloc: job 5236781 has been allocated resources
salloc: Granted job allocation 5236781
salloc: Nodes nid002582 are ready for job
username@login1 ~ $ squeue -u username
  JOBID PARTITION      NAME      USER ST   TIME   NODES NODELIST(REASON)
   5236781   shared interact username  R    0:10      1 nid002582
username@login1 ~ $ ssh -Y nid002582
username@nid002582 ~ $
```




Local
computer




Login
nodes



Computation
nodes





2) Write a script and submit it to SLURM

put all commands in a text file - script



tell SLURM to run the script
(use the same job parameters)

2) Write a script and submit it to SLURM

put all commands in a text file - script

```
#!/bin/bash -l
#SBATCH -A XXXXXXXX
#SBATCH -p shared
#SBATCH -J Template_script
#SBATCH -t 01:00:00

# load some modules
module load bioinfo-tools

# go to some directory
cd ~/testarea

# do something
echo Hello world!
```


2) Write a script and submit it to SLURM

put all commands in a text file - script

```
#!/bin/bash -l
#SBATCH -A XXXXXXXX
#SBATCH -p shared
#SBATCH -J Template_script
#SBATCH -t 01:00:00
```

job parameters

```
# load some modules
module load bioinfo-tools

# go to some directory
cd ~/testarea

# do something
echo Hello world!
```

tasks to be done

2) Write a script and submit it to SLURM

put all commands in a text file - script

```
#!/bin/bash -l
#SBATCH -A naiss2099-99-999
#SBATCH -p shared
#SBATCH -J sample_001.fq_alignment
#SBATCH -t 7-00:00:00

# load some modules
module load bioinfo-tools bwa

# go to project directory
cd /cfs/klemming/projects/supr/naiss2099-99-999/

# align reads
bwa mem ref/human_reference.fa raw/sample_001.fq | samtools sort -o results/sample_001.aligned.sorted.bam
```

2) Write a script and submit it to SLURM

tell SLURM to run the script
(use the same job parameters)

```
sbatch test.sh
```

2) Write a script and submit it to SLURM

tell SLURM to run the script
(use the same job parameters)

```
sbatch test.sh
```

sbatch - command

test.sh - name of the script file

2) Write a script and submit it to SLURM

tell SLURM to run the script
(use the same job parameters)

```
sbatch test.sh
```

```
sbatch -A naiss2099-99-999 -p main -c 8 -t 60:00:00 test.sh
```

Prints to a file instead of terminal

```
username@login1 ~/test $ ll
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $
```

Prints to a file instead of terminal

```
username@login1 ~/test $ ll
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $ cat test.sh
```

Prints to a file instead of terminal

```
username@login1 ~/test $ ll
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $ cat test.sh
#!/bin/bash -l
#SBATCH -A naiss2099-99-999
#SBATCH -p shared
#SBATCH -J echo_test
#SBATCH -t 00:01:00

# go to home directory
cd ~/test

# print stuff
echo "Hello, this will be printed to the slurm-<jobID>.out"

username@login1 ~/test $
```


Prints to a file instead of terminal

```
username@login1 ~/test $ ll
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $ cat test.sh
#!/bin/bash -l
#SBATCH -A naiss2099-99-999
#SBATCH -p shared
#SBATCH -J echo_test
#SBATCH -t 00:01:00

# go to home directory
cd ~/test

# print stuff
echo "Hello, this will be printed to the slurm-<jobID>.out"

username@login1 ~/test $ sbatch test.sh
```

Prints to a file instead of terminal

```
username@login1 ~/test $ ll
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $ cat test.sh
#!/bin/bash -l
#SBATCH -A naiss2099-99-999
#SBATCH -p shared
#SBATCH -J echo_test
#SBATCH -t 00:01:00

# go to home directory
cd ~/test

# print stuff
echo "Hello, this will be printed to the slurm-<jobID>.out"

username@login1 ~/test $ sbatch test.sh
Submitted batch job 5831681
username@login1 ~/test $
```

Prints to a file instead of terminal

```
username@login1 ~/test $ ll
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $ cat test.sh
#!/bin/bash -l
#SBATCH -A naiss2099-99-999
#SBATCH -p shared
#SBATCH -J echo_test
#SBATCH -t 00:01:00

# go to home directory
cd ~/test

# print stuff
echo "Hello, this will be printed to the slurm-<jobID>.out"

username@login1 ~/test $ sbatch test.sh
Submitted batch job 5831681
username@login1 ~/test $ ll
```

Prints to a file instead of terminal

```
username@login1 ~/test $ ll
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $ cat test.sh
#!/bin/bash -l
#SBATCH -A naiss2099-99-999
#SBATCH -p shared
#SBATCH -J echo_test
#SBATCH -t 00:01:00

# go to home directory
cd ~/test

# print stuff
echo "Hello, this will be printed to the slurm-<jobID>.out"

username@login1 ~/test $ sbatch test.sh
Submitted batch job 5831681
username@login1 ~/test $ ll
-rw----- 1 username username 252 Nov 11 13:43 slurm-5831681.out
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $
```

Prints to a file instead of terminal

```
username@login1 ~/test $ ll
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $ cat test.sh
#!/bin/bash -l
#SBATCH -A naiss2099-99-999
#SBATCH -p shared
#SBATCH -J echo_test
#SBATCH -t 00:01:00

# go to home directory
cd ~/test

# print stuff
echo "Hello, this will be printed to the slurm-<jobID>.out"

username@login1 ~/test $ sbatch test.sh
Submitted batch job 5831681
username@login1 ~/test $ ll
-rw----- 1 username username 252 Nov 11 13:43 slurm-5831681.out
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $ cat slurm-5831681.out
```

Prints to a file instead of terminal

```
username@login1 ~/test $ ll
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $ cat test.sh
#!/bin/bash -l
#SBATCH -A naiss2099-99-999
#SBATCH -p shared
#SBATCH -J echo_test
#SBATCH -t 00:01:00

# go to home directory
cd ~/test

# print stuff
echo "Hello, this will be printed to the slurm-<jobID>.out"

username@login1 ~/test $ sbatch test.sh
Submitted batch job 5831681
username@login1 ~/test $ ll
-rw----- 1 username username 252 Nov 11 13:43 slurm-5831681.out
-rw----- 1 username username 209 Nov 11 13:43 test.sh
username@login1 ~/test $ cat slurm-5831681.out
Hello, this will be printed to the slurm-<jobID>.out
username@login1 ~/test $
```

100+ programs installed

Managed by a 'module system'

- Installed, but hidden

- Manually loaded before use

100+ programs installed

Managed by a 'module system'

Installed, but hidden

Manually loaded before use

module avail

- Lists all available modules

module load <module name>

- Loads the module

module unload <module name>

- Unloads the module

module list

- Lists loaded modules

module spider <word>

- Searches all modules after 'word'

Most bioinfo programs hidden under bioinfo-tools
Load bioinfo-tools first, then program module

```
username@login1 ~ $ module load cufflinks
```

Most bioinfo programs hidden under bioinfo-tools
Load bioinfo-tools first, then program module

```
username@login1 ~ $ module load cufflinks
```

```
Lmod has detected the following error:  These module(s) or  
extension(s) exist but cannot be loaded as requested:  
"cufflinks"
```

Most bioinfo programs hidden under bioinfo-tools
Load bioinfo-tools first, then program module

```
username@login1 ~ $ module load cufflinks
```

```
Lmod has detected the following error:  These module(s) or  
extension(s) exist but cannot be loaded as requested:  
"cufflinks"
```

```
username@login1 ~ $ module load bioinfo-tools
```

Most bioinfo programs hidden under bioinfo-tools
Load bioinfo-tools first, then program module

```
username@login1 ~ $ module load cufflinks
```

```
Lmod has detected the following error:  These module(s) or  
extension(s) exist but cannot be loaded as requested:  
"cufflinks"
```

```
username@login1 ~ $ module load bioinfo-tools
```

```
username@login1 ~ $ module load cufflinks
```

Most bioinfo programs hidden under bioinfo-tools
Load bioinfo-tools first, then program module

```
username@login1 ~ $ module load cufflinks
```

```
Lmod has detected the following error:  These module(s) or  
extension(s) exist but cannot be loaded as requested:  
"cufflinks"
```

```
username@login1 ~ $ module load bioinfo-tools
```

```
username@login1 ~ $ module load cufflinks
```

or

```
username@login1 ~ $ module load bioinfo-tools cufflinks
```

username@login1 ~ \$ module avail

```
----- /pdcc/software/eb/modules/all
  angsd/0.940                                googletest/1.8.1                ncurses/6.4                    (L,D)
  ant/1.10.14                               gperf/3.0.4                  nextflow/24.04.2
  apr/1.7.0                                 gperf/3.1                    (D)  ninja/1.10.2
  argtable/2.13                             groff/1.23.0                 ninja/1.11.0
  autoconf-archive/2022.02.11              gsl/2.3                      ninja/1.11.1
  autoconf/2.69                             gsl/2.7.1                   (D)  ninja/1.12.1                    (D)
  autoconf/2.71                             (D)  guile/2.0.14                ntcards/1.2.1
  autodiff/0.5.10                           gzip/1.10                    onetbb/2021.5.0
  autodiff/0.6.5                           (D)  gzip/1.12                    opari2/2.0.6
  automake/1.16.1                           gzip/1.13                   (D)  openexr/3.2.0
  automake/1.16.4                           haploeagle/2.4.1            openjpeg/2.5.0
  automake/1.16.5                           (D)  harfbuzz/8.2.2              osmesa/21.3.7
  autotools/20220317                       hdf/4.2.16-2                ospray/2.4.0
  bamm/2.5.0                               help2man/1.49.2              otf2/2.3
  bamsifter/2.15.0                         hifiasm/0.19.7              otf2/3.0.3                    (D)
  bamtools/2.5.2                           highway/1.2.0                paml/4.9j
  barrnap/0.9                              hisat2/2.2.1                pango/1.50.14
  bazel/6.3.1                              htsslib/1.15.1              paraflly/0.1.0
  bbmap/38.61b                             htsslib/1.20                (L,D) parallel/20230422
  bbmap/39.01                              hwloc/2.6.0                 parasail/2.6.2
  bbmap/39.06                             (D)  hwloc/2.9.0                 patchelf/0.14.5
  bcftools/1.15.1                          hwloc/2.11.1                (D)  pbbam/1.0.7
  bcftools/1.20                            (D)  icu/69.1                   pbccopper/1.8.0
  bcl2fastq2/2.20.0                       icu/74.1                    (D)  pblat/2.5.1
  bedtools/2.31.0                         imagemagick/7.1.0-32        pcre/8.45
  bifrost/1.0.6.4                         imath/3.1.9                 pcre2/10.40
```

PDC Commands

projinfo

(only on login node)

```
username@login1 ~ $ projinfo
```

projinfo

(only on login node)

```
username@login1 ~ $ projinfo
```

```
$HOME folder
```

```
Path: /cfs/klemming/home/u/username
```

```
Storage: 12.34 GiB
```

```
Number of files: 83135
```

```
Project info for all projects for user: username
```

```
Information for compute project: uppmx.staff (PI: username)
```

```
Test allocation for UPPMAX
```

```
Active from 2023-10-01 00:00:00 to 2027-01-01 00:00:00
```

```
Members: username, username01, username02
```

```
dardel: 10000 corehours/month, used 12.52% (1252 corehours) during the past 30 days
```

```
Information for compute project: naiss2024-5-11 (PI: username)
```

```
SNIC systems access for application experts
```

```
Active from 2024-01-09 00:00:00 to 2025-02-01 00:00:00
```

```
Members: username, username01
```

```
dardel: 2000 corehours/month, used 0.00% (0 corehours) during the past 30 days
```


projinfo

(only on login node)

```
username@login1 ~ $ projinfo
```

```
$HOME folder
```

```
Path: /cfs/klemming/home/u/username
```

```
Storage: 12.34 GiB
```

```
Number of files: 83135
```

```
Project info for all projects for user: username
```

```
Information for compute project: uppmx.staff (PI: username)
```

```
Test allocation for UPPMAX
```

```
Active from 2023-10-01 00:00:00 to 2027-01-01 00:00:00
```

```
Members: username, username01, username02
```

```
dardel: 10000 corehours/month, used 12.52% (1252 corehours) during the past 30 days
```

```
Information for compute project: naiss2024-5-11 (PI: username)
```

```
SNIC systems access for application experts
```

```
Active from 2024-01-09 00:00:00 to 2025-02-01 00:00:00
```

```
Members: username, username01
```

```
dardel: 2000 corehours/month, used 0.00% (0 corehours) during the past 30 days
```

Take-home messages

- The difference between **user account** and **project**

Take-home messages

- The difference between **user account** and **project**
- **Login nodes** are not for running jobs

Take-home messages

- The difference between **user account** and **project**
- **Login nodes** are not for running jobs
- SLURM gives you access to the **compute nodes** when you specify a project that you are member of

Take-home messages

- The difference between **user account** and **project**
- **Login nodes** are not for running jobs
- SLURM gives you access to the **compute nodes** when you specify a project that you are member of
- Do not ask for more cores/nodes than your job can actually use

Take-home messages

- The difference between **user account** and **project**
- **Login nodes** are not for running jobs
- SLURM gives you access to the **compute nodes** when you specify a project that you are member of
- Do not ask for more cores/nodes than your job can actually use
- A job script usually consists of:
 - Job settings (-A, -p, -c, -t)
 - Modules to be loaded
 - Bash code to perform actions
 - Run a program, or multiple programs

Laboratory time! (again)

https://nbisweden.github.io/workshop-ngsintro/2603/topics/hpc/intro/lab_intro.html