



DEPLOYMENT MAP

Версия: 1.0.0

Дата: 2026-06-13



DEPLOYMENT TOPOLOGY

Dev Environment

Node: home_aio (primary), laptop_control (local)

Source: Feature branches

Trigger: Manual / PR

```
laptop_control (dev)
  ↓ git push
home_aio
  ↓ docker-compose up
Preview environment running
```

Stage Environment

Node: home_aio (primary), work_server (isolated)

Source: Pull requests

Trigger: PR merge to staging

```
GitHub (staging branch)
  ↓ CI/CD or manual
home_aio or work_server (stage containers)
  ↓ docker-compose -f docker-compose.stage.yml
Stage environment running
```

Production Environment

Node: work_server ONLY

Source: main branch

Trigger: Manual approval from laptop_control

```
laptop_control
  ↓ ssh work_server
  ↓ git pull origin main
  ↓ docker-compose pull
```

```
↓ docker-compose up -d  
Production rollout complete
```

PROJECT SEPARATION

Messenger Ecosystem

Domain: balloo.su

Node: work_server

Containers:

- messenger (port 3000)
- api-server (port 3001)
- admin-portal (port 3002)
- postgres (shared)
- redis (shared)

DEPLOYMENT COMMANDS

From laptop_control:

```
# Dev deployment to home_aio  
ssh home_aio  
cd /opt/balloo/dev  
git pull  
docker-compose -f docker-compose.dev.yml up -d  
  
# Stage deployment  
ssh work_server  
cd /opt/balloo/stage  
git pull origin staging  
docker-compose -f docker-compose.stage.yml up -d  
  
# Production deployment  
ssh work_server  
cd /opt/balloo/prod  
git pull origin main  
docker-compose pull  
docker-compose up -d  
docker-compose logs -f
```

SOURCE OF TRUTH

Production:

- Code: GitHub (main branch)
- Config: work_server .env + home_nas backup
- Database: PostgreSQL on work_server
- Artifacts: home_nas backup

Separation:

- Separate Docker networks per environment

Создано: 2026-06-13

 **Balloo**