



MESSENGER NODE BINDING

Версия: 1.0.0

Дата: 2026-06-13



MESSENGER ECOSYSTEM TO NODES

balloo.su Ecosystem

Primary Node: work_server



WORK_SERVER

Services MUST live here:

Production:

- ☒ API Server (Express.js) - api.balloo.su
- ☒ Messenger Web App - balloo.su
- ☒ Admin Portal - admin.balloo.su
- ☒ PostgreSQL database
- ☒ Redis cache
- ☒ WebSocket server
- ☒ Reverse proxy (Nginx/Caddy)

Optional:

- ☐ Ollama (heavy AI models)
- ☐ Open WebUI

Public Exposure:

- ☒ balloo.su (Messenger)
 - ☒ api.balloo.su (API)
 - ☒ admin.balloo.su (Admin)
 - ☒ Internal endpoints (must NOT be public)
-



HOME_AIO

Services MAY live here:

Dev/Staging:

- ☐ Dev environment (feature branches)
 - ☐ Preview environments
 - ☐ Stage testing
-

Boundaries:

- ✗ NOT production source of truth
 - ✗ NOT for production data
 - ○ Sync with work_server repositories
-

 CONTROL_PLANE

Access Points:

laptop_control:

- ☒ Development (VS Code / Koda)
- ☒ Deployment commands
- ☒ SSH to work_server
- ☒ Git operations

phone_personal:

- ☒ User access to balloo.su
- ☒ Notifications
- ☒ 2FA authentication

phone_service:

- ☒ Admin access
 - ☒ Admin 2FA
 - ☒ Isolated service access
-

 HOME_NAS

Storage Role:

Backups:

- ☒ PostgreSQL backups
- ☒ Application backups
- ☒ Configuration backups
- ☒ Git/artifact mirrors

Boundaries:

- ✗ NOT execution node
 - ✗ NOT for production workload
-

 NETWORK BINDING

Public Endpoints (balloo.su):

Internet → Reverse Proxy → work_server (nginx)

↓

- ├ / → Messenger:3000
- ├ /api → API:3001
- └ /admin → Admin:3002

Private Endpoints:

Tailscale Network:

- ├ laptop_control → work_server (SSH, deployment)
- ├ home_aio → work_server (git sync)
- └ work_server → home_nas (backup sync)

SECURITY BOUNDARIES

Public (MAY be exposed):

- ☒ Messenger web app
- ☒ Public API endpoints
- ☒ WebSocket connections
- ☒ Health checks

Private (MUST NOT be public):

- ☒ Database ports (5432)
- ☒ Redis ports (6379)
- ☒ Internal API endpoints
- ☒ Admin API (unless on subdomain with auth)
- ☒ Metrics/debug endpoints

PROJECT MAPPING

Component	Node	Exposure
Messenger App	work_server	Public (balloo.su)
API Server	work_server	Public (api.balloo.su)
Admin Portal	work_server	Public (admin.balloo.su)
PostgreSQL	work_server	Private only
Redis	work_server	Private only
Dev Env	home_aio	Private/May be public

Component	Node	Exposure
Backups	home_nas	Private only
Control	laptop_control	Private only

Создано: 2026-06-13

🔗 **Baloo**