



NODE DOMAINS CONTRACT

Версия: 1.0.0

Дата: 2026-06-13

Статус: Активный контракт

ЦЕЛЬ

Этот контракт определяет правила привязки доменов к узлам экосистемы, границы публичного и приватного доступа, и политики маршрутизации.

ДОМЕНЫ

1. balloo.su

Domain Owner: Messenger Ecosystem

Project Binding: Balloo Messenger

Scope: PUBLIC

Root Domain Semantics:

- Root domain = messenger ecosystem entry point
- Root MAY redirect to / (messenger app)
- Root MUST NOT expose internal admin endpoints

Allowed Hostnames/Subdomains:

- **balloo.su** - Messenger main app
- **api.balloo.su** - API Server
- **admin.balloo.su** - Admin Portal
- **docs.balloo.su** - Documentation
- ***.balloo.su** - MAY be used for preview environments

Public Endpoints (MAY be exposed):

- **/** - Messenger web app
- **/api/*** - Public API endpoints (auth, users, chats)
- **/socket.io/*** - WebSocket connection
- **/health** - Health checks

Internal Endpoints (MUST NOT be public):

- **/api/admin/*** - Admin API
- **/api/internal/*** - Internal services
- **/metrics** - Prometheus metrics
- **/debug/*** - Debug endpoints

- `/admin/*` - Admin portal (should be on subdomain)

Routing Policy:

- Root: Redirect to `/app` or serve SPA
- `/api/*`: Reverse proxy to API Server
- `/app/*`: Serve Messenger static files
- `/admin/*`: Reverse proxy to Admin Portal

TLS Expectation:

- MUST use HTTPS everywhere
- Certificate via self-hosted CA or Let's Encrypt
- HSTS MUST be enabled

PUBLIC/PRIVATE BOUNDARIES

Public Endpoints (MAY be exposed)

MUST pass through reverse proxy:

- Reverse Proxy → Service

Allowed for public access:

- Messenger web app
- API public endpoints
- Static files
- Health checks (limited info)

REQUIRE authentication:

- User endpoints
- Admin endpoints (even if public URL)
- Websocket connections

Private Endpoints (MUST NOT be public)

MUST stay within private network:

- Database ports (5432)
- Redis ports (6379)
- Internal API endpoints
- Monitoring/metrics
- Debug endpoints
- Admin panels (unless on separate subdomain with auth)

Access methods:

- Tailscale network
- SSH tunnel
- VPN
- Internal service mesh

ARCHITECTURE LAYERS

Layer 1: DNS

balloo.su NS → Self-hosted DNS

Layer 2: Tunnel/Proxy

Internet → Nginx/Caddy Reverse Proxy

Layer 3: Routing

Reverse Proxy → Backend Services

- balloo.su → Messenger (port 3000)
- api.balloo.su → API Server (port 3001)
- admin.balloo.su → Admin Portal (port 3002)

Layer 4: Services

Services run in Docker containers on work_server
Only reverse proxy exposed to public
All other ports internal only

Reverse Proxy

Reverse Proxy (Primary):

- Single entry point on work_server
- Route by hostname/path
- SSL termination
- Load balancing (if multiple instances)

Создано: 2026-06-13

Версия: 1.0.0

 **Balloo** - Share your moments safely!