

Index

Page numbers refer to the PDF-format version. Links are to the appropriate location in this html-format document, usually to the appropriate section containing the referenced term. When viewed in a browser, use the browser search function to find the exact location of the referenced term.

A1DC, 66
 A1DP, 66
 A200X, 62
 A200Y, 62
 A260X, 62
 AACT, 94
 abbreviations
 non-standard, 6
 acceleration
 vertical, 11
 ACDP, 62
 ACINS, 11
 adiabatic compression, 36
 ADIF, 53
 ADIFR, 53, 54
 ADS=aircraft data system, 10
 aeros, 1
 aerosol
 ancillary datasets, 77
 spectrometer, 76
 AF300, 62
 AFIX_x, 87
 AFSSP, 62
 airspeed, 31, 32, 34, 36, 53
 indicated, 88
 AKFX_x, 87
 AKRD, 53, 54
 ALAT, 85
 ALON, 85
 ALPHA, 85
 ALT, 15
 ALTG, 21
 altimeter
 radar, 21
 altitude
 aircraft
 GPS, 19
 geometric, 16
 geopotential, 16, 32
 inertial, 15
 pressure, 13, 16, 22, 32
 ALTX, 23
 angle
 solar azimuth, 82
 solar declination, 81
 solar elevation, 81
 solar zenith, 82
 angles
 solar, 81
 APCAS, 62
 APN-159, 21
 AS100, 62
 AS200, 62
 AT_ITR, 37

ATC, 87
 ATKP, 88
 ATRF, 88
 ATTACK, 54
 attack, angle of, 53
 ATX, 33, 41, 44–46, 48, 50, 53, 75, 91
 ATx, 33, 53
 ATxD, 33
 ATxH, 33
 AUHSAS, 62
 avionics, 29
 Avogadro constant, 4, 42
 AWAS, 72
 baro-inertial loop: see, 12
 baro-loop: see, 12
 base time, 7
 BDIF, 53
 BDIFR, 53, 55
 BFIX_x, 87
 BLATA, 16
 BLONA, 16
 BNORMA, 16
 Bolton, 47
 Boltzmann constant, see
 Constants and Symbols, 4
 BPITCHR, 16
 BROLLR, 16
 Bulletin 21, 31
 Bulletin 23, 53
 Bulletin 24, 93
 Bulletin 25, 92
 Bulletin 9, 2
 BYAWR, 16
 C1DC, 66 C1DP, 66
 C200X, 62
 C200Y, 62
 C260X, 62
 calibration, numerous references throughout, 29
 coefficients, 9
 gas, 68
 CAVP_x, 32
 CCDP, 62
 CCEP, 85
 centrifugal acceleration, 14
 CF300, 62
 CFSEC, 85
 CFSSP, 62
 CGS, 85
 CH4_PIC_x, 68
 chilled-mirror, 44
 CIMS, 72
 CLAT, 85
 CLON, 85
 CMODE, 92

- CN counter, 73
 - 3760A, 73
 - 3786, 73
 - coincidence in, 74
 - dead time, 74
 - flow rate, 73
 - side flow, 74
- CNTEMP, 75
- CNTS, 75
- CO, 92 CO2_PICx, 68
- COCAL, 92
- COCOR, 92
- coefficients
 - calibration, 29
 - sensitivity, 30
- compression
 - adiabatic, 33
- COMR_AL, 68 CONC1DC, 66
- CONC1DP, 66
- CONC3, 63
- CONC6, 63
- CONCD, 63
- concentration
 - 2D, 66
 - aerosol, 73
 - ambient, 73
 - calibration gas, 68
 - chemical species, 5, 6
 - CN, 74
 - droplet, 5
 - FSSP, 63
 - hydrometeor, 62
 - hydrometeor, size distribution, 62
 - particle, 77
 - PCAS, 94
 - ultrafine particles, 73
 - water vapor, 42
- CONCF, 63
- CONCH_UVH, 43
- CONCN, 75
- CONCP, 76
- CONCU, 76
- CONCU100, 76
- CONCU500, 76
- CONCV_VXL, 42
- CONCX, 63
- CONCY, 63
- condensation nucleus counter, see CN counter
- conductivity
 - thermal, 59
- conservation of energy, 34
- constants, see symbols
 - table, 4
- CORAW_AL, 68
- Coriolis acceleration, 14
- correction
 - dynamic pressure, 31
 - moist air, 33
 - pressure, 30
 - vertical wind
 - rotation in pitch, 19
- count rate
 - 2D, 66
- COZRO, 92
- CPCAS, 62
- CPS=counts per second, 68, 70
- CRHP, 89
- CS100, 62
- CS200, 62
- CSEC, 85
- CUHSAS, 62
- d-value, 32
- data
 - acquisition, 1
 - display, 1
 - processing, 1
 - sample rate, 1
- data rates, 8
- Davies-Jones, 46
- DAY, 7
- DBAR1DC, 67
- DBAR1DP, 67
- DBAR3, 63
- DBAR6, 63
- DBARD, 63
- DBARF, 63
- DBARP, 63
- DBARU, 63
- DBARX, 63
- DBARY, 63
- dBz, 64
- DBZ1DC, 67
- DBZ1DP, 67
- DBZ6, 64
- DBZD, 64
- DBZF, 64
- DBZX, 64
- DBZY, 64
- dead time, 66
 - FSSP, 94
- defect
 - static, 30
- DEI, 15
- density
 - water vapor, 44
- derived variables, 46
- dew point, 38
 - corrected, 38, 40

- diameter
 - effective, 64
 - equivalent, 64
 - mean, 1D probes, 63
 - mean, 2D probes, 67
- dimensions in equations, 64
- DISP1DC, 67
- DISP1DP, 67
- DISP3, 63
- DISP6, 63
- DISPD, 63
- dispersion, 67
 - 1D probes, 63
- DISPF, 63
- DISPP, 63
- DISPU, 63
- DISPX, 63
- DISPY, 63
- DNI, 15
- DP_CR2C, 42
- DP_VXL, 41
- DP_x, 38
- DPCRC, 89
- DPx, 41
- DPXC, 91
- DPxC, 40
- dropsonde, 57
- DT1DC, 66
- DVALUE, 32
- dynamic pressure, 52
- EDPC, 88
- enhancement factor, 44
- equation
 - thickness, 32
- equations
 - dimensionless, 9
 - scale factors, 9
- EW_UVH, 43
- EWX, 43–46
- EWx, 43
- FACT, 94
- FBMFR, 94
- FCN, 73
- FCN, 73
- FCNC, 75
- filter
 - Butterworth, 25
 - complementary (for wind), 24
 - electronic, 8
- FIR, 8
- fit matrix, 27
- flight speed, see true airspeed
- flow
 - conversions, 5
 - PCASP, 76
 - SLPM, 5
 - volumetric, 5
- flow distortion, 29
- flow rates, 5
- flux
 - actinic, 80
- FO3_ACD, 69
- FO3_CL, 69
- FO3_x, 69
- foot, 6
- FP_CR2, 42
- FPCRC, 89
- FRANGE, 65
- FRESET, 93
- FRNG, 65
- frost point, 89
- FRST, 93
- FSSP-100
 - activity, 94
 - beam fraction, 94
 - concentration, 63
 - dead time, 93, 94
 - dispersion, 63
 - fast resets, 93
 - liquid water content, 63
 - mean diameter, 63
 - range 65
 - size distribution, 62
 - total strobes, 93
- FSSP-300, 63
- FSTB, 93
- FSTROB, 93
- FXAZIM, 15
- FXDIST, 15
- GALT_A, 19
- gas constant, 4
 - dry air, 4, 46
 - moist air, 33, 34
 - universal, 4
 - water vapor, 4
- GENPRO, 2
- GEOPTH, 19
- GGALT, 19
- GGALTC, 23
- GGEOIDHT, 20
- GGHWGS, 19
- GGLAT, 28
- GGLON, 28
- GGNSAT, 20
- GGQUAL, 20
- GGSPD, 18
- GGSTATUS, 20
- GGTRK, 20

- GGVEW, 26
- GGVNS, 26
- GGVSPD, 19
- GISMOS, 57
- GLAT, 18
- global positioning system, see GPS
- GLON, 18
- GLON, 18
- GMODE, 20
- GNI, 77
- GPS, 27
 - aircraft avionics unit, 17
 - Garmin, 17
 - NovAtel, 16
 - Trimble TANS-III, 17
- GPS receivers, 16
- gravity, see Eqn. (1.1)
 - standard, 16
- ground speed, 15
- GSF, 86
- GSF_G, 18
- GSTAT, 20
- GSTAT, 20
- GSTAT_G, 20
- gust probe 858AJ, 52
 - radome, 52, 53
 - Rosemount 858AJ, 53
- GVZI, 19
- HARP, see HIAPER Atmospheric Radiation Package
- heading
 - magnetic, 11
 - true, 11
- Heimann radiometer, 78
- HGM, 21
- HGM, 21
- HGM232, 21
- HGME, 32
- HI3, 21
- HIAPER Atmospheric Radiation Package, 80
- HOURL, 7
- housekeeping variables, 61
- humidity, 38
 - absolute, 44
 - relative, 44
 - relative to ice, 44
 - specific, 45, 53
- hydrometeor detector, 60
- hydrometeor probes
 - table of, 62
- hydrometeor spectrometer, 63
- hygrometer, 38
 - chilled-mirror, 44
 - CR2, 42
 - cryogenic, 45, 89
 - dew point, 38, 45
 - housing, 38
 - Lyman-alpha, 45, 90
 - tunable diode laser, 40, 45
 - UV, 42, 45, 90
 - VCSEL, 37, 40, 41, 45
- ice water content, 64
- impactor
 - giant nucleus, 77
- indicated airspeed, 88
- inertial navigation system, see INS
- inertial reference unit, see IRU
- INS, 10
 - alignment, 10
 - C-MIGITS, 10
 - C130, 10
 - GV, 10
 - Honeywell, 13
 - Honeywell Laseref, 10
 - Litton LTN-51, 12
 - measurements not in normal data files, 16
 - specifications, 11
- instrument descriptions
 - EOL web site, 29
- instruments
 - radiation, 78
 - user, 1, 71
- International Standard Atmosphere, 22
 - lapse rate, 23
 - tropopause, 23
- interpolation, 8
- irradiance, 78
 - long-wave, 79
 - visible, 80
- IRU, 11
 - Litton LTN-51, 86
 - raw variables, 16
- IRx, 91
- IRxC, 91
- IRxHT, 79
- IRxV, 79
- ISA, see International Standard Atmosphere
- Johnson-Williams sensor, 88
- King probe, 58
 - element dimensions, 59
 - power dissipated, 59
 - sensor temperature, 59
- knot, 6
- lags in sampling
 - static, 8
 - dynamic, 8 LAMS, 31 LAT, 28
- LAT_G, 18
- LATC, 27
- latent heat of vaporization, 59

- latitude, 27
- lifted condensation level, 47
- linkage. temperature and airspeed, 33
- liquid water content, 67
 - 1D probes, 63
 - FSSP-100, 63
 - King probe, 58
 - supercooled, 60
- LON, 28 LON_G, 18
- LONC, 27
- longitude, 27
- LWC, 88
- LWCC, 88
- Lyman-alpha hygrometer, 40
- Mach number, 36
 - uncorrected, 31
- MACHX, 54
- MACHx, 53
- measurement
 - derived, 8
 - original, 8
 - preferred, 29
 - raw, 8, 33
- meter
 - mass flow, 5
- millibar, 5
- MINUTE, 7
- MIRRORT_CR2, 42
- MIRRTMP_DP_x, 38
- mixing ratio, 50
 - conversion, 6
- moist-air properties, 34
- molecular weight
 - dry air, 4
 - water, 4
- MONTH, 7
- motion
 - GPS antenna, 51
- MR, 50
- MRCR, 45
- MRLA, 45
- MRLH, 45
- MRVXL, 45
- MTP, 57
- Murphy and Koop, 39
- names
 - variable, 29
 - location in, 29
 - suffixes, 29
- nautical mile, 6
- NetCDF
 - format, 1
 - header, 1, 10
 - vector, 62
- NIDAS, 7
- nimbus, 1
- nomenclature
 - code, 8
 - dimensionless equations, 8, 9
- O3FS, 92
- O3MR_CL, 69
- OAT, 37
- sample time, 7
- oscillation, 10
- PACT, 94
- PALT, 21
- particles
 - ultrafine, 73
- PCAB, 32
- PCASP, 77
- PCN, 75
- PCORS, see pressure corrections
- perfect gas, 33
- PFLW, 76
- PFLWC, 76
- PHDG, 85
- PITCH, 11
- pitch, 11
- platform
 - stabilized, 79, 80
- PLWC, 58
- PLWC1, 58
- PLWC1DC, 67
- PLWC6, 63
- PLWCC, 58
- PLWCC1, 58
- PLWCD, 63
- PLWCF, 63
- PLWCG, 60
- PLWCX, 63
- PLWCY, 63
- potential temperature, 46
- ppbv, 6
- ppmv, 6
- pptv, 5, 6
- pressure, 29
 - ambient, 29, 31, 33, 36, 52
 - cabin, 32
 - corrections, 30
 - dew point housing, 38
 - dew-point cavity, 32
 - dynamic, 30, 31, 33, 55
 - corrected, 31
 - inlet, 73
 - partial, water vapor, 38
 - pitot, see pressure, total
 - static, see pressure ambient
 - surface, 32

- total, 31, 35, 36
- transducer,
 - ambient pressure, 30
 - dynamic pressure, 31
 - equilibrium, 38, 39, 44
- pressure damping
 - ACINS, 11
 - VSPD, 12
 - WP3, 12
- properties of moist air, 34
- PS_A, 29
- PSDPx, 32
- PSFD, 29
- PSFRD, 29
- PSURF, 32
- PSX, 33
- PSx, 29
- PSxC, 29
- PTIME, 85
- pyranometer, 79, 91
 - calibration, 79
- pyrgeometer, 78, 91
 - calibration, 78
- QCB, 87
- QCBC, 87
- QCF, 54
- QCG, 87
- QCG, 87
- QCGC, 87
- QCLS, 72
- QCR, 31
 - correction, 31
- QCRC, 31
 - flow-angle correction, 31
- QCX, 33
- QCx, 31
- QCXC, 36
- QCxC, 36
- radar reflectivity factor
 - 1D probes, 64
 - 2D probes, 67
- radiation, 78
 - long-wave, 91
 - short wave, 91
- radiometer
 - Heimann, 78
 - Kipp & Zonen IR, 79
 - Kipp & Zonen visible, 79
- radius
 - of the Earth, 4
 - effective, 67
- radome gust probe, 52, 53
- range
 - FSSP, 65
- rate of climb, 12
- RAWCONC_VXL, 42
- recovery factor, 35
 - Rosemount sensors, 35
- REFF2DC, 67
- REFF2DP, 67
- REFFD, 64
- REFFF, 64
- reflectivity factor, 64
 - 1D probes, 64
 - 2D probes, 67
- relative humidity, 44
- relative humidity wrt ice, see humidity, relative to ice
- resets
 - FSSP-100, 93
- reverse-flow temperature sensor, 88
- RHOLA, 45
- RHOUV, 45
- RHOx, 44
- RHUM, 44
- RHUMI, 44
- RICE, 60
- ROLL, 11
- roll, 11
- Rosemount 871F icing probe, 60
- RSTx, 78
- RTHR_x, 32
- RTX, 37
- RTx, 33
- RTxH, 32
- samples per second, 6
- sampling rates, 7
- Schuler oscillation, 27
- SCLWC, 93
- SECOND, 7
- sensitivity coefficient
 - AKRD, 53
 - SSRD, 54
- sensor
 - temperature
 - anti-iced, 33
 - heated, 33
 - K-probe, 33
- SFC, 21
- sideslip, 55
- size distribution
 - 1D probes
 - 2D probes, 66
- SMPS, 77
- SOLAZ, 82
- SOLDE, 81
- SOLEL, 81
- SOLZE, 82
- specific heat, 34
 - dry air

- constant pressure, 4
- constant volume, 4
- ratio, dry air, 4
- moist air, 33, 34
- spectrometer
 - aerosol mass, 77
 - hydrometeor, 63
- speed
 - ground, 15
 - airspeed
 - indicated, 88
 - true, 53
- speed of sound, 35
- SPHUM, 53
- SPxPitch, 80
- SPxRoll, 80
- SSFXX, 87
- SSLIP, 55
- SSRD, 55
- Stephan-Boltzmann Constant, , see
 - Constants and Symbols, 4
- STP (standard conditions), 5
- strobes
 - FSSP, 93
- SWTC, 92
- SWx, 91
- synchronization, 7
- system of units, 5
- TASHC, 53
- TASx, 53
- TASx, 53
- TASxD, 52
- TCAVB, 78
- TCAVT, 78
- TCNTP, 76
- TCNTU, 76
- TEMP1, 73
- TEMP2, 73
- temperature, 32
 - ambient, 32, 33, 41
 - calculation, 33
 - equivalent potential, 47
 - in-cloud, 37
 - inlet, 73
 - potential, 46, 47
 - pseudo-adiabatic equivalent potential, 46
 - radiometric, 37, 78
 - recovery, 32, 34
 - recovery vs. total, 33
 - reverse-flow, 88
 - sensor, 33
 - static air, 33
 - total, 33, 87
 - virtual, 48
 - virtual potential, 48
- TEO3, 70
- TEO3C, 70
- TEO3P, 70
- TEP, 70
- TET, 70
- THDG, 11
- thermal conductivity, see conductivity, thermal
- THETA, 48
- THETA_E, 46
- THETA_Q, 49
- THETA_V, 48
- THF, 86
- THI, 85
- time, 7
 - base_time, 7
 - example of usage, 7
 - interpolation, 8
 - lags, 8
 - offset, 7
 - shifts, 8
 - variable Time, 7
 - variables, 6
- TKAT_G, 20
- TMLAG, 85
- TOGA, 72
- TPTIME, 85
- trailing cone, 30
- transducer
 - barometric, 29
 - Paroscientific, 30
- triple point of water, 4
- TRSTB, 78
- true airspeed, see airspeed
- TTKP, 88
- TTRF, 87
- TTx, 87
- TVIR, 48
- UHSAS, 77
 - flow, 76
 - STP, 76
- UI, 55
- UIC, 56
- uncertainty
 - wind
 - Technical Note, 51
- units, 5
 - exceptions to SI, 5
 - hertz, 6
 - ppmb, 5
- universal gas constant, 4
- UPRESS, 76
- USFLWC, 76
- USMPFLW, 76

- UVx, 92
- UX, 56
- UXC, 57
- variable
 - derived, 9
 - names in brackets, 8
 - preferred choice, 29
- variable names
 - conventions, 29
 - hydrometeor probes, 60
- VCRH, 89
- VEW, 15
- VEW_G, 18
- VEWC, 28
- VI, 55
- VIC, 56
- viscosity, 59
- VISxC, 80
- VISxHT, 80
- VISxHTV, 80
- VISxV, 79
- VLA, 90
- VLA1, 90
- VNS, 15
- VNS_G, 18
- VNSC, 28
- VSPD, 13
- VSPD_G, 19
- VY, 56
- VY, 56
- VYC, 57
- VZI, 86
- VZI, 86
- water
 - boiling point, 58
- water vapor
 - density, 41, 42, 44
 - mixing ratio, 45
- WD, 56
- WDC, 56
- WDRCTN, 86
- wetting
 - of thermometers, 37
- WGS-84 geoid, 4
- WGS84, 19
- WI, 55
- WIC, 56
- wind, 55
 - components, 55
 - direction, 56
 - GPS-corrected, 56
 - lateral component, 57
 - longitudinal component, 57
 - relative, 52
 - sign convention, 55
 - speed, 56
 - uncertainty
 - Tech Note, 10, 51
 - vector, 55, 56
 - vertical, 56
- World Geodetic System, 19
- WP3, 12
- WS, 56
- WSC, 56
- WSPD, 86
- XFO3FNO, 69
- XFO3FS, 69
- XFO3P, 69
- XICN, 74
- XICNC, 74
- XMACH2, 52
- XNCLF, 71
- XNMBT, 71
- XNO, 71
- XNOCAL, 71
- XNOCF, 71
- XNOSF, 71
- XNOY, 71
- XNOYP, 71
- XNOZA, 71
- XNSAF, 71
- XNST, 71
- XNYCAL, 71
- XNZAF, 71
- XO3, 69
- XSIGV_UVH, 42
- XUVI, 90
- XUVP, 90
- XUVT, 90
- XVI, 85
- YEAR, 7
- YVI, 85