

Setting Environment for Real-time Skew-T Plotting

This process runs on tsunami as the joss user (sudo su - joss to become the joss user).

Necessary software:

anaconda2 (already installed on tsunami in /opt/local/anaconda2).

SHARPPy (version 1.4.0a4 was used).

SHARPPy software requires the NumPy library. This library is installed by default with anaconda2. Running the full_gui.py requires the PySide library, but the plotting software does not run the full_gui.py.

To download the SHARPPy software:

git clone <https://github.com/sharppy/SHARPPy.git>
into some directory.

To install the SHARPPy software:

cd to the directory where the software was downloaded and into the SHARPPy directory.

python setup.py install (Use the python binary in /opt/local/anaconda2/bin).

This should install directories named sharppy and runsharp under
/opt/local/anaconda2/lib/python2.7/site-packages

To update the SHARPPy software:

cd to the directory where the software was downloaded

git pull origin master

Follow the directions above for installing the SHARPPy software to update to the latest version.

Note: python 2.7 may not be maintained after 1/1/20. (Not sure if this is still accurate). The SHARPPy software is still using python 2.7. There is a development branch named Andover that is to be used with python 3. See: <https://github.com/sharppy/SHARPPy> for more information on the SHARPPy software.

The following changes were made to the SHARPPy software:

Changed /opt/local/anaconda2/lib/python2.7/site-packages/sharppy/plot/skew.py

In draw_title routine - changed font from 14 to 10

In draw_hodo_inset routine - changed width and height from 1.7 to 1.4

python -m compileall . (to compile the new versions of skew.py. Use python binary in /opt/local/anaconda2/bin).

Downloaded example code for plotting a skew-t from:

https://sharppy.github.io/SHARPPy/auto_examples/plot_sounding.html

During development ran:

jupyter notebook --no-browser --port=8895 (on tikal, same /opt/local disk is also mounted on tsunami).

On personal mac ran:

ssh -L 8015:localhost:8895 anstett@tikal

In local browser:

localhost:8015

(enter token given when starting jupyter on tikal)

After development was finished, the jupyter notebook was converted to a python script:

!python nbconvert --to python plot_sounding.ipynb (run python from /opt/local/anaconda2/bin).
where plot_sounding.ipynb is the name of the jupyter notebook. This command created plot_sounding.py.

Changes made after ipython nbconvert was run:

Add:

#!/opt/local/anaconda2/bin/python (as the first line)

for the correct matlab libraries to be included.

Change plot_sounding.py to executable.

Comment out magic line (first line in file before #! line was added).

Add the following before any matplotlib "from" statements:

import matplotlib

matplotlib.use('Agg')

Add:

plt.ioff() (To turn interactive plotting off).