

# rain-days-abs-self-groupingB-wMPAS

January 25, 2022

## 1 Future-Hist for 8 upper atm variables.

w/ MPAS - Rain signals include MPAS model.

- this version loads netcdf files directly via xarray
- “Gridmet data” can now be replaced with any model’s output

### 1.0.1 TODO items

- better graphs (i.e. include lat/lon scale)

```
[1]: from IPython import display
import numpy as np

#from skimage.metrics import structural_similarity as ssim
import copy
```

```
[2]: # load netcdf files directly via xarray
import xarray as xr
import matplotlib.pyplot as plt
import cartopy.crs as ccrs
import cartopy
```

## 2 Configuration

```
[3]: # Ordering: nRow ordering: obs, raw, RegCM4, WRF, MPAS, CNN, SDSM, KDDM, MBCn, LOCA
mpi_sigfiles=['/glade/work/mcginnis/DCA/data/gen/final/gridmet/hist/prec.hist.
→gridMET.obs.day.1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/mpi/hist/prec.hist.MPI-ESM-LR.raw.day.
→1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/mpi/rcp85/prec.rcp85.MPI-ESM-LR.raw.day.
→2075-2100.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/regcm4/hist/prec.hist.MPI-ESM-LR.RegCM4.
→day.1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/regcm4/rcp85/prec.rcp85.MPI-ESM-LR.
→RegCM4.day.2075-2100.NAM-22i.SGP.x098.y36.nc',
```

```

'/glade/work/mcginnis/DCA/data/gen/final/wrf/hist/prec.hist.MPI-ESM-LR.WRF.day.
→1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/wrf/rcp85/prec.rcp85.MPI-ESM-LR.WRF.day.
→2075-2100.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/mpas/hist/prec.hist.MPI-ESM-LR.MPAS.day.
→1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/mpas/rcp85/prec.rcp85.MPI-ESM-LR.MPAS.
→day.2075-2100.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/cnn/hist/prec.hist.MPI-ESM-LR.CNN.day.
→1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/cnn/rcp85/prec.rcp85.MPI-ESM-LR.CNN.day.
→2075-2100.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/sdsm/hist/prec.hist.MPI-ESM-LR.SDSM.day.
→1976-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/sdsm/rcp85/prec.rcp85.MPI-ESM-LR.SDSM.day.
→2070-2099.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/kddm/hist/prec.hist.MPI-ESM-LR.KDDM.day.
→1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/kddm/rcp85/prec.rcp85.MPI-ESM-LR.KDDM.
→day.2075-2100.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/mbcn/hist/prec.hist.MPI-ESM-LR.MBCn.day.
→1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/mbcn/rcp85/prec.rcp85.MPI-ESM-LR.MBCn.
→day.2075-2100.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/loca/hist/prec.hist.MPI-ESM-LR.LOCA.day.
→1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/loca/rcp85/prec.rcp85.MPI-ESM-LR.LOCA.
→day.2075-2100.NAM-22i.SGP.x098.y36.nc']

```

### 3 Compact configuration

```

[4]: sigdir = '/glade/work/mcginnis/DCA/data/gen/final'
def model2absfilepath(mn, exp, x, y):
    if mn == 'obs' or mn == 'gridMET':
        mn = 'gridMET'
        filename = 'prec.{}.gridMET.{}.day.1980-2005.NAM-22i.SGP.x0{}.y{}.nc'.
→format(exp, 'obs', x, y)
    elif mn == 'raw' or mn == 'mpi':
        mn = 'mpi'
        if exp == 'hist':
            filename = 'prec.{}.MPI-ESM-LR.{}.day.1980-2005.NAM-22i.SGP.x0{}.y{}.
→nc'.format(exp, 'raw', x, y)
        elif exp == 'rcp85':
            filename = 'prec.{}.MPI-ESM-LR.{}.day.2075-2100.NAM-22i.SGP.x0{}.y{}.
→nc'.format(exp, 'raw', x, y)

```

```

        else: print("Unknown experiment!")
    elif mn == 'SDSM': # starts at 1976
        if exp == 'hist':
            filename = 'prec.{}.MPI-ESM-LR.{}.day.1976-2005.NAM-22i.SGP.x0{}.y{}.
→nc'.format(exp, mn, x, y)
            elif exp == 'rcp85':
                filename = 'prec.{}.MPI-ESM-LR.{}.day.2070-2099.NAM-22i.SGP.x0{}.y{}.
→nc'.format(exp, mn, x, y)
            else: print("Unknown experiment!")

        elif exp == 'hist':
            filename = 'prec.{}.MPI-ESM-LR.{}.day.1980-2005.NAM-22i.SGP.x0{}.y{}.nc'.
→format(exp, mn, x, y)
            elif exp == 'rcp85':
                filename = 'prec.{}.MPI-ESM-LR.{}.day.2075-2100.NAM-22i.SGP.x0{}.y{}.nc'.
→format(exp, mn, x, y)
            else: print("Unknown experiment!")
        return sigdir + '/' + mn.lower() + '/' + exp + '/' + filename

```

```

[5]: # test single file
model2absfilepath('RegCM4', 'rcp85', 98, 36)

```

```

[5]: '/glade/work/mcginnis/DCA/data/gen/final/regcm4/rcp85/prec.rcp85.MPI-ESM-
LR.RegCM4.day.2075-2100.NAM-22i.SGP.x098.y36.nc'

```

```

[6]: # create list of abs filepaths
[model2absfilepath(ff, 'hist', 98, 36) for ff in_]
→['obs', 'raw', 'RegCM4', 'WRF', 'MPAS', 'CNN', 'SDSM', 'KDDM', 'MBCn', 'LOCA']]

```

```

[6]: ['/glade/work/mcginnis/DCA/data/gen/final/gridmet/hist/prec.hist.gridMET.obs.day
.1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/mpi/hist/prec.hist.MPI-ESM-
LR.raw.day.1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/regcm4/hist/prec.hist.MPI-ESM-
LR.RegCM4.day.1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/wrf/hist/prec.hist.MPI-ESM-
LR.WRF.day.1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/mpas/hist/prec.hist.MPI-ESM-
LR.MPAS.day.1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/cnn/hist/prec.hist.MPI-ESM-
LR.CNN.day.1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/sdsm/hist/prec.hist.MPI-ESM-
LR.SDSM.day.1976-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/kddm/hist/prec.hist.MPI-ESM-
LR.KDDM.day.1980-2005.NAM-22i.SGP.x098.y36.nc',
'/glade/work/mcginnis/DCA/data/gen/final/mbcn/hist/prec.hist.MPI-ESM-

```

```
LR.MBCn.day.1980-2005.NAM-22i.SGP.x098.y36.nc',
  '/glade/work/mcginnis/DCA/data/gen/final/loca/hist/prec.hist.MPI-ESM-
LR.LOCA.day.1980-2005.NAM-22i.SGP.x098.y36.nc']
```

### 3.0.1 Load model output data

```
[7]: #####
## LOAD GRIDMET ##
#####
# 1980-1989
istart = 365
#ndays = 3653 # 1980-1989
ndays = 13515 # 1980-2016

dv1 = xr.open_dataset('/glade/work/dkorytin/srgan_data/
→prec128_gridmetA_1979-2016.nc')['prec'][istart:istart+ndays]
# dv2 = xr.open_dataset('/glade/work/dkorytin/srgan_data/
→tmax128_gridmetA_1979-2016.nc')['tmax'][istart:istart+ndays]
# dv3 = xr.open_dataset('/glade/work/dkorytin/srgan_data/
→tmin128_gridmetA_1979-2016.nc')['tmin'][istart:istart+ndays]
# dv4 = xr.open_dataset('/glade/work/dkorytin/srgan_data/
→uas128_gridmetA_1979-2016.nc')['uas'][istart:istart+ndays]
# dv5 = xr.open_dataset('/glade/work/dkorytin/srgan_data/
→vas128_gridmetA_1979-2016.nc')['vas'][istart:istart+ndays]
# dv6 = xr.open_dataset('/glade/work/dkorytin/srgan_data/
→huss128_gridmetA_1979-2016.nc')['huss'][istart:istart+ndays]
# dv7 = xr.open_dataset('/glade/work/dkorytin/srgan_data/
→rsds128_gridmetA_1979-2016.nc')['rsds'][istart:istart+ndays]
# dv8 = xr.open_dataset('/glade/work/dkorytin/srgan_data/
→miss128_gridmetB_1979-2016.nc')['miss'][istart:istart+ndays]
```

### 3.0.2 Load UATM data

```
[8]: #####
## LOAD ERAI data: daily ##
#####
def load_uatm_erai():
    global mdv1,mdv2,mdv3,mdv4,mdv5,mdv6,mdv7,mdv8,mnvars

    # load eraionmpi
    #mndays = 11688 # 1979-2010
    mstart = 365
    mndays = 13515 # 1980-2016
    mnvars = 8*1
    mdv1 = xr.open_dataset('/glade/scratch/dkorytin/eraion-mpigrid/U850.ERAI.
→MPIGRID.1979-2018.nc')['U'][mstart:mstart+mndays*1]
```

```

mdv2 = xr.open_dataset('/glade/scratch/dkorytin/eraï-on-mpigrid/V850.ERAï.
↳MPIGRID.1979-2018.nc')['V'][mstart:mstart+mndays*1]
mdv3 = xr.open_dataset('/glade/scratch/dkorytin/eraï-on-mpigrid/Q850.ERAï.
↳MPIGRID.1979-2018.nc')['Q'][mstart:mstart+mndays*1]
mdv4 = xr.open_dataset('/glade/scratch/dkorytin/eraï-on-mpigrid/T700.ERAï.
↳MPIGRID.1979-2018.nc')['T'][mstart:mstart+mndays*1]
mdv5 = xr.open_dataset('/glade/scratch/dkorytin/eraï-on-mpigrid/Z700.ERAï.
↳MPIGRID.1979-2018.nc')['Z'][mstart:mstart+mndays*1]
mdv6 = xr.open_dataset('/glade/scratch/dkorytin/eraï-on-mpigrid/Z500.ERAï.
↳MPIGRID.1979-2018.nc')['Z'][mstart:mstart+mndays*1]
mdv7 = xr.open_dataset('/glade/scratch/dkorytin/eraï-on-mpigrid/U250.ERAï.
↳MPIGRID.1979-2018.nc')['U'][mstart:mstart+mndays*1]
mdv8 = xr.open_dataset('/glade/scratch/dkorytin/eraï-on-mpigrid/V250.ERAï.
↳MPIGRID.1979-2018.nc')['V'][mstart:mstart+mndays*1]

print("Days loaded", len(mdv7))

```

[9]:

```

#####
## LOAD MPI      ##
#####
def load_uatm_mpi_hist():
    global mdv1,mdv2,mdv3,mdv4,mdv5,mdv6,mdv7,mdv8,mnvars

    mnvars = 8

    d='/glade/p/ral/risc/rmccrary/CMIP5_CORDEX/NAmerica/MPI-ESM-LR/native/
↳historical/'

    mdv1 = xr.
↳open_dataset(d+'U_MPI-ESM-LR_historical_r1i1p1_NAmerica_p850_19500101-20051231_dayavg_mpigrid
↳nc')['U'].sel(time=slice('1976-01-01T00:00:00', '2006-01-01T00:00:00'),
↳lat=slice(23,56), lon=slice(-113,-80))
    mdv2 = xr.
↳open_dataset(d+'V_MPI-ESM-LR_historical_r1i1p1_NAmerica_p850_19500101-20051231_dayavg_mpigrid
↳nc')['V'].sel(time=slice('1976-01-01T00:00:00', '2006-01-01T00:00:00'),
↳lat=slice(23,56), lon=slice(-113,-80))
    mdv3 = xr.
↳open_dataset(d+'Q_MPI-ESM-LR_historical_r1i1p1_NAmerica_p850_19500101-20051231_dayavg_mpigrid
↳nc')['Q'].sel(time=slice('1976-01-01T00:00:00', '2006-01-01T00:00:00'),
↳lat=slice(23,56), lon=slice(-113,-80))
    mdv4 = xr.
↳open_dataset(d+'T_MPI-ESM-LR_historical_r1i1p1_NAmerica_p700_19500101-20051231_dayavg_mpigrid
↳nc')['T'].sel(time=slice('1976-01-01T00:00:00', '2006-01-01T00:00:00'),
↳lat=slice(23,56), lon=slice(-113,-80))

```

```

mdv5 = xr.
→open_dataset(d+'Z_MPI-ESM-LR_historical_r1i1p1_NAmerica_p700_19500101-20051231_dayavg_mpigrid.
→nc')[ 'Z' ].sel(time=slice('1976-01-01T00:00:00', '2006-01-01T00:00:00'),
→lat=slice(23,56), lon=slice(-113,-80))

mdv6 = xr.
→open_dataset(d+'Z_MPI-ESM-LR_historical_r1i1p1_NAmerica_p500_19500101-20051231_dayavg_mpigrid.
→nc')[ 'Z' ].sel(time=slice('1976-01-01T00:00:00', '2006-01-01T00:00:00'),
→lat=slice(23,56), lon=slice(-113,-80))

mdv7 = xr.
→open_dataset(d+'U_MPI-ESM-LR_historical_r1i1p1_NAmerica_p250_19500101-20051231_dayavg_mpigrid.
→nc')[ 'U' ].sel(time=slice('1976-01-01T00:00:00', '2006-01-01T00:00:00'),
→lat=slice(23,56), lon=slice(-113,-80))

mdv8 = xr.
→open_dataset(d+'V_MPI-ESM-LR_historical_r1i1p1_NAmerica_p250_19500101-20051231_dayavg_mpigrid.
→nc')[ 'V' ].sel(time=slice('1976-01-01T00:00:00', '2006-01-01T00:00:00'),
→lat=slice(23,56), lon=slice(-113,-80))

def load_uatm_mpi_future():
    global mdv1,mdv2,mdv3,mdv4,mdv5,mdv6,mdv7,mdv8,mnvars

    d='/glade/p/ral/risc/rmccrory/CMIP5_CORDEX/NAmerica/MPI-ESM-LR/native/rcp85/'

    mnvars = 8
    mdv1 = xr.
    →open_dataset(d+'U_MPI-ESM-LR_rcp85_r1i1p1_NAmerica_p850_20060101-21001231_dayavg_mpigrid.
    →nc')[ 'U' ].sel(time=slice('2006-01-01T00:00:00', '2101-01-01T00:00:00'),
    →lat=slice(23,56), lon=slice(-113,-80))

    mdv2 = xr.
    →open_dataset(d+'V_MPI-ESM-LR_rcp85_r1i1p1_NAmerica_p850_20060101-21001231_dayavg_mpigrid.
    →nc')[ 'V' ].sel(time=slice('2006-01-01T00:00:00', '2101-01-01T00:00:00'),
    →lat=slice(23,56), lon=slice(-113,-80))

    mdv3 = xr.
    →open_dataset(d+'Q_MPI-ESM-LR_rcp85_r1i1p1_NAmerica_p850_20060101-21001231_dayavg_mpigrid.
    →nc')[ 'Q' ].sel(time=slice('2006-01-01T00:00:00', '2101-01-01T00:00:00'),
    →lat=slice(23,56), lon=slice(-113,-80))

    mdv4 = xr.
    →open_dataset(d+'T_MPI-ESM-LR_rcp85_r1i1p1_NAmerica_p700_20060101-21001231_dayavg_mpigrid.
    →nc')[ 'T' ].sel(time=slice('2006-01-01T00:00:00', '2101-01-01T00:00:00'),
    →lat=slice(23,56), lon=slice(-113,-80))

    mdv5 = xr.
    →open_dataset(d+'Z_MPI-ESM-LR_rcp85_r1i1p1_NAmerica_p700_20060101-21001231_dayavg_mpigrid.
    →nc')[ 'Z' ].sel(time=slice('2006-01-01T00:00:00', '2101-01-01T00:00:00'),
    →lat=slice(23,56), lon=slice(-113,-80))

```

```

mdv6 = xr.
→open_dataset(d+'Z_MPI-ESM-LR_rcp85_r1i1p1_NAmerica_p500_20060101-21001231_dayavg_mpigrid.
→nc')[ 'Z' ].sel(time=slice('2006-01-01T00:00:00', '2101-01-01T00:00:00'),
→lat=slice(23,56), lon=slice(-113,-80))

mdv7 = xr.
→open_dataset(d+'U_MPI-ESM-LR_rcp85_r1i1p1_NAmerica_p250_20060101-21001231_dayavg_mpigrid.
→nc')[ 'U' ].sel(time=slice('2006-01-01T00:00:00', '2101-01-01T00:00:00'),
→lat=slice(23,56), lon=slice(-113,-80))

mdv8 = xr.
→open_dataset(d+'V_MPI-ESM-LR_rcp85_r1i1p1_NAmerica_p250_20060101-21001231_dayavg_mpigrid.
→nc')[ 'V' ].sel(time=slice('2006-01-01T00:00:00', '2101-01-01T00:00:00'),
→lat=slice(23,56), lon=slice(-113,-80))

#load_uatm_mpi_future()

```

## 4 Averaging code

```

[10]: #####
      ## UATM averages ##
      #####

def calc_uatm_average(mpr_min, mpr_max, rainsignal, ymin, ymax):
    # global inputs: dv[1-8], mdv[1-8], mnvars
    mnvars = 8

    # initialize accumulators
    indices = []
    distribution = []
    raw_ires = len(mdv1[0])
    raininput = np.zeros((mnvars, raw_ires, raw_ires))
    raincount = 0

    for ii in range(0,len(rainsignal)):
        mpr = rainsignal[ii]

        # May = 5
        if mpr["time.month"] == 5 and mpr["time.year"] >= ymin and mpr["time.
→year"] < ymax:

            if mpr >= mpr_min and mpr < mpr_max:
                distribution.append(mpr)
                indices.append(ii)

```

```

        #mpr = dv1[ii].sel(lat=slice(32.125,38.125), lon=slice(-101.
→875,-93.875)).mean()

        # find matching input sample
        #ot= dv1[ii-1]['time']
        ot = str(np.array(mpr['time']))

        mdv1.sel(time=ot,method='nearest')
        isample = [mdv1.sel(time=ot,method='nearest'),mdv2.
→sel(time=ot,method='nearest'),mdv3.sel(time=ot,method='nearest'),mdv4.
→sel(time=ot,method='nearest'),mdv5.sel(time=ot,method='nearest'),mdv6.
→sel(time=ot,method='nearest'),mdv7.sel(time=ot,method='nearest'),mdv8.
→sel(time=ot,method='nearest')]
        #ot= dv1[ii]['time']
        #assert ot["time.day"]==isample[0]['time.day'], "Days are not
→equal"

        isample = np.array(isample)

        raininput += isample
        raincount += 1

    raininput /= raincount
    #print("days:", raincount)

    return raininput, raincount, distribution, indices

```

## 5 Plot routines

```

[11]: # POSTAGE STAMP LAYOUT
import matplotlib.pyplot as plt
import cartopy.crs as ccrs
import cartopy
import cartopy.feature as cfeature

from os.path import basename
from mpl_toolkits.axes_grid1.inset_locator import inset_axes
import matplotlib.ticker as ticker
from matplotlib import ticker

import warnings
warnings.filterwarnings("ignore")

```



```

def plot_diff_postage(sigfiles_hist, sigfiles_rcp85, vmin, vmax, mpr_min,
    ↪mpr_max, title):
    varnames = ['U850', 'V850', 'Q850', 'T700', 'Z700', 'Z500', 'U250', 'V250']
    units = ['m/s', 'm/s', 'kg/kg', 'K', 'mb', 'mb', 'm/s', 'm/s']
    #cmaps = ['PiYG', 'PuOr', 'cividis', 'inferno', 'viridis', 'viridis',
    ↪'PiYG', 'PuOr']
    cmaps = ['PiYG', 'PuOr', 'cubehelix_r', 'inferno', 'terrain', 'Spectral',
    ↪'brg', 'PuOr']

    # Ranges centered on zero for U, V
    vmin[0] = -max(abs(vmin[0]), abs(vmax[0]))
    vmax[0] = max(abs(vmin[0]), abs(vmax[0]))
    vmin[1] = -max(abs(vmin[1]), abs(vmax[1]))
    vmax[1] = max(abs(vmin[1]), abs(vmax[1]))

    # Q850 cubehelix_r, 0:maximum
    vmin[2] = 0

    # U250 brg, 0:max
    vmin[6] = 0

    # V250 PuOr, symmetric around zero
    vmin[7] = -max(abs(vmin[7]), abs(vmax[7]))
    vmax[7] = max(abs(vmin[7]), abs(vmax[7]))

    #fig, axarr = plt.subplots(nrows=3, ncols=8, figsize = (10,10*(3/8.+0.0)),
    ↪gridspec_kw={'hspace': 0.0, 'wspace': 0.0, 'height_ratios':[1,1,1.3]})
    fig, axarr = plt.subplots(nrows=len(sigfiles_hist), ncols=8, figsize =
    ↪(20,20*(len(sigfiles_hist)/8.+0.0)), subplot_kw={'projection': ccrs.
    ↪PlateCarree()}, gridspec_kw={'hspace': 0.0, 'wspace': 0.0, 'height_ratios':
    ↪[1]*(len(sigfiles_hist)-1)+[1.313]})
    lon = mdv1[0].lon
    lat = mdv1[0].lat

    # plots
    #for sigfile in sigfiles:
    #for jj, mpr_min, mpr_max, label in [[0, 0., 0.254, 'Dry'], [1, 0.254, 3.,
    ↪'Moist'], [2, 3., 9999., 'Wet']]:
    #mpr_min, mpr_max = [0., 0.254]
    for jj in range(len(sigfiles_hist)):

        # get jjth sigfile
        sigfn1 = sigfiles_hist[jj]
        sigfn2 = sigfiles_rcp85[jj]

```

```

rainsignal1 = xr.open_dataset(sigfn1)['prec']
rainsignal2 = xr.open_dataset(sigfn2)['prec']

# row label
sigfilename = basename(sigfile)
#print ("days:", count, ", model:", sigfilename)
label = ' '.join(sigfn1.split('.')[3:4])

# calc avg atm for criteria
load_uatm_mpi_hist()
avginput1, count1, distribution1, indices1 = calc_uatm_average(mpr_min,
→mpr_max, rainsignal1, -9999, 9999)
load_uatm_mpi_future()
avginput2, count2, distribution2, indices2 = calc_uatm_average(mpr_min,
→mpr_max, rainsignal2, -9999, 9999)
# future - current
avginput = avginput2-avginput1

# counts
counts1 = [0]*len(sigfiles_hist)
counts2 = [0]*len(sigfiles_rcp85)

# use percentages instead of counts (2021-10-26)
#counts[jj] = count
allavginput, allcount, alldistribution, allindices =
→calc_uatm_average(0, 9999, rainsignal1, -9999, 9999)
counts1[jj] = count1/allcount
allavginput, allcount, alldistribution, allindices =
→calc_uatm_average(0, 9999, rainsignal2, -9999, 9999)
counts2[jj] = count2/allcount

for ii in range(8):
    axarr[jj,ii].coastlines()
    axarr[jj,ii].add_feature(cfeature.STATES)
    img_extent = (lon.min(), lon.max(), lat.min(), lat.max())

    #plot = axarr[jj,ii].imshow(avginput[ii][::-1,:], vmin=vmin[ii],
→vmax=vmax[ii], cmap=cmaps[ii])

```

```

        plot = axarr[jj,ii].imshow(avginput[ii][::-1,:], vmin=vmin[ii],
→vmax=vmax[ii], cmap=cmaps[ii], origin='upper', extent=img_extent,
→transform=ccrs.PlateCarree())

        # show y tics on first column
        if ii==0:
            axarr[jj,ii].get_yaxis().set_visible(True)
            axarr[jj,ii].tick_params(labelsize='xx-small')

            # We need to draw the canvas, otherwise the labels won't be
→positioned and
            # won't have values yet.
            fig.canvas.draw()

            # lat range: 56 to 23
            labels = [item.get_text() for item in axarr[jj,ii].
→get_yticklabels()]
            #labels = ['56','46','36','26']
            axarr[jj,ii].set_yticklabels(labels)

        ## show y labels on last column
        if ii==7:
            ##axarr[jj,ii].get_yaxis().set_visible(True)
            ##axarr[jj,ii].tick_params(labelsize='xx-small')
            #
            #cbar = fig.colorbar(plot, ax=axarr[jj,ii],
→orientation="horizontal", fraction=0.03, pad=0.2)
            #
            #
            ##ax.set_ylabel("Label", rotation=270)
            #
            ##cbar = fig.colorbar(plot, ax=axarr[jj,ii],
→orientation="vertical", fraction=0.046, pad=0.016)
            #cbar.set_label('dry', rotation=90, size='xx-small')
            #cbar.ax.tick_params(labelsize='xx-small')

        if ii>=1:
            axarr[jj,ii].get_yaxis().set_visible(False)
            axarr[jj,ii].tick_params(labelsize='xx-small')

        if jj == 0:

```

```

axarr[jj,ii].set_title(varmames[ii])
axarr[jj,ii].get_xaxis().set_visible(False)
axarr[jj,ii].tick_params(labelsize='xx-small')

if jj==1:
    axarr[jj,ii].get_xaxis().set_visible(False)
    #axarr[jj,ii].tick_params(labelsize='xx-small')

# show custom tics on bottom row: lon=slice(-113,-80)
if jj==len(sigfiles_hist)-1:
    axarr[jj,ii].get_xaxis().set_visible(True)
    axarr[jj,ii].tick_params(labelsize='xx-small')

    # We need to draw the canvas, otherwise the labels won't be
    →positioned and
    # won't have values yet.
    fig.canvas.draw()

    labels = [item.get_text() for item in axarr[jj,ii].
    →get_xticklabels()]
    #labels[1] = '-113'
    #labels[2] = '-103'
    #labels[3] = '-93'
    ##labels[4] = '-83'
    axarr[jj,ii].set_xticklabels(labels)

# colorbar only on 3rd postage stamp
if jj==len(sigfiles_hist)-1:
    # use scientific notation on 3rd column colorbar only
    if ii == 2:
        def fmt(x, pos):
            a, b = '{:.1e}'.format(x).split('e')
            b = int(b)
            return r'${}e{}'.format(a, b)
        cbar = fig.colorbar(plot, ax=axarr[jj,ii],
        →orientation="horizontal", fraction=0.0385, pad=0.2, format=ticker.
        →FuncFormatter(fmt))
        #cbar = fig.colorbar(plot, ax=axarr[jj,ii],
        →orientation="horizontal", fraction=0.0385, pad=0.2, format='%.0e')
        →#format=ticker.FuncFormatter(fmt))
        #cbar.set_ticks([0.2, 0.4, 0.6, 0.8])
        #cbar.set_ticklabels(["A", "B", "C", "D"])
        tick_locator = ticker.MaxNLocator(nbins=4)
        cbar.locator = tick_locator

```

```

        cbar.update_ticks()
    else:
        cbar = fig.colorbar(plot, ax=axarr[jj,ii],
→orientation="horizontal", fraction=0.0385, pad=0.2, format=None)

        cbar.set_label(units[ii], size='xx-small')
        cbar.ax.tick_params(labelsize='xx-small')

    # row titles
    nrows = len(sigfiles_hist)
    #plt.figtext(0.09, 1-(1.4/nrows)-jj*(.73/nrows), label+':␣
→'+str(int(counts[jj]*100))+'%', fontsize=11, rotation=90)
    #plt.figtext(0.095, 1-(1.55/9)-jj*(.74/nrows), label+':␣
→'+str(int(counts1[jj]*100))+'%', fontsize=11, weight='normal', rotation=90)
    plt.figtext(0.095, 1-(1.55/9)-jj*(.74/nrows), label+':␣
→'+str(int(counts1[jj]*100))+'/' +str(int(counts2[jj]*100))+'%', fontsize=11,␣
→weight='normal', rotation=90)

#         # row title
#         sigfilename = basename(sigfile)
#         #print ("days:", count, ", model:", sigfilename)
#         rowtitle = ' '.join(sigfilename.split('.')[0:4]) # + ' Count:␣
→'+str(counts)

    # title
    #fig.suptitle(title, y=1.05, fontsize=14)
    #fig.suptitle(title, y=1-(.5/nrows), fontsize=14, fontweight="bold")
    fig.suptitle(title, y=0.92, fontsize=14)

    #plt.subplots_adjust(left=0.1, right=0.9, bottom=0.1, top=0.9, wspace=0,␣
→hspace=0)
    #plt.subplots_adjust(wspace=0, hspace=0)
    #plt.subplots_adjust(wspace=0.0, hspace=0, right=0.7)

plt.show()

```

## 6 Run over all models

## 6.0.1 Hist

```
[22]: ## find max/min for each variable accross ALL hist files

# files to consider
#sigfiles_hist = [model2absfilepath(ff, 'hist', 98, 36) for ff in_
    ↳['obs', 'raw', 'RegCM4', 'WRF', 'MPAS', 'CNN', 'SDSM', 'KDDM', 'MBCn', 'LOCA']]
sigfiles_hist = [model2absfilepath(ff, 'hist', 98, 36) for ff in_
    ↳['raw', 'RegCM4', 'WRF', 'MPAS', 'CNN', 'SDSM', 'KDDM', 'MBCn', 'LOCA']]
sigfiles_rcp85 = [model2absfilepath(ff, 'rcp85', 98, 36) for ff in_
    ↳['raw', 'RegCM4', 'WRF', 'MPAS', 'CNN', 'SDSM', 'KDDM', 'MBCn', 'LOCA']]

# find min/max values for entire sigfiles set
vmin = 9999*np.ones(8)
vmax = -9999*np.ones(8)
for ii in range(len(sigfiles_hist)):
    sigfn1 = sigfiles_hist[ii]
    sigfn2 = sigfiles_rcp85[ii]

    ## load UATM and signal file
    #if sigfile.lower().find('obs') >= 0:
    #    load_uatm_era4()

    rainsignal1 = xr.open_dataset(sigfn1)['prec']
    rainsignal2 = xr.open_dataset(sigfn2)['prec']

    for mpr_min, mpr_max in [(0,0.254), (0.254, 3.0), (3.0, 9999.0)]:
        load_uatm_mpi_hist()
        avginput1, count1, distribution1, indices1 = calc_uatm_average(mpr_min,
    ↳mpr_max, rainsignal1, -9999, 9999)
        load_uatm_mpi_future()
        avginput2, count2, distribution2, indices2 = calc_uatm_average(mpr_min,
    ↳mpr_max, rainsignal2, -9999, 9999)

        # future - current
        avginput = avginput2-avginput1

        ## subtract clim
        #if sigfile.lower().find('obs') >= 0:
        #    avginput-=era_allinput # era
        #else:
        #    avginput-=allinput # mpi

    vmin = [min(avginput[ii].min(),vmin[ii]) for ii in range(8)]
    vmax = [max(avginput[ii].max(),vmax[ii]) for ii in range(8)]
```

```
[23]: # vmin = [-1.7290460910926873, -2.1924340280545813, -0.0004643575459465322, 2.
→1634636213408385, 17.240660171236414, 43.92078080657393, -5.99357581564627, -6.
→970048931560514]c
# vmax = [2.970072688923015, 2.6753540234688, 0.0032723962877007715, 5.
→740575412338444, 70.81887385633172, 119.64943726022193, 8.746982916879485, 6.
→350572585054327]
```

```
[24]: print(vmin)
print(vmax)
```

```
[-3.0429754180793704, -3.709071938014204, -0.0010835044658083761,
0.8603813150571114, -36.53159494770762, -16.460088217440898, -9.025118991778701,
-15.47618541147965]
[4.377899975810211, 4.849721290167362, 0.003588369503707522, 8.296655861099907,
70.81887385633172, 147.6729155993853, 20.210365402161788, 13.288262560723801]
```


```
[25]: # plot rcp85-hist: dry
print("DRY:")

#sigfiles_hist = list(filter(lambda line:'hist' in line, mpi_sigfiles))
sigfiles_hist = [model2absfilepath(ff, 'hist', 98, 36) for ff in_]
→['raw', 'RegCM4', 'WRF', 'MPAS', 'CNN', 'SDSM', 'KDDM', 'MBCn', 'LOCA']]
sigfiles_rcp85 = [model2absfilepath(ff, 'rcp85', 98, 36) for ff in_]
→['raw', 'RegCM4', 'WRF', 'MPAS', 'CNN', 'SDSM', 'KDDM', 'MBCn', 'LOCA']]

#plot_models(sigfiles_hist, vmin, vmax)
plot_diff_postage(sigfiles_hist, sigfiles_rcp85, vmin, vmax, 0, 0.254,_)
→'Rcp85-Hist: Dry')
```

DRY:

Rcp85-Hist: Dry




```
[26]: # plot rcp85-hist: Moist
print("MOIST:")

#sigfiles_hist = list(filter(lambda line:'hist' in line, mpi_sigfiles))
sigfiles_hist = [model2absfilepath(ff, 'hist', 98, 36) for ff in_]
→['raw','RegCM4','WRF','MPAS','CNN','SDSM','KDDM','MBCn','LOCA']]
sigfiles_rcp85 = [model2absfilepath(ff, 'rcp85', 98, 36) for ff in_]
→['raw','RegCM4','WRF','MPAS','CNN','SDSM','KDDM','MBCn','LOCA']]
```



```
#plot_models(sigfiles_hist, vmin, vmax)
plot_diff_postage(sigfiles_hist, sigfiles_rcp85, vmin, vmax, 0.254, 3,
→'Rcp85-Hist: Moist')
```

MOIST:



```
[27]: # plot_rcp85-hist: dry
print("WET:")
```

```


#sigfiles_hist = list(filter(lambda line:'hist' in line, mpi_sigfiles))
sigfiles_hist = [model2absfilepath(ff, 'hist', 98, 36) for ff in
    →['raw', 'RegCM4', 'WRF', 'MPAS', 'CNN', 'SDSM', 'KDDM', 'MBCn', 'LOCA']]
sigfiles_rcp85 = [model2absfilepath(ff, 'rcp85', 98, 36) for ff in
    →['raw', 'RegCM4', 'WRF', 'MPAS', 'CNN', 'SDSM', 'KDDM', 'MBCn', 'LOCA']]

#plot_models(sigfiles_hist, vmin, vmax)
plot_diff_postage(sigfiles_hist, sigfiles_rcp85, vmin, vmax, 3., 9999,
    →'Rcp85-Hist: Wet')

```

WET:

Rcp85-Hist: Wet



[28]: 2

[28]: 2