Bioconductor / caBIG Task 2.6.1

Test Plan Version 1.0

[Insert approval date of document]

Document Change Record

Version Number	Date	Description
1.0	24 August 2006	Draft

TABLE OF CONTENTS

1.	INT	RODUC	TION	1
	1.1	SCOPE		1
		1.1.1	Identification	1
		1.1.2	Document Overview	1
	1.2	RESOU	RCES	2
	1.3	REFER	ENCED DOCUMENTS	2
2.	SOF	TWARI	E TEST STRATEGY	3
	2.1	OBJECT	TIVES	3
	2.2	APPRO	OACH	3
		2.2.1	caBIG Requirements	
		2.2.2	RWebServices Requirements	
		2.2.3	Exemplar Requirements	4
	2.3	DESCR	IPTION OF FUNCTIONALITY	5
	2.4		IC EXCLUSIONS	
	2.5	DEPEN	DENCIES & ASSUMPTIONS	5
	2.6	GENER	AL CRITERIA FOR SUCCESS	
		2.6.1	Readiness Criteria	
		2.6.2	Pass/Fail Criteria	
		2.6.3	Completion Criteria	
		2.6.4	Acceptance Criteria	6
3.	SOF	TWAR	E TEST ENVIRONMENT	7
	3.1	DEVEL	OPER TEST ENVIRONMENT: FRED HUTCHINSON CANCER RESEARCH CENTER	7
		3.1.1	Software Items	
		3.1.2	Hardware and Firmware Items	7
		3.1.3	Other Materials	7
		3.1.4	Participating Organizations	
	3.2		ER TEST SITE	
		3.2.1	Software Items	
		3.2.2	Hardware and Firmware Items	
		3.2.3	Other Materials	
		3.2.4	Participating Organizations	
4.	TES		EDULES	
	4.1	TIME F	RAMES FOR TESTING	9
5.	RISI	KS		10
ΑP	PEN	DIX A -	- ACRONYM LIST	11
			- TEST REPORT (TEMPLATE)	
			- TEST IDENTIFICATION	
		-	ESTS	
			to be Tested	

1. INTRODUCTION

This Test Plan prescribes the scope, approach, resources, and schedule of the testing activities. It identifies the items being tested, features to be tested, testing tasks to be performed, personnel responsible for each task, and risks associated with this plan.

1.1 SCOPE

This document provides instruction and strategy for incorporating Software Testing practices and procedures into the Bioconductor / caBIG project. This document demonstrates the application of testing on this project and provides guidelines for implementing procedures supporting this function.

Bioconductor is a collection of open-source software components based on the R programming language. Bioconductor is used for gene expression and other high-throughput analysis in molecular biology. R packages are collections of algorithms grouped to facilitate particular analyses. The software within the scope of this document allows R package developers to expose the functionality of their package as analytic services on caGRID. Our *primary concern* is the development of tools for converting existing Bioconductor packages to caGrid analytic services. Our *secondary concern* is to expose exemplar functionality as caGrid analytic services.

1.1.1 Identification

This document refers to Bioconductor / caBIG version 1.0.

1.1.2 Document Overview

This Test Plan defines the strategies necessary to accomplish the testing activities associated with Bioconductor / caBIG. Testing procedural instructions are included in the Standard Operating Procedures (SOPs). The remaining Test Plan sections are organized as follows:

- Section 2: Strategy: Describes the overall approach and techniques to be used during testing.
- Section 3. Software Test Environment: Describes the intended testing environment.
- Section 4. Test Identification: Identifies and describes each of the tests.
- Section 5. Test Schedules: Contains or references the schedules for conducting testing.
- **Section 6. Requirements Traceability:** Identifies traceability from this Test Plan to the Requirements.
- **Section 7. Risks**: Identifies the risks associated with the Test Plan.
- Section 8. Notes: Contains general information that aids in the understanding of this document.

- Appendix A. Acronym List: Defines the acronyms used on the project.
- [Appendix B. Forms and Templates: Contains the forms and templates that will be used on the project.]
- [Other appendices: Provides any additional information published separately for convenience in document maintenance.]

1.2 RESOURCES

Participants involved in creating the Project Test Plan include the Bioconductor / caBIG developers at the Fred Hutchinson Cancer Research Center, and the Adopter group located at Northwestern University. Responsibilities of these groups are outlined below.

1.3 REFERENCED DOCUMENTS

For additional project specific information, refer to the following documents:

- Bioconductor / caBIG Software Requirements and Specifications¹
- Bioconductor / caBIG Use Case documents²
- Bioconductor / caBIG UML Models³

http://gforge.nci.nih.gov/plugins/scmcvs/cvsweb.php/bioconductor/Developer_FHCC/Task%202.7.2_Final%20UML%20Models%20for%20Selected%20Bioconductor%20Packages/?cvsroot=bioconductor

 $http://gforge.nci.nih.gov/plugins/scmcvs/cvsweb.php/bioconductor/Developer_FHCC/Task\%\,202.4.2_Final\%\,20Req\,\%\,20and\%\,20Spec\%\,20Document/?cvsroot=bioconductor$

http://gforge.nci.nih.gov/plugins/scmcvs/cvsweb.php/bioconductor/Developer_FHCC/Task%202.2.2_Final%20Use%20Case%20Document/?cvsroot=bioconductor

2. SOFTWARE TEST STRATEGY

The overall software test strategy is to employ ongoing regression and integration testing during initial phases of development. As software becomes stable and comprehensive, additional system, user acceptance, and performance tests are performed.

2.1 OBJECTIVES

The objective of the test plan is to identify integration, system, and unit testing approaches to ensure deployment of a fully functional Bioconductor / caBIG v 1.0. The test plan includes provision for user acceptance testing, and outlines minimal performance expectations. Specific objectives include:

- Assure that Bioconductor / caBIG meets all approved requirements and specifications.
- Identify and record for future action all risks and issues arising during testing.
- Identify product development and user acceptance enhancements for incorporation in the initial or future software releases.

2.2 APPROACH

2.2.1 caBIG Requirements

caBIG requirements of Bioconductor / caBIG include vocabulary and data element conformance to caDSR and EVS, caCORE-like API access, and operation as caGrid analytic service. Testing these requirements primarily involve system and integration tests. Additional concerns about large-data throughput encourage performance testing.

Availability of exemplar functionality as caGrid services requires conformance to caDSR and EVS standards, caCORE-like API access, and operation as caGrid analytic service. Hence successful deployment and invocation of exemplar services on caGrid necessarily represent system and integration tests of these requirement.

Branch coverage adequacy of these requirement involves both correct return values, and generation of exceptions in response to internal error conditions during service evaluation. The coverage will be obtained by white-box tests using input data known to generate exceptional conditions.

Performance will be evaluated using white-box methods that identify 'typical' sized data objects, and measure throughput and resource use during service invocation. Performance tests will specifically exclude requirements associated with receiving, decoding, and encoding the SOAP-based service request, focusing exclusively on stages when RWebServices and the exemplars regulate data. Test success will be measured as performance within 2-fold of the equivalent evaluation executed exclusively in R.

2.2.2 RWebServices Requirements

RWebServices requirements involve production of Java class representations of R data and methods, and method dispatch and receipt of service requests, including error recovery.

Evaluating RWebServices' ability to generate analytic service interfaces involves functional and structural test approaches. A primary test type will be regression tests, comparing RWebServices generated service interfaces with hand-curated output. Test cases will be designed to evaluate multiple branches of RWebServices, including correct generation corresponding to services of individual and multiple packages, generation of Java data structures corresponding to the full range of 'native' R data types, and generation of Java data structures corresponding to complex S4 objects relevant to the domain models of the exemplar packages. Structural test cases designed to identify error conditions will also be developed.

Functional and structural methods using integration, system, and regression tests will be performed on the R / Java interface. Test suites will ensure correct round-trip data transfer between R and Java. Tests will involve R native, Java native, and S4 objects. Test data objects will include supported IEEE numerical concepts such as NaN, and Inf, the R concept of NA, and invalid object transfer. The diversity of object types provides extensive path coverage. Branch coverage is assured by the diversity of object types, including invalid object transfer.

Integration and system tests will involve RWebServices operating as a scripted server in a JUnit testing environment, with a client-side feed emulating requests for web analytic services. Components involved in these tests include RWebServices and the exemplars, in addition to the SJava package and R program. White-box methods will be used to evaluate exception and error handling.

2.2.3 Exemplar Requirements

Exemplar requirements are that the data and methods of the exemplar be exposed as web services, and that service invocation with domain- or method-specific objects and tuning parameters return appropriately structured return objects. The exemplars are also required to signal error or exception conditions.

Testing of exemplar functionality at the R level will including functional and structural testing approaches designed to provide extensive path and branch coverage. Regression testing methodologies will use data instances relevant to exposed functionality. Path and branch coverage, including handling exceptions, will be evaluated using data instances designed for these purposes.

System and integration tests of exemplar functionality will perform the test suites of the previous paragraph, but with data transfer and service invocation through RWebServices acting as a scripted server.

Performance tests of exemplar functionality will assess ability of functions invoked through RWebServices to fulfill service requirements in no less than 2x the time required for servicing

comparable requests at the native R level, and using no more than 2x the resources required for native requests.

2.3 DESCRIPTION OF FUNCTIONALITY

Functionality being evaluated is as specified in the Software Requirements and Specifications document⁴.

2.4 SPECIFIC EXCLUSIONS

The Bioconductor / caBIG software relies on the correct prior operation of additional software components, and the testing procedures here assume the correct installation and functioning of these existing components. Specific components are as follows. The grid services infrastructure, including Apache, Tomcat, and the Globus toolkit. The Java programming language. The R software for statistical analysis⁵, and underlying R / Bioconductor software packages⁶ required for service fulfillment.

The Bioconductor / caBIG software relies on specific functionality of the additional components outlined above. Key additional component functionality lying outside the scope of the testing procedures outlined here include the ability to formulate, send, and receive appropriately structured requests for analytic services. the ability of the R environment to access necessary packages and to obtain sufficient system resources and permissions for secure evaluation.

2.5 DEPENDENCIES & ASSUMPTIONS

The dependencies and assumptions include those outlined in the previous section (viz., ability to provide analytic services and to perform calculation in the R software environment).

Testing functionality of fully installed Bioconductor / caBIG software makes no special assumptions of the individual performing tests. Testing the portion of Bioconductor / caBIG that involves exposing exemplar services assumes familiarity with the caGrid environment, including detailed understanding of caGrid architecture and installation procedures. Testing procedures required for exposing services in addition to the exemplars provided by

 $http://gforge.nci.nih.gov/plugins/scmcvs/cvsweb.php/bioconductor/Developer_FHCC/Task\%202.4.2_Final\%20Req\%20and\%20Spec\%20Document/?cvsroot=bioconductor$

http://gforge.nci.nih.gov/plugins/scmcvs/cvsweb.php/bioconductor/Developer_FHCC/Task%202.2.2_Final%20Use%20Case%20Document/?cvsroot=bioconductor

 $http://gforge.nci.nih.gov/plugins/scmcvs/cvsweb.php/bioconductor/Developer_FHCC/Task\%202.2.2_Final\%20Use\%20Case\%20Document/?cvsroot=bioconductor$

SE_Test_Plan.doc 5 [Publish Date]

_

⁵ http://www.r-project.org/

⁶ http://www.bioconductor.org/

⁷ Use case 3.3.

⁸ Use cases 3.1 and 3.2,

Bioconductor / caBIG requires detailed understanding of caBIG procedures for semantic annotation, in addition to detailed understanding of underlying service functionality.

2.6 GENERAL CRITERIA FOR SUCCESS

General criteria for success are as follows:

- All tests complete
- Minor defects may be present that limit data types or other aspects of service invocation.
- Minor defects in exemplar functionality resulting in incorrect calculations will be tolerated if identified as exceptions.
- Substantial components of code will be covered, especially in assessing exemplar functionality and RWebServices performance during service invocation.

2.6.1 Readiness Criteria

Work will be ready to be tested following completion of the test plan, development of test data set and test scripts, and realization of the test environments. Unit tests will be employed throughout out product development. Readiness of software components for system and integration tests requires functional (i.e., tested) RWebServices and exemplar components.

2.6.2 Pass/Fail Criteria

Pass / fail criteria will involve test execution in conjunction with assessment of test outcomes as consistent with requirements and specifications.

2.6.3 Completion Criteria

The criteria for completion of the testing procedures is that the system produces the output specified by the test within expected performance requirements. Testing is considered completed when:

- The assigned test scripts have been executed.
- Defects and discrepancies are documented, resolved, verified, or designated as future changes.

2.6.4 Acceptance Criteria

Criteria for acceptance of completion of tests will involve successful test completion coupled with available test logs and documentation of test performance.

3. SOFTWARE TEST ENVIRONMENT

This section describes the software test environment at each intended test site.

3.1 DEVELOPER TEST ENVIRONMENT: FRED HUTCHINSON CANCER RESEARCH CENTER

The developer test environment is a stable area for independent integration, system, and regression testing for use by the developer testing team. The area is populated by objects as they are completed by developers. The environment ensures that objects are tested with supporting software components consistent with requirements and specifications of Bioconductor / caBIG. The test environment is repopulated with revised products of Bioconductor / caBIG as appropriate.

3.1.1 Software Items

Base software items at this test environment include system software (GNU/Linux), R 2.4.0, Bioconductor base packages 1.9, Java 1.5.0, SJava 0.64, gcc 4.0.2 and related libraries, Ant 1.6, Globus 4.0.2.

Software items for test performance include R CMD facilities in R, RUnit 0.4.12, and JUnit 4.0 and other tools employed in an *ad hoc* basis.

Bug tracking will use the gForge bug tracker.

3.1.2 Hardware and Firmware Items

Testing platforms include 32- and 64-bit i386 and x86_64 hardware.

3.1.3 Other Materials

Other major components include sample data sets coupled with test instructions.

3.1.4 Participating Organizations

Regression, integration, and systems testing at this site is performed by project developers.

3.2 ADOPTER TEST SITE

The Adopter test site provides a near-production environment for the client acceptance testing. Bioconductor / caBIG software components are released by the developed and managed by the adopter.

3.2.1 Software Items

Specifics of software items in the adopter test site are to be determined by the adopter, in consultation with the developer.

3.2.2 Hardware and Firmware Items

Specifics of hardware items at this test site are to be determined by the adopter, in consultation with the developer.

3.2.3 Other Materials

Test data and scripts will be provided by the developer. Additional material will be identified and produced by the adopter, in consultation with the developer

3.2.4 Participating Organizations

Adopter participation and the roles and responsibilities of specific adopters will be determined by the adopter group. The emphasis at this site is on user acceptance testing.

4. TEST SCHEDULES

Phase 1: Integration Testing

Duration: September 2006 – March 2007

Phase 2: System Testing

Duration: November 2006 – March 2007

Phase 3: User Acceptance Testing

Duration: November 2006 – March 2007

4.1 TIME FRAMES FOR TESTING

The Test Manager will coordinate with the Project Manager and add the planned testing activities to the master project schedule.

5. RISKS

Risks related to testing are identified in the project's Risk Matrix⁹.

9

 $http://gforge.nci.nih.gov/plugins/scmcvs/cvsweb.php/bioconductor/Developer_FHCC/Task\%202.1_Risk\%20Management\%20Matrix/?cvsroot=bioconductor$

APPENDIX A - ACRONYM LIST

Acronym	Description
CCR	Change control request
HSTOMP	Health Services Team Organizational Management Portal
MS	Microsoft
PM	Project Manager
RM	Requirements Manager
RTM	Requirements Traceability Matrix
SCM	Software Configuration Management
SDLC	Software Development Lifecycle
SE	Software Engineering
SEPG	Software Engineering Process Group
SM	Software Manager
SOP	Standard Operating Procedure
SPI	Software Process Improvement
SQA	Software Quality Assurance
SW	Software
TM	Test Manager
VM	Version Manager

APPENDIX B – TEST REPORT (TEMPLATE)

Test Overview

[Provide a brief overview of the tested software and summarize the testing effort noting the release version, number of test phases, number of rounds of tests executed within each test phase and the overall duration of the entire testing effort. For example, this report documents the results of the xx.xx release testing effort which consisted of xx CCRs. Testing was divided into 3 phases: Phase 1: Integration Testing, Phase 2: System Testing consisting of 2 rounds and Phase 3: User Acceptance Testing (UAT) consisting of 2 rounds. The entire duration of all combined testing phases was approximately 5 months.]

[Note the duration of each test phase by round below]

Phase 1: Integration Testing

Duration: September 2006 – March 2007

Phase 2: System Testing

Duration: November 2006 – March 2007

Phase 3: User Acceptance Testing

Duration: November 2006 – March 2007

Defect Summary

Phase 1: Integration Testing

		Opened CCRs During Phase	Resolved CCRs	Unresolved CCRs
	Х	0	0	0
₹	Х	0	0	0
Priority	Х	0	0	0
ቯ	Х	0	0	0
	Х	0	0	0
To	otal	0	0	0

Phase 2: System Testing

		Opened CCRs During Phase	Resolved CCRs	Unresolved CCRs
±.	Х	0	0	0
riorit	Х	0	0	0
₫	Х	0	0	0

		Opened CCRs During Phase	Resolved CCRs	Unresolved CCRs
	X	0	0	0
	X	0	0	0
Total		0	0	0

Phase 3: User Acceptance Testing

		Opened CCRs During Phase	Resolved CCRs	Unresolved CCRs
	Х	0	0	0
₹	Х	0	0	0
Priority	Х	0	0	0
<u> </u>	Х	0	0	0
	Х	0	0	0
Total		0	0	0

Test Script Summary

[Note the name of the test script executed, execution date, actual test script run time, pass / fail status for each testing phase in the tables below Additional tables / information can be added for each round of testing. This information can be compiled and generated from testing related software if implemented on your project.]

Phase 1: Integration Testing

Test Script Name	Date Executed	Act Run Time (minutes)	P/F	Comments

Phase 2: System Testing

Test Script Name	Date Executed	Act Run Time (minutes)	P/F	Comments

Test Script Name	Date Executed	Act Run Time (minutes)	P/F	Comments

Phase 3: User Acceptance Testing

Test Script Name	Date Executed	Act Run Time (minutes)	P/F	Comments

Conclusion

[Provide a brief summary of any deviations or problems that may have caused, or contributed to, a deviation from the test approach described in the test plan. Summarize successful practices and issues in the table below. Note possible future mitigating actions for each issue.]

Successful Practices:					
•					
•					
Areas for improvement:	Possible mitigation action:				
•	•				

APPENDIX C - TEST IDENTIFICATION

This section identifies and describes each test to which this Test Plan applies.

PLANNED TESTS

This section describes the total scope of the planned testing.

Item(s) to be Tested

CCR ID	Test Script	Dependency
Insert the identifier of the CCR, or unit(s) being tested	The name of the test script to be executed.	Any technical dependencies related to the specific test script.