



Hibernate Annotations

Reference Guide

Version: 3.3.0.GA

Table of Contents

Preface	iv
1. Setting up an annotations project	1
1.1. Requirements	1
1.2. Configuration	1
1.3. Properties	2
2. Entity Beans	4
2.1. Intro	4
2.2. Mapping with EJB3/JPA Annotations	4
2.2.1. Declaring an entity bean	4
2.2.1.1. Defining the table	4
2.2.1.2. Versioning for optimistic locking	5
2.2.2. Mapping simple properties	5
2.2.2.1. Declaring basic property mappings	5
2.2.2.2. Declaring column attributes	7
2.2.2.3. Embedded objects (aka components)	7
2.2.2.4. Non-annotated property defaults	9
2.2.. Mapping identifier properties	9
2.2.4. Mapping inheritance	12
2.2.4.1. Table per class	12
2.2.4.2. Single table per class hierarchy	13
2.2.4.3. Joined subclasses	13
2.2.4.4. Inherit properties from superclasses	14
2.2.5. Mapping entity bean associations/relationships	15
2.2.5.1. One-to-one	15
2.2.5.2. Many-to-one	17
2.2.5.3. Collections	18
2.2.5.4. Transitive persistence with cascading	23
2.2.5.5. Association fetching	24
2.2.6. Mapping composite primary and foreign keys	24
2.2.7. Mapping secondary tables	25
2.3. Mapping Queries	26
2.3. Mapping JPAQL/HQL queries. Mapping JPAQL/HQL queries	26
2.3.2. Mapping native queries	27
2.4. Hibernate Annotation Extensions	30
2.4.1. Entity	30
2.4. Identifier. Identifier	32
2.4.3. Property	32
2.4.3.1. Access type	33
2.4.3.2. Formula	34
2.4.3.3. Type	34
2.4.3.4. Index	35
2.4.3.5. @Parent	35
2.4.3.6. Generated properties	35
2.4.3.7. @Target	36
2.4.3.8. Optimistic lock	36
2.4.4. Inheritance	36
2.4.5. Single Association related annotations	36
2.4.5. Lazy options and fetching modes. Lazy options and fetching modes	37

2.4.6. Collection related annotations	38
2.4.6.1. Enhance collection settings	38
2.4.6.2. Extra collection types	39
2.4.7. Cascade	43
2.4.8. Cache	43
2.4.9. Filters	44
2.4.10. Queries	44
2.4.11. Custom SQL for CRUD operations	45
2.4.12. Tuplizer	46
Overriding metadata through XML. Overriding metadata through XML	48
Overriding metadata through XML.1. Principles	48
Overriding metadata through XML.1.1. Global level metadata	48
Overriding metadata through XML.1.2. Entity level metadata	48
Overriding metadata through XML.1.3. Property level metadata	51
Overriding metadata through XML.1.4. Association level metadata	51
4. Additional modules	53
4.1. Hibernate Validator	53
4.1.1. Description	53
4.1.2. Integration with Hibernate Annotations	53
4.2. Hibernate Search	54
4.2.1. Description	54
4.2.2. Integration with Hibernate Annotations	54

Preface

Hibernate, like all other object/relational mapping tools, requires metadata that governs the transformation of data from one representation to the other (and vice versa). In Hibernate 2.x, mapping metadata is most of the time declared in XML text files. Another option is XDoclet, utilizing Javadoc source code annotations and a preprocessor at compile time. The same kind of annotation support is now available in the standard JDK, although more powerful and better supported by tools. IntelliJ IDEA, and Eclipse for example, support auto-completion and syntax highlighting of JDK 5.0 annotations. Annotations are compiled into the bytecode and read at runtime (in Hibernate's case on startup) using reflection, so no external XML files are needed.

The EJB3 specification recognizes the interest and the success of the transparent object/relational mapping paradigm. The EJB3 specification standardizes the basic APIs and the metadata needed for any object/relational persistence mechanism. *Hibernate EntityManager* implements the programming interfaces and lifecycle rules as defined by the EJB3 persistence specification. Together with *Hibernate Annotations*, this wrapper implements a complete (and standalone) EJB3 persistence solution on top of the mature Hibernate core. You may use a combination of all three together, annotations without EJB3 programming interfaces and lifecycle, or even pure native Hibernate, depending on the business and technical needs of your project. You can at all times fall back to Hibernate native APIs, or if required, even to native JDBC and SQL.

This release is based on the final release of the EJB 3.0 / JPA specification (aka JSP-220) and support all the specification features (including the optional ones). Most of the Hibernate features and extensions are also available through Hibernate specific annotations compared to the specification are also available. While the Hibernate feature coverage is now very high, some are still missing. The eventual goal is to cover all of them. See the JIRA road map section for more informations.

If you are moving from previous Hibernate Annotations versions, please have a look at Java Persistence migration guide [<http://www.hibernate.org/398.html>].

Chapter 1. Setting up an annotations project

1.1. Requirements

- Download and unpack the Hibernate Annotations distribution from the Hibernate website.
- *This release requires Hibernate Core 3.2.0.GA and above.*
- This release is known to work on Hibernate Core 3.2.0 up to 3.2.2.GA
- Make sure you have JDK 5.0 installed or above. You can of course continue using XDoclet and get some of the benefits of annotation-based metadata with older JDK versions. Note that this document only describes JDK 5.0 annotations and you have to refer to the XDoclet documentation for more information.

1.2. Configuration

First, set up your classpath (after you have created a new project in your favorite IDE):

- Copy all Hibernate3 core and required 3rd party library files (see lib/README.txt in Hibernate).
- Copy `hibernate-annotations.jar`, `lib/hibernate-comons-annotations.jar` and `lib/ejb3-persistence.jar` from the Hibernate Annotations distribution to your classpath as well.

If you wish to use Hibernate Validator (TODO make a link to HV doc), download it from the Hibernate website and add `hibernate-validator.jar` in your classpath.

If you wish to use Hibernate Search (TODO make a link to HSearch doc), download it from the Hibernate website and add `hibernate-search.jar` and `lucene-core-x.y.z.jar` in your classpath.

We also recommend a small wrapper class to startup Hibernate in a static initializer block, known as `HibernateUtil`. You might have seen this class in various forms in other areas of the Hibernate documentation. For Annotation support you have to enhance this helper class as follows:

```
package hello;

import org.hibernate.*;
import org.hibernate.cfg.*;
import test.*;
import test.animals.Dog;

public class HibernateUtil {

    private static final SessionFactory sessionFactory;

    static {
        try {
            sessionFactory = new AnnotationConfiguration().buildSessionFactory();
        } catch (Throwable ex) {
            // Log exception!
            throw new ExceptionInInitializerError(ex);
        }
    }

    public static Session getSession()
        throws HibernateException {
```

```

        return sessionFactory.openSession();
    }
}

```

Interesting here is the use of `AnnotationConfiguration`. The packages and annotated classes are declared in your regular XML configuration file (usually `hibernate.cfg.xml`). Here is the equivalent of the above declaration:

```

<!DOCTYPE hibernate-configuration PUBLIC
"-//Hibernate/Hibernate Configuration DTD 3.0//EN"
"http://hibernate.sourceforge.net/hibernate-configuration-3.0.dtd">

<hibernate-configuration>
  <session-factory>
    <mapping package="test.animals"/>
    <mapping class="test.Flight"/>
    <mapping class="test.Sky"/>
    <mapping class="test.Person"/>
    <mapping class="test.animals.Dog"/>
    <mapping resource="test/animals/orm.xml"/>
  </session-factory>
</hibernate-configuration>

```

Note that you can mix the hbm.xml use and the new annotation one. The resource element can be either an hbm file or an EJB3 XML deployment descriptor. The distinction is transparent for your configuration process.

Alternatively, you can define the annotated classes and packages using the programmatic API

```

sessionFactory = new AnnotationConfiguration()
    .addPackage("test.animals") //the fully qualified package name
    .addAnnotatedClass(Flight.class)
    .addAnnotatedClass(Sky.class)
    .addAnnotatedClass(Person.class)
    .addAnnotatedClass(Dog.class)
    .addResource("test/animals/orm.xml")
    .buildSessionFactory();

```

You can also use the Hibernate `EntityManager` which has its own configuration mechanism. Please refer to this project documentation for more details.

There is no other difference in the way you use Hibernate APIs with annotations, except for this startup routine change or in the configuration file. You can use your favorite configuration method for other properties (`hibernate.properties`, `hibernate.cfg.xml`, programmatic APIs, etc). You can even mix annotated persistent classes and classic hbm.cfg.xml declarations with the same `SessionFactory`. You can however not declare a class several times (whether annotated or through hbm.xml). You cannot mix configuration strategies (hbm vs annotations) in a mapped entity hierarchy either.

To ease the migration process from hbm files to annotations, the configuration mechanism detects the mapping duplication between annotations and hbm files. HBM files are then prioritized over annotated metadata on a class to class basis. You can change the priority using `hibernate.mapping.precedence` property. The default is hbm, class, changing it to class, hbm will prioritize the annotated classes over hbm files when a conflict occurs.

1.3. Properties

Asides from the Hibernate core properties, Hibernate Annotations reacts to the following one

Table 1.1. List of properties

Property	Definition
hibernate.validator.apply_to_ddl	Use Hibernate Validator annotations to refine the database schema generation. Default to true.

Chapter 2. Entity Beans

2.1. Intro

This section covers EJB 3.0 (aka Java Persistence) entity annotations and Hibernate-specific extensions.

2.2. Mapping with EJB3/JPA Annotations

EJB3 entities are plain POJOs. Actually they represent the exact same concept as the Hibernate persistent entities. Their mappings are defined through JDK 5.0 annotations (an XML descriptor syntax for overriding is defined in the EJB3 specification). Annotations can be split in two categories, the logical mapping annotations (allowing you to describe the object model, the class associations, etc.) and the physical mapping annotations (describing the physical schema, tables, columns, indexes, etc). We will mix annotations from both categories in the following code examples.

EJB3 annotations are in the `javax.persistence.*` package. Most JDK 5 compliant IDE (like Eclipse, IntelliJ IDEA and Netbeans) can autocomplete annotation interfaces and attributes for you (even without a specific "EJB3" module, since EJB3 annotations are plain JDK 5 annotations).

For more and runnable concrete examples read the JBoss EJB 3.0 tutorial or review the Hibernate Annotations test suite. Most of the unit tests have been designed to represent a concrete example and be a inspiration source.

2.2.1. Declaring an entity bean

Every bound persistent POJO class is an entity bean and is declared using the `@Entity` annotation (at the class level):

```
@Entity
public class Flight implements Serializable {
    Long id;

    @Id
    public Long getId() { return id; }

    public void setId(Long id) { this.id = id; }
}
```

`@Entity` declares the class as an entity bean (i.e. a persistent POJO class), `@Id` declares the identifier property of this entity bean. The other mapping declarations are implicit. This configuration by exception concept is central to the new EJB3 specification and a major improvement. The class `Flight` is mapped to the `Flight` table, using the column `id` as its primary key column.

Depending on whether you annotate fields or methods, the access type used by Hibernate will be `field` or `property`. The EJB3 spec requires that you declare annotations on the element type that will be accessed, i.e. the getter method if you use `property` access, the field if you use `field` access. Mixing EJB3 annotations in both fields and methods should be avoided. Hibernate will guess the access type from the position of `@Id` or `@EmbeddedId`.

Defining the table

`@Table` is set at the class level; it allows you to define the table, catalog, and schema names for your entity bean mapping. If no `@Table` is defined the default values are used: the unqualified class name of the entity.

```
@Entity
@Table(name="tbl_sky")
public class Sky implements Serializable {
    ...
}
```

The `@Table` element also contains a `schema` and a `catalog` attributes, if they need to be defined. You can also define unique constraints to the table using the `@UniqueConstraint` annotation in conjunction with `@Table` (for a unique constraint bound to a single column, refer to `@Column`).

```
@Table(name="tbl_sky",
        uniqueConstraints = {@UniqueConstraint(columnNames={"month", "day"})})
)
```

A unique constraint is applied to the tuple month, day. Note that the `columnNames` array refers to the logical column names.

The logical column name is defined by the Hibernate NamingStrategy implementation. The default EJB3 naming strategy use the physical column name as the logical column name. Note that this may be different than the property name (if the column name is explicit). Unless you override the NamingStrategy, you shouldn't worry about that.

Versioning for optimistic locking

You can add optimistic locking capability to an entity bean using the `@Version` annotation:

```
@Entity
public class Flight implements Serializable {
    ...
    @Version
    @Column(name="OPTLOCK")
    public Integer getVersion() { ... }
}
```

The version property will be mapped to the `OPTLOCK` column, and the entity manager will use it to detect conflicting updates (preventing lost updates you might otherwise see with the last-commit-wins strategy).

The version column may be a numeric (the recommended solution) or a timestamp as per the EJB3 spec. Hibernate support any kind of type provided that you define and implement the appropriate `UserVersionType`.

The application must not alter the version number set up by Hibernate in any way. To artificially increase the version number, check in Hibernate Entity Manager's reference documentation `LockMode.WRITE`

2.2.2. Mapping simple properties

Declaring basic property mappings

Every non static non transient property (field or method) of an entity bean is considered persistent, unless you annotate it as `@Transient`. Not having an annotation for your property is equivalent to the appropriate `@Basic` annotation. The `@Basic` annotation allows you to declare the fetching strategy for a property:

```
public transient int counter; //transient property
```

```

private String firstname; //persistent property

@Transient
String getLengthInMeter() { ... } //transient property

String getName() {... } // persistent property

@Basic
int getLength() { ... } // persistent property

@Basic(fetch = FetchType.LAZY)
String getDetailedComment() { ... } // persistent property

@Temporal(TemporalType.TIME)
java.util.Date getDepartureTime() { ... } // persistent property

@Enumerated(STRING)
Starred getNote() { ... } //enum persisted as String in database

```

counter, a transient field, and `lengthInMeter`, a method annotated as `@Transient`, and will be ignored by the entity manager. `name`, `length`, and `firstname` properties are mapped persistent and eagerly fetched (the default for simple properties). The `detailedComment` property value will be lazily fetched from the database once a lazy property of the entity is accessed for the first time. Usually you don't need to lazy simple properties (not to be confused with lazy association fetching).

Note

To enable property level lazy fetching, your classes have to be instrumented: bytecode is added to the original one to enable such feature, please refer to the Hibernate reference documentation. If your classes are not instrumented, property level lazy loading is silently ignored.

The recommended alternative is to use the projection capability of EJB-QL or Criteria queries.

EJB3 support property mapping of all basic types supported by Hibernate (all basic Java types , their respective wrappers and serializable classes). Hibernate Annotations support out of the box Enum type mapping either into a ordinal column (saving the enum ordinal) or a string based column (saving the enum string representation): the persistence representation, defaulted to ordinal, can be overridden through the `@Enumerated` annotation as shown in the `note` property example.

In core Java APIs, the temporal precision is not defined. When dealing with temporal data you might want to describe the expected precision in database. Temporal data can have `DATE`, `TIME`, or `TIMESTAMP` precision (ie the actual date, only the time, or both). Use the `@Temporal` annotation to fine tune that.

`@Lob` indicates that the property should be persisted in a Blob or a Clob depending on the property type: `java.sql.Clob`, `Character[]`, `char[]` and `java.lang.String` will be persisted in a Clob. `java.sql.Blob`, `Byte[]`, `byte[]` and serializable type will be persisted in a Blob.

```

@Lob
public String getFullText() {
    return fullText;
}

@Lob
public byte[] getFullCode() {
    return fullCode;
}

```

If the property type implements `java.io.Serializable` and is not a basic type, and if the property is not annot-

ated with `@Lob`, then the Hibernate `serializable` type is used.

Declaring column attributes

The column(s) used for a property mapping can be defined using the `@Column` annotation. Use it to override default values (see the EJB3 specification for more information on the defaults). You can use this annotation at the property level for properties that are:

- not annotated at all
- annotated with `@Basic`
- annotated with `@Version`
- annotated with `@Lob`
- annotated with `@Temporal`
- annotated with `@org.hibernate.annotations.CollectionOfElements` (for Hibernate only)

```
@Entity
public class Flight implements Serializable {
    ...
    @Column(updatable = false, name = "flight_name", nullable = false, length=50)
    public String getName() { ... }
```

The `name` property is mapped to the `flight_name` column, which is not nullable, has a length of 50 and is not updatable (making the property immutable).

This annotation can be applied to regular properties as well as `@Id` or `@Version` properties.

```
@Column(
    name="columnName";                               (1)
    boolean unique() default false;                   (2)
    boolean nullable() default true;                  (3)
    boolean insertable() default true;                 (4)
    boolean updatable() default true;                  (5)
    String columnDefinition() default "";              (6)
    String table() default "";                         (7)
    int length() default 255;                          (8)
    int precision() default 0; // decimal precision   (9)
    int scale() default 0; // decimal scale
```

- (1) `name` (optional): the column name (default to the property name)
- (2) `unique` (optional): set a unique constraint on this column or not (default false)
- (3) `nullable` (optional): set the column as nullable (default true).
- (4) `insertable` (optional): whether or not the column will be part of the insert statement (default true)
- (5) `updatable` (optional): whether or not the column will be part of the update statement (default true)
- (6) `columnDefinition` (optional): override the sql DDL fragment for this particular column (non portable)
- (7) `table` (optional): define the targeted table (default primary table)
- (8) `length` (optional): column length (default 255)
- (8) `precision` (optional): column decimal precision (default 0)
- (10) `scale` (optional): column decimal scale if useful (default 0)

Embedded objects (aka components)

It is possible to declare an embedded component inside an entity and even override its column mapping. Component classes have to be annotated at the class level with the `@Embeddable` annotation. It is possible to override the column mapping of an embedded object for a particular entity using the `@Embedded` and `@AttributeOverride` annotation in the associated property:

```
@Entity
public class Person implements Serializable {

    // Persistent component using defaults
    Address homeAddress;

    @Embedded
    @AttributeOverrides( {
        @AttributeOverride(name="iso2", column = @Column(name="bornIso2") ),
        @AttributeOverride(name="name", column = @Column(name="bornCountryName") )
    } )
    Country bornIn;
    ...
}
```

```
@Embeddable
public class Address implements Serializable {
    String city;
    Country nationality; //no overriding here
}
```

```
@Embeddable
public class Country implements Serializable {
    private String iso2;
    @Column(name="countryName") private String name;

    public String getIso2() { return iso2; }
    public void setIso2(String iso2) { this.iso2 = iso2; }

    public String getName() { return name; }
    public void setName(String name) { this.name = name; }
    ...
}
```

A embeddable object inherit the access type of its owning entity (note that you can override that using the Hibernate specific `@AccessType` annotations (see Hibernate Annotation Extensions).

The `Person` entity bean has two component properties, `homeAddress` and `bornIn`. `homeAddress` property has not been annotated, but Hibernate will guess that it is a persistent component by looking for the `@Embeddable` annotation in the `Address` class. We also override the mapping of a column name (to `bornCountryName`) with the `@Embedded` and `@AttributeOverride` annotations for each mapped attribute of `Country`. As you can see, `Country` is also a nested component of `Address`, again using auto-detection by Hibernate and EJB3 defaults. Overriding columns of embedded objects of embedded objects is currently not supported in the EJB3 spec, however, Hibernate Annotations supports it through dotted expressions.

```
@Embedded
@AttributeOverrides( {
    @AttributeOverride(name="city", column = @Column(name="fld_city") ),
    @AttributeOverride(name="nationality.iso2", column = @Column(name="nat_Iso2") ),
    @AttributeOverride(name="nationality.name", column = @Column(name="nat_CountryName") )
    //nationality columns in homeAddress are overridden
}
```

```
} )  
Address homeAddress;
```

Hibernate Annotations supports one more feature that is not explicitly supported by the EJB3 specification. You can annotate an embeddable object with the `@MappedSuperclass` annotation to make the superclass properties persistent (see `@MappedSuperclass` for more informations).

While not supported by the EJB3 specification, Hibernate Annotations allows you to use association annotations in an embeddable object (ie `@ToOne` nor `@ToMany`). To override the association columns you can use `@AssociationOverride`.

If you want to have the same embeddable object type twice in the same entity, the column name defaulting will not work: at least one of the columns will have to be explicit. Hibernate goes beyond the EJB3 spec and allows you to enhance the defaulting mechanism through the `NamingStrategy`. `DefaultComponentSafeNamingStrategy` is a small improvement over the default `EJB3NamingStrategy` that allows embedded objects to be defaulted even if used twice in the same entity.

Non-annotated property defaults

If a property is not annotated, the following rules apply:

- If the property is of a single type, it is mapped as `@Basic`
- Otherwise, if the type of the property is annotated as `@Embeddable`, it is mapped as `@Embedded`
- Otherwise, if the type of the property is `Serializable`, it is mapped as `@Basic` in a column holding the object in its serialized version
- Otherwise, if the type of the property is `java.sql.Clob` or `java.sql.Blob`, it is mapped as `@Lob` with the appropriate `LobType`

2.2.. Mapping identifier properties

The `@Id` annotation lets you define which property is the identifier of your entity bean. This property can be set by the application itself or be generated by Hibernate (preferred). You can define the identifier generation strategy thanks to the `@GeneratedValue` annotation:

- `AUTO` - either identity column, sequence or table depending on the underlying DB
- `TABLE` - table holding the id
- `IDENTITY` - identity column
- `SEQUENCE` - sequence

Hibernate provides more id generators than the basic EJB3 ones. Check `Hibernate Annotation Extensions` for more informations.

The following example shows a sequence generator using the `SEQ_STORE` configuration (see below)

```
@Id @GeneratedValue(strategy=GenerationType.SEQUENCE, generator="SEQ_STORE")  
public Integer getId() { ... }
```

The next example uses the identity generator:

```
@Id @GeneratedValue(strategy=GenerationType.IDENTITY)
public Long getId() { ... }
```

The `AUTO` generator is the preferred type for portable applications (across several DB vendors). The identifier generation configuration can be shared for several `@Id` mappings with the generator attribute. There are several configurations available through `@SequenceGenerator` and `@TableGenerator`. The scope of a generator can be the application or the class. Class-defined generators are not visible outside the class and can override application level generators. Application level generators are defined at XML level (see Chapter Overriding metadata through XML, *Overriding metadata through XML*):

```
<table-generator name="EMP_GEN"
    table="GENERATOR_TABLE"
    pk-column-name="key"
    value-column-name="hi"
    pk-column-value="EMP"
    allocation-size="20"/>

//and the annotation equivalent

@javax.persistence.TableGenerator(
    name="EMP_GEN",
    table="GENERATOR_TABLE",
    pkColumnName = "key",
    valueColumnName = "hi"
    pkColumnValue="EMP",
    allocationSize=20
)

<sequence-generator name="SEQ_GEN"
    sequence-name="my_sequence"
    allocation-size="20"/>

//and the annotation equivalent

@javax.persistence.SequenceGenerator(
    name="SEQ_GEN",
    sequenceName="my_sequence",
    allocationSize=20
)
```

If JPA XML (like `META-INF/orm.xml`) is used to define the generators, `EMP_GEN` and `SEQ_GEN` are application level generators. `EMP_GEN` defines a table based id generator using the hilo algorithm with a `max_lo` of 20. The `hi` value is kept in a table `"GENERATOR_TABLE"`. The information is kept in a row where `pkColumnName` `"key"` is equals to `pkColumnValue` `"EMP"` and column `valueColumnName` `"hi"` contains the the next high value used.

`SEQ_GEN` defines a sequence generator using a sequence named `my_sequence`. The allocation size used for this sequence based hilo algorithm is 20. Note that this version of Hibernate Annotations does not handle `initial-value` in the sequence generator. The default allocation size is 50, so if you want to use a sequence and pickup the value each time, you must set the allocation size to 1.

Note

Package level definition is no longer supported by the EJB 3.0 specification. However, you can use the `@GenericGenerator` at the package level (see Section 2.4.Identifier, “Identifier”).

The next example shows the definition of a sequence generator in a class scope:

```
@Entity
@GeneratedValue(
    name="SEQ_STORE",
    sequenceName="my_sequence"
)
public class Store implements Serializable {
    private Long id;

    @Id @GeneratedValue(strategy=GenerationType.SEQUENCE, generator="SEQ_STORE")
    public Long getId() { return id; }
}
```

This class will use a sequence named `my_sequence` and the `SEQ_STORE` generator is not visible in other classes. Note that you can check the Hibernate Annotations tests in the `org.hibernate.test.metadata.id` package for more examples.

You can define a composite primary key through several syntaxes:

- annotate the component property as `@Id` and make the component class `@Embeddable`
- annotate the component property as `@EmbeddedId`
- annotate the class as `@IdClass` and annotate each property of the entity involved in the primary key with `@Id`

While quite common to the EJB2 developer, `@IdClass` is likely new for Hibernate users. The composite primary key class corresponds to multiple fields or properties of the entity class, and the names of primary key fields or properties in the primary key class and those of the entity class must match and their types must be the same. Let's look at an example:

```
@Entity
@IdClass(FootballerPk.class)
public class Footballer {
    //part of the id key
    @Id public String getFirstname() {
        return firstname;
    }

    public void setFirstname(String firstname) {
        this.firstname = firstname;
    }

    //part of the id key
    @Id public String getLastname() {
        return lastname;
    }

    public void setLastname(String lastname) {
        this.lastname = lastname;
    }

    public String getClub() {
        return club;
    }

    public void setClub(String club) {
        this.club = club;
    }

    //appropriate equals() and hashCode() implementation
}
```

```

@Embeddable
public class FootballerPk implements Serializable {
    //same name and type as in Footballer
    public String getFirstname() {
        return firstname;
    }

    public void setFirstname(String firstname) {
        this.firstname = firstname;
    }

    //same name and type as in Footballer
    public String getLastname() {
        return lastname;
    }

    public void setLastname(String lastname) {
        this.lastname = lastname;
    }

    //appropriate equals() and hashCode() implementation
}

```

As you may have seen, `@IdClass` points to the corresponding primary key class.

While not supported by the EJB3 specification, Hibernate allows you to define associations inside a composite identifier. Simply use the regular annotations for that

```

@Entity
@AssociationOverride( name="id.channel", joinColumns = @JoinColumn(name="chan_id") )
public class TvMagazin {
    @EmbeddedId public TvMagazinPk id;
    @Temporal(TemporalType.TIME) Date time;
}

@Embeddable
public class TvMagazinPk implements Serializable {
    @ManyToOne
    public Channel channel;
    public String name;
    @ManyToOne
    public Presenter presenter;
}

```

2.2.4. Mapping inheritance

EJB3 supports the three types of inheritance:

- Table per Class Strategy: the `<union-class>` element in Hibernate
- Single Table per Class Hierarchy Strategy: the `<subclass>` element in Hibernate
- Joined Subclass Strategy: the `<joined-subclass>` element in Hibernate

The chosen strategy is declared at the class level of the top level entity in the hierarchy using the `@Inheritance` annotation.

Note

Annotating interfaces is currently not supported.

Table per class

This strategy has many drawbacks (esp. with polymorphic queries and associations) explained in the EJB3 spec, the Hibernate reference documentation, Hibernate in Action, and many other places. Hibernate work around most of them implementing this strategy using SQL UNION queries. It is commonly used for the top level of an inheritance hierarchy:

```
@Entity
@Inheritance(strategy = InheritanceType.TABLE_PER_CLASS)
public class Flight implements Serializable {
```

This strategy support one to many associations provided that they are bidirectional. This strategy does not support the IDENTITY generator strategy: the id has to be shared across several tables. Consequently, when using this strategy, you should not use AUTO nor IDENTITY.

Single table per class hierarchy

All properties of all super- and subclasses are mapped into the same table, instances are distinguished by a special discriminator column:

```
@Entity
@Inheritance(strategy=InheritanceType.SINGLE_TABLE)
@DiscriminatorColumn(
    name="planetype",
    discriminatorType=DiscriminatorType.STRING
)
@DiscriminatorValue("Plane")
public class Plane { ... }

@Entity
@DiscriminatorValue("A320")
public class A320 extends Plane { ... }
```

Plane is the superclass, it defines the inheritance strategy `InheritanceType.SINGLE_TABLE`. It also defines the discriminator column through the `@DiscriminatorColumn` annotation, a discriminator column can also define the discriminator type. Finally, the `@DiscriminatorValue` annotation defines the value used to differentiate a class in the hierarchy. All of these attributes have sensible default values. The default name of the discriminator column is `DTYPE`. The default discriminator value is the entity name (as defined in `@Entity.name`) for `DiscriminatorType.STRING`. A320 is a subclass; you only have to define discriminator value if you don't want to use the default value. The strategy and the discriminator type are implicit.

`@Inheritance` and `@DiscriminatorColumn` should only be defined at the top of the entity hierarchy.

Joined subclasses

The `@PrimaryKeyJoinColumn` and `@PrimaryKeyJoinColumns` annotations define the primary key(s) of the joined subclass table:

```
@Entity
@Inheritance(strategy=InheritanceType.JOINED)
public class Boat implements Serializable { ... }

@Entity
public class Ferry extends Boat { ... }

@Entity
@PrimaryKeyJoinColumn(name="BOAT_ID")
```

```
public class AmericaCupClass extends Boat { ... }
```

All of the above entities use the `JOINED` strategy, the `Ferry` table is joined with the `Boat` table using the same primary key names. The `AmericaCupClass` table is joined with `Boat` using the join condition `Boat.id = AmericaCupClass.BOAT_ID`.

Inherit properties from superclasses

This is sometimes useful to share common properties through a technical or a business superclass without including it as a regular mapped entity (ie no specific table for this entity). For that purpose you can map them as `@MappedSuperclass`.

```
@MappedSuperclass
public class BaseEntity {
    @Basic
    @Temporal(TemporalType.TIMESTAMP)
    public Date getLastUpdate() { ... }
    public String getLastUpdater() { ... }
    ...
}

@Entity class Order extends BaseEntity {
    @Id public Integer getId() { ... }
    ...
}
```

In database, this hierarchy will be represented as an `Order` table having the `id`, `lastUpdate` and `lastUpdater` columns. The embedded superclass property mappings are copied into their entity subclasses. Remember that the embeddable superclass is not the root of the hierarchy though.

Note

Properties from superclasses not mapped as `@MappedSuperclass` are ignored.

Note

The access type (field or methods), is inherited from the root entity, unless you use the Hibernate annotation `@AccessType`

Note

The same notion can be applied to `@Embeddable` objects to persist properties from their superclasses. You also need to use `@MappedSuperclass` to do that (this should not be considered as a standard EJB3 feature though)

Note

It is allowed to mark a class as `@MappedSuperclass` in the middle of the mapped inheritance hierarchy.

Note

Any class in the hierarchy non annotated with `@MappedSuperclass` nor `@Entity` will be ignored.

You can override columns defined in entity superclasses at the root entity level using the `@AttributeOverride` annotation.

```

@MappedSuperclass
public class FlyingObject implements Serializable {

    public int getAltitude() {
        return altitude;
    }

    @Transient
    public int getMetricAltitude() {
        return metricAltitude;
    }

    @ManyToOne
    public PropulsionType getPropulsion() {
        return metricAltitude;
    }
    ...
}

@Entity
@AttributeOverride( name="altitude", column = @Column(name="fld_altitude") )
@AssociationOverride( name="propulsion", joinColumns = @JoinColumn(name="fld_propulsion_fk") )
public class Plane extends FlyingObject {
    ...
}

```

The altitude property will be persisted in an `fld_altitude` column of table `Plane` and the propulsion association will be materialized in a `fld_propulsion_fk` foreign key column.

You can define `@AttributeOverride(s)` and `@AssociationOverride(s)` on `@Entity` classes, `@MappedSuperclass` classes and properties pointing to an `@Embeddable` object.

2.2.5. Mapping entity bean associations/relationships

One-to-one

You can associate entity beans through a one-to-one relationship using `@OneToOne`. There are three cases for one-to-one associations: either the associated entities share the same primary keys values, a foreign key is held by one of the entities (note that this FK column in the database should be constrained unique to simulate one-to-one multiplicity), or a association table is used to store the link between the 2 entities (a unique constraint has to be defined on each fk to ensure the one to one multiplicity)

First, we map a real one-to-one association using shared primary keys:

```

@Entity
public class Body {
    @Id
    public Long getId() { return id; }

    @OneToOne(cascade = CascadeType.ALL)
    @PrimaryKeyJoinColumn
    public Heart getHeart() {
        return heart;
    }
    ...
}

```

```

@Entity
public class Heart {
    @Id

```

```

    public Long getId() { ...}
}

```

The one to one is marked as true by using the `@PrimaryKeyJoinColumn` annotation.

In the following example, the associated entities are linked through a foreign key column:

```

@Entity
public class Customer implements Serializable {
    @OneToOne(cascade = CascadeType.ALL)
    @JoinColumn(name="passport_fk")
    public Passport getPassport() {
        ...
    }
}

@Entity
public class Passport implements Serializable {
    @OneToOne(mappedBy = "passport")
    public Customer getOwner() {
        ...
    }
}

```

A Customer is linked to a Passport, with a foreign key column named `passport_fk` in the Customer table. The join column is declared with the `@JoinColumn` annotation which looks like the `@Column` annotation. It has one more parameters named `referencedColumnName`. This parameter declares the column in the targeted entity that will be used to the join. Note that when using `referencedColumnName` to a non primary key column, the associated class has to be `Serializable`. Also note that the `referencedColumnName` to a non primary key column has to be mapped to a property having a single column (other cases might not work).

The association may be bidirectional. In a bidirectional relationship, one of the sides (and only one) has to be the owner: the owner is responsible for the association column(s) update. To declare a side as *not* responsible for the relationship, the attribute `mappedBy` is used. `mappedBy` refers to the property name of the association on the owner side. In our case, this is `passport`. As you can see, you don't have to (must not) declare the join column since it has already been declared on the owners side.

If no `@JoinColumn` is declared on the owner side, the defaults apply. A join column(s) will be created in the owner table and its name will be the concatenation of the name of the relationship in the owner side, `_` (underscore), and the name of the primary key column(s) in the owned side. In this example `passport_id` because the property name is `passport` and the column id of `Passport` is `id`.

The third possibility (using an association table) is very exotic.

```

@Entity
public class Customer implements Serializable {
    @OneToOne(cascade = CascadeType.ALL)
    @JoinTable(name = "CustomerPassports"
        joinColumns = @JoinColumn(name="customer_fk"),
        inverseJoinColumns = @JoinColumn(name="passport_fk"))
    )
    public Passport getPassport() {
        ...
    }
}

@Entity
public class Passport implements Serializable {
    @OneToOne(mappedBy = "passport")
    public Customer getOwner() {
        ...
    }
}

```

```
}
```

A Customer is linked to a Passport through a association table named CustomerPassports ; this association table has a foreign key column named passport_fk pointing to the Passport table (materialized by the inverseJoinColumn, and a foreign key column named customer_fk pointing to the Customer table materialized by the joinColumns attribute.

You must declare the join table name and the join columns explicitly in such a mapping.

Many-to-one

Many-to-one associations are declared at the property level with the annotation @ManyToOne:

```
@Entity()
public class Flight implements Serializable {
    @ManyToOne( cascade = {CascadeType.PERSIST, CascadeType.MERGE} )
    @JoinColumn(name="COMP_ID")
    public Company getCompany() {
        return company;
    }
    ...
}
```

The @JoinColumn attribute is optional, the default value(s) is like in one to one, the concatenation of the name of the relationship in the owner side, _ (underscore), and the name of the primary key column in the owned side. In this example company_id because the property name is company and the column id of Company is id.

@ManyToOne has a parameter named targetEntity which describes the target entity name. You usually don't need this parameter since the default value (the type of the property that stores the association) is good in almost all cases. However this is useful when you want to use interfaces as the return type instead of the regular entity.

```
@Entity()
public class Flight implements Serializable {
    @ManyToOne( cascade = {CascadeType.PERSIST, CascadeType.MERGE}, targetEntity=CompanyImpl.class )
    @JoinColumn(name="COMP_ID")
    public Company getCompany() {
        return company;
    }
    ...
}

public interface Company {
    ...
}
```

You can also map a many to one association through an association table. This association table described by the @JoinTable annotation will contains a foreign key referencing back the entity table (through @JoinTable.joinColumns) and a a foreign key referencing the target entity table (through @JoinTable.inverseJoinColumns).

```
@Entity()
public class Flight implements Serializable {
    @ManyToOne( cascade = {CascadeType.PERSIST, CascadeType.MERGE} )
    @JoinTable(name="Flight_Company",
        joinColumns = @JoinColumn(name="FLIGHT_ID"),
        inverseJoinColumns = @JoinColumn(name="COMP_ID")
    )
    public Company getCompany() {
        return company;
    }
    ...
}
```

```

    )
    public Company getCompany() {
        return company;
    }
    ...
}

```

Collections

Overview

You can map `Collection`, `List` (ie ordered lists, not indexed lists), `Map` and `Set`. The EJB3 specification describes how to map an ordered list (ie a list ordered at load time) using `@javax.persistence.OrderBy` annotation: this annotation takes into parameter a list of comma separated (target entity) properties to order the collection by (eg `firstname asc, age desc`), if the string is empty, the collection will be ordered by id. For true indexed collections, please refer to the Hibernate Annotation Extensions. EJB3 allows you to map Maps using as a key one of the target entity property using `@MapKey(name="myProperty")` (`myProperty` is a property name in the target entity). When using `@MapKey` (without property name), the target entity primary key is used. The map key uses the same column as the property pointed out: there is no additional column defined to hold the map key, and it does make sense since the map key actually represent a target property. Be aware that once loaded, the key is no longer kept in sync with the property, in other words, if you change the property value, the key will not change automatically in your Java model (for true map support please refers to Hibernate Annotation Extensions). Many people confuse `<map>` capabilities and `@MapKey` ones. These are two different features. `@MapKey` still has some limitations, please check the forum or the JIRA tracking system for more informations.

Hibernate has several notions of collections.

Table 2.1. Collections semantics

Semantic	java representation	annotations
Bag semantic	<code>java.util.List</code> , <code>java.util.Collection</code>	<code>@org.hibernate.annotations.CollectionOfElements</code> or <code>@OneToMany</code> or <code>@ManyToMany</code>
Bag semantic with primary key (withtout the limitations of Bag semantic)	<code>java.util.List</code> , <code>java.util.Collection</code>	(<code>@org.hibernate.annotations.CollectionOfElements</code> or <code>@OneToMany</code> or <code>@ManyToMany</code>) and <code>@CollectionId</code>
List semantic	<code>java.util.List</code>	(<code>@org.hibernate.annotations.CollectionOfElements</code> or <code>@OneToMany</code> or <code>@ManyToMany</code>) and <code>@org.hibernate.annotations.IndexColumn</code>
Set semantic	<code>java.util.Set</code>	<code>@org.hibernate.annotations.CollectionOfElements</code> or <code>@OneToMany</code> or <code>@ManyToMany</code>
Map semantic	<code>java.util.Map</code>	(<code>@org.hibernate.annotations.CollectionOfElements</code> or <code>@OneToMany</code> or <code>@ManyToMany</code>) and (nothing or

Semantic	java representation	annotations
		@org.hibernate.annotations.MapKey/MapKeyManyToMany for true map support, OR @javax.persistence.MapKey

So specifically, *java.util.List* collections without *@org.hibernate.annotations.IndexColumn* are going to be considered as bags.

Collection of primitive, core type or embedded objects is not supported by the EJB3 specification. Hibernate Annotations allows them however (see Hibernate Annotation Extensions).

```

@Entity public class City {
    @OneToMany(mappedBy="city")
    @OrderBy("streetName")
    public List<Street> getStreets() {
        return streets;
    }
    ...
}

@Entity public class Street {
    public String getStreetName() {
        return streetName;
    }

    @ManyToOne
    public City getCity() {
        return city;
    }
    ...
}

@Entity
public class Software {
    @OneToMany(mappedBy="software")
    @MapKey(name="codeName")
    public Map<String, Version> getVersions() {
        return versions;
    }
    ...
}

@Entity
@Table(name="tbl_version")
public class Version {
    public String getCodeName() {...}

    @ManyToOne
    public Software getSoftware() { ... }
    ...
}

```

So City has a collection of Streets that are ordered by *streetName* (of *Street*) when the collection is loaded. Software has a map of Versions which key is the Version *codeName*.

Unless the collection is a generic, you will have to define *targetEntity*. This is a annotation attribute that take the target entity class as a value.

One-to-many

One-to-many associations are declared at the property level with the annotation *@OneToMany*. One to many asso-

ciations may be bidirectional.

Bidirectional

Since many to one are (almost) always the owner side of a bidirectional relationship in the EJB3 spec, the one to many association is annotated by `@OneToMany(mappedBy=...)`

```
@Entity
public class Troop {
    @OneToMany(mappedBy="troop")
    public Set<Soldier> getSoldiers() {
        ...
    }

@Entity
public class Soldier {
    @ManyToOne
    @JoinColumn(name="troop_fk")
    public Troop getTroop() {
        ...
    }
}
```

`Troop` has a bidirectional one to many relationship with `Soldier` through the `troop` property. You don't have to (must not) define any physical mapping in the `mappedBy` side.

To map a bidirectional one to many, with the one-to-many side as the owning side, you have to remove the `mappedBy` element and set the many to one `@JoinColumn` as insertable and updatable to false. This solution is obviously not optimized and will produce some additional UPDATE statements.

```
@Entity
public class Troop {
    @OneToMany
    @JoinColumn(name="troop_fk") //we need to duplicate the physical information
    public Set<Soldier> getSoldiers() {
        ...
    }

@Entity
public class Soldier {
    @ManyToOne
    @JoinColumn(name="troop_fk", insertable=false, updatable=false)
    public Troop getTroop() {
        ...
    }
}
```

Unidirectional

A unidirectional one to many using a foreign key column in the owned entity is not that common and not really recommended. We strongly advise you to use a join table for this kind of association (as explained in the next section). This kind of association is described through a `@JoinColumn`

```
@Entity
public class Customer implements Serializable {
    @OneToMany(cascade=CascadeType.ALL, fetch=FetchType.EAGER)
    @JoinColumn(name="CUST_ID")
    public Set<Ticket> getTickets() {
        ...
    }

@Entity
public class Ticket implements Serializable {
    ... //no bidir
}
```


Customer describes a unidirectional relationship with Ticket using the join column CUST_ID.

Unidirectional with join table

A unidirectional one to many with join table is much preferred. This association is described through an @JoinTable.

```
@Entity
public class Trainer {
    @OneToMany
    @JoinTable(
        name="TrainedMonkeys",
        joinColumns = { @JoinColumn( name="trainer_id") },
        inverseJoinColumns = @JoinColumn( name="monkey_id")
    )
    public Set<Monkey> getTrainedMonkeys() {
        ...
    }
}

@Entity
public class Monkey {
    ... //no bidir
}
```

Trainer describes a unidirectional relationship with Monkey using the join table TrainedMonkeys, with a foreign key trainer_id to Trainer (joinColumns) and a foreign key monkey_id to Monkey (inverseJoinColumns).

Defaults

Without describing any physical mapping, a unidirectional one to many with join table is used. The table name is the concatenation of the owner table name, _, and the other side table name. The foreign key name(s) referencing the owner table is the concatenation of the owner table, _, and the owner primary key column(s) name. The foreign key name(s) referencing the other side is the concatenation of the owner property name, _, and the other side primary key column(s) name. A unique constraint is added to the foreign key referencing the other side table to reflect the one to many.

```
@Entity
public class Trainer {
    @OneToMany
    public Set<Tiger> getTrainedTigers() {
        ...
    }
}

@Entity
public class Tiger {
    ... //no bidir
}
```

Trainer describes a unidirectional relationship with Tiger using the join table Trainer_Tiger, with a foreign key trainer_id to Trainer (table name, _, trainer id) and a foreign key trainedTigers_id to Monkey (property name, _, Tiger primary column).

Many-to-many

Definition

A many-to-many association is defined logically using the `@ManyToMany` annotation. You also have to describe the association table and the join conditions using the `@JoinTable` annotation. If the association is bidirectional, one side has to be the owner and one side has to be the inverse end (ie. it will be ignored when updating the relationship values in the association table):

```
@Entity
public class Employer implements Serializable {
    @ManyToMany(
        targetEntity=org.hibernate.test.metadata.manytomany.Employee.class,
        cascade={CascadeType.PERSIST, CascadeType.MERGE}
    )
    @JoinTable(
        name="EMPLOYER_EMPLOYEE",
        joinColumns={@JoinColumn(name="EMPER_ID")},
        inverseJoinColumns={@JoinColumn(name="EMPEE_ID")}
    )
    public Collection getEmployees() {
        return employees;
    }
    ...
}
```

```
@Entity
public class Employee implements Serializable {
    @ManyToMany(
        cascade={CascadeType.PERSIST, CascadeType.MERGE},
        mappedBy="employees"
        targetEntity=Employer.class
    )
    public Collection getEmployers() {
        return employers;
    }
}
```

We've already shown the many declarations and the detailed attributes for associations. We'll go deeper in the `@JoinTable` description, it defines a `name`, an array of join columns (an array in annotation is defined using { A, B, C }), and an array of inverse join columns. The latter ones are the columns of the association table which refer to the `Employee` primary key (the "other side").

As seen previously, the other side don't have to (must not) describe the physical mapping: a simple `mappedBy` argument containing the owner side property name bind the two.

Default values

As any other annotations, most values are guessed in a many to many relationship. Without describing any physical mapping in a unidirectional many to many the following rules applied. The table name is the concatenation of the owner table name, `_` and the other side table name. The foreign key name(s) referencing the owner table is the concatenation of the owner table name, `_` and the owner primary key column(s). The foreign key name(s) referencing the other side is the concatenation of the owner property name, `_`, and the other side primary key column(s). These are the same rules used for a unidirectional one to many relationship.

```
@Entity
public class Store {
    @ManyToMany(cascade = CascadeType.PERSIST)
    public Set<City> getImplantedIn() {
        ...
    }
}
```

```
@Entity
public class City {
    ... //no bidirectional relationship
}
```

A `Store_City` is used as the join table. The `Store_id` column is a foreign key to the `Store` table. The `im-plantedIn_id` column is a foreign key to the `City` table.

Without describing any physical mapping in a bidirectional many to many the following rules applied. The table name is the concatenation of the owner table name, `_` and the other side table name. The foreign key name(s) referencing the owner table is the concatenation of the other side property name, `_`, and the owner primary key column(s). The foreign key name(s) referencing the other side is the concatenation of the owner property name, `_`, and the other side primary key column(s). These are the same rules used for a unidirectional one to many relationship.

```
@Entity
public class Store {
    @ManyToMany(cascade = {CascadeType.PERSIST, CascadeType.MERGE})
    public Set<Customer> getCustomers() {
        ...
    }
}

@Entity
public class Customer {
    @ManyToMany(mappedBy="customers")
    public Set<Store> getStores() {
        ...
    }
}
```

A `Store_Customer` is used as the join table. The `stores_id` column is a foreign key to the `Store` table. The `customers_id` column is a foreign key to the `Customer` table.

Transitive persistence with cascading

You probably have noticed the `cascade` attribute taking an array of `CascadeType` as a value. The cascade concept in EJB3 is very similar to the transitive persistence and cascading of operations in Hibernate, but with slightly different semantics and cascading types:

- `CascadeType.PERSIST`: cascades the persist (create) operation to associated entities `persist()` is called or if the entity is managed
- `CascadeType.MERGE`: cascades the merge operation to associated entities if `merge()` is called or if the entity is managed
- `CascadeType.REMOVE`: cascades the remove operation to associated entities if `delete()` is called
- `CascadeType.REFRESH`: cascades the refresh operation to associated entities if `refresh()` is called
- `CascadeType.ALL`: all of the above

Note

`CascadeType.ALL` also covers Hibernate specific operations like save-update, lock etc... Check Cascade for more information

Please refer to the chapter 6.3 of the EJB3 specification for more information on cascading and create/merge semantics.

Association fetching

You have the ability to either eagerly or lazily fetch associated entities. The `fetch` parameter can be set to `FetchType.LAZY` or `FetchType.EAGER`. `EAGER` will try to use an outer join select to retrieve the associated object, while `LAZY` will only trigger a select when the associated object is accessed for the first time. `@OneToMany` and `@ManyToMany` associations are defaulted to `LAZY` and `@OneToOne` and `@ManyToOne` are defaulted to `EAGER`. For more information about static fetching, check Section 2.4.5. Lazy options and fetching modes, “Lazy options and fetching modes”.

The recommended approach is to use `LAZY` on all static fetching definitions and override this choice dynamically through JPA-QL. JPA-QL has a `fetch` keyword that allows you to override laziness when doing a particular query. This is very useful to improve performance and is decided on a use case to use case basis.

2.2.6. Mapping composite primary and foreign keys

Composite primary keys use an embedded class as the primary key representation, so you'd use the `@Id` and `@Embeddable` annotations. Alternatively, you can use the `@EmbeddedId` annotation. Note that the dependent class has to be serializable and implements `equals()`/`hashCode()`. You can also use `@IdClass` as described in Mapping identifier properties.

```
@Entity
public class RegionalArticle implements Serializable {

    @Id
    public RegionalArticlePk getPk() { ... }
}

@Embeddable
public class RegionalArticlePk implements Serializable { ... }
```

or alternatively

```
@Entity
public class RegionalArticle implements Serializable {

    @EmbeddedId
    public RegionalArticlePk getPk() { ... }
}

public class RegionalArticlePk implements Serializable { ... }
```

`@Embeddable` inherit the access type of its owning entity unless the Hibernate specific annotation `@AccessType` is used. Composite foreign keys (if not using the default sensitive values) are defined on associations using the `@JoinColumns` element, which is basically an array of `@JoinColumn`. It is considered a good practice to express `referencedColumnNames` explicitly. Otherwise, Hibernate will suppose that you use the same order of columns as in the primary key declaration.

```

@Entity
public class Parent implements Serializable {
    @Id
    public ParentPk id;
    public int age;

    @OneToMany(cascade=CascadeType.ALL)
    @JoinColumns ({
        @JoinColumn(name="parentCivility", referencedColumnName = "isMale"),
        @JoinColumn(name="parentLastName", referencedColumnName = "lastName"),
        @JoinColumn(name="parentFirstName", referencedColumnName = "firstName")
    })
    public Set<Child> children; //unidirectional
    ...
}

```

```

@Entity
public class Child implements Serializable {
    @Id @GeneratedValue
    public Integer id;

    @ManyToOne
    @JoinColumns ({
        @JoinColumn(name="parentCivility", referencedColumnName = "isMale"),
        @JoinColumn(name="parentLastName", referencedColumnName = "lastName"),
        @JoinColumn(name="parentFirstName", referencedColumnName = "firstName")
    })
    public Parent parent; //unidirectional
}

```

```

@Embeddable
public class ParentPk implements Serializable {
    String firstName;
    String lastName;
    ...
}

```

Note the explicit usage of the `referencedColumnName`.

2.2.7. Mapping secondary tables

You can map a single entity bean to several tables using the `@SecondaryTable` or `@SecondaryTables` class level annotations. To express that a column is in a particular table, use the `table` parameter of `@Column` or `@JoinColumn`.

```

@Entity
@Table(name="MainCat")
@SecondaryTables({
    @SecondaryTable(name="Cat1", pkJoinColumns={
        @PrimaryKeyJoinColumn(name="cat_id", referencedColumnName="id")
    }),
    @SecondaryTable(name="Cat2", uniqueConstraints={@UniqueConstraint(columnNames={"storyPart2"})})
})
public class Cat implements Serializable {

    private Integer id;
    private String name;
    private String storyPart1;
    private String storyPart2;
}

```

```

@Id @GeneratedValue
public Integer getId() {
    return id;
}

public String getName() {
    return name;
}

@Column(table="Cat1")
public String getStoryPart1() {
    return storyPart1;
}

@Column(table="Cat2")
public String getStoryPart2() {
    return storyPart2;
}

```

In this example, name will be in MainCat. storyPart1 will be in Cat1 and storyPart2 will be in Cat2. Cat1 will be joined to MainCat using the cat_id as a foreign key, and Cat2 using id (ie the same column name, the MainCat id column has). Plus a unique constraint on storyPart2 has been set.

Check out the JBoss EJB 3 tutorial or the Hibernate Annotations unit test suite for more examples.

2.3. Mapping Queries

2.3.Mapping JPAQL/HQL queries. Mapping JPAQL/HQL queries

You can map EJBQL/HQL queries using annotations. @NamedQuery and @NamedQueries can be defined at the class level or in a JPA XML file. However their definitions are global to the session factory/entity manager factory scope. A named query is defined by its name and the actual query string.

```

<entity-mappings>
  <named-query name="plane.getAll">
    <query>select p from Plane p</query>
  </named-query>
  ...
</entity-mappings>
...

@Entity
@NamedQuery(name="night.moreRecentThan", query="select n from Night n where n.date >= :date")
public class Night {
    ...
}

public class MyDao {
    doStuff() {
        Query q = s.getNamedQuery("night.moreRecentThan");
        q.setDate( "date", aMonthAgo );
        List results = q.list();
        ...
    }
    ...
}

```

You can also provide some hints to a query through an array of QueryHint through a hints attribute.

The available Hibernate hints are

Table 2.2. Query hints

hint	description
org.hibernate.cacheable	Whether the query should interact with the second level cache (default to false)
org.hibernate.cacheRegion	Cache region name (default used otherwise)
org.hibernate.timeout	Query timeout
org.hibernate.fetchSize	resultset fetch size
org.hibernate.flushMode	Flush mode used for this query
org.hibernate.cacheMode	Cache mode used for this query
org.hibernate.readOnly	Entities loaded by this query should be in read only mode or not (default to false)
org.hibernate.comment	Query comment added to the generated SQL

2.3.2. Mapping native queries

You can also map a native query (ie a plain SQL query). To achieve that, you need to describe the SQL result-set structure using `@SqlResultSetMapping` (or `@SqlResultSetMappings` if you plan to define several resultset mappings). Like `@NamedQuery`, a `@SqlResultSetMapping` can be defined at class level or in a JPA XML file. However its scope is global to the application.

As we will see, a `resultSetMapping` parameter is defined in `@NamedNativeQuery`, it represents the name of a defined `@SqlResultSetMapping`. The resultset mapping declares the entities retrieved by this native query. Each field of the entity is bound to an SQL alias (or column name). All fields of the entity including the ones of subclasses and the foreign key columns of related entities have to be present in the SQL query. Field definitions are optional provided that they map to the same column name as the one declared on the class property.

```
@NamedNativeQuery(name="night&area", query="select night.id nid, night.night_duration, "
    + " night.night_date, area.id aid, night.area_id, area.name "
    + "from Night night, Area area where night.area_id = area.id", resultSetMapping="joinMapping")
@SqlResultSetMapping(name="joinMapping", entities={
    @EntityResult(entityClass=org.hibernate.test.annotations.query.Night.class, fields = {
        @FieldResult(name="id", column="nid"),
        @FieldResult(name="duration", column="night_duration"),
        @FieldResult(name="date", column="night_date"),
        @FieldResult(name="area", column="area_id"),
        discriminatorColumn="disc"
    }),
    @EntityResult(entityClass=org.hibernate.test.annotations.query.Area.class, fields = {
        @FieldResult(name="id", column="aid"),
        @FieldResult(name="name", column="name")
    })
})
)
```

In the above example, the `night&area` named query use the `joinMapping` result set mapping. This mapping returns 2 entities, `Night` and `Area`, each property is declared and associated to a column name, actually the column name retrieved by the query. Let's now see an implicit declaration of the property / column.

```
@Entity
```

```

@SqlResultSetMapping(name="implicit", entities=@EntityResult(entityClass=org.hibernate.test.annotations.query.SpaceShip.class,
@NamedNativeQuery(name="implicitSample", query="select * from SpaceShip", resultSetMapping="implicit")
public class SpaceShip {
    private String name;
    private String model;
    private double speed;

    @Id
    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    @Column(name="model_txt")
    public String getModel() {
        return model;
    }

    public void setModel(String model) {
        this.model = model;
    }

    public double getSpeed() {
        return speed;
    }

    public void setSpeed(double speed) {
        this.speed = speed;
    }
}

```

In this example, we only describe the entity member of the result set mapping. The property / column mappings is done using the entity mapping values. In this case the `model` property is bound to the `model_txt` column. If the association to a related entity involve a composite primary key, a `@FieldResult` element should be used for each foreign key column. The `@FieldResult` name is composed of the property name for the relationship, followed by a dot ("."), followed by the name or the field or property of the primary key.

```

@Entity
@SqlResultSetMapping(name="compositekey",
    entities=@EntityResult(entityClass=org.hibernate.test.annotations.query.SpaceShip.class,
        fields = {
            @FieldResult(name="name", column = "name"),
            @FieldResult(name="model", column = "model"),
            @FieldResult(name="speed", column = "speed"),
            @FieldResult(name="captain.firstname", column = "firstn"),
            @FieldResult(name="captain.lastname", column = "lastn"),
            @FieldResult(name="dimensions.length", column = "length"),
            @FieldResult(name="dimensions.width", column = "width")
        },
        columns = { @ColumnResult(name = "surface"),
            @ColumnResult(name = "volume") } )
@NamedNativeQuery(name="compositekey",
    query="select name, model, speed, lname as lastn, fname as firstn, length, width, length * width as volume",
    resultSetMapping="compositekey")
} )
public class SpaceShip {
    private String name;
    private String model;
    private double speed;
    private Captain captain;
    private Dimensions dimensions;

    @Id
    public String getName() {

```



```

        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    @ManyToOne(fetch= FetchType.LAZY)
    @JoinColumn( {
        @JoinColumn(name="fname", referencedColumnName = "firstname"),
        @JoinColumn(name="lname", referencedColumnName = "lastname")
    } )
    public Captain getCaptain() {
        return captain;
    }

    public void setCaptain(Captain captain) {
        this.captain = captain;
    }

    public String getModel() {
        return model;
    }

    public void setModel(String model) {
        this.model = model;
    }

    public double getSpeed() {
        return speed;
    }

    public void setSpeed(double speed) {
        this.speed = speed;
    }

    public Dimensions getDimensions() {
        return dimensions;
    }

    public void setDimensions(Dimensions dimensions) {
        this.dimensions = dimensions;
    }
}

@Entity
@IdClass(Identity.class)
public class Captain implements Serializable {
    private String firstname;
    private String lastname;

    @Id
    public String getFirstname() {
        return firstname;
    }

    public void setFirstname(String firstname) {
        this.firstname = firstname;
    }

    @Id
    public String getLastname() {
        return lastname;
    }

    public void setLastname(String lastname) {
        this.lastname = lastname;
    }
}

```

Note

If you look at the dimension property, you'll see that Hibernate supports the dotted notation for embedded objects (you can even have nested embedded objects). EJB3 implementations do not have to support this feature, we do :-)

If you retrieve a single entity and if you use the default mapping, you can use the `resultClass` attribute instead of `resultSetMapping`:

```
@NamedNativeQuery(name="implicitSample", query="select * from SpaceShip",
    resultClass=SpaceShip.class)
public class SpaceShip {
```

In some of your native queries, you'll have to return scalar values, for example when building report queries. You can map them in the `@SqlResultSetMapping` through `@ColumnResult`. You actually can even mix, entities and scalar returns in the same native query (this is probably not that common though).

```
@SqlResultSetMapping(name="scalar", columns=@ColumnResult(name="dimension"))
@NamedNativeQuery(name="scalar", query="select length*width as dimension from SpaceShip", resultSetMapping="scalar")
```

An other query hint specific to native queries has been introduced: `org.hibernate.callable` which can be true or false depending on whether the query is a stored procedure or not.

2.4. Hibernate Annotation Extensions

Hibernate 3.1 offers a variety of additional annotations that you can mix/match with your EJB 3 entities. They have been designed as a natural extension of EJB3 annotations.

To empower the EJB3 capabilities, hibernate provides specific annotations that match hibernate features. The `org.hibernate.annotations` package contains all these annotations extensions.

2.4.1. Entity

You can fine tune some of the actions done by Hibernate on entities beyond what the EJB3 spec offers.

`@org.hibernate.annotations.Entity` adds additional metadata that may be needed beyond what is defined in the standard `@Entity`

- `mutable`: whether this entity is mutable or not
- `dynamicInsert`: allow dynamic SQL for inserts
- `dynamicUpdate`: allow dynamic SQL for updates
- `selectBeforeUpdate`: Specifies that Hibernate should never perform an SQL UPDATE unless it is certain that an object is actually modified.
- `polymorphism`: whether the entity polymorphism is of `PolymorphismType.IMPLICIT` (default) or `PolymorphismType.EXPLICIT`
- `optimisticLock`: optimistic locking strategy (`OptimisticLockType.VERSION`, `OptimisticLockType.NONE`, `OptimisticLockType.DIRTY` or `OptimisticLockType.ALL`)

Note

`@javax.persistence.Entity` is still mandatory, `@org.hibernate.annotations.Entity` is not a replacement.

Here are some additional Hibernate annotation extensions

`@org.hibernate.annotations.BatchSize` allows you to define the batch size when fetching instances of this entity (eg. `@BatchSize(size=4)`). When loading a given entity, Hibernate will then load all the uninitialized entities of the same type in the persistence context up to the batch size.

`@org.hibernate.annotations.Proxy` defines the laziness attributes of the entity. `lazy` (default to true) define whether the class is lazy or not. `proxyClassName` is the interface used to generate the proxy (default is the class itself).

`@org.hibernate.annotations.Where` defines an optional SQL WHERE clause used when instances of this class is retrieved.

`@org.hibernate.annotations.Check` defines an optional check constraints defined in the DDL statetement.

`@OnDelete(action=OnDeleteAction.CASCADE)` on joined subclasses: use a SQL cascade delete on deletion instead of the regular Hibernate mechanism.

`@Table(applyTo="tableName", indexes = { @Index(name="index1", columnNames={"column1", "column2"}) })` creates the defined indexes on the columns of table `tableName`. This can be applied on the primary table or any secondary table. The `@Tables` annotation allows your to apply indexes on different tables. This annotation is expected where `@javax.persistence.Table` OR `@javax.persistence.SecondaryTable(s)` occurs.

Note

`@org.hibernate.annotations.Table` is a complement, not a replacement to `@javax.persistence.Table`. Especially, if you want to change the default name of a table, you must use `@javax.persistence.Table`, not `@org.hibernate.annotations.Table`.

`@org.hibernate.annotations.Table` can also be used to define the following elements of secondary tables:

- `fetch`: If set to `JOIN`, the default, Hibernate will use an inner join to retrieve a secondary table defined by a class or its superclasses and an outer join for a secondary table defined by a subclass. If set to `select` then Hibernate will use a sequential select for a secondary table defined on a subclass, which will be issued only if a row turns out to represent an instance of the subclass. Inner joins will still be used to retrieve a secondary defined by the class and its superclasses.
- `inverse`: If true, Hibernate will not try to insert or update the properties defined by this join. Default to false.
- `optional`: If enabled (the default), Hibernate will insert a row only if the properties defined by this join are non-null and will always use an outer join to retrieve the properties.
- `foreignKey`: defines the Foreign Key name of a secondary table pointing back to the primary table.

`@Immutable` marks an entity as immutable. The entity may not be updated or deleted by the application. This allows Hibernate to make some minor performance optimizations.

`@Persister` lets you define your own custom persistence strategy. You may, for example, specify your own

subclass of `org.hibernate.persister.EntityPersister` or you might even provide a completely new implementation of the interface `org.hibernate.persister.ClassPersister` that implements persistence via, for example, stored procedure calls, serialization to flat files or LDAP.

```
@Entity
@BatchSize(size=5)
@org.hibernate.annotations.Entity(
    selectBeforeUpdate = true,
    dynamicInsert = true, dynamicUpdate = true,
    optimisticLock = OptimisticLockType.ALL,
    polymorphism = PolymorphismType.EXPLICIT)
@Where(clause="1=1")
@org.hibernate.annotations.Table(name="Forest", indexes = { @Index(name="idx", columnNames = { "name"
@Persister(impl=MyEntityPersister.class)
public class Forest { ... }
```

```
@Entity
@Inheritance(
    strategy=InheritanceType.JOINED
)
public class Vegetable { ... }

@Entity
@OnDelete(action=OnDeleteAction.CASCADE)
public class Carrot extends Vegetable { ... }
```

2.4. Identifier. Identifier

`@org.hibernate.annotations.GenericGenerator` allows you to define an Hibernate specific id generator.

```
@Id @GeneratedValue(generator="system-uuid")
@GenericGenerator(name="system-uuid", strategy = "uuid")
public String getId() {

@Id @GeneratedValue(generator="hibseq")
@GenericGenerator(name="hibseq", strategy = "seqhilo",
    parameters = {
        @Parameter(name="max_lo", value = "5"),
        @Parameter(name="sequence", value="heybabyhey")
    }
)
public Integer getId() {
```

`strategy` is the short name of an Hibernate3 generator strategy or the fully qualified class name of an `IdentifierGenerator` implementation. You can add some parameters through the `parameters` attribute.

Contrary to its standard counterpart, `@GenericGenerator` can be used in package level annotations, making it an application level generator (just like if it were in a JPA XML file).

```
@GenericGenerator(name="hibseq", strategy = "seqhilo",
    parameters = {
        @Parameter(name="max_lo", value = "5"),
        @Parameter(name="sequence", value="heybabyhey")
    }
)
package org.hibernate.test.model
```

2.4.3. Property

Access type

The access type is guessed from the position of `@Id` or `@EmbeddedId` in the entity hierarchy. Sub-entities, embedded objects and mapped superclass inherit the access type from the root entity.

In Hibernate, you can override the access type to:

- use a custom access type strategy
- fine tune the access type at the class level or at the property level

An `@AccessType` annotation has been introduced to support this behavior. You can define the access type on

- an entity
- a superclass
- an embeddable object
- a property

The access type is overridden for the annotated element, if overridden on a class, all the properties of the given class inherit the access type. For root entities, the access type is considered to be the default one for the whole hierarchy (overridable at class or property level).

If the access type is marked as "property", the getters are scanned for annotations, if the access type is marked as "field", the fields are scanned for annotations. Otherwise the elements marked with `@Id` or `@embeddedId` are scanned.

You can override an access type for a property, but the element to annotate will not be influenced: for example an entity having access type `field`, can annotate a field with `@AccessType("property")`, the access type will then be property for this attribute, the the annotations still have to be carried on the field.

If a superclass or an embeddable object is not annotated, the root entity access type is used (even if an access type has been define on an intermediate superclass or embeddable object). The russian doll principle does not apply.

```
@Entity
public class Person implements Serializable {
    @Id @GeneratedValue //access type field
    Integer id;

    @Embedded
    @AttributeOverrides({
        @AttributeOverride(name = "iso2", column = @Column(name = "bornIso2")),
        @AttributeOverride(name = "name", column = @Column(name = "bornCountryName"))
    })
    Country bornIn;
}

@Embeddable
@AccessType("property") //override access type for all properties in Country
public class Country implements Serializable {
    private String iso2;
    private String name;

    public String getIso2() {
        return iso2;
    }
}
```

```

    public void setIso2(String iso2) {
        this.iso2 = iso2;
    }

    @Column(name = "countryName")
    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }
}

```

Formula

Sometimes, you want the Database to do some computation for you rather than in the JVM, you might also create some kind of virtual column. You can use a SQL fragment (aka formula) instead of mapping a property into a column. This kind of property is read only (its value is calculated by your formula fragment).

```

@Formula("obj_length * obj_height * obj_width")
public long getObjectVolume()

```

The SQL fragment can be as complex as you want and even include subselects.

Type

`@org.hibernate.annotations.Type` overrides the default hibernate type used: this is generally not necessary since the type is correctly inferred by Hibernate. Please refer to the Hibernate reference guide for more information on the Hibernate types.

`@org.hibernate.annotations.TypeDef` and `@org.hibernate.annotations.TypeDefs` allows you to declare type definitions. These annotations are placed at the class or package level. Note that these definitions will be global for the session factory (even at the class level) and that type definition has to be defined before any usage.

```

@TypeDefs(
{
    @TypeDef(
        name="caster",
        typeClass = CasterStringType.class,
        parameters = {
            @Parameter(name="cast", value="lower")
        }
    )
}
)
package org.hibernate.test.annotations.entity;

...
public class Forest {
    @Type(type="caster")
    public String getSmallText() {
        ...
    }
}

```

When using composite user type, you will have to express column definitions. The `@Columns` has been introduced for that purpose.

```

@Type(type="org.hibernate.test.annotations.entity.MonetaryAmountUserType")

```

```
@Columns(columns = {
    @Column(name="r_amount"),
    @Column(name="r_currency")
})
public MonetaryAmount getAmount() {
    return amount;
}

public class MonetaryAmount implements Serializable {
    private BigDecimal amount;
    private Currency currency;
    ...
}
```

Index

You can define an index on a particular column using the `@Index` annotation on a one column property, the `columnNames` attribute will then be ignored

```
@Column(secondaryTable="Cat1")
@Index(name="story1index")
public String getStoryPart1() {
    return storyPart1;
}
```

@Parent

When inside an embeddable object, you can define one of the properties as a pointer back to the owner element.

```
@Entity
public class Person {
    @Embeddable public Address address;
    ...
}

@Embeddable
public class Address {
    @Parent public Person owner;
    ...
}

person == person.address.owner
```

Generated properties

Some properties are generated at insert or update time by your database. Hibernate can deal with such properties and triggers a subsequent select to read these properties.

```
@Entity
public class Antenna {
    @Id public Integer id;
    @Generated(GenerationTime.ALWAYS) @Column(insertable = false, updatable = false)
    public String longitude;

    @Generated(GenerationTime.INSERT) @Column(insertable = false)
    public String latitude;
}
```

Annotate your property as `@Generated` You have to make sure your insertability or updatability does not conflict with the generation strategy you have chosen. When `GenerationTime.INSERT` is chosen, the property

must not contains insertable columns, when `GenerationTime.ALWAYS` is chosen, the property must not contains insertable nor updatable columns.

`@Version` properties cannot be `@Generated(INSERT)` by design, it has to be either `NEVER` or `ALWAYS`.

@Target

Sometimes, the type guessed by reflection is not the one you want Hibernate to use. This is especially true on components when an interface is used. You can use `@Target` to by pass the reflection guessing mechanism (very much like the `targetEntity` attribute available on associations).

```
@Embedded
@Target(OwnerImpl.class)
public Owner getOwner() {
    return owner;
}
```

Optimistic lock

It is sometimes useful to avoid increasing the version number even if a given property is dirty (particularly collections). You can do that by annotating the property (or collection) with `@OptimisticLock(excluded=true)`.

More formally, specifies that updates to this property do not require acquisition of the optimistic lock.

2.4.4. Inheritance

`SINGLE_TABLE` is a very powerful strategy but sometimes, and especially for legacy systems, you cannot add an additional discriminator column. For that purpose Hibernate has introduced the notion of discriminator formula: `@DiscriminatorFormula` is a replacement of `@DiscriminatorColumn` and use a SQL fragment as a formula for discriminator resolution (no need to have a dedicated column).

```
@Entity
@DiscriminatorFormula("case when forest_type is null then 0 else forest_type end")
public class Forest { ... }
```

By default, when querying the top entities, Hibernate does not put a restriction clause on the discriminator column. This can be inconvenient if this column contains values not mapped in your hierarchy (through `@DiscriminatorValue`). To work around that you can use `@ForceDiscriminator` (at the class level, next to `@DiscriminatorColumn`). Hibernate will then list the available values when loading the entities.

You can define the foreign key name generated by Hibernate for subclass tables in the `JOINED` inheritance strategy.

```
@Entity
@Inheritance(strategy = InheritanceType.JOINED)
public abstract class File { ... }

@Entity
@ForeignKey(name = "FK_DOCU_FILE")
public class Document extends File {
```

The foreign key from the `Document` table to the `File` table will be named `FK_DOCU_FILE`.

2.4.5. Single Association related annotations

By default, when Hibernate cannot resolve the association because the expected associated element is not in database (wrong id on the association column), an exception is raised by Hibernate. This might be inconvenient for legacy and badly maintained schemas. You can ask Hibernate to ignore such elements instead of raising an exception using the `@NotFound` annotation. This annotation can be used on a `@OneToOne` (with FK), `@ManyToOne`, `@OneToMany` or `@ManyToMany` association.

```
@Entity
public class Child {
    ...
    @ManyToOne
    @NotFound(action=NotFoundAction.IGNORE)
    public Parent getParent() { ... }
    ...
}
```

Sometimes you want to delegate to your database the deletion of cascade when a given entity is deleted.

```
@Entity
public class Child {
    ...
    @ManyToOne
    @OnDelete(action=onDeleteAction.CASCADE)
    public Parent getParent() { ... }
    ...
}
```

In this case Hibernate generates a cascade delete constraint at the database level.

Foreign key constraints, while generated by Hibernate, have a fairly unreadable name. You can override the constraint name by use `@ForeignKey`.

```
@Entity
public class Child {
    ...
    @ManyToOne
    @ForeignKey(name="FK_PARENT")
    public Parent getParent() { ... }
    ...
}

alter table Child add constraint FK_PARENT foreign key (parent_id) references Parent
```

Lazy options and fetching modes

EJB3 comes with the `fetch` option to define lazy loading and fetching modes, however Hibernate has a much more option set in this area. To fine tune the lazy loading and fetching strategies, some additional annotations have been introduced:

- `@LazyToOne`: defines the laziness option on `@ManyToOne` and `@OneToOne` associations. `LazyToOneOption` can be `PROXY` (ie use a proxy based lazy loading), `NO_PROXY` (use a bytecode enhancement based lazy loading - note that build time bytecode processing is necessary) and `FALSE` (association not lazy)
- `@LazyCollection`: defines the laziness option on `@ManyToMany` and `@OneToMany` associations. `LazyCollectionOption` can be `TRUE` (the collection is lazy and will be loaded when its state is accessed), `EXTRA` (the collection is lazy and all operations will try to avoid the collection loading, this is especially useful for huge collections when loading all the elements is not necessary) and `FALSE` (association not lazy)
- `@Fetch`: defines the fetching strategy used to load the association. `FetchMode` can be `SELECT` (a select is triggered when the association needs to be loaded), `SUBSELECT` (only available for collections, use a subse-

lect strategy - please refers to the Hibernate Reference Documentation for more information) or `JOIN` (use a SQL JOIN to load the association while loading the owner entity). `JOIN` overrides any lazy attribute (an association loaded through a `JOIN` strategy cannot be lazy).

The Hibernate annotations overrides the EJB3 fetching options.

Table 2.3. Lazy and fetch options equivalent

Annotations	Lazy	Fetch
<code>@[One Many]ToOne(fetch=FetchType.LAZY)</code>	<code>@LazyToOne(PROXY)</code>	<code>@Fetch(SELECT)</code>
<code>@[One Many]ToOne(fetch=FetchType.EAGER)</code>	<code>@LazyToOne(FALSE)</code>	<code>@Fetch(JOIN)</code>
<code>@ManyToOne(fetch=FetchType.LAZY)</code>	<code>@LazyCollection(TRUE)</code>	<code>@Fetch(SELECT)</code>
<code>@ManyToOne(fetch=FetchType.EAGER)</code>	<code>@LazyCollection(FALSE)</code>	<code>@Fetch(JOIN)</code>

2.4.6. Collection related annotations

Enhance collection settings

It is possible to set

- the batch size for collections using `@BatchSize`
- the where clause, using `@Where` (applied on the target entity) or `@WhereJoinTable` (applied on the association table)
- the check clause, using `@Check`
- the SQL order by clause, using `@OrderBy`
- the delete cascade strategy through `@OnDelete(action=OnDeleteAction.CASCADE)`
- the collection immutability using `@Immutable`: if set specifies that the elements of the collection never change (a minor performance optimization in some cases)
- a custom collection persister (ie the persistence strategy used) using `@Persister`: the class must implement `org.hibernate.persister.collection.CollectionPersister`

You can also declare a sort comparator. Use the `@Sort` annotation. Expressing the comparator type you want between unsorted, natural or custom comparator. If you want to use your own comparator implementation, you'll also have to express the implementation class using the `comparator` attribute. Note that you need to use either a `SortedSet` or a `SortedMap` interface.

```
@OneToMany(cascade=CascadeType.ALL, fetch=FetchType.EAGER)
@JoinColumn(name="CUST_ID")
@Sort(type = SortType.COMPARATOR, comparator = TicketComparator.class)
@Where(clause="1=1")
```

```
@OnDelete(action=OnDeleteAction.CASCADE)
public SortedSet<Ticket> getTickets() {
    return tickets;
}
```

Please refer to the previous descriptions of these annotations for more informations.

Foreign key constraints, while generated by Hibernate, have a fairly unreadable name. You can override the constraint name by use `@ForeignKey`. Note that this annotation has to be placed on the owning side of the relationship, `inverseName` referencing to the other side constraint.

```
@Entity
public class Woman {
    ...
    @ManyToMany(cascade = {CascadeType.ALL})
    @ForeignKey(name = "TO_WOMAN_FK", inverseName = "TO_MAN_FK")
    public Set<Man> getMens() {
        return mens;
    }
}

alter table Man_Woman add constraint TO_WOMAN_FK foreign key (woman_id) references Woman
alter table Man_Woman add constraint TO_MAN_FK foreign key (man_id) references Man
```

Extra collection types

List

Beyond EJB3, Hibernate Annotations supports true `List` and `Array`. Map your collection the same way as usual and add the `@IndexColumn`. This annotation allows you to describe the column that will hold the index. You can also declare the index value in DB that represent the first element (aka as base index). The usual value is 0 or 1.

```
@OneToMany(cascade = CascadeType.ALL)
@IndexColumn(name = "drawer_position", base=1)
public List<Drawer> getDrawers() {
    return drawers;
}
```

Note

If you forgot to set `@IndexColumn`, the bag semantic is applied. If you want the bag semantic without the limitations of it, consider using `@CollectionId`.

Map

Hibernate Annotations also supports true Map mappings, if `@javax.persistence.MapKey` is not set, hibernate will map the key element or embeddable object in its/their own columns. To overrides the default columns, you can use `@org.hibernate.annotations.MapKey` if your key is a basic type (defaulted to `mapkey`) or an embeddable object, or you can use `@org.hibernate.annotations.MapKeyManyToMany` if your key is an entity.

Both `@org.hibernate.annotations.MapKey` and `@org.hibernate.annotations.MapKeyManyToMany` allows you to override the target element to be used. This is especially useful if your collection does not use generics (or if you use interfaces).

```
@CollectionOfElements(targetElement = SizeImpl.class)
@MapKeyManyToMany(targetEntity = LuggageImpl.class)
private Map<Luggage, Size> sizePerLuggage = new HashMap<Luggage, Size>();
```

Bidirectional association with indexed collections

A bidirectional association where one end is represented as a `@IndexColumn` or `@org.hibernate.annotations.MapKey[ManyToMany]` requires special consideration. If there is a property of the child class which maps to the index column, no problem, we can continue using `mappedBy` on the collection mapping:

```
@Entity
public class Parent {
    @OneToMany(mappedBy="parent")
    @org.hibernate.annotations.MapKey(columns=@Column(name="name"))
    private Map<String, Child> children;
    ...
}

@Entity
public class Parent {
    ...
    @Basic
    private String name;

    @ManyToOne
    @JoinColumn(name="parent_id", nullable=false)
    private Parent parent;
    ...
}
```

But, if there is no such property on the child class, we can't think of the association as truly bidirectional (there is information available at one end of the association that is not available at the other end). In this case, we can't map the collection `mappedBy`. Instead, we could use the following mapping:

```
@Entity
public class Parent {
    @OneToMany
    @org.hibernate.annotations.MapKey(columns=@Column(name="name"))
    @JoinColumn(name="parent_id", nullable=false)
    private Map<String, Child> children;
    ...
}

@Entity
public class Parent {
    ...
    @ManyToOne
    @JoinColumn(name="parent_id", insertable=false, updatable=false, nullable=false)
    private Parent parent;
    ...
}
```

Note that in this mapping, the collection-valued end of the association is responsible for updates to the foreign key.

Bag with primary key

Another interesting feature is the ability to define a surrogate primary key to a bag collection. This remove pretty much all of the drawbacks of bags: update and removal are efficient, more than one `EAGER` bag per query or per entity. This primary key will be contained in a additional column of your collection table but will not be visible to the Java application. `@CollectionId` is used to mark a collection as id bag, it also allow to override the primary key column(s), the primary key type and the generator strategy. The strategy can be `identity`, or any defined generator name of your application.

```
@Entity
```

```

@TableGenerator(name="ids_generator", table="IDS")
public class Passport {
    ...

    @ManyToMany(cascade = CascadeType.ALL)
    @JoinTable(name="PASSPORT_VISASTAMP")
    @CollectionId(
        columns = @Column(name="COLLECTION_ID"),
        type=@Type(type="long"),
        generator = "ids_generator"
    )
    private Collection<Stamp> visaStamp = new ArrayList();
    ...
}

```

Collection of element or composite elements

Hibernate Annotations also supports collections of core types (Integer, String, Enums, ...), collections of embeddable objects and even arrays of primitive types. This is known as collection of elements.

A collection of elements has to be annotated as `@CollectionOfElements` (as a replacement of `@OneToMany`). To define the collection table, the `@JoinTable` annotation is used on the association property, `joinColumns` defines the join columns between the entity primary table and the collection table (inverseJoincolumn is useless and should be left empty). For collection of core types or array of primitive types, you can override the element column definition using a `@Column` on the association property. You can also override the columns of a collection of embeddable object using `@AttributeOverride`. To reach the collection element, you need to append "element" to the attribute override name (eg "element" for core types, or "element.serial" for the serial property of an embeddable element). To reach the index/key of a collection, append "key" instead.

```

@Entity
public class Boy {
    private Integer id;
    private Set<String> nickNames = new HashSet<String>();
    private int[] favoriteNumbers;
    private Set<Toy> favoriteToys = new HashSet<Toy>();
    private Set<Character> characters = new HashSet<Character>();

    @Id @GeneratedValue
    public Integer getId() {
        return id;
    }

    @CollectionOfElements
    public Set<String> getNickNames() {
        return nickNames;
    }

    @CollectionOfElements
    @JoinTable(
        table=@Table(name="BoyFavoriteNumbers"),
        joinColumns = @JoinColumn(name="BoyId")
    )
    @Column(name="favoriteNumber", nullable=false)
    @IndexColumn(name="nbr_index")
    public int[] getFavoriteNumbers() {
        return favoriteNumbers;
    }

    @CollectionOfElements
    @AttributeOverride( name="element.serial", column=@Column(name="serial_nbr") )
    public Set<Toy> getFavoriteToys() {
        return favoriteToys;
    }

    @CollectionOfElements
    public Set<Character> getCharacters() {

```

```

        return characters;
    }
    ...
}

public enum Character {
    GENTLE,
    NORMAL,
    AGGRESSIVE,
    ATTENTIVE,
    VIOLENT,
    CRAFTY
}

@Embeddable
public class Toy {
    public String name;
    public String serial;
    public Boy owner;

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public String getSerial() {
        return serial;
    }

    public void setSerial(String serial) {
        this.serial = serial;
    }

    @Parent
    public Boy getOwner() {
        return owner;
    }

    public void setOwner(Boy owner) {
        this.owner = owner;
    }

    public boolean equals(Object o) {
        if ( this == o ) return true;
        if ( o == null || getClass() != o.getClass() ) return false;

        final Toy toy = (Toy) o;

        if ( !name.equals( toy.name ) ) return false;
        if ( !serial.equals( toy.serial ) ) return false;

        return true;
    }

    public int hashCode() {
        int result;
        result = name.hashCode();
        result = 29 * result + serial.hashCode();
        return result;
    }
}

```

On a collection of embeddable objects, the embeddable object can have a property annotated with `@Parent`. This property will then point back to the entity containing the collection.

Note

Previous versions of Hibernate Annotations used the `@OneToMany` to mark a collection of elements. Due to semantic inconsistencies, we've introduced the annotation `@CollectionOfElements`. Marking collections of elements the old way still work but is considered deprecated and is going to be unsupported in future releases

2.4.7. Cascade

Hibernate offers more operations than the Java Persistence specification. You can use the `@Cascade` annotation to cascade the following operations:

- `PERSIST`
- `MERGE`
- `REMOVE`
- `REFRESH`
- `DELETE`
- `SAVE_UPDATE`
- `REPLICATE`
- `DELETE_ORPHAN`
- `LOCK`
- `EVICT`

This is especially useful for `SAVE_UPDATE` (which is the operation cascaded at flush time if you use plain Hibernate Annotations - Hibernate EntityManager cascade `PERSIST` at flush time as per the specification). `DELETE_ORPHAN` applies only to `@OneToMany` associations, and indicates that the `delete()/remove()` operation should be applied to any child object that is removed from the association. In other words, if a child is dereferenced by a persistent parent and if `DELETE_ORPHAN` is used, the "orphaned" child is deleted.

```
@OneToMany( cascade = {CascadeType.PERSIST, CascadeType.MERGE} )
@Cascade( {org.hibernate.annotations.CascadeType.SAVE_UPDATE,
           org.hibernate.annotations.CascadeType.DELETE_ORPHAN} )
public Collection<Employer> getEmployers()
```

It is recommended to use `@Cascade` to compliment `@*To*(cascade=...)` as shown in the previous example.

2.4.8. Cache

In order to optimize your database accesses, you can activate the so called second level cache of Hibernate. This cache is configurable on a per entity and per collection basis.

`@org.hibernate.annotations.Cache` defines the caching strategy and region of a given second level cache. This annotation can be applied on the root entity (not the sub entities), and on the collections.

```
@Entity
@Cache(usage = CacheConcurrencyStrategy.NONSTRICT_READ_WRITE)
public class Forest { ... }
```

```

@OneToMany(cascade=CascadeType.ALL, fetch=FetchType.EAGER)
@JoinColumn(name="CUST_ID")
@Cache(usage = CacheConcurrencyStrategy.NONSTRICT_READ_WRITE)
public SortedSet<Ticket> getTickets() {
    return tickets;
}

```

```

@Cache(
    CacheConcurrencyStrategy usage();           (1)
    String region() default "";                 (2)
    String include() default "all";             (3)
)

```

- (1) usage: the given cache concurrency strategy (NONE, READ_ONLY, NONSTRICT_READ_WRITE, READ_WRITE, TRANSACTIONAL)
- (2) region (optional): the cache region (default to the fqcn of the class or the fq role name of the collection)
- (3) include (optional): all to include all properties, non-lazy to only include non lazy properties (default all).

2.4.9. Filters

Hibernate has the ability to apply arbitrary filters on top of your data. Those filters are applied at runtime on a given session. First, you need to define them.

`@org.hibernate.annotations.FilterDef` or `@FilterDefs` define filter definition(s) used by filter(s) using the same name. A filter definition has a `name()` and an array of `parameters()`. A parameter will allow you to adjust the behavior of the filter at runtime. Each parameter is defined by a `@ParamDef` which has a name and a type. You can also define a `defaultCondition()` parameter for a given `@FilterDef` to set the default condition to use when none are defined in each individual `@Filter`. A `@FilterDef(s)` can be defined at the class or package level.

We now need to define the SQL filter clause applied to either the entity load or the collection load. `@Filter` is used and placed either on the entity or the collection element

```

@Entity
@FilterDef(name="minLength", parameters={ @ParamDef( name="minLength", type="integer" ) } )
@Filters( {
    @Filter(name="betweenLength", condition=":minLength <= length and :maxLength >= length"),
    @Filter(name="minLength", condition=":minLength <= length")
} )
public class Forest { ... }

```

When the collection use an association table as a relational representation, you might want to apply the filter condition to the association table itself or to the target entity table. To apply the constraint on the target entity, use the regular `@Filter` annotation. However, if you want to target the association table, use the `@FilterJoinTable` annotation.

```

@OneToMany
@JoinTable
//filter on the target entity table
@Filter(name="betweenLength", condition=":minLength <= length and :maxLength >= length")
//filter on the association table
@FilterJoinTable(name="security", condition=":userlevel >= requiredLevel")
public Set<Forest> getForests() { ... }

```

2.4.10. Queries

Since Hibernate has more features on named queries than the one defined in the EJB3 specification, `@org.hibernate.annotations.NamedQuery`, `@org.hibernate.annotations.NamedQueries`, `@org.hibernate.annotations.NamedNativeQuery` and `@org.hibernate.annotations.NamedNativeQueries` have been introduced. They add some attributes to the standard version and can be used as a replacement:

- `flushMode`: define the query flush mode (Always, Auto, Commit or Never)
- `cacheable`: whether the query should be cached or not
- `cacheRegion`: cache region used if the query is cached
- `fetchSize`: JDBC statement fetch size for this query
- `timeout`: query time out
- `callable`: for native queries only, to be set to true for stored procedures
- `comment`: if comments are activated, the comment seen when the query is sent to the database.
- `cacheMode`: Cache interaction mode (get, ignore, normal, put or refresh)
- `readOnly`: whether or not the elements retrieval from the query are in read only mode.

Those hints can be set in a standard `@javax.persistence.NamedQuery` annotations through the `detyped @QueryHint`. Another key advantage is the ability to set those annotations at a package level.

2.4.11. Custom SQL for CRUD operations

Hibernate gives you the ability to override every single SQL statement generated. We have seen native SQL query usage already, but you can also override the SQL statement used to load or change the state of entities.

```
@Entity
@Table(name="CHAOS")
@SQLInsert( sql="INSERT INTO CHAOS(size, name, nickname, id) VALUES(?,upper(??),?,?)" )
@SQLUpdate( sql="UPDATE CHAOS SET size = ?, name = upper(??), nickname = ? WHERE id = ?" )
@SQLDelete( sql="DELETE CHAOS WHERE id = ?" )
@SQLDeleteAll( sql="DELETE CHAOS" )
@Loader( namedQuery = "chaos" )
@NamedNativeQuery(name="chaos", query="select id, size, name, lower( nickname ) as nickname from CHAOS")
public class Chaos {
    @Id
    private Long id;
    private Long size;
    private String name;
    private String nickname;
```

`@SQLInsert`, `@SQLUpdate`, `@SQLDelete`, `@SQLDeleteAll` respectively override the INSERT statement, UPDATE statement, DELETE statement, DELETE statement to remove all entities.

If you expect to call a store procedure, be sure to set the `callable` attribute to true (`@SQLInsert(callable=true, ...)`).

To check that the execution happens correctly, Hibernate allows you to define one of those three strategies:

- `NONE`: no check is performed: the store procedure is expected to fail upon issues
- `COUNT`: use of rowcount to check that the update is successful

- **PARAM:** like COUNT but using an output parameter rather than the standard mechanism

To define the result check style, use the `check` parameter (`@SQLUpdate(check=ResultCheckStyle.COUNT, ...)`).

You can also override the SQL load statement by a native SQL query or a HQL query. You just have to refer to a named query with the `@Loader` annotation.

You can use the exact same set of annotations to override the collection related statements.

```
@OneToMany
@JoinColumn(name="chaos_fk")
@SQLInsert( sql="UPDATE CASIMIR_PARTICULE SET chaos_fk = ? where id = ?")
@SQLDelete( sql="UPDATE CASIMIR_PARTICULE SET chaos_fk = null where id = ?")
private Set<CasimirParticle> particles = new HashSet<CasimirParticle>();
```

The parameters order is important and is defined by the order Hibernate handle properties. You can see the expected order by enabling debug logging for the `org.hibernate.persister.entity` level. With this level enabled Hibernate will print out the static SQL that is used to create, update, delete etc. entities. (To see the expected sequence, remember to not include your custom SQL through annotations as that will override the Hibernate generated static sql.)

Overriding SQL statements for secondary tables is also possible using `@org.hibernate.annotations.Table` and either (or all) attributes `sqlInsert`, `sqlUpdate`, `sqlDelete`:

```
@Entity
@SecondaryTables({
    @SecondaryTable(name = "`Cat nbr1`"),
    @SecondaryTable(name = "Cat2")})
@org.hibernate.annotations.Tables({
    @Table(applyTo = "Cat", comment = "My cat table" ),
    @Table(applyTo = "Cat2", foreignKey = @ForeignKey(name="FK_CAT2_CAT"), fetch = FetchType.SELECT,
        sqlInsert=@SQLInsert(sql="insert into Cat2(storyPart2, id) values(upper(?), ?)" )
    } )
public class Cat implements Serializable {
```

The previous example also show that you can give a comment to a given table (primary or secondary): This comment will be used for DDL generation.

2.4.12. Tuplizer

`org.hibernate.tuple.Tuplizer`, and its sub-interfaces, are responsible for managing a particular representation of a piece of data, given that representation's `org.hibernate.EntityMode`. If a given piece of data is thought of as a data structure, then a tuplizer is the thing which knows how to create such a data structure and how to extract values from and inject values into such a data structure. For example, for the POJO entity mode, the corresponding tuplizer knows how create the POJO through its constructor and how to access the POJO properties using the defined property accessors. There are two high-level types of Tuplizers, represented by the `org.hibernate.tuple.EntityTuplizer` and `org.hibernate.tuple.ComponentTuplizer` interfaces. `EntityTuplizers` are responsible for managing the above mentioned contracts in regards to entities, while `ComponentTuplizers` do the same for components. Check the Hibernate reference documentation for more information.

To define tuplizer in annotations, simply use the `@Tuplizer` annotation on the according element

```
@Entity
@Tuplizer(impl = DynamicEntityTuplizer.class)
public interface Cuisine {
```

```
@Id
@GeneratedValue
public Long getId();
public void setId(Long id);

public String getName();
public void setName(String name);

@Tuplizer(impl = DynamicComponentTuplizer.class)
public Country getCountry();
public void setCountry(Country country);

}
```

Chapter Overriding metadata through XML. Overriding metadata through XML

The primary target for metadata in EJB3 is annotations, but the EJB3 specification provides a way to override or replace the annotation defined metadata through an XML deployment descriptor. In the current release only pure EJB3 annotations overriding are supported. If you wish to use Hibernate specific features in some entities, you'll have to either use annotations or fallback to hbm files. You can of course mix and match annotated entities and entities describes in hbm files.

The unit test suite shows some additional XML file samples.

Overriding metadata through XML.1. Principles

The XML deployment descriptor structure has been designed to reflect the annotations one. So if you know the annotations structure, using the XML schema will be straightforward for you.

You can define one or more XML files describing your metadata, these files will be merged by the overriding engine.

Overriding metadata through XML.1.1. Global level metadata

You can define global level metadata available for all XML files. You must not define these metadata more than once per deployment.

```
<?xml version="1.0" encoding="UTF-8"?>

<entity-mappings
  xmlns="http://java.sun.com/xml/ns/persistence/orm"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/persistence/orm orm_1_0.xsd"
  version="1.0">

  <persistence-unit-metadata>
    <xml-mapping-metadata-complete/>
    <persistence-unit-defaults>
      <schema>myschema</schema>
      <catalog>mycatalog</catalog>
      <cascade-persist/>
    </persistence-unit-defaults>
  </persistence-unit-metadata>
```

`xml-mapping-metadata-complete` means that all entity, mapped-superclasses and embeddable metadata should be picked up from XML (ie ignore annotations).

`schema / catalog` will override all default definitions of schema and catalog in the metadata (both XML and annotations).

`cascade-persist` means that all associations have PERSIST as a cascade type. We recommend you to not use this feature.

Overriding metadata through XML.1.2. Entity level metadata

You can either define or override metadata informations on a given entity.

```

<?xml version="1.0" encoding="UTF-8"?>

<entity-mappings (1)
  xmlns="http://java.sun.com/xml/ns/persistence/orm"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/persistence/orm orm_1_0.xsd"
  version="1.0">

  <package>org.hibernate.test.annotations.reflection</package> (2)
  <entity class="Administration" access="PROPERTY" metadata-complete="true"> (3)
    <table name="tbl_admin"> (4)
      <unique-constraint>
        <column-name>firstname</column-name>
        <column-name>lastname</column-name>
      </unique-constraint>
    </table>
    <secondary-table name="admin2"> (5)
      <primary-key-join-column name="admin_id" referenced-column-name="id"/>
      <unique-constraint>
        <column-name>address</column-name>
      </unique-constraint>
    </secondary-table>
    <id-class class="SocialSecurityNumber"/> (6)
    <inheritance strategy="JOINED"/> (7)
    <sequence-generator name="seghilo" sequence-name="seghilo"/> (8)
    <table-generator name="table" table="tablehilo"/> (9)
    ...
  </entity>

  <entity class="PostalAdministration">
    <primary-key-join-column name="id"/> (10)
    ...
  </entity>
</entity-mappings>

```

- (1) `entity-mappings`: `entity-mappings` is the root element for all XML files. You must declare the xml schema, the schema file is included in the hibernate-annotations.jar file, no internet access will be processed by Hibernate Annotations.
- (2) `package` (optional): default package used for all non qualified class names in the given deployment descriptor file.
- (3) `entity`: describes an entity.

`metadata-complete` defines whether the metadata description for this element is complete or not (in other words, if annotations present at the class level should be considered or not).

An entity has to have a `class` attribute referring the java class the metadata applies on.

You can overrides entity name through the `name` attribute, if none is defined and if an `@Entity.name` is present, then it is used (provided that metadata complete is not set).

For metadata complete (see below) element, you can define an `access` (either `FIELD` or `PROPERTY` (default)). For non metadata complete element, if `access` is not defined, the `@Id` position will lead position, if `access` is defined, the value is used.

- (4) `table`: you can declare table properties (name, schema, catalog), if none is defined, the java annotation is used.

You can define one or several unique constraints as seen in the example

- (5) `secondary-table`: defines a secondary table very much like a regular table except that you can define the primary key / foreign key column(s) through the `primary-key-join-column` element. On non metadata complete, annotation secondary tables are used only if there is no `secondary-table` definition, annotations are ignored otherwise.
- (6) `id-class`: defines the id class in a similar way `@IdClass` does

- (7) `inheritance`: defines the inheritance strategy (`JOINED`, `TABLE_PER_CLASS`, `SINGLE_TABLE`), Available only at the root entity level
- (8) `sequence-generator`: defines a sequence generator
- (9) `table-generator`: defines a table generator
- (10) `primary-key-join-column`: defines the primary key join column for sub entities when `JOINED` inheritance strategy is used

```
<?xml version="1.0" encoding="UTF-8"?>

<entity-mappings
  xmlns="http://java.sun.com/xml/ns/persistence/orm"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/persistence/orm orm_1_0.xsd"
  version="1.0">

  <package>org.hibernate.test.annotations.reflection</package>
  <entity class="Music" access="PROPERTY" metadata-complete="true">
    <discriminator-value>Generic</discriminator-value>
    <discriminator-column length="34"/>
    ...
  </entity>

  <entity class="PostalAdministration">
    <primary-key-join-column name="id"/>
    <named-query name="adminById">
      <query>select m from Administration m where m.id = :id</query>
      <hint name="org.hibernate.timeout" value="200"/>
    </named-query>
    <named-native-query name="allAdmin" result-set-mapping="adminsrs">
      <query>select *, count(taxpayer_id) as taxPayerNumber
        from Administration, TaxPayer
        where taxpayer_admin_id = admin_id group by ...</query>
      <hint name="org.hibernate.timeout" value="200"/>
    </named-native-query>
    <sql-result-set-mapping name="adminsrs">
      <entity-result entity-class="Administration">
        <field-result name="name" column="fld_name"/>
      </entity-result>
      <column-result name="taxPayerNumber"/>
    </sql-result-set-mapping>
    <attribute-override name="ground">
      <column name="fld_ground" unique="true" scale="2"/>
    </attribute-override>
    <association-override name="referer">
      <join-column name="referer_id" referenced-column-name="id"/>
    </association-override>
    ...
  </entity>
</entity-mappings>
```

- (1) `discriminator-value` / `discriminator-column`: defines the discriminator value and the column holding it when the `SINGLE_TABLE` inheritance strategy is chosen
- (2) `named-query`: defines named queries and possibly the hints associated to them. Those definitions are additive to the one defined in annotations, if two definitions have the same name, the XML one has priority.
- (3) `named-native-query`: defines an named native query and its sql result set mapping. Alternatively, you can define the `result-class`. Those definitions are additive to the one defined in annotations, if two definitions have the same name, the XML one has priority.
- (4) `sql-result-set-mapping`: describes the result set mapping structure. You can define both entity and column mappings. Those definitions are additive to the one defined in annotations, if two definitions have the same name, the XML one has priority
- (5) `attribute-override` / `association-override`: defines a column or join column overriding. This overriding is additive to the one defined in annotations

Same applies for `<embeddable>` and `<mapped-superclass>`.

Overriding metadata through XML.1.3. Property level metadata

You can of course defines XML overriding for properties. If metadata complete is defined, then additional properties (ie at the Java level) will be ignored. Otherwise, once you start overriding a property, all annotations on the given property are ignored. All property level metadata behave in `entity/attributes`, `mapped-superclass/attributes` OR `embeddable/attributes`.

```
<attributes>
  <id name="id">
    <column name="fld_id"/>
    <generated-value generator="generator" strategy="SEQUENCE"/>
    <temporal>DATE</temporal>
    <sequence-generator name="generator" sequence-name="seq"/>
  </id>
  <version name="version"/>
  <embedded name="embeddedObject">
    <attribute-override name="subproperty">
      <column name="my_column"/>
    </attribute-override>
  </embedded>
  <basic name="status" optional="false">
    <enumerated>STRING</enumerated>
  </basic>
  <basic name="serial" optional="true">
    <column name="serialbytes"/>
    <lob/>
  </basic>
  <basic name="terminusTime" fetch="LAZY">
    <temporal>TIMESTAMP</temporal>
  </basic>
</attributes>
```

You can override a property through `id`, `embedded-id`, `version`, `embedded` and `basic`. Each of these elements can have subelements accordingly: `lob`, `temporal`, `enumerated`, `column`.

Overriding metadata through XML.1.4. Association level metadata

You can define XML overriding for associations. All association level metadata behave in `entity/attributes`, `mapped-superclass/attributes` OR `embeddable/attributes`.

```
<attributes>
  <one-to-many name="players" fetch="EAGER">
    <map-key name="name"/>
    <join-column name="driver"/>
    <join-column name="number"/>
  </one-to-many>
  <many-to-many name="roads" target-entity="Administration">
    <order-by>maxSpeed</order-by>
    <join-table name="bus_road">
      <join-column name="driver"/>
      <join-column name="number"/>
      <inverse-join-column name="road_id"/>
      <unique-constraint>
        <column-name>driver</column-name>
        <column-name>number</column-name>
      </unique-constraint>
    </join-table>
  </many-to-many>
  <many-to-many name="allTimeDrivers" mapped-by="drivenBuses">
  </attributes>
```

You can override an association through `one-to-many`, `one-to-one`, `many-to-one`, and `many-to-many`. Each of these elements can have subelements accordingly: `join-table` (which can have `join-columns` and `inverse-`

`join-columns`), `join-columns`, `map-key`, and `order-by`. `mapped-by` and `target-entity` can be defined as attributes when it makes sense. Once again the structure reflects the annotations structure. You can find all semantic informations in the chapter describing annotations.

Chapter 4. Additional modules

Hibernate Annotations mainly focus on persistence metadata. The project also have a nice integration with two Hibernate modules.

4.1. Hibernate Validator

4.1.1. Description

Annotations are a very convenient and elegant way to specify invariant constraints for a domain model. You can, for example, express that a property should never be null, that the account balance should be strictly positive, etc. These domain model constraints are declared in the bean itself by annotating its properties. A validator can then read them and check for constraint violations. The validation mechanism can be executed in different layers in your application without having to duplicate any of these rules (presentation layer, data access layer). Following the DRY principle, Hibernate Validator has been designed for that purpose.

Hibernate Validator works at two levels. First, it is able to check in-memory instances of a class for constraint violations. Second, it can apply the constraints to the Hibernate metamodel and incorporate them into the generated database schema.

Each constraint annotation is associated to a validator implementation responsible for checking the constraint on the entity instance. A validator can also (optionally) apply the constraint to the Hibernate metamodel, allowing Hibernate to generate DDL that expresses the constraint. With the appropriate event listener, you can execute the checking operation on inserts and updates done by Hibernate. Hibernate Validator is not limited to use with Hibernate. You can easily use it anywhere in your application.

When checking instances at runtime, Hibernate Validator returns information about constraint violations in an array of `InvalidValue s`. Among other information, the `InvalidValue` contains an error description message that can embed the parameter values bundle with the annotation (eg. length limit), and message strings that may be externalized to a `ResourceBundle`.

4.1.2. Integration with Hibernate Annotations

If Hibernate Validator (`hibernate-validator.jar`) is available in the classpath, Hibernate Annotations will integrates in two ways:

- Constraints will be applied to the Data Definition Language. In other words, the database schema will reflect the constraints (provided that you use the `hbm2ddl` tool).
- Before an entity change is applied to the database (insert or update), the entity is validated. Validation errors, if any, will be carried over through an `InvalidStateException`.

For entities free of validation rules, the runtime performance cost is null.

To disable constraint propagation to DDL, set up `hibernate.validator.apply_to_ddl` to false in the configuration file. Such a need is very uncommon and not recommended.

To disable pre-entity change validation, set up `hibernate.validator.autoregister_listeners` to false in the configuration file. Such a need is very uncommon and not recommended.

Check the Hibernate Validator reference documentation for more information.

4.2. Hibernate Search

4.2.1. Description

Full text search engines like Apache Lucene™ are a very powerful technology to bring free text/efficient queries to applications. It suffers several mismatches when dealing with a object domain model (keeping the index up to date, mismatch between the index structure and the domain model, querying mismatch...) Hibernate Search indexes your domain model thanks to a few annotations, takes care of the database / index synchronization and brings you back regular managed objects from free text queries. Hibernate Search is using Apache Lucene [<http://lucene.apache.org>] under the cover.

4.2.2. Integration with Hibernate Annotations

Hibernate Search integrates with Hibernate Annotations transparently provided that `hibernate-search.jar` is present in the classpath. If you do not wish to autoregister Hibernate Search event listeners, you can set `hibernate.search.autoregister_listeners` to `false`. Such a need is very uncommon and not recommended.

Check the Hibernate Search reference documentation for more information.