Pass2Certify.com
Prepare, Practice, & Pass.

Oracle

1Z0-580

ExamName: Oracle Solaris 11 Installation and Configuration Essentials

Exam Version: 6.0

Questions & Answers Sample PDF

(Preview content before you buy)

Check the full version using the link below.

https://pass2certify.com/exam/1z0-580

Unlock Full Features:

Stay Updated: 90 days of free exam updates
Zero Risk: 30-day money-back policy
Instant Access: Download right after purchase
Always Here: 24/7 customer support team

Question 1. (Multi Select)

What two entries could complete the following command from the directory listing below?

```
{1c} ok setenv network-boot-arguments="DHCP,tftpserver=10.79.200.222,host-
ip=10.79.200.224,file= _______"

root@eis44-6:~# ls -l
drwxr-xr-x    3  root   root              3   Jul 15  11:23   boot
-rwxr-xr-x    1  root   root   221528   Aug 15 13:16   inetboot.SUN4U.Solaris_10-1
-rwxr-xr-x    1  root   root   220784   Jul 8 2011        inetboot.SUN4V.Solaris_10-1
drwxr-xr-x    4  root   root              5   Nov 7   12:42   media
lrwxrwxrwx    1  root   root             26   Jul 15  11:23   nbp. ->
pxegrub.I86PC.Solaris_10-1
drwxrw-rw-    2  root   root              2   Jul 8 2011        netboot
-rwxr-xr-x     1  root   root   140144   Jun 30 2011      pxegrub.I86PC.Solaris_10-1
-rwxr-xr-x     1  root   root   137072   Nov 6 13:15      s11grub.i86pc
```

A: inetboot.SUN4U.Solaris_10-1

B: inetboot.SUN4V.Solaris_l0-1

C: sllgrub.i86pc

D: nbp.

E: pxegrub.I86PC.Solaris_10-1

Answer: E, D

Explanation:

As per exhibit these are the two files in the netboot directory.

Note:

*Missing argument is:

file=wanbootCGI-URL

Specifies the URL of the wanboot-cgi program on the web server

* During the installation, WAN boot refers to the contents of the /etc/netboot hierarchy on the web server for instructions about how to perform the installation. This directory contains the configuration information, private key, digital certificate, and certificate authority required for a WAN boot installation. During the installation, the wanboot-cgi program converts this information into the WAN boot file system. The wanboot-cgi program then transmits the WAN boot file system to the client.

Question 2. (Single Select)

What information would the "beadm list -ds" command output?

A: a list of all Bes

B: a list of the datasets and snapshot information for the active BE

C: a list of the default sets

D: a list of BEs in machine readable format

E: a list of the datasets and snapshot information for all Bes

Answer: C

Explanation:

You can display information about snapshots, boot environments, and datasets that were created by the beadm command by using the beadm list subcommand. The beadm list command output also displays boot environments that are created by the pkg command.

The beadm list command syntax is:

Syntax: beadm list [-a | [-ds] [-H] [BeName]

The command lists information about the existing boot environment. To view information for a specific boot environment, replace BeName with a boot environment name. If a specific boot environment is not specified, the command lists information about all boot environments. The default is to list boot environments without additional information.

-a – Lists all available information about the boot environment. This information includes subordinate datasets and snapshots.

-d – Lists information about all subordinate datasets that belong to the boot environment.

-s – Lists information about the snapshots of the boot environment.

-H – Prevents listing header information. Each field in the output is separated by a semicolon.

Question 3. (Single Select)

To upgrade a system from Oracle Solaris 10 to Oracle Solaris 11, it is necessary to_____.

A: convert all Oracle Solaris 10 packages to Oracle Solaris 11 packages using IPS

B: use IPS and Live Upgrade to install all updated software

C: use IPS to replace the Oracle Solaris 10 kernel with the Oracle Solaris 11 kernel

D: update Oracle Solaris 10 from an Oracle Solaris 11 repository

E: save user data and perform a new Oracle Solaris 11 install; there is no upgrade method

Answer: D

Explanation:

There are no upgrade methods or tools available to transition from Oracle Solaris 10 to Oracle Solaris 11.

You cannot use an installer to upgrade from Oracle Solaris 10 to Oracle Solaris 11.

Oracle Solaris 11 Transition Tools and Features

Note:

* There are no upgrade methods or tools available to transition from Oracle Solaris 10 to Oracle Solaris 11.

You cannot use an installer to upgrade from Oracle Solaris 10 to Oracle Solaris 11.

/ JumpStart Migration Utility (js2ai)

Used to convert Oracle Solaris 10 JumpStart rules and profiles to a format that is compatible with AI manifest entries.

/ ZFS shadow migration feature

Used to migrate data from an existing file system to a new file system.

/ Oracle Solaris 11 support for Oracle Solaris 10 zones

Used to migrate your Oracle Solaris 10 application environments to an Oracle Solaris 11 system.

/ NFS file sharing and pool migration

Used to access shared files from an Oracle Solaris 10 system on an Oracle Solaris 11 system.

Used to import a ZFS storage pool from an Oracle Solaris 10 system into an Oracle Solaris 11 system.

Question 4. (Single Select)

When attempting to perform an installation of Oracle Solaris 11, you encounter a failure message along the lines of "no offers were received." What is the most likely reason for this message and why?

A: The system could not obtain a DHCP-based lease so it could not proceed.

B: The amount of disk space offered by the installer is inadequate so the installer attempted to compress data in memory.

C: The minimum amount of memory is not sufficient to load the necessary network driver so the installer tried to offer disk as backing store.

D: The IP address provided is outside the range of allocatable addresses.

E: An IP address provided is located on a different network segment because the correct RARP server did

not respond.

Answer: A

Explanation:

No DHCP or Proxy DHCP Offers Were Received

If a DHCP server is not responding to an x86 client,s request, you see the following messages:

Intel(R) Boot Agent PXE Base Code (PXE-2.1 build 0.86)

Copyright(C) 1997-2007, Intel Corporation

CLIENT MAC ADDR 00 14 4F 29 04 12 GUID FF2000008 FFFF FFFF FFFF 7BDA264F1400

DHCP..... No DHCP or ProxyDHCP offers were received

PXE-MOF: Exiting Intel Boot Agent

The timeout message indicates that the client is sending a DHCP request and not getting a response. This issue is probably due to an error in the DHCP configuration. Check to see if your client is configured correctly in the DHCP server.

Question 5. (Multi Select)

What are the three properties of a business critical cloud infrastructure?

A: flexible, virtual application instances

B: service isolation

C: dedicated, single purpose file servers

D: easy, intuitive provisioning, chargeback, and capacity planning

E: rigid, inflexible network design

Answer: B, A, D

Explanation:

Oracle Cloud Infrastructure

Overview

* Flexible cloud infrastructure supports dynamic resource pooling, elastic scalability, and rapid application deployment

* Includes Oracle Enterprise Manager, a complete cloud lifecycle management solution that allows you to quickly set up, manage, and support enterprise clouds and traditional Oracle IT environments from applications to disk
* Built-in security and high availability
* Application-aware virtualization and management capabilities

Need more info? Check the link below:

https://pass2certify.com/exam/1z0-580

Thanks for Being a Valued Pass2Certify User!

Guaranteed Success Pass Every Exam with Pass2Certify.

Save $15 instantly with promo code

SAVEFAST

Sales: sales@pass2certify.com

Support: support@pass2certify.com