Salesforce

JS-Dev-101

Salesforce Certified JavaScript Developer - Multiple Choice

- Up to Date products, reliable and verified.
- Questions and Answers in PDF Format.

For More Information – Visit link below:

Web: www.examkill.com/

Version product

Latest Version: 6.0

Question: 1

Refer to the code below:

```
01 const exec = (item, delay) =>{
02 newPromise(resolve => setTimeout( () => resolve(item), delay)),
03 async function runParallel() {
04 Const (result1, result2, result3) = await Promise.all{
05 [exec ('x', '100') , exec('y', 500), exec('z', '100')]
06 );
07 return `parallel is done: $(result1)$(result2)$(result3)`;
08 }
}
}
```

Which two statements correctly execute the runParallel () function?
Choose 2 answers

A. Async runParallel () .then(data);
B. runParallel ( ). done(function(data){return data;});
C. runParallel () .then(data);
D. runParallel () .then(function(data)return data

Answer: B, D

Question: 2

A developer needs to test this function:

```
01const sum3 = (arr) => (
02if (!arr.length) return 0,
03if (arr.length === 1) return arr[0],
04if (arr.length === 2) return arr[0]+ arr[1],
05 return arr[0] + arr[1] + arr[2],
06 );
```

Which two assert statements are valid tests for the function?
Choose 2 answers

A. console.assert(sum3(1, '2')) == 12);
B. console.assert(sum3(0)) == 0);
C. console.assert(sum3(-3, 2)) == -1);
D. console.assert(sum3('hello', 2, 3, 4)) === NaN);

Answer: A, C

Question: 3

Which statement phrases successfully?

A. JSON.parse (‘ foo ’);
B. JSON.parse (“ foo ”);
C. JSON.parse(“ ‘ foo ’ ”);
D. JSON.parse(‘ “ foo ” ’);

Answer: D

Question: 4

Refer to the code below:

```
01 let car1 = new promise((_, reject) =>
02 setTimeout(reject, 2000, “Car 1 crashed in”));
03 let car2 = new Promise(resolve => setTimeout(resolve, 1500, “Car 2
completed”));
04 let car3 = new Promise(resolve => setTimeout (resolve, 3000, “Car 3
Completed”));
05 Promise.race([car1, car2, car3])
06 .then(value => (
07 let result = $(value) the race. `;
08 ))
09 .catch( arr => (
10 console.log(“Race is cancelled.”, err);
11 ));
```

What is the value of result when Promise.race executes?

A. Car 3 completed the race.
B. Car 1 crashed in the race.
C. Car 2 completed the race.
D. Race is cancelled.

Answer: C

Question: 5

Refer to the code below:

```
for(let number =2 ; number <= 5 ; number += 1 ) {
// insert code statement here
}
```

Thedeveloper needs to insert a code statement in the location shown. The code statement has these requirements:

1. Does require an import
2. Logs an error when the boolean statement evaluates to false
3. Works in both the browser and Node.js

Which meet the requirements?

A. assert (number % 2 === 0);
B. console.error(number % 2 === 0);
C. console.debug(number % 2 === 0);
D. console.assert(number % 2 === 0);

Answer: B

Question: 6

A developer is working on an ecommerce website where the delivery date is dynamically calculated based on the current day. The code line below is responsible for this calculation.

Const deliveryDate = new Date ();

Due to changes in the business requirements, the delivery date must now be today's date + 9 days.

Which code meets thisnew requirement?

A. deliveryDate.setDate((new Date ( )).getDate () +9);
B. deliveryDate.setDate(Date.current () + 9);
C. deliveryDate.date = new Date(+9) ;
D. deliveryDate.date = Date.current () + 9;

Answer: A

Question: 7

Which three statements are true about promises ?
Choose 3 answers

A. The executor of a new Promise runs automatically.
B. A Promise has a .then() method.
C. A fulfilled or rejected promise will not change states .
D. A settled promise can become resolved.
E. A pending promise canbecome fulfilled, settled, or rejected.

Answer: B, C, E

Question: 8

Given the code below:

```
01 function GameConsole (name) {
02 this.name = name;
03 }
04
05 GameConsole.prototype.load = function(gamename) {
06 console.log( ` $(this.name) is loading agame : $(gamename) …`);
07 )
08 function Console 16 Bit (name) {
09 GameConsole.call(this, name) ;
10 }
11 Console16bit.prototype = Object.create ( GameConsole.prototype) ;
12 //insert code here
13 console.log( ` $(this.name) is loading a cartridge game :$(gamename) …`);
14 }
15 const console16bit = new Console16bit(‘ SNEGeneziz ’);
16 console16bit.load(‘ Super Nonic 3x Force ’);
```

What should a developer insert at line 15 to output the following message using the method ?
> SNEGeneziz is loading a cartridgegame: Super Monic 3x Force . . .

A. Console16bit.prototype.load(gamename) = function() {
B. Console16bit.prototype.load = function(gamename) {
C. Console16bit = Object.create(GameConsole.prototype).load = function(gamename) {
D. Console16bit.prototype.load(gamename) {

Answer: B

Question: 9

A developer has the following array of student test grades:
Let arr = [7, 8, 5, 8, 9];
The Teacher wants to double each score and then see an array of the students who scored more than 15 points.
How should thedeveloper implement the request?

A. Let arr1 = arr.filter((val) => (return val > 15)) .map ((num) => (return num *2))
B. Let arr1 = arr.mapBy ((num) => (return num *2)) .filterBy ((val) => return val > 15)) ;
C. Let arr1 = arr.map((num) => num*2). Filter ((val) => val > 15);
D. Let arr1 = arr.map((num) => (num *2)).filterBy((val) => (val >15));

Answer: C

Question: 10

A test has a dependency on database.query. During the test the dependency is replaced with an object called database with the method, query, that returns an array. The developer needs to verify how many times the method was called and the arguments used each time.
Which two test approaches describe the requirement?
Choose 2 answers

A. Integration
B. Black box
C. White box
D. Mocking

Answer: C, D

For More Information – Visit link below:
https://www.examkill.com/

Sales: sales@examkill.com
Support: support@examkill.com

FEATURES:

- 100% Pass Guarantee
- 30 DaysMoney Back Guarantee
- 24/7 Live Chat Support(Technical & Sales)
- Instant download after purchase
- 50,000 +ve Reviews
- 100% Success Rate
- Discounts Available for Bulk Orders
- Updates are free for 90 days
- Verified answers by experts