Distribution of Houses by Predominant Materials of Roof and Wall and Level of Damage Risk

Table No. : HR 10   **State : HARYANA**   **FATEHABAD**

Wall / Roof		Census Houses		Level of Risk under								
		No. of Houses	%	EQ Zone				Wind Velocity m/s				Flood Prone Area in %
				V	IV	III	II	55 & 50	47	44 & 39	33	
						Area in %				Area in %		
						58.4	41.6	2.0	98.0			65.7
WALL												
A1 - Mud &	Rural	11,197	4.6									
Unburnt Brick Wall	Urban	1,952	0.8									
	Total	*13,149*	*5.4*			M	L	VH	H			VH
A2 - Stone Wall	Rural	1,097	0.5									
not packed with mortar	Urban	800	0.3									
	Total	*1,897*	*0.8*			M	L	H	M			VH
Total - Category - A		*15,046*	*6.2*									
B - Burnt Bricks Wall	Rural	175,733	72.5									
& Stone wall packed	Urban	46,222	19.1									
with mortar	*Total*	*221,955*	*91.6*			L	VL	H	M			H/M
Total - Category - B		*221,955*	*91.5*									
C1 - Concrete Wall	Rural	1,847	0.8									
	Urban	692	0.3									
	Total	*2,539*	*1.1*			VL	VL	L	VL			L/VL
C2 - Wood wall	Rural	94	-									
	Urban	30	-									
	Total	*124*	*-*			VL	VL	VH	H			H
Total - Category - C		*2,663*	*1.1*									
X - Other Materials	Rural	2,344	1.0									
	Urban	496	0.2									
	Total	*2,840*	*1.2*			VL	VL	VH	H			VH
Total - Category - X		*2,840*	*1.2*									
TOTAL HOUSES*		**242,504**										
ROOF												
R1 - Light Weight	Rural	70,437	29.0									
Sloping Roof	Urban	8,543	3.5									
	Total	*78,980*	*32.5*			L	VL	VH	VH			VH
R2 - Heavy Weight	Rural	13,594	5.6									
Sloping Roof	Urban	2,071	0.9									
	Total	*15,665*	*6.5*			L	VL	H	M			H
R3 - Flat Roof	Rural	108,281	44.7									
	Urban	39,578	16.3									
	Total	*147,859*	*61.0*	*Damage Risk as per that for the Wall supporting it*								
TOTAL HOUSES*		**242,504**										

Probable Maximum Precipitation at a Station of the district in 24 hrs is   280 mm

Housing Category : Wall Types

Category - A : Buildings in field-stone, rural structures,
        unburnt brick houses, clay houses

Category - B : Ordinary brick building; buildings of the large block & prefabricated
        type, half-timbered structures, building in natural hewn stone

Category - C : Reinforced building, well built wooden structures

Category - X : Other materials not covered in A,B,C. These are generally light.

Notes : *1. Flood prone area includes that protected area which may have more severe*
        damage under failure of protection works. In some other areas the local
        damage may be severe under heavy rains and chocked drainage.

   2. Damage Risk for wall types is indicated assuming heavy flat roof
   in categories A, B and C (Reinforced Concrete) building

   3. Source of Housing Data : Census of Housing, GOI, 2011

Housing Category : Roof Type

Category - R1 - Light Weight (Grass, Thatch,
Bamboo, Wood, Mud, Plastic, Polythene,
GI Metal, Asbestos Sheets, Other Materials)

Category - R2 - Heavy Weight (Tiles, Stone/Slate)

Category - R3 - Flat Roof (Brick, Concrete)

EQ Zone V : Very High Damage Risk Zone (MSK > IX)

EQ Zone IV : High Damage Risk Zone (MSK VIII)

EQ Zone III : Moderate Damage Risk Zone (MSK VII)

EQ Zone II : Low Damage Risk Zone (MSK < VI)

Level of Risk : VH = Very High; H = High;

        M = Moderate; L = Low; VL = Very Low

* Total No.of Houses excluding Vacant/Locked Houses