

Folder structure

Src

|

api→axios.js & auth.js

Components→loginform.jsx

Pages→loginpage.jsx

Routes→ProtectedRoute.jsx

Used proxy in vite

```
import { useState } from "react";
import { useNavigate } from "react-router-dom";
import { loginUser } from "../api/auth";

export default function LoginForm() {
  const [email, setEmail] = useState("");
  const [password, setPassword] = useState("");
  const [loading, setLoading] = useState(false);
  const [error, setError] = useState("");
  const navigate = useNavigate();

  const handleSubmit = async (e) => {
    e.preventDefault();
    setLoading(true);
    setError("");

    try {
      const result = await loginUser({ email, password });

      if (!result.token) {
        setError("Invalid credentials");
        return;
      }

      // store token
      localStorage.setItem("token", result.token);

      // go to dashboard (ProtectedRoute will validate admin)
      navigate("/dashboard", { replace: true });

    } catch (err) {
      setError(err.message || "Login failed");
    } finally {
      setLoading(false);
    }
  }
}
```



```

    </div>

    <div className="flex justify-end">
      <button type="submit" disabled={loading} className="w-full bg-gray-400
text-white py-3 rounded-lg max-w-[90px] self-end">
        {loading ? "Logging in..." : "Log In →"}
      </button>
    </div>
  </form>
</div>
);
}

```

```

import api from "./axios";

export const loginUser = async (data) => {
  try {
    const response = await api.post("/auth/login_user", data);
    return response.data;
  } catch (err) {
    throw err.response?.data || err;
  }
};

```

```

import axios from "axios";

const api = axios.create({
  baseURL: "/api", // use Vite proxy
  headers: { "Content-Type": "application/json" },
  withCredentials: true, // include cookies
});

// Automatically attach token from localStorage
api.interceptors.request.use((config) => {
  const token = localStorage.getItem("token");
  if (token) config.headers.Authorization = `Bearer ${token}`;
  return config;
});

export default api;

```

```

import { Navigate, Outlet } from "react-router-dom";

const decodeJwt = (token) => {
  try {
    const base64Url = token.split(".")[1];

```

```

const base64 = base64Url.replace(/-/g, "+").replace(/_/g, "/");
const jsonPayload = decodeURIComponent(
  atob(base64)
    .split("")
    .map((c) => "%" + ("00" + c.charCodeAt(0).toString(16)).slice(-2))
    .join("")
);
return JSON.parse(jsonPayload);
} catch {
  return null;
}
};

export default function ProtectedRoute() {
  const token = localStorage.getItem("token");

  // 1. No token → login
  if (!token) {
    return <Navigate to="/" replace />;
  }

  const decoded = decodeJwt(token);

  // 2. Invalid token → force logout
  if (!decoded) {
    localStorage.removeItem("token");
    return <Navigate to="/" replace />;
  }

  // 3. Role check
  const isAdmin = decoded?.is_admin === true;

  if (!isAdmin) {
    return <Navigate to="/" replace />;
  }

  // 4. Allow access
  return <Outlet />;
}

```

```

import { Routes, Route } from "react-router-dom";
import LoginPage from "../pages/LoginPage";
// import Dashboard from "../components/Dashboard";
import Rightpanel from '../components/Rightpanel';
import ProtectedRoute from "../routes/ProtectedRoute";
import './App.css'

function App() {

```

```

return (
  <Routes>
    {/* public */}
    <Route path="/" element={<LoginPage />} />

    {/* protected */}
    <Route element={<ProtectedRoute />}>
      <Route path="/dashboard" element={<Rightpanel />} />
    </Route>
  </Routes>
);
}

export default App;

```

```

// main.jsx or index.jsx
import React from "react";
import ReactDOM from "react-dom/client";
import App from "./App";
import { BrowserRouter } from "react-router-dom";

ReactDOM.createRoot(document.getElementById("root")).render(
  <React.StrictMode>
    <BrowserRouter>
      <App />
    </BrowserRouter>
  </React.StrictMode>
);

```