

Dashboard.jsx

```
import { useEffect, useState } from "react";
import { useNavigate } from "react-router-dom";
import { FaEye, FaTrash } from "react-icons/fa";

const Dashboard = () => {
  const [students, setStudents] = useState([]);
  const navigate = useNavigate();

  // Load students from localStorage
  useEffect(() => {
    const data = JSON.parse(localStorage.getItem("students"));
    setStudents(data);
  }, []);

  // Delete student
  const handleDelete = (indexToDelete) => {
    const confirmDelete = window.confirm("Are you sure you want to delete?");
    if (!confirmDelete) return;

    const updatedStudents = students.filter(
      (_, index) => index !== indexToDelete
    );

    setStudents(updatedStudents);
    localStorage.setItem("students", JSON.stringify(updatedStudents));
  };

  return (
    <div className="p-6">
      <h1 className="text-2xl font-bold mb-4">Student Dashboard</h1>

      { /* Navigate to Register */ }
      <button
        onClick={() => navigate("/")}
        className="mb-4 bg-green-500 hover:bg-green-600 text-white px-4 py-2
rounded"
      >
        Go to Register
      </button>

      { /* Table */ }
      <table className="w-full border shadow-md">
        <thead>
          <tr className="bg-gray-200">
            <th className="border p-2">Name</th>
            <th className="border p-2">Email</th>
            <th className="border p-2">Course</th>

```

```

        <th className="border p-2 text-center">Actions</th>
      </tr>
    </thead>

    <tbody>
      {!students || students.length === 0 ? (
        <tr>
          <td colSpan="4" className="text-center p-4">
            No students found
          </td>
        </tr>
      ) : (
        students.map((student, index) => (
          <tr key={index} className="text-center">
            <td className="border p-2">
              {student.name || "NA"}
            </td>
            <td className="border p-2">
              {student.email}
            </td>
            <td className="border p-2">
              {student.course}
            </td>

            { /* ACTIONS */ }
            <td className="border p-2">
              <div className="flex justify-center gap-3">

                { /* VIEW */ }
                <button
                  onClick={() => navigate(`/student/${index}`)}
                  className="bg-blue-500 hover:bg-blue-600 text-white p-2
rounded"

                >
                  <FaEye />
                </button>

                { /* DELETE */ }
                <button
                  onClick={() => handleDelete(index)}
                  className="bg-red-500 hover:bg-red-600 text-white p-2
rounded"

                >
                  <FaTrash />
                </button>

              </div>
            </td>
          </tr>
        ))
      )
    </tbody>
  </table>

```

```

        </tr>
      ))
    }}
  </tbody>
</table>
</div>
);
};

export default Dashboard;

```

StudentDetails.jsx

```

import { useParams } from "react-router-dom";

const StudentDetails = () => {
  const { id } = useParams();
  const students = JSON.parse(localStorage.getItem("students"));

  const student = students?.[id];

  if (!student) {
    return <h2 className="p-6">Student not found</h2>;
  }

  return (
    <div className="p-6">
      <h1 className="text-2xl font-bold mb-4">Student Details</h1>

      <p><strong>Name:</strong> {student.name}</p>
      <p><strong>Email:</strong> {student.email}</p>
      <p><strong>Course:</strong> {student.course}</p>
    </div>
  );
};

export default StudentDetails;

```

App.jsx

```

import { BrowserRouter, Routes, Route } from "react-router-dom";
import Register from "../pages/Register";
import Dashboard from "../pages/Dashboard";
import StudentDetails from "../pages/StudentDetails";
import "../app.css";
function App() {
  return (

```

```
<BrowserRouter>
  <Routes>
    <Route path="/" element={<Register />} />
    <Route path="/dashboard" element={<Dashboard />} />
    <Route path="/student/:id" element={<StudentDetails />} />
  </Routes>
</BrowserRouter>
);
}

export default App;
```