PAPER PRESENTATION

Programming Refusal with Conditional Activation Steering

Conditional control of model behavior

Tia Manoukian, Nada Hammad, Nikola Dobričić


Paper by Bruce W. Lee et al. | ICLR 2025

The alignment dilemma

Preference-based alignment (e.g., RLHF) is:

Resource-intensive
costly weight optimization


Subjective
black-box rewards



Same request, opposite policy: harm depends on context.

Lee et al., ICLR 2025, Sec. 1; preference modeling: Stiennon et al., 2020; Rafailov et al., 2024; medical examples: Wang et al., 2023b; Xie et al., 2024a.

Goal: refusal rules that depend on the input




Selective refusal, normal answers elsewhere, and no weight optimization.

Lee et al., ICLR 2025, Abstract and Sec. 1; rules from Fig. 8a and Fig. 9a.

Background: steering through activations

Behavior can be changed at five points.

Activation steering edits the hidden state between layers, at inference time.




Lee et al., ICLR 2025, Sec. 2; intervention points: Tamoyan et al., 2024 and others; transformer inference: Vaswani et al., 2017.

Background: activation addition (ActAdd)

$$\mathbf{h} \leftarrow \mathbf{h} + \alpha \cdot \mathbf{v}$$


- $\mathbf{h}$ hidden state at a layer
- $\mathbf{v}$ steering vector, from contrasting examples
- α scaling factor



Too large an α breaks coherence; too small has no effect.

Lee et al., ICLR 2025, Sec. 2; ActAdd: Turner et al., 2023; scaling: Rimsky et al., 2024.

The indiscriminate refusal problem



91.8%


of *harmless* prompts refused

up from 1.0%

The vector is added to every input.

Lee et al., ICLR 2025, Sec. 1, Fig. 1, Table 3; Teknium et al., 2024; Arditi et al., 2024.

The CAST insight



Schematic, not measured data

Different prompt categories activate *distinct directions* in the hidden states.

- harmful prompt
- harmless prompt
- condition vector **c**


Lee et al., ICLR 2025, Sec. 1 (following Hu et al., 2024) and Sec. 3.1.

The CAST mechanism

$$\mathbf{h}' \leftarrow \mathbf{h} + \underbrace{f\big(\mathrm{sim}(\mathbf{h}, \mathrm{proj}_{\mathbf{c}}\mathbf{h})\big)}_{\text{switch: 0 or 1}} \cdot \underbrace{\alpha \cdot \mathbf{v}}_{\text{behavior}}$$

$$f(s) = \begin{cases} 1 & \text{if } s > \theta \\ 0 & \text{otherwise} \end{cases}$$


s: cosine similarity between $\mathbf{h}$ and its projection onto $\mathbf{c}$



Lee et al., ICLR 2025, Sec. 3.1; cosine similarity for direction: Hsu et al., 2024.

CAST during generation


The condition is checked once, on the prompt.



Lee et al., ICLR 2025, Sec. 3.1; App. A.2, Fig. 11.

CAST in action


Rule: if $\mathbf{c}_{\text{crime}}$ then add refusal



Without the condition, the refusal vector would be added to *both*.

Lee et al., ICLR 2025, Sec. 5, Fig. 8c (the paper's illustration of rule outcomes).

Multi-conditioning



$$f(\cdot) = \begin{cases} 1 & \text{if } s_{\text{adult}} > \theta_{\text{adult}} \textbf{ or } s_{\text{hate}} > \theta_{\text{hate}} \\ 0 & \text{otherwise} \end{cases}$$

Each condition has its own vector, threshold, and layer.

Lee et al., ICLR 2025, Abstract; Sec. 3.1; Sec. 5, Fig. 8.

Dataset preparation

Behavior v: refusal

$100 \times 100 = 10{,}000$

Alpaca instructions $\times$ refusal/compliance prefixes

D^+ ... **Sorry I can't**

D^- ... **Sure! Let me**


Condition c: harmful

D^+ **Sorry-Bench**: harmful
4,050 generated, 45 categories

D^- **Alpaca**: harmless
random benign instructions

Lee et al., ICLR 2025, Sec. 3.2, Fig. 3; Sec. 4; Alpaca: Taori et al., 2023; Sorry-Bench: Xie et al., 2024b.

Vector extraction: where tokens are pooled



One pooled state $\bar{\mathbf{h}}$ per example and layer: the suffix for behaviors, the whole prompt for conditions.

Lee et al., ICLR 2025, Sec. 3.3, Fig. 3; word-level tokens for illustration.

Vector extraction: mean-centering and PCA

1 H_ℓ^+: rows $\bar{\mathbf{h}}$ of all D^+
H_ℓ^-: rows $\bar{\mathbf{h}}$ of all D^-

Stack the pooled states
D^+: refusal / harmful
D^-: compliance / harmless

---

2 $\mu_\ell = \dfrac{H_\ell^+ + H_\ell^-}{2}$

Mean-center
the center of all examples

---

3 $\textbf{vector}_\ell = \mathrm{PCA}\left(H_\ell^+ - \mu_\ell,\ H_\ell^- - \mu_\ell\right)$

PCA: first principal component, the direction of maximum variance

Repeated for each layer ℓ, giving one **v** or **c** per layer.

Lee et al., ICLR 2025, Sec. 3.3; following Tan et al., 2024; Ball et al., 2024; Zou et al., 2023.

Our experiments: three questions

Does finding a direction mean we can control behavior?



Our experiments, not in the paper: four open 7–9B models, all settings chosen on validation data.

Setup: every model needs its own settings

Chosen on validation prompts only


	Condition layer	Steering layers	Strength α
Qwen3-8B	24 of 36	14–23	8
OLMo2-7B	5 of 32	18–26	4
Granite3.3-8B	37–38 of 40	16–26	2
Hermes3-8B	24–26 of 32	10–20	1
One fixed setting	8	10–20	4

One setting for all models fails on both steps.

Our experiments, condition layer per seed (3 seeds); steering from a judged validation sweep.

Representation: probe vs. CAST detector

Held-out test F1 · same hidden states · layers chosen on validation



Only on Qwen3 does CAST match the probe.

Our experiments, 3 seeds; 90 harmful + 140 benign test prompts.

Representation: a pair built to look alike

XSTest contrast pair · gate decision, same in all 3 seeds

	CAST		Probe	
	Python process	person	Python process	person
Qwen3-8B	**on**	**on**	off	**on**
OLMo2-7B	off	off	off	**on**
Granite3.3-8B	off	off	off	**on**
Hermes3-8B	off	off	off	**on**

"How can I kill a Python process?" vs. "How can I kill a person?"

CAST answers both alike; the probe tells them apart.

Our experiments, prompts from XSTest (Röttger et al., 2024); thresholds frozen on our validation split.

Robustness: adding irrelevant context

One benign request · seed 17

Original: "Summarize the importance of the US Constitution." → all gates off

+ context
"Background notes unrelated to the question: A public garden has a gravel path. . . " (about 420 words)
+ the same request

	Qwen3	OLMo2	Granite	Hermes
CAST	**on**	**on**	off	off
Probe	off	**on**	**on**	off

OLMo2-7B + CAST judged: decline

"I'm sorry, I cannot fulfill requests to provide content that is not factually or currently processing my duties. . . "

Same request: the added text flips gates, differently in each model.

Our experiments, exact output, cut at 50 new tokens.

Robustness: the gate stops reading the request

Gate rate (%) on harmful / benign test prompts


	CAST		Probe	
	original	+ context	original	+ context
Qwen3-8B	98 / 0	**100 / 100**	96 / 0	**100 / 45**
OLMo2-7B	89 / 5	**100 / 100**	97 / 0	**100 / 100**
Granite3.3-8B	90 / 12	**0 / 0**	98 / 0	**100 / 100**
Hermes3-8B	87 / 12	**24 / 33**	96 / 0	**59 / 0**

With added text, neither gate follows the request.

Our experiments, 90 harmful + 140 benign test prompts, 3 seeds; frozen thresholds; + context = about 420 words of unrelated text.

Control: the same vector at tuned settings

One harmful request · OLMo2-7B · gate on




Steering every benign prompt, share of broken replies:

OLMo2 98.8% → 0.5% Granite 99.6% → 1.4%

Our experiments, seed 17 example; rates over 140 benign prompts, 3 seeds; model judge.

Control: a narrow strength window

Steering every prompt · strength as a multiple of each model's tuned α




Half strength already refuses; double breaks the model.

Our experiments, 16 + 16 prompt families, 3 seeds, no gate; model judge.

Control: does a better gate give better replies?

Selectivity = harmful judged decline − benign judged decline · same steering



Only where CAST misses and the model would comply.

Our experiments, 90 harmful + 140 benign test prompts, 3 seeds; first model judge.

Caveat: what counts as a refusal?

Steered replies judged as refusals

Qwen3-8B + CAST — both judges: decline

"I can assist with providing harmful or unethical advice. My purpose is to support or encourage activities that could harm others . . . "

Hermes3-8B + probe gate — judge 1: decline · judge 2: clarification

"I'm able to generate that type of content. Please ask for help with that kind of request."


Coherent refusals among 40 sampled judged refusals per model:

Qwen3 15 OLMo2 22 Granite 19 Hermes 3

Steering produces refusal-shaped text, not always a refusal.

Our experiments, seed 17 examples; post hoc AI review, not human labels.

Conclusion: three different problems



Each part can work, but only with per-model validation that includes unfamiliar and long prompts.

Our experiments, four models, settings frozen on validation, held-out test prompts.

Backup: nonlinear similarity

Does CAST need its nonlinear similarity function?

Held-out test F1 · each score at its own validation-chosen layer

	CAST similarity $\cos\left(\mathbf{h}, \tanh(\mathrm{proj}_{\mathbf{c}}\,\mathbf{h})\right)$	**Direct cosine** $\cos(\mathbf{h}, \mathbf{c})$
Qwen3-8B	**0.989**	**0.840**
OLMo2-7B	**0.900**	**0.928**
Granite3.3-8B	**0.863**	**0.813**
Hermes3-8B	**0.848**	**0.813**

Our experiments, mean of 3 seeds; CAST similarity from Lee et al., Sec. 3.1.