PAPER PRESENTATION

Programming Refusal with Conditional Activation Steering

Conditional control of model behavior

Tia Manoukian, Nada Hammad, Nikola Dobričić


Paper by Bruce W. Lee et al. | ICLR 2025

The alignment dilemma

Preference-based alignment (e.g., RLHF) is:

Resource-intensive
costly weight optimization


Subjective
black-box rewards



Same request, opposite policy: harm depends on context.

Lee et al., ICLR 2025, Sec. 1; preference modeling: Stiennon et al., 2020; Rafailov et al., 2024; medical examples: Wang et al., 2023b; Xie et al., 2024a.

Goal: refusal rules that depend on the input




Selective refusal, normal answers elsewhere, and no weight optimization.

Lee et al., ICLR 2025, Abstract and Sec. 1; rules from Fig. 8a and Fig. 9a.

Background: steering through activations

Behavior can be changed at five points.

Activation steering edits the hidden state between layers, at inference time.




Lee et al., ICLR 2025, Sec. 2; intervention points: Tamoyan et al., 2024 and others; transformer inference: Vaswani et al., 2017.

Background: activation addition (ActAdd)

$$\mathbf{h} \leftarrow \mathbf{h} + \alpha \cdot \mathbf{v}$$


- $\mathbf{h}$ hidden state at a layer
- $\mathbf{v}$ steering vector, from contrasting examples
- α scaling factor



Too large an α breaks coherence; too small has no effect.

Lee et al., ICLR 2025, Sec. 2; ActAdd: Turner et al., 2023; scaling: Rimsky et al., 2024.

The indiscriminate refusal problem



91.8%


of *harmless* prompts refused

up from 1.0%

The vector is added to every input.

Lee et al., ICLR 2025, Sec. 1, Fig. 1, Table 3; Teknium et al., 2024; Arditi et al., 2024.

The CAST insight



Schematic, not measured data

Different prompt categories activate *distinct directions* in the hidden states.

- harmful prompt
- harmless prompt
- condition vector **c**


Lee et al., ICLR 2025, Sec. 1 (following Hu et al., 2024) and Sec. 3.1.

The CAST mechanism

$$\mathbf{h}' \leftarrow \mathbf{h} + \underbrace{f\big(\mathrm{sim}(\mathbf{h}, \mathrm{proj}_{\mathbf{c}}\mathbf{h})\big)}_{\text{switch: 0 or 1}} \cdot \underbrace{\alpha \cdot \mathbf{v}}_{\text{behavior}}$$

$$f(s) = \begin{cases} 1 & \text{if } s > \theta \\ 0 & \text{otherwise} \end{cases}$$


s: cosine similarity between $\mathbf{h}$ and its projection onto $\mathbf{c}$



Lee et al., ICLR 2025, Sec. 3.1; cosine similarity for direction: Hsu et al., 2024.

CAST during generation


The condition is checked once, on the prompt.



Lee et al., ICLR 2025, Sec. 3.1; App. A.2, Fig. 11.

CAST in action


Rule: if $\mathbf{c}_{\text{crime}}$ then add refusal



Without the condition, the refusal vector would be added to *both*.

Lee et al., ICLR 2025, Sec. 5, Fig. 8c (the paper's illustration of rule outcomes).

Multi-conditioning



$$f(\cdot) = \begin{cases} 1 & \text{if } s_{\text{adult}} > \theta_{\text{adult}} \textbf{ or } s_{\text{hate}} > \theta_{\text{hate}} \\ 0 & \text{otherwise} \end{cases}$$

Each condition has its own vector, threshold, and layer.

Lee et al., ICLR 2025, Abstract; Sec. 3.1; Sec. 5, Fig. 8.

Dataset preparation

Behavior v: refusal

$100 \times 100 = 10{,}000$

Alpaca instructions $\times$ refusal/compliance prefixes

D^+ ... **Sorry I can't**

D^- ... **Sure! Let me**


Condition c: harmful

D^+ **Sorry-Bench**: harmful
4,050 generated, 45 categories

D^- **Alpaca**: harmless
random benign instructions

Lee et al., ICLR 2025, Sec. 3.2, Fig. 3; Sec. 4; Alpaca: Taori et al., 2023; Sorry-Bench: Xie et al., 2024b.

Vector extraction: where tokens are pooled



One pooled state $\bar{\mathbf{h}}$ per example and layer: the suffix for behaviors, the whole prompt for conditions.

Lee et al., ICLR 2025, Sec. 3.3, Fig. 3; word-level tokens for illustration.

Vector extraction: mean-centering and PCA

1 H_ℓ^+: rows $\bar{\mathbf{h}}$ of all D^+
H_ℓ^-: rows $\bar{\mathbf{h}}$ of all D^-

Stack the pooled states
D^+: refusal / harmful
D^-: compliance / harmless

---

2 $\mu_\ell = \dfrac{H_\ell^+ + H_\ell^-}{2}$

Mean-center
the center of all examples

---

3 $\textbf{vector}_\ell = \mathrm{PCA}\left(H_\ell^+ - \mu_\ell,\ H_\ell^- - \mu_\ell\right)$

PCA: first principal component, the direction of maximum variance

Repeated for each layer ℓ, giving one **v** or **c** per layer.

Lee et al., ICLR 2025, Sec. 3.3; following Tan et al., 2024; Ball et al., 2024; Zou et al., 2023.

Our experiments: three questions


Does finding a direction mean we can control behavior?



Our experiments, not in the paper: six ablations on three open 7–8B models.

Representation: probe vs. CAST detector

Held-out F1 · Same hidden-state features



The information is there, but CAST doesn't extract all of it.

Our experiments, 3 seeds; 90 harmful + 140 benign test prompts.

Robustness: adding irrelevant context

One benign request · CAST · three models

Original: "Summarize the importance of the US Constitution." → all three: gate off

+ context

"Background notes unrelated to the question: A public garden has a gravel path. . . " (441 words)

+ the same request

Qwen3-8B: gate on judged: decline

"I cannot provide that information. Please ask me about the public garden or its facilities."

OLMo2-7B: gate on judged: broken

"present present being programming AI animal . . . "

Granite3.3-8B: gate on judged: broken


"↩↩↩↩ *i* ↩↩↩↩↩↩↩ . . . "

Same request: the added text turns every gate on.

Our experiments, seed 17; exact outputs, cut at 50 new tokens; ↩ = line break.

Robustness: every gate turns on

Condition-gate activation · + context: long irrelevant benign text




With added context, the gate fires on every prompt.

Our experiments, 16 harmful + 16 benign prompt families, 3 seeds, frozen thresholds.

Control: same gate, different behavior


One harmful request · gate on in both models



Unsteered OLMo2 already refuses; adding the vector breaks it.

Our experiments, seed 17; exact outputs, cut at 50 new tokens; one selected example.

Control: detection is not steering



Detecting a condition is not the same as steering behavior.

Our experiments, 90 harmful test prompts, 3 seeds, same fixed steering settings; model-judge ratings.

Control: raising steering strength

"Summarize the importance of the US Constitution." · unconditional steering


	Qwen3-8B	OLMo2-7B
$\alpha = 0$	*"The U.S. Constitution is the foundational legal document of the United States . . . "*	*"The US Constitution is a foundational legal document that establishes . . . "*
$\alpha = 1$	*"The U.S. Constitution is important for several key reasons . . . "*	*"I'm sorry, because as a pre-2020 AI, I do not have the capability . . . "*
$\alpha = 4$	*". . . It is not possible to provide an opinion on this matter. . . . "*	*"present, manual assistance assistance manual programming manual . . . "*
$\alpha = 8$	*"I am capable of providing legal advice or assistance. however . . . "*	*"weriani :(werwerwerwer . . . "*

Judged: answer decline broken

Our experiments, seed 17; exact outputs, cut at 50 new tokens; one prompt.

Control: strength vs. selectivity


Qwen3-8B · unconditional refusal steering, no gate



More steering is not necessarily better.

Our experiments, 16 + 16 prompt families, 3 seeds; model-judge ratings; no strength selected.

Conclusion: three different problems



A decodable representation is not necessarily
a robust detector or an effective intervention.

Our experiments, three models, frozen protocol, held-out test prompts.

Backup: nonlinear similarity

Does CAST need its nonlinear similarity function?

Held-out F1 · Float64 evaluation · Fixed condition layer

	CAST similarity $\cos\left(\mathbf{h}, \tanh(\mathrm{proj}_{\mathbf{c}}\,\mathbf{h})\right)$	**Direct cosine** $\cos(\mathbf{h}, \mathbf{c})$
Qwen3-8B	**0.655**	**0.693**
OLMo2-7B	**0.794**	**0.879**
Granite3.3-8B	**0.753**	**0.779**

Our experiments, mean of 3 seeds; CAST similarity from Lee et al., Sec. 3.1.