

GeoSAMS Startup

Table of Contents

1	GeoSAMS Setup	1
1.1	Git	1
1.2	Python.....	1
1.3	Math Support.....	1
1.4	Get software and support files	1
2	Using the GUI	2
2.1	Math Setup	2
2.2	Other Noteworthy GUI Settings.....	3
2.3	Starting the Simulation	3
2.4	Upon completion	4

1 GeoSAMS Setup

Starting GeoSAMS can be done entirely via a GUI or manually via scripts, however, before it can be run there exists applications that need to be configured.

- Git
- Python
- Math support, either Matlab or Octave

1.1 Git

Git needs to be installed to pull all files from a repository that supports GeoSAMS. For information on how to use git and other tutorials visit <https://www.atlassian.com/git/tutorials/install-git>

See the NEFS-IT Service Desk to actually have git installed on your GFE, <https://apps-st.fisheries.noaa.gov/jirasm/servicedesk/customer/portal/2>

1.2 Python

Similarly you will need to have python installed. This is also easily done. Start at <https://www.python.org/downloads/>

See the NEFS-IT Service Desk to actually have python installed on your GFE

The user is not expected to have a working knowledge of python. It is only used to call scripts that do the algorithmic processing.

1.3 Math Support

To run this simulation you will need to have Matlab or Octave installed. Octave is a free software package distributed under a GNU License and can be installed by visiting: <https://octave.org/download>

Octave will also need additional packages from <https://gnu-octave.github.io/packages/>

- io
- geometry
- mapping
- statistics

As you install these packages take note of where they are installed. Although you can find out from inside of Octave by executing, *pkg list*.

1.4 Get software and support files

The next step will be to get the current GeoSAMS release. This is easily done via git.

Navigate to the directory where you want to install the files. Then enter the command.

➤ git clone <https://github.com/NEFSC/READ-PDP-GeoSAMS.git> <GeoRoot>

1.5 Windows 10 Terminal Color

By default, Win10 does not support ANSI Escape Sequences to set font color. This can be changed by

To use ANSI colours in the Windows terminal requires setting VirtualTerminalLevel.

In Windows 10 versions 1511 through to 1903 this had to be enabled in the registry at:

[HKEY_CURRENT_USER\Console]

"VirtualTerminalLevel"=dword:00000001

- 1) Select Windows Key and search for Registry Editor, start it. Navigate to
Computer -> HKEY_CURRENT_USER -> Console
- 2) Then right click in right pane and select New -> Dword
- 3) Enter VirtualTerminalLevel
- 4) Right Click on new entry, select Modify, and set value to 1


2 Using the GUI

The remaining setup is all done via the GUI. This is opened via the command line at the <GeoRoot> directory.

<GeoRoot> > python PythonScripts\GUI\GeoSAM\GeoSams.py

2.1 Math Setup

Upon opening the GUI, first go to the Math Setup Tab



Here you can edit the .octaverc file to let Octave know where packages have been installed. Click the Octave radio button and you will be presented with the current setting. Make the changes and click Write Startup File to save the file.

On the off chance you will use Matlab, it defaults to that radio button. You should not need to make any changes as the information presented has already been installed when downloaded from git.

2.2 GUI Help

Each tab within the GUI has a help button noted by a blue background on WIN machines or blue outline otherwise. Clicking this button will open another scrollable window that the user can review for more information on what is present on that tab.

2.3 Starting the Simulation

Peruse the other tabs in the GUI. For now the defaults should be adequate. When ready click the **START Sim** at the bottom of the GUI. This button caused several steps to occur.

- A. Saves all of the configuration files, overwriting if no names were changed.
- B. When this button is clicked the GUI checks to see if the needed data CSV files have been created. If not it will run the Update.bat/.sh script. This script performs the following:

1. Unzip Dredge Data
2. Builds GeoSams and UK executables
3. Runs the TrawlData5mmbin m-file script

TrawlData5mmbin.m takes the trawl data from “*OriginalData/dredgetowbysize7917.csv*” and makes a csv, e.g. “*Data/bin5mmYYYY[MA|GB].csv*”. The output has the dredge observations in 5mm bins for each year and domain requested.

4. Runs the PullOutRecruitData m-file script

PullOutRecruitData.m again looks at the trawl data from “*OriginalData/dredgetowbysize7917.csv*” and sums the shell lengths from 3cm to 6 cm.

5. Runs the ProcessRecruitData m-file script

ProcessRecruitData.m take the recruit estimates from “*OriginalData/NewRecruits.csv*”:

(A) Convert to scallops per m² → “*Data/RecruitsUnadjusted.csv*”

(B) Convert to scallops per m², adjusted for dredge under-sampling → “*Data/RecruitsRockStrataAdjustment.csv*”. This assumes 40% detection generally and 27% detection in rock chain strata.

(C) Split data into GB and MA segments based on a dividing line at *longitude* = -70:5. Add UTM19 coordinates for GB and UTM18 coordinates for MA. → “*Data/RecruitsGB.csv*”, “*Data/RecruitsMA.csv*”

(D) Split data into individual years requested. → “*Data/RecruitsYYYY[MA|GB].csv*”

6. Runs the NearestNeighborRecInterp m-file script

- C. Starts the GeoSAMS growth simulation
- D. Starts the UKInterpolation that takes the GeoSAMS output position on survey locations and interpolates them to regional locations
- E. Plots the results and saves the plots as PDF files in <GeoRoot>\Results

As different applications are run and completed, the GUI will display message boxes informing the user of its progress.

2.3.1 Early Termination

If for any reason the user wishes to terminate the program before completion, type Ctrl-C in the window where you started the GUI. This will terminate the currently executing program but leave the GUI in tact. Typing Ctrl-C twice will stop the current executable and the GUI.

2.4 Upon completion

The user now has a couple of options.

- 1) Under the Main Tab you will see a button to open and view the PDF plot files.
- 2) Under the SortByArea Tab

The screenshot shows the GeoSAMS GUI with the 'Sort By Area' tab selected. The interface includes a menu bar with 'Main', 'Growth', 'Special Access', 'Fishing Mort in Special Access', 'SortByArea', 'UKInterpolation', and 'Math Setup'. A 'Sort By Area Help' button is visible. The 'Sort By Area' section contains a '# of Areas' input field set to 7, an 'Update # Areas' button, and a section for 'Output Parameters Areas of Interest File Name' with a dropdown menu set to 'LPUE_' and a text field containing 'AreasOfInterestDataSort.csv'. There are 'Load Data Sort File' and 'Save Data Sort File' buttons, and a 'Run Sort' button. The 'Export Results' section has 'Export This' and 'Export All' buttons, an 'Export File Name' text field, and a 'Browse For Export File' button. Below this, there are two area configuration sections: 'Area 1' and 'Area 2'. Each area has a table with columns for years (2015, 2016, 2017), a 'Comment' field, a '# corners' input, and corner coordinates (Long, Lat). For Area 1, the comment is 'C2', corners are 3, and coordinates are provided. For Area 2, the comment is 'C2SNEW', corners are 4, and coordinates are provided. There are 'Update # Corners' buttons for each area.

Here the user can click Run Sort to accumulate the identified output parameters by the areas identified in the frames. It will do so by the years given on the Main Tab.

The user may then export this data either for a single output identified in the Output Parameter pull down, **Export This**, or for all of the identified outputs, **Export All**.

3 Manually Running GeoSAMS

The user does not necessarily need to run the GUI. Scripts or manually starting executables are available to walk the simulation and plotting through the command line

3.1 Unpack.sh/.bat

This only needs to be run once to obtain the desired years data. Running it without arguments informs the user what is expected:

➤ <GeoRoot> .\Unpack.bat

Missing arguments

```
"Expecting: Unpack.bat YYYYstart YYYYend DataSource# Domain [M|O]"
>Data Source"
"    NMFS_ALB ==> 1111"
"    CANADIAN ==> 2222"
"    F/V_TRAD ==> 3333"
"    VIMSRSA  ==> 4444"
"    NMFSSHRP ==> 5555"
"    ALL      ==> 0"
"Domain"
"    MA"
"    GB"
"    ALL, both MA and GB"
"[M|O]"
"    M: Use Matlab for numerical processing"
"    O: Use Octave for numerical processing"
```

3.2 Run GeoSAMS

Entering the following command will start the GeoSAMS growth simulation.

➤ <GeoRoot> .\SRC\ScallopPopDensity.exe Scallop.cfg 2015 2017 AL

Without arguments the user will see this response:

➤ <GeoRoot> .\SRC\ScallopPopDensity.exe

Missing parameters

Typical use: \$.\SRC\ScallopPopDensity.exe Scallop.cfg StartYear StopYear Domain

3.3 Process Results

Entering the following command will complete the universal kriging, UK, interpolation and results plots.

➤ <GeoRoot> python .\PythonScripts\ProcessResults.py AL 2015 2017 Scallop.cfg UK.cfg

Without arguments the user will get this response:

➤ <GeoRoot> python .\PythonScripts\ProcessResults.py

Missing command line arguments. Expecting:

\$ ProcessResults.py Domain StartYear EndYear Scallop.cfg UK.cfg