

Zone Assignment

Bryce McManus

2022-01-26

Contents

Intro	1
Library	1
Data	2
Zone assignment	3
FishSET v. NE zone assignment	4
Factors that may affect point assignment	8

Intro

This document shows how observations are assigned in FishSET and compares zone assignments with those found in the most recent version of the scallop data (provided Oct/Nov 2021). It then illustrates certain factors that can affect zone assignment: polygon boundary types, spherical v. planar geometry, and spatial joins.

Library

```
library(sf)
```

```
## Linking to GEOS 3.9.1, GDAL 3.2.1, PROJ 7.2.1
```

```
library(tidyverse)
```

```
## Warning: package 'tidyverse' was built under R version 4.0.5
```

```
## -- Attaching packages ----- tidyverse 1.3.1 --
```

```
## v ggplot2 3.3.5      v purrr  0.3.4
## v tibble  3.1.6      v dplyr  1.0.7
## v tidyr   1.1.4      v stringr 1.4.0
## v readr   2.1.0      v forcats 0.5.1
```

```
## Warning: package 'ggplot2' was built under R version 4.0.5
```

```
## Warning: package 'tidyr' was built under R version 4.0.5

## Warning: package 'dplyr' was built under R version 4.0.5

## Warning: package 'forcats' was built under R version 4.0.5

## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
```

```
library(leaflet)
```

```
## Warning: package 'leaflet' was built under R version 4.0.5
```

Data

This is the data from the most recent Kiteworks folder that was shared with the FishSET team in Oct/Nov of last year.

```
scallop_10_18 <- read_csv("~/NE Scallops/data/updated/cost_join_10_18.csv")
```

```
## New names:
## * `` -> ...1
```

```
## Rows: 34737 Columns: 35
```

```
## -- Column specification -----
## Delimiter: ","
## chr   (7): VTR_PORT, VTR_STATE, GEARCODE, SECGEARFISH, SPPNAME, OPERATOR, NAME
## dbl  (26): ...1, TRIPID, IMGID, YEAR, TRIP_LENGTH, DEALNUM, DOLLAR, POUNDS, ...
## date  (1): Date
## time  (1): Time
```

```
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
tenMinSqr_new <- st_read("~/NE Scallops/data/updated/10 Minute Sq")
```

```
## Reading layer `Ten_Minute_Squares' from data source
##   `C:\Users\bryce.mcmanus\Work\NE Scallops\data\updated\10 Minute Sq'
##   using driver `ESRI Shapefile'
## Simple feature collection with 6291 features and 13 fields
## Geometry type: POLYGON
## Dimension:      XY
## Bounding box:   xmin: -83 ymin: 24 xmax: -65 ymax: 46
## Geodetic CRS:   NAD83
```

Check for duplicate trip IDs.

```
nrow(scallop_10_18)
```

```
## [1] 34737
```

```
scallop_10_18 %>%  
  distinct(TRIPID) %>%  
  nrow()
```

```
## [1] 34737
```

Zone assignment

This is the approach we take in FishSET to assign observations to zones.

```
# create sf version of data, convert to WGS84  
crs <- "+proj=longlat +datum=WGS84"  
# crs <- st_crs(tenMinSqr_new) # using crs from ten minute squares didn't change results  
  
scallop_sf <-  
  st_as_sf(x = scallop_10_18, coords = c("DDLON", "DDLAT"),  
           crs = crs)  
  
# convert Squares to WGS84  
tenMinSqr_new <- st_transform(tenMinSqr_new, crs = st_crs(scallop_sf))  
  
# same results as st_within  
inter <- sf::st_intersects(scallop_sf, tenMinSqr_new)  
  
inter_save <- inter  
  
if (any(lengths(inter) > 1)) { # if more than one zone intersects, assign to closest zone  
  dub <- which(lengths(inter) > 1)  
  inter[dub] <- st_nearest_feature(scallop_sf[dub,], tenMinSqr_new)  
}  
  
# Add ZoneID column to data  
pts <- as.data.frame(as.numeric(inter))  
colnames(pts) <- "col.id"  
pts$ID <- tenMinSqr_new$MN10SQID[pts$col.id]  
scallop_sf$ZoneID <- pts$ID
```

52 points did not intersect a zone and 195 intersected multiple zones. The rest intersected with one zone. Non-intersecting points will show up as NA in the ZoneID column.

```
table(lengths(inter_save))
```

```
##  
##      0      1      2  
##  52 34490  195
```

After reassigning zones with 2+ intersections to the nearest zone.

```
table(lengths(inter))
```

```
##
##      0      1
##    52 34685
```

FishSET v. NE zone assignment

Just to recap: ZoneID is the zone assignment column created using the FishSET approach. MN10SQID is the zone ID column that came with the updated scallop data. There is a 6.15% difference (2086 obs) in zone assignments between ZoneID and MN10SQID.

```
scallop_sf <- scallop_sf %>%
  mutate(fs_ne_match = ZoneID == MN10SQID)

# add ZoneID and match col to scallop_10_18
scallop_10_18 <-
  scallop_sf %>%
  st_set_geometry(NULL) %>%
  select(ZoneID, fs_ne_match) %>%
  bind_cols(scallop_10_18, .)


# summary table of matching IDs
scallop_sf %>%
  st_set_geometry(NULL) %>%
  summarize(n_obs = n(),
            id_match = sum(fs_ne_match, na.rm = TRUE),
            id_no_match = sum(!fs_ne_match, na.rm = TRUE),
            perc_match = id_match/n() * 100,
            perc_no_match = 100 - perc_match)

## # A tibble: 1 x 5
##   n_obs id_match id_no_match perc_match perc_no_match
##   <int>   <int>     <int>     <dbl>     <dbl>
## 1 34737   32599       2086      93.8       6.15
```

All the unassigned points in ZoneID fall on a zone intersection.


```
s_bbox <- st_bbox(filter(scallop_sf, is.na(ZoneID)))

ggplot() +
  geom_sf(data = tenMinSqr_new, fill = "white", color = "black") +
  geom_sf(data = filter(scallop_sf, is.na(ZoneID)), color = "red") +
  coord_sf(xlim = c(s_bbox[1], s_bbox[3]), ylim = c(s_bbox[2], s_bbox[4]))
```



The difference in zone assignment appears only to occur on zone boundaries and intersections.

```
ggplot() +
  geom_sf(data = tenMinSqr_new, fill = "white", color = "black") +
  geom_sf(data = filter(scallop_sf, fs_ne_match),
    aes(color = "Match"),
    alpha = .2,
    show.legend = "point") +
  geom_sf(data = filter(scallop_sf, !fs_ne_match),
    aes(color = "No match"),
    show.legend = "point") +
  coord_sf(xlim = c(s_bbox[1], s_bbox[3]), ylim = c(s_bbox[2], s_bbox[4])) +
  scale_color_manual(values = c("Match" = "blue", "No match" = "red"))
```



This leaflet plot shows the first 20 non-matching zone assignments. Each point has a label showing the zone assigned by FishSET and by NE.

```
# marker labels for leaflet plots
scallop_10_18 <-
  scallop_10_18 %>%
  mutate(ZoneID_lab = paste0("FS: ", ZoneID, "<br/>"),
         MN10SQID_lab = paste0("NE: ", MN10SQID, "<br/>")) %>%
  unite("unite_lab", ZoneID_lab, MN10SQID_lab, sep = " ") %>%
  mutate(unite_lab = paste0(unite_lab, "lon: ", DDLON, "<br/>lat: ", DDLAT))

fs_no_match <- scallop_10_18 %>%
  filter(fs_ne_match == FALSE) %>%
  head(20) %>%
  pull(ZoneID)


ne_no_match <- scallop_10_18 %>%
  filter(fs_ne_match == FALSE) %>%
  head(20) %>%
  pull(MN10SQID)

leaflet() %>%
  addTiles() %>%
  addPolygons(data = filter(tenMinSqr_new, MN10SQID %in% c(fs_no_match, ne_no_match)),
             fillColor = "white",
             fillOpacity = 0.5,
```

```

      color = "black",
      stroke = TRUE,
      weight = 1,
      labelOptions = labelOptions(noHide = TRUE),
      layerId = ~MN10SQID,
      label = ~MN10SQID) %>%
addMarkers(data = head(filter(scallop_10_18, fs_ne_match == FALSE), 20),
  lng = ~DDLON, lat = ~DDLAT,
  label = ~lapply(unite_lab, htmltools::HTML))

```



Leaflet | © OpenStreetMap contributors, CC-BY-SA

Similar to the plot above, but comparing the unassigned points in ZoneID with MN10SQID.

```

fs_na <- scallop_10_18 %>%
  filter(is.na(ZoneID)) %>%
  pull(MN10SQID)


leaflet() %>%
  addTiles() %>%
  addPolygons(data = filter(tenMinSqr_new, MN10SQID %in% fs_na),
    fillColor = "white",
    fillOpacity = 0.5,
    color = "black",
    stroke = TRUE,
    weight = 1,
    labelOptions = labelOptions(noHide = TRUE),
    layerId = ~MN10SQID,

```

```

    label = ~MN10SQID) %>%
  addMarkers(data = filter(scallop_10_18, is.na(ZoneID)),
    lng = ~DDLON, lat = ~DDLAT,
    label = ~lapply(unite_lab, htmltools::HTML))

```



Leaflet | © OpenStreetMap contributors, CC-BY-SA

Factors that may affect point assignment

Polygon boundary types

Point assignment can vary depending on whether polygon boundaries are treated as “closed”, “open”, or “semi-open”.

```

inter_closed <- lengths(st_intersects(scallop_sf, tenMinSqr_new, model = "closed"))
inter_open <- lengths(st_intersects(scallop_sf, tenMinSqr_new, model = "open"))
inter_semi <- lengths(st_intersects(scallop_sf, tenMinSqr_new, model = "semi-open"))

bound_type <- tibble(Closed = inter_closed, Open = inter_open, Semi = inter_semi)

pivot_longer(bound_type, cols = c("Closed", "Open", "Semi"),
  names_to = "boundary_type", values_to = "Zones_assigned") %>%
  group_by(boundary_type) %>%
  count(Zones_assigned)

```

```
## # A tibble: 7 x 3
```



```
## # Groups:   boundary_type [3]
##   boundary_type Zones_assigned     n
##   <chr>         <int> <int>
## 1 Closed         0     52
## 2 Closed         1  34490
## 3 Closed         2    195
## 4 Open           0    247
## 5 Open           1  34490
## 6 Semi           0     52
## 7 Semi           1  34685
```

`sf version < 1.0`

Sf 1.0+ uses spherical geometry (S2) on coordinates, `sf < 1.0` uses planar geometry (R2).

```
# test difference in S2 and R2 methods
sf_use_s2(FALSE)
```

Spherical geometry (s2) switched off

```
inter_closed_r2 <- lengths(st_intersects(scallop_sf, tenMinSqr_new, model = "closed"))
```

```
## although coordinates are longitude/latitude, st_intersects assumes that they are planar
## although coordinates are longitude/latitude, st_intersects assumes that they are planar
```

```
inter_open_r2 <- lengths(st_intersects(scallop_sf, tenMinSqr_new, model = "open"))
```

```
## although coordinates are longitude/latitude, st_intersects assumes that they are planar
## although coordinates are longitude/latitude, st_intersects assumes that they are planar
```

```
inter_semi_r2 <- lengths(st_intersects(scallop_sf, tenMinSqr_new, model = "semi-open"))
```

```
## although coordinates are longitude/latitude, st_intersects assumes that they are planar
## although coordinates are longitude/latitude, st_intersects assumes that they are planar
```

```
sf_use_s2(TRUE)
```

Spherical geometry (s2) switched on

```
bound_type_r2 <- tibble(Closed = inter_closed_r2,
                        Open = inter_open_r2,
                        Semi = inter_semi_r2)

pivot_longer(bound_type_r2, cols = c("Closed", "Open", "Semi"),
              names_to = "boundary_type", values_to = "Zones_assigned") %>%
  group_by(boundary_type) %>%
  count(Zones_assigned)
```

```
## # A tibble: 6 x 3
## # Groups:   boundary_type [3]
##   boundary_type Zones_assigned     n
##   <chr>          <int> <int>
## 1 Closed          1 33505
## 2 Closed          2 1232
## 3 Open            1 33505
## 4 Open            2 1232
## 5 Semi            1 33505
## 6 Semi            2 1232
```

Spatial join

Spatial joins will add additional rows if a point intersects more than one zone. If an inner join is used (`left = FALSE`), points that don't intersect zones are dropped.

```
scallop_sf_join <- st_join(scallop_sf,
                           tenMinSqr_new["MN10SQID"],
                           suffix = c(".x", ".y"),
                           left = TRUE)

scallop_sf_join <-
  scallop_sf_join %>%
  mutate(fs_join_match = ZoneID == MN10SQID.y,
         ne_join_match = MN10SQID.x == MN10SQID.y)

scallop_sf_join %>%
  st_set_geometry(NULL) %>%
  summarize(n_obs = n(),
           fs_join_match = sum(fs_join_match, na.rm = TRUE),
           ne_join_match = sum(ne_join_match, na.rm = TRUE),
           fs_ne_match = sum(fs_ne_match, na.rm = TRUE))
```

```
## # A tibble: 1 x 4
##   n_obs fs_join_match ne_join_match fs_ne_match
##   <int>   <int>       <int>       <int>
## 1 34932     34685       32599       32599
```

Spatial join adds 195 rows: one for each point that intersected two zones.

```
nrow(scallop_sf_join)
```

```
## [1] 34932
```

```
scallop_sf_join %>%
  st_set_geometry(NULL) %>%
  distinct(TRIPID) %>%
  nrow()
```

```
## [1] 34737
```

Table of matching zones by FishSET, NE, and spatial join approaches.

```
scallop_sf_join %>%
  st_set_geometry(NULL) %>%
  count(fs_ne_match, fs_join_match, ne_join_match)
```

```
## # A tibble: 4 x 4
##   fs_ne_match fs_join_match ne_join_match     n
##   <lgl>       <lgl>         <lgl>         <int>
## 1 FALSE      FALSE        FALSE          195
## 2 FALSE      TRUE         FALSE          2086
## 3 TRUE       TRUE         TRUE          32599
## 4 NA        NA           NA              52
```

All 195 of the cases from the first row of the table above (no shared zone assignments) are from points assigned to multiple zones. No approach handled this case in the same way.

```
dup_trip_id <- scallop_10_18$TRIPID[lengths(inter_save) > 1]

scallop_sf_join <-
  scallop_sf_join %>%
  mutate(dup_zone = TRIPID %in% dup_trip_id)

scallop_sf_join %>%
  st_set_geometry(NULL) %>%
  filter(!fs_ne_match & !fs_join_match & !ne_join_match) %>%
  summarize(dup_zone = sum(dup_zone))
```

```
## # A tibble: 1 x 1
##   dup_zone
##   <int>
## 1     195
```