



Started on	Saturday, 30 August 2025, 1:07 PM
State	Finished
Completed on	Saturday, 30 August 2025, 1:08 PM
Time taken	27 secs
Marks	1.00/1.00
Grade	10.00 out of 10.00 (100%)

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor $g[i]$, which is the minimum size of a cookie that the child will be content with; and each cookie j has a size $s[j]$. If $s[j] \geq g[i]$, we can assign the cookie j to the child i , and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

```
3
1 2 3
2
1 1
```

Output:

```
1
```

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

$1 \leq g.length \leq 3 \times 10^4$

$0 \leq s.length \leq 3 \times 10^4$

$1 \leq g[i], s[j] \leq 2^{31} - 1$

Answer: (penalty regime: 0 %)

```
1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int cmp(const void *a, const void *b) {
5      return (*(int *)a - *(int *)b);
6  }
7
8  int main() {
9      int n, m;
10     scanf("%d", &n);
11     int g[n];
12     for (int i = 0; i < n; i++) scanf("%d", &g[i]);
13     scanf("%d", &m);
14     int s[m];
15     for (int i = 0; i < m; i++) scanf("%d", &s[i]);
16
17     qsort(g, n, sizeof(int), cmp);
18     qsort(s, m, sizeof(int), cmp);
19
20     int i = 0, j = 0, count = 0;
21     while (i < n && j < m) {
22         if (s[j] >= g[i]) {
23             count++;
24             i++;
25             j++;
26         } else {
27             j++;
28         }
29     }
30
31     printf("%d\n", count);
32     return 0;
33 }
34
```

	Input	Expected	Got	
✓	2	2	2	✓
	1 2			
	3			
	1 2 3			

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)