

TAYNI: An AI-First Programming Language for Token-Efficient Code Generation

NELAIA Project
`contact@nelaia.ai`

June 2026

Abstract

We present TAYNI, a programming language designed from first principles for AI code generation. Unlike traditional languages optimized for human readability, TAYNI minimizes token consumption in Large Language Models (LLMs) while maintaining semantic clarity. Our compiler generates standalone executables without external dependencies, producing binaries as small as 640 bytes for minimal programs and 10.5KB for functional HTTP servers. We demonstrate a 64% reduction in token usage compared to equivalent Python code and binary sizes 100-500x smaller than Go or Rust equivalents. TAYNI introduces a capability-based security model enforced at compile time, deterministic execution semantics, and multi-target compilation (x86-64, ARM64, WebAssembly, WASI). We present benchmarks showing functional TCP/HTTP servers, verified WebAssembly conformance, and cross-platform execution. TAYNI represents a new paradigm in language design where the primary consumer is an AI system rather than a human programmer.

1 Introduction

The emergence of Large Language Models (LLMs) capable of generating code has fundamentally changed software development. Models like GPT-4, Claude, and Codex can produce functional programs from natural language descriptions. However, these models operate on *tokens*—subword units that determine both computational cost and context window limitations.

Current programming languages were designed for human programmers, optimizing for readability, expressiveness, and familiarity. This creates a mismatch when LLMs generate code:

- **Token inefficiency:** Verbose syntax consumes context window space
- **Ambiguous semantics:** Implicit behaviors require additional reasoning

- **External dependencies:** Generated code often requires runtime environments
- **Security risks:** LLM-generated code may contain vulnerabilities

We introduce TAYNI (Token-Aware Yet Naturally Intuitive), a programming language designed specifically for AI code generation. Our key contributions are:

1. A **token-efficient syntax** that reduces LLM token consumption by 64% compared to Python
2. A **zero-dependency compiler** that generates standalone executables without external libraries
3. A **capability-based security model** enforced at compile time
4. **Deterministic execution semantics** that eliminate undefined behavior
5. **Multi-target compilation** to native code, WebAssembly, and WASI

2 Design Principles

TAYNI’s design follows five core principles derived from the requirements of AI code generation:

2.1 Token Efficiency

Every syntactic element in TAYNI is chosen to minimize token count while preserving semantic clarity. We analyzed tokenization patterns across GPT-4, Claude, and open-source models to identify optimal keyword lengths and syntax structures.

Table 1: Token comparison for equivalent programs

Program	Python	TAYNI	Reduction
Hello World	12	4	67%
Fibonacci	45	18	60%
HTTP Server	156	52	67%
JSON Parser	234	89	62%
Average			64%

2.2 Regular Grammar

TAYNI uses a strictly regular grammar with five patterns:

1. `KEYWORD value` — Operations
2. `KEYWORD name = value` — Declarations
3. `KEYWORD condition { block }` — Control flow
4. `fn name(params) -> type { body }` — Functions
5. `cap capability` — Capability declarations

This regularity enables LLMs to generate syntactically correct code with higher probability.

2.3 Explicit Semantics

TAYNI eliminates implicit behaviors that require additional reasoning:

- No implicit type coercion
- No null/nil values (use explicit `opt<T>`)
- No exceptions (errors are values with `?>` operator)
- No global mutable state

2.4 Zero Dependencies

The TAYNI compiler generates standalone executables that require no run-time, standard library, or external dependencies. This is achieved through:

- Direct system call emission (no libc)
- Inline implementation of required functionality
- Static linking of all code

2.5 Capability-Based Security

Programs must declare required capabilities at the top of the file:

```
1 cap net:tcp      // TCP networking
2 cap fs:read      // File system read access
3 cap time         // Time operations
4
5 fn main() -> i32 {
6     // Code can only use declared capabilities
7 }
```

Listing 1: Capability declaration

The compiler enforces these declarations, preventing LLM-generated code from accessing undeclared resources.

3 Language Syntax

TAYNI supports two syntax variants:

3.1 v1.0 Syntax (Assembly-like)

Optimized for minimal token count:

```
1 LET x = 42
2 LET y = 10
3 ADD x y
4 PRT x
```

Listing 2: TAYNI v1.0 example

3.2 v1.5 Syntax (Modern)

Familiar syntax for complex programs:

```
1 cap net:http
2
3 fn handle_request(req: Request) -> Response {
4     let body = json_encode({"status": "ok"})
5     Response::new(200, body)
6 }
7
8 fn main() -> i32 {
9     http_server(8080, handle_request)
10 }
```

Listing 3: TAYNI v1.5 example

4 Compiler Architecture

The TAYNI compiler is implemented in Rust and follows a traditional pipeline:

1. **Lexer:** Tokenizes source into a stream of tokens
2. **Parser:** Builds an Abstract Syntax Tree (AST)
3. **IR Generation:** Converts AST to graph-based IR
4. **Capability Checking:** Verifies declared capabilities
5. **Code Generation:** Emits target-specific code

4.1 Intermediate Representation

TAYNI uses a graph-based IR where nodes represent operations and edges represent data flow:

```
1 enum Node {  
2     Literal { id, value, runtime },  
3     Operation { id, op, args, runtime },  
4     Control { id, kind, condition, body },  
5 }
```

Listing 4: IR node types

4.2 Code Generation Targets

The compiler supports multiple targets:

Table 2: Supported compilation targets

Target	Format	Status
Windows x86-64	PE	Verified
Linux x86-64	ELF	Verified
macOS x86-64	Mach-O	Implemented
WebAssembly	Wasm	Verified
WASI	Wasm+WASI	Verified
ARM64 Linux	ELF	Implemented

5 Implementation

5.1 PE Generation (Windows)

We generate minimal PE executables by:

- Overlapping headers where possible
- Using direct Windows API calls via Import Address Table
- Eliminating unused sections

Our smallest valid PE is 640 bytes; a functional HTTP server is 10.5KB.

5.2 ELF Generation (Linux)

Linux executables use direct syscalls without libc:

```
1 // sys_write(fd=1, buf, len)  
2 mov eax, 1 // syscall number  
3 mov edi, 1 // stdout
```

```

4 lea rsi, [msg] // buffer
5 mov edx, len  // length
6 syscall

```

Listing 5: Linux syscall emission

5.3 WebAssembly Generation

WASM modules are generated with:

- Minimal section structure
- WASI imports for system interaction
- Exported `_start` entry point

6 Evaluation

6.1 Binary Size Comparison

Table 3: HTTP server binary sizes

Language	Binary Size	vs TAYNI
TAYNI	10.5 KB	1x
C (musl static)	98 KB	9x
Zig	412 KB	39x
Rust	1.2 MB	114x
Go	5.8 MB	552x

6.2 Token Consumption

Using GPT-4’s tokenizer (tiktoken), we measured token counts for equivalent programs:

Table 4: Token consumption by language

Language	HTTP Server Tokens	Relative
TAYNI	52	1.0x
C	89	1.7x
Go	112	2.2x
Rust	134	2.6x
Python	156	3.0x

6.3 Functional Verification

All generated executables were tested for correctness:

Table 5: Functional test results

Test	Platform	Result
Hello World	Windows PE	Pass
TCP Server	Windows PE	Pass
HTTP Server	Windows PE	Pass
Hello World	Linux ELF	Pass
Wasm Conformance	Node.js	6/6 Pass
WASI Hello	Node.js WASI	Pass

7 Related Work

7.1 Domain-Specific Languages for AI

Prior work on AI-friendly languages includes:

- **Mojo** [?]: Python-like syntax with systems programming capabilities, but not designed for token efficiency
- **Triton** [?]: GPU kernel language, domain-specific rather than general-purpose

7.2 Minimal Binary Generation

Techniques for small executables:

- **Tiny ELF** [?]: Demonstrates minimal Linux executables
- **Crinkler** [?]: Compression for demoscene, not general-purpose

7.3 Capability-Based Security

TAYNI’s capability model draws from:

- **Capsicum** [?]: OS-level capability mode
- **WASI** [?]: WebAssembly capability-based security

8 Limitations and Future Work

Current limitations:

- Standard library is incomplete (crypto, TLS in progress)
- IDE tooling is basic (LSP implemented, debugger planned)
- Self-hosting compiler not yet complete

Future directions:

- GPU compute via LLVM backend
- Quantum computing target (QIR)
- Fine-tuned LLMs for TAYNI generation
- Formal verification of capability system

9 Conclusion

TAYNI demonstrates that programming languages can be designed with AI code generation as the primary use case. By optimizing for token efficiency, eliminating implicit behaviors, and enforcing capabilities at compile time, we enable LLMs to generate smaller, safer, and more predictable code.

Our benchmarks show 64% token reduction compared to Python and binary sizes 100-500x smaller than mainstream alternatives. The compiler produces verified, functional executables across multiple platforms.

As AI-generated code becomes increasingly prevalent, languages designed for this paradigm will become essential. TAYNI represents a first step toward this future.

Availability

TAYNI is open source under the MIT license:

<https://github.com/NELAIA-AI/tayni>

References

- [1] Lattner, C. et al. (2023). Mojo: A new programming language for AI developers. Modular Inc.
- [2] Tillet, P. et al. (2019). Triton: An intermediate language and compiler for tiled neural network computations. MAPL.
- [3] Abrash, M. (1996). Tiny ELF executables. Linux Journal.

- [4] Giesen, F. (2005). Crinkler: Executable file compressor. Demoscene.
- [5] Watson, R. et al. (2010). Capsicum: Practical capabilities for UNIX. USENIX Security.
- [6] Clark, L. et al. (2019). Standardizing WASI: A system interface to run WebAssembly outside the web. W3C.