

# Numerical Relation Extraction with Minimal Supervision

Indian Institute of Technology Bombay

June 2015

# Outline


- 1 Introduction
- 2 Problem Statement
- 3 Relation Extraction as a Machine Learning Problem
- 4 Peculiarities of Numerical Relation Extraction
- 5 NumberRule: Rule Based Relation Extraction
- 6 NumberTron: Probabilistic Relation Extraction

# Introduction

# Entities have Numerical Attributes



# Entities have Numerical Attributes



- For popular entities, finding complete knowledge bases is possible.

# Entities and Numerical Attributes

- For popular entities, finding complete knowledge bases is possible.
- [data.worldbank.org](http://data.worldbank.org), Wikipedia infoboxes, freebase ...

# Entities and Numerical Attributes

- For popular entities, finding complete knowledge bases is possible.
- [data.worldbank.org](http://data.worldbank.org), Wikipedia infoboxes, freebase ...
- What about less popular entities?



# Entities and Numerical Attributes

- For popular entities, finding complete knowledge bases is possible.
- [data.worldbank.org](http://data.worldbank.org), Wikipedia infoboxes, freebase ...
- What about less popular entities?
  - What is the population of Arbit Apartments, Powai?

# Entities and Numerical Attributes

- For popular entities, finding complete knowledge bases is possible.
- [data.worldbank.org](http://data.worldbank.org), Wikipedia infoboxes, freebase ...
- What about less popular entities?
  - What is the population of Arbit Apartments, Powai?
  - What is the GDP of Sugarcane Industry of India?

# Entities and Numerical Attributes

- For popular entities, finding complete knowledge bases is possible.
- [data.worldbank.org](http://data.worldbank.org), Wikipedia infoboxes, freebase ...
- What about less popular entities?
  - What is the population of Arbit Apartments, Powai?
  - What is the GDP of Sugarcane Industry of India?
  - Percent of Internet users in Mumbai?

# Motivation

Activities Google Chrome Mon Oct 20, 7:42 PM en2

internet users in india x

https://www.google.co.in/search?q=internet+users+in+india&oq=internet+use&aqs=chrome..69i59lj69i57.1830j0j1&sourceid=chrome&es\_sm=93&ie=UTF-8#q=ir

Maths ML dev awesome sgmp pblog Ganglia: YH Grid R YH cs215 Nucleus tml stats ML/DS Reading NLP shortcuts Other bookmarks

Google internet users in india

Web News Images Maps Videos More Search tools

About 2,49,00,000 results (0.23 seconds)

### 15.1% of the population (2013)

India, Internet users

Year	Percentage of Internet Users
1990	0.0%
1995	0.0%
2000	0.5%
2005	2.0%
2010	5.0%
2013	15.1%

Explore more

Sources include: World Bank

Feedback

## India

Country

India, officially the Republic of India, is a country in South Asia. It is the seventh-largest country by area, the second-most populous country with over 1.2 billion people, and the most populous democracy in the world.

[Wikipedia](#)

### Related statistics

Population	1.252 billion (2013)
Life expectancy	66.21 years (2012)

# Motivation

The screenshot shows a Google Chrome browser window with the address bar displaying a search URL for 'internet users in mumbai'. The search results page shows approximately 26,700,000 results in 0.41 seconds. The top result is 'Global Internet Users - Internet Penetration by Country' from www.internetsociety.org. Below it, a snippet from timesofindia.indiatimes.com states 'Mumbai has most number of internet users: IAMAI data - Th...'. Another snippet from archive.indianexpress.com mentions 'Internet penetration in India: Mumbai tops Internet users list ...'. A snippet from tech.firstpost.com states 'With 12 million Internet users, Mumbai tops list of connected...'. The bottom snippet from tech.firstpost.com states 'Mumbai has the most number of Internet users in India ...'.

Activities Google Chrome Mon Oct 20, 7:37 PM en2

internet users in mumbai

https://www.google.co.in/search?q=internet+users+in+india&oq=internet+use&aqs=chrome..69i59l2j69i57.1830j0j1&sourceid=chrome&es\_sm=93&ie=UTF-8#q=ir

Maths ML dev awesome sgmp pblog Ganglia: YH Grid R YH cs215 Nucleus tml stats ML/DS Reading NLP shortcuts Other bookmarks

Google internet users in mumbai

Web Images News Maps Videos More Search tools

About 26,70,000 results (0.41 seconds)

**Global Internet Users - Internet Penetration by Country** ⓘ  
www.internetsociety.org/Internet-Users  
View the Map & Download the Report  
Download the Report - Introducing the Report - Executive Summary

**Mumbai has most number of internet users: IAMAI data - Th...**  
timesofindia.indiatimes.com > Tech  
Nov 7, 2013 - At 12 million, Mumbai has more internet users than any other city in the country, according to data released by the Internet And Mobile ...

**Internet penetration in India: Mumbai tops Internet users list ...**  
archive.indianexpress.com/.../internet...mumbai...internet-users.../119189...  
Nov 7, 2013 - With 12 million active internet users, Mumbai has emerged as the city with the highest number of internet users in the country, followed by Delhi ...

**With 12 million Internet users, Mumbai tops list of connected...**  
tech.firstpost.com/.../with-12-million-internet-users-mumbai-tops-list-of-...  
Nov 8, 2013 - India's economic capital, Mumbai, has emerged to be the city with the highest number of Internet users in India, ahead of cities like New Delhi ...

**Mumbai has the most number of Internet users in India ...**  
tech.firstpost.com/.../mumbai-has-the-most-number-of-internet-users-in-...

# Motivation

- Web is huge.

---

<sup>1</sup>More on this in the coming slides

# Motivation

- Web is huge.
- Probably, there is some page which contains the information we are looking for.

---

<sup>1</sup>More on this in the coming slides

# Motivation

- Web is huge.
- Probably, there is some page which contains the information we are looking for.
- The way in which you express a fact about an entity depends on the fact, and not the entity.

---

<sup>1</sup>More on this in the coming slides



# Motivation

- Web is huge.
- Probably, there is some page which contains the information we are looking for.
- The way in which you express a fact about an entity depends on the fact, and not the entity.
- We may expect **the sentence structure**<sup>1</sup> to be similar.

---

<sup>1</sup>More on this in the coming slides

# Motivation

- Web is huge.
- Probably, there is some page which contains the information we are looking for.
- The way in which you express a fact about an entity depends on the fact, and not the entity.
- We may expect **the sentence structure**<sup>1</sup> to be similar.
  - Population of India reached 1.3 billion, making it the second largest country in the world.

---

<sup>1</sup>More on this in the coming slides

# Motivation

- Web is huge.
- Probably, there is some page which contains the information we are looking for.
- The way in which you express a fact about an entity depends on the fact, and not the entity.
- We may expect **the sentence structure**<sup>1</sup> to be similar.
  - Population of India reached 1.3 billion, making it the second largest country in the world.
  - Population of Arbit Apartments, Powai reached 1300.

---

<sup>1</sup>More on this in the coming slides

## Problem Statement

# Problem Statement

- Given that we know a lot of facts about some entities, can we train extractors that run over the web and pull similar facts about other entities?

# Problem Statement

- The knowledge is scattered in unstructured text on the Web.

590.56 million people in China were using the internet at mid-2013, an increase of nearly 53 million (or 9.85%) from a year earlier.

The land area of the [contiguous United States](#) is 2,959,064 square miles (7,663,941 km<sup>2</sup>). Alaska, separated from the contiguous United States by Canada, is the largest state at 663,268 square miles (1,717,856 km<sup>2</sup>). Hawaii, occupying an archipelago in the central [Pacific](#), southwest of North America, is 10,931 square miles (28,311 km<sup>2</sup>) in area.<sup>[136]</sup>

- Can such facts be extracted automatically?

# Problem Statement

- Formally, train extractors that can harness the Web for numerical relations, where relations are 3-tuples linking an entity to a number
  - (India, **economy**, 1.842 trillion USD)
  - (China, **internet users**, 590.56 million)
  - (USA, **land area**, 2,959,054 square mile)

## Relation Extraction as a Machine Learning Problem



# Relation Extraction as a Machine Learning Problem

- **Structure** and **content** of sentences expressing the same relations can be *expected* to be similar.
  - The population of Australia is estimated to be 23,622,400 as of 7 October 2014.
  - According to an official estimate for 1 June 2014, the population of Russia is 143,800,000.

# Relation Extraction as a Machine Learning Problem


- **Structure** and **content** of sentences expressing the same relations can be *expected* to be similar.
  - At 17,075,400 square kilometres, Russia is the largest country in the world.
  - With an area of 504,030  $km^2$ , Spain is the second largest country in Western Europe.

# Relation Extraction as a Machine Learning Problem

- Redundancy in grammatical features and dependencies of the sentences expressing same relation.

# Relation Extraction as a Machine Learning Problem


- Redundancy in grammatical features and dependencies of the sentences expressing same relation.




# Relation Extraction as a Machine Learning Problem

- Redundancy in grammatical features and dependencies of the sentences expressing same relation.

At 17,075,400 square kilometres, Russia is the largest country in the world.



With an area of 504,030 km<sup>2</sup>, Spain is the second largest country in Western Europe.



# Possible Workflow

# Possible Workflow

- 1: **Collect enough examples** for each relation so that there are sufficient patterns and enough redundancy to exploit.
- 2:
- 3: **Extract features** (important keywords, grammatical structure, parse trees, etc.) for these sentences.
- 4:
- 5: **Train** a multi-class classifier on this training data.
- 6:
- 7: **for** sentence  $s \in \text{Corpus}$  **do**
- 8:     **Extract** features for  $s$ .
- 9:     **Predict** the relation using the model for these features.
- 10:    **Store** the fact into a database.

# Challenge

- Large Corpus ( $\sim 16$  million sentences), hand labeling is out of question



# Challenge

- Large Corpus ( $\sim 16$  million sentences), hand labeling is out of question
- Need lots of training data to learn high quality extractors

# Challenge

- Large Corpus ( $\sim 16$  million sentences), hand labeling is out of question
- Need lots of training data to learn high quality extractors
- Is there a middle ground?




---

## Peculiarities of Numerical Relation Extraction

# Peculiarities of Numerical Relation Extraction

Numbers are weak entities

- Quantities can appear in far more contexts than typical entities. ("Bill Gates", "Microsoft") vs. ("11", "Microsoft")
- Regular IE have fewer cases of entity disambiguation as compared to numerical IE



# Peculiarities of Numerical Relation Extraction

Numbers are weak entities

- Noise is more for the small whole numbers that are unitless or with popular units (e.g, percent)
- 1 or 5% vs. 11.42145 or 330 m/sec

Number	Frequency (Avg. 57.84)
3	85333
20	86359
2	91608
1	100014
10	100780

# Peculiarities of Numerical Relation Extraction

## Units

- Unit acts as types for numbers.
- Same quantity may be expressed with different unit
  - 20 kms or 12.4 miles
- Unit extractor needs to perform unit conversions for effective matching and extraction

# Peculiarities of Numerical Relation Extraction

## Delta Words

- Not uncommon to find sentences expressing change in the value of a relation (instead of, or in addition to, the actual value).
  - Amazon stock price *increased by* \$35 to close at \$510.
  - India's tiger population sees 30% *increase*.
  - Ford poised to raise dividend by 20% even as profit declines.



# Peculiarities of Numerical Relation Extraction

## Relation/Argument Scoping

- Additional modifiers to arguments or relation words may subtly change the meaning and confuse the extractor.
  - *rural* literacy rate of India
  - literacy rate of *rural* India

# Peculiarities of Numerical Relation Extraction

## Keywords


- Many numerical relations are described using one or a handful of keywords.
  - For example, sentences expressing *inflation rate*, *GDP*, *life expectancy* would often use these keywords.

## NumberRule: Rule Based Relation Extraction

# Rule Based IE

Academia vs. Industry

## Implementations of Entity Extraction




# NumberRule

## Motivation

### From [BM05]

If  $e_1$  and  $e_2$  are two entities mentioned in the same sentence such that they are observed to be in a relationship  $R$ , our hypothesis stipulates that the contribution of the sentence dependency graph to establishing the relationship  $R(e_1, e_2)$  is almost exclusively concentrated in the shortest path between  $e_1$  and  $e_2$  in the undirected version of the dependency graph.



### From [BM05]

If  $e_1$  **and**  $e_2$  are two entities mentioned in the same sentence such that they are observed to be in a **relationship R**, our hypothesis stipulates that the contribution of the sentence **dependency graph** to establishing the relationship  $R(e_1, e_2)$  is almost **exclusively concentrated in the shortest path** between  $e_1$  and  $e_2$  in the undirected version of the dependency graph.

- When looking for clues for relation extraction, dependency path is a good place to start.
- In the case of Numerical Relations, we already know what to look for: *keywords*.
- Need to take care of modifications to the entities, delta words

# NumberRule

## Definitions

- **Keywords** Words that might help in identifying relations. (*GDP, internet, inflation*)
- **Delta words** Words that indicate that the mention expresses a change, and not the actual relation.  
(*change, up, down, increased, changed, risen*)
- **Modifiers** A word  $m$  is said to be a modifier of the word  $w$  if there is a modifying dependency from  $m$  to  $w$ .  
(*blue* modifies *whale* in **blue** *whale*, **urban** *population*).
- **Augmented Phrase** For a word  $W$ , the *Augmented Phrase*  $W'$  is formed by concatenating  $W$  with words  $P$  such that  $W$  and  $P$  are related via a *modifying dependency*.  
(for the word *whale*, **blue whale** is the augmented phrase)

# NumberRule I

## Extraction Algorithm

- 1: Given a sentence  $S$ , let  $E_S$  be the set of entities and  $N_S$  be the set of numbers that are present in the sentence.
- 2: Let  $R$  be the set of relations
- 3: Let  $LegalUnits(r)$  be the set of possible units for a relation  $r$  in  $R$
- 4: Let  $Unit(n)$  be the unit for a given number  $n$  as returned by the unit tagger.
- 5: Let  $K$  be the set of keywords
- 6: Let  $\Delta$  be the set of delta words
- 7: **for**  $(e, n) \in (E_S \times N_S)$  **do** //For all entity-number pairs
- 8:      $P \leftarrow$  the set of words in the dependency path between  $e$  and  $n$
- 9:     **for**  $r \in R$  **do**
- 10:         **if**  $P \cap K_r = \emptyset$  **then** //keyword is not present
- 11:             continue;



# NumberRule II

## Extraction Algorithm

- 12:       **if**  $P \cap \Delta \neq \emptyset$  **then** //delta words are present
- 13:       continue;
- 14:       **if**  $Unit(n) \notin LegalUnits(r)$  **then** //incompatible units?
- 15:       continue;
- 16:       Extract  $r(e', r', n)$ , where  $e'$  and  $r'$  are the augmented entity  
and relation phrases.

# NumberRule

## NumberRule: Extractions

- “The estimated population for 2014 of the Australian continent is about 36.25 million people”

- Australian  $\xrightarrow{amod}$  continent  $\xrightarrow{prep\_of}$  2014  
 $\xrightarrow{prep\_for}$  population  $\xrightarrow{nsubj}$  people  $\xrightarrow{num}$  million  $\xrightarrow{number}$  36.25

- “The estimated population for 2014 of the Australian continent increased by about 3.25 million people”

- Australian  $\xrightarrow{amod}$  continent  $\xrightarrow{prep\_of}$  2014  $\xrightarrow{prep\_for}$  population  $\xrightarrow{nsubj}$   
increased  $\xrightarrow{prep\_by}$  people  $\xrightarrow{num}$  million  $\xrightarrow{number}$  36.25

Sentence	Test
<i>The estimated population of Australia is about 36.25 million people.</i>	-
<i>The estimated population density of Australia is 36.25 million people <b>per sq km</b>.</i>	Incompatible Units
<i>The estimated population of Australia <b>increased</b> by about 36.25 million people.</i>	Delta Word Present
<i>The estimated population of <b>urban</b> Australia is about 36.25 million people.</i>	Entity is Modified
<i>The estimated <b>adolescent</b> population of Australia is about 36.25 million.</i>	Entity is Modified
<i>The estimated populations in 2014 are Australia, <b>100 million</b> and New Zealand, 36.25 million.</i>	100 million is closest to Australia

**Table :** NumberRule outputs (Australia, Total Population, 36.25 million) only in the first sentence. The second column is test number that fails for other sentences. The input keyword is “population”.

## NumberTron: Probabilistic Relation Extraction

For an entity  $e$  (India)


- Let  $S_e$  be the set of sentences that express the entity  $e$ .
- Let  $Q_e$  denote the distinct numbers with unit that appear in  $S_e$ <sup>3</sup>
- $\forall q \in Q_e$ , let  $S_{e,q} \subseteq S_e$  denote the sentences that mention  $e$  and  $q$ .

---

<sup>3</sup>We use the unit tagger by [SC14] to identify units of numbers in the text and to convert all unit variants like "mile", "km" to a canonical SI unit, "meter".

# NumberTron

## Graphical Model




For  $e = (\text{China})$

- $S_{china} = \{(i).. \text{China says that annual inflation...to 4.3 percent, (ii)...China would initiate ... that its inflation rate ... 4.3 percent in October, (iii)...the number of chinese internet users has grown to 840 million...}\}$
- $Q_{china} = \{4.3 \text{ percent, } 8400000000\}$
- $S_{china,4.3percent} = \{(i), (ii)\}$
- $S_{china,8400000000} = \{(iii)\}$

For  $e = (\text{China})$

- $S_{china} = \{(i), (ii), (iii)\}$
- $Q_{china} = \{4.3 \%, 840000000\}$
- $S_{china, 4.3\%} = \{(i), (ii)\}$
- $S_{china, 840000000} = \{(iii)\}$





For each entity  $e$ , for each number  $n_q$

- $n_r^q$ , **number nodes** Binary, 1 if the number  $q$  is related to  $e$  via relation  $r$ .

For each mention,  $s \in S_{e,q}$

- $z_s$ , **mention nodes** multi-ary, can take values  $r \in \mathcal{R} = (R \cup \perp)$ , set to  $r \in R$  if the sentence expresses any of the  $R$  relations, else set to  $z_s = \perp$ .

- **Mintz Features** Lexical and Syntactic features derived from POS tags and dependency path [MBSJ09]
- **Keyword Features** Derived from a pre-specified list of keywords per relation.
- **Number Features** Capture Information on the magnitude, type (whole, fraction) can also be useful for relation extraction.

*Afghanistan , which is mostly rural , has one of the lowest life expectancy rate in the world at 44 year for both man and woman.*

# NumberTron

## Features

Feature type	Features
Fixed Keywords	key: life key: expect
All Keywords	key: life key: expect key: world
Number Features	Num: Billion Num: Integer

*Afghanistan , which is mostly rural , has one of the lowest life expectancy rate in the world at 44 year for both man and woman. The time “44 year” is converted to the SI unit, which comes out to be around 1.3 billion and thus the feature Num: Billion is fired.*

# NumberTron

## Features

- *inverse\_false|LOCATION|\*LONG\*|DURATION*, There is a long dependency path between the two entities, one of which is a location and other duration
- *inverse\_false|B\_-2 B\_-1|LOCATION|\*LONG\*|DURATION|year for*, Same as above, but now with windows of text around entities of interest
- *str:rural[rcmod]— > |LOCATION|[nsubj]— >have[root]< —at[prep]< —year[pobj]< —|DURATION* , The typed dependency path
- *dir:— > |LOCATION|— >< — < — < —|DURATION* , Direction of dependencies

*Afghanistan , which is mostly rural , has one of the lowest life expectancy rate in the world at 44 year for both man and woman.*

# NumberTron Training


## Perceptron

- The classical perceptron forms the core of our training procedure.

$$\theta \leftarrow \theta + \eta * (t_i - o_i) * x_i \quad (1)$$


$$\boxed{\theta} \leftarrow \boxed{\theta} + \eta * (\boxed{t_i} - \boxed{o_i}) * \boxed{x_i} \quad (2)$$

- Weights
- True Label
- Observed Label
- Feature (Binary)




# NumberTron Training

True Labels: Distant Supervision




# NumberTron Training

True Labels: Distant Supervision



# NumberTron Training


True Labels: Distant Supervision






# NumberTron Training

True Labels: Distant Supervision




# NumberTron Training

Observed Labels: Full Inference




# NumberTron Training

Observed Labels: Full Inference




# NumberTron Training

Observed Labels: Full Inference



# NumberTron Training

Observed Labels: Full Inference



# NumberTron Training

## Updating Feature Weights

- Let  $f_1, f_2, \dots, f_k$  be the features fired for *Hungarian inflation accelerate to 3.8 percent in May, defying...Thursday*.
- Examples: **key: inflation, Num: Units** and so on.
- $\theta_{f_i}^{INT} \leftarrow \theta_{f_i}^{INT} - 1$
- $\theta_{f_i}^{INF} \leftarrow \theta_{f_i}^{INF} + 1$
- These features actually indicate inflation relation, and not the internet relation!

- **Sentence Level Extractions**

- Given a sentence  $S$ , let  $E$  be the set of entities and  $Q$  be the set of numbers that are present in the sentence.
- We then calculate a score( $r, e, q$ ) for a  $e \in E$  and  $q \in Q$  for being tagged  $r$  as  $\theta_q^r \phi_q(n_q = 1) + \theta_s \phi_s(r)$  where  $\phi_s$  captures the features in sentence  $S$  tied to entity  $e$  and number  $q$ .
- For each  $(e, q)$  we assign a label  $r$  if the min-max normalized score is greater than some threshold  $\alpha$ .
- We use a cross validation set to obtain the  $\alpha = 0.90$ .

## Results



- Tac KBP 2014 corpus comprising roughly 3 million documents from NewsWire, discussion forums, and the Web.
- Knowledge base is compiled from [data.worldbank.org](http://data.worldbank.org)
  - Dataset contains 1,281 numeric indicators for 249 countries, with over 4 million base facts.
  - Dataset is normalized by converting all the values to their SI base unit value.

# Experiments

## Test Set

- Mix of 430 sentences from TAC corpus and sentences from Web search on relation name.

Relation	Units	Positive	Negative
Land Area	Sq. Km	57	17
Population	-	51	300
Inflation	percent	51	84
Internet Users	percent	15	
FDI	\$ (USD)	10	35
GDP	\$ (USD)	8	
Goods Export	\$ (USD)	11	
Life Expectancy	year	15	34
Electricity Production	kWh	13	6
CO <sub>2</sub> Emissions	kiloton	8	16

**Table :** Test corpus statistics: The third column is the number of instances per relation and the fourth column is the number of "none-on-the-above" ( $\perp$ ) grouped by relation of the same unit.

- **Recall –Prior Baseline:** For each unit, predict the relation with the highest *test* prior ignoring the "none-of-the-above" class.
  - All the numbers with the unit "USD" will be labeled 'Goods Exported' since it is most frequent class ignoring the "none-of-the-above" class.

- **Recall –Prior Baseline:** For each unit, predict the relation with the highest *test* prior ignoring the "none-of-the-above" class.
  - All the numbers with the unit "USD" will be labeled 'Goods Exported' since it is most frequent class ignoring the "none-of-the-above" class.
- **MultiR ++ : Adapting MultiR for Numerical Relations**
  - Added unit tagger as in our algorithms for identifying and normalizing numbers and units.
  - Added our partial matching (using  $\pm\delta_r\%$ ) technique in distant supervision.

# Results

## Numbertron vs NumberRule vs Baselines

System	Precision	Recall	F1 Score
MultiR++	31.81	28.10	29.84
Recall-Prior	28.18	86.19	42.47
NumberRule	59.30	53.60	56.30
NumberTron	60.93	66.92	63.78

**Table :** Aggregate results. NumberTron outperforms all other methods.

- Statistical method like NumberTron outperforms NumberRule on increased recall, which jumps from 53.6% to 67
- MultiR++ performs poorly because it does not model peculiarities of numerical relations.

- NumberRule's missed recall is primarily because of not having a keyword on the dependency path.
  - *" Turkey's central bank said Wednesday it expects the annual inflation rate to reach 6.09 percent at the end of 2009 , lower than the official target of 7.5 percent."*
  - Turkey  $\xrightarrow[\text{num}]{\text{poss}}$  bank  $\xrightarrow{\text{nsbj}}$  said  $\xrightarrow{\text{ccomp}}$  expects  $\xrightarrow{\text{xcomp}}$  reach  $\xrightarrow{\text{dobj}}$  percent  
 $\xrightarrow{\text{num}}$  6.09
  - Since keyword 'inflation' is not on the shortest dependency path between Turkey and 6.09, NumberRule does not extract.
  - Since NumberTron combines evidences from multiple features such as number's range, presence of 'inflation' in context and dependency path features.

# Ablation tests

of various configurations of NumberTron

Distant Supervision	Simple OR			Atleast-K			Agreeing-K		
	P	R	F1	P	R	F1	P	R	F1
KB	43.24	50.93	46.54	40.05	53.93	45.97	35.20	44.52	39.35
Keywords	43.35	73.22	54.46	43.69	73.62	54.83	45.97	70.80	55.74
KB + Keywords	61.56	64.96	63.21	60.93	66.92	63.78	63.46	60.21	61.79

Table : Comparison of various configurations for NumberTron

- Keywords are crucial and KB in conjunction with keyword-based labeling adds significant value.

# Ablation tests

of feature templates for NumberTron

Features	Precision	Recall	F1-score
Mintz features only	22.85	36.86	28.21
Keyword features only	51.24	52.55	51.89
Mintz + Keyword	47.10	39.04	42.71
Mintz + Number	17.80	35.03	23.67
Keyword + Number	45.15	69.70	54.80
Mintz + Keyword + Number	<i>60.93</i>	<i>66.92</i>	<i>63.78</i>

Table : Ablation tests of feature templates for NumberTron

- Large set of Mintz features confuses the classifier; Keyword features are much effective in learning.



# Results

## NumberTron vs NumberRule

Relation	NumberTron F1	NumberRule F1
FDI	0	50.00
Life Expectancy	68.96	69.50
Internet Users	55.73	54.54
Electricity Prod.	50.00	62.50
GDP	57.14	42.80
CO <sub>2</sub> Emissions	47.61	53.30
Inflation	88.40	56.25
Goods export	75.00	35.20
Population	49.99	60.30
Land Area	57.44	52.22

**Table :** Per relation F1 scores for NumberRule and best configuration of NumberTron

# Analysis

per relation analysis of NumberTron vs NumberRule

- For FDI relation, NumberTron does not make a extraction because in our corpus sentence expressing the relation are rare.
- Inflation and Population are well represented in training corpus and hence higher recall.

## Summary

- Numerical relation extraction has several peculiarities, more challenging than standard IE.
- **NumberRule**, a rule based system that can extract any numerical relation given input keywords for that relation.
- **NumberTron**, a probabilistic graphical model, that employs novel task-specific features and can be trained via distant supervision or other heuristic labelings.
- NumberTron aggregates evidence from multiple features and produces higher recall at a precision comparable to NumberRule.
- Both systems vastly outperform baselines and non-numeric IE systems, with NumberTron yielding over 33 point F-score improvement.

# Summary

## NumberTron vs NumberRule

	<b>NumberRule</b>	<b>NumberTron</b>
<b>Idea</b>	Use dep path between the number and the entity in the mention	A Graphical Model with Perceptron like training algorithm
<b>Supervision</b>	Relation specific keywords.	Relation specific keywords + Numerical knowledge base.
<b>Handling False +ves</b>	Look for relation specific keywords in the dep path.	Keyword features.
<b>Handling Mentions Expressing Change</b>	No extraction if a delta word exists on the dep path.	Remove sentences having delta words on the dep path

# Summary

## NumberTron vs NumberRule

<b>Use of Unit Tagger</b>	Used to test compatibility of a relation and the number.	Used for training data creation and flattening to SI units.
<b>Common Number Pruning</b>	N/A	Features included to capture type (whole, fraction), magnitude and frequency.
<b>Modified Relations</b>	Handled by attaching words related via modifying dependencies, <i>urban</i> population.	Not handled in the model, can be handled at the time of extraction using a similar scheme.
<b>Results</b>	P = 59.30, R = 53.60, F-Score = 56.30	P = 60.93, R = 66.92, F-Score = 63.78



Razvan C. Bunescu and Raymond J. Mooney.

A shortest path dependency kernel for relation extraction.

In *HLT/EMNLP 2005, Human Language Technology Conference and Conference on Empirical Methods in Natural Language Processing, Proceedings of the Conference, 6-8 October 2005, Vancouver, British Columbia, Canada, 2005*.



Laura Chiticariu, Yunyao Li, and Frederick R Reiss.

Rule-based information extraction is dead! long live rule-based information extraction systems!

In *EMNLP*, pages 827–832, 2013.

# References II



Mike Mintz, Steven Bills, Rion Snow, and Daniel Jurafsky.  
Distant supervision for relation extraction without labeled data.  
*In ACL 2009, Proceedings of the 47th Annual Meeting of the Association for Computational Linguistics and the 4th International Joint Conference on Natural Language Processing of the AFNLP, 2-7 August 2009, Singapore, pages 1003–1011, 2009.*



Sunita Sarawagi and Soumen Chakrabarti.  
Open-domain quantity queries on web tables: annotation, response, and consensus models.  
*In The 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, KDD '14, New York, NY, USA - August 24 - 27, 2014, pages 711–720, 2014.*