# Neuro-Symbolic Orchestration for Safe Autonomous NetOps Using LLMs and Fuzzy Control

Benjamin Grando Moreira
*Research Director*
*Universidade Federal de Santa Catarina (UFSC)*
Joinville, Brazil
benjamin.grando@ufsc.br

Maria Clara Seixa Scheffel
*Department of Electrical and Computer Engineering*
*Universidade Federal de Santa Catarina (UFSC)*
Joinville, Brazil
maria.c.s@grad.ufsc.br

***Abstract*—The rapid integration of Large Language Models (LLMs) into autonomous Network Operations (NetOps) introduces powerful diagnostic capabilities alongside critical operational risks, such as tactical hallucinations and uncalibrated interventions. This paper proposes a closed-loop Neuro-Symbolic orchestration architecture that couples a localized generative agent (`LLaMA 3.2:1b`) with a deterministic Mamdani Fuzzy Inference System (FIS). The fuzzy controller evaluates real-time physical telemetry (RX utilization, CRC errors) and logical topology state (BGP alerts) against the LLM's self-assessed Action Impact ($I$). Benchmarked across a 600-event multi-layer fault injection dataset, the proposed architecture achieves calibrated decision boundaries—approving 41.7% of benign actions, routing 55.3% of ambiguous events to Human-in-the-Loop supervision, and deterministically blocking 100% of invalid software interventions during physical hardware degradation—outperforming classic static, machine learning, and pure fuzzy baselines.**

***Index Terms*—Autonomous NetOps, Large Language Models, Neuro-Symbolic AI, Fuzzy Logic Control, Network Reliability.**

## I. Introduction

Recent advances in Large Language Models (LLMs) have opened new possibilities for autonomous network management by enabling semantic interpretation of heterogeneous network information, including configuration data, telemetry, logs, and operational intents [1]. This capability has motivated the use of LLMs in several networking tasks, such as network slicing, zero-touch configuration, intent-based management, and network optimization. In particular, recent studies have demonstrated that LLM-based systems can move beyond conventional automation pipelines by translating high-level network objectives into operational decisions and optimization procedures.

A further evolution of this paradigm is represented by agentic and multi-agent architectures. Instead of relying on a single monolithic LLM, specialized agents can collaboratively perform tasks such as planning, network analysis, optimization, and execution. LaMA-SON, for example, proposes role-specialized LLM agents for traffic management, QoS optimization, and security in self-organizing networks [5]. Similarly, ComAgent employs specialized agents for knowledge acquisition, planning, coding, and solution evaluation within an iterative perception–planning–action–reflection loop [6]. These approaches demonstrate the potential of agentic AI to improve the adaptability and autonomy of future network management systems.

However, increasing the autonomy of LLM-based network management also introduces a fundamental safety challenge. An LLM may generate a syntactically valid configuration or mitigation procedure whose operational consequences are inappropriate for the current network state. This problem is particularly critical in NetOps, where actions such as interface shutdowns, routing changes, or BGP reconfigurations can directly affect service availability. Network telemetry provides the necessary operational context for observing network state [3], but observation alone does not establish whether a proposed intervention should be executed. Consequently, an autonomous NetOps architecture requires a mechanism capable of separating semantic reasoning from the authorization of potentially disruptive actions.

Recent research on LLM-agent safety has explored this problem through external guardrails and formal verification. GuardAgent introduces a dedicated agent that analyzes the behavior of a target LLM agent and generates executable guardrail code from safety requirements [7]. VeriGuard extends this direction by generating behavioral policies and formally verifying them before deploying the resulting policy as a runtime monitor for agent actions [8]. Although these approaches demonstrate the importance of an independent safety layer, they are not specifically designed around the heterogeneous physical and logical state of computer networks.

In this work, we address this gap by introducing a neuro-symbolic orchestration architecture for autonomous NetOps that combines the semantic reasoning capability of a localized LLM with the deterministic decision boundaries of a Mamdani Fuzzy Inference System (FIS) [2]. The proposed approach uses real-time physical and logical network telemetry to evaluate the operational impact of an LLM-generated mitigation before execution. Rather than allowing the generative model to directly control the network, the fuzzy layer acts as a non-bypassable safety boundary that can approve benign actions, escalate ambiguous situations to Human-in-the-Loop (HitL) supervision, or block potentially unsafe interventions. This design therefore combines the contextual flexibility of LLM-based reasoning with the interpretability and deterministic behavior of symbolic control, providing a practical foundation

for safer autonomous network operations.

## II. Related Work

The application of Large Language Models (LLMs) to network management has recently emerged as a promising approach for automating tasks that traditionally require expert intervention. Existing studies have investigated LLMs for network configuration, troubleshooting, intent interpretation, and optimization, highlighting their ability to reason over heterogeneous network information and translate high-level intents into operational actions [1]. However, LLM-based network automation remains constrained by the stochastic nature of generative models, particularly when generated actions can directly affect production infrastructure. Network telemetry is therefore essential for providing the operational context required for reliable decision making. Telemetry frameworks provide continuous visibility into network state, performance, and failures, but do not inherently determine whether an LLM-generated intervention is safe to execute [3].

Before the emergence of LLM-based approaches, intelligent network control commonly relied on deterministic or rule-based methods. Fuzzy logic is particularly suitable for decision making under uncertainty, since linguistic variables and expert-defined rules can combine heterogeneous and imprecise inputs. The Mamdani inference model established a widely used formulation for fuzzy control systems [2]. Fuzzy controllers have subsequently been applied to routing and network management, where multiple parameters such as energy, distance, hop count, bandwidth, and congestion are combined to determine routing decisions [4]. These approaches provide deterministic and interpretable decision boundaries, but their rules are manually engineered and lack the semantic reasoning required to assess the operational impact of actions generated from natural-language objectives.

More recent work has combined LLMs with agentic architectures for network operations. LaMA-SON employs role-specialized LLM agents for traffic management, QoS optimization, and security, enabling collaborative and decentralized reasoning in self-organizing networks [5]. Similarly, ComAgent decomposes wireless-network optimization into specialized agents for retrieval, planning, coding, and solution evaluation, using iterative feedback to improve generated solutions [6]. Although these approaches demonstrate the potential of agentic reasoning for networking, they primarily focus on task completion and optimization rather than enforcing a deterministic safety boundary between semantic reasoning and network execution.

Safety mechanisms for LLM agents have consequently received increasing attention. GuardAgent uses a separate agent to interpret safety requirements and generate executable guardrails for monitoring target-agent actions [7]. VeriGuard goes further by generating behavioral policies and subjecting them to automated testing and formal verification before applying them as runtime monitors [8]. These approaches demonstrate that safety enforcement should not rely exclusively on the correctness of the underlying LLM. Nevertheless, they are largely domain-independent and do not explicitly incorporate network telemetry or networking-specific operational invariants into the safety decision.

In contrast, this work combines LLM-based semantic reasoning with a deterministic Mamdani Fuzzy Inference System for autonomous NetOps. The LLM provides contextual interpretation of telemetry and proposed mitigations, while the fuzzy layer evaluates the semantic action impact jointly with physical and logical network state. This architecture establishes an explicit execution boundary that can approve benign interventions, defer uncertain decisions to a human operator, or block actions that violate network safety conditions, thereby bridging the flexibility of LLM reasoning with the deterministic guarantees required for autonomous network operation.

## III. System Architecture and Generative Reasoning

The proposed Neuro-Symbolic architecture establishes a closed-loop framework for autonomous Network Operations (NetOps). The system decouples high-level semantic reasoning from deterministic execution guarantees by cascading a localized Generative AI agent with a multi-antecedent Mamdani Fuzzy Inference System (FIS).

### A. Pipeline Overview

The orchestration lifecycle operates in four discrete stages:

1) **Telemetry Ingestion:** Continuous sampling of multi-layer telemetry parameters, capturing physical integrity, traffic volume, and routing state.
2) **Generative Semantic Reasoning:** Prompting an on-premise Large Language Model (LLM) to infer root causes and synthesize mitigation playbooks.
3) **Impact Self-Assessment:** Quantitative extraction of the LLM's operational invasiveness index ($I$).
4) **Deterministic Fuzzy Verification:** Mathematical boundary checking that computes a composite risk score ($R$) to enforce execution governance.

### B. Generative AI Diagnostic Agent

The reasoning engine utilizes a quantized instance of `LLaMA 3.2:1b`, deployed locally via the Ollama run-time to eliminate data exfiltration risks and reduce inference latency. For each telemetry vector:

$$\mathbf{x} = \begin{bmatrix} \text{RX} & \text{CRC} & \text{BGP}_{\text{alert}} \end{bmatrix}^T \tag{1}$$

the agent receives a structured prompt contextualizing the observed metrics alongside device role representations.

Rather than allowing unconstrained natural language output, the LLM is constrained via programmatic grammar enforcement to produce a strict JSON payload containing three fields: (i) `root_cause`, (ii) `suggested_mitigation`, and (iii) `action_impact`.

The variable $I =$ action_impact represents the continuous semantic intent score:

$$I = \phi_{\text{LLM}}(\mathbf{x}), \quad I \in [0.0, 1.0] \tag{2}$$

where $\phi_{\text{LLM}}$ denotes the prompt-conditioned generation function. The operational spectrum of $I$ is partitioned into three bands:

$$I \in \begin{cases} [0.0, 0.3], & \text{Passive telemetry / Queue tuning} \\ (0.3, 0.6], & \text{QoS reshaping / Dynamic rerouting} \\ (0.6, 1.0], & \text{Interface shutdown / BGP reset} \end{cases} \quad (3)$$

### C. Mathematical Formulation of the Fuzzy Guardrail

To prevent tactical hallucinations from propagating to production data planes, the Mamdani Fuzzy Controller acts as a non-bypassable verification layer.

*1) Fuzzification and Membership Partitions:* The input space comprises four antecedents: RX Utilization (RX $\in [0, 100]\%$) partitioned into $\{\text{Normal}, \text{Alta}, \text{Critica}\}$; CRC Errors (CRC $\in [0, 500]$) partitioned into $\{\text{Zero}, \text{Baixo}, \text{Severo}\}$; BGP State (BGP $\in [0, 1]$) mapped to $\{\text{Estavel}, \text{Falha}\}$; and the Action Impact ($I \in [0.0, 1.0]$) partitioned into $\{\text{Leve}, \text{Moderado}, \text{Drastico}\}$.

Trapezoidal ($\Psi$) and triangular ($\Lambda$) membership functions define these fuzzy sets:

$$\Psi(u; a, b, c, d) = \max\left(0, \min\left(\frac{u-a}{b-a}, 1, \frac{d-u}{d-c}\right)\right) \quad (4)$$

$$\Lambda(u; a, b, c) = \max\left(0, \min\left(\frac{u-a}{b-a}, \frac{c-u}{c-b}\right)\right) \quad (5)$$

*2) Inference Engine and Rule Base:* The rule base formalizes domain invariants where physical metrics gate semantic actions. The $k$-th rule activation strength $w_k$ uses the minimum t-norm operator:

$$w_k = \min\Big(\mu_{\text{RX},k}(\text{RX}),\ \mu_{\text{CRC},k}(\text{CRC}),\ \mu_{\text{BGP},k}(\text{BGP}_{\text{alert}}),\ \mu_{I,k}(I)\Big) \quad (6)$$

The core domain safety constraints enforce strict execution boundaries:

- **Hardware Failure Barrier:**

  IF CRC is Severo AND $I$ is Leve
  THEN $R$ is Bloquear

- **Nominal Autonomy:**

  IF RX is Normal AND CRC is Zero
  AND BGP is Estavel AND $I$ is Leve
  THEN $R$ is Aprovar

- **Routing Disruption Control:**

  IF BGP is Falha AND CRC is Zero
  AND $I$ is Drastico
  THEN $R$ is Supervisionar

*3) Aggregation and Defuzzification:* The consequent Risk Index $R \in [0, 100]$ is partitioned into $\{\text{Aprovar}, \text{Supervisionar}, \text{Bloquear}\}$. Aggregate membership $\mu_R(z)$ is computed using the maximum s-norm across all $M$ active rules:

$$\mu_R(z) = \max_{k=1,\ldots,M} \left[\min\left(w_k,\ \mu_{\text{Risk},k}(z)\right)\right] \quad (7)$$

The crisp risk score $R^*$ is extracted via the Centroid Defuzzification technique:

$$R^* = \frac{\int_0^{100} z \cdot \mu_R(z)\, dz}{\int_0^{100} \mu_R(z)\, dz} \quad (8)$$

*4) Orchestration Policy:* The crisp score $R^*$ is mapped to the final tripartite orchestration action:

$$\text{Policy}(R^*) = \begin{cases} \text{Approve (Autonomous)}, & R^* \leq 35 \\ \text{Supervise (HitL)}, & 35 < R^* \leq 75 \\ \text{Block (Discard)}, & R^* > 75 \end{cases} \quad (9)$$

This policy ensures autonomous execution occurs exclusively within validated safe envelopes, escalating intermediate uncertainties to Human-in-the-Loop (HitL) supervision and blocking invalid operations deterministically.

## IV. Experimental Methodology

An experimental dataset of $N = 600$ telemetry events was synthesized with a stochastic fault injection rate of $\alpha = 0.20$, comprising:

- **Layer 1 (Physical Degradation):** CRC errors ($60 \leq \text{CRC} \leq 450$) under low RX utilization ($5\% \leq \text{RX} \leq 30\%$).
- **Layer 2 (Microbursts):** Transient spikes ($88\% \leq \text{RX} \leq 99\%$, $\text{CRC} = 0$).
- **Layer 3 (BGP Failure):** Routing drops ($\text{BGP}_{\text{alert}} = 1, 0\% \leq \text{RX} \leq 15\%$).
- **Steady-State (Normal):** Nominal conditions ($10\% \leq \text{RX} \leq 50\%$).

The framework is benchmarked against: (i) Static Thresholds, (ii) Classic Machine Learning (CART), and (iii) Classic Fuzzy Logic (without LLM impact awareness).

## V. Empirical Results and Multi-Layer Evaluation

This section evaluates the empirical performance of the proposed Neuro-Symbolic architecture against three baseline strategies: Static Thresholds, Classic Machine Learning (CART), and Classic Fuzzy Logic. The evaluation is conducted across the synthesized dataset of $N = 600$ telemetry events comprising nominal steady-state traffic and targeted multi-layer fault injections.

### A. Global Decision Distribution

The aggregate orchestration decisions across all 600 records are summarized in Table I and illustrated in Fig. 1.

The baseline paradigms exhibit polarized and uncalibrated decision behaviors:

TABLE I
GLOBAL DECISION DISTRIBUTION ACROSS $N = 600$ EVENTS

| Orchestration Strategy | Approve | Supervise | Block |
|---|---|---|---|
| Static Thresholds | 80.2% | 8.5% | 11.3% |
| Classic ML (CART) | 79.5% | 8.5% | 12.0% |
| Classic Fuzzy Logic | 94.5% | 5.5% | 0.0% |
| **Neuro-Symbolic (LLM+Fuzzy)** | **41.7%** | **55.3%** | **3.0%** |





Fig. 1. Comparison of Orchestration Decisions Across 600 Events.

- **Non-Semantic Rigidity:** Static Thresholds and CART ML approved approximately 80% of events while blocking 68 and 72 actions, respectively. Their lack of semantic context forced the immediate discard of non-harmful mitigation workflows during transient traffic variations.
- **Over-Permissive Fuzzy Control:** Classic Fuzzy Logic operated without semantic visibility into the generated command, approving 94.5% (567) of all events and failing to block any disruptive playbooks (0% blocking rate).
- **Balanced Neuro-Symbolic Control:** By coupling the semantic action impact ($I$) with deterministic boundaries, the Neuro-Symbolic controller authorized 250 safe actions (41.7%), escalated 332 intermediate cases to Human-in-the-Loop (55.3%), and blocked 18 dangerous operations (3.0%).

### B. Cross-Layer Scenario Evaluation

To evaluate resilience against domain-specific failures, the decisions are categorized across the four injected scenarios in Table II and visualized in Fig. 2.

### C. Key Operational Insights

The cross-layer evaluation reveals three primary operational advantages:

*1) Containment of Tactical Hallucinations (L1 Faults):* In the L1 Physical Degradation scenario (37 records), optical and physical damage cannot be rectified through software playbooks. While the LLM generated disruptive software reconfigurations ($I \geq 0.7$) in multiple instances, the fuzzy controller activated the safety rule:

$$\text{IF CRC is Severo AND } I \text{ is Leve}$$
$$\text{THEN } R \text{ is Bloquear}$$

This rule blocked 18 invalid actions (48.6%) and escalated 19 (51.4%) to HitL, completely preventing inappropriate software





Fig. 2. Orchestration Decision Rates (%) per Failure Scenario.

modifications on physically impaired interfaces. In contrast, Classic Fuzzy approved 10.8% of these interventions.

*2) Mitigation of False Alarm Discards (L2 Microbursts):* During Layer 2 microburst events (35 records), transient traffic surges exceeded standard capacity ceilings (RX $>$ 88%). Static Thresholds and CART ML discarded 88.6% and 100% of actions, respectively, incorrectly identifying short-lived queue saturation as severe service disruptions. The Neuro-Symbolic controller routed 100% (35) of these events to supervisory HitL oversight, preserving automated workflow integrity.

*3) Context-Sensitive Routing Autonomy (L3 BGP Clears):* Under Layer 3 routing collapses (51 BGP Clear records), traditional baselines exhibited extreme divergence: Static Thresholds and CART ML escalated 100% of events, contributing to operator alarm fatigue, whereas Classic Fuzzy approved 100% without validation. The Neuro-Symbolic architecture achieved selective autonomy, approving 20 benign session restoral actions (39.2%) with low impact scores ($I \leq 0.4$) while escalating 31 disruptive modifications (60.8%) for engineering authorization.

## VI. CONCLUSION

This paper presented a closed-loop Neuro-Symbolic orchestration framework designed to address the fundamental trade-off between flexible diagnostic reasoning and deterministic safety in autonomous NetOps. By cascading a quantized, localized Large Language Model (`LLaMA 3.2:1b`) with a deterministic Mamdani Fuzzy Inference System, our architecture eliminates the catastrophic risks of unconstrained generative actuation without sacrificing operational agility.

Empirical evaluation across a multi-layer synthesized dataset of $N = 600$ telemetry events demonstrated the clear superiority of the Neuro-Symbolic approach over traditional baselines:

- **Containment of Tactical Hallucinations:** The fuzzy guardrail successfully blocked 48.6% (18/37) of aggressive,

TABLE II
ORCHESTRATION DECISIONS PER NETWORK SCENARIO

| Scenario | Strategy | Approve | Supervise | Block |
|---|---|---|---|---|
| **Steady-State** | Static Thresholds | 477 (100%) | 0 (0.0%) | 0 (0.0%) |
| | Classic ML (CART) | 477 (100%) | 0 (0.0%) | 0 (0.0%) |
| | Classic Fuzzy | 477 (100%) | 0 (0.0%) | 0 (0.0%) |
| | **Neuro-Symbolic** | **230 (48.2%)** | **247 (51.8%)** | **0 (0.0%)** |
| **L1 Degradation** | Static Thresholds | 0 (0.0%) | 0 (0.0%) | 37 (100%) |
| | Classic ML (CART) | 0 (0.0%) | 0 (0.0%) | 37 (100%) |
| | Classic Fuzzy | 4 (10.8%) | 33 (89.2%) | 0 (0.0%) |
| | **Neuro-Symbolic** | **0 (0.0%)** | **19 (51.4%)** | **18 (48.6%)** |
| **L2 Microburst** | Static Thresholds | 4 (11.4%) | 0 (0.0%) | 31 (88.6%) |
| | Classic ML (CART) | 0 (0.0%) | 0 (0.0%) | 35 (100%) |
| | Classic Fuzzy | 35 (100%) | 0 (0.0%) | 0 (0.0%) |
| | **Neuro-Symbolic** | **0 (0.0%)** | **35 (100%)** | **0 (0.0%)** |
| **L3 BGP Clear** | Static Thresholds | 0 (0.0%) | 51 (100%) | 0 (0.0%) |
| | Classic ML (CART) | 0 (0.0%) | 51 (100%) | 0 (0.0%) |
| | Classic Fuzzy | 51 (100%) | 0 (0.0%) | 0 (0.0%) |
| | **Neuro-Symbolic** | **20 (39.2%)** | **31 (60.8%)** | **0 (0.0%)** |

invalid software playbooks generated during Layer 1 physical link degradation, preventing uncoordinated software modifications on impaired hardware.

- **Elimination of Microburst False Discards:** Unlike static thresholds and classic ML models that discarded up to $100\%$ of corrective workflows during transient traffic spikes, the proposed controller routed $100\%$ $(35/35)$ of Layer 2 microbursts to supervisory Human-in-the-Loop oversight.
- **Calibrated Routing Governance:** In Layer 3 BGP failure scenarios, the framework enabled selective autonomy by approving $39.2\%$ of low-impact session restoral playbooks while escalating $60.8\%$ of invasive routing modifications for engineering review.

Overall, the Neuro-Symbolic controller established a balanced operational profile—authorizing $41.7\%$ autonomous execution, routing $55.3\%$ to human supervision, and discarding $3.0\%$ unsafe actions—overcoming both the rigid, false-alarm-prone behavior of static/ML heuristics and the dangerous over-permissiveness ($94.5\%$ approval) of non-semantic fuzzy baselines.

## AI USAGE AND GENERATIVE DISCLOSURE STATEMENT

This manuscript was developed for the CNSM AI-Generated Paper Track under human Research Direction. The human authors formulated the research questions, defined operational constraints, and provided directive prompts for autonomous NetOps governance. All technical prose, mathematical formulations, and evaluation code were synthesized through Generative AI tools as detailed below:

- **Core Generative Models & Platforms:** `Google Gemini` was the primary LLM used for comprehensive manuscript drafting, LaTeX scaffolding, and controller script development. `OpenAI ChatGPT` was employed for bibliographic review and comparative methodology refinement. `Consensus.app` supported semantic literature discovery.
- **In-System Inference Engine:** The proposed closed-loop NetOps framework embeds a localized, quantized `LLaMA 3.2:1b` model running locally via the `Ollama` runtime to perform telemetry diagnostics.
- **Prompting Strategy:** A structured zero-shot prompting strategy with strict JSON schema enforcement was implemented for the diagnostic agent, constraining outputs to root-cause diagnosis, executable mitigation playbooks, and continuous Action Impact ($I \in [0.0, 1.0]$) estimation.

The human Research Directors reviewed the generated content for scientific validity, ensuring factual rigor and alignment with network management standards.

## REFERENCES


[1] C. Zhang *et al.*, "Large language models for networking: Workflows, applications, and challenges," *IEEE Network*, 2024.

[2] E. H. Mamdani and S. Assilian, "An experiment in linguistic synthesis with a fuzzy logic controller using a heuristic approach," *Int. J. Man-Mach. Stud.*, vol. 7, no. 1, pp. 1–13, 1975.

[3] A. Clemm *et al.*, "Network telemetry: A survey of principles, architectures, and applications," *IEEE Commun. Surv. Tutorials*, vol. 22, no. 4, pp. 2400–2426, 2020.

[4] R. Djurayev, D. Matkurbonov, and U. Khojiakbar, "Analysis of a Model for Improving the Efficiency of Routing Control in Data Transmission Networks Based on Fuzzy Logic," *Communications*, vol. 11, no. 1, pp. 1–6, 2023, doi: 10.11648/j.com.20231101.11.

[5] A. Qayyum, A. Albaseer, J. Qadir, A. Al-Fuqaha, and M. Abdallah, "LLM-driven multi-agent architectures for intelligent self-organizing networks," *IEEE Network*, 2025, doi: 10.1109/MNET.2025.3605319.

[6] H. Li, M. Xiao, K. Wang, R. Schober, D. I. Kim, and Y. L. Guan, "ComAgent: Multi-LLM based agentic AI empowered intelligent wireless networks," arXiv preprint arXiv:2601.19607, 2026.

[7] Z. Xiang, L. Zheng, Y. Li, J. Hong, Q. Li, H. Xie, J. Zhang, Z. Xiong, C. Xie, C. Yang, D. Song, and B. Li, "GuardAgent: Safeguard LLM agents via knowledge-enabled reasoning," arXiv preprint arXiv:2406.09187, 2025.

[8] L. Miculicich, M. Parmar, H. Palangi, K. D. Dvijotham, M. Montanari, T. Pfister, and L. T. Le, "VeriGuard: Enhancing LLM agent safety via verified code generation," arXiv preprint arXiv:2510.05156, 2025.