

BST02: Using R for Statistics in Medical Research

Part C: Functions and Programming

Nicole Erler Eleni-Rosalina Andrinopoulou

Department of Biostatistics, Erasmus Medical Center

✉ n.erler@erasmusmc.nl ✉ e.andrinopoulou@erasmusmc.nl

24 - 28 February 2020

Recap Part B

Objects

- ▶ vector
- ▶ matrix
- ▶ data.frame
- ▶ list

Data Structures

- ▶ numeric
- ▶ character
- ▶ integer
- ▶ logical
- ▶ factor

Recap Part B

Objects

- ▶ vector
- ▶ matrix
- ▶ data.frame
- ▶ list

Operators

- ▶ +, -, *, /
- ▶ <-, =
- ▶ <, >, ==

Data Structures

- ▶ numeric
- ▶ character
- ▶ integer
- ▶ logical
- ▶ factor

Special Values

- ▶ NA
- ▶ NaN
- ▶ Inf, -Inf

Recap Part B

Objects

- ▶ vector
- ▶ matrix
- ▶ data.frame
- ▶ list

Operators

- ▶ +, -, *, /
- ▶ <-, =
- ▶ <, >, ==

Data Structures

- ▶ numeric
- ▶ character
- ▶ integer
- ▶ logical
- ▶ factor

Data Transformations

- ▶ rounding (format())
- ▶ convert to factor (factor())

Special Values

- ▶ NA
- ▶ NaN
- ▶ Inf, -Inf

Recap Part B

Objects

- ▶ vector
- ▶ matrix
- ▶ data.frame
- ▶ list

Operators

- ▶ +, -, *, /
- ▶ <-, =
- ▶ <, >, ==

Data Structures

- ▶ numeric
- ▶ character
- ▶ integer
- ▶ logical
- ▶ factor

Special Values

- ▶ NA
- ▶ NaN
- ▶ Inf, -Inf

Data Transformations

- ▶ rounding (format())
- ▶ convert to factor (factor())

Data Exploration

- ▶ mean(), median(), sd(), IQR(), ...

Data Visualizations

- ▶ plotting packages
- ▶ plot types (plot(), barplot(), ...)

Recap Part B

Objects

- ▶ vector
- ▶ matrix
- ▶ data.frame
- ▶ list

Operators

- ▶ +, -, *, /
- ▶ <-, =
- ▶ <, >, ==

Data Structures

- ▶ numeric
- ▶ character
- ▶ integer
- ▶ logical
- ▶ factor

Special Values

- ▶ NA
- ▶ NaN
- ▶ Inf, -Inf

Data Transformations

- ▶ rounding (format())
- ▶ convert to factor (factor())

Data Exploration

- ▶ mean(), median(), sd(), IQR(), ...

Data Visualizations

- ▶ plotting packages
- ▶ plot types (plot(), barplot(), ...)

Subsetting

- ▶ [[...]], [...], \$, ...

In this Section

- ▶ What are functions?
- ▶ Useful functions for data exploration
- ▶ Useful functions for data manipulations
- ▶ Writing functions
- ▶ Control-flow constructs
- ▶ The `apply` family
- ▶ Lots of practising

Functions

Sometimes we want to perform the same action / manipulation on several objects.

- ▶ Option 1: copy & paste
 - ▶ a lot of work
 - ▶ susceptible to mistakes

Functions

Sometimes we want to perform the same action / manipulation on several objects.

- ▶ Option 1: copy & paste
 - ▶ a lot of work
 - ▶ susceptible to mistakes
- ▶ Option 2: **functions**

Functions

Sometimes we want to perform the same action / manipulation on several objects.

- ▶ Option 1: copy & paste
 - ▶ a lot of work
 - ▶ susceptible to mistakes
- ▶ Option 2: **functions**

What are functions?

- ▶ a group of (organized) R commands
- ▶ a (small) program with flexible (= not pre-specified) input

Almost all commands in R are functions!

Functions

Some examples:

- ▶ `mean()`
- ▶ `sum()`
- ▶ `plot()`
- ▶ ...

```
class(mean)
## [1] "function"
class(sum)
## [1] "function"
class(plot)
## [1] "function"
```

Functions

Some examples:

- ▶ `mean()`
- ▶ `sum()`
- ▶ `plot()`
- ▶ ...

```
class(mean)
## [1] "function"
class(sum)
## [1] "function"
class(plot)
## [1] "function"
```

Even `class()` is a function:

```
class(class)
```

```
## [1] "function"
```

Useful Functions for Data Exploration

Demos

- ▶ Functions for Data Exploration

R **html**

Practicals

- ▶ Exploring and Summarizing Data **html**

Useful Functions for Data Exploration

Dimension

- ▶ `dim()`
- ▶ `nrow(), ncol()`
- ▶ `length()`

Data Structure

- ▶ `str()`
- ▶ `names(),`
- ▶ `head(), tail()`
- ▶ `is.data.frame(),`
`is.list(),`
`is.matrix()`
`is.numeric(),`
`is.ordered(), ...`

Descriptives for Continuous Variables

- ▶ `summary()`
- ▶ `min(), max(),`
`range()`
- ▶ `mean(), median(),`
`quantile(), IQR()`
- ▶ `sd(), var()`
- ▶ `ave()`

Tables

- ▶ `table(),`
`prop.table()`
- ▶ `addmargins(),`
`ftable()`

for matrix & data.frame

- ▶ `summary()`
- ▶ `var(), cor(), cov2cor()`
- ▶ `colSums(), colMeans(),`
`rowSums(), rowMeans()`

Duplicates & Comparison

- ▶ `duplicated()`
- ▶ `unique()`

Useful functions for Data Manipulation

Demo

- ▶ Functions for Data Manipulation [R](#) [html](#)

Practicals

- ▶ Merging Data [html](#)

Useful functions for Data Manipulation

Transformations

- ▶ `log()`, `log2()`, `log10()`
- ▶ `exp()`, `sqrt()`, `plogis()`

Splitting & Combining

- ▶ `split()`, `cut()`
- ▶ `cbind()`, `rbind()`
- ▶ `merge()`
- ▶ `subset()`
- ▶ `c()`
- ▶ `paste()`

Sorting

- ▶ `sort()`, `order()`, `rev()`, `rank()`

Repetition & Sequence

- ▶ `rep()`, `seq()`
- ▶ `expand.grid()`

Converting Objects

- ▶ `t()`
- ▶ `unlist()`, `unname()`
- ▶ `as.numeric()`, `as.matrix()`,
`as.data.frame()`

Writing Functions

To write your own function:

```
myfun <- function(arguments) {  
  syntax  
}
```

Writing Functions

To write your own function:

```
myfun <- function(arguments) {  
  syntax  
}
```

For example:

```
square <- function(x) {  
  x^2  
}
```

```
square(3)
```

```
## [1] 9
```

Writing Functions

Functions do not always need an argument:

```
random <- function() {  
  rnorm(n = 1)  
}  
random()  
## [1] 0.1213212  
random()  
## [1] -0.04675425  
random()  
## [1] -1.662594
```

Writing Functions

Functions can use **multiple arguments**:

```
subtract <- function(x, y) {  
  x - y  
}  
subtract(x = 5.2, y = 3.3)
```

```
## [1] 1.9
```

Writing Functions

Multiple arguments are interpreted in the **pre-defined order**, unless they are named:

```
subtract(5.2, 1.2)
```

```
## [1] 4
```

is equivalent to

```
subtract(x = 5.2, y = 1.2)
```

```
## [1] 4
```

Writing Functions

Multiple arguments are interpreted in the **pre-defined order**, unless they are named:

```
subtract(5.2, 1.2)
```

```
## [1] 4
```

is equivalent to

```
subtract(x = 5.2, y = 1.2)
```

```
## [1] 4
```

But this is different:

```
subtract(y = 5.2, x = 1.2)
```

```
## [1] -4
```

Writing Functions

We can also define **default values** for arguments.

```
multiply <- function(x, y = 2) {  
  x * y  
}
```

The default value is used when the user does not specify a value for that argument.

```
multiply(x = 3, y = 3)
```

```
## [1] 9
```

```
multiply(x = 3)
```

```
## [1] 6
```

Writing Functions

Practical

► Rolling the Dice [html](#)

Control-flow Constructs: `if()`

Sometimes, we may want to execute code only **if a certain condition is fulfilled**.

To do this we can use an `if` statement

```
if (condition) {expression}
```

Control-flow Constructs: `if()`

Sometimes, we may want to execute code only **if a certain condition is fulfilled**.

To do this we can use an `if` statement

```
if (condition) {expression}
```

For example:

```
x <- rnorm(n = 10)
if (length(x) > 5) {mean(x)}
```

```
## [1] 0.4184219
```

Control-flow Constructs: `if()`

Sometimes, we may want to execute code only **if a certain condition is fulfilled**.

To do this we can use an `if` statement

```
if (condition) {expression}
```

For example:

```
x <- rnorm(n = 10)
if (length(x) > 5) {mean(x)}
```

```
## [1] 0.4184219
x <- rnorm(n = 5)
if (length(x) > 5) {mean(x)}
```

If the condition is not fulfilled, `NULL` is returned.

Control-flow Constructs: `if()` and `else`

We can also specify an expression that is evaluated **if the condition is not fulfilled**.

```
if (cond) {expression} else {alternative expression}
```

Control-flow Constructs: `if()` and `else`

We can also specify an expression that is evaluated **if the condition is not fulfilled**.

```
if (cond) {expression} else {alternative expression}
```

For example:

```
if (length(x) > 5) {  
  mean(x)  
} else {  
  x  
}
```

```
## [1] -2.3620160 -0.7277805  0.5754557  0.1426732 -0.6111593
```

Conditional Element Selection: `ifelse()`

A similar function is `ifelse()`, which performs **conditional element selection**.

```
ifelse(test, yes, no)
```

Conditional Element Selection: `ifelse()`

A similar function is `ifelse()`, which performs **conditional element selection**.

```
ifelse(test, yes, no)
```

For example:

```
(x <- round(rnorm(n = 6), 2))
```

```
## [1] -2.38  1.86 -0.71 -0.95 -0.49  1.15
```

```
ifelse(x > 0, ">0", "<0")
```

```
## [1] "<0" ">0" "<0" "<0" "<0" ">0"
```

Conditional Element Selection: `ifelse()`

A similar function is `ifelse()`, which performs **conditional element selection**.

```
ifelse(test, yes, no)
```

For example:

```
(x <- round(rnorm(n = 6), 2))
```

```
## [1] -2.38  1.86 -0.71 -0.95 -0.49  1.15
```

```
ifelse(x > 0, ">0", "<0")
```

```
## [1] "<0" ">0" "<0" "<0" "<0" ">0"
```

Note:

- ▶ `if()` expects **one** condition
- ▶ `ifelse()` expects a **vector of conditions**

Control-flow Constructs: for()-loop

To perform an operation multiple times, we can use a **for-loop**
`for (variable in sequence) {expression}`

For example:

```
for (i in 1:5) {  
  print(2 * i)  
}
```

```
## [1] 2  
## [1] 4  
## [1] 6  
## [1] 8  
## [1] 10
```

Control-flow Constructs: for()-loop

In a **for-loop** the variable does not need to be used in the expression:

```
for (i in 1:5) {  
  print('test')  
}
```

```
## [1] "test"  
## [1] "test"  
## [1] "test"  
## [1] "test"  
## [1] "test"
```

Note that when using `for()`, always the full sequence is used, i.e., we cannot skip iterations.

Control-flow Constructs: `while()`-loop

The function `while()` repeatedly evaluates an expression as long as a condition is fulfilled:

```
while (condition) {expression}
```

Careful:

If your condition is never `FALSE` this will run forever!!!
(or until you stop it manually)

Note:

`for()` and `while()` loops will not print output, unless we specifically use the function `print()`.

Control-flow Constructs: while()-loop

For example:

```
s <- 0
while (s < 7) {
  x <- rnorm(n = 1, mean = 0, sd = 2)
  s <- s + abs(x)
  print(s)
}
```

```
## [1] 2.414131
```

```
## [1] 2.96899
```

```
## [1] 5.137872
```

```
## [1] 9.829268
```

Control-flow Constructs

Demo

- ▶ Control Flow **R** **html**

Practical

- ▶ Control Flow and Functions
html

Summary: Writing Functions

```
function_name <- function(arguments) {  
  "function body"  
}
```

- ▶ can have 0, 1, 2, ...arguments
- ▶ arguments are interpreted in the **pre-specified order**, unless the **names are used**
- ▶ we can specify **default values**

Summary: Control-flow Constructs

- ▶ `if (condition) expression:`
evaluates the 'expression' only if the 'condition' is 'TRUE'
- ▶ `if (condition) expression1 else expression2:`
evaluates 'expression1' if the 'condition' is 'TRUE' and 'expression2' if the 'condition' is 'FALSE'
- ▶ `ifelse(test, yes, no):`
expects a vector of 'test's
- ▶ `for()` and `while()` loops:
can be used to repeatedly perform the same action
- ▶ to print output from within `for()` and `while()` we need to use `print()`

What is the apply Family

- ▶ Manipulate slices of data from matrices, data frames and lists in a repetitive way avoiding explicit use of loop-constructs
 - ▶ An aggregating function, like for example the mean, or the sum
 - ▶ Other transforming or subsetting functions
 - ▶ Other vectorized functions, which return more complex structures like lists, vectors and matrices

What is the apply Family (cont'd)

`apply()`, `lapply()` , `sapply()`, `tapply()`, `mapply()`

But how and when should we use these?

How To Use `apply()` in R

- ▶ Operates on Matrices and Data Frames

- ▶ By column

```
mat <- matrix(1:6, 3, 3)
```

```
mat
```

	[,1]	[,2]	[,3]
[1,]	1	4	1
[2,]	2	5	2
[3,]	3	6	3

```
apply(mat, 2, sum)
```

```
[1] 6 15 6
```

How To Use `apply()` in R

► Operates on Matrices and Data Frames

► By column

```
mat <- matrix(1:6, 3, 3)
```

```
mat
```

	[,1]	[,2]	[,3]
[1,]	1	4	1
[2,]	2	5	2
[3,]	3	6	3

```
apply(mat, 2, sum)
```

```
[1] 6 15 6
```

► By row

```
apply(mat, 1, sum)
```

```
[1] 6 9 12
```

How To Use `apply()` in R (cont'd)

- Operates on Matrices and Data Frames

```
mat <- matrix(1:6, 3, 3)
```

```
mat
```

	[,1]	[,2]	[,3]
[1,]	1	4	1
[2,]	2	5	2
[3,]	3	6	3

```
apply(mat, 2, mean)
```

```
[1] 2 5 2
```

How To Use `apply()` in R (cont'd)

- Operates on Matrices and Data Frames

```
mat <- matrix(1:6, 3, 3)
```

```
mat
```

	[,1]	[,2]	[,3]
[1,]	1	4	1
[2,]	2	5	2
[3,]	3	6	3

```
apply(mat, 2, mean)
```

```
[1] 2 5 2
```

```
apply(mat, 1, mean)
```

```
[1] 2 3 4
```

How To Use `apply()` in R (cont'd)

- You can also apply your functions

```
mat <- matrix(1:6, 3, 3)
mat
```

	[,1]	[,2]	[,3]
[1,]	1	4	1
[2,]	2	5	2
[3,]	3	6	3

```
apply(mat, 2, function(x)
      sum(x)/(length(x)-1))
```

```
[1] 3.0 7.5 3.0
```

How To Use `apply()` in R (cont'd)

- You can also apply your functions

```
mat <- matrix(1:6, 3, 3)
mat
```

```
      [,1] [,2] [,3]
[1,]     1     4     1
[2,]     2     5     2
[3,]     3     6     3
```

```
apply(mat, 2, function(x)
      sum(x)/(length(x)-1))
```

```
[1] 3.0 7.5 3.0
```

```
apply(mat, 1, function(x)
      sum(x)/(length(x)-1))
```

```
[1] 3.0 4.5 6.0
```

How To Use `lapply()` in R

- ▶ Apply a given function to every element of a list and obtain a list as result
- ▶ The difference with `apply()`:
 - ▶ It can be used for other objects like data frames, lists or vectors
 - ▶ The output returned is a list

How To Use lapply() in R (cont'd)

```
myList <- list(x <- c(1:6),  
              y = c("m", "f"),  
              z = c(30, 4, 23))
```

```
myList
```

```
[[1]]
```

```
[1] 1 2 3 4 5 6
```

```
$y
```

```
[1] "m" "f"
```

```
$z
```

```
[1] 30  4 23
```

How To Use lapply() in R (cont'd)

```
myList <- list(x <- c(1:6),  
              y = c("m", "f"),  
              z = c(30, 4, 23))
```

```
myList
```

```
[[1]]
```

```
[1] 1 2 3 4 5 6
```

```
$y
```

```
[1] "m" "f"
```

```
$z
```

```
[1] 30  4 23
```

```
myList <- list(x <- c(1:6),  
              y = c("m", "f"),  
              z = c(30, 4, 23))
```

```
lapply(myList, length)
```

```
[[1]]
```

```
[1] 6
```

```
$y
```

```
[1] 2
```

```
$z
```

```
[1] 3
```

How To Use lapply() in R (cont'd)

```
myList <- list(x <- c(1:6),  
              y = c("m", "f"),  
              z = c(30, 4, 23))
```

```
myList
```

```
[[1]]
```

```
[1] 1 2 3 4 5 6
```

```
$y
```

```
[1] "m" "f"
```

```
$z
```

```
[1] 30  4 23
```

How To Use lapply() in R (cont'd)

```
myList <- list(x <- c(1:6),  
              y = c("m", "f"),  
              z = c(30, 4, 23))
```

myList

[[1]]

[1] 1 2 3 4 5 6

\$y

[1] "m" "f"

\$z

[1] 30 4 23

```
lapply(myList, median)
```

[[1]]

[1] 3.5

\$y

[1] NA

\$z

[1] 23

How To Use `sapply()` in R

- ▶ `sapply()` is similar to `lapply()`, but it tries to simplify the output

```
myList <- list(x = c(1:6),  
              y = c("m", "f"),  
              z = c(30, 4, 23))
```

```
myList
```

```
[[1]]
```

```
[1] 1 2 3 4 5 6
```

```
$y
```

```
[1] "m" "f"
```

```
$z
```

```
[1] 30  4 23
```

How To Use `sapply()` in R

- `sapply()` is similar to `lapply()`, but it tries to simplify the output

```
myList <- list(x = c(1:6),  
              y = c("m", "f"),  
              z = c(30, 4, 23))
```

```
myList
```

```
[[1]]
```

```
[1] 1 2 3 4 5 6
```

```
$y
```

```
[1] "m" "f"
```

```
$z
```

```
[1] 30  4 23
```

```
sapply(myList, length)
```

```
  y z  
6 2 3
```

```
sapply(myList, median)
```

```
      y      z  
3.5   NA 23.0
```

How To Use `tapply()` in R

- ▶ Apply a function to subsets of a vector and the subsets are defined by some other vector, usually a factor

```
tapply(pbc$bili, pbc$sex, mean)
```

```
      m      f  
2.865909 3.262567
```

```
tapply(pbc$age, pbc$sex, median)
```

```
      m      f  
54.00137 50.19302
```

How To Use `tapply()` in R (cont'd)

- ▶ You can also apply your functions

```
tapply(pbc$bili, pbc$sex, function(x) sum(x)/(length(x)-1))
```

m	f
2.932558	3.271314

How To Use `mapply()` in R

- ▶ Multivariate apply
- ▶ Its purpose is to be able to vectorize arguments to a function that is not usually accepting vectors as arguments
- ▶ `mapply()` applies a function to multiple list or multiple vector arguments

```
mapply(length, pbc)
```

id	time	status	trt	age	sex	ascites	hepato
418	418	418	418	418	418	418	418
spiders	edema	bili	chol	albumin	copper	alk.phos	ast
418	418	418	418	418	418	418	418
trig	platelet	protime	stage				
418	418	418	418				

How To Use `mapply()` in R (cont'd)

```
myList <- list(x <- c(1:6),  
              y = c("m", "f"),  
              z = c(30, 4, 23))  
mapply(length, myList, SIMPLIFY = FALSE)
```

```
[[1]]
```

```
[1] 6
```

```
$y
```

```
[1] 2
```

```
$z
```

```
[1] 3
```

Useful Summary: Apply Family

Vectors

- ▶ `tapply()`
- ▶ `sapply()`
- ▶ `lapply()`
- ▶ `mapply()`

Matrices

- ▶ `apply()`
- ▶ `tapply()`
- ▶ `lapply()`
- ▶ `sapply()`
- ▶ `mapply()`

Data frames

- ▶ `apply()`
- ▶ `tapply()`
- ▶ `lapply()`
- ▶ `sapply()`
- ▶ `mapply()`

Lists

- ▶ `lapply()`
- ▶ `sapply()`
- ▶ `mapply()`

Useful Summary: Apply Family (cont'd)

Demos

- ▶ The Apply Family [R](#) [html](#)

Practicals

- ▶ The Apply Family [html](#)