




2017


UNISTRUT®

GENERAL ENGINEERING CATALOG - NO. 17A



A PART OF





UNISTRUT®

A PART OF **Aatkore**
INTERNATIONAL

Unistrut is the original metal framing system featuring a unique weldless connection. The Unistrut system eliminates welding and drilling, and is easily adjustable and reusable for infinite configurations. Over time, our brand has evolved from a simple connection concept to a comprehensive engineered building and support system featuring a robust line of channels, fittings, fasteners, hangers, pipe clamps, and accessories. Backed by our worldwide network of engineering and distribution centers, we provide customers with total-resource capability, making Unistrut the brand everyone asks for by name.



UNISTRUT®


**The Unistrut World of Support
starts with our network of Unistrut
Service Centers across the nation.**

The Unistrut World of Support starts with our network of Unistrut Service Centers across North America. They go far beyond providing local product inventories... by offering complete application solutions, based on experience gained from thousands of projects worldwide.

It's the kind of knowledgeable assistance that can help save time and cost now, and simplify change in the future.

Technical help? No one knows the engineering side of Unistrut support systems like your local Unistrut team. And if it's special fabrication, cutting or custom finishing you want, the pros at your local Unistrut Service Center will make it happen...quickly, efficiently, economically.


So when it's help you need, call your Unistrut Service Center—the quickest way to unlock Unistrut's World of Support.



**UNISTRUT**

TABLE OF CONTENTS

INTRODUCTION.....	2-20
Unistrut Introduction.....	2-3
Table of Contents.....	4-5
Unistrut Metal Framing Systems.....	6-9
Quality Assurance.....	10
Materials and Finishes.....	11 - 13
Design Fundamentals.....	14 - 15
Conversion Factors.....	16
Reference Tables and Data.....	17 - 18
Guide Specification.....	19
New Products.....	20
1½" CHANNEL.....	21-62
Channel Selection Chart.....	23
P1000 (12 Gauge).....	24 - 29
P1100 (14 Gauge).....	30 - 32
P2000 (16 Gauge).....	33 - 35
P3000 (12 Gauge).....	36 - 38
P3300 (12 Gauge).....	39 - 41
P4000 (16 Gauge).....	42 - 44
P4100 (14 Gauge).....	45 - 47
P4400 (12 Gauge).....	48 - 50
P4520 (12 Gauge).....	51 - 53
P5000 (12 Gauge).....	54 - 56
P5500 (12 Gauge).....	57 - 59
Closure Strips.....	60
End Caps and Frame Caps.....	61
Lateral Bracing Load Reduction Chart & Bearing Loads.....	62
TELESTRUT® SYSTEM.....	63-70
Telescoping Tube.....	65 - 67
Connection Methods.....	69
Specialized Fittings.....	68
Post Bases.....	68 - 69
Cutting Chart.....	70



NUTS & HARDWARE **71-76**

Channel Nuts	72 - 73
Top Retainer Nuts	73
Stud Nuts	74
Hardware	74 - 76
Threaded Rod	75

GENERAL FITTINGS **77-106**

Flat Plate Fittings	81 - 82
Ninety Degree Fittings	82 - 85
Angular Fittings	85
"Z" Shape Fittings	86
"U" Shape Fittings	87 - 88
Wing Shape Fittings	89 - 90
Post Bases	90
Brackets	90 - 93
Brace Fittings	94
Beam Clamps	95 - 101
Trolleys	102
Special Application Fittings	103 - 104
Seismic Retrofit Fittings	104 - 106

PIPE/CONDUIT SUPPORTS..... **107-126**

Pipe/Conduit Clamps	108 - 111
Unicushion®	112
Pipe & Tubing (Cush-A-Clamp®) Clamps	113 - 116
Pipe Hangers	117
Pipe Rollers	117 - 119
Pipe Brackets	119
Reference Tables	120 - 126

ELECTRICAL FITTINGS..... **127-138**

Electrical Fittings	128 - 130
Receptacles	131
Fixture Hangers	131
Accessories and Connectors	132
Junction Boxes	132
In-Channel Joiners	133
Swivel Hangers	133
Cable Entrance Tubing and Accessories	134 - 136
Electrical Fittings Technical Data	137 - 138

CONCRETE INSERTS..... **139-146**

Heavy-Duty Inserts	141
Standard-Duty Inserts	142, 144
Light-Duty Inserts	143
Spot Inserts	144
Deck Inserts	145
Components	145
Technical Data	146

SOLAR COMPONENTS..... **147-150**

Application Example	148
Solar Connectors	149
Key Advantages	150

UNIPIER® 151-168

Sleeper Support	153 - 154
Strut Support	155 - 158
Conduit Supports	
Mounted Support, Polycarbonate Base	157
Elevated Support, Polycarbonate Base	157
Elevated Support, Steel Base	158
Gas and Mechanical Supports	
Mounted Support, Polycarbonate Base	158
Mounted Support, w/Roller Polycarbonate Base	158
Elevated Support, w/Roller, Polycarbonate Base	159
Elevated Support, w/Roller, Steel Base	160
Accessories	
Spacer	160
Support Pads, Deck Plates	160
Pipe Hanger Bases, Polycarbonate and Steel	161
Fabricated Supports	
Single Base Trapeze	162
Double Base Trapeze	163
Heavy Duty Double Base Trapeze	163
Double Base Duct Support	163
Mechanical Supports	164
Bridge Cross-Over, Walkway, Service Platform or Ramp	164
Installation	165
Pipe Diameters and Loading	166
Technical Data	167 - 168

1¼" FRAMING SYSTEM 169-177



A1000 (14 Gauge)	171 - 172
A3300 (14 Gauge)	173 - 174
Channel Nuts and Closure Strips	175
Flat Plate Fittings	175 - 176
Ninety Degree Fittings	176
Angle and Wing Shape Fittings	176
"U" Shape Fittings	177
Pipe / Tubing Clips	177
Brackets	177

1³/₁₆" FRAMING SYSTEM 178-187

P6000 (19 Gauge)	179 - 181
P7000 (19 Gauge)	182 - 183
Channel Nuts, End Caps, and Closure Strips	184
Flat Plate Fittings	184 - 185
Ninety Degree Fittings	185
Angular Fittings, Wing Shape Fittings	186
"Z" Shape Fittings	186
"U" Shape Fittings	186 - 187
Special Application Fittings	187
Beam Clamps	187
Tubing Clips	187

FIBERGLASS SYSTEM 188-203

Heavy Duty Channel (Flange Profile)	190
---	-----



Light Duty Channel (Flange Profile) 191

Heavy Duty Channel (SST Profile) 192

Nuts & Hardware 193 - 195

Fittings 196 - 197

Pipe Clamps and Straps 198

Clevis Hangers and Channel Inserts 199

Beam Clamps 200

Power Rack Stanchions 200

Chemical Compatibility 201 - 202

Specifications 203

SPECIAL METALS 204-209

Stainless Steel Channel	206
Stainless Steel Nuts and Closure Strips	207
Aluminum Channel	208 - 209
Aluminum Closure Strips and End Caps	209

PRIMEANGLE™ 210-215

PrimeAngle™	211
Accessories	212
PrimeAngle™ Technical Data	213 - 215

UNITED INTERLOCK® GRATING . . . 216-231

Ease of Installation	217
Plank Grating	218 - 219
Accessories	220 - 222
Heavy Duty Stair Treads	223
Design and Testing	224
Plank Loads and Deflections	225 - 230
Architectural Specifications	231


ROOFWALKS® 232-233

Roofwalk® Grating Planks	233
Hardware for Membrane, Foam or Coated Roof	233
Standing Seam Installation	233

INDEX 234-239




Featuring The Unique Weldless Connection




Strong, Fast, Economical and Adjustable


Insert the spring nut anywhere along the continuous slotted channel. The rounded nut ends permit easy insertion.

1**2**


A 90° clockwise turn aligns the grooves in the nut with the inturned edges of the channel.



Fittings can be placed anywhere along the channel opening, permitting complete freedom of adjustment. The need for drilling holes is eliminated.


**3**

Insert the bolt through the fitting and into the spring nut. (See illustration 5 for end view showing the nut in place)

**4**

Additional channel sections can now be bolted to the fitting already in place by following procedure described in steps 1–3.

Tightening with a wrench locks the serrated teeth of the nut into the inturned edges of the channel, to complete a strong, vise-like connection.

5

- **100% Adjustable**
- **100% Reusable**
- **No Welding**
- **No Drilling**
- **No Special Tools**




**Serving Design
Professionals for
Over 85 Years**

Unistrut products have been helping to build a better world since 1924. Used extensively in nuclear, industrial and commercial construction markets for over 85 years, Unistrut Metal Framing has set the standard for product design, quality and performance.

The initial Unistrut concept — a simple spring nut and bolt connecting a fitting to a continuous slotted channel — has evolved into a comprehensive engineered building and support system.

Unistrut® — The Original Metal Framing System

There is only one Unistrut Metal Framing System. It incorporates the innovative product improvements that



our research and development group has created to give you the most complete and flexible support system available. Backed by our worldwide network of engineering and distribution centers, Unistrut provides customers with total-resource capability.


A North American network of Unistrut Service Centers — stocking standard Unistrut components — are located in principal cities to serve you quickly and directly. Many Service Centers are equipped to design and supply drawings for any type of metal framing application and also offer fabrication and installation services.

This catalog is a comprehensive presentation of Unistrut Metal Framing components plus technical data required by design, specification and construction professionals.




THE MOST COMPLETE METAL FRAMING SYSTEM — FOUR CHANNEL-WIDTH OPTIONS


Adjustability, demountability and reusability are engineered into each of the four Unistrut channel series. Each series offers channels of varying depth and gage plus a complete line of fittings and accessories.

**1 5/8" (41.3 mm) width**


Designed to carry the heaviest loads and provide the widest variety of applications, the 1 5/8" series has become the accepted standard for use in mechanical, electrical and general construction applications where supports and attachments must meet the highest strength requirements.

**1 1/2" (38.1 mm) width**

A framing system designed for medium to heavy loads, the 1 1/2" series offers hole spacing and fittings where all parts fit together, no matter where they're used, or at what angle.

**1 1/4" (31.8 mm) width**

A framing system designed for medium loads, the 1 1/4" series is especially suitable for use in the OEM, commercial and display markets. It maintains a lightness in scale and a clean line that makes it aesthetically pleasing as well as functional.

**13/16" (20.6 mm) width**

A unique half-size reduction of the 1 5/8" channel-width series, this smaller channel size can be used to carry light loads economically in applications such as instrumentation, retail displays and light-duty laboratory supports. It also provides the flexibility found in all Unistrut framing systems.



PRODUCT LOAD TESTING

Product testing is an important part of Unistrut's Quality Assurance Program. We utilize our own testing facilities, as well as those of independent testing laboratories, to determine design loads with proper and adequate safety factors. These design loads are indicated, where applicable, throughout the catalog. Loads are based on AISI Specification For The Design Of Cold-Formed Steel Structural Members, 2007 Edition.

Destructive and non-destructive testing procedures are used to test for variables such as corrosion, conductivity, electro-static dissipation, ultra-violet resistance, wind resistance, dimensional accuracy, material integrity and slip resistance.

In short, if there's a specification to meet, Unistrut will develop a test to quantify and verify it. Using design properties of the Unistrut framing members, load

data given in this catalog, and/or design procedures of the American Iron & Steel Institute Specification For The Design Of Cold-Formed Steel Structural Members, 2007 Edition, it is possible to design any type of structure within the capabilities of the system.

Assemblies or connections that cannot be calculated using provisions of the AISI specifications must be established by application-specific tests.

QUALITY PROGRAM

Unistrut is committed to being the "best" in the metal framing industry. In order to meet this goal, Unistrut has adopted the philosophy of "Zero Defects and Continuous Improvement". This means on-going reviews of our manufacturing processes,

operating procedures and quality systems to find ways of improving efficiency, productivity and quality. It means establishing process controls and problem-prevention techniques to ensure that superior quality is built into every Unistrut product.

Our drive to be the best includes not just quality products, but on-time delivery and prompt resolution of customer needs and concerns. At Unistrut, quality is number one.

TRACEABILITY

Unistrut channel is stamped with a numeric code that allows traceability to the origin of the steel



MATERIAL**Framing Members**

Unistrut channels and continuous inserts are accurately and carefully cold-formed to size from low carbon strip steel. One side of the channel has a continuous slot with inturned edges. Secure attachments may be made to the framing member with the use of hardened, toothed, slotted nuts which engage the inturned edges.

Raw steel shall conform to the following ASTM specifications:

GAGE	FINISH	ASTM NO.
12	GR & HG	A1011 SS GR 33
	PG	A653 GR 33
14	GR & HG	A1011 SS GR 33
	PG	A653 GR 33
16	GR & HG	A1011 SS GR 33
	PG	A653 GR 33
19	GR	A1008

WEIGHTS AND DIMENSIONS

Weights given for all materials are approximate shipping weights. All dimensions are subject to commercial tolerance within published specifications.


Nuts and Bolts

Unistrut nuts are made from steel bars. After all machining operations are complete, they are thoroughly case hardened. Nuts are rectangular with ends shaped to permit a quarter turn clockwise in the framing member after insertion through the slotted opening in the channel. Two toothed grooves in the top of the nut engage the inturned edges of the channel and, after bolting operations are completed, will prevent any movement of the bolt and nut within the framing member.

All bolts and nuts have Unified coarse screw threads. The standard framing nut is $\frac{1}{2}$ " and conforms to ASTM A576 GR 1015 modified and A1011 SS GR 45. Screws conform to SAE J429 GR 2.

Fittings

Unistrut fittings, unless noted otherwise, are punch-press made from hot rolled, pickled and oiled steel plates, strip or coil, and conform to ASTM specifications A575, A576, A635 or A36. The fitting steel also meets the physical requirement of ASTM A1011 SS GR 33. The pickling of the steel produces a smooth surface free from scale.



WE RESERVE THE RIGHT TO MAKE SPECIFICATION CHANGES WITHOUT NOTICE.

WHILE EVERY EFFORT HAS BEEN MADE TO ASSURE THE ACCURACY OF INFORMATION CONTAINED IN THIS CATALOG AT THE TIME OF PUBLICATION, WE CANNOT ACCEPT RESPONSIBILITY FOR INACCURACIES RESULTING FROM UNDETECTED ERRORS OR OMISSIONS.




THE BLUE COLOR USED ON UNISTRUT COMPONENTS ILLUSTRATED IN THIS CATALOG IS FOR GRAPHIC ENHANCEMENT ONLY, AND DOES NOT REPRESENT ACTUAL PRODUCT COLOR.



Perma-Green® III

The performance of Unistrut's Perma-Green III far exceeds that of conventional finishes. And compared to competitive "high-performance" coatings, Perma-Green III provides superior resistance to chalking, checking and fading and is far less vulnerable to common acidic atmospheres, solvents and alkalis.

Just as important, Perma-Green III is the result of an environmentally neutral process that virtually eliminates the toxic metals commonly found in competitive paint-based finishes.



PERMA-GREEN® III (GR) TECHNICAL DATA

STEEL SUBSTRATE PREPARATION

Ten stage continuous cleaning, phosphate process.

Substrate after "prep": sealed phosphate conversion coating.

COATING

Thermoset epoxy

Color:

Federal Highway Green
Color Tolerance Chart
PR Color No. 4

Hardness: 2H.

Coating Process:
Cathodic Electrodeposition.

PERFORMANCE

Salt Spray:

Scribed: exceeds 400 hours per ASTM B117. (1/8" creep)
Unscribed: exceeds 600 hours per ASTM B117. (6% red rust)

Chalk:

Nominal at 1,000 hours per weatherometer G-23 test.

Checking:

None at 1,000 hours per weatherometer G-23 test.

Fade:

Less than 50% compared to standard epoxy E.C. coatings.

ENVIRONMENTAL ISSUES

Formulated as a "heavy metal"-free coating (trace elements only).

Outgassing in service: essentially none at 350°F for 24 hours.

PLAIN (PL)

Plain finish designation means that the channel retains the oiled surface applied to the raw steel during the rolling process. The fittings have the original oiled surface of the coil or strip steel material.

**Pregalvanized Zinc (PG)
ASTM A653**

Pregalvanized steel is zinc coated by a hot dip process. Steel strip from a coil is fed through a continuous zinc coater which cleans, fluxes and coats the steel with molten zinc. After cooling, the steel is recoiled.

The pregalvanized zinc coating conforms to a G-90 thickness designation per ASTM A653. The zinc thickness is .75 MIL or .45 oz./sq. ft. of surface area.

This coating is offered on Unistrut channel and tubing and is a well-proven, time-tested performer for indoor and outdoor applications. For severe corrosion applications, hot dip galvanizing, as described below, is a good alternative.

**HOT DIP GALVANIZED (HG)
ASTM A123 OR A153**

In hot dip galvanizing, the finished part is immersed in a bath of molten zinc. This method results in complete zinc coverage and a thicker coating than pregalvanized or plated zinc.

The zinc coating is typically 2.6 MIL or 1.5 oz./sq. ft. of surface area.

This is the coating of choice for applications where severe corrosion is a design factor.

SPECIAL COATING

When specific applications require other than standard available finishes, special finishes can be supplied per customer requirements.

**Electroplated Zinc (EG)
ASTM B633, Type III SC1 or SC3**

In the electroplating process, the part to be zinc coated is immersed in a solution of zinc ions. An electric current causes the zinc to be deposited on the part.

SC1 (Mild) has a Zinc coating of 0.2 and is recommended for dry indoor use. SC1 is the standard finish thickness.

SC3 (Severe) has a Zinc coating of 0.5 mill and is the standard finish thickness only on UL Listed raceway products.

**Perma-Gold (ZD)
ASTM B633, Type II SC3**

Similar to the EG process except in a yellow color.

Unistrut Defender (DF)

Unistrut® Defender™ is a combination of two proprietary material coatings conforming to ASTM standards A1046 and A1059. Channel, Fittings and Pipe Clamps meet the physical requirements of ASTM A1011 SS GR 33, ASTM A1046 SS GR 33, or ASTM A1011 HSLAS GR 45 Class 2.

3X the corrosion resistance of HG!

Zinc Coating

Unistrut products are available in four types of zinc coatings:


- Electroplated (EG)
- Perma-Gold (ZD)
- Pregalvanized (PG)
- Hot Dip Galvanized (HG).

Zinc offer two types of protection:

- **Barrier:** The zinc coating protects the steel substrate from direct contact with the environment.
- **Sacrificial:** The zinc coating will protect scratches, cut edges, etc. through an anodic sacrificial process.

The service life of zinc coating is directly related to the zinc coating thickness as shown below.

Comparison of Zinc Finishes	
Finish	Zinc Thickness
Hot Dip Galvanized	2.6 MIL
Pre-galvanized	0.75 MIL
Electro-Galvanized (SC1)	0.2 MIL
Electro-Galvanized (SC3)	0.5 MIL
Perma-Gold (SC3)	0.5 MIL






BEAMS

Beams are structural members loaded at right angles (perpendicular) to their length. Most beams are horizontal and subjected to gravity or vertical loads, e.g. a shelf support. However a vertical member can act as a beam under certain conditions, such as a curtain wall mullion subjected to wind loading. The bending moment developed in a beam is dependent on:


- (a) The amount of load applied,
- (b) The type of loading applied, and
- (c) The support conditions



BEAM LOADING - POINT LOAD


A load concentrated onto a very small length of the beam is a point load.

BEAM LOADING - UNIFORM LOAD



A load spread evenly over a relatively long length of the beam is a uniform load.


Point and uniform loads can be placed on a beam in any combination. A series of point loads can approximate a uniform loading. The load charts and tables are based on a uniform load unless identified otherwise.



SUPPORT CONDITIONS - SIMPLE BEAM


A simple beam has supports that prevent movement left and right, or up and down, but do not restrain the beam from rotating at the supports into a natural deflected curve. Most Unistrut Metal Framing connections produce simple beams. The load charts and tables are based on simple beams unless identified otherwise.

SUPPORT CONDITIONS - CONTINUOUS BEAM




Any simple beam that is supported at one or more intermediate points is a continuous beam. A mezzanine joist that passes over three or more columns is an example of a continuous beam.

SUPPORT CONDITIONS - FIXED-END BEAM




Supports that prevent the beam from rotating into a natural deflected curve produce a fixed-end beam. A welded end connection to very rigid support produces a fixed-end beam.

SUPPORT CONDITIONS - CANTILEVER BEAM



A cantilever beam is a fixed-end beam that is supported at one end only, while the other end is unsupported. Unistrut brackets are examples of cantilever beams.

DEFLECTION



All beams deflect under load. The amount of deflection is dependent on

- (a) the amount of load,
- (b) the support conditions,
- (c) the stiffness of the beam's cross-sectional shape, and
- (d) the stiffness of the beam material.

The stiffness of the beam's cross-sectional shape is measured by its "Moment Of Inertia" or "I". The larger a beam's "I", the stiffer it is and the less it will deflect. A beam's "I" can change for each major axis. The "I" of both major axes (I 1-1 and I 2-2) are provided.

The stiffness of a beam's material is measured by its "Modulus of Elasticity" or "E". The larger a material's "E", the stiffer it is and the less it deflects. For example, steel is about three times stiffer than aluminum and as a result, deflects only one-third as much. Do not confuse stiffness with strength. Two materials may have identical strengths yet still have different "E's". A high-strength aluminum may be as strong as steel and still deflect three times as much.

The load charts and tables give calculated deflections for the loads shown. In many cases, a final design will be determined by the maximum deflection, not the maximum load.

BENDING MOMENT

Is it strong enough? This is the final consideration for any beam. A beam must not only hold up the anticipated loads, but must also have sufficient additional capacity to safely hold unforeseen variations in applied loads and material strengths. This additional capacity is called a safety factor and is usually regulated by the various design codes and standards. A beam's strength is usually measured by an allowable bending moment or an allowable stress. The traditional approach is the allowable stress method, where a beam is determined to have a maximum allowable stress (in pounds per square inch) which is not to be exceeded.

The approach of the current AISI "Specification For The Design Of Cold-Formed Steel Structural Members" is to use a maximum allowable bending moment (in inch-pounds) which is not to be exceeded. Bending moment divided by a beam's section modulus or "S" equals stress.

COLUMNS

Columns are structural members that are loaded parallel to their length. Most columns are vertical and are used to carry loads from a higher level to a lower level. However any member subjected to compression loads, such as a diagonal or prop brace, is a column.

A column fails by "buckling", which is a sudden loss of straightness and subsequent collapse. Allowable column load is dependent on:

- (a) the length of column,
- (b) the type of loading,
- (c) the support conditions, and
- (d) the column's cross-sectional shape and material.

COLUMN LENGTH

The column length is measured from braced point to braced point. A braced point is where the column is restrained from lateral movement (translation) in all directions.

COLUMN LOADING – CONCENTRIC LOADING

Loads applied to the center of gravity of the column cross-section are considered concentric. A beam that passes over and rests on the top of a column is an example of concentric loading.

COLUMN LOADING – ECCENTRIC LOADING

Any load which is not concentric is eccentric. The amount of eccentricity (in inches) has a major effect on the load-carrying capacity of any particular column. A load that is transmitted to a Unistrut Metal Framing column using a standard fitting bolted to the slot face is considered eccentric.


The load tables give allowable loads for both concentric (loaded at C.G.) and certain eccentric (loaded at slot face) loading. Allowable loads for other eccentric loading must be determined by a qualified design professional.

SUPPORT CONDITIONS

Based on the support conditions, an appropriate "K" value is selected. This "K" value, which mathematically describes the column end conditions, is used in the column design equations. The most common support condition combinations are as follows:

SUPPORT CONDITIONS - FIXED TOP – FIXED BOTTOM

Both ends are restrained against rotation and lateral movement (translation).

**CROSS-SECTIONAL SHAPE**

The cross-sectional shape of a column member determines the value of its "Radius of Gyration" or "r". In general, a member with a large "r" makes a better column than a member with a small "r". Each axis of a column has a different "r". Typically the axis with the smallest "r" determines the final design.


BOLT TORQUE

Bolt torque values are given to ensure the proper connection between Unistrut Metal Framing components. It is important to understand that there is a direct, but not necessarily consistent, relationship between bolt torque and tension in the bolt. Too much tension in the bolt can cause it to break or crush the component parts. Too little tension in the bolt can prevent the connection from developing its full load capacity. The torque values given have been developed over many years of experience and testing.

Bolt Torque						
BOLT SIZE	1/4" -20	5/16" -18	3/8" -16	1/2" -13	5/8" -11	3/4" -10
Rec.Torque Ft/Lbs (N·m)	6 (8)	11 (15)	19 (26)	50 (68)	100 (136)	125 (170)
Max Torque Ft/Lbs (N·m)	7 (9)	15 (20)	25 (34)	70 (95)	125 (170)	135 (183)

SUPPORT CONDITIONS - PINNED TOP – FIXED BOTTOM

Both ends are restrained against lateral movement (translation) but are allowed to rotate.



These are based on using a properly calibrated torque wrench with a clean dry (non-lubricated) Unistrut fitting, bolt and nut. A lubricated bolt or nut can cause extremely high tension in the connection and may lead to bolt failure. It must be noted that the accuracy of commercial torque wrenches varies widely and it is the responsibility of the installer to ensure that proper bolt torque has been achieved.

SUPPORT CONDITIONS - PINNED TOP – PINNED BOTTOM

Both ends are restrained against lateral movement (translation) but are allowed to rotate.

**SUPPORT CONDITIONS - FREE TOP – FIXED BOTTOM**

The top is restrained against rotation but is allowed to move laterally. The bottom is restrained against rotation and lateral movement (translation).







UNIT CONVERSIONS

English To Metric		
To Convert From	To	Multiply By
Length		
Inch [in]	Millimeter [mm]	25.400 000
Foot [ft]	Meter [m]	0.304 800
Yard [yd]	Meter [m]	0.914 400
Mile [mi] (U.S. Statute)	Kilometer [km]	1.609 347
Area		
Square Inch [in ²]	Square Millimeter [mm ²]	645.16
Square Foot [ft ²]	Square Meter [m ²]	0.092 903
Square Yard [yd ²]	Square Meter [m ²]	0.836 127
Square Mile [mi ²] (U.S. Statute)	Square Kilometer [km ²]	2.589 998
Acre	Square Meter [m ²]	4046.873
Acre	Hectare	0.404 687
Volume		
Cubic Inch [in ³]	Cubic Millimeter [mm ³]	16387.06
Cubic Foot [ft ³]	Cubic Meter [m ³]	0.028 317
Cubic Yard [yd ³]	Cubic Meter [m ³]	0.764 555
Gallon [gal] (U.S. Liquid)	Litre [l]	3.785 412
Quart [qt] (U.S. Liquid)	Litre [l]	0.946 353
Mass		
Ounce (Avoirdupois) [oz]	Gram [g]	28.349 520
Pound (Avoirdupois) [lb]	Kilogram [kg]	0.453 592
Short Ton	Kilogram [kg]	907.185
Force		
Ounce-Force	Newton [N]	0.278 014
Pound-Force [lbf]	Newton [N]	4.448 222
Bending Moment		
Pound-Force-Inch [lbf-in]	Newton-Meter [N-m]	0.112 985
Pound-Force-Foot [lbf-ft]	Newton-Meter [N-m]	1.355 818
Pressure, Stress		
Pound-Force per Square Inch [lbf/in ²]	Kilopascal [kPa]	6.894 757
Foot of Water (39.2 F)	Kilopascal [kPa]	2.988 980
Inch of Mercury (32 F)	Kilopascal [kPa]	3.386 380
Energy, Work, Heat		
Foot-Pound-Force [ft-lbf]	Joule [J]	1.355 818
British Thermal Unit [Btu]	Joule [J]	1055.056
Calorie [cal]	Joule [J]	4.186 800
Kilowatt Hour [kW-h]	Joule [J]	3,600,000
Power		
Foot-Pound-Force /Second [ft-lbs/s]	Watt [W]	1.355 818
British Thermal Unit /Hour [Btu/h]	Watt [W]	0.293 071
Horsepower [hp] (550 Ft. Lbf/s)	Kilowatt [kW]	0.745 700
Angle		
Degree	Radian [rad]	0.017 453
Temperature		
Degree Fahrenheit [°F]	Degree Celsius [°C]	(F° -32)/1.8

Metric to English		
To Convert From	To	Multiply By
Length		
Millimeter [mm]	Inch [in]	0.039 370
Meter [m]	Foot [ft]	3.280 840
Meter [m]	Yard [yd]	1.093 613
Kilometer [km]	Mile [mi] (U.S. Statute)	0.621 370
Area		
Square Millimeter [mm ²]	Square Inch [in ²]	0.001550
Square Meter [m ²]	Square Foot [ft ²]	10.763 915
Square Meter [m ²]	Square Yard [yd ²]	1.195 991
Square Kilometer [km ²]	Square Mile [mi ²] (U.S. Statute)	0.386 101
Square Meter [m ²]	Acre	0.000 247
Hectare	Acre	2.471 046
Volume		
Cubic Millimeter [mm ³]	Cubic Inch [in ³]	0.000061
Cubic Meter [m ³]	Cubic Foot [ft ³]	35.314 662
Cubic Meter [m ³]	Cubic Yard [yd ³]	1.307 950
Litre [l]	Gallon [gal] (U.S. Liquid)	0.264 172
Litre [l]	Quart [qt] (U.S. Liquid)	1.056 688
Mass		
Gram [g]	Ounce (Avoirdupois) [oz]	0.035 274
Kilogram [kg]	Pound (Avoirdupois) [lb]	2.204 624
Kilogram [kg]	Short Ton	0.00110
Force		
Newton [N]	Ounce-Force	3.596 941
Newton [N]	Pound-Force [lbf]	0.224 809
Bending Moment		
Newton-Meter [N-m]	Pound-Force-Inch [lbf-in]	8.850 732
Newton-Meter [N-m]	Pound-Force-Foot [lbf-ft]	0.737 562
Pressure, Stress		
Kilopascal [kPa]	Pound-Force per Square Inch [lbf/in ²]	0.145 038
Kilopascal [kPa]	Foot of Water (39.2 F)	0.334 562
Kilopascal [kPa]	Inch of Mercury (32 F)	0.295 301
Energy, Work, Heat		
Joule [J]	Foot-Pound-Force [ft-lbf]	0.737 562
Joule [J]	British Thermal Unit [Btu]	0.000948
Joule [J]	Calorie [cal]	0.238 846
Joule [J]	Kilowatt Hour [kW-h]	2.78 ⁻⁷
Power		
Watt [W]	Foot-Pound-Force /Second [ft-lbs/s]	0.737 562
Watt [W]	British Thermal Unit /Hour [Btu/h]	3.412 142
Kilowatt [kW]	Horsepower (550 Ft. Lbf/s) [hp]	1.341 022
Angle		
Radian [rad]	Degree	57.295 788
Temperature		
Degree Celsius [°C]	Degree Fahrenheit [°F]	1.8x°C+32

BEAM SUPPORT CONDITIONS



R – Reaction

M – Moment

P – Concentrated Load

W – Total Uniform Load

V – Shear

L – Length

 Δ – Deflection

E – Modulus of Elasticity

I – Moment of Inertia


CONVERSION FACTORS FOR BEAMS WITH VARIOUS STATIC LOADING CONDITIONS

All Beam Load tables are for single-span (simple) beams supported at the ends. These can be used in the majority of the cases. However, there are times when it is necessary to know what happens with other loading and support conditions. Some common arrangements are shown below. Simply multiply the values from the Beam Load tables by factors given below.

Load and Support Condition	Load Factor	Deflection Factor
1. Simple Beam, Uniform Load	1.00	1.00
2. Simple Beam, Concentrated Load at Center	.50	.80
3. Simple Beam, Two Equal Concentrated Loads at 1/4 pts	1.00	1.10
4. Beam Fixed at Both Ends, Uniform Load	1.50	.30
5. Beam Fixed at Both Ends, Concentrated Load at Center	1.00	.40
6. Cantilever Beam, Uniform Load	.25	2.40
7. Cantilever Beam, Concentrated Load at End	.12	3.20
8. Continuous Beam, Two Equal Spans, Uniform Load on One Span	1.30	.92
9. Continuous Beam, Two Equal Spans, Uniform Load on Both Ends	1.00	.42
10. Continuous Beam, Two Equal Spans, Concentrated Load at Center of One Span	.62	.71
11. Continuous Beam, Two Equal Spans, Concentrated Load at Center of Each Span	.67	.48

EXAMPLE I:


Determine load and deflection of a P 1000 beam continuous over one support and loaded uniformly on one span.


SOLUTION:

- From load table for P1000 on page 25 load for a 5'-0" span is 680# and deflection is .35".
- Multiply by factors from Table above.
Load = $680\# \times 1.30 = 884\#$
Deflection = $.35\" x .92 = .32"$

EXAMPLE II

Determine load and deflection of a P 5500 cantilever beam with a concentrated load on the end.


SOLUTION:

- From load table P5500 on page 58 load for a 3'-0" span is 2180# and deflection is .09".
- Multiply by factors from Table above.
Load = $2180\# \times .12 = 262\#$
Deflection = $.09" \times 3.20 = .29"$

PART I - GENERAL**1.01 SCOPE OF WORK**

- A. Provide all Unistrut Metal Framing material, fittings and related accessories (Strut System) as indicated on the Contract Drawings.
- B. Provide all labor, supervision, engineering, and fabrication required for installation of the Strut System in accordance with the Contract Drawings and as specified herein.
- C. Related work specified elsewhere.

1.02 QUALITY ASSURANCE

- A. Manufacturer's qualifications:
 - 1. The manufacturer shall not have had less than 10 year's experience in manufacturing Strut Systems.
 - 2. The manufacturer must certify in writing all components supplied have been produced in accordance with an established quality assurance program.
- B. Installer's qualifications:
 - 1. Installer must be a Unistrut trained manufacturer's authorized representative/installer with not less than 5 years experience in the installation of Strut Systems of this size and conformation.
 - 2. All Strut System components must be supplied by a single manufacturer.
- C. Standards:
 - 1. Work shall meet the requirements of the following standards:
 - a. Federal, State and Local codes.
 - b. American Iron and Steel Institute (AISI) Specification for the Design of Cold-Formed Steel Structural Members 2007 Edition.
 - c. American Society for Testing And Materials (ASTM).

1.03 SUBMITTALS

- A. Structural Calculations and Shop Drawings
 - 1. Submit structural calculations for approval by the project engineer. Calculations may include, but are not limited to:
 - a. Description of design criteria.
 - b. Stress and deflection analysis.
 - c. Selection of Unistrut framing members, fittings, and accessories.
 - 2. Submit all shop/assembly drawings necessary to completely install the Strut System in compliance with the Contract Drawings.
 - 3. Submit all pertinent manufacturers published data.

1.04 PRODUCT DELIVERY, STORAGE, AND HANDLING

- A. All material is to be delivered to the work site in original factory packaging to avoid damage to the finish.
- B. Upon delivery to the work site, all components shall be protected from the elements by a shelter or other covering.

1.05 GUARANTEE

- A. Separate guarantees shall be issued from the erector and manufacturer, valid for a period of 1 year, against any defects that may arise from the installation or manufacture of the Strut System components.

PART 2 - PRODUCTS**2.01 ACCEPTABLE MANUFACTURERS**

- A. All Strut System components shall be as manufactured by UNISTRUT CORPORATION or approved equal as determined by the Architect or Engineer of record in writing 10 days prior to bid date.

2.02 MATERIALS

- A. All channel members shall be fabricated from structural grade steel conforming to one of the following ASTM specifications:
A 1011 SS GR 33,A 653 GR 33.
- B. All fittings shall be fabricated from steel conforming to one of the following ASTM specifications:
A 575,A 576,A 36 or A 635.
- C. Substitutions
Any substitutions of product or manufacturer must be approved in writing ten days prior to bid date, by Architect or Engineer of record.

2.03 FINISHES

- A. Strut System components shall be finished in accordance with one of the following standards:
 - 1. PERMA-GREEN® III (GR)
Rust inhibiting epoxy enamel paint applied by electro-deposition, after cleaning and phosphating, and thoroughly baked. Color is per Federal Highway Green, Color Tolerance Chart PR Color No. 4. Finish to withstand minimum 400 hours salt spray when tested in accordance with ASTM B117.

- 2. ELECTRO-GALVANIZED (EG)**
Electrolytically zinc coated per ASTM B 633 Type III SC 1

- 3. PRE-GALVANIZED (PG)**
Zinc coated by hot-dipped process prior to roll forming. The zinc weight shall be G90 conforming to ASTM A 653.

- 4. HOT-DIPPED GALVANIZED (HG)**
Zinc coated after all manufacturing operations are complete. Coating shall conform to ASTM A 123 or A 153.

- 5. UNISTRUT DEFENDER™ (DF)**
Coating conforming to ASTM A1046 or A1059.

- 6. SPECIAL COATING / MATERIAL**
(Describe as applicable)

PART 3 - EXECUTION**3.01 EXAMINATION**

- A. The installer shall inspect the work area prior to installation. If work area conditions are unsatisfactory, installation shall not proceed until satisfactory corrections are completed.

3.02 INSTALLATION







- A. Installation shall be accomplished by a fully trained manufacturer authorized installer.
- B. Set Strut System components into final position true to line, level and plumb, in accordance with approved shop drawings.
- C. Anchor material firmly in place. Tighten all connections to their recommended torques.


3.03 CLEANUP

- A. Upon completion of this section of work, remove all protective wraps and debris. Repair any damage due to installation of this section of work.

3.04 PROTECTION

- A. During installation, it shall be the responsibility of the installer to protect this work from damage.
- B. Upon completion of this scope of work, it shall become the responsibility of the general contractor to protect this work from damage during the remainder of construction on the project and until substantial completion.

**UNIPIER® ROOFTOP PIPE SUPPORT SYSTEM****NEW CHANNEL SECTION P4520/P4521 (1⁵/₈" x 1¹³/₁₆")****NEW CHANNEL SECTION P4400/P4401 (1⁵/₈" x 1")****NEW BEAM CLAMP P1640**



MATERIAL

Unistrut channels are accurately and carefully cold formed to size from low-carbon strip steel.

All spot-welded combination members, except P1001T, are welded 3" (76 mm) maximum on center.

STEEL: PLAIN

12 Ga. (2.7 mm), 14 Ga. (1.9 mm) and
16 Ga. (1.5 mm) ASTM A1011 SS GR 33

STEEL: PRE-GALVANIZED

12 Ga. (2.7 mm), 14 Ga. (1.9 mm) and
16 Ga. (1.5mm) ASTM A653 GR 33

For other materials, see Special Metals or Fiberglass sections.

FINISHES

All channels are available in:

- Perma Green III (GR)
- Pre-galvanized (PG), conforming to ASTM A653 G90
- Hot-dipped galvanized (HG), conforming to ASTM A123
- Plain (PL)
- Unistrut Defender™ (DF), conforming to ASTM A1046

Channel Selection Chart	23
P1000 (12 Gauge)	24 - 29
P1100 (14 Gauge)	30 - 32
P2000 (16 Gauge)	33 - 35
P3000 (12 Gauge)	36 - 38
P3300 (12 Gauge)	39 - 41
P4000 (16 Gauge)	42 - 44
P4100 (14 Gauge)	45 - 47
P4400 (12 Gauge)	48 - 50
P4520 (12 Gauge)	51 - 53
P5000 (12 Gauge)	54 - 56
P5500 (12 Gauge)	57 - 59
Closure Strips	60
End Caps and Frame Caps	61
Lateral Bracing Load Reduction Chart & Bearing Loads.....	62

DIMENSIONS

Imperial dimensions are illustrated in inches. Metric dimensions are shown in millimeters and rounded to one decimal place.

STANDARD LENGTHS

Standard lengths are 10 feet (3.05m) and 20 feet (6.10m). Tolerances are $\pm\frac{1}{8}$ " (3 mm). Special lengths are available for a small cutting charge with a tolerance of $\pm\frac{1}{8}$ " (3 mm).
















CURVED CHANNEL

Contact your local Unistrut Service Center or Unistrut Corporation for more information.

LOAD DATA

All beam and column load data pertains to carbon steel and stainless steel channels. Load tables and charts are constructed to be in accordance with the SPECIFICATION FOR THE DESIGN OF COLD-FORMED STEEL STRUCTURAL MEMBERS 2007 EDITION published by the AMERICAN IRON AND STEEL INSTITUTE USING ASD METHOD. Loads are based on 33 ksi steel cold formed to 42 ksi.

Type of Load	Safety Factor to Yield Strength
Beam Loads	1.67
Column Load	1.80

**P1000 Series (12 ga.)****P1100 Series (14 ga.)****P2000 Series (16 ga.)****P3000 Series (12 ga.)****P3300 Series (12 ga.)****P4100 Series (14 ga.)****P4000 Series (16 ga.)****P4400 Series (12 ga.)****P4520 Series (12 ga.)****P5000 Series (12 ga.)****P5500 Series (12 ga.)****P9000 Series (12 ga.)**
Telestrut Channel**End Caps and Frame Caps****1 5/8" Channel Closure Strips****Alternate Framing Systems****A1000 Series (14 gauge) – 1 1/4" Channel****A3300 Series (14 gauge)**
1 1/4" Channel**P6000 Series (19 gauge) – 13/16" Channel****P7000 Series (19 gauge)**
13/16" Channel

CHANNEL SELECTION CHART

Channel	Channel Dimensions		Material & Thickness			Hole Pattern Styles						
	Width In (mm)	Height In (mm)	Steel gauge	Stainless Steel gauge	Alum. In (mm)	HS	T	WT	KO	SL	DS	H3
P1000	1½ (41.3)	1½ (41.3)	12 ga	12 ga	0.109 (2.8)	■	■	■	■	■	■	■
P1100	1½ (41.3)	1½ (41.3)	14 ga	14 ga	—	■	■	■	■	■	—	—
P2000	1½ (41.3)	1½ (41.3)	16 ga	—	—	■	■	■	■	■	—	—
P3000	1½ (41.3)	1¾ (34.9)	12 ga	—	—	■	■	■	■	■	—	—
P3300	1½ (41.3)	7/8 (22.2)	12 ga	12 ga	—	■	■	■	—	■	—	—
P4000	1½ (41.3)	13/16 (20.6)	16 ga	16 ga	0.078 (2.0)	■	■	■	—	■	—	—
P4100	1½ (41.3)	13/16 (20.6)	14 ga	—	—	■	■	■	—	■	—	—
P4400	1½ (41.3)	1(25.4)	12 ga	—	—	■	■	■	—	■	—	—
P4520	1½ (41.3)	13/16 (20.6)	12 ga	—	—	■	■	■	—	■	—	—
P5000	1½ (41.3)	3¼ (82.6)	12 ga	12 ga	—	■	■	■	■	■	—	—
P5500	1½ (41.3)	27/16 (61.9)	12 ga	—	0.109 (2.8)	■	■	■	■	■	—	—

CHANNELS & COMBINATIONS IN DESCENDING ORDER OF STRENGTH




Channel	Area In ² (cm ²)	Weight lbs/ft (kg/m)	I In ⁴ (cm ⁴)	s In ³ (cm ³)	Allow. Moment In-lbs (N·m)
P5001	1.793	6.10	6.227	1.916	48,180
	11.57	9.1	259.2	31.4	5,440
P1004A	1.965	6.68	4.068	1.669	41,980
	12.68	9.9	169.3	27.4	4,740
P5501	1.452	4.94	2.805	1.151	28,940
	9.37	7.3	116.8	18.9	3,270
P1001C41	2.221	7.55	1.856	1.142	28,720
	14.33	11.2	77.2	18.7	3,250
P5000	0.897	3.05	1.098	0.627	15,770
	5.78	4.5	45.7	10.3	1,780
P1001	1.111	3.78	0.928	0.571	14,360
	7.16	5.6	38.6	9.4	1,620
P1101	0.835	2.84	0.733	0.451	11,340
	5.39	4.2	30.5	7.4	1,280
P3001	1.000	3.40	0.591	0.430	10,810
	6.45	5.1	24.6	7.0	1,220
P5500	0.726	2.47	0.522	0.390	9,820
	4.68	3.7	21.7	6.4	1,110
P2001	0.684	2.32	0.618	0.381	9,570
	4.41	3.5	25.7	6.2	1,080
P9200	0.489	2.23	0.279	0.297	7,480
	3.16	3.3	11.6	4.9	850
P4401	0.849	5.77	0.26	0.26	6,410
	5.48	8.5	10.6	4.2	725
A1001	0.609	2.07	0.302	0.242	6,070
	3.93	3.1	12.6	4.0	690
P9000	0.387	1.88	0.166	0.205	5,150
	2.50	2.8	6.9	3.4	580
P1000	0.555	1.89	0.185	0.202	5,070
	3.58	2.8	7.7	3.3	570
P3301	0.790	2.69	0.176	0.201	5,060
	5.10	4.0	7.3	3.3	570
P4521	0.77	2.62	0.15	0.18	4,538
	4.97	3.9	6.1	2.9	513

Channel	Area In ² (cm ²)	Weight lbs/ft (kg/m)	I In ⁴ (cm ⁴)	s In ³ (cm ³)	Allow. Moment In-lbs (N·m)
P1100	0.418	1.42	0.145	0.162	4,060
	2.69	2.1	6.0	2.6	460
P3000	0.500	1.70	0.120	0.153	3,850
	3.23	2.5	5.0	2.5	430
P4101	0.579	1.97	0.117	0.143	3,610
	3.74	2.9	4.9	2.4	410
P2000	0.342	1.16	0.125	0.140	3,520
	2.21	1.7	5.2	2.3	400
P4001	0.478	1.66	0.104	0.128	3,210
	3.14	2.5	4.3	2.1	360
A3301	0.459	1.56	0.077	0.103	2,590
	2.96	2.3	3.2	1.7	290
P4400	0.424	2.89	0.053	0.092	2,300
	2.74	4.3	2.2	1.5	260
A1000	0.305	1.04	0.061	0.086	2,170
	1.96	1.5	2.5	1.4	250
P3300	0.395	1.34	0.037	0.072	1,800
	2.55	2.0	1.5	1.2	200
P4520	0.384	1.31	0.031	0.064	1,615
	2.48	1.9	1.3	1.0	183
A4001	0.264	0.90	0.037	0.058	1,470
	1.70	1.3	1.5	1.0	170
P6001	0.213	0.73	0.045	0.055	1,400
	1.38	1.1	1.9	0.9	160
P4100	0.290	0.98	0.026	0.054	1,360
	1.87	1.5	1.1	0.9	150
P4000	0.244	0.83	0.023	0.049	1,230
	1.57	1.2	0.9	0.8	140
A3300	0.230	0.78	0.017	0.038	950
	1.48	1.2	0.7	0.6	110
P6000	0.107	0.36	0.009	0.020	510
	0.69	0.5	0.4	0.3	60
P7001	0.148	0.50	0.007	0.018	460
	0.96	0.8	0.3	0.3	50
P7000	0.074	0.25	0.002	0.007	170
	0.48	0.4	0.1	0.1	20

Combinations not shown in catalog are available on special order.
Consult factory for more details.






P1000®

 DF GR HG PG PL

Wt/100 Ft: 189 Lbs (281 kg/100 m)
 Allowable Moment: 5,070 In-Lbs (570 N·m)
 12 Gauge Nominal Thickness .105" (2.7mm)

P1001

 DF GR HG PG PL

Wt/100 Ft: 378 Lbs (562 kg/100 m)
 Allowable Moment: 14,360 In-Lbs (1,620 N·m)
 12 Gauge Nominal Thickness .105" (2.7mm)

P1000 DS





P1000 H3

 GR HG PG PL

P1000 HS

 GR HG PG PL

P1000 KO

 GR PG

Wt/100 Ft: 173 Lbs (257 kg/100 m)

Wt/100 Ft: 175 Lbs (260 kg/100 m)

Wt/100 Ft: 190 Lbs (283 kg/100 m)

Wt/100 Ft: 185 Lbs (275 kg/100 m)




P1000 SL

 GR HG PG PL

P1000 T

 DF GR HG PG PL

P1000 WT


 DF GR HG PG PL

Wt/100 Ft: 185 Lbs (275 kg/100 m)

Wt/100 Ft: 185 Lbs (275 kg/100 m)

Wt/100 Ft: 185 Lbs (275 kg/100 m)

CHANNEL NUTS (REFER TO PAGES 73,74 FOR DETAILS)

 SEE PAGE 73, 74

Channel Finishes: DF, PL, GR, HG, PG, ZD; Standard Lengths: 10' & 20'

P1000 - BEAM LOADING

Span In	Max. Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	1,690	0.06	1,690	1,690	1,690
36	1,130	0.13	1,130	1,130	900
48	850	0.22	850	760	500
60	680	0.35	650	480	320
72	560	0.50	450	340	220
84	480	0.68	330	250	160
96	420	0.89	250	190	130
108	380	1.14	200	150	100
120	340	1.40	160	120	80
144	280	2.00	110	80	60
168	240	2.72	80	60	40
192	210	3.55	60	50	NR
216	190	4.58	50	40	NR
240	170	5.62	40	NR	NR

P1001 - BEAM LOADING

Span In	Max. Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	3,500*	0.02	3,500*	3,500*	3,500*
36	3,190	0.07	3,190	3,190	3,190
48	2,390	0.13	2,390	2,390	2,390
60	1,910	0.20	1,910	1,910	1,620
72	1,600	0.28	1,600	1,600	1,130
84	1,370	0.39	1,370	1,240	830
96	1,200	0.51	1,200	950	630
108	1,060	0.64	1,000	750	500
120	960	0.79	810	610	410
144	800	1.14	560	420	280
168	680	1.53	410	310	210
192	600	2.02	320	240	160
216	530	2.54	250	190	130
240	480	3.16	200	150	100

P1000 - COLUMN LOADING

Unbraced Height In	Max. Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	3,550	10,740	9,890	8,770	7,740
36	3,190	8,910	7,740	6,390	5,310
48	2,770	7,260	6,010	4,690	3,800
60	2,380	5,910	4,690	3,630	2,960
72	2,080	4,840	3,800	2,960	2,400
84	1,860	4,040	3,200	2,480	1,980
96	1,670	3,480	2,750	2,110	1,660
108	1,510	3,050	2,400	1,810	**
120	1,380	2,700	2,110	**	**
144	1,150	2,180	1,660	**	**

P1001 - COLUMN LOADING

Unbraced Height In	Max. Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	6,430	24,280	23,610	22,700	21,820
36	6,290	22,810	21,820	20,650	19,670
48	6,160	21,410	20,300	18,670	16,160
60	6,000	20,210	18,670	15,520	12,390
72	5,620	18,970	16,160	12,390	8,950
84	5,170	16,950	13,630	9,470	6,580
96	4,690	14,890	11,190	7,250	5,040
108	4,170	12,850	8,950	5,730	3,980
120	3,690	10,900	7,250	4,640	**
144	2,930	7,630	5,040	**	**

P1000/P1001 - ELEMENTS OF SECTION

Parameter	P1000	P1001
Area of Section	0.555	In ²
Axis 1-1		
Moment of Inertia (I)	0.185	In ⁴
Section Modulus (S)	0.202	In ³
Radius of Gyration (r)	0.577	In
Axis 2-2		
Moment of Inertia (I)	0.236	In ⁴
Section Modulus (S)	0.290	In ³
Radius of Gyration (r)	0.651	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
2. Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
3. For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"H3" Series.....90%	"DS" Series.....70%
"WT" Series.....85%	
4. Deduct channel weight from the beam loads.
5. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
6. All beam loads are for bending about Axis 1-1.



P1000 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	7.6	1	7.6	7.6	7.6
750	6.1	2	6.1	6.1	5.9
1,000	4.6	4	4.6	4.6	3.3
1,250	3.6	6	3.6	3.2	2.1
1,500	3.1	9	3.0	2.2	1.5
1,750	2.6	12	2.2	1.6	1.1
2,000	2.3	15	1.6	1.2	0.8
2,500	1.8	24	1.1	0.8	0.5
3,000	1.5	34	0.8	0.5	0.4
3,500	1.3	46	0.5	0.4	0.3
4,000	1.2	62	0.4	0.3	0.2
4,500	1.0	78	0.3	0.3	0.2
5,000	0.9	97	0.3	0.2	NR
6,000	0.8	136	0.2	NR	NR

P1001 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	15.6 *	1	15.6 *	15.6 *	15.6 *
750	15.6 *	1	15.6 *	15.6 *	15.6 *
1,000	13.0	2	13.0	13.0	13.0
1,250	10.4	3	10.4	10.4	10.4
1,500	8.7	5	8.7	8.7	7.4
1,750	7.4	7	7.4	7.4	5.5
2,000	6.5	9	6.5	6.3	4.2
2,500	5.2	13	5.2	4.0	2.7
3,000	4.3	19	3.7	2.8	1.9
3,500	3.7	26	2.8	2.0	1.4
4,000	3.2	34	2.1	1.6	1.1
4,500	2.9	44	1.6	1.2	0.8
5,000	2.6	53	1.3	1.0	0.7
6,000	2.2	78	0.9	0.7	0.4

P1000 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	15.8	48.0	44.3	39.4	34.8
750	15.2	44.0	39.4	33.8	28.9
1,000	13.7	37.5	32.0	26.1	21.3
1,250	12.1	31.6	26.1	20.3	16.5
1,500	10.7	26.7	21.3	16.5	13.4
1,750	9.6	22.7	17.8	13.8	11.3
2,000	8.7	19.3	15.3	11.9	9.6
2,250	7.9	16.9	13.4	10.4	8.2
2,500	7.2	15.0	11.9	9.1	**
2,750	6.7	13.5	10.6	8.1	**

P1001 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	28.6	108.2	105.3	101.3	97.4
750	28.3	105.0	101.3	96.5	92.2
1,000	27.8	99.6	95.0	89.7	83.9
1,250	27.3	94.7	89.7	81.7	70.1
1,500	26.8	90.3	83.9	70.1	56.4
1,750	25.4	86.7	74.8	58.6	43.5
2,000	23.9	79.4	65.5	47.7	33.3
2,250	22.2	71.9	56.4	37.9	26.3
2,500	20.4	64.4	47.7	30.7	21.3
2,750	18.5	56.9	39.6	25.4	17.6

P1000/P1001 - ELEMENTS OF SECTION (METRIC)

Parameter	P1000	P1001
Area of Section	3.58 cm ²	7.16 cm ²
Axis 1-1		
Moment of Inertia (I)	7.68 cm ⁴	38.62 cm ⁴
Section Modulus (S)	3.30 cm ³	9.36 cm ³
Radius of Gyration (r)	1.46 cm	2.32 cm
Axis 2-2		
Moment of Inertia (I)	9.80 cm ⁴	19.60 cm ⁴
Section Modulus (S)	4.75 cm ³	9.50 cm ³
Radius of Gyration (r)	1.65 cm	1.65 cm

Notes:

* Load limited by spot weld shear.


** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:
"KO" Series.....95% **"T" Series**85%
"HS" Series90% **"SL" Series**85%
"H3" Series.....90% **"DS" Series.....70%**
"WT" Series.....85%
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P1001 T


DF GR PG



Wt/100 Ft: 321 Lbs (478 kg/100 m)
Allowable Moment 12,200 In-Lbs (1,378 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P1001 A


GR PG



Wt/100 Ft: 378 Lbs (562 kg/100 m)
Allowable Moment 18,640 In-Lbs (2,110 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P1001 B


GR PG




Wt/100 Ft: 378 Lbs (562 kg/100 m)
Allowable Moment 18,640 In-Lbs (2,110 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P1001 C


GR PG




Wt/100 Ft: 378 Lbs (562 kg/100 m)
Allowable Moment 15,950 In-Lbs (1,800 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P1001 3


Wt/100 Ft: 566 Lbs (843 kg/100 m)
Allowable Moment 31,840 In-Lbs (3,600 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P1001 A3


Wt/100 Ft: 566 Lbs (843 kg/100 m)
Allowable Moment 32,770 In-Lbs (3,700 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P1001 B3


Wt/100 Ft: 566 Lbs (843 kg/100 m)
Allowable Moment 37,550 In-Lbs (4,240 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P1001 D3


Wt/100 Ft: 566 Lbs (843 kg/100 m)
Allowable Moment 17,550 In-Lbs (1,980 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P1003


Wt/100 Ft: 333 Lbs (495 kg/100 m)
Allowable Moment 6,240 In-Lbs (700 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P1001 C41

Wt/100 Ft: 755 Lbs (1,124 kg/100 m)
Allowable Moment 28,720 In-Lbs (3,250 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P1001 C3

Wt/100 Ft: 566 Lbs (843 kg/100 m)
Allowable Moment 18,680 In-Lbs (2,110 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P1004 A

Wt/100 Ft: 668 Lbs (994 kg/100 m)
Allowable Moment 41,970 In-Lbs (4,740 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

Channel Finishes: DF, PL, GR, HG, PG, ZD; Standard Lengths: 10' & 20'



Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	7,040*	0.02	7,040*	7,040*	7,040*
36	6,380	0.07	6,380	6,380	6,380
48	4,790	0.13	4,790	4,790	4,790
60	3,830	0.20	3,830	3,830	3,240
72	3,190	0.28	3,190	3,190	2,250
84	2,740	0.39	2,740	2,480	1,660
96	2,390	0.50	2,390	1,900	1,270
108	2,130	0.64	2,000	1,500	1,000
120	1,910	0.78	1,620	1,220	810
144	1,600	1.14	1,130	840	560
168	1,370	1.55	830	620	410
192	1,200	2.02	630	480	320
216	1,060	2.54	500	380	250
240	960	3.16	410	300	200

P1004 A - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	9,100*	0.01	9,100*	9,100*	9,100*
36	9,100*	0.05	9,100*	9,100*	9,100*
48	7,000	0.08	7,000	7,000	7,000
60	5,600	0.13	5,600	5,600	5,600
72	4,660	0.19	4,660	4,660	4,660
84	4,000	0.26	4,000	4,000	3,630
96	3,500	0.34	3,500	3,500	2,780
108	3,110	0.43	3,110	3,110	2,200
120	2,800	0.52	2,800	2,670	1,780
144	2,330	0.75	2,330	1,850	1,230
168	2,000	1.03	1,810	1,360	910
192	1,750	1.34	1,390	1,040	690
216	1,550	1.69	1,100	820	550
240	1,400	2.10	890	670	440

P1001 C41 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	12,690	46,920	44,980	42,360	39,890
36	12,250	42,680	39,890	36,660	34,050
48	11,820	38,740	35,720	32,640	30,430
60	11,470	35,500	32,640	29,980	28,220
72	11,180	32,970	30,430	28,220	26,820
84	10,900	31,040	28,840	27,010	24,870
96	10,580	29,570	27,680	26,170	19,840
108	10,310	28,440	26,820	22,310	15,670
120	10,070	27,560	26,170	18,280	12,700
144	8,740	26,320	19,840	12,700	8,820
168	7,360	21,890	14,570	9,330	**

P1004 A - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	11,420	36,800	33,890	30,440	27,600
36	10,600	30,840	27,600	24,400	22,160
48	9,860	26,400	23,560	21,060	19,470
60	9,160	23,370	21,060	19,160	18,020
72	8,610	21,310	19,470	18,020	17,140
84	8,170	19,890	18,410	17,260	15,240
96	7,790	18,890	17,670	16,760	11,670
108	7,460	18,160	17,140	13,280	9,220
120	7,150	17,590	16,760	10,750	7,470
144	5,660	16,840	11,670	7,470	**
168	4,520	12,990	8,570	**	**

P1001 C41/ P1004 A - ELEMENTS OF SECTION

Parameter	P1001 C41	P1004 A
Area of Section	2.221	In ²
Axis 1-1		
Moment of Inertia (I)	1.856	In ⁴
Section Modulus (S)	1.142	In ³
Radius of Gyration (r)	0.914	In
Axis 2-2		
Moment of Inertia (I)	2.408	In ⁴
Section Modulus (S)	1.482	In ³
Radius of Gyration (r)	1.041	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
2. Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
3. For pierced channel, multiply beam loads by the following factor:
 "KO" Series.....95% "T" Series85%
 "HS" Series90% "SL" Series85%
 "WT" Series.....85%
4. Deduct channel weight from the beam loads.
5. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
6. All beam loads are for bending about Axis 1-1.

P1001 C41 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	31.3 *	1	31.3 *	31.3 *	31.3 *
750	31.3 *	1	31.3 *	31.3 *	31.3 *
1,000	26.0	2	26.0	26.0	26.0
1,250	20.8	3	20.8	20.8	20.8
1,500	17.3	5	17.3	17.3	14.9
1,750	14.8	7	14.8	14.8	10.9
2,000	13.0	9	13.0	12.6	8.4
2,500	10.4	13	10.4	8.1	5.4
3,000	8.7	19	7.4	5.6	3.7
3,500	7.4	26	5.5	4.1	2.8
4,000	6.5	34	4.2	3.2	2.1
4,500	5.8	44	3.3	2.5	1.6
5,000	5.2	54	2.7	2.0	1.3
6,000	4.3	77	1.9	1.4	0.9

P1004 A - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	40.5 *	1	40.5 *	40.5 *	40.5 *
750	40.5 *	1	40.5 *	40.5 *	40.5 *
1,000	37.9	2	37.9	37.9	37.9
1,250	30.3	3	30.3	30.3	30.3
1,500	25.3	4	25.3	25.3	25.3
1,750	21.7	6	21.7	21.7	21.7
2,000	18.9	9	18.9	18.9	18.4
2,500	15.2	13	15.2	15.2	11.7
3,000	12.6	18	12.6	12.2	8.2
3,500	10.9	23	10.9	9.0	6.0
4,000	9.5	29	9.2	6.9	4.6
4,500	8.5	36	7.2	5.4	3.6
5,000	7.6	52	5.9	4.4	2.9
6,000	6.3	77	4.1	3.1	2.0

P1001 C41 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	56.5	209.3	200.8	189.3	178.4
750	55.6	200.1	189.3	175.8	164.1
1,000	53.9	184.7	171.7	157.3	146.1
1,250	52.4	170.7	157.3	143.8	134.1
1,500	51.1	158.9	146.1	134.1	126.1
1,750	50.0	149.3	137.6	127.3	120.7
2,000	49.2	141.5	131.1	122.3	116.8
2,250	47.9	135.4	126.1	118.6	101.9
2,500	46.8	130.4	122.3	114.5	83.9
2,750	45.9	126.4	119.2	98.8	69.4

P1004 A - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	50.9	164.6	151.8	136.5	123.8
750	49.1	150.8	136.5	121.1	109.5
1,000	46.3	130.9	116.9	103.4	94.3
1,250	43.5	115.8	103.4	92.6	85.8
1,500	40.9	104.8	94.3	85.8	80.6
1,750	38.9	96.8	88.1	81.3	77.0
2,000	37.1	91.0	83.7	78.1	74.8
2,250	35.7	86.6	80.6	75.8	60.9
2,500	34.3	83.3	78.1	71.1	49.4
2,750	33.1	80.7	76.2	58.8	40.8

P1001 C41/ P1004 A - ELEMENTS OF SECTION (METRIC)

Parameter	P1001 C41	P1004 A
Area of Section	14.33	cm ²
Axis 1-1		
Moment of Inertia (I)	77.24	cm ⁴
Section Modulus (S)	18.71	cm ³
Radius of Gyration (r)	2.32	cm
Axis 2-2		
Moment of Inertia (I)	100.24	cm ⁴
Section Modulus (S)	24.29	cm ³
Radius of Gyration (r)	2.64	cm

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.


- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.



P1100

GR PG




Wt/100 Ft: 142 Lbs (211 kg/100 m)
 Allowable Moment 4,060 In-Lbs (460 N·m)
 14 Gauge Nominal Thickness .075" (1.9mm)

P1101 A

P1101


GR PG



Wt/100 Ft: 284 Lbs (423 kg/100 m)
 Allowable Moment 11,340 In-Lbs (1,280 N·m)
 14 Gauge Nominal Thickness .075" (1.9mm)

P1101 B


P1101 B



Wt/100 Ft: 284 Lbs (423 kg/100 m)
 Allowable Moment 14,000 In-Lbs (1,580 N·m)
 14 Gauge Nominal Thickness .075" (1.9mm)

P1101 C

GR PG



Wt/100 Ft: 284 Lbs (423 kg/100 m)
 Allowable Moment 12,330 In-Lbs (1,390 N·m)
 14 Gauge Nominal Thickness .075" (1.9mm)


P1100 HS

GR PG


P1100 KO

GR PG

9/16" (14.3) Dia. Holes
 1 7/8" (47.6) on Center



7/8" (22.2) Knockouts
 6" (152.4) on Center



P1100 SL

GR PG


P1100 T

GR PG

P1100 WT


DF GR HG PG PL

Slots are
 3" (76.2) x 13/32" (10.3)
 4" (101.6) on Center




Wt/100 Ft: 136 Lbs (202 kg/100 m)

Slots are
 1 1/8" (28.6) x 9/16" (14.3)
 2" (50.8) on Center



Wt/100 Ft: 136 Lbs (202 kg/100 m)

Slots are
 2" (50.8) x 1 1/16" (17.5)
 3" (76.2) on Center



Wt/100 Ft: 136 Lbs (202 kg/100 m)

CHANNEL NUTS (REFER TO PAGES 73,74 FOR DETAILS)

SEE PAGE 73, 74



P1006-0832
 P1006-1024
 P1006-1420
 P1007
 P1008
 P1009
 P1010



P1008T
 P1006T1420
 P1010T



P1024
 P1012S
 P1023S
 P1012
 P1023
 P1024S



P3006-0832
 P3006-1024
 P3006-1420
 P3007
 P3008
 P3009
 P3010



P3016-0632
 P3016-0832
 P3016-1024
 P3016-1420

Channel Finishes: DF, PL, GR, HG, PG, ZD; Standard Lengths: 10' & 20'

P1100 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	1,350	0.06	1,350	1,350	1,350
36	900	0.13	900	900	700
48	680	0.23	680	590	400
60	540	0.36	510	380	250
72	450	0.51	350	260	180
84	390	0.70	260	190	130
96	340	0.92	200	150	100
108	300	1.15	160	120	80
120	270	1.42	130	90	60
144	230	2.09	90	70	40
168	190	2.75	60	50	30
192	170	3.67	50	40	NR
216	150	4.61	40	30	NR
240	140	5.90	30	NR	NR

P1101 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	2,180*	0.02	2,180*	2,180*	2,180*
36	2,180*	0.06	2,180*	2,180*	2,180*
48	1,890	0.13	1,890	1,890	1,890
60	1,510	0.20	1,510	1,510	1,280
72	1,260	0.28	1,260	1,260	890
84	1,080	0.39	1,080	980	650
96	950	0.51	950	750	500
108	840	0.64	790	590	400
120	760	0.79	640	480	320
144	630	1.13	440	330	220
168	540	1.54	330	250	160
192	470	2.00	250	190	130
216	420	2.55	200	150	100
240	380	3.16	160	120	80

P1100 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	2,800	8,040	7,330	6,360	5,430
36	2,410	6,480	5,430	4,190	3,210
48	1,940	4,990	3,830	2,760	2,160
60	1,550	3,740	2,760	2,050	1,640
72	1,290	2,860	2,160	1,640	1,320
84	1,100	2,310	1,780	1,370	1,110
96	950	1,950	1,520	1,180	950
108	840	1,690	1,320	1,030	**
120	760	1,490	1,180	**	**
144	630	1,210	950	**	**

P1101 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	5,010	18,250	17,700	16,880	16,030
36	4,860	16,990	16,030	14,770	13,620
48	4,700	15,610	14,380	12,930	11,750
60	4,480	14,280	12,930	11,490	9,290
72	4,210	13,100	11,750	9,290	6,700
84	3,880	12,090	10,220	7,090	4,930
96	3,480	11,170	8,390	5,430	3,770
108	3,060	9,640	6,700	4,290	2,980
120	2,680	8,170	5,430	3,480	**
144	2,090	5,710	3,770	**	**

P1100/P1101 - ELEMENTS OF SECTION

Parameter	P1100	P1101
Area of Section	0.418	In ²
Axis 1-1		
Moment of Inertia (I)	0.145	In ⁴
Section Modulus (S)	0.162	In ³
Radius of Gyration (r)	0.589	In
Axis 2-2		
Moment of Inertia (I)	0.176	In ⁴
Section Modulus (S)	0.217	In ³
Radius of Gyration (r)	0.650	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.



P1100 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	6.1	1	6.1	6.1	6.1
750	4.9	2	4.9	4.9	4.7
1,000	3.7	4	3.7	3.7	2.6
1,250	2.9	6	2.9	2.5	1.7
1,500	2.4	9	2.3	1.7	1.2
1,750	2.1	12	1.7	1.3	0.8
2,000	1.8	15	1.3	1.0	0.7
2,500	1.5	24	0.8	0.6	0.4
3,000	1.2	36	0.6	0.4	0.3
3,500	1.1	49	0.4	0.3	0.2
4,000	0.9	64	0.3	0.3	0.2
4,500	0.8	77	0.3	0.2	0.1
5,000	0.8	100	0.2	0.2	NR
6,000	0.6	143	0.1	NR	NR

P1101 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	9.7 *	0	9.7 *	9.7 *	9.7 *
750	9.7 *	1	9.7 *	9.7 *	9.7 *
1,000	9.7 *	2	9.7 *	9.7 *	9.7 *
1,250	8.2	3	8.2	8.2	8.2
1,500	6.9	5	6.9	6.9	5.9
1,750	5.9	7	5.9	5.9	4.3
2,000	5.1	9	5.1	5.0	3.3
2,500	4.1	13	4.1	3.2	2.1
3,000	3.4	19	2.9	2.2	1.5
3,500	2.9	26	2.2	1.6	1.1
4,000	2.6	35	1.6	1.2	0.8
4,500	2.3	43	1.3	1.0	0.7
5,000	2.0	54	1.1	0.8	0.5
6,000	1.7	77	0.8	0.5	0.4

P1100 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	12.5	35.9	32.9	28.6	24.5
750	11.8	32.6	28.6	23.5	19.0
1,000	10.1	26.9	22.0	16.4	12.5
1,250	8.5	21.6	16.4	11.8	9.3
1,500	7.0	17.0	12.5	9.3	7.4
1,750	6.0	13.5	10.1	7.7	6.2
2,000	5.2	11.2	8.6	6.5	5.3
2,250	4.6	9.6	7.4	5.7	4.7
2,500	4.1	8.4	6.5	5.1	**
2,750	3.7	7.5	5.9	4.5	**

P1101 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	22.3	81.4	79.0	75.4	71.7
750	22.0	78.7	75.4	70.7	66.1
1,000	21.4	73.8	69.2	63.3	58.0
1,250	20.8	68.8	63.3	56.8	51.6
1,500	20.0	64.0	58.0	51.6	42.3
1,750	19.0	59.5	53.5	44.0	32.6
2,000	18.0	55.6	49.2	35.7	25.0
2,250	16.6	52.3	42.3	28.4	19.7
2,500	15.1	48.3	35.7	23.0	16.0
2,750	13.6	42.7	29.7	19.0	13.2

P1100/P1101 - ELEMENTS OF SECTION (METRIC)

Parameter	P1100	P1101
Area of Section	2.69	cm ²
Axis 1-1		
Moment of Inertia (I)	6.03	cm ⁴
Section Modulus (S)	2.65	cm ³
Radius of Gyration (r)	1.50	cm
Axis 2-2		
Moment of Inertia (I)	7.34	cm ⁴
Section Modulus (S)	3.56	cm ³
Radius of Gyration (r)	1.65	cm


Notes:

* Load limited by spot weld shear.


** KL/r > 200

NR = Not Recommended.


- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:
 "KO" Series.....95% "T" Series85%
 "HS" Series90% "SL" Series85%
 "WT" Series.....85%
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P2000**GR PG**


Wt/100 Ft: 116 Lbs (173 kg/100 m)
Allowable Moment 3,520 In-Lbs (400 N·m)
16 Gauge Nominal Thickness .060" (1.5mm)

P2001 A


Wt/100 Ft: 232 Lbs (346 kg/100 m)
Allowable Moment 11,660 In-Lbs (1,320 N·m)
16 Gauge Nominal Thickness .060" (1.5mm)

P2001 C


Wt/100 Ft: 232 Lbs (346 kg/100 m)
Allowable Moment 10,350 In-Lbs (1,170 N·m)
16 Gauge Nominal Thickness .060" (1.5mm)

P2000 SL**GR PG**

Wt/100 Ft: 113 Lbs (168 kg/100 m)

P2000 T**GR PG**

Wt/100 Ft: 113 Lbs (168 kg/100 m)

P2000 WT**DF GR HG PG PL**

Wt/100 Ft: 113 Lbs (168 kg/100 m)

CHANNEL NUTS (REFER TO PAGES 73,74 FOR DETAILS)**SEE PAGE 73, 74**

- P1006-0832**
P1006-1024
P1006-1420
P1007
P1008
P1009
P1010



- P1008T**
P1006T1420
P1010T



- P1024**
P1012S
P1023S



- P3006-0832**
P3006-1024
P3006-1420
P3007
P3008
P3009
P3010



- P3016-0632**
P3016-0832
P3016-1024
P3016-1420

Channel Finishes: PL, GR, HG, PG, ZD; Standard Lengths: 10' & 20'



P2000 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	1,170	0.06	1,170	1,170	1,170
36	780	0.13	780	780	610
48	590	0.23	590	510	340
60	470	0.36	440	330	220
72	390	0.52	300	230	150
84	340	0.71	220	170	110
96	290	0.91	170	130	90
108	260	1.16	130	100	70
120	230	1.41	110	80	50
144	200	2.12	80	60	40
168	170	2.86	60	40	30
192	150	3.76	40	30	20
216	130	4.64	30	30	NR
240	120	5.88	30	NR	NR

P2001 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	1,610*	0.02	1,610*	1,610*	1,610*
36	1,610*	0.05	1,610*	1,610*	1,610*
48	1,600	0.13	1,600	1,600	1,600
60	1,280	0.20	1,280	1,280	1,080
72	1,060	0.28	1,060	1,060	750
84	910	0.38	910	830	550
96	800	0.51	800	630	420
108	710	0.64	670	500	330
120	640	0.79	540	410	270
144	530	1.13	380	280	190
168	460	1.56	280	210	140
192	400	2.02	210	160	110
216	350	2.52	170	130	80
240	320	3.16	140	100	70

P2000 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	2,400	6,650	6,080	5,280	4,470
36	2,050	5,380	4,470	3,370	2,500
48	1,600	4,090	3,040	2,100	1,590
60	1,230	2,960	2,100	1,500	1,160
72	970	2,190	1,590	1,160	910
84	790	1,720	1,270	950	760
96	660	1,410	1,060	800	650
108	570	1,200	910	700	**
120	510	1,040	800	620	**
144	420	830	650	**	**

P2001 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	4,200	15,030	14,600	13,940	13,220
36	4,070	14,030	13,220	12,090	10,990
48	3,920	12,850	11,720	10,290	9,040
60	3,700	11,630	10,290	8,760	7,530
72	3,410	10,460	9,040	7,530	5,740
84	3,140	9,410	7,990	6,080	4,220
96	2,890	8,490	7,120	4,650	3,230
108	2,530	7,700	5,740	3,680	2,550
120	2,210	6,950	4,650	2,980	**
144	1,690	4,890	3,230	**	**

P2000/P2001 - ELEMENTS OF SECTION

Parameter	P2000	P2001
Area of Section	0.342	In ²
Axis 1-1		
Moment of Inertia (I)	0.125	In ⁴
Section Modulus (S)	0.140	In ³
Radius of Gyration (r)	0.604	In
Axis 2-2		
Moment of Inertia (I)	0.151	In ⁴
Section Modulus (S)	0.186	In ³
Radius of Gyration (r)	0.665	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:
 "KO" Series.....95% "T" Series85%
 "HS" Series90% "SL" Series85%
 "WT" Series.....85%
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P2000 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	5.3	1	5.3	5.3	5.3
750	4.2	2	4.2	4.2	4.0
1,000	3.2	4	3.2	3.2	2.3
1,250	2.5	6	2.5	2.2	1.4
1,500	2.1	9	2.0	1.5	1.0
1,750	1.8	12	1.5	1.1	0.8
2,000	1.6	16	1.1	0.8	0.6
2,500	1.3	25	0.7	0.5	0.4
3,000	1.1	36	0.5	0.4	0.3
3,500	0.9	47	0.4	0.3	0.2
4,000	0.8	63	0.3	0.2	0.1
4,500	0.7	80	0.2	0.2	0.1
5,000	0.6	96	0.2	0.1	0.1
6,000	0.5	142	0.1	NR	NR

P2001 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	7.2 *	0	7.2 *	7.2 *	7.2 *
750	7.2 *	1	7.2 *	7.2 *	7.2 *
1,000	7.2 *	2	7.2 *	7.2 *	7.2 *
1,250	6.9	3	6.9	6.9	6.9
1,500	5.8	5	5.8	5.8	5.0
1,750	4.9	7	4.9	4.9	3.6
2,000	4.3	9	4.3	4.2	2.8
2,500	3.5	13	3.5	2.7	1.8
3,000	2.9	19	2.5	1.9	1.2
3,500	2.5	27	1.8	1.4	0.9
4,000	2.2	35	1.4	1.1	0.7
4,500	1.9	43	1.1	0.8	0.5
5,000	1.7	54	0.9	0.7	0.4
6,000	1.4	76	0.6	0.4	0.3

P2000 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	10.7	29.8	27.3	23.8	20.2
750	10.1	27.0	23.8	19.3	15.3
1,000	8.5	22.3	18.0	12.9	9.6
1,250	6.9	17.6	12.9	9.0	6.8
1,500	5.6	13.5	9.6	6.8	5.2
1,750	4.6	10.5	7.6	5.5	4.3
2,000	3.8	8.5	6.2	4.6	3.6
2,250	3.3	7.1	5.2	4.0	3.2
2,500	2.8	6.1	4.6	3.5	2.8
2,750	2.5	5.3	4.1	3.1	**

P2001 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	18.7	67.0	65.1	62.2	59.1
750	18.4	64.9	62.2	58.3	54.2
1,000	17.9	61.0	56.9	51.5	46.3
1,250	17.3	56.6	51.5	45.0	39.5
1,500	16.5	52.1	46.3	39.5	34.0
1,750	15.5	47.9	41.6	34.8	27.9
2,000	14.5	43.9	37.5	30.4	21.3
2,250	13.6	40.2	34.0	24.3	16.9
2,500	12.5	37.0	30.4	19.7	13.7
2,750	11.3	34.2	25.4	16.3	11.3

P2000/P2001 - ELEMENTS OF SECTION (METRIC)

Parameter	P2000		P2001	
Area of Section	2.21	cm ²	4.41	cm ²
Axis 1-1				
Moment of Inertia (I)	5.19	cm ⁴	25.74	cm ⁴
Section Modulus (S)	2.29	cm ³	6.24	cm ³
Radius of Gyration (r)	1.53	cm	2.42	cm
Axis 2-2				
Moment of Inertia (I)	6.29	cm ⁴	12.58	cm ⁴
Section Modulus (S)	3.05	cm ³	6.10	cm ³
Radius of Gyration (r)	1.69	cm	1.69	cm

Notes:




- * Load limited by spot weld shear.
- ** KL/r > 200
- NR = Not Recommended.
- 1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- 2. Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to page 62 for reduction factors for unbraced lengths.
- 3. For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
- 4. Deduct channel weight from the beam loads.
- 5. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- 6. All beam loads are for bending about Axis 1-1.



P3000




GR PG



Wt/100 Ft: 170 Lbs (253 kg/100 m)
 Allowable Moment 3,840 In-Lbs (430 N·m)
 12 Gauge Nominal Thickness .105" (2.7mm)

P3001

GR PG




Wt/100 Ft: 340 Lbs (506 kg/100 m)
 Allowable Moment 10,810 In-Lbs (1,220 N·m)
 12 Gauge Nominal Thickness .105" (2.7mm)

P3000 HS

GR PG

9/16" (14.3) Dia. Holes
 1 7/8" (47.6) on Center




Wt/100 Ft: 165 Lbs (246 kg/100 m)

P3000 KO

GR PG

7/8" (22.2) Knockouts
 6" (152.4) on Center




Wt/100 Ft: 170 Lbs (253 kg/100 m)

P3000 SL

GR PG

Slots are
 3" (76.2) x 1 13/32" (10.3)
 4" (101.6) on Center




Wt/100 Ft: 165 Lbs (246 kg/100 m)

P3000 T

GR PG

Slots are
 1 1/8" (28.6) x 9/16" (14.3)
 2" (50.8) on Center




Wt/100 Ft: 165 Lbs (246 kg/100 m)

P3000 WT

DF GR HG PG PL

Slots are
 2" (50.8) x 1 1/16" (17.5)
 3" (76.2) on Center



Wt/100 Ft: 165 Lbs (246 kg/100 m)

CHANNEL NUTS (REFER TO PAGES 73,74 FOR DETAILS)

SEE PAGE 73, 74



P1006-0832
 P1006-1024
 P1006-1420
 P1007
 P1008
 P1009
 P1010



P1008T
 P1006T1420
 P1010T



P1024
 P1012S
 P1023S
 P1012
 P1023
 P1024S



P3006-0832
 P3006-1024
 P3006-1420
 P3007
 P3008
 P3009
 P3010



P3016-0632
 P3016-0832
 P3016-1024
 P3016-1420

Channel Finishes: PL, GR, HG, PG, ZD; Standard Lengths: 10' & 20'

P3000 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	1,280	0.07	1,280	1,280	1,280
36	850	0.15	850	850	580
48	640	0.26	640	490	330
60	510	0.41	420	310	210
72	430	0.59	290	220	150
84	370	0.81	210	160	110
96	320	1.05	160	120	80
108	280	1.30	130	100	60
120	260	1.66	100	80	50
144	210	2.32	70	50	40
168	180	3.15	50	40	30
192	160	4.18	40	30	NR
216	140	5.21	NR	NR	NR
240	130	6.64	NR	NR	NR

P3001 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	2,960*	0.03	2,960*	2,960*	2,960*
36	2,400	0.08	2,400	2,400	2,400
48	1,800	0.15	1,800	1,800	1,610
60	1,440	0.23	1,440	1,440	1,030
72	1,200	0.33	1,200	1,080	720
84	1,030	0.46	1,030	790	530
96	900	0.59	810	610	400
108	800	0.75	640	480	320
120	720	0.93	520	390	260
144	600	1.34	360	270	180
168	510	1.81	260	200	130
192	450	2.38	200	150	100
216	400	3.01	160	120	80
240	360	3.72	130	100	NR

P3000 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	3,180	9,690	8,980	8,050	7,210
36	2,920	8,160	7,210	6,130	5,240
48	2,590	6,820	5,810	4,730	3,860
60	2,300	5,740	4,730	3,690	2,990
72	2,040	4,850	3,860	2,990	2,270
84	1,830	4,100	3,240	2,400	**
96	1,650	3,530	2,770	1,840	**
108	1,450	3,080	2,270	**	**
120	1,250	2,710	1,840	**	**

P3001 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	5,740	21,780	21,200	20,430	19,720
36	5,620	20,520	19,720	18,830	17,680
48	5,520	19,400	18,570	16,570	14,260
60	5,330	18,510	16,570	13,670	10,810
72	5,030	16,850	14,260	10,810	7,730
84	4,630	14,990	11,930	8,180	5,680
96	4,190	13,090	9,720	6,260	4,350
108	3,720	11,230	7,730	4,950	**
120	3,300	9,460	6,260	4,010	**
144	2,620	6,590	4,350	**	**

P3000/P3001 - ELEMENTS OF SECTION

Parameter	P3000	P3001
Area of Section	0.500	In ²
Axis 1-1		1.000
Moment of Inertia (I)	0.120	In ⁴
Section Modulus (S)	0.153	In ³
Radius of Gyration (r)	0.489	In
Axis 2-2		0.769
Moment of Inertia (I)	0.203	In ⁴
Section Modulus (S)	0.250	In ³
Radius of Gyration (r)	0.638	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.



P3000 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	5.8	2	5.8	5.8	5.8
750	4.6	3	4.6	4.6	3.8
1,000	3.5	4	3.5	3.2	2.2
1,250	2.8	7	2.8	2.1	1.4
1,500	2.3	10	1.9	1.4	1.0
1,750	2.0	14	1.4	1.1	0.7
2,000	1.7	18	1.1	0.8	0.5
2,500	1.4	28	0.7	0.5	0.4
3,000	1.2	40	0.5	0.4	0.2
3,500	1.0	54	0.4	0.3	0.2
4,000	0.9	73	0.3	0.2	0.1
4,500	0.8	89	0.2	0.2	NR
5,000	0.7	115	0.2	0.1	NR
6,000	0.6	161	NR	NR	NR

P3001 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	13.2 *	1	13.2 *	13.2 *	13.2 *
750	13.0	1	13.0	13.0	13.0
1,000	9.8	3	9.8	9.8	9.8
1,250	7.8	4	7.8	7.8	6.9
1,500	6.5	6	6.5	6.5	4.8
1,750	5.6	8	5.6	5.2	3.5
2,000	4.9	10	4.9	4.0	2.7
2,500	3.9	16	3.4	2.6	1.7
3,000	3.2	23	2.4	1.8	1.2
3,500	2.8	31	1.7	1.3	0.9
4,000	2.4	41	1.3	1.0	0.7
4,500	2.2	52	1.1	0.8	0.5
5,000	2.0	64	0.8	0.6	0.4
6,000	1.6	92	0.6	0.4	0.3

P3000 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	14.2	43.3	40.2	36.1	32.4
750	13.6	39.9	36.1	31.5	27.6
1,000	12.5	34.5	30.2	25.3	21.3
1,250	11.4	29.8	25.3	20.5	16.7
1,500	10.3	25.8	21.3	16.7	13.6
1,750	9.4	22.5	18.1	14.0	11.0
2,000	8.5	19.6	15.5	11.9	8.5
2,250	7.8	17.2	13.6	9.6	**
2,500	7.2	15.3	11.9	**	**
2,750	6.4	13.7	10.1	**	**

P3001 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	25.5	97.1	94.5	91.1	88.0
750	25.3	94.3	91.1	87.3	84.0
1,000	24.9	89.8	86.1	82.2	74.5
1,250	24.6	85.8	82.2	72.4	61.8
1,500	23.8	82.6	74.5	61.8	49.2
1,750	22.8	77.0	66.1	51.3	37.5
2,000	21.4	70.3	57.6	41.3	28.7
2,250	19.9	63.4	49.2	32.7	22.7
2,500	18.2	56.5	41.3	26.5	18.4
2,750	16.5	49.8	34.2	21.9	**

P3000/P3001 - ELEMENTS OF SECTION (METRIC)

Parameter	P3000		P3001	
Area of Section	3.23	cm ²	6.45	cm ²
Axis 1-1				
Moment of Inertia (I)	4.97	cm ⁴	24.61	cm ⁴
Section Modulus (S)	2.51	cm ³	7.05	cm ³
Radius of Gyration (r)	1.24	cm	1.95	cm
Axis 2-2				
Moment of Inertia (I)	8.47	cm ⁴	16.93	cm ⁴
Section Modulus (S)	4.10	cm ³	8.20	cm ³
Radius of Gyration (r)	1.62	cm	1.62	cm




Notes:

* Load limited by spot weld shear.




** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:
 "KO" Series.....95% "T" Series85%
 "HS" Series90% "SL" Series85%
 "WT" Series.....85%
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P3300**DF GR PG PL**


Wt/100 Ft: 134 Lbs (200 kg/100 m)
Allowable Moment 1,800 In-Lbs (200 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P3301**DF GR PG**

Wt/100 Ft: 269 Lbs (400 kg/100 m)
Allowable Moment 5,060 In-Lbs (570 N•m)
12 Gauge Nominal Thickness .105" (2.7mm)

P3300 HS**GR PG**


$\frac{9}{16}$ " (14.3) Dia. Holes
1 $\frac{1}{8}$ " (47.6) on Center



Wt/100 Ft: 130 Lbs (193 kg/100 m)

P3300 SL**GR PG**


Slots are
3" (76.2) x $\frac{13}{32}$ " (10.3)
4" (101.6) on Center



Wt/100 Ft: 130 Lbs (193 kg/100 m)

P3300 T**DF GR PG**


Slots are
1 $\frac{1}{8}$ " (28.6) x $\frac{9}{16}$ " (14.3)
2" (50.8) on Center



Wt/100 Ft: 130 Lbs (193 kg/100 m)

P3300 WT**DF GR HG PG PL**

Slots are
2" (50.8) x $\frac{11}{16}$ " (17.5)
3" (76.2) on Center



Wt/100 Ft: 130 Lbs (193 kg/100 m)

CHANNEL NUTS (REFER TO PAGES 73,74 FOR DETAILS)**SEE PAGE 73, 74**

P4006-0832
P4006-1024
P4006-1420
P4007
P4008
P4009
P4010



P4010T



P4012
P4023



P3006-0832
P3006-1024
P3006-1420
P3007
P3008
P3009
P3013



P3016-0632
P3016-0832
P3016-1024
P3016-1420



P3300 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	600	0.10	600	600	400
36	400	0.22	360	270	180
48	300	0.40	200	150	100
60	240	0.62	130	100	60
72	200	0.89	90	70	40
84	170	1.20	70	50	30
96	150	1.59	50	40	30
108	130	1.96	40	30	20
120	120	2.48	30	20	20

P3301 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	1,690	0.06	1,690	1,690	1,690
36	1,130	0.13	1,130	1,130	860
48	840	0.23	840	720	480
60	680	0.37	620	460	310
72	560	0.52	430	320	210
84	480	0.71	310	240	160
96	420	0.93	240	180	120
108	380	1.20	190	140	100
120	340	1.47	150	120	80
144	280	2.09	110	80	50

P3300 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	2,360	7,740	7,260	6,350	5,390
36	2,120	6,470	5,390	3,990	2,810
48	1,760	4,910	3,550	2,270	1,580
60	1,380	3,440	2,270	1,460	**
72	1,080	2,390	1,580	**	**

P3301 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	4,290	16,990	16,580	15,770	14,720
36	4,150	15,890	14,720	12,980	11,120
48	3,940	14,160	12,360	9,880	7,510
60	3,650	12,210	9,880	6,940	4,820
72	3,270	10,190	7,510	4,820	3,350
84	2,800	8,220	5,530	3,540	**
96	2,410	6,420	4,240	**	**
108	2,080	5,070	3,350	**	**

P3300/P3301 - ELEMENTS OF SECTION

Parameter	P3300	P3301	
Area of Section	0.395	In ²	0.790
Axis 1-1			In ²
Moment of Inertia (I)	0.037	In ⁴	0.176
Section Modulus (S)	0.072	In ³	0.201
Radius of Gyration (r)	0.306	In	0.472
Axis 2-2			In
Moment of Inertia (I)	0.143	In ⁴	0.285
Section Modulus (S)	0.176	In ³	0.351
Radius of Gyration (r)	0.601	In	0.601

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P3300 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	2.7	2	2.7	2.7	1.9
750	2.2	4	2.2	1.8	1.2
1,000	1.6	7	1.3	1.0	0.7
1,250	1.3	10	0.8	0.6	0.4
1,500	1.1	15	0.6	0.4	0.3
1,750	0.9	21	0.4	0.3	0.2
2,000	0.8	27	0.3	0.3	0.2
2,500	0.7	43	0.2	0.2	0.1
3,000	0.5	60	0.1	0.1	0.1
3,500	0.4	79	0.1	0.1	NR

P3301 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	7.6	1	7.6	7.6	7.6
750	6.1	2	6.1	6.1	5.6
1,000	4.6	4	4.6	4.6	3.2
1,250	3.6	6	3.6	3.1	2.0
1,500	3.1	9	2.8	2.1	1.4
1,750	2.6	12	2.1	1.6	1.0
2,000	2.3	16	1.6	1.2	0.8
2,500	1.8	25	1.0	0.8	0.5
3,000	1.5	36	0.7	0.5	0.4
3,500	1.3	48	0.5	0.4	0.3
4,000	1.2	65	0.4	0.3	0.2

P3300 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	10.5	34.6	32.6	28.6	24.4
750	10.1	32.3	28.6	23.3	18.2
1,000	9.1	26.9	21.6	15.0	10.5
1,250	7.6	21.2	15.0	9.6	6.7
1,500	6.3	15.8	10.5	6.7	**
1,750	5.1	11.6	7.6	**	**

P3301 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kg
600	19.1	75.7	73.9	70.5	66.0
750	18.9	73.8	70.5	64.7	58.4
1,000	18.2	68.6	62.7	53.9	44.8
1,250	17.4	62.1	53.9	42.6	31.9
1,500	16.4	55.0	44.8	31.9	22.2
1,750	15.0	47.6	36.0	23.4	16.3
2,000	13.3	40.3	28.0	17.9	**
2,250	11.8	33.4	22.2	14.1	**
2,500	10.4	27.2	17.9	**	**
2,750	9.2	22.5	14.8	**	**

P3300/P3301 - ELEMENTS OF SECTION (METRIC)

Parameter	P3300	P3301
Area of Section	2.55 cm ²	5.10 cm ²
Axis 1-1		
Moment of Inertia (I)	1.54 cm ⁴	7.33 cm ⁴
Section Modulus (S)	1.18 cm ³	3.30 cm ³
Radius of Gyration (r)	0.78 cm	1.20 cm
Axis 2-2		
Moment of Inertia (I)	5.94 cm ⁴	11.87 cm ⁴
Section Modulus (S)	2.88 cm ³	5.75 cm ³
Radius of Gyration (r)	1.53 cm	1.53 cm

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.


- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.




P4000

GR HG PG GR



Wt/100 Ft: 83 Lbs (123 kg/100 m)
 Allowable Moment 1,230 In-Lbs (140 N·m)
 16 Gauge Nominal Thickness .060" (1.5mm)


P4003



Wt/100 Ft: 248 Lbs (370 kg/100 m)
 Allowable Moment 8,600 In-Lbs (970 N·m)
 16 Gauge Nominal Thickness .060" (1.5mm)

P4000 HS


GR PG



Wt/100 Ft: 79 Lbs (118 kg/100 m)

P4000 SL

GR PG



Wt/100 Ft: 79 Lbs (118 kg/100 m)

CHANNEL NUTS (REFER TO PAGES 73,74 FOR DETAILS)



- P4006-0832
- P4006-1024
- P4006-1420
- P4007
- P4008
- P4009
- P4010



P4010T



- P4012
- P4023



- P3006-0832
- P3006-1024
- P3006-1420
- P3007
- P3008
- P3009
- P3013



- P3016-0632
- P3016-0832
- P3016-1024
- P3016-1420

SEE PAGE 73, 74

Channel Finishes: PL, GR, HG, PG, ZD; Standard Lengths: 10' & 20'

P4000 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	410	0.11	410	370	250
36	270	0.24	220	170	110
48	200	0.43	120	90	60
60	160	0.67	80	60	40
72	140	1.01	60	40	30
84	120	1.38	40	30	20
96	100	1.72	30	20	20
108	90	2.20	20	20	10
120	80	2.68	20	10	10

P4001 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	810*	0.05	810*	810*	810*
36	710	0.14	710	710	500
48	540	0.25	540	430	280
60	430	0.40	360	270	180
72	360	0.57	250	190	130
84	310	0.78	190	140	90
96	270	1.02	140	110	70
108	240	1.29	110	80	60
120	210	1.54	90	70	50
144	180	2.29	60	50	30

P4000 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	1,630	4,670	4,290	3,780	3,310
36	1,450	3,840	3,310	2,460	1,730
48	1,160	3,030	2,190	1,400	970
60	870	2,120	1,400	900	**
72	670	1,470	970	**	**

P4001 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	2,830	10,390	10,000	9,470	8,960
36	2,740	9,530	8,960	7,870	6,700
48	2,590	8,620	7,480	5,910	4,440
60	2,340	7,380	5,910	4,090	2,840
72	2,020	6,110	4,440	2,840	1,970
84	1,700	4,880	3,260	2,090	**
96	1,440	3,780	2,500	**	**
108	1,230	2,990	1,970	**	**

P4000/P4001 - ELEMENTS OF SECTION

Parameter	P4000	P4001
Area of Section	0.244	In ²
Axis 1-1		
Moment of Inertia (I)	0.023	In ⁴
Section Modulus (S)	0.049	In ³
Radius of Gyration (r)	0.306	In
Axis 2-2		
Moment of Inertia (I)	0.092	In ⁴
Section Modulus (S)	0.113	In ³
Radius of Gyration (r)	0.613	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.



P4000 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	1.9	3	1.9	1.7	1.2
750	1.5	4	1.5	1.1	0.7
1,000	1.1	8	0.8	0.6	0.4
1,250	0.9	12	0.5	0.4	0.3
1,500	0.8	17	0.4	0.3	0.2
1,750	0.6	23	0.3	0.2	0.1
2,000	0.5	29	0.2	0.1	0.1
2,500	0.4	47	0.1	0.1	NR
3,000	0.4	65	0.1	0.1	NR

P4001 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	3.6 *	1	3.6 *	3.6 *	3.6 *
750	3.6 *	2	3.6 *	3.6 *	3.3
1,000	2.9	4	2.9	2.8	1.9
1,250	2.3	7	2.3	1.8	1.2
1,500	2.0	10	1.6	1.2	0.8
1,750	1.6	13	1.2	0.9	0.6
2,000	1.5	17	0.9	0.7	0.5
2,500	1.2	27	0.6	0.4	0.3
3,000	1.0	39	0.4	0.3	0.2
3,500	0.8	54	0.3	0.2	0.1

P4000 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	7.2	20.9	19.2	17.0	14.9
750	6.9	19.1	17.0	14.4	11.3
1,000	6.1	16.1	13.3	9.2	6.5
1,250	5.0	13.0	9.2	5.9	4.1
1,500	4.0	9.7	6.5	4.1	**
1,750	3.2	7.2	4.7	**	**

P4001 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	12.6	46.3	44.6	42.3	40.0
750	12.4	44.5	42.3	39.5	35.4
1,000	12.1	41.3	38.2	32.6	26.9
1,250	11.4	37.8	32.6	25.4	18.8
1,500	10.5	33.3	26.9	18.8	13.0
1,750	9.4	28.6	21.3	13.8	9.6
2,000	8.1	24.1	16.5	10.5	**
2,250	7.1	19.8	13.0	8.4	**
2,500	6.2	16.0	10.5	**	**
2,750	5.4	13.2	8.7	**	**

P4000/P4001 - ELEMENTS OF SECTION (METRIC)

Parameter	P4000		P4001	
Area of Section	1.57	cm ²	3.14	cm ²
Axis 1-1				
Moment of Inertia (I)	0.95	cm ⁴	4.32	cm ⁴
Section Modulus (S)	0.80	cm ³	2.09	cm ³
Radius of Gyration (r)	0.78	cm	1.17	cm
Axis 2-2				
Moment of Inertia (I)	3.81	cm ⁴	7.62	cm ⁴
Section Modulus (S)	1.85	cm ³	3.69	cm ³
Radius of Gyration (r)	1.56	cm	1.56	cm

Notes:

* Load limited by spot weld shear.



** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:
 "KO" Series.....95% "T" Series85%
 "HS" Series90% "SL" Series85%
 "WT" Series.....85%
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.



P4100

DF GR PG



P4101

DF GR PG




Wt/100 Ft: 98 Lbs (147 kg/100 m)
Allowable Moment 1,360 In-Lbs (150 N·m)
14 Gauge Nominal Thickness .075" (1.9mm)

Wt/100 Ft: 197 Lbs (293 kg/100 m)
Allowable Moment 3,610 In-Lbs (410 N·m)
14 Gauge Nominal Thickness .075" (1.9mm)

P4100 HS

GR PG

9/16" (14.3) Dia. Holes
1 7/8" (47.6) on Center




Wt/100 Ft: 87 Lbs (129 kg/100 m)

P4100 SL

GR PG


Slots are
3" (76.2) x 13/32" (10.3)
4" (101.6) on Center



Wt/100 Ft: 87 Lbs (129 kg/100 m)

P4101 T

Slots are
1 1/8" (28.6) x 9/16" (14.3)
2" (50.8) on Center




Wt/100 Ft: 174 Lbs (259 kg/100 m)

P4100 T

DF GR PG

Slots are
1 1/8" (28.6) x 9/16" (14.3)
2" (50.8) on Center




Wt/100 Ft: 87 Lbs (129 kg/100 m)

P4100 WT

DF GR HG PG PL

Slots are
2" (50.8) x 1 1/16" (17.5)
3" (76.2) on Center




Wt/100 Ft: 87 Lbs (129 kg/100 m)

P4101 WT

DF GR HG PG PL

Slots are
2" (50.8) x 1 1/16" (17.5)
3" (76.2) on Center



Wt/100 Ft: 174 Lbs (259 kg/100 m)

CHANNEL NUTS (REFER TO PAGES 73,74 FOR DETAILS)

SEE PAGE 73, 74



- P4006-0832
- P4006-1024
- P4006-1420
- P4007
- P4008
- P4009
- P4010



P4010T



- P4012
- P4023



- P3006-0832
- P3006-1024
- P3006-1420
- P3007
- P3008
- P3009
- P3013



- P3016-0632
- P3016-0832
- P3016-1024
- P3016-1420



P4100 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	450	0.11	450	420	280
36	300	0.24	250	190	130
48	230	0.44	140	110	70
60	180	0.67	90	70	50
72	150	0.96	60	50	30
84	130	1.32	50	30	20
96	110	1.67	40	30	20
108	100	2.16	30	20	10
120	90	2.67	20	20	10
144	80	4.09	20	NR	NR
168	60	4.88	NR	NR	NR
192	60	7.28	NR	NR	NR
216	50	8.64	NR	NR	NR
240	50	11.85	NR	NR	NR

P4101 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	1,090*	0.06	1,090*	1,090*	1,090*
36	800	0.14	800	800	570
48	600	0.25	600	480	320
60	480	0.39	410	310	200
72	400	0.57	280	210	140
84	340	0.76	210	160	100
96	300	1.00	160	120	80
108	270	1.29	130	90	60
120	240	1.57	100	80	50
144	200	2.26	70	50	40
168	170	3.05	50	40	30
192	150	4.02	40	NR	NR
216	130	4.96	NR	NR	NR
240	120	6.28	NR	NR	NR

P4100 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	1,840	5,610	5,210	4,570	3,850
36	1,640	4,660	3,850	2,800	1,960
48	1,310	3,490	2,480	1,590	1,100
60	1,000	2,400	1,590	**	**
72	770	1,670	1,100	**	**

P4101 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	3,240	12,370	11,950	11,370	10,540
36	3,120	11,470	10,540	9,160	7,720
48	2,940	10,090	8,680	6,770	4,980
60	2,680	8,560	6,770	4,590	3,190
72	2,310	7,010	4,980	3,190	2,220
84	1,950	5,530	3,660	2,340	**
96	1,650	4,250	2,800	**	**
108	1,410	3,360	2,220	**	**

P4100/P4101 - ELEMENTS OF SECTION

Parameter	P4100	P4101
Area of Section	0.290	In ²
Axis 1-1		0.579
Moment of Inertia (I)	0.026	In ⁴
Section Modulus (S)	0.054	In ³
Radius of Gyration (r)	0.298	In
Axis 2-2		0.449
Moment of Inertia (I)	0.107	In ⁴
Section Modulus (S)	0.132	In ³
Radius of Gyration (r)	0.609	In
	0.608	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:
 "KO" Series.....95% "T" Series85%
 "HS" Series90% "SL" Series85%
 "WT" Series.....85%
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P4100 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	2.0	3	2.0	2.0	1.3
750	1.6	4	1.6	1.2	0.8
1,000	1.2	7	0.9	0.7	0.4
1,250	1.0	11	0.6	0.4	0.3
1,500	0.8	16	0.4	0.3	0.2
1,750	0.7	23	0.3	0.2	0.1
2,000	0.6	30	0.2	0.2	0.1
2,500	0.5	46	0.1	0.1	0.1
3,000	0.4	65	0.1	0.1	NR

P4101 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	4.8 *	1	4.8 *	4.8 *	4.8 *
750	4.4	2	4.4	4.4	3.7
1,000	3.2	4	3.2	3.2	2.1
1,250	2.6	7	2.6	2.0	1.3
1,500	2.2	10	1.9	1.4	0.9
1,750	1.9	13	1.4	1.0	0.7
2,000	1.6	17	1.1	0.8	0.5
2,500	1.3	27	0.7	0.5	0.4
3,000	1.1	38	0.5	0.4	0.2
3,500	0.9	53	0.4	0.3	0.2

P4100 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	8.2	25.1	23.3	20.6	17.4
750	7.8	23.2	20.6	16.6	12.8
1,000	6.9	19.3	15.3	10.5	7.3
1,250	5.6	15.0	10.5	6.7	4.7
1,500	4.5	11.0	7.3	4.7	**
1,750	3.6	8.1	5.3	**	**

P4101 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	14.4	55.1	53.3	50.8	47.2
750	14.2	53.2	50.8	46.3	41.2
1,000	13.7	49.4	44.7	37.8	30.8
1,250	13.0	44.2	37.8	29.1	21.1
1,500	12.0	38.7	30.8	21.1	14.6
1,750	10.7	33.0	24.2	15.5	10.8
2,000	9.3	27.4	18.5	11.9	**
2,250	8.1	22.2	14.6	9.4	**

P4100/P4101 - ELEMENTS OF SECTION (METRIC)

Parameter	P4100	P4101
Area of Section	1.87	cm ²
Axis 1-1	3.74	cm ²
Moment of Inertia (I)	1.07	cm ⁴
Section Modulus (S)	0.88	cm ³
Radius of Gyration (r)	0.76	cm
Axis 2-2	1.14	cm
Moment of Inertia (I)	4.46	cm ⁴
Section Modulus (S)	2.16	cm ³
Radius of Gyration (r)	1.55	cm

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.




- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.






P4400

GR PG




Wt/100 Ft: 144 Lbs (210 kg/100 m)
Allowable Moment 2,300 In-Lbs (260 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)



Wt/100 Ft: 289 Lbs (430 kg/100 m)
Allowable Moment 6,410 In-Lbs (725 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)

P4400 HS

GR PG




5/16" (14.3) Dia. Holes
1 7/8" (47.6) on Center

Wt/100 Ft: 136 Lbs (201 kg/100 m)

P4400 T

GR PG




Slots are
1 1/8" (28.6) x 9/16" (14.3)
2" (50.8) on Center

Wt/100 Ft: 136 Lbs (201 kg/100 m)

P4400 SL

GR PG




Slots are
3" (76.2) x 13/32" (10.3)
4" (101.6) on Center

Wt/100 Ft: 136 Lbs (201 kg/100 m)

P4400 WT

DF GR HG PG PL



Slots are
2" (50.8) x 11/16" (17.5)
3" (76.2) on Center

Wt/100 Ft: 136 Lbs (201 kg/100 m)

CHANNEL NUTS (REFER TO PAGES 73,74 FOR DETAILS)

SEE PAGE 73, 74



P4006-0832
P4006-1024
P4006-1420
P4007
P4008
P4009
P4010



P4010T



P4012
P4023



P3006-0832
P3006-1024
P3006-1420
P3007
P3008
P3009
P3013



P3016-0632
P3016-0832
P3016-1024
P3016-1420

Channel Finishes: PL, GR, HG, PG, ZD; Standard Lengths: 10' & 20'

P4400 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	770	0.09	770	770	580
36	510	0.20	510	390	260
48	380	0.35	290	220	150
60	310	0.56	190	140	90
72	260	0.80	130	100	60
84	220	1.08	90	70	50
96	190	1.39	70	50	40
108	170	1.78	60	40	30
120	150	2.15	50	30	20
144	130	3.22	30	20	20

P4401 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	2,140*	0.05	2,140*	2,140*	2,140*
36	1,420	0.11	1,420	1,420	1,240
48	1,070	0.20	1,070	1,040	700
60	850	0.32	850	670	450
72	710	0.46	620	460	310
84	610	0.63	450	340	230
96	530	0.81	350	260	170
108	470	1.03	280	210	140
120	430	1.29	220	170	110
144	360	1.86	150	120	80
168	310	2.54	110	90	60
192	270	3.31	90	70	NR
216	240	4.19	70	NR	NR
240	210	5.03	60	NR	NR

P4400 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	2,620	8,280	7,760	7,140	6,580
36	2,470	7,210	6,580	5,310	4,030
48	2,180	6,200	4,870	3,280	2,280
60	1,770	4,760	3,280	2,100	**
72	1,420	3,450	2,280	**	**
84	1,150	2,530	1,670	**	**
96	**	1,940	**	**	**

P4401 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	4,720	18,310	17,840	17,300	16,760
36	4,640	17,360	16,760	15,260	13,610
48	4,470	16,280	14,720	12,460	10,170
60	4,230	14,590	12,460	9,610	6,980
72	3,930	12,750	10,170	6,980	4,840
84	3,520	10,880	7,990	5,130	3,560
96	3,070	9,050	6,130	3,920	**
108	2,690	7,340	4,840	3,100	**
120	2,360	5,940	3,920	**	**

P4400/P4401 - ELEMENTS OF SECTION

Parameter	P4400		P4401	
Area of Section	0.424	In ²	0.849	In ²
Axis 1-1				
Moment of Inertia (I)	0.053	In ⁴	0.255	In ⁴
Section Modulus (S)	0.092	In ³	0.255	In ³
Radius of Gyration (r)	0.354	In	0.548	In
Axis 2-2				
Moment of Inertia (I)	0.161	In ⁴	0.322	In ⁴
Section Modulus (S)	0.198	In ³	0.396	In ³
Radius of Gyration (r)	0.616	In	0.616	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.



P4400 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	3.5	2.2	3.5	3.5	2.7
750	2.8	3.4	2.8	2.6	1.7
1000	2.1	6.0	2.0	1.5	1.0
1250	1.7	9.3	1.3	1.0	0.6
1500	1.4	13.4	0.9	0.6	0.5
1750	1.2	18.6	0.6	0.5	0.3
2000	1.0	23.6	0.5	0.4	0.2
2500	0.9	38.1	0.3	0.2	0.1
3000	0.7	55.5	0.2	0.2	0.1
3500	0.6	71.6	0.2	0.1	0.1

P4401 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	9.7	1.2	9.7	9.7	9.7
750	7.9	2.0	7.9	7.9	7.9
1000	5.9	3.5	5.9	5.9	4.7
1250	4.7	5.5	4.7	4.5	3.0
1500	3.9	7.9	3.9	3.1	2.1
1750	3.4	10.6	3.1	2.3	1.5
2000	2.9	14.0	2.4	1.8	1.2
2500	2.4	21.8	1.5	1.1	0.8
3000	2.0	31.2	1.0	0.8	0.5
3500	1.7	42.6	0.8	0.6	0.4
4000	1.5	56.7	0.6	0.5	0.3
4500	1.3	70.9	0.5	0.4	0.2
5000	1.2	87.2	0.4	0.3	NR
6000	1.0	127.5	0.3	NR	NR

P4400 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	11.9	37.7	35.4	32.6	30.1
750	11.6	35.2	32.6	29.5	24.5
1000	10.9	31.5	27.9	21.3	15.3
1250	9.7	27.4	21.3	14.2	9.8
1500	8.2	22.1	15.3	9.8	**
1750	6.8	17.1	11.3	7.2	**
2000	5.7	13.1	8.6	**	**
2500	**	8.4	**	**	**

P4401 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	21.4	83.2	81.1	78.7	76.4
750	21.2	81.0	78.7	75.4	69.8
1000	20.9	77.7	73.6	65.8	57.3
1250	20.2	73.1	65.8	55.2	44.5
1500	19.3	66.8	57.3	44.5	32.7
1750	18.2	60.0	48.8	34.6	24.0
2000	16.8	53.1	40.5	26.4	18.4
2500	13.6	39.5	26.4	16.9	**
3000	10.9	27.9	18.4	**	**

P4400/P4401 - ELEMENTS OF SECTION (METRIC)

Parameter	P4100	P4101
Area of Section	2.74	cm ²
Axis 1-1	5.48	cm ²
Moment of Inertia (I)	2.21	cm ⁴
Section Modulus (S)	1.51	cm ³
Radius of Gyration (r)	0.90	cm
Axis 2-2	1.39	cm
Moment of Inertia (I)	6.70	cm ⁴
Section Modulus (S)	3.24	cm ³
Radius of Gyration (r)	1.57	cm


Notes:

* Load limited by spot weld shear.


** KL/r > 200

NR = Not Recommended.



- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:
"KO" Series.....95% **"T" Series85%**
"HS" Series90% **"SL" Series85%**
"WT" Series.....85%
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P4520**GR PG****P4521****GR PG**

Wt/100 Ft: 131 Lbs (190 kg/100 m)
Allowable Moment 1,615 In-Lbs (183 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)





Wt/100 Ft: 262 Lbs (390 kg/100 m)
Allowable Moment 4,540 In-Lbs (513 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)

P4520 HS**GR PG****P4520 T****GR PG**

Wt/100 Ft: 120 Lbs (177 kg/100 m)

Wt/100 Ft: 120 Lbs (177 kg/100 m)

P4520 SL**GR PG****P4520 WT****DF GR HG PG PL**

Wt/100 Ft: 118 Lbs (175 kg/100 m)

Wt/100 Ft: 120 Lbs (177 kg/100 m)

CHANNEL NUTS (REFER TO PAGES 73,74 FOR DETAILS)**SEE PAGE 73, 74**

P4006-0832
P4006-1024
P4006-1420
P4007
P4008
P4009
P4010



P4010T



P4012
P4023



P3006-0832
P3006-1024
P3006-1420
P3007
P3008
P3009
P3013



P3016-0632
P3016-0832
P3016-1024
P3016-1420

Channel Finishes: PL, GR, HG, PG, ZD; Standard Lengths: 10' & 20'



P4520 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	540	0.11	540	510	340
36	360	0.24	300	220	150
48	270	0.43	170	130	80
60	220	0.68	110	80	50
72	180	0.96	70	60	40
84	150	1.27	60	40	30
96	130	1.65	40	30	20
108	120	2.16	30	20	20
120	110	2.72	30	20	NR
144	90	3.84	20	NR	NR

P4521 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	1,510	0.06	1,510	1,510	1,510
36	1,010	0.14	1,010	1,010	710
48	760	0.25	760	600	400
60	610	0.40	510	380	260
72	500	0.56	360	270	180
84	430	0.77	260	200	130
96	380	1.01	200	150	100
108	340	1.29	160	120	80
120	300	1.56	130	100	60
144	250	2.25	90	70	40
168	220	3.14	70	50	NR
192	190	4.05	50	NR	NR
216	170	5.16	NR	NR	NR
240	150	6.24	NR	NR	NR

P4520 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	2,250	7,480	6,800	5,820	4,810
36	1,980	5,950	4,810	3,380	2,350
48	1,580	4,310	2,970	1,900	**
60	1,210	2,880	1,900	**	**
72	950	2,000	**	**	**

P4521 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	4,140	16,490	15,980	14,970	13,810
36	3,980	15,100	13,810	11,910	9,940
48	3,730	13,190	11,260	8,650	6,270
60	3,390	11,090	8,650	5,780	4,010
72	2,950	8,970	6,270	4,010	2,790
84	2,510	6,980	4,610	2,950	**
96	2,130	5,340	3,530	**	**
108	1,820	4,220	2,790	**	**
120	**	3,420	**	**	**

P4520/P4521 - ELEMENTS OF SECTION

Parameter	P4400	P4401
Area of Section	0.384	In ²
Axis 1-1		
Moment of Inertia (I)	0.031	In ⁴
Section Modulus (S)	0.064	In ³
Radius of Gyration (r)	0.283	In
Axis 2-2		
Moment of Inertia (I)	0.138	In ⁴
Section Modulus (S)	0.170	In ³
Radius of Gyration (r)	0.599	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P4520 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	2.5	2.6	2.5	2.4	1.6
750	2.0	4.1	2.0	1.5	1.0
1000	1.5	7.3	1.1	0.9	0.6
1250	1.2	11.3	0.7	0.5	0.4
1500	1.0	16.5	0.5	0.4	0.3
1750	0.9	22.6	0.4	0.3	0.2
2000	0.7	28.4	0.3	0.2	0.1
2500	0.6	45.0	0.2	0.1	0.1
3000	0.5	65.8	0.1	0.1	NR
3500	0.4	85.5	0.1	0.1	NR

P4521 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	7.0	1.6	7.0	7.0	7.0
750	5.6	2.4	5.6	5.6	4.8
1000	4.2	4.3	4.2	4.0	2.7
1250	3.4	6.7	3.4	2.6	1.7
1500	2.8	9.6	2.4	1.8	1.2
1750	2.4	13.3	1.8	1.3	0.9
2000	2.1	17.2	1.4	1.0	0.7
2500	1.7	27.0	0.9	0.6	0.5
3000	1.4	39.1	0.6	0.5	0.3
3500	1.2	52.0	0.5	0.3	0.2
4000	1.0	68.7	0.3	0.3	0.2
4500	0.9	85.1	0.3	0.2	NR
5000	0.8	105.0	0.2	NR	NR
6000	0.7	151.2	NR	NR	NR

P4520 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	10.3	34.1	31.1	26.8	22.2
750	9.7	30.9	26.8	21.1	15.8
1000	8.5	24.9	19.3	12.8	8.9
1250	6.9	18.9	12.8	8.2	**
1500	5.6	13.5	8.9	**	**
1750	4.6	9.9	6.5	**	**

P4521 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	18.8	74.9	72.8	68.3	63.1
750	18.5	72.5	68.3	61.8	54.7
1000	17.8	66.2	59.5	49.8	40.1
1250	16.8	58.9	49.8	37.8	27.0
1500	15.5	51.1	40.1	27.0	18.8
1750	14.0	43.1	31.1	19.9	13.8
2000	12.2	35.5	23.8	15.2	**
2500	9.3	23.0	15.2	**	**
3000	**	16.0	**	**	**

P4520/P4521 - ELEMENTS OF SECTION (METRIC)

Parameter	P4100	P4101
Area of Section	2.48	cm ²
Axis 1-1		4.97 cm ²
Moment of Inertia (I)	1.29	cm ⁴
Section Modulus (S)	1.05	cm ³
Radius of Gyration (r)	0.72	cm
Axis 2-2		1.11 cm
Moment of Inertia (I)	5.74	cm ⁴
Section Modulus (S)	2.79	cm ³
Radius of Gyration (r)	1.52	cm
	1.53	cm

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.



1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
2. Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
3. For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
4. Deduct channel weight from the beam loads.
5. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
6. All beam loads are for bending about Axis 1-1.



P5000



DF GR PL PG



Wt/100 Ft: 305 Lbs (454 kg/100 m)
Allowable Moment 15,770 In-Lbs (1,780 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)

P5001


DF GR PG



Wt/100 Ft: 610 Lbs (907 kg/100 m)
Allowable Moment 48,180 In-Lbs (5,440 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)

P5000 HS


GR PG



Wt/100 Ft: 300 Lbs (446 kg/100 m)

P5000 SL


GR PG



Slots are
3" (76.2) x 1 3/32" (10.3)
4" (101.6) on Center

Wt/100 Ft: 300 Lbs (446 kg/100 m)


P5000 T



Slots are
1 1/8" (28.6) x 9/16" (14.3)
2" (50.8) on Center

Wt/100 Ft: 300 Lbs (446 kg/100 m)

P5000 KO




7/8" (22.2) Knockouts
6" (152.4) on Center

Wt/100 Ft: 305 Lbs (454 kg/100 m)

P5000 WT

DF GR HG PG PL



Slots are
2" (50.8) x 1 1/16" (17.5)
3" (76.2) on Center

Wt/100 Ft: 300 Lbs (446 kg/100 m)

CHANNEL NUTS (REFER TO PAGES 73,74 FOR DETAILS)

SEE PAGE 73, 74



P5506-0832
P5506-1024
P5506-1420
P5507
P5508
P5509
P5510



P1006T1420
P1008T
P1010T



P1012
P1023
P1024



P3006-0832
P3006-1024
P3006-1420
P3007
P3008
P3009
P3010



P3016-0632
P3016-0832
P3016-1024
P3016-1420

Channel Finishes: DF, PL, GR, HG, PG, ZD; Standard Lengths: 10' & 20'

P5000 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	5,260	0.03	5,260	5,260	5,260
36	3,500	0.07	3,500	3,500	3,500
48	2,630	0.12	2,630	2,630	2,630
60	2,100	0.18	2,100	2,100	1,920
72	1,750	0.26	1,750	1,750	1,330
84	1,500	0.36	1,500	1,470	980
96	1,310	0.47	1,310	1,120	750
108	1,170	0.59	1,170	890	590
120	1,050	0.73	960	720	480
144	880	1.06	670	500	330
168	750	1.43	490	370	240
192	660	1.88	370	280	190
216	580	2.35	300	220	150
240	530	2.95	240	180	120

P5001 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	6,890*	0.01	6,890*	6,890*	6,890*
36	6,890*	0.02	6,890*	6,890*	6,890*
48	6,890*	0.05	6,890*	6,890*	6,890*
60	6,420	0.10	6,420	6,420	6,420
72	5,350	0.14	5,350	5,350	5,350
84	4,590	0.19	4,590	4,590	4,590
96	4,020	0.25	4,020	4,020	4,020
108	3,570	0.32	3,570	3,570	3,360
120	3,210	0.39	3,210	3,210	2,720
144	2,680	0.57	2,680	2,680	1,890
168	2,290	0.77	2,290	2,080	1,390
192	2,010	1.01	2,010	1,590	1,060
216	1,780	1.27	1,680	1,260	840
240	1,610	1.58	1,360	1,020	680

P5000 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	5,650	16,870	15,180	12,850	10,600
36	4,690	13,140	10,600	7,650	5,660
48	3,560	9,550	6,860	4,790	3,660
60	2,730	6,680	4,790	3,450	2,710
72	2,160	4,980	3,660	2,710	2,170
84	1,760	3,950	2,960	2,240	1,820
96	1,500	3,270	2,500	1,930	1,580
108	1,310	2,800	2,170	1,690	1,390
120	1,170	2,450	1,930	1,510	**
144	980	1,980	1,580	**	**
168	850	1,670	1,340	**	**

P5001 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	10,670	39,230	38,030	36,210	34,240
36	10,350	36,450	34,240	31,200	28,260
48	9,940	33,220	30,200	26,430	23,190
60	9,290	29,950	26,430	22,470	19,380
72	8,560	26,880	23,190	19,380	16,450
84	7,860	24,140	20,520	17,040	12,090
96	7,220	21,790	18,370	13,330	9,250
108	6,600	19,790	16,450	10,530	7,310
120	5,760	18,130	13,330	8,530	**
144	4,390	14,020	9,250	**	**
168	3,420	10,300	6,800	**	**

P5000/P5001 - ELEMENTS OF SECTION

Parameter	P5000	P5001
Area of Section	0.897	In ²
Axis 1-1		1.793 In ²
Moment of Inertia (I)	1.098	In ⁴
Section Modulus (S)	0.627	In ³
Radius of Gyration (r)	1.107	In
Axis 2-2		1.864 In
Moment of Inertia (I)	0.433	In ⁴
Section Modulus (S)	0.533	In ³
Radius of Gyration (r)	0.695	In
	0.695	0.695 In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:
 "KO" Series.....95% "T" Series85%
 "HS" Series90% "SL" Series85%
 "WT" Series.....85%
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.



P5000 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	23.8	1	23.8	23.8	23.8
750	19.0	1	19.0	19.0	19.0
1,000	14.2	2	14.2	14.2	14.2
1,250	11.4	3	11.4	11.4	11.4
1,500	9.5	5	9.5	9.5	8.8
1,750	8.1	6	8.1	8.1	6.5
2,000	7.1	8	7.1	7.1	4.9
2,500	5.7	12	5.7	4.8	3.2
3,000	4.8	18	4.4	3.3	2.2
3,500	4.1	25	3.2	2.4	1.6
4,000	3.6	32	2.5	1.9	1.2
4,500	3.2	40	2.0	1.5	1.0
5,000	2.8	50	1.6	1.2	0.8
6,000	2.4	71	1.1	0.8	0.5

P5001 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	30.6 *	0	30.6 *	30.6 *	30.6 *
750	30.6 *	0	30.6 *	30.6 *	30.6 *
1,000	30.6 *	1	30.6 *	30.6 *	30.6 *
1,250	30.6 *	1	30.6 *	30.6 *	30.6 *
1,500	29.0	2	29.0	29.0	29.0
1,750	24.9	3	24.9	24.9	24.9
2,000	21.8	4	21.8	21.8	21.8
2,500	17.4	7	17.4	17.4	17.4
3,000	14.5	10	14.5	14.5	12.5
3,500	12.5	13	12.5	12.5	9.2
4,000	10.9	17	10.9	10.5	7.0
4,500	9.7	22	9.7	8.3	5.6
5,000	8.7	27	8.7	6.8	4.5
6,000	7.2	39	6.2	4.7	3.1

P5000 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	25.2	75.5	68.1	58.0	48.0
750	23.5	67.5	58.0	45.7	35.0
1,000	19.4	53.7	41.9	29.3	21.8
1,250	15.4	41.0	29.3	20.5	15.7
1,500	12.4	30.5	21.8	15.7	12.3
1,750	10.2	23.8	17.3	12.8	10.2
2,000	8.5	19.3	14.4	10.8	8.7
2,250	7.3	16.3	12.3	9.4	7.6
2,500	6.5	14.1	10.8	8.3	6.9
2,750	5.8	12.4	9.6	7.5	6.2

P5001 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	47.5	174.9	169.7	161.7	153.2
750	46.8	169.2	161.7	150.9	139.8
1,000	45.6	158.2	147.2	132.6	118.8
1,250	44.0	146.3	132.6	115.6	101.2
1,500	41.6	134.3	118.8	101.2	87.4
1,750	38.9	122.9	106.6	89.4	76.8
2,000	36.3	112.5	96.2	80.0	61.2
2,250	33.9	103.2	87.4	69.6	48.4
2,500	31.6	95.0	80.0	56.4	39.1
2,750	29.3	87.8	72.9	46.6	32.4

P5000/P5001 - ELEMENTS OF SECTION (METRIC)

Parameter	P5000		P5001	
Area of Section	5.78	cm ²	11.57	cm ²
Axis 1-1				
Moment of Inertia (I)	45.70	cm ⁴	259.17	cm ⁴
Section Modulus (S)	10.28	cm ³	31.40	cm ³
Radius of Gyration (r)	2.81	cm	4.73	cm
Axis 2-2				
Moment of Inertia (I)	18.02	cm ⁴	36.04	cm ⁴
Section Modulus (S)	8.73	cm ³	17.46	cm ³
Radius of Gyration (r)	1.77	cm	1.77	cm

Notes:

* Load limited by spot weld shear.



** $KL/r > 200$

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:
"KO" Series.....95% **"T" Series85%**
"HS" Series90% **"SL" Series85%**
"WT" Series.....85%
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P5500



GR PG



Wt/100 Ft: 247 Lbs (367 kg/100 m)
Allowable Moment 9,820 In-Lbs (1,110 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)

P5501

GR PG




Wt/100 Ft: 494 Lbs (734 kg/100 m)
Allowable Moment 28,940 In-Lbs (3,270 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)

P5500 HS

GR PG

$\frac{9}{16}$ " (14.3) Dia. Holes
1 7/8" (47.6) on Center




Wt/100 Ft: 242 Lbs (360 kg/100 m)

P5500 KO

GR PG

7/8" (22.2) Knockouts
6" (152.4) on Center




Wt/100 Ft: 247 Lbs (368 kg/100 m)

P5500 SL

GR PG

Slots are
3" (76.2) x $1\frac{13}{32}$ " (10.3)
4" (101.6) on Center




Wt/100 Ft: 242 Lbs (360 kg/100 m)

P5500 T

GR PG

Slots are
1 1/8" (28.6) x $\frac{9}{16}$ " (14.3)
2" (50.8) on Center




Wt/100 Ft: 242 Lbs (360 kg/100 m)

P5500 WT

DF GR HG PG PL

Slots are
2" (50.8) x $1\frac{11}{16}$ " (17.5)
3" (76.2) on Center



Wt/100 Ft: 242 Lbs (360 kg/100 m)

CHANNEL NUTS (REFER TO PAGES 73,74 FOR DETAILS)

SEE PAGE 73, 74



P5506-0832
P5506-1024
P5506-1420
P5507
P5508
P5509
P5510



P1006T1420
P1008T
P1010T



P1012
P1023
P1024



P3006-0832
P3006-1024
P3006-1420
P3007
P3008
P3009
P3010



P3016-0632
P3016-0832
P3016-1024
P3016-1420

Channel Finishes: PL, GR, HG, PG, ZD; Standard Lengths: 10' & 20'



P5500 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	3,270	0.04	3,270	3,270	3,270
36	2,180	0.09	2,180	2,180	2,180
48	1,640	0.15	1,640	1,640	1,420
60	1,310	0.24	1,310	1,310	910
72	1,090	0.34	1,090	950	630
84	940	0.47	930	700	470
96	820	0.61	710	530	360
108	730	0.78	560	420	280
120	650	0.95	460	340	230
144	550	1.39	320	240	160
168	470	1.89	230	170	120
192	410	2.46	180	130	90
216	360	3.07	140	110	70
240	330	3.86	110	90	60

P5501 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	5,220*	0.01	5,220*	5,220*	5,220*
36	5,220*	0.04	5,220*	5,220*	5,220*
48	4,820	0.08	4,820	4,820	4,820
60	3,860	0.13	3,860	3,860	3,860
72	3,220	0.19	3,220	3,220	3,220
84	2,760	0.26	2,760	2,760	2,500
96	2,410	0.34	2,410	2,410	1,920
108	2,140	0.42	2,140	2,140	1,510
120	1,930	0.52	1,930	1,840	1,230
144	1,610	0.76	1,610	1,280	850
168	1,380	1.03	1,250	940	630
192	1,210	1.35	960	720	480
216	1,070	1.70	760	570	380
240	960	2.09	610	460	310

P5500 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	4,640	13,840	12,570	10,840	9,190
36	3,970	11,050	9,190	7,030	5,370
48	3,180	8,420	6,390	4,620	3,630
60	2,550	6,250	4,620	3,450	2,780
72	2,120	4,790	3,630	2,780	2,260
84	1,810	3,890	3,010	2,330	1,910
96	1,580	3,290	2,580	2,020	1,650
108	1,400	2,860	2,260	1,770	1,440
120	1,270	2,530	2,020	1,580	**
144	1,060	2,070	1,650	**	**
168	920	1,750	1,380	**	**

P5501 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	8,580	31,810	30,880	29,520	28,100
36	8,350	29,700	28,100	26,000	24,070
48	8,080	27,390	25,330	22,910	20,940
60	7,720	25,170	22,910	20,510	17,170
72	7,270	23,190	20,940	17,170	12,700
84	6,780	21,510	18,740	13,430	9,330
96	6,130	20,110	15,630	10,290	7,150
108	5,450	17,750	12,700	8,130	5,650
120	4,800	15,260	10,290	6,590	**
144	3,760	10,830	7,150	**	**
168	2,970	7,950	5,250	**	**

P5500/P5501 - ELEMENTS OF SECTION

Parameter	P5500	P5501
Area of Section	0.726	In ²
Axis 1-1		
Moment of Inertia (I)	0.522	In ⁴
Section Modulus (S)	0.390	In ³
Radius of Gyration (r)	0.848	In
Axis 2-2		
Moment of Inertia (I)	0.334	In ⁴
Section Modulus (S)	0.411	In ³
Radius of Gyration (r)	0.679	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
- For pierced channel, multiply beam loads by the following factor:
 "KO" Series 95% "T" Series 85%
 "HS" Series 90% "SL" Series 85%
 "WT" Series 85%
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P5500 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	14.8	1	14.8	14.8	14.8
750	11.8	1	11.8	11.8	11.8
1,000	8.9	3	8.9	8.9	8.9
1,250	7.1	4	7.1	7.1	6.1
1,500	5.9	6	5.9	5.9	4.2
1,750	5.1	8	5.1	4.6	3.1
2,000	4.5	10	4.5	3.5	2.4
2,500	3.6	16	3.0	2.3	1.5
3,000	3.0	24	2.1	1.6	1.1
3,500	2.5	32	1.6	1.2	0.8
4,000	2.2	42	1.2	0.9	0.6
4,500	2.0	53	0.9	0.7	0.4
5,000	1.8	66	0.8	0.6	0.4
6,000	1.5	94	0.5	0.4	0.3

P5501 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	23.2 *	0	23.2 *	23.2 *	23.2 *
750	23.2 *	1	23.2 *	23.2 *	23.2 *
1,000	23.2 *	1	23.2 *	23.2 *	23.2 *
1,250	20.9	2	20.9	20.9	20.9
1,500	17.4	3	17.4	17.4	17.4
1,750	14.9	4	14.9	14.9	14.9
2,000	13.1	6	13.1	13.1	12.7
2,500	10.5	9	10.5	10.5	8.1
3,000	8.7	13	8.7	8.5	5.6
3,500	7.5	18	7.5	6.2	4.1
4,000	6.5	23	6.3	4.8	3.2
4,500	5.8	29	5.0	3.7	2.5
5,000	5.2	36	4.1	3.0	2.0
6,000	4.4	52	2.8	2.1	1.4

P5500 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	20.7	61.9	56.4	48.8	41.6
750	19.6	55.9	48.8	39.8	31.9
1,000	16.7	45.7	37.0	27.4	21.0
1,250	13.8	36.4	27.4	19.9	15.7
1,500	11.5	28.5	21.0	15.7	12.6
1,750	9.8	22.6	17.1	13.0	10.6
2,000	8.6	18.9	14.5	11.2	9.1
2,250	7.6	16.2	12.6	9.8	8.0
2,500	6.9	14.2	11.2	8.7	7.2
2,750	6.2	12.7	10.1	7.9	6.4

P5501 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	38.2	141.5	137.4	131.3	125.0
750	37.1	132.1	125.0	115.6	107.1
1,000	35.9	121.8	112.7	101.9	93.1
1,250	34.3	112.0	101.9	91.2	76.4
1,500	32.3	103.2	93.1	76.4	56.5
1,750	30.2	95.7	83.4	59.7	41.5
2,000	27.3	89.5	69.5	45.8	31.8
2,500	24.2	79.0	56.5	36.2	25.1
3,000	21.3	67.9	45.8	29.3	**
3,500	16.7	48.2	31.8	**	**
4,000	13.2	35.4	23.3	**	**

P5500/P5501 - ELEMENTS OF SECTION (METRIC)

Parameter	P5500	P5501
Area of Section	4.68 cm ²	9.37 cm ²
Axis 1-1		
Moment of Inertia (I)	21.71 cm ⁴	116.76 cm ⁴
Section Modulus (S)	6.40 cm ³	18.86 cm ³
Radius of Gyration (r)	2.15 cm	3.53 cm
Axis 2-2		
Moment of Inertia (I)	13.91 cm ⁴	27.83 cm ⁴
Section Modulus (S)	6.74 cm ³	13.48 cm ³
Radius of Gyration (r)	1.72 cm	1.72 cm

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.



1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
2. Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 62 for reduction factors for unbraced lengths.
3. For pierced channel, multiply beam loads by the following factor:

"KO" Series.....95%	"T" Series85%
"HS" Series90%	"SL" Series85%
"WT" Series.....85%	
4. Deduct channel weight from the beam loads.
5. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
6. All beam loads are for bending about Axis 1-1.



P1184 P

CP





Material: Paintable PVC
 Color: Green, Grey
 Standard length: 10' (3m)

Wt/100 Ft: 11 Lbs (16.5 kg/100 m)

P3184

CPG





Finish: GR, PG, PL
 Standard length: 10' (3m)

Wt/100 Ft: 47 Lbs (69.9 kg/100 m)

P3184 F

P3184 P





Material : G.E. Noryl® Plastic
 Color: Green, Grey and White
 Standard length: 10' (3m)

Wt/100 Ft: 9.4 Lbs (14.0 kg/100 m)



P3712 P

CP




Finish: GR, PG, PL
 Standard length: 16' (4.9m)

Wt/100 Ft: 90 Lbs (134 kg/100 m)



Material: Plastic
 Color: Black
 Standard length: 10' (3m)
 Note: Use with P3170, P3270, and
 P3370 series concrete insert.

Wt/100 Ft: 5.4 Lbs (8.0 kg/100 m)

P1280**EG**

Use with P1000
Material: .060" (1.5)


Wt/100 pcs: 11 Lbs (5.0 Kg.)

P2407, P3280, P3380**END CAPS****EG**

Part Number	Fits Channel	Wt/100 pcs Lbs (kg)
P2407	P1000	10 4.5
P3280	P3000	8 3.6
P3380*	P3300	5 2.3


P1180, P2280, P4280, P5280, P5580**EG**

Part Number	Use With Channel	Wt/100 pcs Lbs (kg)
P1180	P1100	12 5.4
P2280	P2000	11 5.0
P4280	P4000	5 2.3
P5280	P5000	22 10.0
P5580	P5500	17 7.7

P1280 A, P2280 A





Part Number	Use With Channel	Wt/100 pcs Lbs (kg)
P1280A	P1000	11 5.0
P2280A	P2000	11 5.0

Material: .075" (1.9)

P2859**FRAME CAPS****GY WH**

Part Number*	Use With Channel	Wt/100 pcs Lbs (kg)
P2859-10	P1000	12 5.4
P2859-11	P1001	12 5.4
P2859-12	P3300	5 2.3
P2859-13	P5000	22 10.0
P2859-14	P5500	17 7.7

* Add color suffix:
GR - Green
WH - White
GY - Grey
"A" series frame caps available

P2860**PLASTIC WHITE END CAPS****VY****P2860-10**

Use with P1000, P1100, P2000 channels & P9000 Telestrut.
Wt/100 pcs 3.4 Lbs (1.5 kg)

P2860-33

Use with P3300 channel.
Wt/100 pcs 2.5 Lbs (1.1 kg)

P2860-50

Use with P5000 & P1001 channels.
Wt/100 pcs 5 Lbs (2.3 kg)

P2860-55

Use with P5500 channel.
Wt/100 pcs 4.7 Lbs (2.1 kg)




LATERAL BRACING LOAD REDUCTION CHARTS

Span Ft. (m)	In. (cm)	Single Channel										Double Channel											
		P1000	P1100	P2000	P3000	P3300	P4000	P4100	P4400	P4520	P5000	P5500	P1001	P1101	P2001	P3001	P3301	P4001	P4101	P4401	P4521	P5001	P5501
2 (0.61)	24 (61)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.98	0.99	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
3 (0.91)	36 (91)	0.94	0.89	0.88	0.96	1.00	0.94	0.98	1.00	1.00	0.85	0.89	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
4 (1.22)	48 (122)	0.88	0.78	0.75	0.91	1.00	0.88	0.94	0.98	1.00	0.70	0.77	1.00	0.98	0.98	1.00	1.00	0.98	1.00	1.00	1.00	0.97	0.98
5 (1.52)	60 (152)	0.82	0.68	0.61	0.88	0.98	0.83	0.91	0.96	1.00	0.55	0.67	0.97	0.93	0.92	0.98	1.00	0.93	0.96	1.00	1.00	0.90	0.93
6 (1.83)	72 (183)	0.78	0.59	0.48	0.84	0.97	0.79	0.89	0.94	0.98	0.44	0.58	0.93	0.87	0.85	0.95	0.97	0.88	0.92	0.97	0.97	0.83	0.87
7 (2.13)	84 (213)	0.75	0.52	0.41	0.82	0.96	0.75	0.86	0.92	0.97	0.38	0.51	0.89	0.82	0.78	0.92	0.95	0.83	0.89	0.95	0.95	0.76	0.81
8 (2.44)	96 (244)	0.71	0.47	0.35	0.79	0.94	0.72	0.84	0.91	0.96	0.33	0.46	0.85	0.76	0.71	0.88	0.92	0.79	0.85	0.92	0.92	0.68	0.76
9 (2.74)	108 (274)	0.69	0.43	0.32	0.77	0.93	0.69	0.82	0.89	0.95	0.30	0.42	0.81	0.70	0.64	0.85	0.90	0.74	0.81	0.90	0.90	0.61	0.70
10 (3.05)	120 (305)	0.66	0.40	0.29	0.75	0.92	0.66	0.80	0.87	0.94	0.28	0.40	0.78	0.65	0.57	0.82	0.87	0.69	0.78	0.87	0.87	0.54	0.64
12 (3.66)	144 (366)	0.61	0.36	0.25	0.70	0.89	0.60	0.76	0.84	0.91	0.24	0.36	0.70	0.54	0.45	0.76	0.82	0.60	0.71	0.82	0.83	0.43	0.53
14 (4.27)	168 (427)	0.55	0.32	0.23	0.66	0.86	0.55	0.73	0.81	0.89	0.22	0.32	0.63	0.45	0.38	0.70	0.78	0.51	0.64	0.77	0.78	0.35	0.45
16 (4.88)	192 (488)	0.51	0.30	0.21	0.62	0.84	0.50	0.69	0.78	0.87	0.21	0.30	0.56	0.39	0.32	0.64	0.73	0.44	0.57	0.72	0.73	0.30	0.39
18 (5.49)	216 (549)	0.47	0.28	0.19	0.58	0.81	0.47	0.65	0.75	0.84	0.19	0.28	0.49	0.34	0.28	0.58	0.68	0.39	0.50	0.67	0.68	0.27	0.34
20 (6.10)	240 (610)	0.44	0.26	0.18	0.54	0.78	0.43	0.61	0.72	0.82	0.18	0.26	0.44	0.31	0.25	0.52	0.63	0.35	0.45	0.62	0.63	0.24	0.30

BEARING LOADS ON UNISTRUT CHANNEL

Channel	Bearing Length 1½" (41 mm) Maximum Allowable Loads Lbs (kN)		Bearing Length 1½" (41 mm) Maximum Allowable Loads Lbs (kN)		Bearing Length 3¼" (82 mm) Maximum Allowable Loads Lbs (kN)	
	6,700	29.80	3,100	13.79	7,700	34.25
P1000	3,500	15.57	1,700	7.56	4,000	17.79
P1100	2,500	11.12	1,200	5.34	3,000	13.34
P2000	6,700	29.80	3,200	14.23	7,700	34.25
P3000	6,800	30.25	3,200	14.23	7,800	34.70
P3300	2,600	11.57	1,200	5.34	3,000	13.34
P4000	3,500	15.57	1,800	8.01	4,100	18.24
P4100	7,300	32.47	3,400	15.12	8,400	37.37
P4400	7,300	32.47	3,400	15.12	8,400	37.37
P4520	6,500	28.91	3,000	13.34	7,500	33.36
P5000	6,600	29.36	3,100	13.79	7,600	33.81
P5500						



MATERIAL

TELESTRUT is accurately and carefully cold formed to size from low-carbon strip steel.

STEEL: PLAIN

12 Ga. (2.7 mm), ASTM A1011 SS GR 33.

STEEL: PRE-GALVANIZED

12 Ga. (2.7 mm), ASTM A653 GR 33.

FINISHES

Telestrut is available in:

Plain (PL)

Pre-Galvanized (PG)

Green powder coat (GR)

Fittings are available in:

Green Powder Coat (GR), conforming to commercial standards for Powder Coating

Electro-galvanized (EG), conforming to ASTM B633 Type III SC1

Hot-dipped Galvanized (HG), conforming to ASTM A153

Plain (PL)

DIMENSIONS

Imperial dimensions are illustrated in inches. Metric dimensions are shown in parenthesis or as noted. Unless noted, all metric dimensions are in millimeters and rounded to one decimal place.

Telescoping Tube.....	65-67
Specialized Fittings	68
Connection Methods	69
Post Bases.....	68-69
Cutting Chart.....	70

DESIGN BOLT TORQUE

BOLT SIZE	1/4"-20	5/16"-18	3/8"-16	1/2"-13	5/8"-11	3/4"-10
Rec.Torque Ft/Lbs (N·m)	6 (8)	11 (15)	19 (26)	50 (68)	100 (136)	125 (170)
Max Torque Ft/Lbs (N·m)	7 (9)	15 (20)	25 (34)	70 (95)	125 (170)	135 (183)


DESIGN LOAD

Load tables and charts are constructed to be in accordance with the SPECIFICATION FOR THE DESIGN OF COLD-FORMED STEEL STRUCTURAL MEMBERS 2007 EDITION published by the AMERICAN IRON AND STEEL INSTITUTE USING ASD METHOD.

Type of Load	Safety Factor to Yield Strength
Beam Loads	1.67
Column Load	1.80




Telestrut Telescoping Tubing



1 5/8" x 1 5/8"

12 Ga.

P9000-Pg 65



1 7/8" x 1 7/8"


12 Ga.

P9200-Pg 65


Special Fittings and Post Bases for Telestrut Telescoping Tubing




P9324-Pg 68




P9011-Pg 68




P9012-Pg 68



P9013-Pg 69



P9014-Pg 69



P9207-Pg 68


Standard 1 5/8" – Flat Plate Fittings




P9209-Pg 68




P9010-Pg 68




P1065-Pg 81




P1924-Pg 81




P1066-Pg 81




P1925-Pg 81




P1067-Pg 81




P2079-Pg 81




P1941-Pg 81




P1036-Pg 81




P1380A-Pg 81




P1334-Pg 81




P1380-Pg 81




P1873-Pg 82




P1031-Pg 82




P1028-Pg 82




P1356-Pg 82



P1358-Pg 82




P1726-Pg 82




P1953-Pg 82


Standard 1 5/8" – Ninety Degree Fittings




P1950-Pg 82




P2325-Pg 81




P2324-Pg 81




P1026-Pg 82




P1068-Pg 82



P1750-Pg 83




P1281-Pg 82




P1538A-Pg 83




P1498-Pg 83




P1747-Pg 83




P1458-Pg 82




P1326-Pg 83




P1346-Pg 83




P1325-Pg 83




P1822-Pg 83




P1823-Pg 83




P1821-Pg 83




P1934-Pg 84




P1033-Pg 83




P1037-Pg 83




P1038-Pg 83




P1034-Pg 83




P1035-Pg 84




P1029-Pg 84




P1357-Pg 84




P1359-Pg 84




P1381-Pg 84




P1290-Pg 84



P1291-Pg 84




P1579-Pg 84



P1727-Pg 84


Standard 1 5/8" – "Z" and "U" Shape Fittings




P1728-Pg 84




P2235-Pg 84




P1713-Pg 84




P1130-Pg 85




P1956-Pg 84




P1957-Pg 84




P1045-Pg 86



P1347-Pg 86




P1479A-Pg 86




P1047-Pg 87


Standard 1 5/8" – Wing Shape Fittings




P1048-Pg 88




P2326-Pg 88




P2343 R-L-Pg 89




P2223-Pg 89




P2224-Pg 89




P2225-Pg 89




P2227-Pg 89




P2228-Pg 89



P2229-Pg 89




P2345-Pg 89





P2346-Pg 89

Standard 1 5/8" Metal Framing – Wing Shape Fittings




Standard 1 5/8" – Misc. Fittings



Many of the standard metal framing components are compatible with the Telestrut telescoping tubing.
Refer to the appropriate page in other sections of the catalog for information on the particular fittings shown here.

P9000


GR PG



Wt/100 Ft: 188 Lbs (279 kg/100 m)
Allowable Moment 5,140 In-Lbs (580 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)

P9200






GR PG



Wt/100 Ft: 223 Lbs (331 kg/100 m)
Allowable Moment 7,480 In-Lbs (850 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)

TELESTRUT'S TELESCOPING POWER

Telestrut can be combined with metal framing channel



Note: Will not telescope with GR or HG finish



P9000 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	1,710	0.06	1,710	1,710	1,710
36	1,140	0.14	1,140	1,140	810
48	860	0.25	860	680	450
60	690	0.40	580	440	290
72	570	0.57	400	300	200
84	490	0.77	300	220	150
96	430	1.01	230	170	110
108	380	1.27	180	130	90
120	340	1.56	150	110	70
144	290	2.30	100	80	50
168	240	3.02	70	60	40
192	210	3.95	60	40	NR
216	190	5.09	40	NR	NR
240	170	6.24	40	NR	NR

P9200 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	2,490	0.05	2,490	2,490	2,490
36	1,660	0.12	1,660	1,660	1,350
48	1,250	0.22	1,250	1,140	760
60	1,000	0.34	980	730	490
72	830	0.49	680	510	340
84	710	0.67	500	370	250
96	620	0.87	380	290	190
108	550	1.10	300	230	150
120	500	1.37	240	180	120
144	420	1.98	170	130	80
168	360	2.70	120	90	60
192	310	3.47	100	70	50
216	280	4.47	80	60	NR
240	250	5.47	60	50	NR

P9000 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	3,640	8,730	8,570	8,330	8,040
36	3,540	8,360	8,040	7,530	6,950
48	3,400	7,880	7,340	6,530	5,660
60	3,210	7,290	6,530	5,440	4,360
72	2,990	6,640	5,660	4,360	3,160
84	2,730	5,940	4,790	3,340	2,320
96	2,430	5,220	3,940	2,560	1,780
108	2,110	4,520	3,160	2,020	1,400
120	1,820	3,840	2,560	1,640	**
144	1,390	2,690	1,780	**	**

P9200 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
24	4,620	11,120	10,980	10,740	10,460
36	4,530	10,770	10,460	9,950	9,370
48	4,390	10,300	9,760	8,940	8,030
60	4,220	9,720	8,940	7,800	6,590
72	4,000	9,050	8,030	6,590	5,180
84	3,750	8,320	7,080	5,410	3,890
96	3,460	7,560	6,110	4,290	2,980
108	3,140	6,770	5,180	3,390	2,360
120	2,790	5,990	4,290	2,750	1,910
144	2,170	4,510	2,980	1,910	**
168	1,720	3,320	2,190	**	**

P9000/P9200 - ELEMENTS OF SECTION

Parameter	P9000	P9200
Area of Section	0.387	In ²
Axis 1-1		
Moment of Inertia (I)	0.166	In ⁴
Section Modulus (S)	0.205	In ³
Radius of Gyration (r)	0.655	In
Axis 2-2		
Moment of Inertia (I)	0.166	In ⁴
Section Modulus (S)	0.205	In ³
Radius of Gyration (r)	0.655	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).

4. Deduct Telestrut weight from the beam loads.

5. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.

P9000 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/z0 kN	Span/360 kN
600	7.7	2	7.7	7.7	7.7
750	6.2	2	6.2	6.2	5.3
1,000	4.7	4	4.7	4.5	3.0
1,250	3.7	7	3.7	2.9	1.9
1,500	3.1	10	2.7	2.0	1.3
1,750	2.7	13	2.0	1.5	1.0
2,000	2.3	17	1.5	1.1	0.8
2,500	1.9	27	1.0	0.7	0.5
3,000	1.6	39	0.7	0.5	0.3
3,500	1.3	53	0.5	0.4	0.3
4,000	1.2	68	0.4	0.3	0.2
4,500	1.0	86	0.3	0.2	0.1
5,000	0.9	108	0.2	0.2	NR
6,000	0.8	151	0.2	NR	NR

P9200 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	11.3	1	11.3	11.3	11.3
750	9.0	2	9.0	9.0	8.9
1,000	6.8	4	6.8	6.8	5.0
1,250	5.4	6	5.4	4.8	3.2
1,500	4.5	8	4.5	3.3	2.2
1,750	3.9	11	3.3	2.4	1.6
2,000	3.4	15	2.5	1.9	1.2
2,500	2.7	23	1.6	1.2	0.8
3,000	2.3	34	1.1	0.8	0.6
3,500	1.9	45	0.8	0.6	0.4
4,000	1.7	60	0.6	0.5	0.3
4,500	1.5	76	0.5	0.4	0.3
5,000	1.3	92	0.4	0.3	0.2
6,000	1.1	132	0.3	0.2	NR

P9000 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	16.2	38.9	38.2	37.1	35.9
750	16.0	38.2	37.1	35.5	33.7
1,000	15.6	36.7	35.0	32.3	29.4
1,250	15.0	34.8	32.3	28.6	24.6
1,500	14.4	32.6	29.4	24.6	19.8
1,750	13.6	30.3	26.2	20.6	15.3
2,000	12.7	27.8	23.0	16.8	11.7
2,250	11.7	25.2	19.8	13.3	9.3
2,500	10.5	22.6	16.8	10.8	7.5
2,750	9.3	20.0	14.0	8.9	6.2

P9200 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	20.6	49.5	48.9	47.9	46.6
750	20.4	48.8	47.9	46.3	44.4
1,000	20.0	47.4	45.7	43.1	40.1
1,250	19.5	45.6	43.1	39.3	35.1
1,500	18.8	43.5	40.1	35.1	29.9
1,750	18.1	41.1	36.8	30.7	24.6
2,000	17.2	38.5	33.4	26.3	19.7
2,250	16.2	35.7	29.9	22.1	15.6
2,500	15.1	32.9	26.3	18.2	12.6
2,750	13.9	30.1	23.0	15.0	10.4

P9000/P9200 - ELEMENTS OF SECTION (METRIC)

Parameter	P9000		P9200	
Area of Section	2.50	cm ²	3.16	cm ²
Axis 1-1				
Moment of Inertia (I)	6.92	cm ⁴	11.61	cm ⁴
Section Modulus (S)	3.35	cm ³	4.87	cm ³
Radius of Gyration (r)	1.66	cm	1.92	cm
Axis 2-2				
Moment of Inertia (I)	6.92	cm ⁴	11.61	cm ⁴
Section Modulus (S)	3.35	cm ³	4.87	cm ³
Radius of Gyration (r)	1.66	cm	1.92	cm

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
4. Deduct Telestrut weight from the beam loads.
5. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.







P9010

MULTI-GRIP RIVET

P9209

GRAVITY PIN

P9000 Inside
P9200Fitting Attached
to Tube Section
or ChannelFitting Attached
to Tube Section
with Tube Section
or Channel Inside

Wt/100 pcs: 10 Lbs (4.5 kg)




Wt/100 pcs: 47 Lbs (21.3 kg)

P9207


CUTTING ALIGNMENT GAUGE

P9324

EG, GR



The cutting alignment guide ensures correct cutting of branch members when used with fittings to make connections. Refer to the table of page 70 for the appropriate value for "A" for cutting.




Wt/100 pcs: 78 Lbs (35.0 kg)

P9011



EG, GR

P9012


EG, GR



Wt/100 pcs: 332 Lbs (150.7 kg)




Wt/100 pcs: 340 Lbs (154 kg)




Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)
 Hole Diameter: 5/16" (14mm); Hole Spacing - From End: 1 1/16" (21mm); Hole Spacing - On Center: 1 1/8" (48mm); Width: 1 5/8"(41.3mm); Thickness: 1/4" (6mm)

P9014


EG, GR



Wt/100 pcs: 303 Lbs (137.5 kg)

PREFERRED THREE-PIECE ASSEMBLY

In most applications, telescoping assemblies should be made from three sections of Telestrut material. The simplest construction utilizes a center section of $1\frac{1}{8}$ " material (P9200) into which a $1\frac{1}{8}$ " member (P9000) is telescoped from each end. In this way, all intersecting verticals and horizontals are formed from $1\frac{1}{8}$ " members assuring maximum compatibility and ease of assembly


TWO-PIECE ASSEMBLY

Two-piece telescoping assemblies can be used, but special cutting of one or both telescoping members is needed to achieve proper alignment of fittings at the intersecting connections.


In addition, the right-angle members to which telescoping pieces are attached must be cut according to the illustration at right to insure smooth movement of telescoping members.

P9013


EG, GR





Wt/100 pcs: 318 Lbs (144.7 kg)

ALTERNATE THREE-PIECE ASSEMBLY

A similar technique is to use a center $1\frac{1}{8}$ " center member (P9000) which can be telescoped into $1\frac{1}{8}$ " members used at both ends. With this method, all intersecting connections should be formed from compatible $1\frac{1}{8}$ " members.

CHANNEL NUT CONNECTION – INFINITE ADJUSTMENT

Any of the $1\frac{1}{8}$ " (41.3 mm) channel can be connected to the P9000 using standard channel nuts.

THROUGH-BOLT CONNECTION – INCREMENTAL ADJUSTMENT

Standard Dimensions for $1\frac{1}{8}$ " (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: $\frac{13}{16}$ " (14mm); Hole Spacing - From End: $1\frac{5}{16}$ " (21mm); Hole Spacing - On Center: $1\frac{1}{8}$ " (48mm); Width: $1\frac{1}{8}$ "(41.3mm); Thickness: $1\frac{1}{8}$ " (6mm)



CUTTING CHART

1½" Channel

Telestrut

Nuts & Hardware

General Fittings

Pipe/Conduit Supports


Electrical Fittings

Concrete Inserts

Unipier® Solar

Fitting	1½" (41.3) Branch		1½" (47.6) Branch	
	Trunk 1½" (41.3)	Trunk 1½" (47.6)	Trunk 1½" (41.3)	Trunk 1½" (47.6)
P1026	A	A	A	B
P1028	A	A	A	B
P1029	†	†	†	†
P1031	A	A	A	B
P1033	B	A	A	B
P1034	†	†	†	†
P1035	A	†	†	†
P1036	A	A	A	B
P1037	†	†	†	†
P1038	†	†	†	†
P1045	†	†	†	†
P1047	†	†	†	†
P1048	†	†	†	†
P1049	†	†	†	†
P1050	†	†	†	†
P1065	A	A	A	B
P1066	A	A	A	B
P1068	C	NR	NR	NR
P1130	A	A	A	C
P1131	A	A	A	C
P1290	A	NR	NR	NR
P1291	A	NR	NR	NR
P1325	A	NR	NR	NR
P1326	C	NR	NR	NR
P1334	A	A	A	B
P1346	A	A	A	B
P1347	C	NR	NR	NR
P1354	D	D	D	D
P1356	A	A	A	B
P1357	A	NR	NR	NR
P1358	A	A	A	B
P1359	A	NR	NR	NR
P1380	A	A	A	B
P1380 A	A	A	A	B
P1381	†	†	†	†
P1382	†	†	†	†
P1458	A	NR	NR	NR
P1498	†	†	†	†
P1499	†	†	†	†
P1538 A	C	A	A	C
P1538 B	C	A	A	C
P1538 C	C	A	A	C
P1538 D	C	A	A	C
P1579	A	NR	NR	NR
P1713	†	†	†	†

This table shows the value for "A" when using the specified fitting to connect the branch and trunk. Sizes "A" and "B" can be cut with the cutting alignment gauge (P9207). Other sizes require special cutting. Those marked NR are not recommended.




Fitting	1½" (41.3) Branch		1½" (47.6) Branch	
	Trunk 1½" (41.3)	Trunk 1½" (47.6)	Trunk 1½" (41.3)	Trunk 1½" (47.6)
P1726	A	A	A	B
P1727	B	NR	NR	NR
P1728	†	†	†	†
P1747	†	†	†	†
P1750	†	†	†	†
P1821	†	†	†	†
P1822	†	†	†	†
P1823	†	†	†	†
P1843	D	D	D	D
P1873	†	†	†	†
P1834	†	NR	NR	NR
P1941	A	A	A	B
P1950	A	A	A	B
P1953	A	A	A	B
P1956	†	†	†	†
P1957	†	†	†	†
P2223	A	NR	A	NR
P2224	A	NR	A	NR
P2225	A	NR	A	NR
P2226	A	NR	A	NR
P2227	A	NR	A	NR
P2228	A	NR	A	NR
P2229	A	NR	A	NR
P2230	A	NR	A	NR
P2235	A	NR	NR	NR
P2245	A	NR	A	NR
P2324	E	NR	NR	F
P2325	E	A	A	F
P2326	E	NR	NR	F
P2341 R-L	A	NR	A	NR
P2343 R-L	A	NR	A	NR
P2344 R-L	A	NR	A	NR
P2345	A	NR	A	NR
P2346	A	NR	A	NR
P2347	A	NR	A	NR
P2348	A	NR	A	NR
P2472 R-L	C	NR	A	NR
P2815	C	NR	NR	NR
P2815 D	C	NR	NR	NR
P9324	G	G	G	G
P9325	A	A	A	A
P9484	A	A	A	A

Legend

Designator	"A" In (mm)
A	1½" 27.0
B	1¾" 23.8
C	1⅓" 20.6
D	1¼" 31.8
E	¾" * 15.9

Designator	"A" In (mm)
F	7/16" * 11.1
G	1⅓" 29.4
NR	Not Recommended
†	Special Cutting Req'd (See part dwg)



MATERIAL

Unistrut channel nuts are manufactured from mild steel cold rolled coil, and after stamping and machining operations are completed, they are case hardened, assuring positive biting action into the turned edge of the Unistrut channel.

Screws conform to SAE J429 GR 2 (exceeds ASTM A307). Proof Load 55KSI, Tensile Load 74 KSI

Bolt Size	Channel Nut ASTM
1/4" & 5/16"	A1011 SS GR33
3/8", 7/16" & 1/2"	A576 GR1015 Modified
5/8" & 3/4"	A36 or A675 GR60
7/8"	A36

FINISHES

All Channel nuts are available in:

Electro-galvanized (EG), conforming to ASTM B633 type III SC1

Hot-dipped galvanized (HG), conforming to ASTM A153

Plain (PL)

Unistrut Defender™ (DF), conforming to ASTM A1059

Hardware items such as Hex Nuts bolts and washers are Electro-Galvanized (EG), ASTM B633 Type III SC1 finish, unless otherwise noted.

Many hardware items are also available in stainless steel. Consult factory for ordering information.

Channel Nuts With Springs	73
Channel Nuts Without Springs	73
Top Retainer Nuts	73
Stud Nuts.....	74
Hardware.....	74-76

THREADS

Unistrut nuts and bolts are manufactured to meet the Unified Screw Thread standard, ANSI B1.1, coarse series (UNC) class 2.

DESIGN BOLT TORQUE

BOLT SIZE	1/4"-20	5/16"-18	3/8"-16	1/2"-13	5/8"-11	3/4"-10
Rec.Torque Ft/Lbs (N·m)	6 (8)	11 (15)	19 (26)	50 (68)	100 (136)	125 (170)
Max Torque Ft/Lbs (N·m)	7 (9)	15 (20)	25 (34)	70 (95)	125 (170)	135 (183)

DIMENSIONS

Imperial dimensions are illustrated in inches. Metric dimensions are shown in parenthesis or as noted. Unless noted, all metric dimensions are in millimeters and rounded to one decimal place.

Many Unistrut nuts, bolts and hardware items are also available in standard metric dimensions. Consult factory for ordering information.





Channel Nuts With Spring

P1006 - P1010
Pg 73P1012S - P1024S
Pg 73P4006 - P4010
Pg 73P5506 - P5510
Pg 73P2378 - P2382
Pg 74

Channel Nuts Without Spring

P3016
Pg 73P3006 - P3013
Pg 73P1012 - P1024
Pg 73P4012 - P4023
Pg 73P1006T - P1010T, P4010T
Pg 73P4908
Pg 73P1016
Pg 73

Hardware

HHCS
Pg 74HFMS
Pg 74HRMS
Pg 74HSHS
Pg 74HCSS
Pg 74HSQN
Pg 75HHXN
Pg 75HFLW
Pg 75HLKW
Pg 75HOCW
Pg 76HTHR
Pg 75HRCN
Pg 75P2486
Pg 76P2485
Pg 76P2485K
Pg 76K1062 - K1064
Pg 76

MAXIMUM ALLOWABLE PULL-OUT AND SLIP LOADS

Channel	Channel Nut Size-Thread	Gauge	Allowable Pull-Out Strength Lbs (kN)	Resistance to Slip Lbs (kN)	Torque Ft-Lbs (N·m)
P1000 P3000 P4400 P4526 P5000 P5500	7/8" - 9	12	2,500 11.12	1,700 7.56	*125 170
	3/4" - 10	12	2,500 11.12	1,700 7.56	*125 170
	5/8" - 11	12	2,500 11.12	1,500 6.67	*100 135
	1/2" - 13	12	2,000 8.90	1,500 6.67	50 70
	7/16" - 14	12	1,400 6.23	1,000 4.45	35 50
	5/8" - 16	12	1,000 4.45	800 3.56	19 25
	5/16" - 18	12	800 3.56	500 2.22	11 15
	1/4" - 20	12	600 2.67	300 1.33	6 8
P3300	1/2" - 13	12	1,500 6.67	1,500 6.67	50 70
	3/8" - 16	12	1,000 4.45	800 3.56	19 25
	5/16" - 18	12	800 3.56	500 2.22	11 15
	1/4" - 20	12	600 2.67	300 1.33	6 8

Channel	Channel Nut Size-Thread	Gauge	Allowable Pull-Out Strength Lbs (kN)	Resistance to Slip Lbs (kN)	Torque Ft-Lbs (N·m)
P1100 & P4100	1/2" - 13	14	1,400 6.23	1,000 4.45	50 70
	3/8" - 16	14	1,000 4.45	750 3.34	19 25
	5/16" - 18	14	800 3.56	400 1.78	11 15
	1/4" - 20	14	600 2.67	300 1.33	6 8
P2000 & P4000	1/2" - 13	16	1,000 4.45	1,000 4.54	50 70
	3/8" - 16	16	1,000 4.45	750 3.34	19 25
	5/16" - 18	16	800 3.56	400 1.78	11 15
	1/4" - 20	16	600 2.67	300 1.33	6 8

* May require 5/8" or 1/2" thick fitting.

Nut design loads include a minimum safety factor of 3.

Note: Refer to the Channel Nut Selection Chart on the following two pages for the part number.

CHANNEL NUT WITH SPRING

EG, HG

	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P1006-0832	#8 -32	7 (3.2)	P1000, P1100, P2000, P3000
	P1006-1024	#10 -24	7 (3.2)	
	P1006-1420	1/4" -20	7 (3.2)	
	P1007	5/16" -18	6 (2.7)	
	P1008	3/8" -16	10 (4.5)	
	P1009	7/16" -14	9 (4.1)	
	P1010	1/2" -13	12 (5.4)	
	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P1012S	5/8" -11	21 (9.5)	P1000, P1100, P2000, P3000
	P1023S	3/4" -10	21 (9.5)	
	P1024S	7/8" -9	21 (9.5)	
	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P4006-0832	# 8 -32	7 (3.2)	P3300, P4000, P4400, P4520, P4100
	P4006-1024	#10 -24	7 (3.2)	
	P4006-1420	1/4" -20	7 (3.2)	
	P4007	5/16" -18	6 (2.7)	
	P4008	3/8" -16	9 (4.1)	
	P4009	7/16" -14	9 (4.1)	
	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P5506-0832	#8 -32	7 (3.2)	P5000, P5500
	P5506-1024	#10 -24	7 (3.2)	
	P5506-1420	1/4" -20	7 (3.2)	
	P5507	5/16" -18	6 (2.7)	
	P5508	3/8" -16	10 (4.5)	
	P5509	7/16" -14	10 (4.5)	
	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P5510	1/2" -13	12 (5.4)	

CHANNEL NUT WITHOUT SPRING

EG, HG

	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P3016-0632	#6 -32	2 (0.9)	Any Channel
	P3016-0832	#8 -32	2 (0.9)	
	P3016-1024	#10 -24	4 (1.8)	
	P3016-1420	1/4" -20	4 (1.8)	
	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P3006-0832	#8 -32	6 (2.7)	Any Channel
	P3006-1024	#10 -24	6 (2.7)	
	P3006-1420	1/4" -20	6 (2.7)	
	P3007	5/16" -18	6 (2.7)	
	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P3008	3/8" -16	9 (4.1)	Any Channel Except P3300, P4000, P4400, P4520, P4100
	P3009	7/16" -14	9 (4.1)	
	P3010	1/2" -13	11 (5.0)	
	P3013	1/2" -13	8 (3.6)	
	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P1012	5/8" -11	20 (9.1)	Any Channel Except P3300, P4000, P4400, P4520, P4100
	P1023	3/4" -10	20 (9.1)	
	P1024	7/8" -9	20 (9.1)	
	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P4012	5/8" -11	11 (5.0)	P3300, P4000, P4400, P4520, P4100
	P4023	3/4" -10	11 (5.0)	
	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P1006T1420	1/4" -20	7 (3.2)	Any Channel
	P1008T	5/8" -16	10 (4.5)	
	P1010T	1/2" -13	12 (5.4)	Any Channel Except P3300, P4000, P4400, P4520, P4100
	P4010T	1/2" -13	8 (3.6)	
	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P4908	3/8" -16	17.5 (7.9)	Any Channel
	Double Conveyor Adjusting Nut			
	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	P1016	3/8" -16	17.5 (7.9)	Any "T" Slotted Channel
	Missing Link Multi-Purpose Strut Fastener			



CHANNEL STUD NUT WITH SPRING

EG



All Stud Nut grooves are serrated.

Part No.	Thread	"A" Stud In (mm)	Wt/100 pcs Lbs (kg)
P2378-1	1/4" - 20	1 (25.4)	8 (3.6)
P2378-2		1/4 (31.8)	9 (4.1)
P2378-3		1 1/2 (38.1)	9 (4.1)
P2379-1		1 (25.4)	12 (5.4)
P2379-2		1/4 (31.8)	12 (5.4)
P2379-3		1 1/2 (38.1)	13 (5.9)
P2380-1		1 (25.4)	13 (5.9)
P2380-2		1/4 (31.8)	13 (5.9)
P2380-3		1 1/2 (38.1)	13 (5.9)
P2380-4		1 1/4 (44.5)	15 (6.8)
Use With P1000, P1100, P2000, P3000			

Part No.	Thread	"A" Stud In (mm)	Wt/100 pcs Lbs (kg)
P2380-5	5/8" - 16	2 (50.8)	16 (7.3)
P2380-6		2 1/4 (57.2)	16 (7.3)
P2381-2		1 (25.4)	14 (6.4)
P2381-3		1/4 (31.8)	15 (6.8)
P2381-4		1 1/2 (38.1)	17 (7.7)
P2381-5		1 1/4 (44.5)	18 (8.2)
P2381-6		2 (50.8)	19 (8.6)
P2381-7		2 1/4 (57.2)	20 (9.1)
P2382-2		1 1/4 (31.8)	18 (8.2)
P2382-3		1 1/2 (38.1)	20 (9.1)
Use With P1000, P1100, P2000, P3000			

HEX HEAD CAP SCREWS

CDF EG



HEX SLOTTED MACHINE SCREWS



FLAT HEAD MACHINE SCREWS



Part No.	Size	Wt/100 pcs Lbs (kg)
HHCS025044EG	1/4" x 7/16"	1.0 (0.5)
HHCS025075EG	1/4" x 3/4"	1.3 (0.6)
HHCS025150EG	1/4" x 1 1/2"	2.6 (1.2)
HHCS031125EG	5/16" x 1 1/4"	3.6 (1.6)
HHCS037075EG	3/8" x 3/4"	4.0 (1.8)
HHCS037087EG	3/8" x 7/8"	4.4 (2.0)
HHCS037100EG	3/8" x 1"	4.5 (2.0)
HHCS037125EG	3/8" x 1 1/4"	5.3 (2.4)
HHCS037150EG	3/8" x 1 1/2"	6.0 (2.7)
HHCS037200EG	3/8" x 2"	7.6 (3.4)
HHCS037225EG	3/8" x 2 1/4"	8.4 (3.8)
HHCS037250EG	3/8" x 2 1/2"	9.2 (4.2)
HHCS050094EG	1/2" x 15/16"	9.1 (4.1)
HHCS050119EG	1/2" x 1 3/16"	10.2 (4.6)
HHCS050125EG	1/2" x 1 1/4"	11.0 (5.0)
HHCS050150EG	1/2" x 1 1/2"	11.6 (5.3)
HHCS050175EG	1/2" x 1 3/4"	13.1 (5.9)
HHCS050200EG	1/2" x 2"	14.6 (6.6)
HHCS050225EG	1/2" x 2 1/4"	16 (7.3)
HHCS050250EG	1/2" x 2 1/2"	17.5 (7.9)

Part No.	Size	Wt/100 pcs Lbs (kg)
HSHS025050EG	1/4" x 1/2"	1.4 (0.6)
HSHS025062EG	1/4" x 5/8"	1.5 (0.7)
HSHS025075EG	1/4" x 3/4"	1.7 (0.8)
HSHS031100EG	5/16" x 1"	2.6 (1.2)
HSHS031125EG	5/16" x 1 1/4"	3.0 (1.4)
HSHS031150EG	5/16" x 1 1/2"	3.4 (1.5)
HSHS037125EG	3/8" x 1 1/4"	5.3 (2.4)

Part No.	Size	Wt/100 pcs Lbs (kg)
HFMS025062EG	1/4" x 5/8"	1.2 (0.5)
HFMS031100EG	5/16" x 1"	2.6 (1.2)
HFMS050100EG	1/2" x 1"	9.3 (4.2)

CONE POINT SET SCREWS



ROUND HEAD MACHINE SCREWS



Part No.	Size	Wt/100 pcs Lbs (kg)
HCSS025100EG	1/4" x 1"	2.8 (1.3)
HCSS031150EG	5/16" x 1 1/2"	3.9 (1.8)
HCSS037150EG	3/8" x 1 1/2"	4.5 (2.0)
HCSS037200EG	3/8" x 2"	6.1 (2.8)
HCSS050150EG	1/2" x 1 1/2"	8.5 (3.9)
HCSS050200EG	1/2" x 2"	11.4 (5.2)
HCSS062150EG	5/8" x 1 1/2"	14.5 (6.6)
HCSS062200EG	5/8" x 2"	23.0 (10.4)

Part No.	Size	Wt/100 pcs Lbs (kg)
HRMS025050EG	1/4" x 1/2"	1 (0.5)
HRMS025075EG	1/4" x 3/4"	1.2 (0.5)
HRMS025100EG	1/4" x 1"	1.5 (0.7)
HRMS031100EG	5/16" x 1"	2.6 (1.2)
HRMS031125EG	5/16" x 1 1/4"	3.0 (1.4)
HRMS037100EG	3/8" x 1"	4.1 (1.9)
HRMS037125EG	3/8" x 1 1/4"	4.7 (2.1)
HRMS037150EG	3/8" x 1 1/2"	5.3 (2.4)

SQUARE NUTS



HEXAGON NUTS

DF EG

FLAT WASHERS

DF EG


Part No.	Size	Wt/100 pcs Lbs (kg)
HSQN025EG	1/4"	0.9 (0.4)
HSQN031EG	5/16"	1.6 (0.7)
HSQN037EG	3/8"	2.7 (1.2)
HSQN050EG	1/2"	5.8 (2.6)
HSQN062EG	5/8"	10.7 (4.9)
HSQN075EG	3/4"	15.4 (6.9)
HSQN087EG	7/8"	24.9 (11.3)
HSQN100EG	1"	36.3 (16.5)

Part No.	Size	Wt/100 pcs Lbs(kg)
HHXN025EG	1/4"	0.6 (0.3)
HHXN031EG	5/16"	1.2 (0.5)
HHXN037EG	3/8"	1.6 (0.7)
HHXN050EG	1/2"	4.8 (2.2)
HHXN062EG	5/8"	7.3 (3.3)
HHXN075EG	3/4"	11.9 (5.4)
HHXN087EG	7/8"	19.0 (8.6)
HHXN100EG	1"	28.3 (12.8)

Part No.	Size	Wt/100 pcs Lbs(kg)
HFLW025EG	1/4"	0.8 (0.4)
HFLW031EG	5/16"	1.0 (0.5)
HFLW037EG	3/8"	1.5 (0.7)
HFLW050EG	1/2"	3.5 (1.6)
HFLW062EG	5/8"	7.7 (3.5)
HFLW075EG	3/4"	11.0 (5.0)
HFLW087EG	7/8"	15.3 (6.9)
HFLW100EG	1"	18.8 (8.5)

STEEL THREADED ROD

DF EG



Low Carbon Steel Grade 1006 - 1010
 $F_y = 36,000 \text{ psi}$ minimum
 $F_t = 58,000 \text{ psi}$ minimum

Standard Length 12' (3.7m)

Part No.	Size	Wt/100 Ft. Lbs (kg)
HTHR025	1/4" x 20	13 (5.9)
HTHR031	5/16" x 18	20 (9.1)
HTHR037	3/8" x 16	30 (13.6)
HTHR044	7/16" x 14	30 (13.6)
HTHR050	1/2" x 13	53 (24.0)
HTHR062	5/8" x 11	84 (38.1)
HTHR075	3/4" x 10	124 (56.2)
HTHR087	7/8" x 9	170 (77.1)
HTHR100	1" x 8	223 (101.2)

LOCK WASHERS

DF EG




Part No.	Size	Wt/100 pcs Lbs (kg)
HLKW025EG	1/4"	0.25 (0.1)
HLKW031EG	5/16"	0.41 (0.2)
HLKW037EG	3/8"	0.63 (0.3)
HLKW050EG	1/2"	1.32 (0.60)
HLKW062EG	5/8"	2.20 (1.0)
HLKW075EG	3/4"	3.80 (1.7)
HLKW087EG	7/8"	6.00 (2.7)
HLKW100EG	1"	8.80 (4.0)

LOAD CARRYING CAPACITY OF THREADED HOT ROLLED STEEL
 CONFORMING TO ASTM A575 AND A576

STEEL COUPLER NUTS

DF EG



Threaded Rod Loads for Piping Applications (based on MSS SP-58)		
Nominal Dia.	Root Area In ² (mm ²)	Max. Safe Load at 650°F (343°C) Lbs (kN)
5/8	0.068 (43.9)	730 (3.25)
1/2	0.126 (81.3)	1,350 (6.01)
5/8	0.202 (130.3)	2,160 (9.61)
3/4	0.302 (194.8)	3,230 (14.37)
7/8	0.419 (270.3)	4,480 (19.93)
1	0.552 (356.1)	5,900 (26.24)



Threaded Rod Loads for Structural Applications		
(Based on AISC, Steel Construction Manual, ASD, 14th Edition. Per AISC, Allowed Tensile Stress = 0.33 * F _u)		
Nominal Dia.	Nominal Area In ² (mm ²)	Allowed Tension Load Lbs (kN)
1/4	0.049 (31.6)	930 (4.14)
5/8	0.110 (71.0)	2,110 (9.39)
7/16	0.150 (96.8)	2,870 (12.77)
1/2	0.196 (126.5)	3,750 (16.68)
5/8	0.307 (198.2)	5,870 (26.11)
3/4	0.442 (285.4)	8,450 (37.59)
7/8	0.601 (388.0)	11,500 (51.15)
1	0.785 (506.8)	15,030 (66.86)

Part Number	Size	Length In (mm)	Wt/100 pcs Lbs (kg)
HRCN025	1/4" - 20	7/8" (22.2)	1.9 (0.9)
HRCN031	5/16" - 18	1 3/4" (44.5)	7.5 (3.4)
HRCN037	3/8" - 16	1 3/4" (44.5)	9.0 (4.1)
HRCN044	7/16" - 14	1 3/4" (44.5)	10.4 (4.7)
HRCN050	1/2" - 13	1 3/4" (44.5)	10.0 (4.5)
HRCN062	5/8" - 11	2 1/8" (54.0)	18.0 (8.2)
HRCN075	3/4" - 10	2 1/4" (57.2)	28.0 (12.7)
HRCN087	7/8" - 9	2 1/2" (63.5)	55.0 (24.9)
HRCN100	1" - 8	2 3/4" (69.9)	73.0 (33.1)




SLOT ADAPTER™

EG




KWIW WASHER™

EG





Overhead installation with one hand.
Available in zinc plated and hot dip galvanized



P2486 SEISMIC ROD STIFFENER

EG





Wt/100 pcs: 16 Lbs (7.3 kg)

Part No.	Size In (mm)	Load Lbs (kN)	Wt/100 pcs Lbs (kg)
K1062	1/4" (6.4)	250 (1.11)	1.2 (0.5)
K1063	3/8" (9.5)	610 (2.71)	2.6 (1.2)
K1064	1/2" (12.7)	1,130 (5.03)	9.3 (4.2)

P2485 CRADLE CLIP




EG



Cradle clip only, order other items separately.

P2485K

SEISMIC CRADLE CLIP ASSEMBLY



Wt/100 pcs: 3.0 Lbs (1.4 kg)

P2485 & P2486 – SPACING CHART


Rod Stiffener Clip Spacing (L).....							
Rod Size In (mm)	Root Area In ² (mm ²)	Radius of Gyration In (mm)	Design Load Lbs (kN)	Rod Stress @100% In (mm)	Rod Stress @75% In (mm)	Rod Stress @50% In (mm)	Rod Stress @35% In (mm)
3/8	0.068	0.074	730	9	11	13	15
9.5	49.5	1.99	3.25	228.6	279.4	330.2	381.0
1/2	0.126	0.100	1,350	12	14	17	21
12.7	72.4	2.40	6.01	304.8	355.6	431.8	533.4
5/8	0.202	0.127	2,160	15	18	22	26
15.9	138.3	3.32	9.61	381.0	457.2	558.8	660.4

Notes:

1. Minimum Tensile Stress is 50,000 psi (345MPa)
2. Working Stress is 10,700 psi (73.9 MPa) – Same as for Tension
3. Compression Will Only Occur During a Seismic Event
4. Compression Requires the Use of Rod Stiffeners
5. KL/r = 200 When Rod Stress is at 35%

Refer to seismic bracing systems catalog for more detailed information.

GENERAL FITTINGS



MATERIAL

Fittings, unless noted, are made from hot-rolled, pickled and oiled steel plates, bar, strip or coil, and conform to one or more of the following specifications: ASTM specifications A575, A576, A635, A1011 SS GR 33, A1011 HSLAS GR 45 or A36. All fittings meet or exceed physical properties of ASTM A1011 GR 33. The pickling of the steel produces a smooth surface free from scale.

Many fittings are also available in stainless steel, aluminum and fiberglass. Consult factory for ordering information.

FINISHES

Fittings are available in:

- Green Powder Coat (GR), conforming to commercial standards for Powder Coating
- Electro-galvanized (EG), conforming to ASTM B633 Type III SC1;
- Hot-dipped galvanized (HG), conforming to ASTM A123 or A153 and
- Plain (PL)
- Unistrut Defender (DF), conforming to ASTM A1059 or A1046

APPLICATION

All parts drawings illustrate only one application of each fitting. In most cases many other applications are possible. The channels shown in the illustrations are P1000, 1 $\frac{5}{8}$ " square, except where noted otherwise.

All $\frac{1}{16}$ " diameter holes use $\frac{1}{2}$ " x $1\frac{5}{16}$ " hex head cap screws and $\frac{1}{2}$ " nuts – P1010, P3010, P4010 or P5510 – depending on the channel used. Nuts and bolts are not included with the fitting and must be ordered separately.

Flat Plate Fittings	81 - 82
Ninety Degree Fittings.....	82 - 85
Angular Fittings	85
"Z" Shape Fittings.....	86
"U" Shape Fittings	87 - 88
Wing Shape Fittings	89 - 90
Post Bases.....	90
Brackets	90 - 93
Brace Fittings.....	94
Beam Clamps.....	95 - 101
Trolleys.....	102
Special Application Fittings.....	103 - 104
Seismic Retrofit Fittings.....	104 - 106

DESIGN BOLT TORQUE

BOLT SIZE	$\frac{1}{4}$ "-20	$\frac{5}{16}$ "-18	$\frac{3}{8}$ "-16	$\frac{1}{2}$ "-13	$\frac{5}{8}$ "-11	$\frac{3}{4}$ "-10
Rec. Torque Ft/Lbs (N•m)	6 (8)	11 (15)	19 (26)	50 (68)	100 (136)	125 (170)
Max Torque Ft/Lbs (N•m)	7 (9)	15 (20)	25 (34)	70 (95)	125 (170)	135 (183)

SET SCREW TORQUE

BOLT SIZE	$\frac{1}{4}$ "-20	$\frac{3}{8}$ "-16	$\frac{1}{2}$ "-13	$\frac{5}{8}$ "-11	$\frac{3}{4}$ "-10	$\frac{7}{8}$ "-9
Set Screw Torque In/Lbs (N•m)	40 (4)	60 (7)	125 (14)	250 (28)	400 (44.5)	665 (75)

Note: Caution should be taken not to overtighten the set screw

DIMENSIONS

Imperial dimensions are illustrated in inches. Metric dimensions are shown in parenthesis or as noted. Unless noted, all metric dimensions are in millimeters and rounded to one decimal place.

DESIGN LOAD


Design load data, where shown, is based on the ultimate strength of the connection with a safety factor of 2.5, unless otherwise noted.

BEAM CLAMPS


Clamps are designed to be used with W, M, S and HP Shape beams, Standard C and Miscellaneous MC Channels, Angles and Structural Tees. Clamps must be used in pairs mounted in opposite directions where indicated. For beam clamps with HG finish, standard hardware is EG finish. For optional stainless steel hardware, please contact the factory for availability.

**Flat Plate Fittings**


P1062-Pg 81 P1959-Pg 81 P2862-Pg 81 P1065-Pg 81 P1924-Pg 81 P2325-Pg 81 P2324-Pg 81 P1066-Pg 81 P1925-Pg 81 P1067-Pg 81 P2079-Pg 81 P1941-Pg 81 P1036-Pg 81




P1380 A-Pg 81 P1334-Pg 81 P1380-Pg 81 P1873-Pg 82 P1031-Pg 82 P1028-Pg 82 P1356-Pg 82 P1358-Pg 82 P1726-Pg 82 P1953-Pg 82 P1950-Pg 82 P1962-Pg 82

Angle Fittings


P2626-Pg 82 P1026-Pg 82 P1723-Pg 82 P1068-Pg 82 P1281-Pg 82 P1315-Pg 82 P1458-Pg 82 P1538A-Pg 83 P1750-Pg 83 P1498-Pg 83 P1747-Pg 83 P1326-Pg 83 P1821-Pg 83




P1346-Pg 83 P1325-Pg 83 P1822-Pg 83 P1823-Pg 83 P1033-Pg 83 P1037-Pg 83 P1038-Pg 83 P1034-Pg 83 P1029-Pg 84 P1035-Pg 84 P1290-Pg 84 P1291-Pg 84




P1357-Pg 84 P1359-Pg 84 P1381-Pg 84 P1382-Pg 84 P1934-Pg 84 P1713-Pg 84 P1579-Pg 84 P1727-Pg 84 P1728-Pg 84 P2235-Pg 84 P1956-Pg 84 P1957-Pg 84

"Z" Shape Fittings


P2484-Pg 85 P2484W-Pg 85 P1130-Pg 85 P1546-Pg 85 P2101-Pg 85 P1186-Pg 85 P2260-Pg 85 P1045-Pg 86 P1347-Pg 86 P1453-Pg 86 P1454-Pg 86



P1479A-Pg 86 P1730-Pg 86 P1734-Pg 86 P1736-Pg 86 P2360-Pg 86 P5560-Pg 86 P3045-Pg 86 P3345, P612-Pg 86 P4045-Pg 86 P5545-Pg 86 P2469-Pg 86

"U" Shape Fittings


P2800-Pg 87 P1320-Pg 87 P1363A-Pg 87 P1376-Pg 87 P4376-Pg 87 P1376A-Pg 87 P4376A-Pg 87 P1377-Pg 87 P1047-Pg 87 P3047, P976-Pg 87 P4047-Pg 87 P1455-Pg 87








P5547-Pg 87 P1383-Pg 88 P1732-Pg 88 P2237-Pg 88 P5543-Pg 88 P1048-Pg 88 P1043A-Pg 88 P1737-Pg 88 P2473-Pg 88 P4043-Pg 88 P1044-Pg 88 P1973-Pg 88



P2326-Pg 88 P2328-Pg 88 P2329-Pg 88

Wing Shape Fittings

Post Bases

**Brackets and Brace Fittings****Beam Clamps****Trolley Assemblies****Special Applications Fittings**



DESIGN LOAD DATA FOR TYPICAL UNISTRUT CHANNEL CONNECTIONS

90° Fittings (When used in position shown)

		Channel Thickness		
Load - P1026		12 ga.	14 ga.	16 ga.
Lbs		1,500	1,000	750
kN		6.67	4.45	3.34

LOAD

		Channel Thickness		
Load - P2484		12 ga.	14 ga.	16 ga.
Lbs		3,000	2,000	1,500
kN		13.34	8.90	6.67

LOAD

		Channel Thickness		
Load - P1026		12 ga.	14 ga.	16 ga.
Lbs		1,000	650	500
kN		4.45	2.89	2.22

LOAD

		Channel Thickness		
Load - P1068		12 ga.	14 ga.	16 ga.
Lbs		500	500	500
kN		2.22	2.22	2.22

LOAD

		Channel Thickness		
Load - P1325, P2235		12 ga.	14 ga.	16 ga.
Lbs		2,000	2,000	1,500
kN		8.90	8.90	6.67

LOAD

		Channel Thickness		
Load - P1326		12 ga.	14 ga.	16 ga.
Lbs		500	500	500
kN		2.22	2.22	2.22

LOAD

		Channel Thickness		
Load - P1458, P1579		12 ga.	14 ga.	16 ga.
Lbs		1,500	1,000	1,000
kN		6.67	4.45	4.45

LOAD

		Channel Thickness		
Load - P1346		12 ga.	14 ga.	16 ga.
Lbs		1,200	1,200	1,000
kN		5.34	5.34	4.45

LOAD

		Channel Thickness		
Load - P1346		12 ga.	14 ga.	16 ga.
Lbs		2,000	1,500	900
kN		8.90	6.67	4.00

LOAD


		Channel Thickness		
Load - P1065		12 ga.	14 ga.	16 ga.
Lbs		1,000	800	600
kN		4.45	3.56	2.67

LOAD

Note:


- (1) Both ends of beams supported.
- (2) Load data is based on P1010 nut and ½" bolt.
- (3) Safety factor = 2½ based on ultimate strength of connection.

P1062, P1063, P1064, P1964,
P2471, P2490 DF, EG, GR, HG




Part No.	Bolt Size	Hole Size	Wt/100 pcs
P1062	5/16"	1 1/32"	18 (8.2)
	Lbs (kg)		
P1063	3/8"	7/16"	18 (8.2)
P1064	1/2"	9/16"	17 (7.7)
P1964	5/8"	11/16"	16 (7.3)
P2471	3/4"	13/16"	15 (6.8)
P2490	7/8"	15/16"	14 (6.4)


P1959, P1960,
P1961 EG, GR, HG




P2862, 2863,
2864 DF, EG, GR, HG



P1065 DF, EG, GR, HG




P1924 EG, GR, HG




Wt/100 pcs: 35 Lbs (15.9 kg)

P2325 EG, GR, HG




Wt/100 pcs: 55 Lbs (24.9 kg)

P2324 DF, EG, GR, HG




Wt/100 pcs: 38 Lbs (17.2 kg)

P1066 DF, EG, GR, HG




P1925 EG, GR, HG




Wt/100 pcs: 50 Lbs (22.7 kg)

P1067 EG, GR, HG




Wt/100 pcs: 78 Lbs (35.4 kg)

P2079 EG, GR, HG




Wt/100 pcs: 75 Lbs (34.0 kg)

P1941 EG, GR, HG




Wt/100 pcs: 56 Lbs (25.4 kg)

P1036 DF, EG, GR, HG




Wt/100 pcs: 58 Lbs (26.3 kg)

P1380 A DF, EG, GR, HG




Wt/100 pcs: 80 Lbs (36.3 kg)

P1334 EG, GR, HG



Wt/100 pcs: 70 Lbs (31.8 kg)

P1380 EG, GR, HG



Wt/100 pcs: 105 Lbs (47.6 kg)


Standard Dimensions for 1 5/16" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 13/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (47.6mm); Width: 1 5/16" (41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45



P1873


EG, GR, HG



Wt/100 pcs: 150 Lbs (68.0 kg)

P1031


DF, EG, GR, HG



Wt/100 pcs: 80 Lbs (36.3 kg)

P1028


DF, EG, GR, HG



Wt/100 pcs: 105 Lbs (47.6 kg)

P1356


EG, GR, HG



Wt/100 pcs: 70 Lbs (31.8 kg)

P1358


EG, GR, HG



Wt/100 pcs: 105 Lbs (47.6 kg)

P1726


EG, GR, HG



Wt/100 pcs: 148 Lbs (67.1 kg)

P1953


EG, GR, HG



Wt/100 pcs: 176 Lbs (79.8 kg)

P1950


EG, GR, HG



Wt/100 pcs: 240 Lbs (108.9 kg)

P1962


EG, GR, HG



Wt/100 pcs: 112 Lbs (50.8 kg)

P2626


EG, GR, HG



Wt/100 pcs: 40 Lbs (18.1 kg)

P1026


DF, EG, GR, HG



Wt/100 pcs: 38 Lbs (17.2 kg)

P1723


EG, GR, HG



Wt/100 pcs: 34 Lbs (15.4 kg)

P1068

DF, EG, GR, HG




Wt/100 pcs: 38 Lbs (17.2 kg)

P1281, P1282,

P1283

EG, GR, HG




Part No.	"A"	Wt/100 pcs
	In (mm)	Lbs (kg)
P1281	3	49
	76.2	22.2
P1282	3½	54
	88.9	24.5
P1283	4	61
	101.6	27.7

Wt/100 pcs: 45 Lbs (20.4 kg)

P1315


EG, GR, HG




Wt/100 pcs: 58 Lbs (26.3 kg)

Standard Dimensions for 1½" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)


Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 1 ½" (20.6mm); Hole Spacing - On Center: 1 ¼" (27.9mm); Width: 1 ½" (41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45

P1538A THRU P1538D**EG, GR, HG**


Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)
P1538A	3 1/8 98.4	61 27.7
P1538B	5 1/8 149.2	84 38.1
P1538C	7 1/8 200.0	107 48.5
P1538D	9 1/8 250.8	130 59.0

P1498, P1499**DF, EG, GR, HG**


Part Number	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)
P1498	4 1/8 123.8	2 1/2 63.5	65 29.5
P1499	6 1/8 174.6	4 1/2 114.3	85 38.6

P1750**EG, GR, HG**


Wt/100 pcs: 38 Lbs (17.2 kg)

P1346**EG, GR, HG****P1747****EG, GR, HG**


Wt/100 pcs: 66 Lbs (29.9 kg)

P1325**EG, GR, HG****P1326****EG, GR, HG**


Wt/100 pcs: 58 Lbs (26.3 kg)

P1822**EG, GR, HG****P1821****EG, GR, HG**


Wt/100 pcs: 71 Lbs (32.2 kg)




Wt/100 pcs: 58 Lbs (26.3 kg)

P1033**EG, GR, HG**


Wt/100 pcs: 78 Lbs (35.4 kg)

P1037**EG, GR, HG**


Wt/100 pcs: 55 Lbs (24.9 kg)

P1038**EG, GR, HG**


Wt/100 pcs: 55 Lbs (24.9 kg)

P1034**EG, GR, HG**


Wt/100 pcs: 80 Lbs (36.3 kg)



Wt/100 pcs: 58 Lbs (26.3 kg)




Wt/100 pcs: 58 Lbs (26.3 kg)




Wt/100 pcs: 80 Lbs (36.3 kg)

Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)


Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 13/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (41.6mm); Width: 1 5/8"(41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45


P1029
EG, GR, HG
P1035
EG, GR, HG
P1290
EG, GR, HG
P1291
EG, GR, HG



Wt/100 pcs: 105 Lbs (47.6 kg)




Wt/100 pcs: 80 Lbs (36.3 kg)




Wt/100 pcs: 101 Lbs (45.8 kg)




Wt/100 pcs: 101 Lbs (45.8 kg)

P1357
EG, GR, HG
P1359
EG, GR, HG
P1381
EG, GR, HG
P1382
EG, GR, HG



Wt/100 pcs: 70 Lbs (31.8 kg)




Wt/100 pcs: 105 Lbs (47.6 kg)




Wt/100 pcs: 105 Lbs (47.6 kg)




Wt/100 pcs: 105 Lbs (47.6 kg)

P1934
P1713
P1579
P1727



Wt/100 pcs: 75 Lbs (34.0 kg)




Wt/100 pcs: 97 Lbs (44.0 kg)




Wt/100 pcs: 103 Lbs (46.7 kg)




Wt/100 pcs: 154 Lbs (69.9 kg)

P1728
P2235
P1956
P1957
EG, GR, HG



Wt/100 pcs: 154 Lbs (69.9 kg)



Wt/100 pcs: 135 Lbs (61.2 kg)




Wt/100 pcs: 230 Lbs (104.3 kg)




Wt/100 pcs: 230 Lbs (104.3 kg)

 Standard Dimensions for 1⁵/₈" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)


Hole Diameter: $\frac{1}{16}$ " (14.3mm); Hole Spacing - From End: $\frac{1}{16}$ " (20.6mm); Hole Spacing - On Center: $\frac{1}{4}$ " (47.6mm); Width: 1⁵/₈"(41.3mm); Thickness: $\frac{1}{4}$ " (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45

P2484**DF, EG, GR, HG**

Wt/100 pcs: 134 Lbs (60.8 kg)


P2484W**EG, GR, HG**

Wt/100 pcs: 134 Lbs (60.8 kg)

P1130, P1131**EG, GR, HG**

Part Number	"A" In (mm)	"B" In (mm)	Wt/100 pcs
P1130	6 5/16	4	190
	168.3	101.6	86.2


P1131	8 5/16	6	242
	219.1	152.4	109.8

P1546, P2094 THRU P2100**DF, EG, GR, HG**

Wt/100 pcs: 58 Lbs (26.3 kg)


Part No.	"A" Degree (rad)	"B" In (mm)	"C" In (mm)
P2094	82 1/2°	3 5/16	11 1/16
	1.44	90.5	42.9
P2095	75°	3 5/16	11 1/16
	1.31	90.5	42.9
P2096	67 1/2°	3 1/2	1 1/4
	1.18	88.9	44.5
P2097	60°	3 3/16	1 1/8
	1.05	85.7	47.6
P2098	52 1/2°	3 1/4	2 1/16
	0.92	82.6	52.4
P1546	45°	3	2 5/16
	0.79	76.2	58.7
P2099	37 1/2°	3 1/2	1 13/16
	0.65	88.9	46.0
P2100	37 1/2°	2 1/16	2 5/8
	0.65	68.3	66.7

Wt/100 pcs: 58 Lbs (26.3 kg)

P2101 THRU P2104**EG, GR, HG**


Part No.	"A" Degree (rad)	"B" In (mm)
P2101	30°	3 1/4
	0.52	82.6
P2102	22 1/2°	3 5/16
	0.39	84.1
P2103	15°	3 5/16
	0.26	84.1
P2104	7 1/2°	3 5/16
	0.13	84.1

Wt/100 pcs: 58 Lbs (26.3 kg)

P1186, P2105 THRU P2110**DF, EG, GR, HG**

Part Number	"A" Degree (rad)	"B" In (mm)
P2105	82 1/2°	3 1/4
	1.44	82.6
P2106	75°	3 1/4
	1.31	82.6
P2107	67 1/2°	3 5/16
	1.18	81.0
P2108	60°	3 5/16
	1.05	81.0
P2109	52 1/2°	3 1/8
	0.92	79.4
P1186	45°	3 1/8
	0.79	79.4
P2110	37 1/2°	3 5/16
	0.65	77.8

Wt/100 pcs: 58 Lbs (26.3 kg)


P2260 THRU P2270**DF, EG, GR, HG**

Part Number	"A" Degree (rad)	"B" In (mm)
P2270	82 1/2°	3 5/16
	1.44	92.1
P2269	75°	3 5/16
	1.31	92.1
P2268	67 1/2°	3 5/16
	1.18	92.1
P2267	60°	3 1/4
	1.05	93.7
P2266	52 1/2°	3 5/16
	0.92	93.7
P2265	45°	3 1/4
	0.79	93.7
P2264	37 1/2°	3 1/4
	0.65	93.7
P2263	30°	3 1/4
	0.52	93.7
P2262	22 1/2°	3 5/16
	0.39	95.3
P2261	15°	3 5/16
	0.26	95.3
P2260	7 1/2°	3 5/16
	0.13	95.3


Wt/100 pcs: 78 Lbs (35.4 kg)

Standard Dimensions for 1 1/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)


Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 13/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (27.6mm); Width: 1 1/8" (41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45


P1045
DF, EG, GR, HG
P1347
EG, GR, HG
P1453
EG, GR, HG
P1454
EG, GR, HG



Wt/100 pcs: 55 Lbs (24.9 kg)




Wt/100 pcs: 55 Lbs (24.9 kg)




Wt/100 pcs: 70 Lbs (31.8 kg)




Wt/100 pcs: 38 Lbs (17.2 kg)

P1479A THRU P1479E



Part Number	"A"	Wt/100 pcs
In (mm)	Lbs (kg)	
P1479A	4 (101.6)	81 (36.7)
P1479B	5 (127.0)	92 (41.7)
P1479C	6 (152.4)	104 (47.2)
P1479D	7 (177.8)	115 (52.2)
P1479E	8 (203.2)	127 (57.6)

P1730



Wt/100 pcs: 54 Lbs (24.5 kg)

P1734



Wt/100 pcs: 70 Lbs (31.8 kg)

P1736



Wt/100 pcs: 70 Lbs (31.8 Kg)

P2360



Wt/100 pcs: 9 Lbs (4.1 kg)

P5560



Wt/100 pcs: 11 Lbs (5.0 kg)

P3345 **EG, GR, HG**



Wt/100 pcs: 47 Lbs (21.3 kg)

P4045 **EG, GR, HG**



Wt/100 pcs: 47 Lbs (21.3 kg)

P3045
EG, GR, HG



Wt/100 pcs: 53 Lbs (24.0 kg)

P612


Wt/100 pcs: 47 Lbs (21.3 kg)

P5545 **EG, GR, HG**
EG, GR, HG


Wt/100 pcs: 67 Lbs (30.4 kg)

P2469


Wt/100 pcs: 93 Lbs (42.2 kg)

Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)


Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 1 1/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (47.6mm); Width: 1 5/8" (41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45

"U" Shape Fittings

UNISTRUT®


P2800

EG, GR, HG




Part Number	Bolt Size (in)	Hole Size (in)	Wt/100 pcs
P2800-25	1/4"	5/32"	14
			6.4
P2800-37	3/8"	7/16"	14
			6.4
P2800-50	1/2"	9/16"	13
			5.9
P2800-62	5/8"	11/16"	13
			5.9
P2800-75	3/4"	13/16"	13
			5.9

P1363A THRU P1363E



Part Number	"A" In (mm)	Wt/100 pcs
P1363A	4	78
	101.6	35.4
P1363B	5	89
	127.0	40.4
P1363C	6	101
	152.4	45.8
P1363D	7	112
	177.8	50.8
P1363E	8	124
	203.2	56.2

P1320



Wt/100 pcs: 63 Lbs (28.6 kg)

P1376

EG, GR, HG

P4376


EG, GR, HG

P1376A


EG, GR, HG

P4376A


EG, GR, HG




Wt/100 pcs: 128 Lbs (58.1 kg)



Wt/100 pcs: 85 Lbs (38.6 kg)




Wt/100 pcs: 197 Lbs (89.4 kg)




Wt/100 pcs: 130 Lbs (59.0 kg)

P1377, P4377, P5077, P5577

EG, GR, HG



Part Number	For Use With	"A" in (mm)	Wt/100 pcs
P1377	P1000, P1100, P2000	1 15/16	265
		39.7	120
P4377	P3300, P4000, P4100	15/16	176
		23.8	80
P5077	P5000	3 3/16	390
		81.0	177
P5577	P5500	2 3/8	310
		60.3	141




P1047

DF, EG, GR, HG

P3047

EG, GR, HG



P976

P4047


EG, GR, HG

P1455


EG, GR, HG

P5547


EG, GR, HG




Wt/100 pcs: 71 Lbs (32.2 kg)



Wt/100 pcs: 71 Lbs (32.2 kg)



Wt/100 pcs: 58 Lbs (26.3 kg)



Wt/100 pcs: 108 Lbs (49.0 kg)


Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 13/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (47.6mm); Width: 1 5/8" (41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45



P1383


EG, GR, HG



Wt/100 pcs: 95 Lbs (43.1 kg)

P1732


EG, GR, HG



Wt/100 pcs: 88 Lbs (39.9 kg)

P2237

EG, GR, HG




Material: 1/8" (3.2) thick.

Wt/100 pcs: 18 Lbs (8.2 kg)

P5543

EG, GR, HG




P5500

Wt/100 pcs: 97 Lbs (44.0 kg)

P1048, P1049, P1050


DF, EG, GR, HG



Part Number	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)
P1048	7 1/4 184.2	4 1/8 104.8	105 47.6
P1049	8 1/2 215.9	5 5/8 136.5	120 54.4
P1050	10 1/8 263.5	7 1/4 184.2	130 59.0

P2473


EG, GR, HG



Wt/100 pcs: 197 Lbs (89.4 kg)

P4043


EG, GR, HG

P4004 (shown), P1001,
P1101, P2001, or P5000

Wt/100 pcs: 106 Lbs (48.1 kg)

P2326


EG, GR, HG



Wt/100 pcs: 171 Lbs (77.6 kg)

P2328


EG, GR, HG



Wt/100 pcs: 209 Lbs (94.8 kg)

P1043A


EG, GR, HG



Wt/100 pcs: 105 Lbs (47.6 kg)

P1737


EG, GR, HG



Wt/100 pcs: 128 Lbs (58.1 kg)

P1044


EG, GR, HG



Wt/100 pcs: 70 Lbs (31.8 kg)

P1973


EG, GR, HG



Wt/100 pcs: 53 Lbs (24.0 kg)

P2329


EG, GR, HG



Wt/100 pcs: 257 Lbs (116.6 kg)

P1046A

EG, GR, HG



Wt/100 pcs: 76 Lbs (34.5 kg)


Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 1 5/16" (20.6mm); Hole Spacing - On Center: 1 7/8" (47.6mm); Width: 1 5/8"(41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45

Wing Shape Fittings

UNISTRUT®


P2341 R-L EG, GR, HG



R - As shown
L - Opposite hand

Wt/100 pcs: 60 Lbs (27.2 kg)


P2472 R-L EG, GR, HG



R - As shown
L - Opposite hand

Wt/100 pcs: 75 Lbs (34.0 kg)


P2343 R-L



R - As shown
L - Opposite hand


Wt/100 pcs: 119 Lbs (54.0 kg)

P2223 EG, GR, HG




Wt/100 pcs: 76 Lbs (34.5 kg)

P2224 EG, GR, HG




Wt/100 pcs: 115 Lbs (52.2 kg)

P2225 EG, GR, HG




Wt/100 pcs: 155 Lbs (70.3 kg)

P2227 EG, GR, HG




Wt/100 pcs: 113 Lbs (51.3 kg)

P2228 EG, GR, HG




Wt/100 pcs: 177 Lbs (80.3 kg)

P2229 EG, GR, HG




Wt/100 pcs: 230 Lbs (104.3 kg)

P2345 EG, GR, HG




Wt/100 pcs: 93 Lbs (42.2 kg)

P2346 EG, GR, HG




Wt/100 pcs: 150 Lbs (68.0 kg)

P2347 EG, GR, HG



Wt/100 pcs: 193 Lbs (87.5 kg)


P2344 R-L EG, GR, HG



R - As shown
L - Opposite hand


Wt/100 pcs: 176 Lbs (79.8 kg)

P2226 EG, GR, HG



Wt/100 pcs: 217 Lbs (98.4 kg)


P2230 EG, GR, HG



Wt/100 pcs: 310 Lbs (140.6 kg)

P2225 EG, GR, HG

Fitting notched for continuous vertical.



Wt/100 pcs: 315 Lbs (142.9 kg)

Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 9/16" (14.3mm); Hole Spacing - From End: 13/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (47.6mm); Width: 1 5/8" (41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45



P2348

EG, GR, HG

P2453


EG, GR, HG

P1887


EG, GR, HG

P2941, P2942


EG, GR, HG




Wt/100 pcs: 274 Lbs (124.3 kg)



Wt/100 pcs: 116 Lbs (52.6 kg)



Wt/100 pcs: 297 Lbs (134.8 kg)



P2941

P2942

Wt/100 pcs: 358 Lbs (162.4 kg)

P2072,
P2072 SQ

EG, GR, HG

P2072A,
P2072A SQ






DF, EG, GR, HG

P2073,
P2073 SQ


EG, GR, HG

P2073A,
P2073A SQ


EG, GR, HG




P2072




P2072A



P2073




P2073A



P2072 SQ

Wt/100 pcs: 307 Lbs (139.3 kg)



P2072A SQ


Wt/100 pcs: 373 Lbs (169.2 kg)

EG, GR

Vertical Channel Part No.	Gauge	Uniform Design Load Lbs (kN)
P1000	12	800 3.56
P1100	14	600 2.67
P2000	16	400 1.81

Safety Factor 2 1/2

P1769




Material: 1/4" (6.4) thick steel.

Wt/100 pcs: 174 Lbs (78.9 kg)

P1771

EG, GR



Material: 1/4" (6.4) thick steel.

Wt/100 pcs: 206 Lbs (93.4 kg)

Vertical Channel Part No.	Gauge	Uniform Design Load Lbs (kN)
P1000	12	800 3.56
P1100	14	600 2.67
P2000	16	400 1.81


Safety Factor 2 1/2

Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 1 1/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (47.6mm); Width: 1 5/8"(41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45

P1773

EG, GR



Material: 1/4" (6.4) thick steel.


Vertical Channel		Uniform Design Load
Part No.	Gauge	Lbs (kN)
P1000	12	900 (4.00)
P1100	14	800 (3.56)
P2000	16	450 (2.04)

Safety Factor 2 1/2

Wt/100 pcs: 264 Lbs (119.7 kg)

P1075

EG, GR

P1000
P1100
P2000
P4001

Material: 1/4" (6.4) thick steel.


Wt/100 pcs: 229 Lbs (103.9 kg)

Vertical Channel		Allowable Moment*
Part No.	Gauge	In-Lbs (N·M)
P1000	12	5,100 (576)
P1100	14	4,400 (497)
P2000	16	3,200 (362)

Safety Factor 2 1/2

* Allowable moment for fitting only.
Channel may determine overall capacity.**P1777**

EG, GR



Material: 1/4" (6.4) thick steel.


Wt/100 pcs: 385 Lbs (174.6 kg)

Vertical Channel		Uniform Design Load
Part No.	Gauge	Lbs (kN)
P1000	12	1,200 (5.44)
P1100	14	900 (4.00)
P2000	16	600 (2.67)

Safety Factor 2 1/2

P2491 R-L THRU P2493 R-L

EG, GR



R - As shown; L - Opposite hand

Material : 12 Gauge Steel.

Vertical Channel		Uniform Design Load
Part No.	Gauge	Lbs (kN)
P1000	12	300 (1.33)
P1100	14	250 (1.11)
P2000	16	200 (.89)

Safety Factor - 2 1/2


Part Number	Stamped Ident. No.	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)
P2491 R-L	121892 R-L	6	11 1/16	67
		152.4	49.2	30.4
P2492 R-L	121893 R-L	8	27 1/16	92
		203.2	61.9	41.7
P2493 R-L	121894 R-L	10	21 1/16	120
		254.0	74.6	54.4

Standard Dimensions for 1 1/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 9/16" (14.3mm); Hole Spacing - From End: 13/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (47.6mm); Width: 1 1/8" (41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45

P1775

EG, GR



Material: 1/4" (6.4) thick steel.


Vertical Channel		Uniform Design Load
Part No.	Gauge	Lbs (kN)
P1000	12	900 (4.00)
P1100	14	800 (3.56)
P2000	16	450 (2.04)

Safety Factor 2 1/2

Wt/100 pcs: 295 Lbs (133.8 kg)

P1593

EG, GR


P1001
P1101
P5000
P2001

Vertical Channel		Allowable Moment*
Part No.	Gauge	In-Lbs (N·M)
P1000	12	13,000
		1,469
P1100	14	9,100
		1,028
P2000	16	6,500
		734

Safety Factor 2 1/2

Material: 1/4" (6.4) thick steel.


Wt/100 pcs: 272 Lbs (123.4 kg)

* Allowable moment for fitting only.
Channel may determine overall capacity.**P2547 THRU P2551****CABLE TRAY BRACKET**

Part Number	"A" In (mm)	"B" In (mm)	Wt/100 pcs	Uniform Load* Lbs (kg)
P2547	15	8 3/4	420	1,000
	381.0	222	190.5	4.45
P2548	21	8 3/4	628	1,000
	533.4	222	284.9	4.45
P2549	27	11 1/4	860	900
	685.8	286	390.1	4.00
P2550	33	11 1/4	1010	900
	838.2	286	458.1	4.00
P2551	39	16	1257	800
	990.6	406.4	683.3	3.56



P2494 R-L THRU P2499 R-L



Vertical Channel		Uniform Design Load Lbs (kN)
Part No.	Gauge	
P1000	12	300 (1.33)
P1100	14	250 (1.11)
P2000	16	200 (.89)


Safety Factor - 2½

Part Number	Stamped Ident. No.	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)
P2494 R-L	121895 R-L	12 304.8	3 7/16 87.3	152 68.9
P2495 R-L	121896 R-L	14 355.6	3 15/16 100.0	173 78.5
P2496 R-L	121897 R-L	16 406.4	4 7/16 112.7	223 101.2
P2497 R-L	121898 R-L	18 457.2	4 15/16 125.4	266 120.7
P2498 R-L	121899 R-L	20 508.0	5 5/16 138.1	308 139.7
P2499 R-L	121900 R-L	22 558.8	5 15/16 150.8	355 161.0

Material : 12 Gauge Steel.

R - As shown; L - Opposite hand

P2500 R-L THRU P2503 R-L



Vertical Channel		Uniform Design Load Lbs (kN)
Part No.	Gauge	
P1000	12	300 (1.33)
P1100	14	250 (1.11)
P2000	16	200 (.89)

Safety Factor - 2½


Part Number	Stamped Ident. No.	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)
P2500 R-L	121901 R-L	24 609.6	6 7/16 164	400 181.4
P2501 R-L	121902 R-L	26 660	6 15/16 176	445 201.8
P2502 R-L	121903 R-L	28 711	7 7/16 189	493 223.6
P2503 R-L	121904 R-L	30 762.0	7 15/16 202	545 247.2

Material : 12 Gauge Steel.

R - As shown; L - Opposite hand

P2944, P2945, P2946, P2947

EG, GR, HG




Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)	Uniform Load* Lbs (kN)
P2944	6 152.4	185 84	1200 5.34
P2945	12 304.8	293 133	600 2.67
P2946	18 457.2	401 182	400 1.78
P2947	24 609.6	509 231	300 1.33

Safety Factor 2½

* Mounted on 12 Ga. Channel

P2542 THRU P2546

EG, GR, HG




Safety Factor - 2½

Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)	Vertical Channel Part No.	Gauge	Uniform Design Load Lbs (kN)
P2542	12 304.8	502 228	P1000	12	2,000 (8.90)
			P1100	14	1,400 (6.23)
			P2000	16	1,000 (4.45)
P2543	18 457.2	692 314	P1000	12	1,300 (5.78)
			P1100	14	900 (4.00)
			P2000	16	650 (2.89)
P2544	24 609.6	882 400	P1000	12	1,000 (4.45)
			P1100	14	700 (3.11)
			P2000	16	500 (2.22)
P2545	30 762.0	1,072 486	P1000	12	800 (3.56)
			P1100	14	560 (2.49)
			P2000	16	400 (1.78)
P2546	36 914.4	1,262 572	P1000	12	650 (2.89)
			P1100	14	450 (2.00)
			P2000	16	320 (1.42)

Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 1 1/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (27.6mm); Width: 1 5/8" (41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45


P2231, P2232



Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)	Vertical Channel		Uniform Design Load Lbs (kN)
			Part No.	Gauge	
P2231	6 152.4	191 86.6	P1000	12	1,600 (7.12)
			P1100	14	1,200 (5.34)
			P2000	16	800 (3.56)
P2232	12 304.8	292 132.4	P1000	12	800 (3.56)
			P1100	14	600 (2.67)
			P2000	16	400 (1.78)

Safety Factor - 2½


P2233, P2234



Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)	Vertical Channel		Uniform Design Load Lbs (kN)
			Part No.	Gauge	
P2233	18 457.2	436 197.8	P1000	12	600 (2.67)
			P1100	14	450 (2.00)
			P2000	16	300 (1.33)
P2234	24 609.6	536 243.1	P1000	12	450 (2.00)
			P1100	14	330 (1.47)
			P2000	16	220 (.98)

Safety Factor - 2½

P2513 THRU P2516



When installed in inverted position use 60% of loads shown.


Safety Factor 2½

Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)	Vertical Channel		Uniform Design Load Lbs (kN)
			Part No.	Gauge	
P2513	6 152.4	161 73.0	P1000	12	1,200 (5.34)
			P1100	14	800 (3.56)
			P2000	16	600 (2.67)
P2514	12 304.8	261 118.4	P1000	12	600 (2.67)
			P1100	14	400 (1.78)
			P2000	16	300 (1.33)
P2515	18 457.2	361 163.7	P1000	12	400 (1.78)
			P1100	14	270 (1.20)
			P2000	16	200 (.89)
P2516	24 609.6	461 209.1	P1000	12	300 (1.33)
			P1100	14	200 (.89)
			P2000	16	150 (.67)

Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 13/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (47.6mm); Width: 1 5/8" (41.3mm); Thickness: 1/4" (6.4mm)


P2231A, P2232A



Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)	Vertical Channel		Uniform Design Load Lbs (kN)
			Part No.	Gauge	
P2231A	6 152.4	191 86.6	P1000	12	1,600 (7.12)
			P1100	14	1,200 (5.34)
			P2000	16	800 (3.56)
P2232A	12 304.8	292 132.4	P1000	12	800 (3.56)
			P1100	14	600 (2.67)
			P2000	16	400 (1.78)

Safety Factor - 2½


P2233A, P2234A



Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)	Vertical Channel		Uniform Design Load Lbs (kN)
			Part No.	Gauge	
P2233A	18 457.2	436 197.8	P1000	12	600 (2.67)
			P1100	14	450 (2.00)
			P2000	16	300 (1.33)
P2234A	24 609.6	536 243.1	P1000	12	450 (2.00)
			P1100	14	330 (1.47)
			P2000	16	220 (.98)

Safety Factor - 2½

P2513A THRU P2516A



When installed in inverted position use 60% of loads shown.



Safety Factor 2½

Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)	Vertical Channel		Uniform Design Load Lbs (kN)
			Part No.	Gauge	
P2513A	6 152.4	161 73.0	P1000	12	1,200 (5.34)
			P1100	14	800 (3.56)
			P2000	16	600 (2.67)
P2514A	12 304.8	261 118.4	P1000	12	600 (2.67)
			P1100	14	400 (1.78)
			P2000	16	300 (1.33)
P2515A	18 457.2	361 163.7	P1000	12	400 (1.78)
			P1100	14	270 (1.20)
			P2000	16	200 (.89)
P2516A	24 609.6	461 209.1	P1000	12	300 (1.33)
			P1100	14	200 (.89)
			P2000	16	150 (.67)



P2815



ADJUSTABLE BRACE FITTING EG HG



Wt/100 pcs: 307 Lbs (139.3 kg)

P2815D

ADJUSTABLE BRACE FITTING





Wt/100 pcs: 497 Lbs (225.4 kg)

P2452 KNEE BRACE EG GR

P2458-18 THRU P2458-36


TUBULAR KNEE BRACES



Design Axial Load
1200 Lbs (5.34 kN)

Material: 1/4" (6.4) thick steel.



Wt/100 pcs: 277 Lbs (125.6 kg)




P2459-36 THRU P2459-96

TUBULAR BACK BRACES

EG GR



1. The vertical lines of the graph correspond to the center to center line dimension of the uprights.
2. Along this vertical line locate the (maximum usable) horizontal bracing height line.
3. The arc line that intersects the point formed by the intersection of the two lines, indicates the brace required.
4. 30° - 60° maximum, minimum brace angles are indicated for maximum effect.




Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)
P2459-36	36	255
	914.4	115.7
P2459-42	42	296
	1,066.8	134.3
P2459-48	48	336
	1,219.2	152.4
P2459-54	54	377
	1,371.6	171.0
P2459-60	60	418
	1,524.0	189.6
P2459-72	72	499
	1,828.8	226.3
P2459-84	84	580
	2,133.6	263.1
P2459-96	96	661
	2,438.4	299.8


Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 1/16" (1.6mm); Hole Spacing - From End: 1/16" (20.6mm); Hole Spacing - On Center: 1/16" (47.6mm); Width: 1 5/8" (41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45

P2897




P2784



Part Number	For Use With	Load Lbs (kN)	Wt/100 pcs Lbs (kg)
P2784-1	P1000, P1100, P2000	1,200 5.34	175 79.3
P2784-2	P1001, P1101, P2001	1,200 5.34	179 81.1
P2784-3	P5001, P5501	1,200 5.34	180 81.5


P2675

EG GR



Clamp Materials: .105" (2.7) thick steel.
Clamp P2675 is designed for light duty rod suspension.
It also may be used with P3016-1024 or P3016-1420
nut as illustrated above for mounting insulators, etc.

Wt/100 pcs: 33 Lbs (15.0 kg)



**P8000, P8001 – JUNIOR DUCTILE IRON TOP BEAM CLAMP****Material:** 3/8" and 1/2" rod sizes**Finish:** Plain (PL) and Electro-Galvanized (EG)**Function:** Structural attachment to top or bottom of metal beams, purlins, channel, or angle iron**Features:**

- Set screw made of hardened steel
- Complies with Federal Specification A-A192A (Type 19) and MSS SP-69 (Type 19)



Part No. Plain & EG	Rod Size	Max Load Top Lbs*	Max Load Bottom Lbs*	Weight Lbs	W
P8000	3/8	500	250	0.33	7/8
P8001	1/2	950	760	0.34	1 1/16

NOTE: *Max load may exceed allowable load for threaded rod size shown.





Note: When used for mechanical supports, load capacities of brackets, fittings and other supporting elements should be in compliance with the American Standard Code for Pressure Piping. Clamps are designed to be used with W, M, S & HP Shape beams, Standard C & Misc. MC Channels, Angles & Structural Tees. Clamps must be used in pairs where indicated. For beam clamps with HG finish, standard hardware is EG finish. For optional stainless steel hardware, please contact the factory for availability.



P2676

EG GR




Clamp P2676 provides a means of rod suspension where a free swing of up to 15° (0.08π) is required. Clamp will accommodate 1/4" (6.4), 5/16" (9.5), or 1/2" (12.7) rods. Order swivel nuts P2679-4, -6, or -8 as required. Clamp may also be used with P2677 as illustrated in application drawings.

Clamp Materials: 1/8" (3.2) thick steel. Not available in SS or ST.

P2898


UNIVERSAL BEAM CLAMP EG



	A In In (mm)	B In In (mm)	C In In (mm)	D In In (mm)	E In In (mm)	F In In (mm)	G In In (mm)	Max Load Lbs (kN)	Wt/100 pcs Lbs (kg)
P2898-37	5/8	1	1 1/2	1/2	1	3/4	7/8	400	33
		25.4	38.1	12.7	25.4	19.1	22.2	1.78	15.0
P2898-50	1/2	1 5/16	1 1/2	1/2	1	3/4	7/8	500	33
		25.4	38.1	12.7	25.4	19.1	22.2	2.22	15.0
P2898-62	5/8	1 1/2	1 1/2	1/2	1	3/4	1	600	22
		38.1	38.1	12.7	25.4	19.1	25.4	2.67	10.0
P2898-75	3/4	1 1/8	1 3/4	5/8	1 1/8	1	1 1/4	800	88
		47.6	44.5	15.9	34.9	25.4	31.8	3.56	40.0
P2898-87	7/8	2	1 1/4	5/8	1 1/2	1	1 1/4	1,200	79
		50.8	44.5	15.9	38.1	25.4	31.8	5.34	35.9

P2899

WIDE THROAT BEAM CLAMP EG




	Rod Size					Max. Load Lbs (kN)	Wt/100 pcs Lbs (kg)
	A in In (mm)	B In In (mm)	C In In (mm)	D In In (mm)	E In In (mm)		
P2899-37	5/8	1 1/8	2	1	7/8	400	28
		41.3	50.8	25.4	22.2	1.78	12.7
P2899-50	1/2	1 5/16	2	1	7/8	500	34
		41.3	50.8	25.4	22.2	2.22	15.4
P2899-62	5/8	1 3/4	2 1/4	1 1/4	1	600	66
		44.5	57.2	31.8	25.4	2.67	30.0
P2899-75	3/4	1 1/8	2 5/8	1 1/8	1 1/4	800	83
		47.6	60.3	34.9	31.8	3.56	37.7

P2682

EG

EG




Hanger clevis for up to 1/2" (12.7) rod suspension from wood ceilings. May also be used with P2677 as illustrated in application drawings.

Wt/100 pcs: 55 Lbs (24.9 kg)


P2679-4, -6 & -8

SWIVEL NUT EG



- Use w/P2676 and P2677.
- Order size as required.

Part No.	Thread Size	Wt/100 pcs Lbs (kg)
P2679-4	1/4"-20	4 (1.8)
P2679-6	5/16"-16	5 (2.3)
P2679-8	1/2"-13	6 (2.7)



Clevis hanger to be used with P2676 or P2682 to provide angle adjustment and 15° (0.08π) free swing for up to 1/2" (12.7) rod suspension. Order swivel nuts P2679-4, -6, or -8 as required.



Design Load
500 Lbs (2.22 kN)

Wt/100 pcs: 30 Lbs (13.6 kg)

Note: When used for mechanical supports, load capacities of brackets, fittings and other supporting elements should be in compliance with the American Standard Code for Pressure Piping. Clamps are designed to be used with W, M, S & HP Shape beams, Standard C & Misc. MC Channels, Angles & Structural Tees. Clamps must be used in pairs where indicated. For beam clamps with HG finish, standard hardware is EG finish. For optional stainless steel hardware, please contact the factory for availability.

P2674

EG GR




Design Load
250 Lbs (1.11 kN)

Clevis hanger to be used with P2675 to provide angle adjustment for up to 5/8" rod suspension as illustrated.

Wt/100 pcs: 17 Lbs (7.7 kg)

P1640


EG GR



Part Number	Thread Size
P1640-025	1/4"-20
P1640-037	5/16"-16
P1640-050	5/16"-13

P2398S, P2401S, P2403S, P2405S

EG GR




Weld is not continuous it is either 1 1/4" (31.8) - 1 3/4" (44) long or 2 spot welds. All welds are on the top and bottom.

For beams between 3/4" (19.1) to 1 5/8" (41.3) thick flanges.


Part Number	"A" In	"B" In (mm)	"C" In	"D" In (mm)	"E" In (mm)	Design Load	
						Wt/100 pcs	Lbs (kg)
P2398S	1/4- 20	1/8	3/8 x 2	12 1/32	7/8	109	800
						3.2	3.56
P2401S	5/16- 16	5/16	1/2 x 2	11 1/16	29/32	156	1,300
						4.8	5.78
P2403S	1/2- 13	1/4	1/2 x 2	11 1/16	15/16	201	1,900
						6.4	8.45
P2405S	5/8- 11	5/8	5/8 x 2	11 1/16	15/16	311	2,400
						7.9	10.68

P1648S THRU P1653S

EG GR



For beams under 7/8" (22.2) thick flange.




Weld is not continuous it is either 1 1/4" (31.8) - 1 3/4" (44.5) long or 2 spot welds. All welds are on the top and bottom.


Part Number	"A" In	"B" In (mm)	"C" In	"D" In (mm)	Wt/100 pcs	Design Load
					Lbs (kg)	Lbs (kN)
P1648S	1/4- 20	1/8	3/8 x 1 1/2	7/8	67	650
		3.2		22.2	30.4	2.89
P1649S	5/16- 18	1/8	3/8 x 1 1/2	7/8	67	650
		3.2		22.2	30.4	2.89
P1650S	3/8- 16	3/16	1/2 x 1 1/2	15/16	100	1,100
		4.8		23.8	45.4	4.89
P1651S	1/2- 13	1/4	1/2 x 1 1/2	15/16	130	1,600
		6.4		23.8	59.0	7.12
P1652S	5/8- 11	5/16	5/8 x 1 1/2	15/16	160	2,400
		7.9		33.3	72.6	10.68
P1653S	3/4- 10	5/16	5/8 x 1 1/2	15/16	160	2,400
		7.9		33.3	72.6	10.68

P1654A THRU P1661A

RETAINER STRAP EG GR



For beams under 7/8" (22.2) thick flange.




Strap Part Number	Flange Width In (mm)	"A" In (mm)	Wt/100 pcs	Beam Clamp Used With
P1654 A	6	7	25	P2675
P1655 A	9	10	34	P2675
P1656 A	6	9	35	P1648 S Thru P1651 S, P2398S, P2401S & P2403S
P1657 A	9	12	47	P1648 S Thru P1651 S, P2398S, P2401S & P2403S
	228.6	304.8	21.3	
P1658 A	12	15	59	P2676
	304.8	381.0	26.8	
P1659 A	6	9	33	P2676
	152.4	228.6	15.0	
P1660 A	9	12	45	P2676
	228.6	304.8	20.4	
P1661 A	12	15	57	P2676
	304.8	381.0	25.9	

Note: When used for mechanical supports, load capacities of brackets, fittings and other supporting elements should be in compliance with the American Standard Code for Pressure Piping. Clamps are designed to be used with W, M, S & HP Shape beams, Standard C & Misc. MC Channels, Angles & Structural Tees. Clamps must be used in pairs where indicated. For beam clamps with HG finish, standard hardware is EG finish. For optional stainless steel hardware, please contact the factory for availability.




P1271S DF, EG, GR, HG




Note: Requires P1010 Channel Nut and bolt.
Design Load Each 500 Lbs (2.22 kN)
Use in Pairs Only
Wt/100 pcs: 95 Lbs (43.1 kg)

P1796S EG GR HG




Design Load Each 500 Lbs (2.22 kN)
Use in Pairs Only
Wt/100 pcs: 91 Lbs (41.3 kg)

P2824-6,-9,-12 EG GR HG




For use with Beams up to 3/4" (19.1) max flange thickness



Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)	Design Load Lbs (kN)
P2824-6	2 1/2 - 6	125	500
	63.5 - 152.4	56.7	2.22
P2824-9	5 1/2 - 9	140	500
	139.7 - 228.6	63.5	2.22
P2824-12	8 1/2 - 12	171	500
	215.9 - 304.8	77.6	2.22

P2785 DF, EG, GR, HG




• For use with Beams up to 3/4" (19.1)
Flanges and with
Channels P1000, P1100, P2000,
P3000, P3300, P3301,
P4000, P4001, P4100, and P4101.

Design Load Each 1000 Lbs (4.45 kN)
Use in Pairs Only

Wt/100 pcs: 83 Lbs (37.6 kg)

P2787 DF, EG, HG




• For use with Beams up to 3/4" (19.1)
Flanges and with
Channels P5001 and P5501.

Design Load Each 1000 Lbs (4.45 kN)
Use in Pairs Only


Wt/100 pcs: 112 Lbs (50.8 kg)

P2867A EG GR HG



• Includes: "J" Bolt, "U" Bolt and Hex Nuts.
• For use with Channel P1001, P1101, P2001, P3001, P5000, and P5501.

P2786 DF, EG, GR, HG




• For use with Beams up to 3/4" (19.1)
Flanges and with
Channels P1001, P1101, P2001,
P3001, P5000, and P5500.

Design Load Each 1000 Lbs (4.45 kN)
Use in Pairs Only


Wt/100 pcs: 92 Lbs (41.7 kg)

P2867 DF, EG, GR HG



• Includes: "J" Bolt, "U" Bolt and Hex Nuts.
• For use with Channels P1000, P1100,
P2000, P3000, P3300, P3301, P4000, P4001,
P4100, and P4101.

P2867B EG GR HG




• Includes: "J" Bolt, "U" Bolt and Hex Nuts.
• For use with Channel P5001, and P5501.

Note: When used for mechanical supports, load capacities of brackets and fittings should be in compliance with the American Standard Code for Pressure Piping.

Clamps are designed to be used with W, M, S & HP Shape beams, Standard C & Misc. MC Channels, Angles & Structural Tees. Clamps must be used in pairs where indicated. For beam clamps with HG finish, standard hardware is EG finish. For optional stainless steel hardware, please contact the factory for availability.

P2868

EG GR HG




Part Number	Beam Size "A"	Wt/100 pcs Lbs (kg)
P2868	4"-6"	282 (127.9)
P2868-9	6"-9"	289 (131.1)
P2868-12	9"-12"	296 (134.3)
P2868-15	12"-15"	304 (137.9)
P2868-18	15"-18"	311 (141.1)

- Includes: Center Rod, "U" Bolts and Hex Nuts.
- For use with Channels P1000, P1100, P2000, P3000, P3300, P3301, P4000, P4001, P4100, and P4101.

P2868A

EG GR HG




Part Number	Beam Size "A"	Wt/100 pcs Lbs (kg)
P2868A	4"-6"	300 (136.1)
P2868A-9	6"-9"	307 (139.3)
P2868A-12	9"-12"	314 (142.2)
P2868A-15	12"-15"	322 (146.1)
P2868A-18	15"-18"	329 (149.2)

- Includes: Center Rod, "U" Bolts and Hex Nuts.
- For use with Channels P1001, P1101, P2001, P3001, P5000, and P5500.

P2868B

EG GR HG




Part Number	Beam Size "A"	Wt/100 pcs Lbs (kg)
P2868B	4"-6"	320 (145.1)
P2868B-9	6"-9"	327 (148.3)
P2868B-12	9"-12"	334 (151.5)
P2868B-15	12"-15"	342 (155.1)
P2868B-18	15"-18"	349 (153.3)

- Includes: Center Rod, "U" Bolts and Hex Nuts.
- For use with Channels P5001, and P5501.

P2894

EG




Material: Malleable Iron
1/8" Maximum Flange Thickness
Note: Tapped Hole on Top and Bottom

Part Number	Rod Size In	"A" In (mm)	"B" In (mm)	Load Ratings Lbs (kN)	Wt/100 pcs Lbs (kg)
P2894-25	1/4	1 1/8 28.6	1 1/4 31.8	150 .67	23 10.4
P2894-37	3/8	2 50.8	2 50.8	350 1.56	95 43.1
P2894-50	1/2	2 5/8 66.7	2 1/2 63.5	400 1.78	195 88.5

P2893


EG



Material: Steel
Use With: 1/4" rod
Load Rating: 75 lbs. (.33 kN)

Wt/100 pcs: 14 lbs. (6.4 kg)


P2895



Material: Steel

Part Number	Rod Size In	"A" In (mm)	"B" In (mm)	Load Ratings Lbs (kN)	Wt/100 pcs Lbs (kg)
P2895-37	3/8	2 5/16 58.7	3/8 9.5	330 1.47	35 15.9
P2895-50	1/2	2 1/4 57.2	1/2 12.7	380 1.69	41 18.6
P2895-62	5/8	2 3/8 60.3	5/8 15.9	450 2.00	67 30.4
P2895-75	3/4	2 1/4 57.2	1/2 12.7	500 2.22	72 32.7

P2896



Material: Malleable Iron,
Steel Set Screw


Part Number	Rod Size In	"A" In (mm)	"B" In (mm)	Load Ratings Lbs (kN)	Wt/100 pcs Lbs (kg)
P2896-37	3/8	1 1/16 42.9	1 3/4 44.5	400 1.78	38 17.2
P2896-50	1/2	1 23/32 43.7	1 3/4 44.5	400 1.78	52 23.6
P2896-62	5/8	1 15/16 49.2	2 50.8	450 2.00	68 30.8
P2896-75	3/4	2 1/2 51.6	2 50.8	600 2.67	128 58.1

Note: When used for mechanical supports, load capacities of brackets, fittings and other supporting elements should be in compliance with the American Standard Code for Pressure Piping. Clamps are designed to be used with W, M, S & HP Shape beams, Standard C & Misc. MC Channels, Angles & Structural Tees. Clamps must be used in pairs where indicated. For beam clamps with HG finish, standard hardware is EG finish. For optional stainless steel hardware, please contact the factory for availability.



P1386

DF, EG, GR, HG




Channel Style	Design Load Each (Use in Pairs Only)
Lbs (kN)	
P1000	600 2.67
P1100	500 2.22
P2000	450 2.00

Wt/100 pcs: 27 Lbs (12.2 kg)

P1379S

EG GR HG




Channel Style	Design Load Each (Use in Pairs Only)
Lbs (kN)	
P1000	600 2.67
P1100	500 2.22
P2000	450 2.00

Wt/100 pcs: 75 Lbs (34.0 kg)

P1272S, P1985S, P1986S

EG GR HG




Part Number	"A" In (mm)	Flange Thickness In (mm)	"D" Set Screw Included	Wt/100 Pcs Lbs (kg)	Design Load Per Pair (Use in Pairs Only) Lbs (kN)
P1272S	1/4 6.4	Up to 3/4 Up to 19.1	3/8-16 x 1 1/2	39 17.7	450 2.00
P1985S	3/8 9.5	Up to 3/4 Up to 19.1	1/2-13 x 1 1/2	62 28.1	1,000 4.45
P1986S	3/8 9.5	7/8 to 2 22.2 - 50.8	1/2-13 x 1 1/2	74 33.6	900 4.00

P3087


COLUMN INSERT

EG



Channel Part Number	Design Pull Out Load Lbs (kN)	Design Slip Load Lbs (kN)
P1000	1,000 4.45	800 3.56
P1100	700 3.34	500 2.22
P2000	500 2.22	300 1.33


Safety factor of 3.



Wt/100 pcs: 136 Lbs (61.7 kg)


P3088

COLUMN INSERT





Channel Part Number	Design Pull Out Load Lbs (kN)	Design Slip Load Lbs (kN)
P3300	1,000 4.45	800 3.56
P4100	700 3.11	500 2.22
P4000	500 2.22	300 1.33

Safety factor of 3.




Wt/100 pcs: 120 Lbs (54.4 kg)

Note: When used for mechanical supports, load capacities of brackets, fittings and other supporting elements should be in compliance with the American Standard Code for Pressure Piping. Clamps are designed to be used with W, M, S & HP Shape beams, Standard C & Misc. MC Channels, Angles & Structural Tees. Clamps must be used in pairs where indicated. For beam clamps with HG finish, standard hardware is EG finish. For optional stainless steel hardware, please contact the factory for availability.

PFL050T**FLANGE CLAMP**

Material: Malleable Iron.



Cup point set screw and lock nut included.

Set Screw Torque = 6 Ft-Lb
Lock Nut Torque = 16 Ft-Lb

Safety Factor: 4

Part Number	Type of Hole	Rod Size	"Z" Set Screw Size	Wt/100 pcs Lbs (kg)	Max. Allowable Load Lbs (kN)
PFL050	Clear	1/2"	3/8"	40 (18.1)	700 (3.11)
PFL050T	Tapped	1/2"	3/8"	40 (18.1)	700 (3.11)

Part Number	Dimensions					
	"T" In (mm)	"U" In (mm)	"V" In (mm)	"W" In (mm)	"X" In (mm)	"Y" In (mm)
PFL050	2	1 ²³ / ₃₂	1	2 ⁹ / ₃₂	1 ¹ / ₃₂	9/16
PFL050T	50.8	43.7	25.4	23.0	27.8	14.3



PLF3075**FLANGE CLAMP**

Material: Malleable Iron.

Safety Factor: 4

Part Number	Rod Size	Wt/100 pcs Lbs (kg)	Max. Allowable Load Lbs (kN)	Torque Ft-Lbs
PLF3050	1/2"	91	450	29
		41	2.00	
PLF3062	5/8"	186	900	69
		84	4.00	
PLF3075	3/4"	334	1,350	130
		152	6.01	

Part Number	"X" In (mm)	"W" In (mm)	"V" In (mm)	"T" In (mm)	"R" In (mm)	"S" In (mm)
PLF3050	1 ¹ / ₁₆	0 - 1 ¹⁵ / ₁₆	1/2	1 ¹¹ / ₃₂	1 ¹⁵ / ₁₆	1 ¹ / ₃₂
	34.9	0 - 39.7	12.7	8.7	49.2	29.4
PLF3062	1 ¹³ / ₁₆	0 - 2 ³ / ₁₆	5/8	1/2	2 ¹ / ₃₂	1 ⁷ / ₁₆
	46.0	0 - 55.6	15.9	12.7	59.5	36.5
PLF3075	2 ³ / ₁₆	0 - 1 ¹ / ₄	3/4	5/8	3	1 ¹ / ₄
	55.6	0 - 44.5	19.1	15.9	76.2	44.5

PLF9037 THRU PLF9100**FLANGE CLAMP**

Part Number	Rod Size	Wt/100 pcs Lbs (kg)	Max. Allowable Load Lbs (kN)	Torque Ft-Lbs	"X" In (mm)	"W" In (mm)	"V" In (mm)	"T" In (mm)	"S" In (mm)
PLF9037	3/8"	55	440	15	1	3/4 - 11 ¹⁵ / ₁₆	1/2	3/4	1
		24.9	1.96		25.4	19.1 - 42.9	12.7	19.1	25.4
PLF9050	1/2"	122	630	29	1 ¹ / ₈	1 - 2 ³ / ₈	2 ¹ / ₃₂	1 ⁵ / ₁₆	1 ³ / ₁₆
		55.3	2.80		34.9	25.4 - 60.3	16.7	23.8	30.2
PLF9062	5/8"	200	1,260	69	11 ¹ / ₁₆	1 ¹ / ₈ - 2 ⁹ / ₁₆	1 ³ / ₁₆	1/8	1 ¹ / ₈
		90.7	5.60		42.9	28.6 - 69.9	20.6	28.6	34.9
PLF9075	3/4"	367	1,880	131	2	1 ¹ / ₄ - 3 ¹ / ₄	1	1 ¹ / ₈	1 ³ / ₄
		166.5	8.36		50.8	31.8 - 82.6	25.4	34.9	44.5
PLF9100	1"	1,101	3,150	173	3	1 ¹ / ₄ - 3 ³ / ₄	1 ¹ / ₂	2 ³ / ₁₆	2 ¹ / ₂
		499.4	14.01		76.2	44.9 - 95.3	38.1	55.6	63.5

Material: Malleable Iron.


Safety Factor: 4

Note: When used for mechanical supports, load capacities of brackets, fittings and other supporting elements should be in compliance with the American Standard Code for Pressure Piping. Clamps are designed to be used with W, M, S & HP Shape beams, Standard C & Misc. MC Channels, Angles & Structural Tees. Clamps must be used in pairs where indicated. For beam clamps with HG finish, standard hardware is EG finish. For optional stainless steel hardware, please contact the factory for availability.



P1834

CHANNEL TROLLEY SUPPORT EG




Requires $\frac{3}{8}$ " x $2\frac{1}{2}$ " Bolt and $\frac{3}{8}$ " Nut
(not included)

Design Load
1200 Lbs (5.34 kN)

Wt/100 pcs: 102 Lbs (46.3 kg)

P2749, P2749N[†]


EG



Clevis Material:
12 gauge.

*Wheel bearings are stainless steel, and
should not be lubricated.


† "N" indicates acetal wheels.



Part Number	Design Load Lbs (kN)	Wt/100 pcs Lbs (kg)
P2749	50 .22	21 9.5
P2749N	10 .04	13 5.9

P2750, P2750N[†]


EG



Clevis Material: 12 gauge.

*Wheel bearings are stainless steel, and
should not be lubricated.



† "N" indicates acetal wheels.



Part Number	Design Load Lbs (kN)	Wt/100 pcs Lbs (kg)
P2750	100 .44	55 24.9
P2750N	20 .09	32 14.5

P2949

EG




Wheel bearings are
stainless steel.
Do not lubricate.

Wt/100 pcs: 46 Lbs (20.9 kg)

P1834A

CHANNEL TROLLEY SUPPORT EG





Requires $\frac{3}{8}$ " x $2\frac{1}{2}$ " Bolt and $\frac{3}{8}$ " Nut
(not included)

Design Load
2500 Lbs (11.12 kN)

Wt/100 pcs: 220 Lbs (99.8 kg)

P2751, P2751 N[†]

EG



Part Number	Design Load Lbs (kN)	Wt/100 pcs Lbs (kg)
P2751	100 .44	63 28.6
P2751N	20 .09	40 18.1



Clevis Material: 12 gauge.

*Wheel bearings are stainless steel, and
should not be lubricated.

† "N" indicates acetal wheels.

P2950

EG




FPM	RPM	Design Load In P1000 Lbs (kN)
180	600	300 1.33
90	300	450 2.00
30	100	600 2.67

Wheel bearings are stainless steel.
Do not lubricate.

Wt/100 pcs: 110 Lbs (49.9 kg)


Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: $\frac{9}{16}$ " (14.3mm); Hole Spacing - From End: $\frac{13}{16}$ " (20.6mm); Hole Spacing - On Center: $1\frac{1}{8}$ " (47.6mm); Width: $1\frac{5}{8}$ "(41.3mm); Thickness: $\frac{1}{4}$ " (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45


P2354 R-L, P2355 R-L**REEL RACK SUPPORTS FOR 1¼" & 2" PIPE**

Vertical Channel Part No.	Gauge	Max. Allowable Load Lbs (kN)
P1000	12	3,000 (13.34)
P1100	14	2,000 (8.90)
P2000	16	2,000 (8.90)

Part Number	"A" In (mm)	Std. Pipe Size In (mm)	Wt/100 pcs Lbs (kg)
P2354 R-L	3	1 1/4	220
	76.2	31.8	99.8
P2355 R-L	3 5/8	2	252
	92.1	50.8	114.3

P1204 THRU P1208**WALL LADDER BRACKET EG**


Part Number	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)
P1204	2 3/8	6	113
	60.3	152.4	51.3
P1205	4 3/8	8	164
	111.1	203.2	74.4
P1206	6 3/8	10	216
	161.9	254.0	98.0
P1207	8 3/8	12	267
	212.7	304.8	121.1
P1208	10 3/8	14	318
	263.5	355.6	144.2

P2454**DOUBLE PIPE AXLE SUPPORT**


Load Rating 4,000 Lbs (17.79 kN)

For 1¼" (31.8) Standard Pipe


Wt/100 pcs: 310 Lbs (140.6 kg)

P1201, P1202, P1203**LADDER RUNG**


Part Number	"A" In (mm)	Wt/100 pcs Lbs (kg)
P1201	12	186
	304.8	84.4
P1202	15	221
	381.0	100.2
P1203	18	254
	457.2	115.2

P2470-50, -75, -100**PIPE COUPLING FITTING**

Part Number	Size In	Wt/100 pcs Lbs (kg)
P2470-50	1/2	77 (34.9)
P2470-75	3/4	93 (42.2)
P2470-100	1	103 (46.7)

P1944**45° (.25π) STAIR TREAD SUPPORT**

Wt/100 pcs: 220 Lbs (99.8 kg)

P2655**37½° (.21π) STAIR TREAD SUPPORT**

Wt/100 pcs: 213 Lbs (96.6 kg)

Standard Dimensions for 1 5/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)




Hole Diameter: 1/16" (14.3mm); Hole Spacing - From End: 13/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (47.6mm); Width: 1 5/8" (41.3mm); Thickness: 1/4" (6.4mm) with steel meeting or exceeding ASTM A1011 SS GR 33, or 0.220" (5.6mm) with steel meeting or exceeding ASTM A1011 HSLAS GR 45



P1843 ADJ. HINGE CONNECTION EG GR

P1354A ADJ. HINGE CONNECTION EG GR

P1354 ADJ. HINGE CONNECTION EG GR





Wt/100 pcs: 68 Lbs (30.8 kg)

Wt/100 pcs: 89 Lbs (40.4 kg)

Wt/100 pcs: 109 Lbs (49.4 kg)

SPF® 100

SEISMIC PIVOT FITTINGS



Part Number	Rod Size In (mm)	"R" - Hole Diameter In (mm)	Design Load Lbs (KN)
SPF 100-037	3/8 9.5	7/16 11.1	1,400 6.23
SPF 100-050	1/2 12.7	9/16 14.3	2,100 9.34
SPF 100-062	5/8 15.9	1 1/16 17.5	2,100 9.34
SPF 100-075	3/4 19.1	1 3/16 20.6	2,400 10.68

Safety Factor = 3

FINISH


Electro-galvanized (EG), conforming to ASTM B633 Type III SC1.

Notes:

1. Design load is limited to slip capacity of a channel nut at hole "R".
2. Allowable loads have been determined by the manufacturers testing, analysis and technical specifications.
3. For retrofit application, engineer of record must verify.
4. Square washer provided with fitting.
5. When a hanger rod is thru-bolted (in lieu of channel nut installation), higher transverse loads may be transmitted due to the higher allowed rod shear loads compared to channel nut slip values. This higher load may be used with verification through engineering calculations.

SPF® 200

ADJUSTABLE SEISMIC PIVOT FITTINGS



FINISH
Electro-galvanized (EG), conforming to ASTM B633 Type III SC1.

Part Number	Rod Size In (mm)	"R" - Hole Diameter In (mm)	Design Load Lbs (KN)
SPF 200-037	3/8 9.5	7/16 11.1	1,400 6.23
SPF 200-050	1/2 12.7	9/16 14.3	2,100 9.34
SPF 200-062	5/8 15.9	1 1/16 17.5	2,100 9.34
SPF 200-075	3/4 19.1	1 3/16 20.6	2,400 10.68

Safety Factor = 3.0


Notes:

1. Design load is limited to slip capacity of a channel nut at hole "R" ..
2. Allowable loads have been determined by the manufacturers testing, analysis and technical specifications at 45° from horizontal.
3. For retrofit application, engineer of record must verify.
4. Square washer provided with fitting.
5. When a hanger rod is thru-bolted (in lieu of channel nut installation), higher transverse loads may be transmitted due to the higher allowed rod shear loads compared to channel nut slip values. This higher load may be used with verification through engineering calculations.



SPF® 300

SEISMIC PIVOT FITTINGS



Notes:

1. Design load is limited to slip capacity of a channel nut at hole "R".
2. Allowable loads have been determined by the manufacturers testing, analysis and technical specifications at 45° from horizontal.
3. For retrofit application, engineer of record must verify.
4. Square washer provided with fitting.
5. When a hanger rod is thru-bolted (in lieu of channel nut installation), higher transverse loads may be transmitted due to the higher allowed rod shear loads compared to channel nut slip values. This higher load may be used with verification through engineering calculations.

Part Number	Rod Size In (mm)	"R" - Hole Diameter In (mm)	Design Load Lbs (kN)
SPF 300-037	5/8 9.5	7/16 11.1	1,400 6.23
SPF 300-050	1/2 12.7	9/16 14.3	2,100 9.34
SPF 300-062	5/8 15.9	1 1/16 17.5	2,100 9.34
SPF 300-075	3/4 19.1	13/16 20.6	2,400 10.68





Safety Factor = 3.0

FINISH

Electro-galvanized (EG), conforming to ASTM B633 Type III SC1.



SEISMIC PIVOT FITTINGS



Notes:



1. Allowable loads have been determined by the manufacturers testing, analysis and technical specifications.
2. Galvanized wire rope, 7 x 19 IWSC, RHRL (Prestretched).
3. Torque on nut/spacer: 50 ft-lbs.
4. Safety Factor of 3 for prestretched cable..

Part Number	Rod Size In (mm)	"R" - Hole Diameter In (mm)
SPF 400-037	5/8 9.5	7/16 11.1
SPF 400-050	1/2 12.7	9/16 14.3
SPF 400-062	5/8 15.9	1 1/16 17.5
SPF 400-075	3/4 19.1	13/16 20.6

FINISH

Electro-galvanized (EG), conforming to ASTM B633 Type III SC1.




Horizontal Design Load			
Wire Rope Diameter In (mm)	4-Way Splayed		
	Transverse lbs (kN)	Longitudinal lbs (kN)	Single Cable Transverse lbs (kN)
5/16 4.8	1050 4.67	1116 4.96	650 2.89





LS 410

SEISMIC PIVOT FITTINGS



Part Number	Anchor Size In (mm)	"R" - Hole Diameter In (mm)
LS 410-037	3/8 9.5	7/16 11.1
LS 410-050	1/2 12.7	9/16 14.3
LS 410-062	5/8 15.9	11/16 17.5
LS 410-075	3/4 19.1	13/16 20.6

FINISH


Electro-galvanized (EG), conforming to ASTM B633 Type III SC1.

Note:

1. Allowable loads have been determined by the manufacturers testing, analysis and technical specifications.
2. For retrofit application, engineer of record must verify.
3. Torque on nut/spacer: 50 ft-lbs.
4. Square washer provided with fitting.
5. Loads are the same as the SPF 400

LS 500

SEISMIC PIVOT FITTINGS



Example
LS500-037-096

Cable Length
Anchor Size
Fitting Number

Cable	Length
096	8' (2.4M)
120	10' (3.0M)
144	12' (3.6M)
180	15' (4.5M)
240	20' (6.1M)
300	25' (7.6M)
360	30' (9.1M)
480	40' (12.2M)

Part Number	Anchor Size In (mm)	"R" - Hole Diameter In (mm)
LS 500-037	3/8 9.5	7/16 11.1
LS 500-050	1/2 12.7	9/16 14.3
LS 500-062	5/8 15.9	11/16 17.5
LS 500-075	3/4 19.1	13/16 20.6


FINISH

Electro-galvanized (EG), conforming to ASTM B633 Type III SC1.

Note:

1. Allowable loads have been determined by the manufacturers testing, analysis and technical specifications.
2. For retrofit application, engineer of record must verify.
3. Square washer provided with fitting.
4. Loads are the same as the SPF 400

PIPE/CONDUIT SUPPORTS



MATERIAL

Unistrut pipe clamps, unless noted, are punch-press made from hot-rolled, pickled and oiled steel plates, strip, bar or coil, and conform to one or more of the following specifications: ASTM A1008, A575, A576, A635, A1011 SS GR 33, A1011 HSLAS GR 45, A1046 or A36. The fitting steel also meets the or exceeds the physical properties of ASTM A1011 GR 33. The pickling of the steel produces a smooth surface free from scale.

Many items are also available in stainless steel, aluminum and fiberglass.

Consult factory for ordering information.

FINISHES

Pipe supports are available in:

- Electro-galvanized (EG), conforming to ASTM B633 Type III SC1
- Hot-dipped galvanized (HG), conforming to ASTM A123 or A153 (hardware)
- Green Powder Coat (GR), conforming to commercial standards for Powder Coating, and plain (PL)
- Unistrut Defender (DF), conforming to ASTM A1059 or A1046

APPLICATION

Unistrut pipe clamps, pipe hangers, brackets and rollers are designed for the support of electrical and mechanical services. Supports to meet nearly every requirement can be attained using Unistrut Metal Framing components.

Pipe Clamps In Special Materials (P1109, P1211, P1425, P2024 Series)

Material/Finish	Part Number Suffix	Pipe Clamp Material / Finish	Fasteners (Screw & Nut) Material / Finish	Example
Electro-galvanized	EG	EG	EG	P1109 EG
Hot-dipped galvanized	HG	HG	SS	P1109 HG
Unistrut Defender	DF	DF	DF	P1109 DF
Stainless Steel Type 304	SS	SS	SS	P1109 SS
Stainless Steel Type 316	ST	ST	SS	P1109 ST
Aluminum	AL	AL	AL	P1109 AL
Copper Coated	CC	CC	CC	P1109 CC
Everdur	E EG	EG	E	P1109E EG

Pipe/Conduit Clamps	108 - 111
Unicushion®	112
Pipe & Tubing (Cush-A-Clamp®) Clamps	113 - 115
Pipe & Tubing (Cush-A-Grip® & Cush-A-Therm™) Clamps.....	116
Pipe Hangers	117
Pipe Rollers.....	117 - 119
Pipe Brackets	119
Reference Tables	120 - 126

DIMENSIONS

Imperial dimensions are illustrated in inches. Metric dimensions are shown in parenthesis or as noted. Unless noted, all metric dimensions are in millimeters and rounded to one decimal place.

DESIGN BOLT TORQUE

BOLT SIZE	1/4"-20	5/16"-18	3/8"-16	1/2"-13	5/8"-11	3/4"-10
Rec.Torque Ft/Lbs (Nm)	6 (8)	11 (15)	19 (26)	50 (68)	100 (136)	125 (170)
Max Torque Ft/Lbs (Nm)	7 (9)	15 (20)	25 (34)	70 (95)	125 (170)	135 (183)

Note: When tightening 1/4" screws used with a two piece pipe clamp, a torque of 5 foot pounds (60 inch-pounds) should be used.


DESIGN LOAD

Design load data, where shown, is based on the ultimate strength of the connection with a safety factor of 5.0, unless otherwise noted.


When used for mechanical supports, load capacities of brackets, fittings and other supporting elements should be in compliance with the American Standard Code for Pressure Piping.



Pipe & Conduit Clamps



P1109 - Pg 108



P1211 - Pg 109




P1425 - Pg 109




P2024 - Pg 110




P1563 - Pg 109




P2008 - Pg 109




P2558 - Pg 110




P3409 - Pg 111



MU025 - Pg 111




P2600 - Pg 112



004T008 - Pg 113




004M007 - Pg 114



UB1/2PA - Pg 115



CG-10 - Pg 116




PUX3834 - Pg 116


Pipe Rollers




J1205 - Pg 117




P2474 - Pg 117



P2474-1 - Pg 118




P2475 - Pg 118




P2476 - Pg 119


Pipe Brackets



P2481 - Pg 119




P2482 - Pg 119



P2243 - Pg 119

P1109 THRU P1126

PIPE CLAMPS FOR RIGID STEEL CONDUIT




Part No.	Conduit Size In	O.D. Size In (mm)	Thickness Gauge (mm)	Wt/100 pcs Lbs (kg)	Design Load Lbs (kN)
P1109	3/8	0.675 17.1	16 1.5	10 4.5	400 1.78
P1111	1/2	0.840 21.3	16 1.5	11 5.0	400 1.78
P1112	3/4	1.050 26.7	14 1.9	15 6.8	600 2.67
P1113	1	1.315 33.4	14 1.9	17 7.7	600 2.67
P1114	1 1/4	1.660 42.2	14 1.9	19 8.6	600 2.67
P1115	1 1/2	1.900 48.3	12 2.7	29 13.2	800 3.56
P1117	2	2.375 60.3	12 2.7	34 15.4	800 3.56

Part No.	Conduit Size In	O.D. Size In (mm)	Thickness Gauge (mm)	Wt/100 pcs Lbs (kg)	Design Load Lbs (kN)
P1118	2 1/2	2.875 73.0	12 2.7	40 18.1	800 3.56
P1119	3	3.500 88.9	12 2.7	47 21.3	800 3.56
P1120	3 1/2	4.000 101.6	11 3.0	62 28.1	1,000 4.45
P1121	4	4.500 114.3	11 3.0	67 30.4	1,000 4.45
P1123	5	5.563 141.3	11 3.0	80 36.3	1,000 4.45
P1124	6	6.625 168.3	10 3.4	102 46.3	1,000 4.45
P1126	8	8.625 219.1	10 3.4	130 59.0	1,000 4.45

Slotted hex head screw and nut included

P1425 THRU P1431**PIPE CLAMPS FOR THIN WALL CONDUIT (E.M.T.)**

[DF EG HG]




Slotted hex head screw and nut included

Part No.	Conduit Size In (mm)	O.D. Size In (mm)	Thickness Gauge (mm)	Wt/100 pcs	Design Load Lbs (kg)
P1425	9.5	14.7	1.5	4.1	1.78
	12.7	17.9	1.5	5.0	1.78
P1426	19.1	23.4	1.5	5.4	1.78
	25.4	29.5	1.9	6.8	2.67
P1427	31.8	38.4	1.9	8.2	2.67
	38.1	44.2	2.7	13.2	3.56
P1428	50.8	55.8	2.7	15.0	3.56
	63.5	73.0	2.7	18.1	3.56
P1118	76.2	88.9	2.7	21.3	3.56
	88.9	101.6	3.0	28.1	4.45
P1119	101.6	114.3	3.0	30.4	4.45
P1120					
P1121					

P1211 THRU P1217**UNIVERSAL CLAMPS FOR RIGID OR THINWALL CONDUIT**

[DF EG HG]




Slotted hex head screw and nut included

Part No.	Conduit Size In (mm)	Thickness Gauge (mm)	Wt/100 pcs	Design Load Lbs (kg)
P1211	12.7	1.5	4.5	1.78
P1212	19.1	1.5	5.0	1.78
P1213	25.4	1.5	5.4	1.78
P1214	31.8	1.9	8.2	2.67
P1215	38.1	1.9	9.1	2.67
P1217	50.8	1.9	10.0	2.67
P1118	63.5	2.7	18.1	3.56
P1119	76.2	2.7	21.3	3.56
P1120	88.9	3.0	28.1	4.45
P1121	101.6	3.0	30.4	4.45

P1563 THRU P1573**PARALLEL CLAMPS FOR RIGID CONDUIT AND PIPE**

[EG]




Slotted hex head screw and nut included.

Finish: Electro-galvanized.

Part No.	Pipe Size In (mm)	O.D. Size In (mm)	Thickness Gauge (mm)	Wt/100 pcs
P1563	9.5	17.1	1.9	12.2
	12.7	21.3	1.9	13.2
P1564	19.1	26.7	1.9	13.6
	25.4	33.4	1.9	14.1
P1565	31.8	42.2	1.9	17.2
	38.1	48.3	2.7	18.1
P1566	50.8	60.3	2.7	21.3
	63.5	73.0	2.7	29.9
P1567	76.2	88.9	2.7	35.4
	88.9	101.6	2.7	39.5
P1568	101.6	114.3	2.7	40.8
P1569				
P1570				
P1571				
P1572				
P1573				

P2008 THRU P2020 ONE HOLE CLAMP FOR O.D. TUBING

[EG HG]

1/4" X 3/4" Round Head
Machine Screw
and Channel Nut
Not Included


Part No.	O.D. Tube Size In (mm)	Thickness Gauge (mm)	Wt/100 pcs
P2008	6.4	1.5	1.8
	7.9	1.5	2.3
P2009	9.5	1.5	2.3
	12.7	1.5	2.7
P2010	15.9	1.9	3.6
	19.1	1.9	4.1
P2012	22.2	1.9	4.5
	25.4	1.9	5.0
P2014			
P2016			
P2018			
P2020			



P2024 THRU P2070-84

PIPE CLAMPS FOR O.D. TUBING

EG HG



Slotted hex head screw and nut included

P2024 - P2029 16 ga.
 P2030 - P2035 14 ga.
 P2037 - P2052 12 ga.
 P2053 - P2066 11 ga.
 P2067 - P2070-84 10 ga.

Part Number	O.D. Size In (mm)	Wt/100 pcs Lbs (kg)	Design Load Lbs (kN)
P2024	1/4 (6.4)	8 (3.6)	400 (1.78)
P2025	5/16 (9.5)	8 (3.6)	
P2026	1/2 (12.7)	9 (4.1)	
P2027	5/8 (15.9)	10 (4.5)	
P2028	3/4 (19.1)	11 (5.0)	
P2029	7/8 (22.2)	12 (5.4)	
P2030	1 (25.4)	14 (6.4)	600 (2.67)
P2031	1 1/16 (28.6)	15 (6.8)	
P2032	1 1/4 (31.8)	16 (7.3)	
P2033	1 1/8 (34.9)	17 (7.7)	
P2034	1 1/2 (38.1)	18 (8.2)	
P2035	1 5/8 (41.3)	19 (8.6)	
P1430	1 1/4 (44.5)	29 (13.2)	800 (3.56)
P2037	1 1/2 (47.6)	28 (12.7)	
P2038	2 (50.8)	31 (14.1)	
P2039	2 1/8 (54.0)	32 (14.5)	
P2040	2 1/4 (57.2)	33 (15)	
P1117	2 5/8 (60.3)	34 (15.4)	
P2042	2 1/2 (63.5)	35 (15.9)	1000 (4.45)
P2043	2 1/4 (66.7)	37 (16.8)	
P2044	2 3/4 (69.9)	38 (17.2)	
P1118	2 1/2 (73.0)	40 (18.1)	
P2046	3 (76.2)	41 (18.6)	
P2047	3 1/4 (79.4)	43 (19.5)	
P2048	3 1/2 (82.6)	45 (20.4)	1000 (4.45)
P2049	3 3/4 (85.7)	46 (20.9)	
P1119	3 1/2 (88.9)	47 (21.3)	
P2051	3 1/2 (92.1)	56 (25.4)	
P2052	3 3/4 (95.3)	58 (26.3)	
P2053	3 5/8 (98.4)	60 (27.2)	
P1120	4 (101.6)	62 (28.1)	1000 (4.45)
P2055	4 1/8 (104.8)	62 (28.1)	
P2056	4 1/4 (108.0)	64 (29.0)	
P2057	4 1/2 (111.1)	66 (29.9)	
P1121	4 1/2 (114.3)	67 (30.4)	
P2059	4 1/2 (117.5)	70 (31.8)	
P2060	4 3/4 (120.7)	72 (32.7)	

Part Number	O.D. Size In (mm)	Wt/100 pcs Lbs (kg)	Design Load Lbs (kN)
P2061	4 1/8 (123.8)	73 (33.1)	
P2062	5 (127.0)	74 (33.6)	
P2063	5 1/8 (130.2)	76 (34.5)	
P2064	5 1/4 (133.4)	77 (34.9)	
P2065	5 5/8 (136.5)	78 (35.4)	
P2066	5 1/2 (140.0)	79 (35.8)	
P2067	5 1/4 (142.9)	88 (39.9)	
P2068	5 3/4 (146.1)	90 (40.8)	
P2069	5 5/8 (149.2)	92 (41.7)	
P2070	6 (152.4)	94 (42.6)	
P2070-61	6 1/8 (155.6)	96 (43.5)	
P2070-62	6 1/4 (158.8)	98 (44.5)	
P2070-63	6 5/8 (161.9)	99 (44.9)	
P2070-64	6 1/2 (165.1)	100 (45.4)	
P1124	6 1/4 (168.3)	102 (46.3)	
P2070-66	6 3/4 (171.5)	104 (47.2)	
P2070-67	6 7/8 (174.6)	106 (48.1)	
P2070-70	7 (177.8)	108 (49.0)	
P2070-71	7 1/8 (181.0)	110 (49.9)	
P2070-72	7 1/4 (184.2)	112 (50.8)	
P2070-73	7 5/8 (187.3)	114 (51.7)	
P2070-74	7 1/2 (190.5)	116 (52.6)	
P2070-75	7 7/8 (193.7)	117 (53.1)	
P2070-76	7 3/4 (196.9)	119 (54.0)	
P2070-77	7 7/8 (200.0)	121 (54.9)	
P2070-80	8 (203.2)	123 (55.8)	
P2070-81	8 1/8 (206.4)	125 (56.7)	
P2070-82	8 1/4 (209.6)	126 (57.2)	
P2070-83	8 5/8 (212.7)	128 (58.1)	
P2070-84	8 1/2 (215.9)	129 (58.5)	
P1126	8 7/8 (219.1)	130 (59.0)	

P2558-5 THRU P2558-60

SINGLE PIECE PIPE STRAP EG GR HG




Hardware sold separately.

Part No.	Nom. Pipe Size In	A In (mm)	"B" In (mm)	C In (mm)	Thickness In (mm)	Wt/100 pcs Lbs (kg)	Design Load Lbs (kN)
P2558-05	1/2	2 7/8	73.0	7/16	1/8	23	500 2.22
P2558-07	3/4	3 1/8				26	
P2558-10	1	3 3/8				11.8	
P2558-12	1 1/4	3 3/4				31	
P2558-15	1 1/2	3 7/8				14.1	
P2558-20	2	5 1/4				35	
P2558-25	2 1/2	6 1/4	95.3	11.1	3.2	15.9	1,000 4.45
P2558-30	3	6 7/8				39	
P2558-35	3 1/2	7 7/8				17.7	
P2558-40	4	7 1/2				94	
P2558-50	5	9				42.6	
P2558-60	6	10				114	

P3409 THRU P3417

STAND-OFF PIPE CLAMPS




Hardware included.
Finish: Electro-galvanized.
Pipe Clamp 1¼" Wide

Part No.	Pipe Size In (mm)	O.D. Size In (mm)	Load "D" Lbs (kN)	Load "E" Lbs (kN)	A In (mm)	B In (mm)	C Gauge (mm)	Wt/100 pcs Lbs (kg)
P3409	¾	0.675	100	25	1⅓	2⅓	14	14
	9.5	17.1	0.44	0.11	28.6	54.0	1.9	6.4
P3411	½	0.840	150	35	1⅓	2⅓	14	15
	12.7	21.3	0.67	0.16	31.8	58.7	1.9	6.8
P3412	¾	1.050	175	40	1⅓	2⅓	14	19
	19.1	26.7	0.78	0.18	33.3	63.5	1.9	8.6
P3413	1	1.315	200	50	1⅓	2⅓	14	22
	25.4	33.4	0.89	0.22	38.1	69.9	1.9	10.0
P3414	1¼	1.660	300	70	1⅓	3⅓	12	34
	31.8	42.2	1.33	0.31	42.9	82.6	2.7	15.4
P3415	1½	1.900	400	80	1⅓	3⅓	11	49
	38.1	48.3	1.78	0.36	44.5	88.9	3.0	22.2
P3417	2	2.375	500	120	2	4	10	55
	50.8	60.3	2.22	0.53	50.8	101.6	3.4	24.9

Safety factor of 5


MU025 THRU MU400

MUSTANG UNIVERSAL ONE-PIECE PIPE, CONDUIT (GRC, EMT & IMC) AND TUBING CLAMPS



Finish: Electro-galvanized.
Clamps are 14 ga.

Part No.	Nominal Trade Size In (mm)	Trade Size O.D.		Height Above Channel "H"	
		Min In (mm)	Max In (mm)	Min In (mm)	Max. In (mm)
MU025	¼ 6.4	0.375 9.5	0.5 13.7	1⅓ 44.5	2 50.8
MU037	¾ 9.5	0.5 12.7	0.7 17.1	1⅓ 47.6	2⅓ 54.0
MU050	½ 12.7	0.63 15.9	0.84 21.3	2 50.8	2⅓ 57.2
MU075	¾ 19.1	0.88 22.2	1.05 26.7	2⅓ 57.2	2⅓ 63.5
MU100	1 25.4	1.13 28.6	1.32 33.4	2⅓ 60.3	2⅔ 69.9
MU125	1¼ 31.8	1.38 34.9	1.66 42.2	2⅓ 69.9	3⅓ 79.4
MU150	1½ 38.1	1.63 41.3	1.90 48.3	3 76.2	3⅓ 85.7
MU200	2 50.8	2.13 54.0	2.38 60.3	3⅓ 85.7	3⅓ 98.4
MU250	2½ 63.5	2.63 66.7	2.88 73.0	4⅓ 108.0	4⅓ 117.5
MU300	3 76.2	3.13 79.4	3.50 88.9	4⅓ 123.8	5⅓ 136.5
MU350	3½ 88.9	3.63 92.1	4.00 101.6	5⅓ 133.4	5⅓ 149.2
MU400	4 101.6	4.13 104.8	4.50 114.3	5⅓ 146.1	6⅓ 161.9



- 25 feet per carton.
- Cut to length as shown in chart below.

Wt/Carton: 2.5 Lbs (1.1 kg)

UNICUSHION FEATURES

- Shock absorption
- Protection from corrosion and abrasion
- Allowance for expansion and contraction in pipe diameter
- Sound and vibration isolation
- Stability in use from - 50° F (-47° C) to + 350°F (+177° C)
- Flexible elastomer material
- Will not support combustion

UNICUSHION® CLAMP SELECTION GUIDE

EMT CONDUIT

Nominal Size	Use with Clamp	UNICUSHION Length In (mm)
3/8"	P1426	1 1/4 (44.5)
1/2"	P1111	2 1/8 (54.0)
3/4"	P1112	2 3/4 (69.9)
1"	P2032	3 5/8 (92.1)
1 1/4"	P2035	4 3/4 (120.7)
1 1/2"	P2037	5 1/2 (139.7)
2"	P1117	6 3/4 (171.5)

STANDARD PIPE OR RIGID CONDUIT

Nominal Size	Use with Clamp	UNICUSHION Length In (mm)
3/8"	P1111	2 1/8 (54.0)
1/2"	P2030	3 (76.2)
3/4"	P2031	3 1/4 (82.6)
1"	P2034	4 1/4 (108.0)
1 1/4"	P2037	5 1/4 (133.4)
1 1/2"	P2038	6 (152.4)
2"	P2042	7 1/8 (190.5)
2 1/2"	P2046	9 (228.6)
3"	P2051	11 (279.4)
3 1/2"	P2055	12 1/4 (311.2)
4"	P2059	14 (355.6)
5"	P2067	17 1/2 (444.5)
6"	P2070-66	20 3/4 (527.1)

COPPER TUBING TYPE K OR L

Nominal Size	Use with Clamp	UNICUSHION Length In (mm)
1/4"	P2026	1 1/16 (27.0)
3/8"	P2027	1 1/2 (38.1)
1/2"	P2028	2 1/8 (54.0)
5/8"	P2029	2 1/4 (57.2)
3/4"	P2030	3 (76.2)
1"	P2032	3 5/8 (92.1)
1 1/4"	P2034	4 1/2 (114.3)
1 1/2"	P1430	5 1/4 (133.4)
2"	P2040	6 3/4 (171.5)
2 1/2"	P2044	8 1/4 (209.6)
3"	P2048	10 (254.0)
3 1/2"	P2052	11 1/4 (285.8)
4"	P2056	12 1/2 (317.5)
5"	P2064	16 (406.4)
6"	P2070-62	19 (482.6)
8"	P2070-82	25 (635.0)

UNICUSHION® CLAMP CUTTING GUIDE

O. D. Size In (mm)	Use With Clamp	UNICUSHION Length In (mm)
1/4 (6.4)	P2025	7/8 (22.2)
3/8 (9.5)	P2026	1 1/16 (27.0)
1/2 (12.7)	P2027	1 1/2 (38.1)
5/8 (15.9)	P2028	2 1/8 (54.0)
3/4 (19.1)	P2029	2 1/4 (57.2)
7/8 (22.2)	P2030	3 (76.2)
1 (25.4)	P2031	3 1/4 (82.6)
1 1/8 (28.6)	P2032	3 5/8 (92.1)
1 1/4 (31.8)	P2033	4 (101.6)
1 1/8 (34.9)	P2034	4 1/2 (114.3)
1 1/2 (38.1)	P2035	4 3/8 (123.8)
1 1/8 (41.3)	P1430	5 1/4 (133.4)
1 1/4 (44.5)	P2037	5 1/2 (139.7)
1 1/8 (47.6)	P2038	6 (152.4)
2 (50.8)	P2039	6 1/2 (165.1)
2 1/8 (54.0)	P2040	6 3/4 (171.5)
2 1/4 (57.2)	P1117	7 1/4 (184.2)
2 1/8 (60.3)	P2042	7 1/2 (190.5)
2 1/2 (63.5)	P2043	8 (203.2)
2 1/8 (66.7)	P2044	8 1/4 (209.6)
2 3/4 (69.9)	P1118	8 3/4 (222.3)
2 1/2 (73.0)	P2046	9 1/4 (235.0)
3 (76.2)	P2047	9 1/2 (241.3)



O. D. Size In (mm)	Use With Clamp	UNICUSHION Length In (mm)
3 1/8 (79.4)	P2048	10 (254.0)
3 1/4 (82.6)	P2049	10 1/2 (266.7)
3 3/8 (85.7)	P1119	10 3/4 (273.1)
3 1/2 (88.9)	P2051	11 (279.4)
3 5/8 (92.1)	P2052	11 1/4 (285.8)
3 3/4 (95.3)	P2053	11 1/2 (292.1)
3 1/8 (98.4)	P1120	11 3/4 (298.5)
4 (101.6)	P2055	12 (304.8)
4 1/8 (104.8)	P2056	12 1/2 (317.5)
4 1/4 (108.0)	P2057	13 (330.2)
4 1/8 (111.1)	P1121	13 1/4 (342.9)
4 1/4 (114.3)	P2059	14 (355.6)
4 1/8 (117.5)	P2060	14 1/4 (362.0)
4 1/4 (120.7)	P2061	14 1/4 (374.7)
4 1/8 (123.8)	P2062	15 (381.0)
5 (127.0)	P2063	15 1/2 (393.7)
5 1/8 (130.2)	P2064	16 (406.4)
5 1/4 (133.4)	P2065	16 1/4 (412.8)
5 1/8 (136.5)	P2066	16 1/2 (419.1)
5 1/4 (139.7)	P2067	17 (431.8)
5 5/8 (142.9)	P2068	17 1/2 (444.5)
5 1/4 (146.1)	P2069	17 1/4 (450.9)
5 1/8 (149.2)	P2070	18 1/4 (463.6)

O. D. Size In (mm)	Use With Clamp	UNICUSHION Length In (mm)
6 (152.4)	P2070-61	18 1/2 (469.9)
6 1/8 (155.6)	P2070-62	19 (482.6)
6 1/4 (158.8)	P2070-63	19 1/4 (489.0)
6 5/8 (161.9)	P2070-64	19 3/4 (501.7)
6 1/2 (165.1)	P1124	20 (508.0)
6 1/8 (168.3)	P2070-66	20 1/2 (520.7)
6 3/8 (171.5)	P2070-67	21 (533.4)
6 7/8 (174.6)	P2070-70	21 1/4 (539.8)
7 (177.8)	P2070-71	21 3/4 (552.5)
7 1/8 (181.0)	P2070-72	22 (558.8)
7 1/4 (184.2)	P2070-73	22 1/2 (571.5)
7 5/8 (187.3)	P2070-74	22 3/4 (577.9)
7 1/2 (190.5)	P2070-75	23 1/4 (590.6)
7 5/8 (193.7)	P2070-76	23 3/4 (596.9)
7 1/4 (196.9)	P2070-77	24 (609.6)
7 1/8 (200.0)	P2070-80	24 1/2 (622.3)
8 (203.2)	P2070-81	24 3/4 (628.7)
8 1/8 (206.4)	P2070-82	25 (635.0)
8 1/4 (209.6)	P2070-83	25 1/2 (647.7)
8 3/8 (212.7)	P2070-84	26 (660.4)
8 1/2 (215.9)	P1126	26 1/4 (666.8)

004T008 THRU 098N106, 009N012 THRU 106N114

CUSH-A-CLAMP® ASSEMBLY

CEG



Materials:

Clamp: Electro-galvanized or stainless steel.

Cushion: Thermoplastic elastomer. (UV Resistant)

Includes cushion, clamp and hardware.

Temperature Rating:

-50°F to +275°F (-45°C to +135°C)

Insert Width: 1.56" (39.6)

Part Numbers are "coded" to designate cushion size and clamp size. Examples:

- 004T008** 004 - Cushion Size $\frac{1}{16}$ " (6.4)
T - With Controlled Squeeze Shoulder Bolt
Available on sizes up to 1 $\frac{3}{8}$ "
008 - Clamp Size $\frac{8}{16}$ " (12.7)
- 009N012** 009 - Cushion Size $\frac{9}{16}$ " (14.3)
N - With Standard Bolt
012 - Clamp Size $\frac{12}{16}$ " (19.1)

Pipe Series Assembly

Part No.	Nominal Pipe Size	Dimensions				Wt/100 pcs
		"A" In(mm)	"B" In(mm)	"C" In(mm)	"D" In(mm)	
009N012	$\frac{1}{4}$	0.54 13.7	0.98 24.9	1.34 34.0	0.43 10.9	13 5.9
011N014	$\frac{3}{8}$	0.67 17.0	1.13 28.7	1.54 39.1	0.49 12.4	14 6.4
014N018	$\frac{1}{2}$	0.84 21.3	1.29 32.8	1.82 46.2	0.58 14.7	15 6.8
017N022	$\frac{3}{4}$	1.05 26.7	1.5 38.1	1.95 49.5	0.7 17.8	17 7.7
021N026	1	1.31 33.3	1.76 44.7	2.34 59.4	0.81 20.6	19 8.6
027N032	$\frac{1}{4}$	1.66 42.2	2.17 55.1	2.73 69.3	0.99 25.1	35 15.9
030N034*	$\frac{1}{2}$	1.9 48.3	2.35 59.7	2.86 72.6	1.09 27.7	39 17.7
038N044	2	2.37 60.2	2.82 71.6	3.67 93.2	1.41 35.8	49 22.2
046N052	$2\frac{1}{2}$	2.87 72.9	3.32 84.3	4.17 105.9	1.66 42.2	57 25.9
056N062	$3\frac{1}{2}$	3.12 79.2	3.6 90.7	4.42 112.3	1.78 45.2	60 27.2
058N064	$3\frac{3}{4}$	3.31 84.1	4.0 100.6	4.75 120.7	1.9 48.3	62 28.1
064N072	4	3.5 88.9	4.0 100.3	4.79 121.7	1.97 50.0	55 24.9
066N074	$4\frac{1}{2}$	3.62 91.9	4.2 106.7	4.99 126.7	2.03 51.6	70 31.8
069N076	$4\frac{5}{16}$	4.12 104.6	4.5 116.1	5.44 140.7	2.34 59.4	88 42.6
072N080	$4\frac{1}{2}$	4.34 110.2	5.0 126.0	5.84 148.3	2.4 61.0	100 45.4
082N090	$5\frac{1}{8}$	5.12 130.0	5.6 141.5	6.54 166.1	2.84 72.1	125 56.7
098N106	$6\frac{1}{8}$	6.12 155.4	6.6 166.9	7.54 191.5	3.34 84.8	130 59.0

Tube Series Assembly



Part Number	Copper & Steel Tube O. D. Size	Copper Water Pipe (Nominal)	"A" In(mm)	"B" In(mm)	"C" In(mm)	"D" In(mm)	Wt/100 pcs
004T008	$\frac{1}{4}$		0.25 6.4	0.62 15.7	0.98 24.9	0.27 6.9	10 4.5
006T010	$\frac{3}{8}$	$\frac{1}{4}$	0.37 9.4	0.82 20.8	1.13 28.7	0.33 8.4	11 5.0
008T012	$\frac{1}{2}$	$\frac{3}{8}$	0.5 12.7	0.94 23.9	1.34 34.0	0.4 10.2	13 5.9
010T014	$\frac{5}{8}$	$\frac{1}{2}$	0.62 15.7	1.06 26.9	1.54 39.1	0.46 11.7	14 6.4
012T016	$\frac{3}{4}$	$\frac{5}{8}$	0.75 19.1	1.2 30.5	1.68 42.7	0.52 13.2	14 6.4
014T018	$\frac{7}{8}$	$\frac{3}{4}$	0.87 22.1	1.31 33.3	1.82 46.2	0.58 14.7	15 6.8
016T020	1		1 25.4	1.44 36.6	1.95 49.5	0.65 16.5	17 7.7
018T022	$1\frac{1}{8}$	1	1.12 28.4	1.57 39.9	2.08 52.8	0.7 17.8	18 8.2
020T024	$1\frac{1}{4}$		1.25 31.8	1.7 43.2	2.21 56.1	0.77 19.6	18 8.2
022T026	$1\frac{3}{8}$	$1\frac{1}{4}$	1.37 34.8	1.82 46.2	2.34 59.4	0.83 21.1	20 9.1
024N028	$1\frac{1}{2}$		1.5 38.1	1.95 49.5	2.47 62.7	0.9 22.9	33 15.0
026N030	$1\frac{5}{8}$	$1\frac{1}{2}$	1.62 41.1	2.07 52.6	2.6 66.0	0.96 24.4	35 15.9
028N032	$1\frac{3}{4}$		1.75 44.5	2.2 55.9	2.73 69.3	1.02 25.9	37 16.8
030N034	$1\frac{7}{8}$		1.9 48.3	2.35 59.7	2.86 72.6	1.09 27.7	39 17.7
032N036	2		2 50.8	2.45 62.2	3.04 77.2	1.15 29.2	46 20.9
034N040	$2\frac{1}{8}$	2	2.12 53.8	2.57 65.3	3.23 82.0	1.27 32.3	47 21.3
038N044	$2\frac{3}{8}$		2.37 60.2	2.82 71.6	3.67 93.2	1.41 35.8	49 22.2
040N046	$2\frac{1}{2}$		2.5 63.5	2.94 74.7	3.79 96.3	1.46 37.1	51 23.1
042N048	$2\frac{5}{8}$	$2\frac{1}{2}$	2.62 66.5	3.1 78.0	3.92 99.6	1.53 38.9	55 24.9
046N052	$2\frac{7}{8}$		2.87 72.9	3.3 84.3	4.17 105.9	1.66 42.2	57 25.9
050N054	3		3 76.2	3.6 90.7	4.42 112.3	1.78 45.2	60 27.2
050N056	$3\frac{1}{8}$	3	3.12 79.2	3.6 90.7	4.42 112.3	1.78 45.2	60 27.2
053N060	$3\frac{5}{16}$		3.31 84.1	4.0 100.6	4.75 120.7	1.9 48.3	62 28.1
056N062	$3\frac{1}{2}$		3.5 88.9	4.0 100.3	4.79 121.7	1.97 50.0	55 24.9
058N064	$3\frac{3}{4}$	$3\frac{1}{2}$	3.62 91.9	4.2 106.7	4.99 126.7	2.03 51.6	70 31.8
064N072	4		4 101.6	4.5 113.0	5.42 137.7	2.28 57.9	88 39.9
066N074	$4\frac{1}{2}$	4	4.12 104.6	4.6 116.1	5.54 140.7	2.34 59.4	94 42.6
069N076	$4\frac{5}{16}$		4.34 110.2	5.0 126.0	5.84 148.3	2.4 61.0	100 45.4
072N080	$4\frac{1}{2}$		4.5 114.3	5.0 125.7	5.92 150.4	2.53 64.3	110 49.9
082N090	$5\frac{1}{8}$	5	5.12 130.0	5.6 141.5	6.54 166.1	2.84 72.1	125 56.7
098N106	$6\frac{1}{8}$	6	6.12 155.4	6.6 166.9	7.54 191.5	3.34 84.8	130 59.0



004M007 THRU 034M040 CUSH-A-CLAMP®



Assembly Omega Series™



Includes clamp and cushion.


Materials: Clamp: ZD or stainless steel.

Cushion: Thermoplastic elastomer.

Note: 1-1/4 and larger can be used with Unistrut Channel.

Can be mounted to any flat surface.

CUSH-A-CLAW™



UV standardized thermo plastic

Temp Range: -50° to 275°F

Sure Grip Base

No Fasteners needed


Corrosion resistant

Prevents Galvanic Corrosion - Great for Unistrut® Defender™

Part Number	Size
CL04	1/4"
CL06	3/8"
CL08	1/2"
CL10	5/8"
CL12	3/4"
CL14	7/8"
CL18	1-1/8"

Part Number	Copper & Steel Tubing O. D. In	Copper Water Pipe (Nominal) In	Pipe Size (Nominal) In	Dimensions										Wt/100 pcs Lbs (kg)
				"A" In (mm)	"B" In (mm)	"C" In (mm)	"D" In (mm)	"E" In (mm)	"F" In (mm)	"G" In (mm)	"H" In (mm)	"J" In (mm)		
004M007	1/4		1/4	0.25	1.8	0.06	0.6	0	0.53	0.48	0.62	0.78	3.4	
				6.4	46.0	1.5	15.2	5.1	13.5	12.2	15.7	19.8	1.5	
006M008	5/8	1/4	1/4	0.37	1.9	0.06	0.65	0	0.62	0.62	0.62	0.81	4.0	
				9.4	48.3	1.5	16.5	5.1	15.7	15.7	15.7	20.6	1.8	
008M011	1/2	5/8	1/4	0.5	2.2	0.06	0.8	0	0.82	0.75	0.75	0.98	5.5	
				12.7	55.9	1.5	20.3	6.6	20.8	19.1	19.1	24.9	2.5	
010M013	5/8	1/2	5/8	0.62	2.3	0.06	0.86	0	0.94	0.87	0.75	0.98	6.0	
				15.7	58.9	1.5	21.8	6.6	23.9	22.1	19.1	24.9	2.7	
012M015	3/4	5/8	5/8	0.75	2.4	0.06	0.9	0	1.03	1.01	0.75	0.98	6.5	
				19.1	61.2	1.5	22.9	6.6	26.2	25.7	19.1	24.9	2.9	
014M017	7/8	3/4	1/2	0.87	2.6	0.06	0.98	0	1.18	1.03	0.75	0.98	7.1	
				22.1	65.0	1.5	24.9	6.6	30.0	26.2	19.1	24.9	3.2	
016M019	1		1	1	2.7	0.06	1.04	0	1.31	1.25	0.75	0.98	7.8	
				25.4	68.1	1.5	26.4	6.6	33.3	31.8	19.1	24.9	3.5	
018M020			3/4	1.05	2.7	0.06	1.04	0	1.31	1.25	0.75	0.98	8.1	
				26.7	68.1	1.5	26.4	6.6	33.3	31.8	19.1	24.9	3.7	
018M021	1 1/8	1	1	1.12	2.8	0.06	1.11	0	1.44	1.33	0.75	0.98	8.4	
				28.4	71.6	1.5	28.2	6.6	36.6	33.8	19.1	24.9	3.8	
020M024	1 1/4			1.25	3.0	0.08	1.2	0	1.65	1.47	1.25	1.56	17	
				31.8	76.2	2.0	30.5	6.6	41.9	37.3	31.8	39.6	7.7	
021M026		1	1	1.31	3.1	0.08	1.26	0	1.76	1.71	1.25	1.56	20	
				33.3	79.2	2.0	32.0	6.6	44.7	43.4	31.8	39.6	9.1	
022M026	1 1/8	1 1/4		1.37	3.1	0.08	1.26	0	1.76	1.71	1.25	1.56	19	
				34.8	79.2	2.0	32.0	6.6	44.7	43.4	31.8	39.6	8.6	
024M028	1 1/2			1.5	3.7	0.08	1.42	0	1.93	1.88	1.25	1.56	20	
				38.1	92.7	2.0	36.1	6.6	49.0	47.8	31.8	39.6	9.1	
026M030	1 1/8	1 1/2		1.62	3.8	0.08	1.48	0	2.07	2	1.25	1.56	23	
				41.1	95.8	2.0	37.6	6.6	52.6	50.8	31.8	39.6	10.4	
027M032		1 1/4		1.66	3.9	0.1	1.55	0	2.21	2.12	1.25	1.56	32	
				42.2	99.1	2.5	39.4	8.4	56.1	53.8	31.8	39.6	14.5	
028M032	1 3/4			1.75	3.9	0.1	1.55	0	2.21	2.12	1.25	1.56	32	
				44.5	99.1	2.5	39.4	8.4	56.1	53.8	31.8	39.6	14.5	
030M034	1 1/8	1 1/2		1.87	4.0	0.1	1.61	0	2.33	2.25	1.25	1.56	34	
				47.5	102.1	2.5	40.9	8.4	59.2	57.2	31.8	39.6	15.4	
032M036	2			2	4.2	0.1	1.67	0	2.46	2.38	1.25	1.56	36	
				50.8	105.4	2.5	42.4	8.4	62.5	60.5	31.8	39.6	16.3	
034M040	2 1/8			2.12	4.4	0.1	1.8	0	2.71	2.62	1.25	1.56	41	
				53.8	111.8	2.5	45.7	8.4	68.8	66.5	31.8	39.6	18.6	
038M044		2		2.37	4.7	0.1	1.94	0	2.96	2.88	1.25	1.56	44	
				60.2	119.6	2.5	49.3	8.4	75.2	73.2	31.8	39.6	20.0	
082M090	5 1/8	5		5.12	7.6	0.1	3.41	0	5.83	6.75	1.25	1.56	120	
				130.0	194.1	2.5	86.6	10.2	148.1	171.5	31.8	39.6	54.4	

UB1½PA THRU UB12PA



Includes: U bolt, cushion, and hardware.


Materials:

U Bolt: Electro-galvanized finish or Type 316 SS

Cushion: Thermoplastic elastomer.

Note: Not intended for use with metal framing components due to the length of the thread.


CUSH-A-CLAMP® ASSEMBLY U-BOLT SERIES CEG



Part Number	Pipe Size (Nominal) In (mm)	Dimensions						Wt/100 pcs	Lbs (kg)
		"A" In (mm)	"B" In (mm)	"C" In (mm)	"D" In (mm)	"E" In (mm)	"F" In (mm)		
UB1½PA	1/2 12.7	0.84 21.3	1.6 40.6	0.68 17.3	1.5 38.1	1 17.0	1/4 6.4	1/4-20 UNC-2B	9 4.1
	3/4 19.1	1.1 26.7	1.8 45.7	0.7 17.3	1.6 40.6	0.8 19.8	1/4 6.4	1/4-20 UNC-2B	10 4.5
UB1PA	1 25.4	1.3 33.3	2.1 52.1	0.7 17.3	1.7 43.2	0.9 23.1	1/4 6.4	1/4-20 UNC-2B	12 5.4
	1 1/4 31.8	1.7 42.2	2.5 64.5	1.2 31.5	2.1 53.3	1.1 27.4	5/8 9.5	5/8-16 UNC-2B	36 16.3
UB1 1/2PA	1 1/2 38.1	1.9 48.3	2.8 70.6	1.2 31.5	2.2 55.9	1.2 30.2	5/8 9.5	5/8-16 UNC-2B	32 14.5
	2 50.8	2.4 60.2	3.3 84.3	1.2 31.5	2.5 63.5	1.5 36.8	5/8 9.5	5/8-16 UNC-2B	42 19.1
UB2 1/2PA	2 1/2 63.5	2.9 72.9	3.9 98.6	1.2 31.5	3.0 76.2	1.7 42.9	1/2 12.7	1/2-13 UNC-2B	72 32.7
	3 76.2	3.5 88.9	4.5 114.3	1.2 31.5	3.3 83.8	2.0 50.8	1/2 12.7	1/2-13 UNC-2B	84 38.1
UB3 1/2PA	3 1/2 88.9	4.0 101.6	5.0 127.0	1.2 31.5	3.7 94.0	2.3 57.2	1/2 12.7	1/2-13 UNC-2B	93 42.2
	4 101.6	4.5 114.3	5.5 139.7	1.2 31.5	3.9 99.1	2.5 63.5	1/2 12.7	1/2-13 UNC-2B	102 46.3
UB4PA	5 127.0	5.6 141.2	6.6 167.4	1.2 31.5	4.5 114.3	3.0 77.0	1/2 12.7	1/2-13 UNC-2B	123 55.8
	6 152.4	6.6 168.1	7.8 198.4	1.4 36.6	5.4 137.2	3.6 90.4	5/8 15.9	5/8-11 UNC-2B	123 55.8
UB6PA	8 203.2	8.6 218.9	9.8 249.9	1.4 36.6	6.4 162.6	4.6 115.8	5/8 15.9	5/8-11 UNC-2B	243 110.2
	10 254.0	10.8 273.1	12.3 311.2	1.7 41.9	7.7 195.6	5.7 144.3	5/8 19.1	5/8-10 UNC-2B	492 223.2
UB10PA	12 304.8	12.8 323.9	14.3 362.0	1.7 41.9	8.7 221.0	6.7 169.7	5/8 19.1	5/8-10 UNC-2B	563 255.4

CUSH-A-NATOR®

STEEL



The Cush-A-Nator cushion is made from a new extremely durable thermoplastic rubber that resists high heat and provides longer life against vibration fatigue.


Part Number	Clamp Material	Size
CN04	Steel	1/4"
CN26	Steel	1-5/8"
CN24	Steel	1-1/2"
CN22	Steel	1-3/8"
CN18	Steel	1-1/8"
CN16	Steel	1"
CN14	Steel	7/8"
CN12	Steel	3/4"
CN10	Steel	5/8"
CN08	Steel	1/2"
CN06	Steel	3/8"
CN34	Steel	1-1/8"

Part Number	Clamp Material	Size
HT04	Steel	1/4"
HT26	Steel	1-5/8"
HT24	Steel	1-1/2"
HT22	Steel	1-3/8"
HT18	Steel	1-1/8"
HT16	Steel	1"
HT14	Steel	7/8"
HT10	Steel	5/8"
HT08	Steel	1/2"
HT06	Steel	3/8"
HT34	Steel	2-1/8"



CG-10 THRU CG-40

CUSH-A-GRIP®



Part Number	O.D. Tube Sizes In(mm)			Nominal Pipe Sizes In(mm)		Diameters In(mm)	PullOut Load Lbs(kN)	Slip Load Lbs(kN)
	1/4	5/16	1/2	1/4	5/16	1/2		
CG-10	6.4	9.5	12.7	6.4	9.5	12.7	0.25 - 0.54 6.4 - 13.7	500 2.22 0.18
CG-20	15.9	19.1	22.2	9.5	12.7	15.7 - 22.1	500 2.22 0.18	40 0.18
CG-30	22.2	25.4	28.6	19.1	22.1	28.4	0.87 - 1.12 22.1 - 28.4	500 2.22 0.18
CG-40	25.4	28.6	31.8	19.1	25.4	33.3	1.00 - 1.31 25.4 - 33.3	500 2.22 0.18

Includes: Cushion, V-pad, and Hardware.

Materials: Cushion: Thermoplastic elastomer.

Hardware: Stainless Steel with Captured Nylon Locknut

Temperature Rating: -40°F to +275°F (-40°C to 135°C)


Part Number	Nominal Pipe Size	Dimensions				Hex Head Cap Screw & Lock Nut	Wt/100 Pcs
		"A" In(mm)	"B" In(mm)	"C" In(mm)	"D" In(mm)		
CG-10	1/4	11 5/16 49.2	1 1/8 34.9	3/8 9.5	5/16 4.8	1/4-20 x 1 1/2"	4 1.8
CG-20	5/8	2 3/8 60.3	1 1/8 41.3	7/16 11	1/4 6.4	1/4-20 x 2"	6 2.7
CG-30	1/2	2 9/16 65.1	1 15/16 46.0	7/16 11	5/16 7.9	1/4-20 x 2"	8 3.6
CG-40	3/4	2 11/16 68.3	1 15/16 49.2	7/16 11	5/16 7.9	1/4-20 x 2"	8 3.6

PUX1234 THRU PUX41810

CUSH-A-THERM™

The only airtight, crush-resistant insulation clamp on the market.

- Maintains thermal barrier protection
- Prevents condensation
- Properly supports pipe and tube
- Absorbs vibration



Nominal 3/4" Wall


Part Number	Hole Size In(mm)	Copper Nom. I.D. In(mm)	O.D. In(mm)	IPS In(mm)	O.D. In(mm)	Length In(mm)
PUX3834	9.5	6.4	9.5	-	46.0	55.1
PUX1234	12.7	9.5	12.7	6.4	48.0	55.1
PUX5834	15.9	12.7	15.9	9.5	52.1	55.1
PUX3434	19.1	15.9	19.1	-	56.4	55.1
PUX7834	22.2	19.1	22.2	12.7	62.0	55.1
PUX11834	28.6	25.4	28.6	19.1	70.1	55.1
PUX13834	34.9	31.8	34.9	25.4	81.0	65.0
PUX15834	41.3	38.1	41.3	31.8	85.1	65.5
PUX21834	54.0	50.8	54.0	-	98.0	65.0
PUX23834	60.3	57.2	60.3	50.8	109.0	75.2
PUX25834	66.7	63.5	66.7	-	123.7	75.2
PUX31834	79.4	76.2	79.4	-	127.0	85.1
PUX35834	92.1	88.9	92.1	-	150.9	100.1
PUX41834	104.8	101.6	104.8	88.9	156.0	100.1

Nominal 1" Wall

Part Number	Hole Size In(mm)	Copper Nom. I.D. In(mm)	O.D. In(mm)	IPS In(mm)	O.D. In(mm)	Length In(mm)
PUX5810	15.9	12.7	15.9	-	9.5	64.5
PUX3410	19.1	15.9	19.1	-	-	71.6
PUX7810	22.2	19.1	22.2	12.7	71.6	55.1
PUX11810	28.6	25.4	28.6	19.1	-	77.7
PUX13810	34.9	31.8	34.9	25.4	-	84.6
PUX15810	41.3	38.1	41.3	31.8	-	92.7
PUX21810	54.0	50.8	54.0	-	-	105.7
PUX23810	60.3	57.2	60.3	50.8	-	99.6
PUX25810	66.7	63.5	66.7	-	-	123.7
PUX31810	79.4	76.2	79.4	-	-	130.6
PUX35810	92.1	88.9	92.1	-	-	164.6
PUX41810	104.8	101.6	104.8	88.9	-	164.6

J1205 THRU J1280, J1205 N THRU J1280 N (PLASTIC COATED)

"J" CONDUIT & PIPE HANGER EGG





Part No.	Wt/100 pcs Lbs (kg)	Part No.	Wt/100 pcs Lbs (kg)	Pipe Size In	"A" In (mm)	"B" In (mm)	"C" In (mm)	"D" In (mm)	"E" In (mm)	"F" In (mm)	Load Lbs (kN)
J1205	20 9.1	J1205N	21 9.5	1/2	3/8	2 5/8	1	2	1 3/32	1/4 x 2 1/4	400
J1207	21 9.5	J1207N	22 10.0	3/4	3/8	2 7/8	1	2 1/4	1 3/32	1/4 x 2 1/4	400
J1210	24 10.9	J1210N*	25 11.3	1	3/8	3	1	2 3/8	1 3/32	1/4 x 2 1/2	400
J1212	27 12.2	J1212N	29 13.2	1 1/4	3/8	3 1/4	1	2 1/2	1 3/32	1/4 x 2 3/4	400
J1215	29 13.2	J1215N*	31 14.1	1 1/2	3/8	3 1/2	1	2 5/8	1 3/32	1/4 x 3	400
J1220	33 15.0	J1220N*	35 15.9	2	3/8	3 3/4	1 1/8	2 5/8	1 3/32	1/4 x 3 1/2	400
J1225	71 32.2	J1225N	74 33.6	2 1/2	1/2	4 3/8	1 1/8	3 5/8	9/16	3/8 x 4 1/2	800
J1230	78 35.4	J1230N*	81 36.7	3	1/2	4 7/8	1 1/8	4	9/16	3/8 x 5	800
J1235	85 38.6	J1235N	88 39.9	3 1/2	1/2	5 1/8	1 1/8	4 1/4	9/16	3/8 x 6	800
J1240	178 80.7	J1240N*	182 82.6	4	5/8	6 1/8	1 1/8	5 1/8	9/16	3/8 x 6	800
J1250	199 90.3	J1250N	203 92.1	5	5/8	6 3/4	1 1/8	5 3/4	9/16	3/8 x 7 1/2	800
J1260	231 104.8	J1260N*	236 107.0	6	3/4	7 3/4	1 1/4	6 1/2	9/16	3/8 x 8 1/2	1,000
J1280	449 203.7	J1280N	458 207.7	8	7/8	9 1/4	1 1/4	8	9/16	3/8 x 10	1,200

*Standard glass drainline and glass process pipe sizes. Minimum safety factor of five (5) on ultimate load.

P2474

PIPE ROLLER FOR 1/2" - 4" PIPE EGG GR



Sold in pairs.

Requires 2 each 1/2" x 15/16" bolts and 1/2" channel nuts per assembly. Sold separately.

Design Load
500 Lbs (2.22kN)

Wt/100 pcs: 268 Lbs (121.6 kg)


Chart for Dimension A

Pipe Size In	No Insulation In (mm)	Insulation Thickness					
		1" In (mm)	1 1/2" In (mm)	2" In (mm)	2 1/2" In (mm)	3" In (mm)	4" In (mm)
1/2	6 1/2	6 1/2	-	-	-	-	-
	165.1	165.1	-	-	-	-	-
3/4	6 1/2	6 1/2	6 1/8	6 1/8	-	-	-
	165.1	165.1	168.3	174.6	-	-	-
1	6 1/2	6 1/2	6 1/8	6 1/8	-	-	-
	165.1	165.1	168.3	174.6	-	-	-
1 1/4	6 1/2	6 1/2	6 1/8	7 1/8	7 1/8	-	-
	165.1	165.1	174.6	181.0	187.3	-	-
1 1/2	6 1/2	6 1/2	6 1/8	7 1/8	7 1/8	-	-
	165.1	165.1	174.6	181.0	187.3	-	-
2	6 1/2	6 1/8	7 1/8	7 1/8	7 1/2	8	-
	165.1	168.3	181.0	187.3	190.5	203.2	-
2 1/2	6 1/2	6 1/8	7 1/8	7 1/8	7 1/2	8	-
	165.1	168.3	181.0	187.3	190.5	203.2	-
3	6 1/2	7	7 1/8	7 1/4	7 1/8	8 1/8	-
	165.1	177.8	190.5	196.9	200.0	206.4	-
3 1/2	6 1/2	7	7 1/8	7 1/4	7 1/8	8 1/8	-
	165.1	177.8	190.5	196.9	200.0	206.4	-
4	6 1/2	7 1/4	7 1/8	7 1/4	8	8 1/8	9
	168.3	184.2	193.7	200.0	203.2	212.7	228.6



P2474-1 THRU P2474-4

PIPE ROLLER FOR 1" - 8" PIPE EG GR



Parts are shipped loose and are easily assembled during installation.

Design Load
750 Lbs (3.34 kN)


Part Number	A In (mm)	Wt/100 pcs Lbs (kg)
P2474-1	6 1/4	299
	171.5	135.6
P2474-2	7 1/2	304
	190.5	137.9
P2474-3	8 1/2	311
	215.9	141.1
P2474-4	9 1/16	319
	242.9	144.7

Chart for Roller Part Number Selection

Pipe Size In	No Insulation	Insulation Thickness					
		1" (25.4)	1 1/2" (38.1)	2" (50.8)	2 1/2" (63.5)	3" (76.2)	4" (101.6)
1/2	P2474-1	P2474-1	P2474-1	P2474-2	-	-	-
3/4	P2474-1	P2474-1	P2474-1	P2474-2	-	-	-
1	P2474-1	P2474-1	P2474-1	P2474-2	-	-	-
1 1/4	P2474-1	P2474-1	P2474-1	P2474-2	-	-	-
1 1/2	P2474-1	P2474-1	P2474-2	P2474-2	P2474-2	-	-
2	P2474-1	P2474-1	P2474-2	P2474-2	P2474-2	-	-
2 1/2	P2474-1	P2474-1	P2474-2	P2474-2	P2474-2	-	-
3	P2474-1	P2474-2	P2474-2	P2474-3	P2474-3	P2474-3	-
3 1/2	P2474-1	P2474-2	P2474-2	P2474-3	P2474-3	P2474-3	-
4	P2474-1	P2474-2	P2474-2	P2474-3	P2474-3	P2474-3	-
5	P2474-2	P2474-3	P2474-3	P2474-3	P2474-3	P2474-4	P2474-4
6	P2474-2	P2474-3	P2474-3	P2474-3	P2474-3	P2474-4	P2474-4
8	P2474-2	P2474-3	P2474-4	P2474-4	P2474-4	P2474-4	P2474-4

- Pipe roller will fit standard saddles.
- Select proper roller from chart.
- Requires 2 each 1/2" x 15/16" bolts and 1/2" channel nuts per assembly. Sold separately.


Sold in pairs.



Material: Cast iron rollers.

- Requires 2 each 1/2" x 15/16" bolts and 1/2" channel nuts per assembly.
- Sold separately.

Design Load
1500 Lbs (6.67 kN)



Wt/100 pcs: 680 Lbs (308.4 kg)


Chart for Dimension A

Pipe Size In	No Insulation In (mm)	Insulation Thickness					
		1" In (mm)	1 1/2" In (mm)	2" In (mm)	2 1/2" In (mm)	3" In (mm)	4" In (mm)
6	9 1/2 241.3	10 1/4 260.4	10 1/2 266.7	10 1/4 273	11 279.4	11 1/8 288.9	11 1/8 301.6
8	10 1/2 257.2	*	11	11 1/8 279.4	11 1/4 288.9	12 298.5	12 1/2 304.8
10	10 1/4 273.1	*	11 1/8 295.3	12 304.8	12 1/4 311.2	12 1/2 317.5	13 330.2
12	11 1/4 285.8	*	12 1/8 308.0	12 1/2 317.5	12 3/4 323.9	13 330.2	13 1/2 342.9
14	11 1/2 295.3	*	12 1/2 317.5	12 7/8 327.0	13 330.2	13 3/8 339.7	14 355.6
16	12 1/2 308.0	*	13	13 1/8 339.7	13 7/8 352.4	14 355.6	14 1/2 368.3

(*Not used for this size)

Standard Dimensions for 1" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 5/16" (14.3mm); Hole Spacing - From End: 13/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (47.6mm); Width: 1 5/8" (41.3mm); Thickness: 1/4" (6.4mm)

P2476

Design Load
2000 Lbs (8.90 kN)

Material: Cast iron rollers.

- Requires 4 each $\frac{1}{2}'' \times \frac{15}{16}''$ bolts and $\frac{1}{2}''$ channel nuts per assembly. Sold separately.






Chart for Dimension A

Pipe Size	Insulation Thickness				
	1 1/2" In	2" In (mm)	2 1/2" In (mm)	3" In (mm)	4" In (mm)
16	-	-	-	13 5/8	14
	-	-	-	352.4	355.6
18	13 5/8	14	14 1/8	14 1/2	15
	346.1	355.6	358.8	368.3	381.0
20	14 1/8	14 1/2	14 1/4	15	15 1/2
	358.8	368.3	374.7	381.0	393.7
24	15 1/4	15 1/2	15 1/8	16 1/8	16 1/2
	387.4	393.7	403.2	409.6	422.3


Wt/100 pcs: 1046 Lbs (474.5 kg)

P2481**PIPE SUPPORT BRACKET**

For $\frac{1}{2}''$ pipe to $1\frac{1}{2}''$ pipe.

P2482**PIPE SUPPORT BRACKET**

For 2" pipe to 3" pipe.

P2243**PIPE BLOCK**

For 2" (50.8) to 8" (203.2) Pipes

Design Load (Upright Channel)			
Wt/100 pcs	P1000 Lbs (kg)	P1100 Lbs (kN)	P2000 Lbs (kN)
90	85	85	85
40.8	0.38	0.38	0.38

Design Load (Upright Channel)			
Wt/100 pcs	P1000 Lbs (kg)	P1100 Lbs (kN)	P2000 Lbs (kN)
139	185	120	95
63.0	0.82	0.53	0.42

Wt/100 pcs: 40 Lbs (18.1 kg)

Standard Dimensions for 1 1/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: $\frac{9}{16}''$ (14.3mm); Hole Spacing - From End: $\frac{13}{16}''$ (20.6mm); Hole Spacing - On Center: $1\frac{1}{8}''$ (47.6mm); Width: 1 1/8" (41.3mm); Thickness: $\frac{1}{4}''$ (6.4mm)



Centerline to Centerline (In/mm)																			
Nominal Pipe Dia.		¾" (19.1mm)			1" (25.4mm)			1¼" (31.8mm)			1½" (38.1mm)			2" (50.8mm)			2½" (63.5mm)		
		T	S	T	F	S	T	F	S	T	F	S	T	F	S	T	F	S	
19.1mm	¾"	T	4¾	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
		120.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
	S	4½	4¾	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
25.4mm	1"	114.3	120.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
		5	4¾	5¼	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
	F	127.0	120.7	133.4	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
		152.4	146.1	158.8	184.2	—	—	—	—	—	—	—	—	—	—	—	—	—	
	S	4¾	4½	5	6	4½	—	—	—	—	—	—	—	—	—	—	—	—	
31.8mm	1¼"	120.7	114.3	127.0	152.4	114.3	—	—	—	—	—	—	—	—	—	—	—	—	
		133.4	127.0	139.7	165.1	127.0	139.7	—	—	—	—	—	—	—	—	—	—	—	
	F	6½	6	6½	7½	6½	6¾	7¾	—	—	—	—	—	—	—	—	—	—	
		158.8	152.4	165.1	190.5	158.8	171.5	196.9	—	—	—	—	—	—	—	—	—	—	
	S	4¾	4½	5	6	4½	5¼	6¼	4¾	—	—	—	—	—	—	—	—	—	
38.1mm	1½"	120.7	114.3	127.0	152.4	114.3	133.4	158.8	120.7	—	—	—	—	—	—	—	—	—	
		133.4	127.0	139.7	165.1	133.4	146.1	171.5	133.4	146.1	—	—	—	—	—	—	—	—	
	F	6½	6¼	6¾	7¾	6½	6¾	8	6½	7	8	—	—	—	—	—	—	—	
		165.1	158.8	171.5	196.9	158.8	171.5	203.2	165.1	177.8	203.2	—	—	—	—	—	—	—	
	S	5	4¾	5¼	6½	4¾	5¼	6	5	5½	6½	5	—	—	—	—	—	—	
50.8mm	2"	127.0	114.3	133.4	158.8	120.7	133.4	152.4	127.0	139.7	165.1	127.0	—	—	—	—	—	—	
		146.1	139.7	152.4	177.8	139.7	152.4	184.2	146.1	158.8	184.2	146.1	165.1	—	—	—	—	—	
	F	7	6¾	7½	8½	6¾	7½	8½	7	7½	8½	7	7½	9	—	—	—	—	
		177.8	171.5	184.2	209.6	171.5	184.2	215.9	177.8	190.5	215.9	177.8	196.9	228.6	—	—	—	—	
	S	5½	5	5½	6½	5	5½	6¾	5¼	5½	6½	5¼	6	7½	5½	—	—	—	
63.5mm	2½"	133.4	127.0	139.7	165.1	127.0	139.7	171.5	133.4	146.1	171.5	133.4	152.4	184.2	—	—	—	—	
		152.4	146.1	158.8	184.2	152.4	165.1	190.5	152.4	165.1	196.9	158.8	177.8	209.6	165.1	184.2	—	—	
	F	7½	7¼	7¾	8¾	7¼	7¾	9	7½	8	9	7½	8½	9½	7¾	8¾	10	—	
		190.5	184.2	196.9	222.3	184.2	196.9	228.6	190.5	203.2	228.6	190.5	209.6	241.3	196.9	222.3	254.0	—	
	S	5½	5¼	5¾	6¾	5¼	5¾	7	5½	6	7	5½	6½	7½	5¾	6¾	8	6	
76.2mm	3"	139.7	133.4	146.1	171.5	133.4	146.1	177.8	139.7	152.4	177.8	139.7	158.8	190.5	146.1	171.5	203.2	152.4	
		158.8	152.4	165.1	190.5	158.8	171.5	196.9	158.8	171.5	203.2	165.1	184.2	215.9	171.5	190.5	228.6	177.8	
	F	7¾	7½	8	9	7½	8	9¼	7¾	8½	9¼	7¾	8½	9¾	8	9	10½	8½	
		196.9	190.5	203.2	228.6	190.5	203.2	235.0	196.9	209.6	235.0	196.9	215.9	247.7	203.2	228.6	260.4	209.6	
	S	5¾	5½	6	7	5½	6	7½	5¾	6½	7½	5¾	6½	7½	5¾	6½	8	6½	
101.6mm	4"	171.5	165.1	177.8	203.2	165.1	177.8	209.6	171.5	184.2	209.6	171.5	190.5	222.3	184.2	203.2	254.0	203.2	
		190.5	184.2	196.9	222.3	184.2	196.9	228.6	190.5	203.2	228.6	190.5	209.6	241.3	196.9	222.3	254.0	203.2	
	F	9	8¾	9¼	10½	8¾	9¼	10½	9	9½	10½	9	9½	11	9¼	10½	11½	9½	
		228.6	222.3	235.0	260.4	222.3	235.0	266.7	228.6	241.3	266.7	228.6	247.7	279.4	235.0	260.4	292.1	241.3	
	S	6¾	6½	7	8	6½	7	8½	6¾	7½	8½	6¾	7½	8½	7	8	9½	7½	
127.0mm	5"	171.5	165.1	177.8	203.2	165.1	177.8	209.6	171.5	184.2	209.6	171.5	190.5	222.3	184.2	203.2	254.0	203.2	
		203.2	196.9	209.6	235.0	196.9	209.6	241.3	203.2	215.9	241.3	203.2	222.3	254.0	209.6	235.0	266.7	215.9	
	F	9½	9¼	9¾	10½	9¼	9¾	11	9½	10	11	9½	10½	11½	9¾	10¾	12	10	
		241.3	235.0	247.7	273.1	235.0	247.7	279.4	241.3	254.0	279.4	241.3	260.4	292.1	247.7	273.1	304.8	254.0	
	S	7½	7	7½	8½	7	7½	8¾	7½	7½	8½	7½	8½	9½	7½	8½	9½	7½	
152.4mm	6"	184.2	177.8	190.5	209.6	177.8	190.5	209.6	177.8	190.5	222.3	184.2	203.2	235.0	190.5	215.9	247.7	196.9	
		222.3	215.9	228.6	254.0	215.9	228.6	260.4	222.3	235.0	260.4	222.3	241.3	273.1	228.6	254.0	285.8	235.0	
	F	10	9¾	10½	11½	9¾	10½	11½	10	10½	11½	10	10½	12	10½	11½	12½	10½	
		254.0	247.7	260.4	285.8	247.7	260.4	292.1	254.0	266.7	292.1	254.0	273.1	304.8	260.4	285.8	317.5	266.7	
	S	7¾	7½	8	9	7½	8	9¼	7¾	8½	9¼	7¾	8½	9½	8	9	10½	8½	
203.2mm	8"	171.5	165.1	177.8	203.2	165.1	177.8	209.6	171.5	184.2	209.6	171.5	190.5	228.6	184.2	203.2	254.0	203.2	
		222.3	214.3	234.0	279.4	214.3	234.0	266.7	222.3	247.7	266.7	222.3	254.0	273.1	228.6	254.0	285.8	235.0	
	F	11½	11	11½	12½	11	11½	12½	11½	11½	12½	11½	12	13½	11½	12½	13½	11½	
		285.8	279.4	292.1	317.5	279.4	292.1	323.9	285.8	298.5	323.9	285.8	304.8	336.6	292.1	317.5	349.3	298.5	
	S	11½	11	11½	12½	11	11½	12½	11½	11½	12½	11½	12	13½	11½	12½	13½	11½	
254.0mm	10"	285.8	279.4	292.1	317.5	279.4	292.1	323.9	285.8	298.5	323.9	285.8	304.8	336.6	292.1	317.5	349.3	298.5	
		317.5	311.2	323.9	349.3	311.2	323.9	355.6	317.5	330.2	355.6	317.5	336.6	368.3	323.9	349.3	381.0	330.2	
	F	12½	12¼	12¾	13¼	12¼	12½	14	12½	13½	14½	12½	13	14½	12½	13½	15	13	
		317.5	311.2	323.9	349.3	311.2	323.9	355.6	317.5	330.2	355.6	317.5	336.6	368.3	323.9	349.3	381.0	330.2	
	S	12½	12	12½	13½	12	12½	13½	12½	12½	13½	12½	13	14½	12½	13½	14½	12½	
304.8mm	12"	311.2	304.8	317.5	342.9	304.8	317.5	349.3	311.2	323.9	349.3	311.2	330.2	362.0	317.5	342.9	374.7	323.9	
		355.6	349.3	362.0	387.4	349.3	362.0	393.7	355.6	368.3	393.7	355.6	374.7	406.4	362.0	387.4	419.1	368.3	

PIPE SPACING TABLE

This chart, developed by Julius Getlan of Seelye Stevenson Value & Knect, consulting engineers, New York City, enables one to quickly determine the centerline-to-centerline dimension between any two size pipes on a rack.

Select the smaller pipe size at top and select the other at the side of the table. Where the appropriate columns intersect, the dimension is given.

These factors are included in the dimensions given:

- O.D. of flanges and fittings.
- 1" insulation over flanges and fittings.
- All fractional dimensions less than $\frac{1}{4}$ " were increased to the next larger $\frac{1}{4}$ ".
- Clear space between fittings as follows:
 1. 1" between piping 3" and smaller.
 2. $\frac{1}{2}$ " between a pipe 3" and smaller and a pipe 4" or larger.
 3. 2" between piping 4" and larger.

T – denotes threaded IPS pipe. F – denotes flanged fittings on pipe. S – denotes soldered or brazed tubing.

3" (76.2mm)			4" (101.6mm)			5" (127.0mm)			6" (152.4mm)			8" (203.2mm)			10" (254.0mm)			12" (304.8mm)			Nominal Pipe Dia.
T	F	S	T	F	S	T	F	S	T	F	S	T	F	S	T	F	S	T	F	F	
7½	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	T	3" 76.2mm
196.9	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
9¼	10½	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
235.0	266.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
7½	8½	6½	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
184.2	215.9	165.1	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
9	10¼	8¼	10	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
228.6	260.4	209.6	254.0	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
10½	11¾	9¾	11½	13	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
266.7	298.5	247.7	292.1	330.2	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
8½	9½	7½	9¼	10¾	8½	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	S
209.6	241.3	190.5	235.0	273.1	215.9	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
9½	10¾	8¾	10¼	12	9¾	11	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
241.3	273.1	222.3	260.4	304.8	247.7	279.4	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
11	12¼	10¼	12	13½	11½	12½	14	—	—	—	—	—	—	—	—	—	—	—	—	—	
279.4	311.2	260.4	304.8	342.9	285.8	317.5	355.6	—	—	—	—	—	—	—	—	—	—	—	—		
8¾	10	8	9¾	11¼	9	10¼	11¾	9½	—	—	—	—	—	—	—	—	—	—	—	—	
222.3	254.0	203.2	247.7	285.8	228.6	260.4	298.5	241.3	—	—	—	—	—	—	—	—	—	—	—		
10¼	11½	9½	11½	12¾	10½	11¾	13¼	11	12½	—	—	—	—	—	—	—	—	—	—	T	5" 127.0mm
260.4	292.1	241.3	285.8	323.9	266.7	298.5	336.6	279.4	317.5	—	—	—	—	—	—	—	—	—	—		
11½	12½	10¾	12½	14	11¾	13	14½	12½	13¼	15	—	—	—	—	—	—	—	—	—	F	
292.1	311.2	273.1	317.5	355.6	298.5	330.2	368.3	311.2	336.6	381.0	—	—	—	—	—	—	—	—	—		
9½	10½	8½	10¼	11¾	9½	10¾	12¼	10	11½	12¾	10½	—	—	—	—	—	—	—	—	S	
235.0	266.7	215.9	260.4	298.5	241.3	273.1	311.2	254.0	292.1	323.9	266.7	—	—	—	—	—	—	—	—		
11½	12½	10¾	12½	14	11¾	13	14½	12½	13¼	15	—	—	—	—	—	—	—	—	—	F	
285.8	323.9	273.1	317.5	355.6	298.5	330.2	368.3	311.2	349.3	381.0	323.9	374.7	—	—	—	—	—	—	—	T	8" 203.2mm
12½	14	12	13¾	15¼	13	14¼	15¾	13½	15	16½	14	16½	17.5	—	—	—	—	—	—	F	
323.9	355.6	304.8	349.3	387.4	330.2	362.0	400.1	342.9	381.0	412.8	355.6	412.8	17.5	—	—	—	—	—	—		
12½	14	12	13¾	15¼	13	14¼	15¾	13½	15	16½	14	16½	17½	—	—	—	—	—	—	T	10" 254.0mm
323.9	355.6	304.8	349.3	387.4	330.2	362.0	400.1	342.9	381.0	412.8	355.6	412.8	444.5	—	—	—	—	—	—	F	
14	15¼	13¼	15	16½	14¼	15½	17	14¾	16½	17½	15¼	17½	18¾	—	—	—	—	—	—	F	
355.6	387.4	336.6	381.0	419.1	362.0	393.7	431.8	374.7	412.8	444.5	387.4	444.5	476.3	476.3	508.0	—	—	—	—		
13¾	15	13	14¾	16¼	14	15¼	16¾	14½	16	17½	15	17½	18½	18½	20	—	—	—	—	T	12" 304.8mm
349.3	381.0	330.2	374.7	412.8	355.6	387.4	425.5	368.3	406.4	438.2	381.0	438.2	469.9	469.9	501.7	495.3	—	—	—	T	
15½	16¾	14¾	16½	18	15¾	17	18½	16¼	17¾	19	16¾	14	20½	20½	21½	21½	29	—	—	F	
393.7	425.5	374.7	419.1	457.2	400.1	431.8	463.6	412.8	450.9	482.6	425.5	455.6	514.4	514.4	546.1	539.8	736.6	—	—	F	



CHANNEL SELECTION FOR SCHEDULE 10 SPRINKLER PIPE TRAPEZE HANGERS

Note: Based on NFPA-13-2013-Table 9.1.1.7.1(a). Each of the following tables indicate the allowable span of the trapezeeze and the nominal pipe size for the specified channel. An entry of "N/A" indicates that the channel cannot be used for this span/pipe size combination. The table is based on a maximum allowable bending stress of 15 KSI and a midspan concentrated load from 15 ft of water-filled pipe, plus 250 lb.

Unistrut Channel	Section Modulus in ³ (cm ³)
P3000	0.154 2.52
P1000	0.202 3.31
P5500	0.391 6.41
P5000	0.628 10.29

Unistrut Channel	Section Modulus in ³ (cm ³)
P3001	0.431 7.06
P1001	0.572 9.37
P5501	1.153 18.89
P5001	1.916 31.40

Nominal Pipe Dia. (in)	Schedule 10 Pipe				
	O.D. (in)	Wall Thickness (in)	I. D. (in)	Pipe Weight (p/f)	Water Weight (p/f)
1	1.315	0.109	1.097	1.41	0.42
1¼	1.660	0.109	1.442	1.81	0.73
1½	1.900	0.109	1.682	2.09	0.99
2	2.375	0.109	2.157	2.64	1.63
2½	2.875	0.120	2.635	3.53	2.44
3	3.500	0.120	3.260	4.34	3.73
3½	4.000	0.120	3.760	4.98	4.97
4	4.500	0.120	4.260	5.62	6.38
5	5.563	0.134	5.295	7.78	9.85
6	6.625	0.134	6.357	9.30	14.20
8	8.625	0.188	8.249	16.96	23.91
10	10.750	0.188	10.374	21.23	37.82
					59.04

Trapeze Span	NFPA 13 Required Trapeze Section Modulus for Sch 10 Pipe										
	Pipe Diameter										
1"	1¼"	1½"	2"	2½"	3"	3½"	4"	5"	6"	8"	10"
1' - 6"	0.08	0.08	0.09	0.09	0.10	0.11	0.12	0.13	0.15	0.18	0.26
2' - 0"	0.11	0.11	0.12	0.13	0.14	0.15	0.16	0.17	0.2	0.24	0.34
2' - 6"	0.14	0.14	0.15	0.16	0.18	0.21	0.23	0.25	0.3	0.36	0.5
3' - 0"	0.16	0.17	0.18	0.19	0.2	0.22	0.24	0.26	0.31	0.36	0.51
4' - 0"	0.22	0.22	0.24	0.25	0.27	0.30	0.32	0.34	0.41	0.48	0.68
5' - 0"	0.27	0.28	0.3	0.31	0.34	0.37	0.40	0.43	0.51	0.60	0.85
6' - 0"	0.33	0.34	0.35	0.38	0.41	0.44	0.48	0.51	0.61	0.71	1.02
7' - 0"	0.38	0.39	0.41	0.44	0.47	0.52	0.56	0.6	0.71	0.83	1.19
8' - 0"	0.43	0.45	0.47	0.5	0.54	0.59	0.63	0.68	0.82	0.95	1.36
9' - 0"	0.49	0.50	0.53	0.56	0.61	0.66	0.71	0.77	0.92	1.07	1.53
10' - 0"	0.54	0.56	0.59	0.63	0.68	0.74	0.79	0.85	1.02	1.19	1.7

Values taken from NFPA 13 (2013 Edition), Table 9.1.1.7.1(a)

Trapeze Span	Single Channel Trapeze for Sch 10 Pipe										
	Pipe Diameter										
1"	1¼"	1½"	2"	2½"	3"	3½"	4"	5"	6"	8"	10"
1' - 6"	P3000	P3000	P3000	P3000	P3000	P3000	P3000	P3000	P3000	P1000	P5500
2' - 0"	P3000	P3000	P3000	P3000	P3000	P1000	P1000	P1000	P5500	P5500	P5000
2' - 6"	P3000	P3000	P3000	P1000	P1000	P5500	P5500	P5500	P5500	P5000	N/A
3' - 0"	P1000	P1000	P1000	P1000	P5500	P5500	P5500	P5500	P5500	P5000	N/A
4' - 0"	P5500	P5500	P5500	P5500	P5500	P5500	P5500	P5000	P5000	N/A	N/A
5' - 0"	P5500	P5500	P5500	P5500	P5500	P5000	P5000	P5000	P5000	N/A	N/A
6' - 0"	P5500	P5500	P5500	P5000	P5000	P5000	P5000	P5000	P5000	N/A	N/A
7' - 0"	P5500	P5500	P5000	P5000	P5000	P5000	P5000	N/A	N/A	N/A	N/A
8' - 0"	P5000	P5000	P5000	P5000	P5000	P5000	N/A	N/A	N/A	N/A	N/A
9' - 0"	P5000	P5000	P5000	P5000	N/A						
10' - 0"	P5000	P5000	P5000	N/A							

Trapeze Span	Double Channel Trapeze for Sch 10 Pipe										
	Pipe Diameter										
1"	1¼"	1½"	2"	2½"	3"	3½"	4"	5"	6"	8"	10"
1' - 6"	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001
2' - 0"	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001
2' - 6"	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P1001	P5501
3' - 0"	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P1001	P5501
4' - 0"	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P1001	P5501
5' - 0"	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P1001	P5501	P5501
6' - 0"	P3001	P3001	P3001	P3001	P3001	P1001	P1001	P1001	P5501	P5501	P5001
7' - 0"	P3001	P3001	P3001	P1001	P1001	P1001	P1001	P5501	P5501	P5001	P5001
8' - 0"	P3001	P1001	P1001	P1001	P5501	P5501	P5501	P5501	P5501	P5001	P5001
9' - 0"	P1001	P1001	P1001	P1001	P5501	P5501	P5501	P5501	P5501	P5001	N/A
10' - 0"	P1001	P1001	P5501	P5001	N/A						

CHANNEL SELECTION FOR SCHEDULE 40 SPRINKLER PIPE TRAPEZE HANGERS

Note: Based on NFPA-13-2013-Table 9.1.1.7.1(a). Each of the following tables indicate the allowable span of the trapezee and the nominal pipe size for the specified channel. An entry of "N/A" indicates that the channel cannot be used for this span/pipe size combination. The table is based on a maximum allowable bending stress of 15 KSI and a midspan concentrated load from 15 ft of water-filled pipe, plus 250 lb.

Unistrut Channel	Section Modulus in ³ (cm ³)
P3000	0.154 2.52
P1000	0.202 3.31
P5500	0.391 6.41
P5000	0.628 10.29

Unistrut Channel	Section Modulus in ³ (cm ³)
P3001	0.431 7.06
P1001	0.572 9.37
P5501	1.153 18.89
P5001	1.916 31.40

Nominal Pipe Dia. (in)	O.D. (in)	Wall Thickness (in)	Schedule 40 Pipe			Total Weight (p/f)
			I. D. (in)	Pipe Weight (p/f)	Water Weight (p/f)	
1	1.315	0.133	1.049	1.68	0.39	2.07
1 1/4	1.660	0.140	1.380	2.27	0.67	2.94
1 1/2	1.900	0.145	1.610	2.72	0.91	3.63
2	2.375	0.154	2.067	3.66	1.50	5.16
2 1/2	2.875	0.203	2.469	5.80	2.14	7.94
3	3.500	0.216	3.068	7.58	3.31	10.89
3 1/2	4.000	0.226	3.548	9.12	4.42	13.54
4	4.500	0.237	4.026	10.80	5.70	16.50
5	5.563	0.258	5.047	14.63	8.95	23.58
6	6.625	0.280	6.065	18.99	12.93	31.92
8	8.625	0.322	7.981	28.58	22.38	50.96
10	10.750	0.365	10.020	40.52	35.28	75.80

Trapeze Span	NFPA 13 Required Trapeze Section Modulus for Sch 40 Pipe											
	Pipe Diameter											
1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	5"	6"	8"	10"	
1' - 6"	0.08	0.09	0.09	0.1	0.11	0.12	0.14	0.15	0.18	0.22	0.3	0.41
2' - 0"	0.11	0.11	0.12	0.13	0.15	0.16	0.18	0.2	0.24	0.29	0.4	0.55
2' - 6"	0.14	0.14	0.15	0.16	0.17	0.18	0.2	0.21	0.25	0.3	0.43	0.56
3' - 0"	0.16	0.17	0.18	0.2	0.22	0.25	0.27	0.3	0.36	0.43	0.6	0.82
4' - 0"	0.22	0.23	0.24	0.26	0.29	0.33	0.36	0.4	0.48	0.58	0.8	1.1
5' - 0"	0.27	0.29	0.3	0.33	0.37	0.41	0.45	0.49	0.6	0.72	1	1.37
6' - 0"	0.33	0.34	0.36	0.39	0.44	0.49	0.54	0.59	0.72	0.87	1.2	1.64
7' - 0"	0.38	0.4	0.43	0.46	0.52	0.58	0.63	0.69	0.84	1.01	1.41	1.92
8' - 0"	0.44	0.46	0.49	0.52	0.59	0.66	0.72	0.79	0.96	1.16	1.61	2.19
9' - 0"	0.49	0.51	0.55	0.59	0.66	0.74	0.81	0.89	1.08	1.3	1.81	2.47
10' - 0"	0.55	0.57	0.61	0.65	0.74	0.82	0.9	0.99	1.2	1.45	2.01	2.74

Values taken from NFPA 13 (2013 Edition), Table 9.1.1.7.1(a)

Trapeze Span	Single Channel Trapeze for Sch 40 Pipe										
	Pipe Diameter										
1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	5"	6"	8"	10"
1' - 6"	P3000	P3000	P3000	P3000	P3000	P3000	P3000	P1000	P5500	P5500	P5000
2' - 0"	P3000	P3000	P3000	P3000	P3000	P1000	P1000	P5500	P5500	P5000	P5000
2' - 6"	P3000	P3000	P3000	P1000	P1000	P1000	P1000	P5500	P5500	P5000	P5000
3' - 0"	P1000	P1000	P1000	P5500	P5500	P5500	P5500	P5000	P5000	P5000	N/A
4' - 0"	P5500	P5500	P5500	P5500	P5500	P5000	P5000	P5000	P5000	N/A	N/A
5' - 0"	P5500	P5500	P5500	P5500	P5000	P5000	P5000	P5000	N/A	N/A	N/A
6' - 0"	P5500	P5500	P5500	P5000	P5000	P5000	P5000	N/A	N/A	N/A	N/A
7' - 0"	P5500	P5000	P5000	P5000	P5000	P5000	N/A	N/A	N/A	N/A	N/A
8' - 0"	P5000	P5000	P5000	P5000	N/A	N/A	N/A	N/A	N/A	N/A	N/A
9' - 0"	P5000	P5000	P5000	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
10' - 0"	P5000	P5000	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Trapeze Span	Double Channel Trapeze for Sch 40 Pipe										
	Pipe Diameter										
1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	5"	6"	8"	10"
1' - 6"	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001
2' - 0"	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P1001
2' - 6"	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P1001
3' - 0"	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P5501
4' - 0"	P3001	P3001	P3001	P3001	P3001	P3001	P3001	P1001	P5501	P5501	P5501
5' - 0"	P3001	P3001	P3001	P3001	P3001	P3001	P1001	P1001	P5501	P5501	P5001
6' - 0"	P3001	P3001	P3001	P3001	P1001	P1001	P1001	P5501	P5501	P5501	P5001
7' - 0"	P3001	P3001	P3001	P1001	P1001	P5501	P5501	P5501	P5501	P5501	P5001
8' - 0"	P1001	P1001	P1001	P1001	P5501	P5501	P5501	P5501	P5501	P5001	N/A
9' - 0"	P1001	P1001	P1001	P5501	P5501	P5501	P5501	P5501	P5501	P5001	N/A
10' - 0"	P1001	P1001	P5501	P5501	P5501	P5501	P5501	P5501	P5001	P5001	N/A



ELECTRICAL METALLIC TUBING (EMT) - THIN WALL

Tubing Size (Nominal) In	Outside Diameter In (mm)	Inside Diameter In (mm)	Weight Of Tubing Lbs/Ft (kg/m)
3/8	0.577	0.497	0.23
	14.7	12.6	0.34
1/2	0.706	0.626	0.29
	17.9	15.9	0.43
5/8	0.922	0.830	0.44
	23.4	21.1	0.65
1	1.163	1.055	0.64
	29.5	26.8	0.95
1 1/4	1.510	1.388	0.95
	38.4	35.3	1.41
1 1/2	1.740	1.618	1.10
	44.2	41.1	1.64
2	2.197	2.075	1.40
	55.8	52.7	2.08
2 1/2	2.875	2.731	2.30
	73.0	69.4	3.42
3	3.500	3.356	2.70
	88.9	85.2	4.02
3 1/2	4.000	3.834	3.40
	101.6	97.4	5.06
4	4.500	4.334	4.00
	114.3	110.1	5.95

INTERMEDIATE METALLIC CONDUIT (IMC)

Conduit Size (Nominal) In	Outside Diameter In (mm)	Inside Diameter In (mm)	Weight Of Conduit Lbs/Ft (kg/m)	Weight of Conduit and Conductor Lbs/Ft (kg/m)
1/2	0.815	0.745	0.60	0.12
	20.7	18.9	0.89	0.18
5/8	1.029	0.954	0.82	1.13
	26.1	24.2	1.22	1.68
1	1.290	1.205	1.16	1.82
	32.8	30.6	1.73	2.71
1 1/4	1.638	1.553	1.50	2.67
	41.6	39.4	2.23	3.97
1 1/2	1.883	1.793	1.82	3.42
	47.8	45.5	2.71	5.09
2	2.360	2.266	2.42	5.04
	59.9	57.6	3.60	7.50
2 1/2	2.857	2.727	4.01	7.75
	72.6	69.3	5.97	11.53
3	3.476	3.346	4.43	10.69
	88.3	85.0	6.59	15.91
3 1/2	3.971	3.841	5.73	13.46
	100.9	97.6	8.53	20.03
4	4.466	4.336	6.38	16.37
	113.4	110.1	9.49	24.36

COPPER TUBE (TYPE L)

Nom. Tube Size	O.D. Tubing In (mm)	O.D. In (mm)	Wall Thick. In (mm)	Weight Lbs/Ft (kg/m)	Weight Water Lbs/Ft (kg/m)
1/4"	0.375	0.30	0.126	0.124	0.034
	9.5	9.5	0.19	0.05	
3/8"	0.500	0.35	0.198	0.062	
	12.7	12.7	0.29	0.09	
1/2"	0.625	0.40	0.285	0.100	
	15.9	15.9	0.42	0.15	
5/8"	0.750	0.42	0.362	0.151	
	19.1	19.1	0.54	0.22	
3/4"	0.875	0.45	0.455	0.209	
	22.2	22.2	0.68	0.31	
1"	1.125	0.50	0.655	0.357	
	28.6	28.6	0.97	0.53	
1 1/4"	1.375	0.55	0.884	0.546	
	34.9	34.9	1.32	0.81	
1 1/2"	1.625	0.60	1.140	0.767	
	41.3	41.3	1.70	1.14	
2"	2.125	0.70	1.750	1.341	
	54.0	54.0	2.60	2.00	
2 1/2"	2.625	0.80	2.480	2.064	
	66.7	66.7	3.69	3.07	
3"	3.125	0.90	3.330	2.949	
	79.4	79.4	4.96	4.39	
3 1/2"	3.625	1.00	4.290	3.989	
	92.1	92.1	6.38	5.94	
4"	4.125	1.10	5.380	5.188	
	104.8	104.8	8.01	7.72	
5"	5.125	1.25	7.610	8.081	
	130.2	130.2	11.32	12.03	
6"	6.125	1.40	10.200	11.616	
	155.6	155.6	15.18	17.29	
8"	8.125	2.00	19.290	20.289	
	206.4	206.4	28.71	30.19	
10"	10.125	0.250	30.100	31.590	
	257.2	257.2	44.79	47.01	
12"	12.125	0.280	40.400	45.426	
	308.0	308.0	60.12	67.60	

COPPER TUBE (TYPE K)

Nom. Tube Size	O.D. Tubing In (mm)	O.D. In (mm)	Wall Thick. In (mm)	Weight Lbs/Ft (kg/m)	Weight Water Lbs/Ft (kg/m)
1/4"	0.375	0.35	0.145	0.032	
	9.5	9.53	0.89	0.05	
3/8"	0.500	0.05	0.269	0.055	
	12.7	12.70	0.13	0.08	
1/2"	0.625	0.49	0.344	0.094	
	15.9	15.88	1.24	0.51	
5/8"	0.750	0.49	0.418	0.144	
	19.1	19.05	1.24	0.62	
3/4"	0.875	0.65	0.641	0.188	
	22.2	22.23	1.65	0.95	
1"	1.125	0.65	0.839	0.337	
	28.6	28.58	1.65	1.25	
1 1/4"	1.375	0.65	1.040	0.527	
	34.9	34.93	1.65	1.55	
1 1/2"	1.625	0.72	1.360	0.743	
	41.3	41.28	1.83	2.02	
2"	2.125	0.83	2.060	1.310	
	54.0	53.98	2.11	3.07	
2 1/2"	2.625	0.95	2.920	2.000	
	66.7	66.68	2.41	4.35	
3"	3.125	0.109	4.000	2.960	
	79.4	79.38	2.77	5.95	
3 1/2"	3.625	0.120	5.120	3.900	
	92.1	92.08	3.05	7.62	
4"	4.125	0.134	6.510	5.060	
	104.8	104.78	3.40	9.69	
5"	5.125	0.160	9.670	8.000	
	130.2	130.18	4.06	14.39	
6"	6.125	0.192	13.870	11.200	
	155.6	155.58	4.88	20.64	
8"	8.125	0.271	25.900	19.500	
	206.4	206.38	6.88	38.54	
10"	10.125	0.338	40.300	30.423	
	257.2	257.18	8.59	59.97	
12"	12.125	0.405	57.800	43.675	
	308.0	307.98	10.29	86.02	

RIGID STEEL (HEAVY DUTY) CONDUIT

Conduit Size (Nominal) In	I. D. Of Conduit In (mm)	O. D. Of Conduit In (mm)	O. D. Of Coupling In (mm)	Weight of Conduit Lbs/Ft (kg/m)	Maximum Weight* Of Conduit And Conductor Lead Covered Lbs/Ft (kg/m)	Not Lead Covered Lbs/Ft (kg/m)
½	0.622 15.8	0.840 21.3	1.063 27.0	0.85 1.26	1.20 1.79	1.00 1.49
¾	0.824 20.9	1.050 26.7	1.297 32.9	1.13 1.68	1.80 2.68	1.40 2.08
1	1.049 26.6	1.315 33.4	1.563 39.7	1.68 2.50	2.60 3.87	2.30 3.42
1¼	1.380 35.1	1.660 42.2	1.969 50.0	2.28 3.39	4.30 6.40	3.60 5.36
1½	1.610 40.9	1.900 48.3	2.234 56.7	2.73 4.06	5.90 8.78	4.50 6.70
2	2.067 52.5	2.375 60.3	2.719 69.1	3.68 5.48	8.50 12.65	7.20 10.71
2½	2.469 62.7	2.875 73.0	3.313 84.2	5.82 8.66	11.50 17.11	10.20 15.18
3	3.068 77.9	3.500 88.9	3.938 100.0	7.62 11.34	16.50 24.55	14.50 21.58
3½	3.548 90.1	4.000 101.6	4.438 112.7	9.20 13.69	19.00 28.28	17.50 26.04
4	4.026 102.3	4.500 114.3	4.938 125.4	10.89 16.21	24.80 36.91	21.50 32.00
5	5.047 128.2	5.563 141.3	6.296 159.9	14.81 22.04	35.90 53.43	30.80 45.84
6	6.065 154.1	6.625 168.3	7.358 186.9	19.19 28.56	50.70 75.45	43.40 64.59

* Maximum weight equals weight of rigid conduit plus weight of heaviest conductor combination (from the National Electrical Code Handbook.)

WATER FILLED PIPE SUPPORT SPACING

Nominal Pipe Size In	Max. Span Ft (m)	Nominal Pipe Size In	Max. Span Ft (m)
1	7 2.13	8	19 5.79
1½	9 2.74	10	22 6.71
2	10 3.05	12	23 7.01
2½	11 3.35	14	25 7.62
3	12 3.66	16	27 8.23
3½	13 3.96	18	28 8.53
4	14 4.27	20	30 9.14
5	16 4.88	24	32 9.75

The above spacing based on a combined bending and shear stress of 1500 PSI when pipe is filled with water and the pitch of the line is such that a sag of 0.1 in. between supports is permissible.

CONDUIT SUPPORT SPACING

346-12. Supports. Rigid metal conduit shall be installed as a complete system as provided in Article 344 and shall be securely fastened in place. Conduit shall be firmly fastened within 3 feet (914.4 mm) of each outlet box, junction box, cabinet, or fitting. Conduit shall be supported at least every 10 feet (3.05 m).

Exception: If made up with threaded couplings, it shall be permissible to support straight runs of rigid metal conduit in accordance with Table 344.30 (B)(2), provided such supports prevent transmission of stresses to termination where conduit is deflected between supports.

Table 344.30 (B)(2)
Support for Rigid Metal Conduit

Conduit Size In (mm)	Maximum Distance Between Supports Ft (m)
½-¾	10
12.7 - 19.1	3.05
1	12
25.4	3.66
1¼-1½	14
31.8 - 38.1	4.27
2-2½	16
50.8 - 63.5	4.88
3 & larger	20
76.2 - Larger	6.10

SCHEDULE 40: PVC PLASTIC PIPE


Pipe Size (Nominal) In	Outside Diameter In (mm)	Inside Diameter In (mm)	Pipe Weight Lbs/Ft (kg/m)	Pipe and Water Weight Lbs/Ft (kg/m)
¼	0.540 13.7	0.354 9.0	0.081 0.12	0.12 0.18
¾	0.675 17.1	0.483 12.3	0.109 0.16	0.19 0.28
½	0.840 21.3	0.608 15.4	0.161 0.24	0.29 0.43
¾	1.050 26.7	0.810 20.6	0.214 0.32	0.44 0.65
1	1.315 33.4	1.033 26.2	0.315 0.47	0.68 1.01
1¼	1.660 42.2	1.364 34.6	0.426 0.63	1.06 1.58
1½	1.900 48.3	1.592 40.4	0.509 0.76	1.37 2.04
2	2.375 60.3	2.049 52.0	0.682 1.01	2.11 3.14
2½	2.875 73.0	2.445 62.1	1.076 1.60	3.11 4.63
3	3.500 88.9	3.042 77.3	1.409 2.10	4.55 6.77
4	4.500 114.3	3.998 101.5	2.006 2.99	7.44 11.07
6	6.625 168.3	6.031 153.2	3.535 5.26	15.90 23.66
8	8.625 219.1	7.943 201.8	5.305 7.89	26.75 39.81
10	10.750 273.1	9.976 253.4	7.532 11.21	41.35 61.54



DATA FOR SCHEDULE STEEL PIPE

Nom. Size In	Pipe Schedule	Outside Dia. In (mm)	Inside Dia. In (mm)	Pipe Weight Lbs/Ft (kg/m)	Pipe and Water Weight Lbs/Ft (kg/m)
1/8	40	0.405	0.269	0.24	0.27
		10.3	6.8	0.36	0.40
	80	0.405	0.215	0.31	0.33
		10.3	5.5	0.46	0.49
1/4	40	0.540	0.364	0.42	0.47
		13.7	9.2	0.63	0.70
	80	0.540	0.302	0.53	0.57
		13.7	7.7	0.79	0.85
3/8	40	0.675	0.493	0.57	0.65
		17.1	12.5	0.85	0.97
	80	0.675	0.423	0.74	0.80
		17.1	10.7	1.10	1.19
1/2	40	0.840	0.622	0.85	0.98
		21.3	15.8	1.26	1.46
	80	0.840	0.546	1.09	1.19
		21.3	13.9	1.62	1.77
5/8	40	0.840	0.464	1.31	1.38
		21.3	11.8	1.95	2.05
	80	1.050	0.824	1.13	1.36
		26.7	20.9	1.68	2.02
3/4	80	1.050	0.742	1.47	1.66
		26.7	18.8	2.19	2.47
	160	1.050	0.612	1.94	2.07
		26.7	15.5	2.89	3.08
1	40	1.315	1.049	1.68	2.05
		33.4	26.6	2.50	3.05
	80	1.315	0.957	2.17	2.48
		33.4	24.3	3.23	3.69
1 1/4	40	1.315	0.815	2.84	3.07
		33.4	20.7	4.23	4.57
	80	1.660	1.380	2.27	2.92
		42.2	35.1	3.38	4.35
1 1/2	80	1.660	1.278	2.99	3.55
		42.2	32.5	4.45	5.28
	160	1.660	1.160	3.76	4.22
		42.2	29.5	5.60	6.28
1 1/2	40	1.900	1.610	2.71	3.60
		48.3	40.9	4.03	5.36
	80	1.900	1.500	3.63	4.39
		48.3	38.1	5.40	6.53
2	40	1.900	1.338	4.85	5.46
		48.3	34.0	7.22	8.13
	80	2.375	2.067	3.65	5.10
		60.3	52.5	5.43	7.59
2 1/2	80	2.375	1.939	5.02	6.30
		60.3	49.3	7.47	9.38
	160	2.375	1.687	7.45	8.42
		60.3	42.8	11.09	12.53
3	40	2.875	2.469	5.79	7.86
		73.0	62.7	8.62	11.70
	80	2.875	2.323	7.65	9.49
		73.0	59.0	11.38	14.12
3 1/2	80	2.875	2.125	10.00	11.54
		73.0	54.0	14.88	17.17
	160	3.500	3.068	7.57	10.77
		88.9	77.9	11.27	16.03
4	40	3.500	2.900	10.24	13.11
		88.9	73.7	15.24	19.51
	80	3.500	2.624	14.31	16.65
		88.9	66.6	21.30	24.78
5	40	4.000	3.548	9.10	13.39
		101.6	90.1	13.54	19.93
	80	4.000	3.364	12.49	16.35
		101.6	85.4	18.59	24.33

Nom. Size In	Pipe Schedule	Outside Dia. In (mm)	Inside Dia. In (mm)	Pipe Weight Lbs/Ft (kg/m)	Pipe and Water Weight Lbs/Ft (kg/m)
4	40	4.500	4.026	10.78	16.30
		114.3	102.3	16.04	24.26
	80	4.500	3.826	14.97	19.95
		114.3	97.2	22.28	29.69
5	40	4.500	3.624	18.98	23.45
		114.3	92.0	28.25	34.90
	120	4.500	3.438	22.48	26.51
		114.3	87.3	33.45	39.45
6	40	6.625	5.047	14.60	23.27
		168.3	128.2	21.73	34.63
	80	6.625	4.813	20.75	28.64
		168.3	122.2	30.88	42.62
8	40	8.625	6.065	18.95	31.48
		219.1	154.1	28.20	46.85
	80	8.625	5.761	28.54	39.84
		219.1	146.3	42.47	59.29
10	40	8.625	5.501	36.35	46.66
		219.1	139.7	54.09	69.44
	120	8.625	7.981	28.52	50.21
		219.1	202.7	42.44	74.72
12	40	8.625	7.813	35.60	56.39
		219.1	198.5	52.98	83.92
	80	8.625	7.625	43.34	63.14
		219.1	193.7	64.50	93.96
14	40	8.625	7.437	50.89	69.73
		219.1	188.9	75.73	103.77
	120	8.625	7.187	60.65	78.23
		219.1	182.5	90.26	116.42
16	40	8.625	7.001	67.68	84.37
		219.1	177.8	100.72	125.56
	160	8.625	6.813	74.61	90.42
		219.1	173.1	111.03	134.56
18	20	10.750	10.250	28.01	63.78
		273.1	260.4	41.68	94.92
	30	10.750	10.136	34.20	69.19
		273.1	257.5	50.90	102.97
20	40	10.750	10.020	40.44	74.63
		273.1	254.5	60.18	111.06
	60	10.750	9.750	54.68	87.05
		273.1	247.7	81.37	129.54
24	80	10.750	9.562	64.36	95.50
		273.1	242.9	95.78	142.12
	100	10.750	9.312	76.95	106.47
		273.1	236.5	114.51	158.44
30	120	10.750	9.062	89.20	117.16
		273.1	230.2	132.74	174.35
	140	10.750	8.750	104.02	130.09
		273.1	222.3	154.80	193.60
36	160	10.750	8.500	115.52	140.13
		273.1	215.9	171.91	208.54



MATERIAL

Unistrut fittings, unless noted, are made from hot-rolled, pickled and oiled steel plates, strip, bar or coil, and conform to one or more of the following specifications:

ASTM A575, A576, A635, A1011 SS GR 33, A1011 HSLAS GR 45 or A36. The fitting steel also meets or exceeds the physical requirements of ASTM A1011 SS GR 33.

Maple cable saddles, cable clamps and bus bar clamps are made from kiln-dry maple treated with paraffin to a depth of $\frac{1}{16}$ " (1.6mm). Special sizes of clamps can be fabricated upon request. Cable saddles are fiberglass-reinforced polyester.

CHANNEL RACEWAYS

The Unistrut Metal Framing System includes an exclusive combination of channel, fittings and hardware listed under new UL classification 5B. This classification covers strut-type channel raceways and fittings for use in accordance with Article 384 of the National Electrical Code, NFPA 70. Included are metal strut-type channel raceways at least .071 inch (1.81mm) thick and metal or non-metal closure strips at least .040 inch (1.02mm) thick.

The Unistrut system requires no welding, drilling or other complex fabrication techniques. This means faster, easier solutions for virtually any electrical support problem.

Unistrut channel offers structural and spanning capabilities not available with conventional surface raceway products and is available in continuous lengths of up to 20 feet. Just as important, it is part of an integrated system that can be used for raceways, trapeze hangers, cable-tray supports, lighting grids, fluorescent-fixture supports and countless other electrical applications.

Electrical Fittings.....	128 - 130
Receptacles.....	131
Fixture Hangers.....	131
Accessories and Connectors.....	132
Junction Boxes	132
In-Channel Joiners	133
Swivel Hangers	133
Cable Entrance Tubing and Accessories	134 - 136
Electrical Fittings Technical Data.....	137 - 138

CHANNEL COMPATABILITY

All of the electrical components in this section are intended for use with any of the $1\frac{5}{8}$ " wide channel. They are not intended for use with $1\frac{1}{4}$ " or $1\frac{3}{16}$ " framing systems.

FINISHES

Components listed in this section are available in:

- Electro-galvanized (EG), conforming to
ASTM B633 Type III SC1;
- Hot-dipped galvanized (HG), conforming to
ASTM A123 or A153,
- Green Powder Coat (GR), conforming to
commercial standards for Powder Coating
- Plain (PL)

Note: Many Unistrut Metal Framing components, when used with appropriate closures, are UL® listed, and CSA approved.

DESIGN LOAD

Design load data, where shown, is based on the ultimate strength of the connection with a safety factor of 2.5, unless otherwise noted.

DIMENSIONS

Imperial dimensions are illustrated in inches. Metric dimensions are shown in parenthesis or as noted. Unless noted, all metric dimensions are in millimeters and rounded to one decimal place.

LISTINGS

UL File No. - E19459	Channel & Closure Strips
UL File No. - E25629	Fittings
CSA File No. - 013669	All Products



Electrical Fittings




P1753-Pg 128



P2649 A-Pg 128



P2645 A-Pg 129



P2647 A-Pg 129




P1690-Pg 129



P1787-Pg 130



P2537-Pg 131




P2539-Pg 131




P2755-Pg 131



P2855-Pg 131




P3922-Pg 131



P2534-50-Pg 129



P2535-Pg 130



P2536-Pg 130



P2522-Pg 130



P3521-50-Pg 131



P2521-50-Pg 131



P5521-50-Pg 131



P5021-50-Pg 132



P2521-100-Pg 131



P5021-100-Pg 132



P5521-100-Pg 132



P1180 W-Pg 132



P2541-Pg 132



P2552-Pg 133



P2540-Pg 132



P3116-125-Pg 133




P2602-Pg 131



P2801-Pg 132




P2802-Pg 132



P2803-Pg 132




P2900-Pg 133



P2901-Pg 133



P2902-Pg 133



P2903-Pg 133



P2904-Pg 133



M2037-Pg 133



M2137-Pg 133




M2250-Pg 133




M2350-Pg 133



P16F-Pg 134




P21H-Pg 134




P2820-Pg 136




P2822-Pg 136




P2823-Pg 136



P2821-Pg 136




P2920-Pg 136



P2928-Pg 136

P2649A THRU P2649H


MAPLE CABLE SADDLES



- ¾" Flat Head Machine Screw included.
 - Specify hole size when ordering.
 - Order channel nuts as required.
- Material: Paraffin impregnated maple hardwood.

Part No.	Hole Size In (mm)	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)
P2649A	0 - 1	3	1 ¼	31
	0 - 25.4	76.2	44.5	14.1
P2649B	1 - 1 ½	3 ½	2	38
	25.4 x 38.1	88.9	50.8	17.2
P2649C	1 ½ - 2	4	2 ¼	47
	38.1 - 50.8	101.6	57.2	21.3
P2649D	2 - 2 ½	4 ½	2 ½	57
	50.8 x 63.5	114.3	63.5	25.9
P2649E	2 ½ - 3	5	2 ¾	68
	63.5 - 76.2	127.0	69.9	30.8
P2649F	3 - 3 ½	5 ½	3	80
	76.2 x 88.9	139.7	76.2	36.3
P2649G	3 ½ - 4	6	3 ¼	94
	88.9 - 101.6	152.4	82.6	42.6
P2649H	over 4			
	over 101.6			

P1753, P1754 CABLE SADDLES FG




Part Number	"A" In (mm)	Maximum Cable Dia. In (mm)	Wt/100 pcs Lbs (kg)
P1753 FG	2 13/16 71.4	3 76.2	12 5.4
P1754 FG	3 ¾ 95.3	4 ½ 114.3	17 7.7
P1753 PO	3 76.2	3 76.2	75 34.0
P1754 PO	4 101.6	4 ½ 114.3	95 43.1

Material: FG - Fiberglass Reinforced Polyester,
PO - Dry Process White Glazed Porcelain

P2645A THRU P2645H

MAPLE CABLE CLAMPS



- 3/8" studs, square nuts and washers included.
 - Specify hole size when ordering.
 - Order channel nuts as required.
- Material: Paraffin impregnated maple hardwood.

Part No.	Hole Size In (mm)	"A" & "B" Dimensions In (mm)	Wt/100 pcs Lbs (kg)
P2645A	0 - 1	3 1/2	84
	0 - 25.4	88.9	38.1
P2645B	1 - 1 1/2	4	102
	25.4 x 38.1	101.6	46.3
P2645C	1 1/2 - 2	4 1/2	121
	38.1 - 50.8	114.3	54.9
P2645D	2 - 2 1/2	5 1/2	165
	50.8 x 63.5	139.7	74.8
P2645E	2 1/2 - 3	6	189
	63.5 - 76.2	152.4	85.7
P2645F	3 - 3 1/2	6 1/2	215
	76.2 x 88.9	165.1	97.5
P2645G	3 1/2 - 4	7	243
	88.9 - 101.6	177.8	110.2
P2645H	over 4	-	-
	over 101.6	-	-

P2647A THRU P2647F


4" (101.6) BUS BAR MAPLE CLAMPS

- 1/2" studs, square nuts and washers are included.

- Channel nuts must be ordered separately.


- Bus bar maple clamps also available in 1/4" (6.4) x 2" (50.8) and 1/4" (6.4) x 6" (152.4).

Material: Paraffin impregnated maple hardwood.



P1690 THRU P1697

MAPLE CABLE CLAMPS




- Use with steel clamp and Everdur hardware. Order clamp separately.
 - Specify hole size when ordering.
- Material: Paraffin impregnated maple hardwood.

Part No.	Steel Clamp No.	Hole Size In (mm)	"A" In (mm)	Wt/100 pcs Lbs (kg)
P1690	P1113 E	0 - 5/8	1 5/16	24
		0 - 15.9	33.3	10.9
P1691	P1115 E	1/2 - 1	1 15/16	42
P1692	P1117 E	12.7 - 25.4	49.2	19.1
P1693	P1118 E	3/4 - 1 1/2	2 3/8	54
P1694	P1119 E	19.1 x 38.1	60.3	24.5
P1695	P1120 E	1/4 - 1 3/4	2 7/8	65
P1696	P1121 E	31.8 x 44.5	73.0	29.5
P1697	P1123 E	1/2 - 2 1/4	3 1/2	84
		38.1 x 57.2	88.9	38.1
		2 - 2 1/2	4	107
		50.8 x 63.5	101.6	48.5
		2 1/4 - 3	4 1/2	123
		57.2 - 76.2	114.3	55.8
		3 - 4	5 5/16	163
		76.2 - 101.6	141.3	73.9


P2534-50, P2534-75

Design Load
300 Lbs (1.33 kN)



Wt/100 pcs: 96 Lbs (43.5 kg)

CONDUIT SWING FITTING




- Conduit hanger fittings allow a free swivel of 15° in one direction.
- Fitting may be mounted to the slot side of the Unistrut channel or to the back.



P1787 THRU P1795

PORCE-A-CLAMP™



Patents Pending

Strap Material:

Electro-galvanized Steel (EG) or
Stainless Steel (SS)

Use With: All 1 5/8" channel


Porce-A-Clamp™

- Non-Breakable TPE Material.
- U.V. Resistant.
- U.L. Listed.
- Optional Stainless Steel Clamps.
- Tapered Flange to Protect Cable.
- Dielectric Strength 640 Volts Per Mil.
- One Piece Insulator.
- Replaces Porcelain & Maple Cable Clamp.
- For use in accordance with National Electrical Code ANSI/NFPA 70.
- Includes Pipe Strap.
- Temperature Rating -50°F to +275°F (-45°C to +135°C)


Part Number	Hole Size In (mm)	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)
P1787A	5/8 9.5	1.36	1.82	25 11.3
P1787B	1/2 12.7	34.5	46.2	
P1787C	5/8 15.9			
P1788	3/4 19.1			
P1788A	7/8 22.2	1.86	2.34	37 16.8
P1788B	1 25.4	47.2	59.4	
P1788C	1 1/8 28.6			
P1789	1 1/4 31.8			
P1789A	1 1/8 34.9	2.36	2.86	58 26.3
P1789B	1 1/2 38.1	59.9	72.6	
P1789C	1 1/8 41.3			
P1790	1 1/4 44.5			
P1790A	1 1/8 47.6	2.86	3.50	76 34.5
P1790B	2 50.8	72.6	88.9	
P1790C	2 1/8 54.0			
P1791	2 1/4 57.2	3.36	4.05	90 40.8
P1791A	2 1/8 60.3	835	102.9	

Part Number	Hole Size In (mm)	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)
P1791B	2 1/2 63.5	3.36	4.05	90 40.8
P1791C	2 5/8 66.7	85.3	102.9	
P1792	2 3/4 69.9			
P1792A	2 7/8 73.0	3.86	4.75	109 49.4
P1792B	3 76.2	98.0	120.7	
P1792C	3 1/8 79.4			
P1793	3 1/4 82.6			
P1793A	3 1/8 85.7	4.36	5.125	130 59.0
P1793B	3 1/2 88.9	110.7	130.2	
P1793C	3 5/8 92.1			
P1794	3 3/4 95.3			
P1794A	3 7/8 98.4	4.86	5.54	160 72.6
P1794B	4 101.6	123.4	140.7	
P1794C	4 1/8 104.8			
P1795	4 1/4 108.0			
P1795A	4 5/8 111.1	5.24	5.92	160 72.6
P1795B	4 1/2 114.3	133.1	150.4	


P2535
**CONDUIT HANGER CONNECTION
FOR 1/2" CONDUIT**



P2536
**CONDUIT HANGER CONNECTION
FOR 3/4" CONDUIT**




P2522
OUTLET BOX CONNECTION



Wt/100 pcs: 28 Lbs (12.7 kg)

Wt/100 pcs: 36 Lbs (16.3 kg)


Wt/100 pcs: 35 Lbs (15.9 kg)

P2755, P2756, P2757**RACEWAY HANGERS**

Design Load
120 Lbs (0.53 kN)

Part No.	"A" In (mm)	Wt/100 pcs
P2755	9/16	44
	14.3	20.0
P2756	7/8	44
	22.2	20.0
P2757	1 1/32	44
	10.3	20.0



Use with Channels:
P1001, P1101, P2001,
P5000, & P5500.
Material: 14 gauge (1.9).

P2855, P2856, P2857**RACEWAY HANGERS**

Design Load
120 Lbs (0.53 kN)


Use with Channels:
P1000, P1100,
P3000, P3300
Material: 14 gauge (1.9).

Part No.	"A" In (mm)	Wt/100 pcs
P2855	9/16	32
	14.3	14.5
P2856	7/8	32
	22.2	14.5
P2857	1 1/32	32
	10.3	14.5

P2602

Use with 1 1/8" Channel
Finish: Electro-galvanized
Stock Size: 1/4"
NOTE: Supports fixture in slot up or down system.


Wt/100 pcs: 154 Lbs (69.9 kg)

P3922 THRU P3926**SPICE FITTINGS**

P2869 14 (2) Gage

Material: 16 gauge (1.6).

Assy. No.	Use W/ Channel	"A" In (mm)	Clevis No.	Back Clevis No.	Plate Nut No.	Wt/100 pcs
P3922	P1000	1 1/8	P2377	P2517	P2869	100
	P1100	41.3				45.4
P3923	P3000	1 1/8	P3377	P2517	P2869	97
		34.9				44.0
P3924	P4000	1 1/16	P5377	P2517	P2869	80
		20.6				36.3
P3925	P5500	1 1/8	P2377	P5517	P2869	103
		41.3				46.7
P3926	P5000	1 1/8	P2377	P5017	P2869	106
		41.3				48.1


P3521-50**END CONNECTORS FOR 1/2" CONDUIT**

Material: 12 gauge (3).

Wt/100 pcs: 27 Lbs (12.2 kg)


P2521-50, P2521-75**END CONNECTORS FOR 1/2" & 3/4" CONDUIT**

1/4" X 5/8" Flat Head Machine Screw and P3016-1420 Nut Included



Part No.	Conduit Size A In	Wt/100 pcs
P2521-50	1/2	27
		12.2
P2521-75	3/4	26
		11.8

Use with channels:
P1000 and P1100.
Material:
12 gauge (3).


P2537, P5537**FLUORESCENT FIXTURE HANGERS**

Design Load
120 Lbs (0.53 kN)

- Hanger provides more than 1/2" (12.7) space between channel and fixtures.

Materials: 18 gauge (1.2).

Part No.	Use w/Channel	"A" In (mm)	Wt/100 Lbs (kg)
P2537	P1000	2 1/16	19
	P1100	61.9	8.6
P5537	P3000	3 1/4	22
	P5500	82.6	10.0

P2539, P3539, P5539**FLUORESCENT FIXTURE HANGERS**

Design Load
120 Lbs (0.53 kN)


- Hanger provides 1/8" (3.2) space between channel and fixtures.

Materials: 18 gauge (1.2).

Part No.	Use w/Channel	"A" In (mm)	Wt/100 Lbs (kg)
P2539	P1000	1 1/4	17
	P1100	44.5	7.7
P3539	P3000	1 1/2	15
		38.1	6.8
P5539	P5500	2 1/16	18
		65.1	8.2




P5521-50, P5521-75**END CONNECTORS FOR 1/2" & 3/4" CONDUIT**

1/4" X 5/8" Flat Head Machine Screw and P3016-1420 Nut Included




Part No.	Conduit Size A In	Wt/100 Lbs (kg)
P5521-50	1/2	27
		12.2
P5521-75	3/4	26
		11.8

Material:
12 gauge (3).


P3116-125**Fixture Stud Nut****P2552****POLYPROPYLENE WIRE RETAINER****P2904**

3/8"-16 x 1/4" Socket Cup Point
Set Screws Included
Extruded Aluminum

Wt/100 pcs: 11 Lbs (5.0 kg)

P2900**P2901**


Wt/100 pcs: .30 Lbs (.1 kg)

**P2902**

P1000

P2903

Wt/100 pcs: 12 Lbs (5.4kg)

P2903

3/8"-16 x 1/4" Socket Cup Point
Set Screws Included
Material: Cast aluminum.


3/8"-16 x 1/4" Socket Cup Point
Set Screws Included
Material: Cast aluminum.

3/8"-16 x 1/4" Socket Cup Point
Set Screws Included
Material: Cast aluminum.

3/8"-16 x 1/4" Socket Cup Point
Set Screws Included
Material: Cast aluminum.

Wt/100 pcs: 20 Lbs (9.1 kg)

Wt/100 pcs: 35 Lbs (15.9 kg)


M2037, M2050**SWIVEL HANGERS**

Design Load
600 Lbs (2.67 kN)

Part No.	"A"	"B"	Wt/100 pcs
	In	In (mm)	Lbs (kg)
M2037	3/8" - 16	2 ¹ / ₂ ₃₂ 75.4	23 10.4
M2050	1/2" - 13	2 ³ / ₄ 69.9	32 14.5


Wt/100 pcs: 27 Lbs (12.2 kg)

Wt/100 pcs: 45 Lbs (20.4 kg)

M2250**SWIVEL HANGER**


Design Load
600 Lbs (2.67 kN)

Wt/100 pcs: 18 Lbs (8.2 kg)

M2137, M2150**SWIVEL HANGERS**

Design Load
600 Lbs (2.67 kN)

Part No.	"A"	"B"	Wt/100 pcs
	In	In (mm)	Lbs (kg)
M2137	3/8" - 16	2 ²⁹ / ₃₂ 74	27 12.2
M2150	1/2" - 13	2 ³ / ₄ 69.9	45 20.4




Design Load
600 Lbs (2.67 kN)


Wt/100 pcs: 20 Lbs (9.1 kg)



P16F



Slot spacing
1 1/4" (31.8)
on center.



Tubing Finishes: PL, GR, HG, PG;
Standard Lengths: 10' & 20'

Wt/100 Ft: 178 Lbs (260 kg/100 m)
Allowable Moment 4,800 In-Lbs (540 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)


P16F - COLUMN LOADING

Unbraced Height In	Max. Allowable Load Column Loaded at C.G. Lbs	Max. Allowable Load Column Loaded at Slot Face Lbs
24	9,600	3,300
36	9,000	3,100
48	8,300	2,900
60	7,500	2,700
72	6,600	2,400
84	5,600	2,200
96	4,500	1,900
108	3,600	1,600
120	2,900	1,400
144	2,000	1,100


P16F - COLUMN LOADING (METRIC)

Unbraced Height mm	Max. Allowable Load Column Loaded at C.G. kN	Max. Allowable Load Column Loaded at Slot Face kN
610	42.7	14.7
914	40.0	13.8
1,219	36.9	12.9
1,524	33.4	12.0
1,829	29.4	10.7
2,134	24.9	9.8
2,438	20.0	8.5
2,743	16.0	7.1
3,048	12.9	6.2
3,658	8.9	4.9

P21H



Slot spacing
1 1/4" (31.8)
on center.



Tubing Finishes: PL, GR, HG, PG;
Standard Lengths: 10' & 20'

Wt/100 Ft: 297 Lbs (440 kg/100 m)
Allowable Moment 11,370 In-Lbs (540 N·m)
12 Gauge Nominal Thickness .105" (2.7mm)

P21H - COLUMN LOADING

Unbraced Height In	Max. Allowable Load Column Loaded at C.G. Lbs	Max. Allowable Load Column Loaded at Slot Face Lbs
24	17,700	6,200
36	16,900	6,000
48	16,000	5,700
60	15,000	5,400
72	13,900	5,100
84	12,600	4,700
96	11,300	4,300
108	9,900	3,900
120	8,300	3,500
144	5,800	2,800
168	4,230	2,300

P21H - COLUMN LOADING (METRIC)

Unbraced Height mm	Max. Allowable Load Column Loaded at C.G. kN	Max. Allowable Load Column Loaded at Slot Face kN
610	78.7	27.6
914	75.2	26.7
1,219	71.2	25.4
1,524	66.7	24.0
1,829	61.8	22.7
2,134	56.0	20.9
2,438	50.3	19.1
2,743	44.0	17.3
3,048	36.9	15.6
3,658	25.8	12.5
4,267	18.8	10.2

P16F - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	1,600	0.06	1,600	1,600	1,600
36	1,070	0.13	1,070	1,070	820
48	800	0.23	800	690	460
60	640	0.36	590	440	290
72	530	0.52	410	310	200
84	460	0.71	300	220	150
96	400	0.93	230	170	110
108	360	1.18	180	140	90
120	320	1.45	150	110	70
144	270	2.09	100	80	50
168	230	2.85	70	60	40

P21H - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
24	3,790	0.05	3,790	3,790	3,790
36	2,530	0.11	2,530	2,530	2,380
48	1,900	0.19	1,900	1,900	1,340
60	1,520	0.29	1,520	1,280	860
72	1,260	0.42	1,190	890	590
84	1,080	0.58	870	660	440
96	950	0.76	670	500	330
108	840	0.96	530	400	260
120	760	1.18	430	320	210
144	630	1.70	300	220	150
168	540	2.31	220	160	110

P16F - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	7.2	1	7.2	7.2	7.2
750	5.8	2	5.8	5.8	5.4
1,000	4.3	4	4.3	4.3	3.0
1,250	3.5	6	3.5	2.9	1.9
1,500	2.9	9	2.7	2.0	1.4
1,750	2.5	12	2.0	1.5	1.0
2,000	2.2	16	1.5	1.1	0.8
2,500	1.7	25	1.0	0.7	0.5
3,000	1.5	36	0.7	0.5	0.3
3,500	1.2	49	0.5	0.4	0.2
4,000	1.1	64	0.4	0.3	0.2

P21H - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	17.1	1	17.1	17.1	17.1
750	13.7	2	13.7	13.7	13.7
1,000	10.3	3	10.3	10.3	8.8
1,250	8.2	5	8.2	8.2	5.7
1,500	6.9	7	6.9	5.9	3.9
1,750	5.9	10	5.8	4.3	2.9
2,000	5.1	13	4.4	3.3	2.2
2,500	4.1	20	2.8	2.1	1.4
3,000	3.4	29	2.0	1.5	1.0
3,500	2.9	40	1.4	1.1	0.7
4,000	2.6	52	1.1	0.8	0.5

Notes:

1. Above loads include the weight of the member. This weight must be deducted to arrive at the net allowable load the beam will support.
2. Long span beams should be supported in such a manner as to prevent rotation and twist.
3. Allowable uniformly distributed loads are listed for various simple spans, that is, a beam on two supports. If load is concentrated at the center of the span, multiply load from the table by 0.5 and corresponding deflection by 0.8.

P16F - ELEMENTS OF SECTION


Parameter	P16F	P16F (metric)
Area of Section	0.416	In ²
Axis 1-1		cm ²
Moment of Inertia (I)	0.168	In ⁴
Section Modulus (S)	0.192	In ³
Radius of Gyration (r)	0.650	In
Axis 2-2		cm
Moment of Inertia (I)	0.210	In ⁴
Section Modulus (S)	0.240	In ³
Radius of Gyration (r)	0.725	In
		cm

P21H - ELEMENTS OF SECTION


Parameter	P21H	P21H (metric)
Area of Section	0.749	In ²
Axis 1-1		cm ²
Moment of Inertia (I)	0.490	In ⁴
Section Modulus (S)	0.455	In ³
Radius of Gyration (r)	0.820	In
Axis 2-2		cm
Moment of Inertia (I)	0.590	In ⁴
Section Modulus (S)	0.540	In ³
Radius of Gyration (r)	0.900	In
		cm




P2820, P2940
CHANNEL/TUBE CONNECTORS




Part No.	Use With	Wt/100 pcs Lbs (kg)
P2820	P16F	116 (2.6)
P2940	P21H	148 (67.1)

P2822, P2932**SPlice FITTINGS****P2823****90° RACK FITTING**


Part No.	Use With	Wt/100 pcs Lbs (kg)
P2822	P16F	97 (44.0)
P2932	P21H	122 (55.3)



Wt/100 pcs: 66 Lbs (29.9 kg)

P2821**LOCKING CLIP****P2928, P2929 AND P2930****CABLE BRACKETS**

Exclusive Cable Hook
Locking Clip prevents Cable
Hook removal.




Use with P16F or P21H.

Material: 12 gauge steel.

Part Number	"L" In (mm)	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)	Uniform Design Load Lbs (kN)
P2928	6 152.4	3 1/2 88.9	1/8 22.2	92 41.7	500 2.22
P2929	12 304.8	3 1/2 88.9	1 1/8 41.3	320 145.1	250 1.11
P2930	18 457.2	3 1/2 88.9	1 1/8 41.3	420 190.5	170 0.76

Safety factor of 3.

Wt/100 pcs: 3 Lbs (1.4 kg)

P2920 THRU P2924**CABLE BRACKETS**

Use with P16F or P21H.

Material: 12 gauge steel.

Part Number	"L" In (mm)	"A" In (mm)	"B" In (mm)	Wt/100 pcs Lbs (kg)	Uniform Design Load Lbs (kN)
P2920	5 1/2 139.7	3 1/2 88.9	1/8 22.2	90 40.8	500 2.22
P2921	8 1/4 209.6	3 1/2 88.9	1/8 22.2	120 54.4	325 1.45
P2922	11 279.4	3 1/2 88.9	1 1/8 41.3	300 136.1	275 1.22
P2923	13 3/4 349.3	3 1/2 88.9	1 1/8 41.3	340 154.2	220 0.98
P2924	19 1/4 489.0	3 1/2 88.9	1 1/8 41.3	430 195.0	160 0.71

Safety factor of 3.

U.L. LISTED

Unistrut channel is listed by Underwriters' Laboratories as a surface metal raceway. Snap-in closure strip is used to complete the raceway. Accessory parts listed by Underwriters are noted on drawings.

The following tables represent maximum number of conductors when raceway is not employed with fixtures or where the clearance between fixtures and raceway is greater than $\frac{1}{2}$ " (12.7). In all cases the snap-in cover is required to complete raceway enclosure.

P3300

Number and Conductor Size (AWG)					
Gauge	14	12	10	8	6
THWN, THHN	40	30	19	9	6
XHHW	26	21	16	7	5
T, TW	26	20	15	7	4
THW	17	14	11	6	4
RH	15	12	7	4	3
RHH, RHW	10	9	7	4	2

P1000, & -KO, P1100 & -KO

Number and Conductor Size (AWG)					
Gauge	14	12	10	8	6
THWN, THHN	88	66	42	20	14
XHHW	58	46	35	16	12
T, TW	57	44	34	16	9
THW	37	30	24	12	9
RH	33	27	16	9	6
RHH, RHW	23	20	16	9	6

Channel Size and Inside Area					
Channel Part Number	Size	Area	40% Area	25% Area	
P3300 & KO	$1\frac{1}{8}$ " x $\frac{7}{8}$ "	0.975 629	0.390 252	0.244 157	
P3000 & KO	$1\frac{1}{8}$ " x $1\frac{1}{2}$ "	1.677 1,082	0.671 433	0.419 270	
P1000 & KO, P1100 & KO	$1\frac{1}{8}$ " x $1\frac{1}{2}$ "	2.028 1,308	0.811 523	0.507 327	
P5500 & KO	$1\frac{1}{8}$ " x $2\frac{1}{16}$ "	3.169 2,045	1.268 818	0.792 511	
P5000 & KO	$1\frac{1}{8}$ " x $3\frac{1}{4}$ "	4.308 2,779	1.723 1,112	1.077 695	

C.S.A. APPROVED

Suitable for number of wires in Column A when installed to support and supply electric discharge type lighting fixtures when raceway wiring is suitable for at least 75° C except wire suitable for 60° C may be used when clearance between fixtures and raceways is at least $\frac{1}{2}$ " (12.7). Also suitable for number of wires in column B when

P3000, & -KO

Gauge	Number and Conductor Size (AWG)				
	14	12	10	8	6
THWN, THHN	72	54	34	17	12
XHHW	48	37	29	13	10
T, TW	46	36	28	13	7
THW	30	25	20	10	7
RH	27	22	13	7	5
RHH, RHW	19	16	13	7	5

P5500, & -KO

Gauge	Number and Conductor Size (AWG)				
	14	12	10	8	6
THWN, THHN	141	105	66	33	23
XHHW	93	73	57	27	19
T, TW	91	58	55	26	15
THW	59	49	39	20	15
RH	53	44	26	14	10
RHH, RHW	37	32	26	14	10

P5000, & -KO

Gauge	Number and Conductor Size (AWG)				
	14	12	10	8	6
THWN, THHN	193	105	91	45	32
XHHW	128	101	78	37	27
T, TW	125	98	75	35	20
THW	81	67	54	28	20
RH	73	60	36	19	13
RHH, RHW	51	44	36	19	13

Note:

Raceways with external joiners shall use a 40% wire fill calculation to determine the number of conductors permitted.

Raceways with internal joiners shall use a 25% wire fill calculation to determine the number of conductors permitted

Also UL Listed

P1001, P1101, P3001, P3301, P5001 & P5501

Raceway Wire Size AWG	P1000, &-KO		P3000, &-KO		P3300		P5000 &-KO		P5500, &-KO	
	A	B	A	B	A	B	A	B	A	B
14	6	10	5	10	4	6	10	10	10	10
12	6	10	4	10	3	6	10	10	10	10
10	5	8	4	6	-	-	8	10	8	10
8	4	6	3	4	-	-	6	9	6	8
6	2	3	2	2	-	-	4	6	4	6


Unistrut channels are also certified by Canadian Standards Association.



FLUORESCENT FIXTURES - SUPPORT APPLICATIONS


Spring-Nut attachment system

Conduit connects through knockout in fixture. Fixture is supported by P1006-1420 spring nut and 1/4" round head machine screw. Assembly is supported by P2855 hinged hanger.



Slotted channel attachment system


Conduit connects through knockout in fixture. Fixture is supported by HCSS series hex bolt and hex nut. Raceway is supported by P2855 hanger. To splice a continuous run, use P3922.



HIGH-BAY FIXTURE RACEWAY APPLICATIONS

H.I.D. Knockout mounted system

Fixture attached to and wired from raceway by 1/2" nipple assembly of desired length at channel knockout. P1280W end cap, P3184 closure strip, P2535 conduit connector, and P2855 channel hanger complete assembly. For splicing channels into continuous raceway runs, use joiner fitting P3922.




Deflection Table

Channel	Distance Between Supports - In (mm)								
	8' (2.4m)	10' (3m)	12' (3.7m)	14' (4.3m)	16' (4.9m)	18' (5.5m)	20' (6.1m)	22' (6.7m)	24' (7.3m)
P3300	0.187 4.7	-	-	-	-	-	-	-	-
P3000	0.100 2.5	0.250 6.4	0.500 12.7	-	-	-	-	-	-
P1100	0.088 2.2	0.250 6.4	0.437 11.1	0.875 22.2	-	-	-	-	-
P1000	-	0.180 4.6	0.312 7.9	0.625 15.9	1.000 25.4	1.625 41.3	-	-	-
P5500	-	-	-	0.250 6.4	0.500 12.7	0.812 20.6	1.620 41.1	-	-
P5000	-	-	-	-	0.310 7.9	0.625 15.9	1.000 25.4	1.800 45.7	2.500 63.5
P1001	-	-	-	-	0.310 7.9	0.625 15.9	1.000 25.4	1.800 45.7	2.500 63.5
P5001	-	-	-	-	-	0.200 5.1	0.250 6.4	0.400 10.2	0.500 12.7


High-Bay dual mounted system

Fixtures are connected to and wired from raceway by conduit connector fitting P2536. Raceway is supported by P2855 hanger. P1280W end caps and P3184 closure strip complete the assembly. Conduit connected to raceway through channel knockout.




H.I.D. Plug-in system (rigid mount)

Raceway is supported and wired by top mounted P2535 conduit connectors. P1280W end caps and P3184 closure strip complete assembly.




H.I.D. Plug-in system (with swivel)


P2855 hangers support raceway and P251-75 end connector joins conduit raceway. P1280W end caps (not shown) and P3184 closure strip complete assembly.



Uplighting with underhung or remote ballast



Fixtures attached to and wired from P2535 conduit fittings mounted to slot side of channel. Raceway can be wired by P2521 as shown or, conduit can enter through available knockout. Ballasts in P2521 are connected at the knockout by fixture adapter. In remote ballast installations, follow manufacturers instructions. P2855 hinged hangers support both types of installations. P3184 closure strip and P1280W end caps complete assembly. For continuous raceways, use joiner fitting P3922. P2521-75 end connector joins conduit to raceway.



MATERIAL

Cold-formed inserts are manufactured from standard 12 gauge (2.7 mm) Unistrut channel sections conforming to ASTM A1011 SS GR 33 or ASTM A653 GR 33, unless otherwise noted.

To inhibit concrete seepage, all inserts (except spot inserts) are provided with closure strips and end caps or foam filler, unless otherwise requested.

Most concrete inserts are available in stainless steel on special order. Consult factory for ordering information.

APPLICATION

A wide range of heavy-duty to light-duty "continuous" and "spot" concrete inserts are available for use in pre-cast, pre-stressed or poured-in-place concrete floors, walls or ceilings.

FINISHES

Cold-formed, standard-duty, light-duty and spot concrete inserts are available in:

Hot dipped galvanized (HG), conforming to
ASTM A123 or A153;

Pre-galvanized (PG), conforming to ASTM A653 GR 33

Plain (PL)

Heavy-Duty Inserts	141
Standard-Duty Inserts.....	142, 144
Light-Duty Inserts	143
Spot Inserts	144
Deck Inserts	145
Components	145
Technical Data	146

DESIGN LOAD

Design loads, where shown, are based on 3,000 PSI concrete, unless noted.

STANDARD LENGTHS

Insert lengths range from 3 inches (76.2 mm) to 20 feet (6.10m) with a tolerance of $\pm\frac{1}{4}$ -inch (6.4mm).

DIMENSIONS


Imperial dimensions are illustrated in inches. Metric dimensions are shown in parentheses or as noted. Unless noted, all metric dimensions are in millimeters and rounded to one decimal place.

Custom-designed inserts are available on special order. Consult factory for ordering information.




Heavy Duty Light Duty


Standard Duty




P3754-Pg 141




P3349-Pg 143




P3352-Pg 143




P3354-Pg 143




P3249-Pg 142



P3253-Pg 142



P3254-Pg 142



P3165-Pg 144



P2865-Pg 144

Spot Inserts and Components



P3245-Pg 144



P3245N4-Pg 144




M24-Pg 144



M2506-Pg 144




P3700-Pg 145



P1703-Pg 145




P2407-Pg 145



P3663-Pg 145


Fiberglass Concrete Inserts



Heavy Duty-Pg 193



Light Duty-Pg 194



Heavy Duty - Standard Profile-Pg 195

Closure Strips



P1184P Pg 60



P3184 Pg 60



P3184P Pg 60



P3184F Pg 60



P3712P Pg 60

Channel Nuts



Heavy Duty-Pg 73



Heavy Duty-Pg 73



Standard Duty-Pg 73



Standard Duty-Pg 73




Light Duty-Pg 73



Light Duty-Pg 73


INSTALLING CONCRETE INSERTS

- Nail insert to concrete form using prepunched nail holes
- Attach rebars to flanges on insert




The Unistrut concrete insert is firmly fixed to the concrete side of the form before pouring. When the forms are removed, the insert is ready for use. Brackets and other components can be attached at any point of the continuous entry channel.


USING INSTALLED CONCRETE INSERT



1. Scrape out filler



2. Insert channel nut.



3. Attach fitting

P3246

- Up to 5,700 lbs. tension capacity in 3,000 psi concrete
- Sizes available to accept threaded rod from $\frac{3}{4}$ " to 1- $\frac{1}{2}$ "
- Fiberglass rods to interface with the rebar or reinforcing rods, reducing the potential for a galvanic interaction
- 316 Stainless steel body with fiberglass rods to prevent corrosion
- Meets several industry and federal specifications, including: A-A-1192A (Type 18), WW-H-171-E (Type 18), ANSI/MSS SP-69 and MSS SP-58 (Type 18)







P3246 Installed

Part Number	Threaded Hole Size ^a	Maximum Allowable Load (lbs.)		
		Vertical	Shear ^b	45° Pull
P3246-75 ST	$\frac{3}{4}$ " - 10	3,230 ^a	1,930	2,740
P3246-87 ST	$\frac{7}{8}$ " - 9	4,480 ^a	2,680	3,800
P3246-1 ST	1" - 8	5,700	3,540	5,000
P3246-125 ST	$\frac{1}{4}$ " - 7	5,700	5,700	6,000
P3246-150 ST	$\frac{1}{2}$ " - 6	5,700	8,280	6,000

Safety Factor of 5 in 3,000 psi concrete

^a Limited by Threaded Rod Safe Load in accordance with MSS-SP-58^b Limited by MSS-SP-58 Tension Safe Load multiplied by 0.6**P3754****1 $\frac{5}{8}$ " x 1 $\frac{5}{8}$ " CHANNEL**

- Closure strip P3712 P and a styrene bead end cap that fits inside the channel to inhibit concrete seepage are included.
- The recommended design load when used for curtain wall anchorage is 5,000 pounds and is based on use in average, good concrete. The design load includes $\frac{1}{8}$ increase in load as permitted by AISI Specifications and Uniform Building Code when stresses are produced by wind or earthquake and other loads.
- The recommended design load is based on using two P1010 nuts at no less than 3" O.C. and no closer than 2" to either end of the insert. The distance between the insert centerline and the concrete edge must be a minimum of 3".
- All nuts and fittings for P3200 series concrete inserts will fit.
- Material: Cold formed from 12 Ga. (2.7mm) steel conforming to ASTM A1011 SS GR 33 or ASTM A653 GR 33 A.
- Finish: Choice of hot-dipped galvanized (HG) conforming to ASTM A123 or A153, or pre-galvanized (PG) conforming to ASTM A653-G90.



Part Number	Insert Length $\pm\frac{1}{4}$ " (6.4mm) In (mm)	Wt/100 pcs Lbs (kg)	Max. Anchor Spacing In (mm)	Max. Allowable Point Load Lbs (kN)	Spacing of Point Loads In (mm)	Max. Allowable Uniform Load Lbs (kN)
P3754	12 304.8	210 95.3	8 203.2	2,500 11.12	3 76.2	5,000 22.24


Safety factor 3



P3200 SERIES


1 5/8" x 1 3/8" CHANNEL PG HG

P3249 thru P3252




"NC" Suffix – No Closure Strip, With End Caps
 "WC" Suffix – With Closure Strip & End Caps

P3253





"NC" Suffix – No Closure Strip, With End Caps & Back Plates
 "WC" Suffix – With Closure Strip, End Caps & Back Plates

P3254 thru P3270



"NC" Suffix – No Closure Strip, W/End Caps & Back Plates
 "WC" Suffix – W/Closure Strip, End Caps & Back Plates
 "X" – No Closure Strip, No End Caps, W/Back Plates



- Includes closure and end caps unless otherwise requested.
- P3280 end cap used when distance to first anchor is up to 2" (51 mm).
- P3704 end cap is used when end distance to first anchor is over 2" (51 mm).
- Nail or anchor inserts to forms every 16" (406.4 mm) to 24" (609.6 mm).
- Anchors are 8" (203.2 mm) on center.
- Material: Cold formed from 12 Ga. (3) steel conforming to ASTM A1011 SS GR 33 or ASTM A653 GR 33. A. Stainless steel available on special order.
- Finish: Choice of hot-dipped galvanized (HG) conforming to ASTM A123 or A153, or pre-galvanized (PG) conforming to ASTM A653-G90.


Part Number	Insert Length In/Ft (mm)	Wt/100 pcs Lbs (kg)	Max. Allowable Point Load Lbs (kN)	Min. Spacing of Pt. Loads In (mm)	Max. Allowable Uniform Load Lbs (kN)
P3249	3" 76.2	85 39	500 2.22	—	500 2.22
P3250	4" 101.6	100 45	800 3.56	—	800 3.56
P3251	6" 152.4	130 59	1,000 4.45	—	1,000 4.45
P3252	8" 203.2	159 72	1,200 5.34	—	1,200 5.34
P3253	12" 304.8	227 103	2,000 8.90	—	2,000 8.90
P3254	16" 406.4	270 122	2,000 8.90	12 304.8	4,000 17.79
P3255	20" 508.0	357 162	2,000 8.90	12 304.8	4,000 17.79
P3256	24" 609.6	399 181	2,000 8.90	12 304.8	4,000 17.79
P3257	32" 812.8	527 239	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3257A	36" 914.4	616 279	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3258	40" 1,016.0	661 300	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3259	4" 1,219.2	786 357	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3260	5' 1,524.0	1,003 455	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3261	6' 1,828.8	1,173 532	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3262	7' 2,133.6	1,390 630	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3263	8' 2,438.4	1,560 708	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3264	9' 2,743.2	1,741 790	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3265	10' 3,048.0	1,947 883	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3266	12' 3,657.6	2,334 1,059	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3267	14' 4,267.2	2,717 1,232	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3268	16' 4,876.8	3,116 1,413	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3269	18' 5,486.4	3,530 1,601	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)
P3270	20' 6,096.0	3,882 1,761	2,000 8.90	12 304.8	2,000 2,976.3 Lbs./Ft. (kg/m)

Safety factor 3.

P3300 SERIES

1 5/8" x 7/8" CHANNEL PG HG


P3349 thru P3351



"NC" Suffix – No Closure Strip, With End Caps
 "WC" Suffix – With Closure Strip & End Caps


- Includes closure and end caps unless otherwise requested.
- P3380 end cap used when distance to first anchor is up to 2" (51 mm).
- P3703 end cap is used when end distance to first anchor is over 2" (51 mm).
- Nail or anchor inserts to forms every 16" (406.4 mm) to 24" (609.6 mm).
- Anchors are 8" (203.2 mm) on center.
- Material: Cold formed from 12 Ga. (3 mm) steel conforming to ASTM A1011 SS GR. 33 or A653 GR 33. A. Stainless steel available on special order.
- Finish: Choice of hot-dipped galvanized (HG) conforming to ASTM A123 or A153, or pre-galvanized (PG) conforming to ASTM A653-G90.

P3352 thru P3353








"NC" Suffix – No Closure Strip, With End Caps & Back Plates
 "WC" Suffix – With Closure Strip, End Caps & Back Plates

P3354 thru P3370



"NC" Suffix – No Closure Strip, W/End Caps & Back Plates
 "WC" Suffix – W/Closure Strip, End Caps & Back Plates
 "X" – No Closure Strip, No End Caps, W/Back Plates




Part Number	Insert Length In/Ft. (mm)	Wt/100 pcs Lbs (kg)	Max. Allowable Point Load Lbs (kN)	Min. Spacing of Pt. Loads In (mm)	Max. Allowable Uniform Load Lbs (kN)
P3349	3"	68	400	—	400
	76.2	31	1.78		1.78
P3350	4"	81	500	—	500
	101.6	37	2.22		2.22
P3351	6"	102	750	—	750
	152.4	46	3.34		3.34
P3352	8"	122	1,000	—	1,000
	203.2	55	4.45		4.45
P3353	12"	174	1,500	—	1,500
	304.8	79	6.67		6.67
P3354	16"	185.0	1,500	12	3,000
	406.4	84	6.67	304.8	13.34
P3355	20"	231	1,500	12	3,000
	508.0	105	6.67	304.8	13.34
P3356	24"	277	1,500	12	3,000
	609.6	126	6.67	304.8	13.34
P3357	32"	370	1,500	12	1,500 Lbs./Ft. (kg/m)
	812.8	168	6.67	304.8	2,232.2 (kg/m)
P3357A	36"	416	1,500	12	1,500 Lbs./Ft. (kg/m)
	914.4	189	6.67	304.8	2,232.2 (kg/m)
P3358	40"	463	1,500	12	1,500 Lbs./Ft. (kg/m)
	1,016.0	210	6.67	304.8	2,232.2 (kg/m)
P3359	4'	555	1,500	12	1,500 Lbs./Ft. (kg/m)
	1,219.2	252	6.67	304.8	2,232.2 (kg/m)
P3360	5'	694	1,500	12	1,500 Lbs./Ft. (kg/m)
	1,524.0	315	6.67	304.8	2,232.2 (kg/m)
P3361	6'	832	1,500	12	1,500 Lbs./Ft. (kg/m)
	1,828.8	377	6.67	304.8	2,232.2 (kg/m)
P3362	7'	971	1,500	12	1,500 Lbs./Ft. (kg/m)
	2,133.6	440	6.67	304.8	2,232.2 (kg/m)
P3363	8'	1,110	1,500	12	1,500 Lbs./Ft. (kg/m)
	2,438.4	503	6.67	304.8	2,232.2 (kg/m)
P3364	9'	1,249	1,500	12	1,500 Lbs./Ft. (kg/m)
	2,743.2	567	6.67	304.8	2,232.2 (kg/m)
P3365	10'	1,387	1,500	12	1,500 Lbs./Ft. (kg/m)
	3,048.0	629	6.67	304.8	2,232.2 (kg/m)
P3366	12'	1,665.0	1,500	12	1,500 Lbs./Ft. (kg/m)
	3,657.6	755	6.67	304.8	2,232.2 (kg/m)
P3367	14'	1,942	1,500	12	1,500 Lbs./Ft. (kg/m)
	4,267.2	881	6.67	304.8	2,232.2 (kg/m)
P3368	16'	2,220	1,500	12	1,500 Lbs./Ft. (kg/m)
	4,876.8	1,007	6.67	304.8	2,232.2 (kg/m)
P3369	18'	2,497	1,500	12	1,500 Lbs./Ft. (kg/m)
	5,486.4	1,133	6.67	304.8	2,232.2 (kg/m)
P3370	20'	2,775	1,500	12	1,500 Lbs./Ft. (kg/m)
	6,096.0	1,259	6.67	304.8	2,232.2 (kg/m)

Safety factor 3.




P3165 SERIES

1 5/8" x 7/8" CHANNEL



"X" Suffix - No Closure Strip, No End Caps
 "WC" Suffix - With Closure Strip & End Caps



Part No.	Length Ft (M)	Wt/100 pcs Lbs (kg)
P3165	10	1,650
	3.05	748.4

Part No.	Length Ft (M)	Wt/100 pcs Lbs (kg)
P3170	20	3,280
	6.10	1,487.8

Maximum allowable load/ft.

Concrete	A Lbs (kN)	B Lbs (kN)
Light Wt	425	800
	1.89	3.56

Concrete	A Lbs (kN)	B Lbs (kN)
Normal Wt	500	1,000
	2.22	4.45

Safety factor 3.

- Designed for use in prestressed concrete.
- Anchors 8" (203.2 mm) on center; first anchor 4" (101.6 mm) from end.
- Includes closure and end caps unless otherwise requested.
- Material: Cold formed from 12 Ga. (2.7 mm) steel conforming to ASTM A1011 SS GR 33 or ASTM A653 GR 33. A. Stainless steel available on special order.
- Finish: Choice of pre-galvanized (PG) conforming to ASTM A653-G90, or plain (PL).

Safety factor 3.





Finish: Plain

Part Number	A In (mm)	Wt/100 pcs Lbs (kg)
P2865-10	1 25.4	0.9
P2865-15	1 1/2 38.1	0.9
P2865-20	2 50.8	0.9

P3245

M24

SPOT INSERT



Square Nut for P3245 Insert

Part Number	Wt/100 pcs Lbs (kg)	Max. Allowable Pt. Load Lbs (kN)
P3245	54 24.5	1,000 4.45

Part Number	Size/Thread In	T In (mm)	Wt/100 pcs Lbs (kg)
P3245-N4	1/4" — 20	5/16" 7.9	6 2.7
P3245-N6	5/16" — 16	7.9	5 2.3
HSQN050	1/2" — 13	7/16" 11.1	6 2.7

Finish: Pre-galvanized

Safety factor of 3

- For 1/4", 3/8", or 1/2" size attachment or hanger rod.
- Insert nuts to be ordered separately.

Part Number	Wt/100 pcs Lbs (kg)	Max. Allowable Pt. Load Lbs (kN)
M24	52 23.6	800 3.56



Part Number	Size/ Thread In	T In (mm)	Wt/100 pcs Lbs (kg)
M2506	1/4" — 20	1/4" 6.4	13 5.9
M2508	3/8" — 16	3/8" 9.5	14 6.4
M2510	1/2" — 13	1/2" 12.7	14 6.4
M2512	5/8" — 11	1/2" 12.7	12 5.4
M2523	3/4" — 10	1/2" 12.7	11 5.0
M2524	7/8" — 9	1/2" 12.7	10 4.5

Finish: Electro-galvanized

Safety factor of 5

- Ribs along sides of slot give extra strength to case.
- Insert nuts M2506 thru M2524 to be ordered separately.

P3700 SERIES




Part Number	Rod Dia. In	Tension Load Lbs (kN)	Shear Load Lbs (kN)	Wt/100 pcs Lbs (kg)
P3700-37	3/8	850 3.78	600 2.67	89 40.4
P3700-50	1/2	1,380 6.14	1000 4.45	111 50.3
P3700-62	5/8	1920 8.54	1760 7.83	141 64.0

Notes:

1. Allowable loads have been determined by the manufacturer's testing, analysis, and technical specification.
2. Values are based on a safety factor of 5.
3. 20 Gauge Metal Deck

P1703, P1704, P3703, P3704, P4703

END CAP ANCHORS PG HG



Part Number	Channel	"A"	Wt/100 pcs
		In (mm)	Lbs (kg)
P1703	P1000	2 5/32 61.1	30 13.6
P1704	P1000	3 1/2 89.7	37 16.8
P3703	P3300	2 7/16 61.9	17 7.7
P3704	P3000	3 76.2	20 9.1
P4703	P4000	2 3/8 60.3	27 12.2

Note: End cap anchor for use with 1 5/8" wide standard Unistrut inserts only.


P2407, P3280, P3380

END CAPS EG

P3663, P4663

JOINT COVERS

Part Number	Fits Channel	Wt/100 pcs Lbs (kg)
P2407	P1000	10 4.5
P3280	P3000	8 3.6
P3380	P3300	5 2.3



Part Number	Use With Insert Series	Wt/100 pcs Lbs (kg)
P3663	P3270	10 4.5
P4663	P3370	6 2.7

NOTE: Joint cover for use with 1 5/8" wide standard Unistrut inserts only.



LOAD CHART BY LENGTH

Part Number	Insert Length In (mm)	Wt/100 ft Lbs (kg)	Anchor Spacing In (mm)	Max. Allowable Point Load Lbs (kN)	Min. Spacing Between Pt. Loads In (mm)	Max. Allowable Uniform Load Lbs (kN)
P3249	3	85 38.6	3 76.2	500 2.22	—	500 2.22
		68 30.8	3 76.2	400 1.78	—	400 1.78
P3250	4	100 45.4	4 101.6	800 3.56	—	800 3.56
		81 36.7	4 101.6	500 2.22	—	500 2.22
P3251	6	130 59.0	6 152.4	1,000 4.45	—	1,000 4.45
P3351		102 46.3	6 152.4	750 3.34	—	750 3.34
P3252	8	159 72.1	8 203.2	1,200 5.34	—	1,200 5.34
P3352		122 55.3	8 203.2	1,000 4.45	—	1,000 4.45
P3754	12	210 95.3	8 203.2	2,500 11.12	3 76.2	5,000 22.24
P3253		227 103.0	4 101.6	2,000 8.90	—	2,000 8.90
P3353	16	174 122.5	4 101.6	1,500 8.90	—	1,500 17.79
P3254		185 83.9	4 101.6	1,500 6.67	12 304.8	3,000 13.34
P3255	20	357 161.9	4 101.6	2,000 8.90	12 304.8	4,000 17.79
P3355		231 104.8	4 101.6	1,500 6.67	12 304.8	3,000 13.34
P3256	24	399 181.0	4 101.6	2,000 8.90	12 304.8	4,000 17.79
P3356		277 125.6	4 101.6	1,500 6.67	12 304.8	3,000 13.34

CONTINUOUS CONCRETE INSERT LOAD CHART

Up To 20 Ft. (6.10m)

Part Number	Wt/100 ft Lbs (kg)	Anchor Spacing In (mm)	Max. Allowable Point Load Lbs (kN)	Min. Spacing Between Pt. Loads In (mm)	Max. Allowable Uniform Load Lbs/Ft (kg/m)
P3270	194 88.0	4 101.6	2,000 8.90	12 304.8	2,000 2,976.3
P3370	139 63.0	4 101.6	1,500 6.67	12 304.8	1,500 2,232.2
P3170*	165 74.8	8 203.2	1,000 4.45	12 304.8	1,000 1,488.2


*When used in prestressed concrete "T" Beam.

Load data is based on use of 3000 PSI concrete.

SPOT INSERT LOAD CHART


Part Number	Wt/100 pcs Lbs (kg)	Anchor Spacing In (mm)	Max. Allowable Point Load Lbs (kN)
P3246	414 187.8	—	5,700 25.35
M26/M2812	54 24.5	—	1,500 6.67
M3245	52 23.6	—	1,000 4.45
M24/M2512	52 23.6	—	800 3.56

MAXIMUM ALLOWABLE POINT LOAD




The maximum allowable point load may be placed anywhere along the insert.
All loads placed less than 2" from the end of an insert must be reduced by 50%.

MAXIMUM ALLOWABLE UNIFORM LOAD





The maximum allowable uniform load must be placed as a series of point loads.

SPACING OF MULTIPLE POINT LOADS



PULL-OUT LOAD

Minimum Edge Distance to Achieve Rated Pull-Out Capacity

17/8" (47.6mm); P3170
A = 3" (76.2mm); all others

Unistrut® represents a line of steel, aluminum, and fiberglass strut and accessories used extensively in electrical infrastructure support.

Application Example.....	148
Solar Connectors.....	149
Key Advantages.....	150

Unistrut is available in a range of corrosion inhibiting finishes making it a prime choice in today's marketplace. The Unistrut system is infinitely adjustable for a multitude of configurations and uses.

The solar components shown in this section allow you to shape an effective solution for mounting solar panels that fits your exact needs.

MATERIAL

Unistrut channels are accurately and carefully cold formed to size from low-carbon strip steel.

STEEL: PLAIN

12 Ga. (2.7 mm), 14 Ga.(1.9 mm) and
16 Ga. (1.5 mm) ASTM A1011 SS GR 33.

STEEL: PRE-GALVANIZED

12 Ga. (2.7 mm), 14 Ga. (1.9 mm) and
16 Ga. (1.5mm) ASTM A653 GR 33.

FINISHES

Fittings are available in:

- Green Powder Coat (GR), conforming to commercial standards for Powder Coating,
- Electro-galvanized (EG), conforming to ASTM B633 Type III SC1;
- Hot-dipped Galvanized (HG), conforming to ASTM A123 or A153
- Plain (PL).

DIMENSIONS

Imperial dimensions are illustrated in inches. Metric dimensions are shown in parenthesis or as noted. Unless noted, all metric dimensions are in millimeters and rounded to one decimal place.

DESIGN BOLT TORQUE






BOLT SIZE	1/4"-20	5/16"-18	3/8"-16	1/2"-13	5/8"-11	3/4"-10
Rec.Torque Ft/Lbs (N·m)	6 (8)	11 (15)	19 (26)	50 (68)	100 (136)	125 (170)
Max Torque Ft/Lbs (N·m)	7 (9)	15 (20)	25 (34)	70 (95)	125 (170)	135 (183)


LISTINGS

UL File No. - E361025	PV Mounting Systems
-----------------------	---------------------




TYPICAL SOLAR INSTALLATION



SLR200 – SOLAR END CLAMP

- $5/16'' \times 2\frac{3}{4}''$ hex head cap screw; stainless steel nut; lock washer included
- End-clamp design for use with strut based racking system
- Patent-pending end-stop feature allows use with vertical strut
- Meets uplift loads of 350 lbs.


*Patent-pending

SLR100 – SOLAR MID-CLAMP

- $5/16'' \times 2\frac{3}{4}''$ hex head cap screw; stainless steel nut; lock washer included
- Mid-clamp design for use with strut based racking system
- Provides .8"(21 mm) panel spacing
- Meets spacing requirements of WEEB-WMC
- Meets uplift loads of 350 lbs.






WEEB - WMC - ELECTRICAL EQUIPMENT BONDING WASHER

- Patented design features stainless steel teeth that pierce into anodized aluminum, providing a gas tight connection which prevents oxidation
- Meets ANSI/UL467 requirements for bonding/grounding systems
- Quick installation that is safe, reliable and consistent



**KEY ADVANTAGES**

- The market's only specific panel mounting components made exclusively for use with Unistrut.
- Simple design used by the industry for a variety of installation methods and applications.
- Stainless steel hardware included with all solar clamps.
- Available in Black or Silver Anodized (Material AA-6063-T6) for corrosion protection and sleek appearance.
- Best fit with Unistrut channel to create less penetration, and superior slip resistance.
- Available and supported by Unistrut's national network of distributors.



Sleeper Support	153 - 154
Strut Support	155 - 156

Conduit Supports

Mounted Support, Polycarbonate Base	157
Elevated Support, Polycarbonate Base	157
Elevated Support, Steel Base	158

Gas and Mechanical Supports

Mounted Support, Polycarbonate Base	158
Mounted Support, w/Roller Polycarbonate Base	158
Elevated Support, w/Roller, Polycarbonate Base	159
Elevated Support, w/Roller, Steel Base	160

Accessories

Spacer	160
Support Pads, Deck Plates	160
Pipe Hanger Bases, Polycarbonate and Steel	161



















Fabricated Supports


Single Base Trapeze	162
Double Base Trapeze	163
Heavy Duty Double Base Trapeze	163
Double Base Duct Support	163
Mechanical Supports	164
Bridge Cross-Over, Walkway, Service Platform or Ramp	164

Installation	165
--------------------	-----

Pipe Diameters and Loading	166
----------------------------------	-----

Technical Data	167 – 168
----------------------	-----------

**Sleeper Support**Rooftop Sleeper Support
Pg 153 - 154**Strut Support**Model UP
Strut Support
Pg 155**Conduit Support**Mounted
Polycarbonate Base
Pg 157Elevated Support
Polycarbonate Base
Pg 157Elevated Support
Steel Base
Pg 158**Gas and Mechanical Support**Mounted
Polycarbonate Base
Pg 158Mounted, w/Roller
Polycarbonate Base
Pg 158Elevated Support, w/Roller
Polycarbonate Base
Pg 159Elevated Support,
w/Roller
Steel Base
Pg 160**Accessories**Spacer for Model 1.5, 3-R
Pg 160Support Pads &
Deck Plates
Pg 160Polycarbonate Bases
Pg 161Steel Bases
Pg 161**Fabricated Supports**Single Base Trapeze
Pg 162Double Base Trapeze
Pg 163Heavy Duty, Double Base Trapeze
Pg 163Double Base Duct Support
Pg 163Heavy Duty Mechanical Support
Pg 164Light Duty Mechanical Support
Pg 164Bridge Cross-Over, Walkway,
Service Platform or Ramp
Pg 164



The Unipier rooftop sleeper is the first rooftop support that is white to reflect the sun's UV rays. It is cost-effective, lightweight and can be cut to the desired length while on the job site.


The model RSS4 is conveniently packaged in shrink wrap bundles of 9 - 4 ft. supports that can be easily carried to the rooftop.



The Unipier sleeper support is lightweight, just 4 lbs./4 ft. section, so it is easily transported to the job site in bundles of 9 supports.



The Unipier sleeper support can be conveniently cut to lengths of 6" or longer right on the job site.



TEK screws or other self tapping fasteners are used to attach conduit supports, pipe clamps or other clamping fittings.


NOTE: Load not to exceed 50 lbs./6" length
Part Number: RSS4



The Sleeper Support is not restricted to just pipe clamps. It makes a perfect companion for the Roofwalk® Rooftop Walkways.




Position the grating on the Unipier sleeper support and insert the appropriate size hold down clip (G639, G607, or G620).




Use a TEK screw to attach the hold down clip.

That's all that is required!



You can even use the Unipier support for multiple tasks. Here we have Unistrut Roofwalks® Rooftop Walkways and a piece of electrical conduit attached to the sleeper.



Grating can also be used to construct a platform for heavy equipment or even as a workstand.

UP-SPSS Style Support



- Align Center hole of P4100T on base.
- Place square washer inside P4100T.
- Insert screw & torque to 19 ft./lbs.

Part Number	Qty. Unipier Bases	Supporting Channel	
		Qty.	Description
UP-BK	4	0	Base Only
UP-SPSS-6 HG	4	4	6" - P4100T HG (up to 3 1/2" Pipe)
UP-SPSS-10HG	4	4	10" - P4100T HG (4" to 8" Pipe)


NOTE:

1. The maximum uniform load on P1000T is 400 lbs.
2. Uniform load is limited by roof base allowed load of 200 lbs. (5 psi on roof).

Single Pier Installation

1. Align center hole of Unistrut P4100T on base and attach using supplied hardware. Torque screw to 19 ft./lbs.
2. Place pipe/tubing on P4100T and attach pipe/tubing clamp.

UP-MPDS Style Support



Trapeze Installation

1. Align end holes of Unistrut P1000T on bases and attach using supplied hardware. Torque screw to 19 ft./lbs.
2. Place pipe/tubing on support and attach with appropriate pipe/tubing clamp.

Part Number	Qty. Unipier Bases	Supporting Channel	
		Qty.	Description
UP-MPDS-26HG	4	2	26" - P1000T HG for Trapeze
UP-MPDS-38HG	4	2	38" - P1000T HG for Trapeze
UP-MPDS-50HG	4	2	50" - P1000T HG for Trapeze
UP-MPDS-62HG	4	2	62" - P1000T HG for Trapeze

NOTE:

1. The maximum uniform load on P1000T is 400 lbs.
2. Uniform load is limited by roof base allowed load of 200 lbs. (5 psi on roof).

NOTE: Kits do not include pipe/tubing or clamps.



Support Spacing

Pipe Size (Nom.)	Support Spacing			
	Sch. 40 Pipe Water-Filled ^(a)		Conduit GRC ^(b)	
Single Pier	Trapeze ^(d)	Single Pier	Trapeze ^(d)	
3/8"	7'	7'	N/A	N/A
1/2"	7'	7'	10'	10'
3/4"	7'	7'	10'	10'
1"	7'	7'	12'	12'
1 1/4"	7'	7'	14'	14'
1 1/2"	9'	9'	14'	14'
2"	10'	10'	16'	16'

Pipe Size (Nom.)	Support Spacing			
	Sch. 40 Pipe Water-Filled ^(a)		Conduit GRC ^(b)	
Single Pier	Trapeze ^(d)	Single Pier	Trapeze ^(d)	
2 1/2"	11'	11'	16'	16'
3"	12'	12'	13' ^(c)	20'
3 1/2"	13'	13'	11' ^(c)	20'
4"	12' ^(c)	14'	9' ^(c)	20'
5"	8' ^(c)	16'	6' ^(c)	20'
6"	6' ^(c)	17'	4' ^(c)	20'
8"	4' ^(c)	19'	N/A	N/A

Note:

(a) Based on ANSI/MSS SP-69, 2003 Edition, Table 3.




(b) Based on 2002 NEC, Table 344.30(B)(2).

(c) Spacing limited to roof base allowed load of 200 lbs. (5 psi on roof).


(d) Spacing may be limited by maximum allowed weight on trapeze to 400 lbs.

Application Examples

Unipier Rooftop Support System provides a simple and versatile way to support and manage pipe, tubing, conduit, HVAC systems, and the like. The Unipier Rooftop Support System does not require roof surface penetration and allows the parts to remain off the surface.



Mounted Support, Polycarbonate Base



Part Number	Material	Max. Uniform Load	Wt./Each
2.5-CS-2	Polycarbonate	100 lbs.	2.3 lbs.
24-BS-4	Polycarbonate	640 lbs.	8.0 lbs.

Determining Maximum Pipe Size


Maximum pipe size supported by any of the strut supports is determined by the load and the clear space required between the pipes. The spacing between pipes should be as follows:

- 1" between piping 3" and smaller.
- 1-½" between a pipe 3" and smaller and a pipe 4" or larger.
- 2" between piping 4" and larger.
- At least 1" between pipe clamp and end of strut

For example, a support for two 3" pipes would require:

$$1" + 3" + 1\frac{1}{2}" + 3" + 1" = 9\frac{1}{2}" \text{ wide channel support}$$

Elevated Support, Polycarbonate Base



Note: Base for 2.5-CS-5, 2.5-CS-7 shown. Other bases have additional support or flanges to handle the increased loads.


All bases are polycarbonate material

Shipped assembled.

Part Number	"H" (max) in. (mm)	"W" in. (mm)	"L" in. (mm)	"T" in. (mm)	Max. Uniform Load (lbs.)	Wt./Each (lbs.)
2.5-CS-5	5" (127.0)	7 1/2" (190.5)	10" (254.0)	12" (304.8)	100 lbs.	2.1
2.5-CS-7	7 1/2" (190.5)	7 1/2" (190.5)	10" (254.0)	12" (304.8)	100 lbs.	2.5
2.5-CS-12	12" (304.8)	9" (228.6)	15 1/4" (387.4)	12" (304.8)	100 lbs.	4.0
16-BS-7	7" (177.8)	9" (228.6)	15 1/4" (387.4)	16" (406.4)	125 lbs.	5.0
16-BS-12	12" (304.8)	9" (228.6)	15 1/4" (387.4)	16" (406.4)	125 lbs.	8.0
20-BS-7	7" (177.8)	16" (406.4)	18" (457.2)	20" (508.0)	440 lbs.	10.8
20-BS-12	12" (304.8)	16" (406.4)	18" (457.2)	20" (508.0)	440 lbs.	15.1
24-BS-18	12" (304.8)	23" (584.2)	19" (482.6)	24" (609.6)	640 lbs.	8.0



Elevated Support, Steel Base




Part Number	Base Material	Max. Uniform Load	Wt./Each
16-BS-7 HG	Hot-Dipped Galvanized	150 lbs.	7.5 lbs.
16-BS-7 SS	Stainless Steel	150 lbs.	7.5 lbs.

Part Number	Base Material	Max. Uniform Load	Wt./Each
12-BS-7 HG	Hot-Dipped Galvanized	150 lbs.	7.5 lbs.
12-BS-7 SS	Stainless Steel	150 lbs.	7.5 lbs.

Unipier® Rooftop Pipe Support System - Gas & Mechanical Support

Mounted, Polycarbonate Base





Part Number	Max. Pipe Capacity	Max. Uniform Load	Wt./Ea.	Optional Pipe Strap
1.5 Pipe Support	1 1/2" ID, 1.9" OD	80 lbs.	0.35 lbs.	1.5 Pipe Strap

Note: Base is polycarbonate

Optional pipe strap aluminum w/SS Screws



Shipped assembled.

Mounted, with Roller, Polycarbonate Base



Note: All bases are polycarbonate

Part Number	"H" in. (mm)	"W" in. (mm)	"L" in. (mm)	Roller size	Max. Pipe Capacity	Max. Uniform Load	Wt./Ea. lbs.	Optional Pipe Strap
3-R-2	2.15" (54.6)	7 3/4" (196.9)	7 3/4" (196.9)	3"	3" ID 3 3/4" OD	100 lbs.	1.1 lbs.	3-R-2 Pipe Strap
3-R-4	4" (101.6)	7 3/4" (196.9)	7 3/4" (196.9)	3"	3" ID 3 3/4" OD	100 lbs.	1.2 lbs.	3-R-4 Pipe Strap
5-R	2.35" (59.7)	9"	15 1/4" (387.4)	5"	5" ID 6" OD	150 lbs.	2.4 lbs.	6-RAH Pipe Strap


Elevated Support, with Roller, Polycarbonate Base

Note: Base for 3-RAH-7 shown. Other bases have additional support or flanges to handle the increased loads.

All bases are polycarbonate material

Optional pipe strap aluminum w/SS Screws


Shipped assembled.



Part Number	"H" (max) in. (mm)	"W" in. (mm)	"L" in. (mm)	Roller Size in. (mm)	Max. Pipe Capacity	Max. Uniform Load	Wt./Ea. Lbs.	Optional Pipe Strap
3-RAH-7	7" (177.8)	7 1/2" (190.5)	10" (254.0)	3" (76.2)	3" ID 3 3/4" OD	100 lbs.	1.9	3-RAH Pipe Strap
3-RAH-12	12" (304.8)	9" (228.6)	15 1/4" (387.4)	3" (76.2)	3" ID 3 3/4" OD	100 lbs.	5.8	3-RAH Pipe Strap
5-RAH-7	7" (177.8)	9" (228.6)	15 1/4" (387.4)	5" (127.0)	5" ID 6" OD	150 lbs.	4.8	6-RAH Pipe Strap
5-RAH-12	12" (304.8)	9" (228.6)	15 1/4" (387.4)	5" (127.0)	5" ID 6" OD	150 lbs.	4.8	6-RAH Pipe Strap
6-RAH-7	7 1/2" (190.5)	16" (406.4)	18" (457.2)	5" (127.0)	6" ID 8 1/2" OD	250 lbs.	8.8	6-RAH Pipe Strap
6-RAH-12	12" (304.8)	16" (406.4)	18" (457.2)	5" (127.0)	6" ID, 8 1/2" OD	250 lbs.	9.8	6-RAH Pipe Strap
8-RAH-18	18" (457.2)	19" (482.6)	23" (584.2)	12" (304.8)	6" ID, 8 1/2" OD	640 lbs.	20.0	8-RAH Pipe Strap



Elevated Support, with Roller, Steel Base




Part Number	"W" in. (mm)	"L" in. (mm)	Roller in. (mm)	Material	Max. Pipe Capacity	Max. Uniform Load	Wt. Each Lbs
3-RAH-7 HG	8" (203.2)	14" (355.6)	3" (76.2)	Hot-Dipped Galvanized	3" ID 3 3/4" OD	100 lbs.	3.3
3-RAH-7 SS	8" (203.2)	14" (355.6)	3" (76.2)	Stainless Steel	3" ID 3 3/4" OD	100 lbs.	3.3
4-RAH-7 HG	12.07" (306.6)	16.07" (408.2)	5" (127.0)	Hot-Dipped Galvanized	4" ID 5" OD	150 lbs.	6.8
4-RAH-7 SS	12.07" (306.6)	16.07" (408.2)	5" (127.0)	Stainless Steel	4" ID 5" OD	150 lbs.	5.8

Note: Optional 3-RAH Pipe Strap aluminum w/SS Screws

Unipier® Rooftop Pipe Support System - Accessories


Spacer for Model 1.5 and Model 3-R



Part Number	Use With	"W"	Added Pipe Clearance	Wt./Ea.
1.5 Spacer	1.5	6"	1 1/2"	0.43 lbs
3-R Spacer	3-R-2 or 3-R-4	7-1/2"	2"	0.75 lbs

Material: Polycarbonate

Support Pad, Polycarbonate



The Unipier support pad is designed to provide a barrier between the roof membrane and rooftop equipment. The support pad is 1/8" thick and are compatible with all current types of decking and commonly used built-up and single-ply roof membranes.


Support pads should be installed in the following areas:

- Under all Unipier pipe supports. The pipe support must be placed evenly over the support pad.
- In high traffic points or where regular maintenance is necessary to service rooftop equipment.


When installing the support pad, remove all rock, aggregate, dirt and excess dust from an area of the roof membrane slightly larger than the support pad. Then, apply the support pad on the cleaned area and center the Unipier pipe support on the rooftop pad.

The maximum roof top load should not exceed 5 p.s.i. The rooftop pad can withstand higher loading, but the roof membrane and insulation are typically limited to 5 p.s.i.


Deck Plate, Stainless Steel




Part Number	Material	Width "W"	Wt./Each
Deck Plates 12 SS	Stainless Steel	12"	2.0 lbs.
Deck Plates 18 SS	Stainless Steel	18"	4.5 lbs.

Polycarbonate Base**Model 6-H Base P**


Note: Maximum 150 lbs. Load
Wt./Ea.: 2.5 lbs.

Model 8-H-DB Base P

Note: Maximum 350 lbs. Load
Wt./Ea.: 4.5 lbs.

Model 16-H Base P


Note: Maximum 350 lbs. Load
Wt./Ea.: 18.5 lbs.



Stainless Steel / Hot Dip Galvanized Steel Base**Model 6-H, 8-H, 16-H Base HG or S.S.**

Part Number	"W"	"L"	"Opening"
6-H Base HG	8" (203.2mm)	14" (355.6mm)	1-5/8" x 7/8" (41.3 x 22.2)
6-H Base SS	8" (203.2mm)	14" (355.6mm)	1-5/8" x 7/8" (41.3 x 22.2)
8-H Base HG	16" (406.4mm)	12" (304.8mm)	1-5/8" x 1-5/8" (41.3 x 41.3)
8-H Base SS	16" (406.4mm)	12" (304.8mm)	1-5/8" x 1-5/8" (41.3 x 41.3)
16-H Base HG	20" (508.0mm)	20" (508.0mm)	3" x 3" (76.2 x 76.2)
16-H Base SS	20" (508.0mm)	20" (508.0mm)	3" x 3" (76.2 x 76.2)




Single Base Trapeze



Double Base Trapeze**Double Base Duct Support**


Model	Material	Max. Uniform Load Per Pipe Stand	Max. Pipe Capacity
6-H-P	Polycarbonate	300 lbs.	7 1/2"
8-H-P	Polycarbonate	700 lbs.	9"
6-H-HG	Hot-Dipped Galvanized	300 lbs.	7 1/2"
6-H-SS	Stainless Steel	300 lbs.	7 1/2"
8-H-HG	Hot-Dipped Galvanized	700 lbs.	9"
8-H-SS	Stainless Steel	700 lbs.	9"
10-H-P	Polycarbonate	1,600 lbs.	9"
16-H-HG	Hot-Dipped Galvanized	1,600 lbs.	18"
16-H-SS	Stainless Steel	1,600 lbs.	18"

Heavy Duty Double Base Trapeze



Model	Max. Uniform Load Per Pipe Stand	Max. Pipe Capacity
8-H-DB	700 lbs.	9"
16-H-DB	1,600 lbs.	18"

Base Material: Polycarbonate

Model	Material	Max. Uniform Load Per Duct
6-DSA	Polycarbonate	150 lbs.
8-DSA	Polycarbonate	300 lbs.

Double Base Duct Support


Model	Material	Max. Uniform Load Per Duct
6-DS-P	Polycarbonate	150 lbs.
6-DS-HG	Hot-Dipped Galvanized	300 lbs.
6-DS-SS	Stainless Steel	300 lbs.
8-DS-P	Polycarbonate	300 lbs.
8-DS-HG	Hot-Dipped Galvanized	300 lbs.
8-DS-SS	Stainless Steel	300 lbs.
8-DS-DB-P	Polycarbonate	300 lbs.
10-DS-P	Polycarbonate	300 lbs.

**Heavy Duty Mechanical Support****Light Duty Mechanical Support**

Note: Adjustable height, maximum load 200 lbs.

Available Sizes: 18" x 18", 24" x 24", 30" x 30", 36" x 36"

Note: Custom sizes available, Contact Unistrut for information.

Bridge Cross-OVER, Walkway, Service Platform or Ramp

Product Description:

A pipe support used to support roof mounted gas pipes, electrical conduit, solar piping and other mechanical piping. Unique design absorbs thermal expansion and contraction of pipes thus preventing damage to the roof membrane. Pipes rests include:

- "U" shaped cradle situated in a polycarbonate resin seat.
- Self-lubricating roller polycarbonate resin rod and roller. As daytime temperatures warm the roof membrane and the mechanical pipe network found on the roof, causing them to expand, the roller bearing in the pipe stand rolls beneath the pipe it supports. A difference between night and day temperatures of 20° F. causes 100 ft. of 1" steel pipe to move as much as 1/4".
- A strut system constructed of hot-dipped galvanized steel components including clevis hangers or band hangers.
- For the duct supports, the ducts rest on a 1 5/8" x 1 5/8" or 1 5/8" x 7/8" Unistrut channel and are adjustable in height.

Composition and Material:

Support base is made of polycarbonate resin or hot-dipped galvanized or stainless steel as indicated for the specific base. The base is gently rounded to prevent gouging the roof membrane. Carbon black is added to the polycarbonate resin for UV resistance and protection.

Pipe Roller is made of polycarbonate, or steel as indicated for the specific part.

Other Metal Parts are made of hot-dipped galvanized or stainless steel.

Duct Supports are made of hot-dipped galvanized Unistrut channel

All-Thread Rod are 1/2" or 3/8" stainless steel and are used for vertical supports.

Compatibility:

Pillow Block Pipe Stands are recommended for use on and compatible with all current types of decking and with all commonly used built-up and single-ply roofing membranes where roof-mounted pipes occur. For heavier loads it is prudent to use a Unipier Support Pad or other traffic pad to further protect the roof membrane.

Adjustable Height:

Several models allow adjustable height as desired or required by the code or roof system. Each model can be configured to allow plus or minus height above the roof. Purchasers should specify desired heights upon ordering the pillow block hangers.

Installation Process:

1. Center the support beneath the pipes or ducts so that the pipe or ducts are squarely over the pipe stand.
2. For adjustable models, adjust the support to the desired height and to ensure a uniform load with other supports. Make certain the horizontal support strut is level.
3. Place the pipe or duct on the support without dropping or causing undue impact.

For heavier loads it is prudent to install an additional sheet of roofing material, a Unipier Deck Plate, or Unipier Support Pad beneath the duct support.

For built-up roofs, all loose aggregate from an area 2" larger than each base should be removed from the area directly beneath the support. Care should be taken to install each support so it supports a proportional and equal amount of weight at each support.

Optional Straps:

For many of the models, the pipe may be secured to the pipe stand by using optional Unipier Pipe Straps.

Note:

When using a pipe strap, allow sufficient room between the pipe and the strap to allow free movement of the pipe without binding.

Loads and Spacing:

Unistrut recommends that spacing not exceed 10' between centers depending upon the load. Make certain each pipe stand is properly elevated to ensure a uniform load weight at all pipe stands and not exceed the load specified for the particular model support. All loads given in this catalog are for uniformly distributed loads.

Maintenance:

Normally maintenance is not required. Semi-annual inspection is required to check pipe stand position and set pipe alignment, weight distribution and improper installation which may cause pipe stand damage or failure.



Typical Steel Pipe Weights – Pipe Standing Load

For Schedule 40 Steel Pipe. (ASTM A53-86)

Pipe Size	Pounds per Foot of Pipe Empty	Pounds per Foot Containing Gas		PSI per Foot on Model 6-RAH-7 BASE	5 Feet Spacing	7.5 Feet Spacing	10 Feet Spacing
		Pounds per Foot Containing Water					
3"	7.575	7.578	.02	37.89 lbs..13 psi	56.84 lbs..20 psi	75.78 lbs..26 psi	
		13.4	.04	67.00 lbs..23 psi	100.50 lbs..35 psi	134.00 lbs..47 psi	
4"	10.790	10.794	.03	53.97 lbs..19 psi	80.96 lbs..28 psi	107.94 lbs..37 psi	
		16.3	.05	81.50 lbs..28 psi	122.25 lbs..42 psi	163.00 lbs..57 psi	
5"	14.620	14.627	.04	73.14 lbs..25 psi	109.7 lbs..38 psi	146.27 lbs..51 psi	
		23.2	.07	116.00 lbs..40 psi	174.00 lbs..60 psi	232.00 lbs..80 psi	
6"	18.970	18.98	.05	94.49 lbs..33 psi	142.35 lbs..49 psi	189.80 lbs..66 psi	
		31.5	.09	157.50 lbs..55 psi	236.25 lbs..82 psi	315.00 lbs..1.09 psi	
8"	28.55	28.567	.08	142.84 lbs..50 psi	214.25 lbs..74 psi	285.67 lbs..99 psi	
		50.1	.14	250.00 lbs..87 psi	375.75 lbs..1.30 psi	501.00 lbs..1.74 psi	
10"	40.48	40.507	.12	202.54 lbs..70 psi	303.80 lbs..1.05 psi	405.07 lbs..1.41 psi	
		74.6	.21	373.00 lbs..1.30 psi	559.50 lbs..1.94 psi	746.00 lbs..2.60 psi	

PSI is in pounds per square inch on models 6-RAH-7 BASE, which contain 2 bases for a total of 288 square inches of roof contact area support.

Typical Pipe Diameters

PIPE	PVC (Steel Size)	PVC (C900)	Cast Iron	Steel	Conduit
Inside Diameter	Outside Diameter	Outside Diameter	Outside Diameter	Outside Diameter	Outside Diameter
1/2"	.84"	–	–	.84"	.840"
3/4"	1.05"	–	–	1.05"	1.050"
1"	1.32"	–	–	1.32"	1.315"
1 1/4"	1.66"	–	–	1.66"	1.660"
1 1/2"	1.90"	–	–	1.90"	1.90"
2"	2.38"	2.50"	2.50"	2.38"	2.375"
2 1/2"	2.88"	–	–	2.88"	2.875"
3"	3.50"	–	3.96"	3.50"	3.500"
3 1/2"	–	–	–	–	4.000"
4"	4.50"	4.80"	5.00"	4.50"	4.500"
5"	–	–	–	5.56"	5.563"
6"	6.63"	6.90"	7.22"	6.63"	6.625"
8"	8.63"	9.05"	9.42"	8.63"	–
10"	10.75"	11.10"	11.60"	10.75"	–

Unipier Specifications for Typical Bases

Base Model	Outside Dimension at Roof Contact (in.)	Roof Contact Area (in. ²)	Allowable Loading in Pounds	PSI on Roof for Each Base Under Maximum Load	Composition of Material of Base
1.5	6 X 6	24.42	80	3.27	P
1.5 SPACER	6 X 6	33.06	80	2.41	P
2.5-CS-2, 2.5-CS-5, 2.5-CS-7	7.5 X 10	57.50	100	1.73	P
2.5-CS-12	9 X 15.25	111.75	100	0.89	P
2.5-SB-H P	9 X 15.25	111.75	125	1.11	P
3-R-2; 3-R-4	7.75 X 7.75	39.64	100	2.52	P
3-R SPACER	7.25 X 7.25	52.56	100	1.90	P
3-RAH-7	7.5 X 10	57.50	100	1.73	P
3-RAH-12	9 X 15.25	111.75	100	1.11	P
3-RAH-7 HG / SS	8 X 14	96.06	100	1.04	HG / SS
4-RAH-7 HG / SS	12 X 16	174.89	150	0.85	HG / SS
5-R; 5-RAH-7; 5-RAH-12	9 X 15.25	111.75	150	1.34	P
5-SB-H HG	12 X 16	174.89	170	0.97	HG / SS
5-SB-H P	16 X 18	220.32	250	1.13	P
6-RAH-7; 6-RAH-12	16 X 18	220.32	250	1.13	P
6-RAH-7 HG/SS; 6-RAH-RS HG/SS	12 X 16	174.89	150	0.85	HG / SS
6-H-P (used in pairs)	9 X 15.25	223.50	310	1.38	P
6-H (2 Bases) HG / SS	8 X 14	192.12	310	1.61	HG / SS
8-H-DB-P (used in pairs)	9 X 31.69	447.00	700	1.56	P
8-H HG / SS (used in pairs)	12 X 16	349.78	700	2.00	HG / SS
8-RAH-18	19 x 23	325.98	640	1.96	P
8-SB-H	19 x 23	325.98	640	1.96	P
10-H-DS P	19 x 23	325.98	640	1.96	P
12-BS-7 HG / SS	12 X 16	174.89	150	0.85	HG / SS
16-BS-7; 16-BS-12	9 X 15.25	111.75	125	1.11	P
16-BS-7 HG / SS	12 X 16	174.89	150	0.85	HG / SS
16-H-P (used in pairs)	16 X 39	881.28	1600	1.81	P
16-H HG / SS (used in pairs)	20 X 20	800.00	1600	2.00	HG / SS
20-BS-7; 20-BS-12	16 X 18	220.32	250	1.13	P
24-BS-4; 24-BS-18	19 x 23	325.98	640	1.96	P

P – Polycarbonate Resin, SS – Stainless Steel - ASTM No. 304, HG – Hot-Dipped Galvanized

Note: Care should be taken to properly engineer the roof design so as to not overload the actual limits or manufacturer's recommended limits for each pipe support, the roof membrane, the roof top insulation, or the roof structure.

Note: Unipier has set the above load limits for each base to come within usual and customary roof structure, roof insulation, and roof membrane load limits. Unipier's manufacturing recommendations do not replace actual engineering required for each specific job.




Technical Properties For Polycarbonate Resin*

PROPERTY	ASTM TEST METHOD	VALUE
PHYSICAL		
Specific Gravity	D792	1.20
Specific Volume, in ³ /lb (cm ³ /g)	–	23.1 (0.83)
Weight/Volume, lbs/in ³ (g/cm ³)	–	0.043 (1.20)
Water Absorption %	D570	–
24 hours @ 73°F (23°C)	–	0.15
Equilibrium, 73°F (23°C)	–	0.35
Equilibrium, 212°F (100°C)	–	0.58
Mold Shrinkage, in/in (mm/mm)	D955	0.005-0.007
Light Transmittance, % at 0.125"	D1003	89
Haze, % @ 0.125"	D1003	1
Refractive Index	–	1.586
THERMAL		
Deflection Temperature °F (°C)	D648	–
@ 66 psi (0.46 MPa)	–	–
@ 254 psi (1.82 MPa)	–	270 ()
Specific Heat, Btu/lb/°F (kJ/kg/°K)	–	0.30 (1.25)
Thermal Conductivity	–	–
Btu-in/h-ft ² °F (W/Km)	–	1.35 (.19)
Coefficient of Thermal Expansion	–	–
in/in/°F (m.m/°C)	D696	3.75 x 10 ⁻⁵ (6.75 s 10 ⁻⁵)
Vicat Softening Temperature, °F (°C)	D1525	305-315 (152-157)
Viscosity Midpoint	D1238	9.5
(Melt Flow Rate) g/10 min.	Condition 0	–
Brittleness Temperature, °F (°C)	D746	<-200 (-129)
Flammability Ratings	–	–
ASTM	D365°	AEB>1"
UL Standard 94° 1/16 (1.6 mm)	UL94	V-2
UL Standard 94° 1/8" (3.2 mm)	UL94	V-2
Oxygen Index	D2863	25.0
PHYSICAL		
Dielectric Strength, volts/mil (kV/mm)	D149	380 (15.0)
Short time, 125 mils (3.2mm)	–	–
Dielectric Constant	D150	–
60 Hz	–	3.17
106 Hz	–	2.96
Dielectric Factor	D150	–
60 Hz	–	0.0009
106 Hz	–	0.010
Volume Resistivity, ohm-cm	–	D257
@ 73°F, dry (23°C)	–	>10 ¹⁶
Arc Resistance, sec	D495	–
Stainless Steel Electrodes	–	10-11
Tungsten Electrodes	–	120

PROPERTY	ASTM TEST METHOD	VALUE
MECHANICAL		
Tensile Strength, psi (MPa)	D638	–
Yield	–	9,000 (62)
Ultimate	–	10,000 (69)
Elongation, %	D638	–
Rupture	–	130
Flexural Strength, psi (MPa)	D790	14,000 (97)
Flexural Modules, 10 ⁵ psi (MPa)	D790	3.40 (2,300)
Compressive Strength, psi (MPa)	D695	12,500 (86)
Compressive Modules, psi (MPa)	D695	–
10 ⁵ osu (MPa)	–	3.45 (2,400)
Shear Strength, psi (MPa)	D732	–
Yield	–	6,000 (40)
Ultimate	–	10,000 (70)
Shear Modules, 10 ⁵ psi (MPa)	–	1.14 (790)
Izod Impact Strength, ft-lbs/in (J/m)	D1822	–
Notched, ¼" thick (3.22mm)	–	15 (801)
Tensile Impact Strength, ft-lbs/in ² (kJ/m ²)	D1822	–
S-type	–	275 (579)
Dynatup Impact Strength, ft-lbs/in (J)	D3763	47 (64)
Fatigue Strength, psi @ 2.5mm cycles (MPa)	D671	–
cycles (MPa)	–	1,000 (7.0)
Rockwell Hardness	D785	–
M	–	70
R	–	118
Deformation Under Load %	D621	–
4000 psi @ 73°F (27 MPa @ 23°C)	–	0.2
4000 psi @ 158°F (27 MPa @ 70°C)	–	0.5
Taber Abrasion Resistance	–	–
Weight Loss, mg/1000 cycles	D1044	10

*Polycarbonate Resin is used in all models indicated in catalog as Polycarbonate, and in all rollers.



MATERIAL

Unistrut channels are accurately and carefully cold formed to size from low-carbon strip steel.

STEEL: PLAIN

14 Gauge (1.9 mm), ASTM A1011 SS GR 33
19 Gauge (1.0 mm) ASTM A1008

STEEL: PRE-GALVANIZED

14 Gauge (1.9 mm) ASTM A653 GR 33,
19 Gauge (1.0 mm) ASTM A653 GR 33

Channel nuts are manufactured from mild steel bars conforming to ASTM A576, GR 1015, and are case hardened.

Fittings are made from hot rolled, pickled and oiled steel plate or strip and conform to ASTM A1011 SS GR 33.

Many framing channels are available in special metal on request. Consult factory for ordering information.

FINISHES

All channels and fittings are available in: Perma-Green III (GR), Pre-galvanized (PG), conforming to ASTM A653 GR 33 and plain (PL).

Nuts are available in plain or electro-galvanized (EG) finish. Fittings are available in Perma-Green III (GR) or plain (PL).

STANDARD LENGTHS

Standard lengths are 10 feet (3.05M) and 20 feet (6.10M). Tolerances are: +½" (3.2 mm) to +½" (12.7 mm) to allow for cutting. Special lengths are available for a small cutting charge with a tolerance of ±½" (3.2mm).

APPLICATION

A framing system designed for medium loads, the 1¼" series is especially suitable for use in the OEM, commercial and display markets. It maintains a lightness in scale and a clean line that makes it aesthetically pleasing as well as functional.

A1000 (14 Gauge)	171 - 172
A3300 (14 Gauge)	173 - 174
Channel Nuts and Closure Strips	175
Flat Plate Fittings	175 - 176
Ninety Degree Fittings.....	176
Angle and Wing Shape Fittings	176
"U" Shape Fittings	177
Pipe / Tubing Clips	177
Brackets	177

THREADS

All threads on the nuts and bolts are Unified and American coarse screw threads.

DESIGN BOLT TORQUE

BOLT SIZE	¼"-20	⁵/₁₆"-18	¾"-16
Rec. Torque	6	11	19
Ft/Lbs (N·m)	(8)	(15)	(26)
Max Torque	7	15	25
Ft/Lbs (N·m)	(9)	(20)	(34)


DIMENSIONS

Imperial dimensions are illustrated in inches. Metric dimensions are shown in parenthesis or as noted. Unless noted, all metric dimensions are in millimeters and rounded to one decimal place.


LOAD DATA

All beam and column load data pertains to carbon steel and stainless steel channels. Load tables and charts are constructed to be in accordance with the SPECIFICATION FOR THE DESIGN OF COLD-FORMED STEEL STRUCTURAL MEMBERS 2007 EDITION published by the AMERICAN IRON AND STEEL INSTITUTE USING ASD METHOD. Loads are based on 33 ksi steel cold formed to 42 ksi.


Type of Load	Safety Factor to Yield Strength	Safety Factor to Ultimate Strength
Beam Loads	1.67	2.0
Column Load	1.80	2.2

**A1000 Series**1 1/4" x 1 1/4"
14 Ga.

A1000-Pg 171




A1001-Pg 171



A1001 A-Pg 172




A1001 B-Pg 172



A1001 C-Pg 172

A3300 Series1 1/4" x 3/4"
14 Ga.

A3300-Pg 173



A3301-Pg 173

Channel Nuts & Closures

A1006-1420-Pg 175



A4006-1420-Pg 175

A Series Fittings

A1063-Pg 175




A1065-Pg 175



A1191-Pg 175




A1066-Pg 176



A2324-Pg 176



A1036-Pg 176




A1031-Pg 176




A1026-Pg 176




A1068-Pg 176



A1326-Pg 176



A1458-Pg 176



A1325-Pg 176




A2110-Pg 176




A2126-Pg 176




A2084-Pg 176



A2472 R-L-Pg 176



A2223-Pg 176



A2345-Pg 176




A2227-Pg 176




A1047-Pg 177



A3347-Pg 177




A4047-Pg 177



A5047-Pg 177




A2608-Pg 177




A2492 R-Pg 177



A2492 L-Pg 177




A2494 R-Pg 177



A2494 L-Pg 177

A1000 - 1 1/4" x 1 1/4"



Wt/100 Ft: 104 Lbs(154 kg/100m)
 Allowable Moment 2,170 In-Lbs (240 N·m)
 14 Gauge Nominal Thickness .075" (1.9mm)

A1000 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Defl.		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
18	960	0.04	960	960	960
24	720	0.07	720	720	660
36	480	0.16	480	440	300
48	360	0.29	330	250	170
60	290	0.45	210	160	110
72	240	0.65	150	110	70
84	210	0.90	110	80	50
96	180	1.16	80	60	40
108	160	1.46	70	50	30
120	140	1.75	50	40	30


A1000 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
18	1,960	5,900	5,430	4,800	4,210
24	1,840	5,210	4,590	3,850	3,220
36	1,500	3,940	3,220	2,480	2,010
48	1,220	2,950	2,300	1,790	1,460
60	1,020	2,260	1,790	1,400	1,130
72	880	1,840	1,460	1,130	910
84	780	1,550	1,230	940	**
96	690	1,340	1,050	**	**
108	620	1,170	910	**	**

A1000/A1001 - ELEMENTS OF SECTION

Parameter	A1000	A1001
Area of Section	0.305	In ²
Axis 1-1		
Moment of Inertia (I)	0.061	In ⁴
Section Modulus (S)	0.086	In ³
Radius of Gyration (r)	0.447	In
Axis 2-2		
Moment of Inertia (I)	0.078	In ⁴
Section Modulus (S)	0.125	In ³
Radius of Gyration (r)	0.506	In

A1001 - 1 1/4" x 2 1/2"



Wt/100 Ft: 207 Lbs (308 kg/100m)
 Allowable Moment 6,070 In-Lbs (690 N·m)
 14 Gauge Nominal Thickness .075" (1.9mm)

A1001 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Defl.		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
18	1,650*	0.01	1,650*	1,650*	1,650*
24	1,650*	0.03	1,650*	1,650*	1,650*
36	1,350	0.09	1,350	1,350	1,350
48	1,010	0.16	1,010	1,010	820
60	810	0.26	810	790	530
72	670	0.37	670	550	370
84	580	0.50	540	400	270
96	510	0.66	410	310	210
108	450	0.83	330	240	160
120	400	1.01	260	200	130

A1001 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
18	3,530	13,300	12,920	12,400	11,880
24	3,480	12,750	12,220	11,550	10,950
36	3,370	11,630	10,950	10,220	9,150
48	3,260	10,680	10,020	8,260	6,500
60	2,960	9,930	8,260	6,080	4,270
72	2,630	8,480	6,500	4,270	2,970
84	2,260	7,040	4,900	3,140	2,180
96	1,940	5,680	3,750	2,400	**
108	1,670	4,490	2,970	**	**
120	1,440	3,640	2,400	**	**

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
2. Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 177 for reduction factors for unbraced lengths.
3. Deduct channel weight from the beam loads.
4. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
5. All beam loads are for bending about Axis 1-1.

A1000 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	3.2	2	3.2	3.2	3.1
750	2.6	3	2.6	2.6	2.0
1,000	2.0	5	2.0	1.6	1.1
1,250	1.6	8	1.4	1.1	0.7
1,500	1.3	11	1.0	0.7	0.5
1,750	1.1	15	0.7	0.5	0.4
2,000	1.0	20	0.5	0.4	0.3
2,500	0.8	32	0.4	0.3	0.2
3,000	0.7	46	0.2	0.2	0.1

A1001 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	7.3*	1	7.3*	7.3*	7.3
750	7.3*	2	7.3*	7.3*	7.3
1,000	5.5	3	5.5	5.5	5.5
1,250	4.4	4	4.4	4.4	3.5
1,500	3.6	6	3.6	3.6	2.4
1,750	3.2	9	3.2	2.7	1.8
2,000	2.8	11	2.7	2.0	1.4
2,500	2.2	17	1.7	1.3	0.9
3,000	1.8	25	1.2	0.9	0.6
3,500	1.6	34	0.9	0.7	0.4

A1000 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Max. Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	8.2	23.4	20.7	17.3	14.6
750	7.5	20.5	17.3	14.0	11.3
1,000	6.3	16.2	13.0	9.9	8.1
1,250	5.3	12.8	9.9	7.7	6.3
1,500	4.6	10.2	8.1	6.3	5.2
1,750	4.1	8.6	6.8	5.3	4.3
2,000	3.6	7.4	5.9	4.5	**
2,250	3.3	6.5	5.2	3.9	**
2,500	3.0	5.8	4.5	**	**
2,750	2.7	5.2	4.0	**	**

A1001 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Max. Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	15.5	56.9	54.5	51.6	48.9
750	15.2	54.4	51.6	48.4	45.7
1,000	14.9	50.4	47.4	43.9	37.4
1,250	14.4	47.2	43.9	35.7	27.8
1,500	13.3	44.6	37.4	27.8	19.6
1,750	12.1	39.4	30.9	20.7	14.4
2,000	10.8	34.1	24.8	15.9	11.0
2,250	9.5	29.0	19.6	12.5	**
2,500	8.4	24.1	15.9	10.2	**
2,750	7.4	19.9	13.1	**	**

Notes:

* Load limited by spot weld shear.

** KL/r > 200


NR = Not Recommended.

1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
2. Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 177 for reduction factors for unbraced lengths.
3. Deduct channel weight from the beam loads.
4. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
5. All beam loads are for bending about Axis 1-1.


Finishes: PL, GR, HG, PG Standard Lengths: 10' & 20'

A1000/A1001 - ELEMENTS OF SECTION (METRIC)


Parameter	A1000		A1001		
Area of Section	1.96	cm ²	3.93	cm ²	
Axis 1-1	Moment of Inertia (I)	2.53	cm ⁴	12.57	cm ⁴
	Section Modulus (S)	1.41	cm ³	3.96	cm ³
	Radius of Gyration (r)	1.14	cm	1.79	cm
Axis 2-2	Moment of Inertia (I)	3.25	cm ⁴	6.50	cm ⁴
	Section Modulus (S)	2.05	cm ³	4.09	cm ³
	Radius of Gyration (r)	1.29	cm	1.29	cm

A1001A - 1 1/4" x 2 1/2"


Wt/100 Ft: 207 Lbs (308 kg/100m)
 Allowable Moment 7,930 In-Lbs (900 N·m)
 14 Gauge Nominal Thickness .075" (1.9mm)


A1001B - 1 1/4" x 2 1/2"


Wt/100 Ft: 207 Lbs (308 kg/100m)
 Allowable Moment 7,930 In-Lbs (900 N·m)
 14 Gauge Nominal Thickness .075" (1.9mm)

A1001C - 1 1/4" x 2 1/2"



Wt/100 Ft: 207 Lbs (308 kg/100m)
 Allowable Moment 6,760 In-Lbs (760 N·m)
 14 Gauge Nominal Thickness .075" (1.9mm)

A3300 - 1 1/4" x 3/4"



Wt/100 Ft: 78 Lbs (116 kg/100m)
Allowable Moment 950 In-Lbs (110 N·m)
14 Gauge Nominal Thickness .075" (1.9mm)

A3301 - 1 1/4" x 1 1/2"



Wt/100 Ft: 156 Lbs (232 kg/100m)
Allowable Moment 2,590 In-Lbs (290 N·m)
14 Gauge Nominal Thickness .075" (1.9mm)

A3300 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
18	420	0.07	420	420	320
24	320	0.12	320	270	180
36	210	0.26	160	120	80
48	160	0.47	90	70	50
60	130	0.75	60	40	30
72	110	1.09	40	30	20
84	90	1.42	30	20	10
96	80	1.88	20	20	10

A3301 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
18	990*	0.03	990*	990*	990*
24	860	0.07	860	860	850
36	580	0.15	580	560	380
48	430	0.27	420	320	210
60	350	0.43	270	200	140
72	290	0.62	190	140	90
84	250	0.85	140	100	70
96	220	1.11	110	80	50

A3300 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Max. Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
18	1,430	4,490	4,210	3,860	3,550
24	1,370	4,090	3,750	3,310	2,680
36	1,190	3,390	2,680	1,820	1,260
48	900	2,380	1,600	1,020	**
60	680	1,550	1,020	**	**

A3301 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Max. Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
18	2,540	9,890	9,620	9,300	9,020
24	2,510	9,510	9,200	8,710	7,960
36	2,410	8,800	7,960	6,730	5,490
48	2,230	7,560	6,320	4,690	3,310
60	1,970	6,210	4,690	3,050	2,120
72	1,650	4,890	3,310	2,120	**
84	1,380	3,680	2,430	**	**
96	1,160	2,820	1,860	**	**

A3300/A3301 - ELEMENTS OF SECTION

Parameter	A3300		A3301		
Area of Section Axis 1-1	0.230	In ²	0.459	In ²	
Axis 2-2	Moment of Inertia (I)	0.017	In ⁴	0.077	In ⁴
	Section Modulus (S)	0.038	In ³	0.103	In ³
	Radius of Gyration (r)	0.269	In	0.411	In
Axis 2-2	Moment of Inertia (I)	0.052	In ⁴	0.104	In ⁴
	Section Modulus (S)	0.083	In ³	0.167	In ³
	Radius of Gyration (r)	0.477	In	0.477	In

Notes:

* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).

2. Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 177 for reduction factors for unbraced lengths.

3. Deduct channel weight from the beam loads.

4. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.

5. All beam loads are for bending about Axis 1-1.



A3300 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	1.4	3	1.4	1.2	0.8
750	1.2	5	1.1	0.8	0.5
1,000	0.8	8	0.6	0.4	0.3
1,250	0.7	12	0.4	0.3	0.2
1,500	0.6	18	0.3	0.2	0.1
1,750	0.5	24	0.2	0.1	0.1
2,000	0.4	33	0.1	0.1	0.1

A3301 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
600	3.9	2	3.9	3.9	3.9
750	3.1	3	3.1	3.1	2.5
1,000	2.4	5	2.4	2.1	1.4
1,250	1.9	7	1.8	1.3	0.9
1,500	1.6	10	1.2	0.9	0.6
1,750	1.3	14	0.9	0.7	0.4
2,000	1.2	18	0.7	0.5	0.4
2,500	0.9	29	0.4	0.4	0.2
3,000	0.8	43	0.3	0.2	0.1

A3300 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Max. Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	6.1	18.3	16.8	14.9	12.2
750	5.8	16.7	14.9	11.5	8.4
1,000	4.9	13.8	10.4	6.8	4.7
1,250	3.9	10.1	6.8	4.3	**
1,500	3.1	7.1	4.7	**	**

A3301 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Max. Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
600	11.2	42.4	41.0	39.0	35.7
750	11.0	40.9	39.0	34.9	30.4
1,000	10.5	37.7	33.4	27.4	21.4
1,250	9.8	33.0	27.4	20.0	14.0
1,500	8.9	28.1	21.4	14.0	9.7
1,750	7.7	23.2	16.1	10.3	**
2,000	6.7	18.6	12.3	7.9	**
2,250	5.8	14.7	9.7	**	**
2,500	5.0	11.9	7.9	**	**

A3300/A3301 - ELEMENTS OF SECTION (METRIC)

Parameter	A3300		A3301	
	1.48	cm ²	2.96	cm ²
Axis 1-1	Moment of Inertia (I)	0.69	cm ⁴	3.22 cm ⁴
	Section Modulus (S)	0.62	cm ³	1.69 cm ³
	Radius of Gyration (r)	0.68	cm	1.04 cm
	Moment of Inertia (I)	2.17	cm ⁴	4.34 cm ⁴
	Section Modulus (S)	1.37	cm ³	2.73 cm ³
	Radius of Gyration (r)	1.21	cm	1.21 cm

Notes:




* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.

1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
2. Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 177 for reduction factors for unbraced lengths.
3. Deduct channel weight from the beam loads.
4. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
5. All beam loads are for bending about Axis 1-1.

BEARING LOADS ON UNISTRUT CHANNEL

Loads are calculated based on 2001 Specification For The Design Of Cold Formed Steel Structural Members published by AISI			
Channel	Bearing Length 1 1/4" (31.8 mm) Maximum Allowable Loads - Lbs (kN)	Bearing Length 1 1/4" (31.8 mm) Maximum Allowable Loads - Lbs (kN)	Bearing Length 2 1/2" (63.5 mm) Maximum Allowable Loads - Lbs (kN)
A1000	3,700 (16.46)	1,700 (7.56)	4,300 (19.13)
A3300	3,800 (16.90)	1,700 (7.56)	4,300 (19.13)

CHANNEL NUT WITH SPRING



	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	A1006-1420	1/4" -20	6 (2.7)	A1000
	A1007	5/16" -18	6 (2.7)	
	A1008	3/8" -16	6 (2.7)	
	A4006-1420	1/4" -20	5 (2.3)	A3300
	A4007	5/16" -18	5 (2.3)	
	A4008	3/8" -16	5 (2.3)	

CHANNEL NUT WITHOUT SPRINGS

	Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	A3006-1420	1/4" -20	5 (2.3)	A1000 or A3300
	A3007	5/16" -18	5 (2.3)	
	A3008	3/8" -16	5 (2.3)	
	A3016-0832	#8 -32	1 (0.5)	A1000 or A3300
	A3016-1024	#10 -24	1 (0.5)	
	A3016-1032	#10 -32	1 (0.5)	
	A3016-1420	1/4" -20	1 (0.5)	

A1280

END CAP

A4280

END CAP

A1184

CLOSURE STRIP




Material: .075" (1.9)

Note: Use with A1000 channel

Wt/100 pcs: 7 Lbs (3.2 kg)

Material: .075" (1.9)

Note: Use with A3300 channel

Finish:
Perma-Green II (GR), Plain (PL).

Wt/100 Ft: 21 Lbs (31.3 kg/100M)

A1191


A1063




A1065

A1184P


CLOSURE STRIP




Wt/100 pcs: 87 Lbs (39.5 kg)



Wt/100 pcs: 8 Lbs (3.6 kg)



Wt/100 pcs: 17 Lbs (7.7 kg)



Standard length: 10 Ft.

Material: Paintable PVC.
Color: Green, Grey.


Wt/100 Ft: 21 Lbs (31.3 kg/100M)

Standard Dimensions for 1 1/4" (31.8 mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 13/32" (10.3mm); Hole Spacing - From End: 5/8" (15.9 mm); Hole Spacing - On Center: 1 1/2" (38.1mm); Width: 1 1/4"(31.8mm); Thickness: 3/16" (4.8mm)




A1066




Wt/100 pcs: 26 Lbs (11.8 kg)

A2324




Wt/100 pcs: 39 Lbs (17.7 kg)

A1036




Wt/100 pcs: 27 Lbs (12.2 kg)

A1031




Wt/100 pcs: 34 Lbs (15.4 kg)

A1026




Wt/100 pcs: 17 Lbs (7.7 kg)

A1068




Wt/100 pcs: 17 Lbs (7.7 kg)

A1326




Wt/100 pcs: 27 Lbs (12.2 kg)

A1458




Wt/100 pcs: 27 Lbs (12.2 kg)

A1325




Wt/100 pcs: 38 Lbs (17.2 kg)

A2110




Wt/100 pcs: 23 Lbs (10.4 kg)

A2126




Wt/100 pcs: 17 Lbs (7.7 kg)

A2084



Wt/100 pcs: 90 Lbs (40.8 kg)


A2472 R-L



R-As shown
L-Opposite hand


Wt/100 pcs: 33 Lbs (15.0 kg)

A2223




Wt/100 pcs: 34 Lbs (15.4 kg)

A2345



Wt/100 pcs: 41 Lbs (18.6 kg)

A2227




Wt/100 pcs: 52 Lbs (23.6 kg)

Standard Dimensions for 1 1/4" (31.8 mm) width series channel fittings (Unless Otherwise Shown on Drawing)


Hole Diameter: 1 3/32" (10.3mm); Hole Spacing - From End: 5/8" (15.9 mm); Hole Spacing - On Center: 1 1/2" (38.1mm); Width: 1 1/4"(31.8mm); Thickness: 3/16" (4.8mm)

A1047



Wt/100 pcs: 43 Lbs (19.5 kg)



A3347



Wt/100 pcs: 37 Lbs (16.8 kg)

A2608 THRU A2617


UNI-CLIP®



Part Number	Pipe Size In (mm)	O.D. Size In (mm)	Wt/100 pcs Lbs (kg)
A2608	1/4 (6.4)	0.540 (13.7)	0.6 (0.3)
A2609	5/16 (9.5)	0.675 (17.1)	0.7 (0.3)
A2611	1/2 (12.7)	0.840 (21.3)	1.0 (0.5)
A2612	3/4 (19.1)	1.050 (26.7)	1.4 (0.6)
A2613	1 (25.4)	1.35 (33.4)	2.0 (0.9)
A2614	1 1/4 (31.8)	1.660 (42.2)	2.4 (1.1)
A2615	1 1/2 (38.1)	1.900 (48.3)	3.2 (1.5)
A2617	2 (50.8)	2.375 (60.3)	4.7 (2.1)

Stainless steel, Type 301.

A2492 R-L



Right

Left

Design Uniform Load
(Channel Upright Listed)


A1000 200 Lbs (.89 kN)
A3300 130 Lbs (.58 kN)

Safety Factor of 2 1/2


Material: 14 Gauge Steel.

Wt/100 pcs: 56 Lbs (25.4 kg)

A2494 R-L



Right



Left

Design Uniform Load
(Channel Upright Listed)

A1000 200 Lbs (.89 kN)
A3300 130 Lbs (.58 kN)

Safety Factor of 2 1/2

Material: 14 Gauge Steel.

Wt/100 pcs: 94 Lbs (42.6 kg)


Standard Dimensions for 1 1/4" (31.8 mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 13/32" (10.3mm); Hole Spacing - From End: 5/8" (15.9 mm); Hole Spacing - On Center: 1 1/2" (38.1mm); Width: 1 1/4"(31.8mm); Thickness: 3/16" (4.8mm)



UNISTRUT®

13/16" FRAMING SYSTEM



MATERIAL

Channels are accurately and carefully cold formed to size from low-carbon strip steel.

STEEL: PLAIN

19 Gauge (1.0 mm) ASTM A1008

STEEL: PRE-GALVANIZED

19 Gauge (1.0 mm) ASTM A653 GR 33

All nuts are manufactured from mild steel bars conforming to ASTM A1011 SS Grade 33.

Fittings are made from hot rolled, pickled and oiled steel plate or strip and conform to ASTM A1011 SS GR 33.

FINISHES

Channels are available in: Perma-Green III (GR), electro-galvanized (EG), Pre-galvanized (PG), conforming to ASTM A653 GR 33 and plain (PL).

Nuts are available in plain or electro-galvanized (EG) finish.

Fittings are available in Perma-Green III, electrogalvanized (EG) with zinc electrolytically to commercial standards ASTM B653-G90 Type III SC1; or plain (PL).

STANDARD LENGTHS

P-6000 – 16 Feet (4.88m)

P-7000 – 10 Feet (3.05m)

Tolerances are $\pm\frac{1}{8}$ " (3.2 mm) to $\pm\frac{1}{2}$ " (12.7 mm) to allow for cutting. Special lengths are available for a small cutting charge with a tolerance of $\pm\frac{1}{8}$ " (3.2mm).

P6000 (19 Gauge)	179-181
P7000 (19 Gauge)	182-183
Channel Nuts, End Caps, and Closure Strips	184
Flat Plate Fittings	184-185
Ninety Degree Fittings.....	185
Angular Fittings, Wing Shape Fittings	186
"Z" Shape Fittings.....	186
"U" Shape Fittings	186-187
Special Application Fittings.....	187
Beam Clamps.....	187
Tubing Clips.....	187

APPLICATION

A unique half-size reduction of the 1 $\frac{5}{8}$ " channel width series, this smaller channel size can be used to carry light loads economically in applications such as instrumentation, retail displays and light-duty laboratory supports. It also provides the flexibility found in all Unistrut® framing systems.

DESIGN BOLT TORQUE

BOLT SIZE	1/4"-20	Rec. Torque Ft/Lbs (N•m)	6 (8)	Max Torque Ft/Lbs (N•m)	7 (9)
-----------	---------	-----------------------------	----------	----------------------------	----------


DIMENSIONS

Imperial dimensions are illustrated in inches. Metric dimensions are shown in parenthesis or as noted. Unless noted, all metric dimensions are in millimeters and rounded to one decimal place.

LOAD DATA

All beam and column load data pertains to carbon steel and stainless steel channels. Load tables and charts are constructed to be in accordance with the SPECIFICATION FOR THE DESIGN OF COLD-FORMED STEEL STRUCTURAL MEMBERS 2007 EDITION published by the AMERICAN IRON AND STEEL INSTITUTE USING ASD METHOD. Loads are based on 33 ksi steel cold formed to 42 ksi.

Type of Load	Safety Factor to Yield Strength	Safety Factor to Ultimate Strength
Beam Loads	1.67	2.0
Column Load	1.80	2.2

P6000 Series13/16" x 13/16"
19 Ga.

P6000 - Pg 180



P6001 - Pg 180




P6001 A - Pg 181




P6001 B - Pg 181



P6001 C - Pg 181

13/16" x 13/32"
19 Ga.

P7000 - Pg 182



P7001 - Pg 182

Channel Nuts & Closures**13/16" Series Fittings**

P6006-0832 - Pg 184



P7006-0832 - Pg 184



P6280 - Pg 184



P7280 - Pg 184



P6184P - Pg 184



P6062 - Pg 184



P6065 - Pg 184




P6924 - Pg 184




P7325 - Pg 184




P7324 - Pg 184




P6925 - Pg 184




P6066 - Pg 184




P6067 - Pg 184




P6962 - Pg 184




P6356 A - Pg 184




P6358 A - Pg 184



P6726 A - Pg 184



P6334 - Pg 184



P6380 - Pg 184




P6036 - Pg 184



P6380 A - Pg 184



P6031 - Pg 185



P6028 - Pg 185




P6026 - Pg 185



P6068 - Pg 185



P6281 - Pg 185



P6326 - Pg 185

P6346 - Pg 185



P6458 - Pg 185



P6325 - Pg 185



P6357 - Pg 185



P6359-Pg 185




P6579-Pg 185



P7235-Pg 185



P6887-Pg 185



P6331-Pg 185

P6332-Pg 186

P6546-Pg 186




P6045-Pg 186



P6186-Pg 186



P6454-Pg 186



P7045-Pg 186




P6453-Pg 186



P6047-Pg 186



P6737-Pg 186



P6048-Pg 186

P6376-Pg 186

P7376-Pg 186



P6376 A-Pg 186



P7376 A-Pg 186



P6377-Pg 186



P7377-Pg 186



P6455-Pg 187



P6973-Pg 187



P6349-Pg 187



P6127-Pg 187

P6386-Pg 187



P6379 S-Pg 187



P6805-Pg 187




P7008-Pg 187



P6000

CPG




Wt/100 Ft: 36 Lbs (54 kg/100 m)
 Allowable Moment: 510 In-Lbs (60 N·m)
 19 Gauge Nominal Thickness .040" (1.0 mm)

P6000 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
18	230	0.06	230	230	180
24	170	0.11	170	150	100
30	140	0.18	130	100	70
36	110	0.24	90	70	50
42	100	0.35	70	50	30
48	80	0.42	50	40	30
54	80	0.60	40	30	20
60	70	0.72	30	20	20
66	60	0.82	30	20	10
72	60	1.06	20	20	10

P6001



Wt/100 Ft: 73 Lbs (108 kg/100 m)
 Allowable Moment: 1,390 In-Lbs (160 N·m)
 19 Gauge Nominal Thickness .040" (1.0 mm)

P6001 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
18	620	0.04	620	620	620
24	460	0.06	460	460	460
30	370	0.10	370	370	320
36	310	0.14	310	310	220
42	270	0.20	270	240	160
48	230	0.25	230	180	120
54	210	0.32	190	150	100
60	190	0.40	160	120	80
66	170	0.48	130	100	70
72	150	0.55	110	80	50

P6000 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
18	600	1,660	1,400	1,100	860
24	490	1,300	1,010	740	590
30	420	990	740	560	450
36	340	770	590	450	370
42	300	630	490	380	310
48	260	540	420	330	270
54	240	470	370	290	**
60	210	410	330	**	**
66	210	370	300	**	**
72	180	340	270	**	**

P6001 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
18	1,210	4,320	4,080	3,770	3,500
24	1,170	3,980	3,680	3,330	3,060
30	1,130	3,650	3,330	3,000	2,460
36	1,070	3,370	3,060	2,460	1,800
42	1,020	3,140	2,690	1,900	1,320
48	900	2,930	2,230	1,460	1,010
54	820	2,550	1,800	1,150	800
60	700	2,180	1,460	930	**
66	700	1,830	1,210	770	**
72	550	1,530	1,010	**	**

P6000 & P6001 - ELEMENTS OF SECTION

Parameter	P6000	P6001
Area of Section	0.107	In ²
Axis 1-1		
Moment of Inertia (I)	0.009	In ⁴
Section Modulus (S)	0.020	In ³
Radius of Gyration (r)	0.295	In
Axis 2-2		
Moment of Inertia (I)	0.012	In ⁴
Section Modulus (S)	0.029	In ³
Radius of Gyration (r)	0.333	In

Notes:

* Load limited by spot weld shear.

** $KL/r > 200$

NR = Not Recommended.

- Beam loads are given in *total* uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 186 for reduction factors for unbraced lengths.
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P6000 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
300	1.5	1	1.5	1.5	1.5
450	1.0	2	1.0	1.0	0.8
600	0.8	3	0.8	0.7	0.5
750	0.6	4	0.6	0.4	0.3
1,000	0.4	7	0.4	0.3	0.2
1,250	0.4	11	0.2	0.2	0.1
1,500	0.3	17	0.1	0.1	0.1
1,750	0.3	24	0.1	0.1	0.0

P6001 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
300	2.9*	0	2.9*	2.9*	2.9*
450	2.8	1	2.8	2.8	2.8
600	2.1	2	2.1	2.1	2.1
750	1.7	2	1.7	1.7	1.5
1,000	1.2	4	1.2	1.2	0.8
1,250	1.0	7	1.0	0.8	0.5
1,500	0.8	10	0.7	0.5	0.4
1,750	0.7	13	0.5	0.4	0.3
2,000	0.6	17	0.4	0.3	0.2

P6000 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
300	3.1	9.2	8.4	7.3	6.3
450	2.7	7.5	6.3	5.0	3.9
600	2.2	5.9	4.6	3.4	2.7
750	1.8	4.5	3.4	2.5	2.0
1,000	1.4	3.0	2.4	1.8	1.5
1,250	1.1	2.3	1.8	1.4	1.2
1,500	0.9	1.9	1.5	1.2	**
1,750	0.8	1.6	1.2	**	**

P6001 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
300	5.5	20.7	20.1	19.2	18.2
450	5.4	19.3	18.2	16.9	15.7
600	5.2	17.8	16.5	14.9	13.7
750	5.0	16.4	14.9	13.5	11.2
1,000	4.6	14.4	12.9	9.5	6.7
1,250	3.9	12.7	9.5	6.2	4.3
1,500	3.2	9.9	6.7	4.3	**
1,750	2.6	7.5	4.9	**	**
2,000	2.2	5.7	3.8	**	**

P6000 & P6001 - ELEMENTS OF SECTION (METRIC)

Parameter	P6000		P6001	
	Area of Section Axis 1-1		cm ²	cm ²
Axis 2-2	Moment of Inertia (I)	0.39	cm ⁴	1.88 cm ⁴
	Section Modulus (S)	0.33	cm ³	0.91 cm ³
	Radius of Gyration (r)	0.75	cm	1.17 cm
	Moment of Inertia (I)	0.49	cm ⁴	0.99 cm ⁴
	Section Modulus (S)	0.48	cm ³	0.96 cm ³
	Radius of Gyration (r)	0.85	cm	0.85 cm

Notes:


* Load limited by spot weld shear.

** KL/r > 200

NR = Not Recommended.


- Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).
- Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 186 for reduction factors for unbraced lengths.
- Deduct channel weight from the beam loads.
- For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.
- All beam loads are for bending about Axis 1-1.

P6001A




Wt/100 Ft: 73 Lbs (108 kg/100 m)
 Allowable Moment 1,820 In-Lbs (210 N•m)
 19 Gauge Nominal Thickness .040" (1.0 mm)

P6001B



Wt/100 Ft: 73 Lbs (108 kg/100 m)
 Allowable Moment 1,820 In-Lbs (210 N•m)
 19 Gauge Nominal Thickness .040" (1.0 mm)

P6001C




Wt/100 Ft: 73 Lbs (108 kg/100 m)
 Allowable Moment 1,550 In-Lbs (180 N•m)
 19 Gauge Nominal Thickness .040" (1.0 mm)





P7000


CPG PL





Wt/100 Ft: 25 Lbs (38 kg/100m)
 Allowable Moment 170 In-Lbs (20 N·m)
 19 Gauge Nominal Thickness .040" (1.0 mm)



P7001



Wt/100 Ft: 50 Lbs (75 kg/100m)
 Allowable Moment 450 In-Lbs (50 N·m)
 19 Gauge Nominal Thickness .040" (1.0 mm)



P7000 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
18	80	0.12	60	50	30
24	60	0.22	40	30	20
30	50	0.36	20	20	10
36	40	0.50	20	10	10

P7001 - BEAM LOADING

Span In	Max Allowable Uniform Load Lbs	Defl. at Uniform Load In	Uniform Loading at Deflection		
			Span/180 Lbs	Span/240 Lbs	Span/360 Lbs
18	200	0.07	200	200	140
24	150	0.12	150	120	80
30	120	0.19	100	80	50
36	100	0.28	70	50	40
42	90	0.40	50	40	30
48	80	0.53	40	30	20

P7000 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
18	420	1,200	990	720	510
24	330	900	640	410	280
30	260	620	410	**	**
36	200	430	280	**	**

P7001 - COLUMN LOADING

Unbraced Height In	Maximum Allowable Load at Slot Face Lbs	Maximum Column Load Applied at C.G.			
		K = 0.65 Lbs	K = 0.80 Lbs	K = 1.0 Lbs	K = 1.2 Lbs
18	790	2,930	2,690	2,330	1,960
24	740	2,570	2,210	1,720	1,260
30	680	2,180	1,720	1,160	800
36	580	1,780	1,260	800	560
42	500	1,400	920	590	**
48	420	1,070	710	**	**
54	360	850	560	**	**

Notes:

* Load limited by spot weld shear.

** $KL/r > 200$

NR = Not Recommended.

1. Beam loads are given in total uniform load (W Lbs) not uniform load (w lbs/ft or w lbs/in).

2. Beam loads are based on a simple span and assumed to be adequately laterally braced. Unbraced spans can reduce beam load carrying capacity. Refer to Page 186 for reduction factors for unbraced lengths.

3. Deduct channel weight from the beam loads.

4. For concentrated midspan point loads, multiply beam loads by 50% and the corresponding deflection by 80%. For other load conditions refer to page 18.

5. All beam loads are for bending about Axis 1-1.

P7000 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
300	0.5	1	0.5	0.5	0.4
450	0.4	3	0.3	0.2	0.1
600	0.3	5	0.2	0.1	0.1
750	0.2	9	0.1	0.1	0.0
1,000	0.2	16	0.0	0.0	0.0
1,250	0.1	24	0.0	0.0	NR
1,500	0.1	28	0.0	NR	NR

P7001 - BEAM LOADING (METRIC)

Span mm	Max Allowable Uniform Load kN	Defl. at Uniform Load mm	Uniform Loading at Deflection		
			Span/180 kN	Span/240 kN	Span/360 kN
300	1.4	1	1.4	1.4	1.4
450	0.9	2	0.9	0.9	0.7
600	0.7	3	0.7	0.5	0.4
750	0.5	5	0.5	0.4	0.2
1,000	0.4	8	0.3	0.2	0.1
1,250	0.3	13	0.2	0.1	0.1
1,500	0.3	19	0.1	0.1	NR

P7000 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
300	2.1	6.4	6.0	5.3	4.5
450	1.9	5.4	4.5	3.3	2.3
600	1.5	4.1	2.9	1.9	1.3
750	1.2	2.8	1.9	1.2	**




P7001 - COLUMN LOADING (METRIC)

Unbraced Height mm	Maximum Allowable Load at Slot Face kN	Maximum Column Load Applied at C.G.			
		K = 0.65 kN	K = 0.80 kN	K = 1.0 kN	K = 1.2 kN
300	3.6	14.0	13.6	13.0	12.1
450	3.5	13.1	12.1	10.5	8.9
600	3.3	11.6	10.0	7.8	5.8
750	3.0	9.8	7.8	5.3	3.7
1,000	2.4	6.9	4.7	3.0	**
1,250	1.8	4.5	3.0	**	**

P7000 & P7001 - ELEMENTS OF SECTION (METRIC)

Parameter	P7000		P7001		
Area of Section	0.48	cm ²	0.96	cm ²	
Axis 1-1	Moment of Inertia (I)	0.07	cm ⁴	0.31	cm ⁴
	Section Modulus (S)	0.11	cm ³	0.30	cm ³
	Radius of Gyration (r)	0.38	cm	0.57	cm
	Moment of Inertia (I)	0.29	cm ⁴	0.58	cm ⁴
	Section Modulus (S)	0.28	cm ³	0.56	cm ³
	Radius of Gyration (r)	0.78	cm	0.78	cm

BEARING LOADS ON UNISTRUT CHANNEL

Loads are calculated based on 2001 Specification For The Design Of Cold Formed Steel Structural Members published by AISI			
	Bearing Length 13/16" (20.6 mm) Maximum Allowable Loads - Lbs (kN)	Bearing Length 13/16" (20.6 mm) Maximum Allowable Loads - Lbs (kN)	Bearing Length 13/16" (41.3 mm) Maximum Allowable Loads - Lbs (kN)
	P6000	1,000 (4.45)	500 (2.22)
Channel	P7000	1,000 (4.45)	500 (2.22)
			1,200 (5.34)

MAXIMUM ALLOWABLE PULL-OUT AND SLIP LOADS

Nut Size/ Thread	Max. Allowable Pull-Out Lbs (kN)	Resistance to Slip Lbs (kN)	Torque Ft-Lbs (N·m)
1/4"-20	250 1.11	150 0.67	6 8



P6006-0832 THRU P6006-1420
CHANNEL NUT W/SPRING



Part Number	Thread Size In	Wt/100 pcs Lbs (kg)
P6006-0836	#8 - 36	1 (0.5)
P6006-0832	#8 - 32	1 (0.5)
P6006-1032	#10 - 32	1 (0.5)
P6006-1024	#10 - 24	1 (0.5)
P6006-1420	1/4"- 20	1 (0.5)

P6013-0832 THRU P7006-1420
CHANNEL NUT




Part Number	Thread Size In	Wt/100 pcs Lbs (kg)
P6013-0836	#8 - 36	1 (0.5)
P6013-0832	#8 - 32	1 (0.5)
P6013-1032	#10 - 32	1 (0.5)
P6013-1024	#10 - 24	1 (0.5)
P6013-1420	1/4"- 20	1 (0.5)

P7006-0832 THRU P7006-1420
CHANNEL NUT W/SPRING



Part Number	Thread Size In	Wt/100 pcs Lbs (kg)
P7006-0836	#8 - 36	1 (0.5)
P7006-0832	#8 - 32	1 (0.5)
P7006-1032	#10 - 32	1 (0.5)
P7006-1024	#10 - 24	1 (0.5)
P7006-1420	1/4"- 20	1 (0.5)

P6184 P - CLOSURE STRIP



Material: PVC, Plastic.
Standard Length: 10 Feet (3.05 m).
Wt/100 Ft: 4 Lbs (6.0 kg/100m)

P6280 - END CAP FOR P6000



Material: .060" (1.5)

Wt/100 pcs: 3 Lbs (1.4 kg)


P7280 - END CAP FOR P7000




Material: .048" (1.2)

Wt/100 pcs: 1 Lbs (0.5 kg)

P6924




Wt/100 pcs: 5 Lbs (2.3 kg)




Wt/100 pcs: 7 Lbs (3.2 kg)

P6062




Wt/100 pcs: 2 Lbs (0.9 kg)

P6065




Wt/100 pcs: 5 Lbs (2.3 kg)

P6925




Wt/100 pcs: 7 Lbs (3.2 kg)

P6066




Wt/100 pcs: 8 Lbs (3.6 kg)

P6067




Wt/100 pcs: 11 Lbs (5.0 kg)

P6356A




Wt/100 pcs: 15 Lbs (6.8 kg)

P6358A




Wt/100 pcs: 22 Lbs (10.0 kg)

P6036




Wt/100 pcs: 8 Lbs (3.6 kg)

P6380A




Wt/100 pcs: 11 Lbs (5.0 kg)

P6962




Wt/100 pcs: 19 Lbs (8.6 kg)

P6334



Wt/100 pcs: 11 Lbs (5.0 kg)


P6380




Wt/100 pcs: 15 Lbs (6.8 kg)

Standard Dimensions for 13/16" (20.6mm) width series channel fittings (Unless Otherwise Shown on Drawing)


Hole Diameter: 5/32" (7.1mm); Hole Spacing - From End: 13/32" (10.3mm); Hole Spacing - On Center: 1 1/16" (27.0mm); Width: 13/16" (20.6mm); Thickness: 1/8" (3.2mm)

P6031


Wt/100 pcs: 11 Lbs (5.0 kg)

P6028


Wt/100 pcs: 14 Lbs (6.4 kg)

P6026

Wt/100 pcs: 5 Lbs (2.3 kg)


P6068

Wt/100 pcs: 5 Lbs (2.3 kg)


P6281 , P6282, P6283

Part Number	A In (mm)	Wt/100 pcs Lbs (kg)
P6281	2 50.8	8 3.6
P6282	2 1/2 63.5	9 4.1
P6283	3 76.2	10 4.5


Wt/100 pcs: 8 Lbs (3.6 kg)

P6069


Wt/100 pcs: 8 Lbs (3.6 kg)

P6326


Wt/100 pcs: 8 Lbs (3.6 kg)

P6346


Wt/100 pcs: 8 Lbs (3.6 kg)

P6458


Wt/100 pcs: 8 Lbs (3.6 kg)

P6325


Wt/100 pcs: 11 Lbs (5.0 kg)

P6357


Wt/100 pcs: 10 Lbs (4.5 kg)

P6359


Wt/100 pcs: 15 Lbs (6.8 kg)

P6579


Wt/100 pcs: 15 Lbs (6.8 kg)

P7235

Wt/100 pcs: 18 Lbs (8.2 kg)

P6887


Wt/100 pcs: 28 Lbs (12.7 kg)

P6331


Wt/100 pcs: 19 Lbs (8.6 kg)

Standard Dimensions for 13/16" (20.6mm) width series channel fittings (Unless Otherwise Shown on Drawing)


Hole Diameter: 9/32" (7.1mm); Hole Spacing - From End: 13/32" (10.3mm); Hole Spacing - On Center: 1 1/16" (27.0mm); Width: 13/16"(20.6mm); Thickness: 1/8" (3.2mm)




Wt/100 pcs: 19 Lbs (8.6 kg)



Wt/100 pcs: 8 Lbs (3.6 kg)




Wt/100 pcs: 7 Lbs (3.2 kg)




Wt/100 pcs: 8 Lbs (3.6 kg)

P6454




Wt/100 pcs: 5 Lbs (2.3 kg)

P7045




Wt/100 pcs: 6 Lbs (2.7 kg)

P6453




Wt/100 pcs: 9 Lbs (4.1 kg)

P6047, P7047




Part No.	A In (mm)	Wt/100 pcs	Use with Channel
P6047	13/16 20.6	12 5.4	P6000
P7047	13/32 10.3	10 4.5	P7000

P6737




Wt/100 pcs: 16 Lbs (7.3 kg)

P6048




Wt/100 pcs: 14 Lbs (6.4 kg)

P6376




Wt/100 pcs: 17 Lbs (7.7 kg)

P7376




Wt/100 pcs: 11 Lbs (5.0 kg)


P6376A




Wt/100 pcs: 26 Lbs (11.8 kg)



Wt/100 pcs: 16 Lbs (7.3 kg)



Wt/100 pcs: 36 Lbs (16.3 kg)



Wt/100 pcs: 24 Lbs (10.9 kg)

Standard Dimensions for 13/16" (20.6mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 5/32" (7.1mm); Hole Spacing - From End: 13/32" (10.3mm); Hole Spacing - On Center: 1 1/16" (27.0mm); Width: 13/16" (20.6mm); Thickness: 1/8" (3.2mm)

P6455


P6973

P6349


ACETAL SLIDE

P6353


ACETAL SLIDE




Wt/100 pcs: 8 Lbs (3.6 kg)



Wt/100 pcs: 8 Lbs (3.6 kg)




Wt/100 pcs: 1 Lbs (0.5 kg)



Wt/100 pcs: 1 Lbs (0.5 kg)

P6127 - P6129

BRACKET




Part No.	Uniform Design Load Lbs (kN)	"A" In (mm)	"B" In (mm)	"C" In (mm)	Wt/100 pcs Lbs (kg)
P6127	150	6 1/2	2 1/2	2 1/2	30
	0.67	165.1	63.5	63.5	13.6
P6128	150	8 1/2	3 1/4	3 1/2	40
	0.67	215.9	82.6	88.9	18.1
P6129	130.0	10 1/2	4	4 1/2	50
	0.58	266.7	101.6	114.3	22.7

Safety Factor 2 1/2

Wt/100 pcs: 4 Lbs (1.8 kg)

P6386

BEAM CLAMP




Requires 1/4" x 3/4" (6.4) x (19.1) Machine Screw and Channel Nut Not Included

Use in pairs.

P6379 S

BEAM CLAMP


Use in pairs.



Wt/100 pcs: 13 Lbs (5.9 kg)

P7008 THRU P7020

TUBING CLIPS



Part Number	O.D. Tube Size "A" In (mm)	Wt/100 pcs Lbs (kg)
P7008	1/4 6.4	1 0.45
P7009	5/16 7.9	1 0.45
P7010	3/8 9.5	2 0.91
P7012	1/2 12.7	2 0.91
P7014	5/8 15.9	3 1.4
P7016	3/4 19.1	4 1.8
P7018	7/8 22.2	5 2.3
P7020	1 25.4	5 2.3

Material: 16 Gauge (1.5)


Part Number	O.D. Tube Size "A" In (mm)	O.D. Tube Size "B" In (mm)	"C" In (mm)	Wt/100 pcs Lbs (kg)
P6805	1/4 6.4	1/4 6.4	3/4 19.1	1 0.5
P6806	3/8 9.5	3/8 9.5	1 25.4	2 0.9
P6807	1/2 12.7	1/2 12.7	1 31.8	3 1.4
P6808	1/4 6.4	3/8 9.5	7/8 22.2	2 0.9
P6809	1/4 6.4	1/2 12.7	1 25.4	2 0.9
P6810	3/8 9.5	1/2 12.7	1 1/8 28.6	3 1.4

Standard Dimensions for 13/16" (20.6mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 9/32" (7.1mm); Hole Spacing - From End: 13/32" (10.3mm); Hole Spacing - On Center: 1 1/16" (27.0mm); Width: 13/16" (20.6mm); Thickness: 1/8" (3.2mm)



UNISTRUT



FIBERGLASS SYSTEM

Heavy Duty Channel (Flange Profile)	190
Light Duty Channel (Flange Profile)	191
Heavy Duty Channel (SST Profile).....	192
Nuts & Hardware	193 - 195
Fittings.....	196 - 197
Pipe Clamps	198
Clevis Hangers and Channel Inserts	199
Beam Clamps.....	200
Power Rack Stanchions	200
Chemical Compatibility	201 - 202
Specifications	203

POLYESTER AND VINYL ESTER MATERIALS

Polyester and vinyl ester channels are manufactured from the pultrusion process and are color coded gray and beige respectively. Components are made by reinforcing a polymer resin (polyester or vinyl ester) with multiple strands of glass filament, alternating layers of glass mat and U.V. resistant surfacing veils. The glass is drawn through the liquid resin, which coats and saturates the fibers. The combination of resin, glass and veil is then continuously guided and pulled (pultruded) through a heated die that determines the shape of the component.

In the die, the resin is cured to form a reinforced part which can be cut to length. The hardened fiberglass pultrusion is reinforced with an internal arrangement of permanently bonded continuous glass fibers to increase its strength.

INSTALLATION

Fabrication requires just three simple operations: cutting, drilling and sealing as described below.

Cutting – Hand held saws, such as hack saws (24 to 32 teeth per inch) are suitable when a few cuts are required. For frequent cutting, a circular power saw with a carbide-tipped masonry blade yields the best results. When using a power saw, dust filter masks, gloves and long sleeve clothing should be worn.

Drilling – Any standard twist bit, even when used with battery-powered drills will work well. Carbide-tipped drill bits are recommended.

Sealing – To protect against future migration of corrosive elements into the cut sections, all cuts and holes should be properly sealed with clear urethane sealer.


OPERATING ENVIRONMENT

Temperature Ranges – Fiberglass parts are supplied in five different materials covering distinct temperature ranges. The temperature ranges indicated are meant to be used only as a general guideline. Continual exposure to elevated temperatures reduces the strength properties of plastics and glass-reinforced fiberglass. Actual resin test data confirms that a 50% reduction in strength occurs at the extreme high temperature levels.


Chemical Resistance – See the chart on page 204-205 for corrosion resistance. The results are based upon immersion for a 24 hour period. This is typically the "worst case" exposure to corrosion. Less severe contact such as spills, splashes and vapor condensate will exceed the performance results listed in the table.

Loading – Channel loading is defined with description of each type of channel. Additional loading and design limitations for fittings and accessories are described in the appropriate section for that part.


Material Temperature Ratings		
Material Code	Low Temp.	High Temp.
E - (Rigid PVC)	-25°F (-31°C)	130°F (54°C)
P - (Poly/Glass)	-35°F (-37°C)	200°F (93°C)
V - (Vinyl/Glass)	-35°F (-37°C)	200°F (93°C)
PU - (Poly)	-40°F (-40°C)	140°F (60°C)
N - (Nylon)	-20°F (-29°C)	150°F (66°C)

Channel - Aickinstrut Flange Profile


**Heavy Duty
Aickinstrut
Flange Profile
1 5/8" x 1 5/8"**




20P/V-2000-Pg 190



20P/V-2100-Pg 190




20P/V-2200-Pg 190




20P/V-2300-Pg 190

**Light Duty
Aickinstrut
Flange Profile
1 1/2" x 1 1/8"**




20P/V-1000-Pg 191




20P/V-1100-Pg 191




20P/V-1200-Pg 191




20P/V-1300-Pg 191

Channel - SST Profile

**Heavy Duty
SST Profile
1 5/8" x 1 5/8"**




20P/V-2000 SST-Pg 192



20P/V-2100 SST-Pg 192



20P/V-2200 SST-Pg 192




20P/V-2300 SST-Pg 192

Hardware & Accessories


Heavy Duty-Pg 193



Standard Duty-Pg 193



Saddle Clip-Pg 193



Stop Lock-Pg 193

Hex Flange Bolt-Pg 193

Hex Bolt-Pg 194

Hex Flange Nut-Pg 194


Hex Nut - Pg 194

Flat Washer-Pg 194

Spacer - Pg 194

Threaded Rod - Pg 195

Rod Coupler-Pg 195

Fittings

End Cap-Pg 195

Capping Strip-Pg 195

U-Bolt-Pg 195

20P/V-2500-Pg 196

20P/V-2502-Pg 196

20P/V-2504-Pg 196

20P/V-2506-Pg 196

20P/V-2508-Pg 196

20P/V-2510-Pg 196

20P/V-2512-Pg 196

20P/V-2514-Pg 196

20P/V-2516-Pg 196

20P/V-2518-Pg 196

20P/V-2520-Pg 196

20P/V-2522-Pg 196

20P/V-2524-Pg 196

20P/V-2526-Pg 197

20P/V-2528-Pg 197

20P/V-2530-Pg 197

20P/V-2534-Pg 197

20P/V-2540-Pg 197


20PU-2538-Pg 197

20PU-2611-Pg 197

20PU-2613-Pg 197

50PU-1508

50PU-2008-Pg 197

Pipe Clamps, Beam Clamps and Stanchions

50PU-2045-Pg 197

50PU-2636-Pg 197

50PU-2090-Pg 197

50PU-2616-Pg 197

20PU-5853

20PU-5855-Pg 197

20PU-5903

20PU-5095-Pg 197

Adj. Pipe Clamp-Pg 198

Rigid Pipe Clamp-Pg 198

Pipe Strap-Pg 198

Fabricated Clevis Hanger-Pg 199

Molded Clevis Hanger-Pg 199

Channel Insert-Pg 199

Molded Beam Clamp Assembly-Pg 200



Molded Beam Clamp-Pg 200

Rack Stanchion-Pg 200



20P-2000, 20V-2000


HEAVY DUTY SINGLE CHANNEL - AICKINSTRUT FLANGE PROFILE



Wt/100 Ft: 82 Lbs(122 kg/100 m)

SECTION PROPERTIES

Part Number	Weight lbs./ft. (kg/m)	Area in ² (mm ²)	X - X Axis			Y - Y Axis		
			I in ⁴ (mm ⁴)	R in (mm)	C1 in (mm)	I in ⁴ (mm ⁴)	R in (mm)	C in (mm)
20P-2000, 20V-2000	0.82	1.06	0.31	0.54	0.7	0.93	0.42	0.63
20P-2000, 20V-2000	1.2	6.8	12.9	13.7	17.8	23.622	17.5	16.0
20P-2100, 20V-2100	1.64	2.12	1.77	0.91	1.63	1.63	0.85	0.63
20P-2100, 20V-2100	2.4	13.7	73.7	23.1	41.4	41.402	35.4	16.0



Wt/100 Ft: 164 Lbs (244 kg/100 m)

FLANGE LOADING


Part Number	Pull-Out Strength* Lbs (kN)
20V-2000/2100	449 2.0
20P-2000/2100	360 1.6



*Values shown represent a 3:1 safety factor

20P-2200, 20V-2200

SLOTTED CHANNEL



Wt/100 Ft: 82 Lbs (122 kg/100 m)



20P-2000, 20V-2000

CHANNEL BEAM/COLUMN LOADING

Span In (mm)	Max. Uniform Beam Load (Safety Factor - 3:1)		Uniform Load at Deflection of 1/360 Span			Maximum Column Load Lbs (kN)
	Load Lbs (kN)	Deflection In (mm)	Load Lbs (kN)	Deflection In (mm)	Column Load Lbs (kN)	
12	3,561	0.102	1,159	0.033	5,160	
304.8	15.8	2.6	5.2	0.8	23.0	
18	2,374	0.23	515	0.05	4,704	
457.2	10.6	5.8	2.3	1.3	20.9	
24	1,781	0.41	290	0.067	4,168	
609.6	7.9	10.4	1.3	1.7	18.5	
30	1,424	0.64	185	0.083	3,553	
762.0	6.3	16.3	0.8	2.1	15.8	
36	1,187	0.922	129	0.1	2,859	
914.4	5.3	23.4	0.6	2.5	12.7	
48	890	1.638	72	0.133	1,636	
1,219.2	4.0	41.6	0.3	3.4	7.3	
60	712	2.56	46	0.167	1,047	
1,524.0	3.2	65	0.2	4.2	4.7	
72	594	3.686	32	0.2	727	
1,828.8	2.6	93.6	0.1	5.1	3.2	

20P-2300, 20V-2300

w/CONCRETE INSERT



Wt/100 Ft: 88 Lbs (131 kg/100 m)

20P-2100, 20V-2100

CHANNEL BEAM/COLUMN LOADING



Span In (mm)	Max. Uniform Beam Load (Safety Factor - 3:1)		Uniform Load at Deflection of 1/360 Span			Maximum Column Load Lbs (kN)
	Load Lbs (kN)	Deflection In (mm)	Load Lbs (kN)	Deflection In (mm)	Column Load Lbs (kN)	
12	5,559	0.028	5,559	0.033	9,454	
304.8	24.7	0.7	24.7	0.8	42.1	
18	3,706	0.064	2,914	0.05	8,866	
457.2	16.5	1.6	13.0	1.3	39.4	
24	2,780	0.113	1,639	0.067	8,181	
609.6	12.4	2.9	7.3	1.7	36.4	
30	2,224	0.177	1,049	0.083	7,405	
762.0	9.9	4.5	4.7	2.1	32.9	
36	1,853	0.254	730	0.1	6,451	
914.4	8.2	6.5	3.2	2.5	28.7	
48	1,390	0.452	410	0.133	4,534	
1,219.2	6.2	11.5	1.8	3.4	20.2	
60	1,112	0.707	262	0.167	2,902	
1,524.0	4.9	18.0	1.2	4.2	12.9	
72	927	1.018	182	0.2	2,015	
1,828.8	4.1	25.9	0.8	5.1	9.0	

Light Duty Channel - Aickinstrut flange Profile

UNISTRUT®

20P-1000, 20V-1000



LIGHT DUTY SINGLE CHANNEL - AICKINSTRUT FLANGE PROFILE



Wt/100 Ft: 47 Lbs (70 kg/100 m)

20P-1100, 20V-1100

LIGHT DUTY BACK-TO-BACK CHANNEL - AICKINSTRUT FLANGE PROFILE



Wt/100 Ft: 94 Lbs (140 kg/100 m)

SECTION PROPERTIES

Part Number	Weight lbs./ft. (kg/m)	Area in ² (mm ²)	X - X Axis			Y - Y Axis		
			I in ⁴ (mm ⁴)	R in (mm)	C1 in (mm)	C2 in (mm)	I in ⁴ (mm ⁴)	R in (mm)
20P-1000, 20V-1000	0.47	0.61	0.1	0.4	0.51	0.62	0.22	0.6
	0.7	3.9	4.2	10	13	16	9.2	15
20P-1100, 20V-1100	0.94	1.22	0.42	0.59	1.13	1.13	0.44	0.6
	1.4	7.9	17.5	15	29	28	18.3	15

FLANGE LOADING


Part Number	Pull-Out Strength* Lbs (kN)
20V-1000/1100	213 1.0
20P-1000/1100	213 1.0



*Values shown represent a 3:1 safety factor

20P-1200, 20V-1200

SLOTTED CHANNEL





Slots are 1" (25.4) x 7/16" (11.1)

2" (50.8) on Center

Wt/100 Ft: 47 Lbs (70 kg/100 m)

20P-1300, 20V-1300

w/CONCRETE INSERT



Wt/100 Ft: 53 Lbs (79 kg/100 m)

20P-1000, 20V-1000



CHANNEL BEAM/COLUMN LOADING

20P-1100, 20V-1100


CHANNEL BEAM/COLUMN LOADING

Span In (mm)	Max. Uniform Beam Load (Safety Factor - 3:1)		Uniform Load at Deflection of 1/360 Span			Maximum Column Load Lbs (kN)
	Load Lbs (kN)	Deflection In (mm)	Load Lbs (kN)	Deflection In (mm)	Load Lbs (kN)	
12	1,629	0.151	359	0.033	2,759	
304.8	7.2	3.8	1.6	0.8	12.3	
18	1,086	0.340	160	0.050	2,351	
457.2	4.8	8.6	0.7	1.3	10.5	
24	815	0.605	90	0.067	1,862	
609.6	3.6	15.4	0.4	1.7	8.3	
30	652	0.945	57	0.083	1,298	
762.0	2.9	24.0	0.3	2.1	5.8	
36	543	1.360	40	0.100	901	
914.4	2.4	34.5	0.2	2.5	4.0	
48	407	2.418	22	0.133	507	
1,219.2	1.8	61.4	0.1	3.4	2.3	
60	326	3.779	14	0.167	324	
1,524.0	1.5	96.0	0.1	4.2	1.4	
72	272	5.441	10	0.200	225	
1,828.8	1.2	138.2	0.0	5.1	1.0	



Span In (mm)	Max. Uniform Beam Load (Safety Factor - 3:1)		Uniform Load at Deflection of 1/360 Span			Maximum Column Load Lbs (kN)
	Load Lbs (kN)	Deflection In (mm)	Load Lbs (kN)	Deflection In (mm)	Load Lbs (kN)	
12	3,804	0.082	1,556	0.033	5,961	
304.8	16.9	2.1	6.9	0.8	26.5	
18	2,536	0.183	691	0.05	5,509	
457.2	11.3	4.6	3.1	1.3	24.5	
24	1,902	0.326	389	0.067	4,979	
609.6	8.5	8.3	1.7	1.7	22.1	
30	1,522	0.509	249	0.083	4,375	
762.0	6.8	12.9	1.1	2.1	19.5	
36	1,268	0.734	173	0.1	3,698	
914.4	5.6	18.6	0.8	2.5	16.4	
48	951	1.304	97	0.133	2,254	
1,219.2	4.2	33.1	0.4	3.4	10.0	
60	761	2.038	62	0.167	1,442	
1,524.0	3.4	51.8	0.3	4.2	6.4	
72	634	2.935	43	0.2	1,001	
1,828.8	2.8	74.5	0.2	5.1	4.5	

20P-2000 SST, 20V-2000 SST
HEAVY DUTY SINGLE CHANNEL - SST PROFILE



Wt/100 Ft: 82 Lbs (122 kg/100 m)

20P-2200 SST, 20V-2200 SST
SLOTTED CHANNEL

Slots are 1" (25.4) x 7/16" (11.1)
2" (50.8) on Center

Wt/100 Ft: 82 Lbs (122 kg/100 m)

20P-2100 SST, 20V-2100 SST
HEAVY DUTY BACK-TO-BACK CHANNEL - SST PROFILE


Wt/100 Ft: 164 Lbs (244 kg/100 m)

20P-2300 SST, 20V-2300 SST
w/CONCRETE INSERT


Wt/100 Ft: 88 Lbs (131 kg/100 m)

NOTE: Unistrut SST Channel is not compatible with the Unistrut fiberglass pipe clamps and channel nuts shown in this catalog. Metal clamps and channel nuts are compatible with this profile and are shown elsewhere in this catalog.


20P-2000 SST, F20V-2000 SST
CHANNEL BEAM/COLUMN LOADING

Span In (mm)	Maximum Uniform Beam Load (Safety Fac- tor - 3:1)		Deflection @ Max. Allowable Beam Load		Deflection @ Max. Deflection = 0.25 In (Lbs)		Uniform Load @ Max. Deflection = 0.50 In (Lbs)		Max. Column Load Lbs (kN)
	Poly Lbs (kN)	Vinyl Lbs (kN)	Poly In (mm)	Vinyl In (mm)	Poly Lbs (kN)	Vinyl Lbs (kN)	Poly Lbs (kN)	Vinyl Lbs (kN)	
12	1,720	2,150	0.07	0.07	—	—	—	—	3,650
304.8	7.6	9.6	1.8	1.8	—	—	—	—	16.2
18	1,150	1,440	0.15	0.17	—	—	—	—	3,370
457.2	5.1	6.4	3.8	4.3	—	—	—	—	15.0
24	860	1,080	0.27	0.3	810	910	—	—	2,960
609.6	3.8	4.8	6.9	7.6	3.6	4.0	—	—	13.2
30	690	870	0.42	0.48	410	460	—	—	2,450
762.0	3.1	3.9	10.7	12.2	1.8	2.0	—	—	10.9
36	580	730	0.61	0.69	240	270	480	540	1,800
914.4	2.6	3.2	15.5	17.5	1.1	1.2	2.1	2.4	8.0
48	430	540	1.07	1.2	100	115	200	230	1,010
1,219.2	1.9	2.4	27.2	30.5	0.4	0.5	0.9	1.0	4.5
60	350	440	1.7	1.91	60	70	120	135	260
1,524.0	1.6	2.0	43.2	48.5	0.3	0.3	0.5	0.6	1.2
72	290	370	2.44	2.78	30	34	60	70	NR
1,828.8	1.3	1.6	62.0	70.6	0.1	0.2	0.3	0.3	NR

20P-2100 SST, F20V-2100 SST
CHANNEL BEAM/COLUMN LOADING

Span In (mm)	Maximum Uniform Beam Load (Safety Fac- tor - 3:1)		Deflection @ Max. Allowable Beam Load		Deflection @ Max. Deflection = 0.25 In (Lbs)		Uniform Load @ Max. Deflection = 0.50 In (Lbs)		Max. Column Load Lbs (kN)
	Poly Lbs (kN)	Vinyl Lbs (kN)	Poly In (mm)	Vinyl In (mm)	Poly Lbs (kN)	Vinyl Lbs (kN)	Poly Lbs (kN)	Vinyl Lbs (kN)	
12	5,080	6,350	0.04	0.04	—	—	—	—	7,300
304.8	22.6	28.2	1.0	1.0	—	—	—	—	32.5
18	3,390	4,240	0.09	0.1	—	—	—	—	6,740
457.2	15.1	18.9	2.3	2.5	—	—	—	—	30.0
24	2,540	3,180	0.16	0.17	—	—	—	—	5,920
609.6	11.3	14.1	4.1	4.3	—	—	—	—	26.3
30	2,040	2,550	0.24	0.27	—	2,350	—	—	4,900
762.0	9.1	11.3	6.1	6.9	—	10.5	—	—	21.8
36	1,700	2,130	0.35	0.39	1,220	1,370	—	—	3,600
914.4	7.6	9.5	8.9	9.9	5.4	6.1	—	—	16.0
48	1,270	1,590	0.62	0.69	520	590	1,040	1,170	2,020
1,219.2	5.6	7.1	15.7	17.5	2.3	2.6	4.6	5.2	9.0
60	1,020	1,280	0.97	1.09	270	310	540	610	520
1,524.0	4.5	5.7	24.6	27.7	1.2	1.4	2.4	2.7	2.3
72	850	1,070	1.4	1.57	160	180	320	360	NR
1,828.8	3.8	4.8	35.6	39.9	0.7	0.8	1.4	1.6	NR

HEAVY DUTY CHANNEL NUTS




- Heavy duty channel nuts are designed to be used where high thread shear values or spring nuts are required. They can not be used with light duty 1000 series channel or SST profile channel.
- Material: glass-reinforced polyurethane.

Part Number	Size	Thread Shear Lbs (kN)*	Torque Ft/Lbs (N·m)	Wt/100 pcs Lbs (kg)
375PU-CNHD	3/8"-16	1,400	8	5.7
		6.23	11	2.6
500PU-CNHD	1/2"-13	1,400	8	5.3
		6.23	11	2.4
625PU-CNHD	5/8"-11	1,400	10	5.1
		6.23	14	2.3
750PU-CNHD	3/4"-10	1,400	10	4.4
		6.23	14	2.0
10PU-CNMHD	10 mm	1,400	8	5.8
		6.23	11	2.6
12PU-CNMHD	12 mm	1,400	8	5.5
		6.23	11	2.5
16PU-CNMHD	16 mm	1,400	10	5.3
		6.23	14	2.4
20PU-CNMHD	20 mm	1,400	10	4.4
		6.23	14	2.0

*Thread shear values shown represent a 3:1 safety factor.


SADDLE CLIPS



- Saddle clips mate with the exterior of the channel flanges and are secured with threaded rods and nuts.
- Material: glass-reinforced polyurethane.

Part Number	Size (In.)	Wt/100 pcs Lbs (kg)
200-4226	3/8	3.5
		1.6
200-4217	1/2	2.5
		1.1
200-4341	5/8	3.0
		1.4
200-4342	3/4	2.5
		1.1

STOP-LOCK ASSEMBLIES




- Stop-Lock Assemblies reduce the chance of pipe slippage when running supports vertically and are recommended for applications that are subject to vibration, have regular contact with fluids or are vertically mounted. The Stop-Locks fit both sizes of channel.
- Material: glass-reinforced polyurethane.

Part Number	Size (in.)	Force Resistance Lbs (kN)*	Torque Ft/Lbs (N·m)	Wt/100 pcs Lbs (kg)
200-4227	3/8"	200	7	6.3
		0.9	9	2.9
200-4219	1/2"	220	12	6.4
		1.0	16	2.9
200-4343	5/8***	250	15	11.0
		1.1	20	5.0

* Force resistance values shown represents a 3:1 safety factor.

** Supplied with a heavy duty channel nut for use only with the heavy duty series 2000 channel.

STANDARD DUTY CHANNEL NUTS




- Standard Duty channel nuts are designed for light duty applications that do not require high thread shear values. They can be used with both light duty series 1000 and heavy duty series 2000 fiberglass channel.
- Not for use with SST profile channel.
- Material: glass-reinforced polyurethane.

Part Number	Size	Thread Shear Lbs (kN)*	Torque Ft/Lbs (N·m)	Wt/100 pcs Lbs (kg)
250PU-CN	1/4"-20	460	2	1.8
		2.05	3	0.8
312PU-CN	5/16"-18	460	2	1.7
		2.05	3	0.8
375PU-CN	3/8"-16	460	3	1.8
		2.05	4	0.8
500PU-CN	1/2"-13	460	3	1.4
		2.05	4	0.6
10PU-CN	10 mm	460	3	1.7
		2.05	4	0.8
12PU-CN	12 mm	460	3	1.4
		2.05	4	0.6
10PU-CNS	#10 Screw	460	N/A	1.9
		2.05		0.9

*Thread shear values shown represent a 3:1 safety factor.

HEX FLANGE BOLTS




- Fiberfast bolts are ideal for mechanical connections that require a high degree of corrosion resistance. The 3/8" diameter fasteners are recommended for all channel fitting mechanical connections.
- Material: glass-reinforced polyurethane.

Part Number	Size (in.)	Thread Shear Lbs (kN)*	Shank Shear Lbs (kN)*	Shoulder Length In (mm)	Torque Ft/Lbs (N·m)	Wt/100 pcs Lbs (kg)
250PU-075	1/4 x 3/4	110	210	Full Thread	0.8	.4
		0.49	0.93		1	0.2
250PU-100	1/4 x 1	110	210	Full Thread	0.8	.5
		0.49	0.93		1	.02
250PU-150	1/4 x 1 1/2	110	210	1/2	0.8	.6
		0.49	0.93		12.7	0.3
500PU-125	1/2 x 1 1/4	450	870	Full Thread	8	1.0
		2.00	3.87		11	0.5
500PU-150	1/2 x 1 1/2	450	870	Full Thread	8	1.1
		2.00	3.87		11	.05
500PU-200	1/2 x 2	450	870	3/4	8	1.3
		2.00	3.87		19.1	0.6
500PU-250	1/2 x 2 1/2	450	870	Full Thread	8	1.6
		2.00	3.87		11	0.7
500PU-300	1/2 x 3	450	870	1	8	1.8
		2.00	3.87		25.4	11
500PU-350	1/2 x 3 1/2	450	870	2 1/16	8	2.0
		2.00	3.87		55.6	11

*Thread shear values shown represent a 3:1 safety factor.



HEX BOLTS



- Fiberfast bolts are ideal for mechanical connections that require a high degree of corrosion resistance. The $\frac{3}{8}$ " diameter fasteners are recommended for all channel fitting mechanical connections.
- Material: glass-reinforced polyurethane.


Part Number	Size (in.)	Thread Shear Lbs (kN)*	Shank Shear Lbs (kN)*	Shoulder Length In (mm)	Torque Ft/Lbs (Nm)	Wt/100 pcs Lbs (kg)
375PU-125	$\frac{3}{8} \times 1\frac{1}{4}$	250 1.11	470 2.09	Full Thread	3 4	1.0 0.5
375PU-150	$\frac{3}{8} \times 1\frac{1}{2}$	250 1.11	470 2.09	$\frac{1}{4}$ 6.4	3 4	1.1 0.5
375PU-200	$\frac{3}{8} \times 2$	250 1.11	470 2.09	$\frac{1}{2}$ 12.7	3 4	1.3 0.6
375PU-250	$\frac{3}{8} \times 2\frac{1}{2}$	250 1.11	470 2.09	$\frac{3}{4}$ 19.1	3 4	1.6 0.7
375PU-300	$\frac{3}{8} \times 3$	250 1.11	470 2.09	1	3 4	1.8 0.8
625PU-125	$\frac{5}{8} \times 1\frac{1}{4}$	700 3.11	1,360 6.05	$\frac{1}{4}$ 6.4	12 16	2.5 1.1
625PU-150	$\frac{5}{8} \times 1\frac{1}{2}$	700 3.11	1,360 6.05	$\frac{1}{4}$ 6.4	12 16	2.8 1.3
625PU-200	$\frac{5}{8} \times 2$	700 3.11	1,360 6.05	$\frac{1}{4}$ 6.4	12 16	3.2 1.5
625PU-250	$\frac{5}{8} \times 2\frac{1}{2}$	700 3.11	1,360 6.05	$\frac{1}{4}$ 6.4	12 16	3.4 1.5
625PU-300	$\frac{5}{8} \times 3$	700 3.11	1,360 6.05	$\frac{1}{4}$ 6.4	12 16	3.9 1.8
625PU-350	$\frac{5}{8} \times 3\frac{1}{2}$	700 3.11	1,360 6.05	$\frac{1}{4}$ 6.4	12 16	5.5 2.5

*Thread shear values shown represent a 3:1 safety factor.

FLAT WASHERS

Material: PVC

Note: PVC washers are recommended for connections that utilize hex nuts and bolts.



Part Number	Size (in.)	Outside Diameter In (mm)	Wt/100 pcs Lbs (kg)
250E-999	$\frac{1}{4}$	0.49 12	0.1 0.05
375E-999	$\frac{3}{8}$	1.00 25	0.1 0.05
500E-999	$\frac{1}{2}$	1.25 32	0.5 0.2
625E-999	$\frac{5}{8}$	1.50 38	0.5 0.2
750E-999	$\frac{3}{4}$	1.50 38	1.0 0.5
1000E-999	1	2.25 57	1.5 0.7

HEX FLANGE NUTS



- The hex flange nut is preferred for applications that require additional thread engagement (such as with all-thread rod) or maximum thread shear strength.
- Material: glass-reinforced polyurethane.

Part Number	Size (in.)	Thread Shear Lbs (kN)*	Height In (mm)	Torque Ft/Lbs (Nm)	Wt/100 pcs Lbs (kg)
375PU-FN-000	$\frac{3}{8}-16$	500 2.22	0.750 19.1	3 4	0.8 0.4
500PU-FN-000	$\frac{1}{2}-13$	1,200 5.34	0.855 21.7	8 11	1.6 0.7
625PU-FN-000	$\frac{5}{8}-11$	2,200 9.79	1.220 31.0	12 16	3.5 1.6
750PU-FN-000	$\frac{3}{4}-10$	2,900 12.90	1.590 40.4	15 20	5.5 2.5

*Thread shear values shown represent a 3:1 safety factor.


HEX NUTS




Part Number	Size (in.)	Thread Shear Lbs (kN)*	Height In (mm)	Torque Ft/Lbs (Nm)	Wt/100 pcs Lbs (kg)
250PU-000	$\frac{1}{4}-20$	150 0.67	0.218 5.5	0.8 1	0.1 0.05
375PU-000	$\frac{3}{8}-16$	460 2.05	0.328 8.3	3 4	0.3 0.1
500PU-000	$\frac{1}{2}-13$	800 3.56	0.437 11.1	8 11	0.5 0.2
625PU-000	$\frac{5}{8}-11$	1,000 4.45	0.546 13.9	12 16	1.5 0.7

*Thread shear values shown represent a 3:1 safety factor.

50PU-500SP




- Channel spacers are designed to prevent wall compression under heavy loading conditions. Such loading occurs during the torquing of hardware for channel fittings.
- The spacers are designed to be used only with $1\frac{1}{8}$ " channels and will accommodate $\frac{3}{8}$ " and $\frac{1}{2}$ " bolts.
- Material: molded from polyurethane



Wt/100 pcs: 2.0 Lbs (.91 kg)

THREADED ROD




Material: pultruded vinyl ester resin
and is gray in color.

* Thread shear values shown represent a 3:1 safety factor.

** Standard lengths are 4' and 8'. The part number shown is for 4' lengths. To order eight foot lengths, add suffix "96" to part number
(Example: F200-3827-96)

Part Number	Size (in.)	Weight Lbs (kg)	Thread Shear Lbs (kN)*	Torque Ft/Lbs (N·m)	Wt/100 pcs 4' in Len. Lbs (kg)
200-3827	3/8-16	0.07	415	5	35
		0.03	1.85	7	15.9
200-3828	1/2-13	0.12	570	10	57
		0.05	2.54	14	25.9
200-3829	5/8-11	0.18	1,260	40	91
		0.08	5.60	54	41.3
200-3830	3/4-10	0.28	1,700	50	133
		0.13	7.56	68	60.3
200-3831	1-8	0.50	3,000	60	200
		0.23	13.34	81	90.7




A-KONNECTOR ROD COUPLERS

A-Konnectors provide an excellent means for extending FRP all-thread rods beyond their standard lengths. A-Konnectors are manufactured from glass-reinforced polyurethane and are colored gray. A-Konnectors are packaged in bags containing 25 pieces.

Part Number	Size (in.)	Length In (mm)	Thread Shear Lbs (kN)*	Wt/100 pcs Lbs (kg)
200-3840	3/8-16	2 1/4	800	6.5
		57.2	3.56	2.9
200-3841	1/2-13	2 1/4	870	6.0
		57.2	3.87	2.7
200-3842	5/8-11	2 1/4	1,500	13.0
		57.2	6.67	5.9
200-3843	3/4-10	2 1/4	1,500	11.0
		57.2	6.67	5.0

* Thread shear values shown represent a 3:1 safety factor.



AIC-EC – CHANNEL END CAP



- Material: red PVC and designed for 1 5/8" channel.
- End caps are desired when the ends of the channel need to be enclosed. The cap easily installs by pressing it onto the end of the channel opening.

Wt/100 pcs: 3.4 Lbs (1.5 kg)

NONMETALLIC U-BOLTS



Note: Plate not included.
Illustration purpose only

*Torque and load values shown represent a 3:1 safety factor.

Part Number	Size In	"A" Dim. In (mm)	"B" Dim. In (mm)	"C" Dim. In (mm)	"D" Dim. In (mm)	"TL" Dim. In (mm)	Load Lbs (kN)*	Torque In/Lbs (N·m)	Wt/100 pcs Lbs (kg)
UB-050	1/2	0.937 23.8	0.375 9.5	1.568 39.8	2.412 61.3	1.25 31.8	135 0.60	40 5	3 1.4
UB-075	3/4	1.125 28.6	0.375 9.5	1.662 42.2	2.600 66.0	1.25 31.8	135 0.60	40 5	3 1.4
UB-100	1	1.375 34.9	0.375 9.5	1.787 45.4	2.850 72.4	1.25 31.8	135 0.60	40 5	4 1.8
UB-125	1 1/4	1.687 42.8	0.375 9.5	1.943 49.4	3.162 80.3	1.25 31.8	135 0.60	40 5	4 1.8
UB-150	1 1/2	2.000 50.8	0.375 9.5	2.100 53.3	3.475 88.3	1.25 31.8	135 0.60	40 5	5 2.3
UB-200	2	2.437 61.9	0.500 12.7	2.468 62.7	4.187 106.3	1.50 38.1	135 0.60	80 9	10 4.5
UB-250	2 1/2	2.937 74.6	0.500 12.7	2.718 69.0	4.687 119.0	1.50 38.1	135 0.60	80 9	11 5.0
UB-300	3	3.562 90.5	0.500 12.7	3.031 77.0	5.312 134.9	1.50 38.1	135 0.60	80 9	14 6.4
UB-350	3 1/2	4.062 103.2	0.500 12.7	3.281 83.3	5.812 147.6	1.50 38.1	135 0.60	80 9	15 6.8
UB-400	4	4.562 115.9	0.500 12.7	3.531 89.7	6.312 160.3	1.50 38.1	135 0.60	80 9	16 7.3
UB-600	6	6.750 171.5	0.625 15.9	5.750 146.1	9.875 250.8	3.25 82.6	135 0.60	120 14	17 7.7


- Unistrut Nonmetallic U-Bolts provide a corrosion resistant alternative to traditional metallic U-Bolts. They have oversized diameters which allow them to hold steel conduit and plastic pipe. These bolts will outlast stainless steel in most corrosive applications.
- Each U-Bolt comes with two polyurethane hex nuts. Additional nuts and washers can be purchased separately.
- Material: glass-reinforced polyurethane




CHANNEL FITTINGS

- Channel Fittings are required to fabricate structures and are easily attached to Channels with channel nuts and polyurethane fasteners. The fittings are offered in two types; fabricated (cut from flat stock) or molded.
- Material (Fabricated Fittings): Either polyester (P Series) or vinyl ester (V Series) material.
- Material (Molded Fittings): All molded fittings with the exception of the post bases are molded in polyurethane.



Note: The drawings for all fittings are shown with the Aickinstrut flange profile, however they can be used with either channel profile. All fittings are provided with 13/32" holes which accommodate 3/8" hardware. However several of the molded fittings are 1/4" thick and come with 9/16" holes which accommodate 1/2" hardware.

20P-2502, 20V-2502



Wt/100 pcs: 17 Lbs (7.7 kg)

20P-2504, 20V-2504



Wt/100 pcs: 24 Lbs (10.9 kg)




Wt/100 pcs: 12 Lbs (5.4 kg)

20P-2506, 20V-2506



Wt/100 pcs: 32 Lbs (14.5 kg)

20P-2508, 20V-2508



Wt/100 pcs: 17 Lbs (7.7 kg)

20P-2510, 20V-2510



Wt/100 pcs: 25 Lbs (11.3 kg)




Wt/100 pcs: 26 Lbs (11.8 kg)

20P-2514, 20V-2514



Wt/100 pcs: 20 Lbs (9.1 kg)

20P-2516, 20V-2516



Wt/100 pcs: 32 Lbs (14.5 kg)

20P-2518, 20V-2518



Wt/100 pcs: 33 Lbs (15.0 kg)







Wt/100 pcs: 45 Lbs (20.4 kg)

20P-2522, 20V-2522


Wt/100 pcs: 21 Lbs (9.5 kg)

20P-2524, 20V-2524


Wt/100 pcs: 32 Lbs (14.5 kg)





20P-2526, 20V-2526**20P-2528, 20V-2528****20P-2530, 20V-2530****20P-2534, 20V-2534**

Wt/100 pcs: 45 Lbs (20.4 kg)

Wt/100 pcs: 20 Lbs (9.1 kg)

Wt/100 pcs: 50 Lbs (22.7 kg)

Wt/100 pcs: 77 Lbs (34.9 kg)





20P-2540, F20V-2540

Wt/100 pcs: 41 Lbs (18.6 kg)

Wt/100 pcs: 57 Lbs (26.0 kg)

Wt/100 pcs: 9 Lbs (4.1 kg)

Wt/100 pcs: 16 Lbs (7.3 kg)




**50PU-1508 (1 1/2"),
50PU-2008 (1 5/8")**

Wt/100 pcs: 27 Lbs (12.2 kg)

Wt/100 pcs: 35 Lbs (15.9 kg)

Wt/100 pcs: 14 Lbs (6.4 kg)

Wt/100 pcs: 35 Lbs (15.9 kg)

50PU-2616**20PU-5853 (1 5/8"),
20PU-5855 (1 1/8")****20PU-5903 (3 1/4"),
20PU-5905 (2 1/4")**

Wt/100 pcs: 51 Lbs (23.1 kg)


Wt/100 pcs: 71 Lbs (32.2 kg)

Wt/100 pcs: 86 Lbs (39.0 kg)



ADJUSTABLE PIPE CLAMPS

- Unistrut Adjustable Pipe Clamps are manufactured from glass-reinforced polyurethane and are adjustable to accommodate a wide range of outside diameters. They can be utilized with a variety of piping systems including: PVC, fiberglass, copper, rigid steel conduit and PVC coated rigid steel conduit.
- Care should be taken not to exceed 3 ft./lbs. of torque on the adjustable pipe straps.



Part Number	O.D. Pipe Size (in.)	Design Load		Torque Ft/Lbs (N·m)	Wt/100 pcs Lbs (kg)
		Type 1 Lbs (kN)	Type 2 Lbs (kN)		
200-3100	1/2 - 1 1/2	135 (0.6)	65 (0.3)	0.8 (1)	3 (1.4)
200-3110	1 1/2 - 2 1/4	135 (0.6)	65 (0.3)	3 (4)	5 (2.3)
200-3120	2 1/4 - 3 1/4	145 (0.6)	70 (0.3)	3 (4)	5 (2.3)
200-3130	3 - 4	215 (1.0)	70 (0.3)	3 (4)	8 (3.6)
200-3140	4 - 6 1/2	215 (1.0)	70 (0.3)	3 (4)	10 (4.5)

*Design loads shown represent a 3:1 safety factor.

RIGID PIPE CLAMPS


Part Number	PVC, Sch. 80 Design Loads*			FRP Bolt			
	Nominal & Rigid Metal Size (in.)	In (mm)	Type 1 Lbs (kN)	Type 2 Lbs (kN)	FRP Bolt Size (in.)	Torque Ft/Lbs (N·m)	Wt/100 pcs Lbs (kg)
PCR-050	1/2	0.840 (21.3)	225 (1.0)	90 (0.4)	3/8 x 1 1/4	3 (4)	3 (1.4)
PCR-075	3/4	1.050 (26.7)	225 (1.0)	90 (0.4)	3/8 x 1 1/4		3 (1.4)
PCR-100	1	1.315 (33.4)	225 (1.0)	90 (0.4)	3/8 x 1 1/4		4 (1.8)
PCR-125	1 1/4	1.660 (42.2)	225 (1.0)	90 (0.4)	3/8 x 1 1/4		5 (2.3)
PCR-150	1 1/2	1.900 (48.3)	225 (1.0)	90 (0.4)	3/8 x 1 1/4		5 (2.3)
PCR-200	2	2.375 (60.3)	225 (1.0)	90 (0.4)	3/8 x 1 1/4		5 (2.3)
PCR-250	2 1/2	2.875 (73.0)	225 (1.0)	90 (0.4)	3/8 x 1 1/4		7 (3.2)
PCR-300	3	3.500 (88.9)	225 (1.0)	90 (0.4)	3/8 x 1 1/4		10 (4.5)
PCR-400	4	4.500 (114.3)	300 (1.3)	125 (0.6)	3/8 x 1 1/4		12 (5.4)
PCR-600	6	6.625 (168.3)	300 (1.3)	125 (0.6)	3/8 x 1 1/4		15 (6.8)
PCR-800	8	8.625 (219.1)	300 (1.3)	125 (0.6)	3/8 x 1 1/4		18 (8.1)

*Design loads shown represent a 3:1 safety factor.

Rigid Pipe Clamps resemble the more traditional style of pipe clamps and are sized based on the pipe inside diameter or nominal size. Polyurethane clamps are recommended for applications up to 160°F. For high temperature applications (up to 230°F).


Care should be taken not to exceed the recommended torque values of the rigid pipe clamps.

Material: glass-reinforced polyurethane.



TWO HOLE PIPE STRAPS


Part No.	Dimension		Bolt Size (in.)	Material Size (in.)	Design Load (lbs)*		Torque (ft./lbs.)	
	A (in.)	B (in.)			Type 1	Type 2		
PS050	0.840	4.840	1/2	1/4 X 1 1/8	135	50	4	
PS075	1.050	5.050						
PS100	1.315	5.315						
PS150	1.900	5.900			175	60		
PS200	2 3/8	6.375						
PS250	2 7/8	6.875						
PS300	3 1/2	7.500						
PS350	4	8.000			225	125		
PS400	4 1/2	8.500						
PS500	5 9/16	9.563						
PS600	6 5/8	10.625	5/8	1/4 X 1 1/8	225	125	10	
PS800	8 5/8	12.625						
PS1000	10 3/4	15.750						
PS1200	12 3/4	16.250			250	150		
PS1400	14	18.000						
PS1600	16	20.000						
PS1800	18	23.000						



- Two Hole Pipe Straps are designed for use in securing pipe, conduit and ducts to Channel. Two hole fiberglass straps can also be used independently from the channel for surface mounting. All sizes of the straps are suitable for load bearing applications.
- Material: fire-retardant, glass-reinforced polyester resin.
- For extreme chemical environments, the straps can be manufactured from vinyl ester resin. Larger diameter straps for special applications are also available. Contact the factory for pricing and availability of vinyl ester and large diameter straps. Two hole pipe straps should not be torqued above recommended values.

Notes:


- Bolts and channel nuts are sold separately.
- When bolting onto 1 1/8" channel a 1 1/4" long bolt is req'd.

MOLDED CLEVIS HANGERS

Material: glass-reinforced polyurethane.

*Design load values shown represent a 3:1 safety factor.

Part Number	Nominal Diameter In (mm)	Max. Pipe O.D. In (mm)	"A" Dim. In (mm)	"B" Dim. In (mm)	"C" Dim. In (mm)	Hanger Rod In (mm)	Load* Lbs (kN)	Wt/100 pcs Lbs (kg)
CVHPU-100	1/2 - 1	1	1.500	4.25	1.25	1/2	670	29
	12.7 - 25.4	25.4	38.1	108	32	12.7	2.98	13.2
CVHPU-150	1 1/4 - 1 1/2	1 1/2	2.000	5.14	1.25	1/2	670	40
	31.8 - 38.1	38.1	50.8	131	32	12.7	2.98	18.1
CVHPU-200	1 1/2 - 2	2	2.500	6.52	1.25	1/2	730	43
	38.1 - 50.8	50.8	63.5	166	32	12.7	3.25	19.5
CVHPU-400	2 1/2 - 4	4	5.125	10.00	1.50	1/2	1,150	129
	63.5 - 101.6	101.6	130.2	254	38	12.7	5.12	58.5
CVHPU-600	4 1/2 - 6	6	6.750	12.33	1.50	1/2	1,170	168
	114.3 - 152.4	152.4	171.5	313	38	12.7	5.20	76.2

FABRICATED CLEVIS HANGERS

Material: glass-reinforced polyester resin.


*Design load values shown represent a 3:1 safety factor.

Part Number	Size Range In (mm)	Dimensions - In (mm)				Hanger Rod In (mm)	Trans Rod In (mm)	Spreader Rod O.D. In (mm)	Loads* Lbs (kN)	Wt/100 pcs Lbs (kg)
	A	T	H	H1	W					
100-1500	1-1 1/2	1/8	2 3/4	1 1/8	1 1/2	1/2	3/8	1/2	60	21
	25.4 - 38.1	3.2	69.9	47.6	38.1	12.7	9.5	12.7	0.27	9.5
100-1501	1 1/2 - 2	1/8	3 1/2	2 2/3	1 1/2	1/2	3/8	1/2	60	25
	38.1 - 50.8	3.2	88.9	60.3	38.1	12.7	9.5	12.7	0.27	11.3
100-1502	2 - 2 5/8	1/8	4 3/4	3	2	1/2	3/8	1/2	90	55
	50.8 - 66.7	3.2	120.7	76.2	50.8	12.7	9.5	12.7	0.40	24.9
100-1503	2 1/2 - 3 1/4	1/8	5 1/2	3 3/8	2	1/2	3/8	1/2	120	57
	63.5 - 82.6	3.2	139.7	92.1	50.8	12.7	9.5	12.7	0.53	25.9
100-1504	3 - 3 3/8	1/8	7	4 1/4	2	5/8	3/8	1/2	160	61
	76.2 - 98.4	3.2	177.8	108.0	50.8	15.9	9.5	12.7	0.71	27.7
100-1505	4 - 5 1/8	13/16	8 1/2	5 5/8	2	5/8	3/8	1/2	250	82
	101.6 - 130.2	20.6	215.9	142.9	50.8	15.9	9.5	12.7	1.11	37.2
100-1506	6 - 7 1/8	13/16	10 7/8	7 1/2	3	5/8	3/8	1/2	300	136
	152.4 - 181.0	20.6	276.2	190.5	76.2	15.9	9.5	12.7	1.33	61.7
100-1507	8 - 9 1/4	1/4	14	9 3/4	3	5/8	3/8	1/2	350	189
	203.2 - 235.0	6.4	355.6	247.7	76.2	15.9	9.5	12.7	1.56	85.7
100-1508	10 - 11 1/8	1/4	18	12	4	5/8	1/2	3/4	450	333
	254.0 - 288.9	6.4	457.2	304.8	101.6	15.9	12.7	19.1	2.00	151.0
100-1509	12 - 13 1/2	1/4	21 1/2	14 1/8	5	5/8	1/2	3/4	600	350
	304.8 - 342.9	6.4	546.1	358.8	127.0	15.9	12.7	19.1	2.67	158.8
100-1510	14 - 15 3/4	1/4	24 1/2	16 1/2	5	3/4	1/2	3/4	700	872
	355.6 - 400.1	6.4	622.3	419.1	127.0	19.1	12.7	19.1	3.11	395.5
100-1511	16 - 18	3/8	27 3/8	19 1/2	6	3/4	3/4	1	750	1,023
	406.4 - 457.2	9.5	695.3	495.3	152.4	19.1	19.1	25.4	3.34	464.0
100-1512	19 - 21	3/8	34 1/2	22 1/2	6	3/4	3/4	1	800	1,673
	482.6 - 533.4	9.5	876.3	571.5	152.4	19.1	19.1	25.4	3.56	758.9
100-1513	21 - 22	1/2	35 1/2	24	6	3/4	3/4	1	850	2,323
	533.4 - 558.8	12.7	901.7	609.6	152.4	19.1	19.1	25.4	3.78	1,053.7
100-1514	22 - 24	1/2	41	28	6	3/4	3/4	1	900	2,973
	558.8 - 609.6	12.7	1,041.4	711.2	152.4	19.1	19.1	25.4	4.00	1,348.5

200-4101**UNISERT CHANNEL INSERT**

- Unisert is a polyurethane nonmetallic insert which can be used with standard cable ties for securing tubing, conduit and cables to standard metal channels.
- The Unisert works with all 1 1/8" channels that are 1 1/16" deep or more. One size fits 12, 14 and 16 metal gauge channels.

Note: For use only with metallic channel.




Wt/100 pcs: 1.0 Lbs (.5 kg)



375PU & 500PU

MOLDED BEAM CLAMPS

Material: glass-reinforced polyurethane




Assembly Part Number	Size In	Thread Shear Lbs (kN)*	Torque Ft/Lbs (N·m)	Wt/100 pcs Lbs (kg)
375PU-BC	3/8	400 1.78	10 14	30 13.6
500PU-BC	1/2	400 1.78	10 14	30 13.6

*Design load values shown represent a 3:1 safety factor.

RGBC

MOLDED BEAM CLAMP ASSEMBLY



F375PU-BCCLP (3/8")
Beam Clip Only

Note: Beam clamp clip must be purchased separately.
Illustration purpose only



Material: glass-reinforced polyurethane.

Part Number	Size In	Thread Shear Lbs (kN)*	Torque Ft/Lbs (N·m)	Wt/100 pcs Lbs (kg)
RGBC-1	3/8	500 2.22	10 14	43 19.5
RGBC-2	1/2	500 2.22	10 14	43 19.5
RGBC-3	5/8	500 2.22	10 14	43 19.5

*Design load values shown represent a 3:1 safety factor.

POWER-RACK STANCHIONS

The Power-Rack Stanchion is made entirely from glass-reinforced nylon, these stanchions offer greater corrosion resistance than classical metal stanchions. The interlocking design allows the arm to "lock" into nine different levels on the 14 1/4" stanchions and fourteen on the 17 1/2" stanchion. Glass-reinforced polyurethane stanchions are available as a special order. Contact Unistrut for pricing and availability.

Dimensions – The stanchion back has $\frac{1}{16}$ " x $\frac{1}{16}$ " holes to accept fasteners for mounting. There are two mounting holes in the 21 1/8" long stanchion and three in the 33 1/16" long stanchion. Thickness at the slotted mounting holes is 1 1/8". The mounting holes are spaced on 12" centers and require 1/2" diameter fasteners.

Installation – The Stanchions can be anchored into existing concrete structures using any industrial anchoring system. For new concrete structures, the Stanchions can be mounted to fiberglass concrete embedment channel and attached with 1/2" channel nuts and 1/2"x 3" Fiberfast Bolts.

Fire Retardance – Power-Rack materials meet or exceed the requirements of UL94 HB.

Loading – The recommended allowable loads on Power-Rack Stanchions vary depending upon the position of the arm. Use these guidelines for a safe, reliable installation:


- Total load on any one arm should not exceed 800 lbs.
- The sum of the loads on an arm multiplied by their distances to the wall stanchion should not exceed 1200 in./lbs.

Example: A cable weighing 200 lbs. is positioned on an arm at a distance of 5" from the wall stanchion.

If the total load is less than 800 lbs and the sum of the load multiplied by their distances to the wall stanchion does not exceed 1200 in./lbs., then the system is adequate. In this case,

$$\text{Total load (200<800 lbs)} = \text{OK}$$

$$\text{Tot. moment (200x5 in.)} = 1000 < 1200 \text{ in./lbs.} = \text{OK}$$



Part No.	Description	Size In (mm)	Wt/100 pcs Lbs (kg)	Load (lbs.)* Lbs (kN)
20N-ARM08	Arm	8 203.2	100 45.4	800 3.56
20N-ARM14	Arm	14 1/4 362.0	116 52.6	800 3.56
20N-ARM17	Arm	17 1/2 444.5	145 65.8	800 3.56
20N-ARM23	Arm	23 7/8 606.4	186 84.4	800 3.56
20N-STA21	Stanchion	21 1/8 542.9	149 67.6	N/A
20N-STA33	Stanchion	33 1/16 846.1	231 104.8	N/A

*Design load values shown represent a 3:1 safety factor.

FIBERGLASS CLAMPS DESIGN LOAD INFORMATION

There are two types of piping system loadings:


- overhead (Type 1) and
- vertical (Type 2)

as described below.

All pipe straps and clamps show the recommended loading for both types of loading.


Type 1 Overhead Design Load

The design load shown represents pipes supported below the strut. The design loads shown are based on a minimum ultimate failure safety factor of 3:1.

**Type 2 Vertical Design Load**

The design loading shown can be achieved with the addition of a vertical stop lock assembly (Part #F200-4219) installed directly beneath the pipe clamp. The adjacent illustration shows how the vertical stop lock assembly provides additional support for pipe and how it can be used to achieve full Type 2 design loads.

Design loads are based on a minimum clamp slip safety factor of 3:1. It is recommended that stop lock assemblies be used for all vertical pipe support applications.



CHEMICAL COMPATIBILITY TABLE

Chemical	Series									
	E		P		V		PU		N	
	Rigid PVC	Poly/Glass	Vinyl/Glass	Poly	Nylon	70°	160°F	70°	160°F	70°
Acetic Acid, Up to 50%	R	R	R	R	R	R	R	–	nr	nr
Acetone, Up to 10%	nr	nr	nr	nr	nr	nr	R	–	R	R
Aluminum Hydroxide	R	R	R	R	R	R	R	–	nr	nr
Ammonium Hydroxide (Aqueous Ammonia), Up to 5%	R	R	nr	nr	R	R	R	–	–	–
Ammonium Hydroxide (Aqueous Ammonia), Up to 10%	R	R	nr	nr	R	150°	R	–	–	–
Ammonium Hydroxide, Up to 20%	R	R	nr	nr	R	150°	R	–	–	–
Ammonium Nitrate	R	nr	R	R	R	R	R	–	–	–
Ammonium Phosphate	R	R	R	nr	R	R	R	–	–	–
Ammonium Sulfide, saturated	R	R	nr	nr	R	120°	R	–	–	–
Aqua Regia, fumes	nr	nr	nr	nr	R	150°	nr	–	–	–
Benzene	nr	nr	nr	nr	nr	nr	R	R	–	R
Benzoic Acid	R	R	R	R	R	R	R	–	–	–
Bromine, wet gas	R	nr	nr	nr	R	100°	–	–	–	–
Butylene Glycol, Up to 100%	R	R	R	R	R	R	R	–	R	R
Butyric Acid, Up to 50%	nr	nr	R	R	R	R	R	–	–	–
Calcium Hydroxide	R	R	R	nr	R	R	R	–	–	–
Calcium Hypochlorite	R	R	R	nr	R	R	R	–	nr	nr
Chlorine, Dry Gas	nr	nr	nr	nr	R	R	–	–	–	–
Chlorine, Wet Gas	nr	nr	nr	nr	R	R	–	–	–	–
Chlorine, Liquid	nr	nr	nr	nr	nr	nr	–	–	–	–
Chlorine, Water	nr	nr	R	R	R	R	R	–	nr	nr
Chromic Acid, Up to 5%	R	R	nr	nr	R	R	–	–	R	R
Copper Chloride	R	R	R	R	R	R	R	–	–	–
Copper Cyanide	R	R	R	nr	R	R	R	–	–	–
Copper Fluoride	R	R	R	nr	R	R	R	–	–	–
Copper Nitrate	R	R	R	R	R	R	R	–	–	–
Copper Sulfate	R	R	R	R	R	R	R	–	–	–
Dechlorinated Brine Storage	R	R	–	–	R	R	R	–	–	–
Esters, Fatty Acid	nr	nr	R	R	R	R	R	–	–	–
Ferric Chloride	R	R	R	R	R	R	R	–	–	–
Ferrous Chloride	R	R	R	R	R	R	R	–	–	–
Fluoboric Acid	R	R	R	120°	R	R	–	–	–	–
Fluosilicic Acid, Up to 10%	nr	nr	nr	nr	R	R	–	–	nr	nr
Fluosilicic Acid, Up to 32%	nr	nr	nr	nr	R	100°	–	–	–	–



CHEMICAL COMPATIBILITY TABLE

Chemical	Series									
	E		P		V		PU		N	
	Rigid PVC		Poly/Glass		Vinyl/Glass		Poly		Nylon	
	70°	160°F	70°	160°F	70°	160°F	70°	160°F	70°	160°F
Formic Acid, Up to 10%	R	R	nr	nr	R	R	R	-	nr	nr
Formic Acid, Up to 50%	R	R	nr	nr	R	100°	R	-	-	-
Gasoline, Aviation	R	nr	R	nr	R	R	R	-	-	-
Green Liquor, Pulp Mill	R	R	-	-	R	R	-	-	-	-
Hydrochloric Acid, Up to 15%	R	R	R	nr	R	R	R	-	-	-
Hydrochloric Acid, Up to 37%	R	R	R	nr	R	R	R	-	-	-
Hydrofluoric Acid, Up to 10%	R	R	nr	nr	R	150°	-	-	-	-
Hydrofluoric Acid, Up to 20%	R	nr	nr	nr	R	100°	-	-	-	-
Hydrogen Chloride Wet Gas	nr	nr	R	nr	R	R	nr	-	-	-
Hydrogen Sulfide Wet Gas	R	R	R	nr	R	R	R	-	-	-
Lactic Acid	R	R	R	nr	R	R	R	-	-	-
Lead Nitrate	R	R	-	-	R	R	R	-	-	-
Magnesium Hydroxide	R	R	nr	nr	R	R	R	-	R	R
Nickel Sulfate	R	R	nr	nr	R	R	R	-	-	-
Nitric Acid, Up to 5%	R	R	nr	nr	R	150°	R	-	-	-
Nitric Acid, Up to 35%	R	R	nr	nr	R	150°	R	-	-	-
Nitric Acid, Vapor	R	R	nr	nr	R	R	R	-	-	-
Perchloric Acid, Up to 10%	nr	nr	nr	nr	R	150°	R	-	nr	nr
Pickling Liquids, 3-5% H ₂ S0 ₄	R	R	R	R	R	R	R	-	-	-
Phosphoric Acid	R	R	nr	nr	R	R	R	-	nr	nr
Super or Poly (115%, P20%)	R	R	nr	nr	R	R	R	-	-	-
Vapor or Condensate	R	R	nr	nr	R	R	R	-	-	-
Potassium Chloride	R	R	R	R	R	R	R	-	-	-
Potassium Nitrate	R	R	R	R	R	R	R	-	-	-
Potassium Persulfate	R	R	nr	nr	R	R	R	-	-	-
Silver Cyanide, Up to 5%	R	R	nr	nr	R	R	R	-	-	-
Sodium Hydroxide, Up to 25%	R	R	nr	nr	R	150°	R	-	-	-
Sodium Hydroxide, Up to 50%	R	R	nr	nr	R	180°	R	-	R	R
Sodium Hypochlorite, Up to 15%	R	R	nr	nr	R	150°	R	-	nr	nr
Sodium Nitrate	R	R	R	R	R	R	R	-	-	-
Sodium Sulfate	R	R	R	nr	R	R	R	-	-	-
Sodium Sulfide	R	R	nr	nr	R	R	R	-	-	-
Sulfuric Acid, Up to 25%	R	R	R	R	R	R	R	-	nr	nr
Sulfuric Acid, Up to 70%	R	R	nr	nr	R	R	R	-	nr	nr
Sulfuric Acid, Up to 75%	nr	nr	nr	nr	R	120°	R	-	nr	nr
Sulfuric Acid, Up to 80%	nr	nr	nr	nr	nr	nr	nr	-	nr	nr
Sulfuric Acid, Vapor	R	R	R	nr	R	R	R	-	-	-
Trichlorethylene, Fumes	nr	nr	nr	nr	R	120°	R	-	-	-
Trisodium Phosphate	R	R	R	nr	R	R	R	-	-	-
Urea	R	R	R	nr	R	150°	R	-	R	R
Vegetable Oils	R	R	R	R	R	R	R	-	R	R
Vinegar	R	R	R	R	R	R	R	-	R	R
White Liquor, Pulp Mill	R	R	-	-	R	R	R	-	-	-

Note

The recommendations contained in this table are made without guarantee of representation as to results. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Unistrut as to effects of such use or results to be obtained nor does Unistrut assume any liability arising out of the use by others of the products referenced in this table. Nor is the information herein to be construed as absolutely complete since additional information may be needed or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence, or otherwise is limited to the purchase price of the material.

Legend

"nr" - "Not Recommended" for use

"R" - "Recommended"

"—" - no information available

FIBERGLASS SPECIFICATIONS

1.0 SCOPE

- 1.1 This specification covers the requirements for the Unistrut Nonmetallic Channel Framing System.

2.0 MATERIAL

- 2.1 FRP channel shall be of pultruded glass-reinforced polyester or vinyl ester resin having the physical property values listed in this catalog.
- 2.2 Some accessories shall be of injection molded, 40% long glass fiber reinforced polyurethane, or nylon.

3.0 COMPOSITION

- 3.1 Glass-reinforced channel shall have a synthetic surfacing veil applied on exterior surfaces to improve weatherability and inhibit ultraviolet degradation. An ultraviolet stabilizer shall be incorporated in the resin formulation to further inhibit ultraviolet degradation.

4.0 STRUCTURAL DESIGN

- 4.1 Channel shall incorporate Unistrut's Aickinstrut flange profile design which allows full and positive interlocking contact of channel accessories and prohibits premature flange failure from torqued accessories.
- 4.2 Channel profile dimensions shall be:
 1 $\frac{5}{8}$ " x 1 $\frac{5}{8}$ " x $\frac{1}{4}$ " or
 1 $\frac{1}{2}$ " x 1 $\frac{1}{8}$ " x $\frac{1}{8}$ ".
- 4.3 All 1 $\frac{5}{8}$ " x 1 $\frac{5}{8}$ " channel profiles shall have a minimum pull out resistance of 1,000 pounds when load is applied over a $\frac{3}{8}$ " long section of the inside flanges.
- 4.4 Channel section lengths shall be supplied in 10' or 20' lengths ($\pm\frac{1}{8}$ ").
- 4.5 Universal Pipe Clamps shall have full interlocking contact with interior channel flanges to maximize pull-out resistance and be adjustable to accommodate a minimum $\frac{3}{4}$ " variance in piping or conduit O.D. sizes.

5.0 STANDARDS

- 5.1 Glass-reinforced channels covered in this specification shall have a flame spread rating of 25 or less when tested per ASTM E84 and meet the requirements of UL 94V0 thereby qualifying them as Class 1 material in the Uniform Building Code.
- 5.2 Glass-reinforced channels covered in this specification shall comply with the requirements of ASTM D 3917 and ASTM D 4385 which govern the dimensional tolerance and visual defects of pultruded shapes.

6.0 GENERAL

- 6.1 Unistrut nonmetallic Channel Framing shall be furnished as a system which includes all the necessary fasteners, channel splice plates, brackets, sealants, hangers, pipe clamps, etc.
- 6.2 Nonmetallic fasteners shall be manufactured from long glass fiber reinforced polyurethane to ensure maximum strength and corrosion resistance.
- 6.3 All components of the Unistrut Channel Framing System shall be nonmetallic except where type 316 stainless steel hardware is used as part of the assembly.
- 6.4 The manufacturer shall not have had less than 10 years experience in manufacturing strut systems.
- 6.5 All products are manufactured in the United States of America.

1 $\frac{1}{4}$ " System1 $\frac{3}{16}$ " System

Fiberglass System

Special Metals

PrimeAngle

Metal Grating


Roofwalk

Index



UNISTRUT

SPECIAL METALS



MATERIAL

STAINLESS STEEL

Channels: ASTM A 240 (Type 304)

Sintered nuts: ASTM B783 (Type SS316N1-25)

Fittings:

ASTM A240 (Type 304 or Type 316) or ASTM A276
(Type 304 or Type 316)

Contact factory for specific material availability.

ALUMINUM

Channels (Extruded): ASTM B221 (Type 6063-T6)

Fittings: ASTM B209 (Type 1100F or Type 5052-H32)

Nuts: Stainless steel nuts are recommended for
Aluminum channel

Material/Finish	Part Number Suffix	Example
Stainless Steel Type 304	SS	P1109 SS
Stainless Steel Type 316	ST	P1109 ST

LOAD DATA (BEAM & COLUMN)

To determine maximum allowable beam and column loading for channels in this section, multiply the load data in the appropriate mild steel channel sections of this catalog by the following factors:

Channel Material	Beam Load % Factor	Column Load % Factor
Extruded Aluminum	33%	33%
Stainless Steel	100%	100%

LOAD DATA (SLIP & PULL OUT)

Stainless Steel Channel	206
Stainless Steel Nuts and Closure Strips	207
Extruded Aluminum Channels	208 - 209
Aluminum Closure Strips and End Caps	209

EXTRUDED ALUMINUM

To determine nut slip resistance, multiply load data for appropriate nut by 75%. To determine nut pull-out load, multiply load data for appropriate nut by 50%.

STAINLESS STEEL


For design assistance, consult Unistrut customer engineering.

PRODUCT AVAILABILITY

Most fittings and channels shown in this catalog, are available in aluminum or stainless steel. Consult factory for ordering information.


DIMENSIONS

Imperial dimensions are illustrated in inches. Metric dimensions are shown in parenthesis or as noted. Unless noted, all metric dimensions are in millimeters and rounded to one decimal place.


P1000 Series (12 gauge)P1000 SS
Pg 206P1001 SS
Pg 206**P1100 Series (14 gauge)**P1100 SS
Pg 206P1101 SS
Pg 206**P3000 Series (12 gauge)**P3000 SS
Pg 206**P3300 Series (12 gauge)**P3300 SS
Pg 206P3301 SS
Pg 206**P4000 Series (16 gauge)**P4000 SS
Pg 206**P6000 Series (19 gauge)**P6000 SS
Pg 206**P7000 Series (19 gauge)**P7000 SS
Pg 206**Closure Strips and End Caps**P3184 EA
Pg 209P1280 EA, P4280 EA,
P5580 EA Pg 209**Stainless Steel Channel Nuts**P1006 - P1010
Pg 207P4006 - P4010
Pg 207P5506 U - P5510U
Pg 207P4008UT
Pg 207A1006 SS, A1008 SS
Pg 207A4006 SS, A4008 SS
Pg 207**Extruded Aluminum Channels**P1000 EA
Pg 208P1001 EA
Pg 208P4000 EA
Pg 208P4001 EA
Pg 208P5500 EA
Pg 208A1000 EA
Pg 208A4000 EA
Pg 208A4001 EA
Pg 209P6000 EA
Pg 209P6001 EA
Pg 209P7000 EA
Pg 209P7001 EA
Pg 209




P1000 Series

P1000


Wt/100 Ft: 190 Lbs (283 kg/100m)


P1001


Wt/100 Ft: 380 Lbs (566 kg/100m)

P1000HS


$\frac{5}{16}$ " (14.3) Dia. Holes
1 $\frac{1}{8}$ " (47.6) on Center


Wt/100 Ft: 185 Lbs (275 kg/100m)

P1000T



Slots are
1 $\frac{1}{8}$ " (28.6) x $\frac{5}{16}$ " (14.3)
2" (50.8) on Center

Wt/100 Ft: 185 Lbs (275 kg/100m)

P1100 Series

P1100


Wt/100 Ft: 142 Lbs (211 kg/100m)


P1101


Wt/100 Ft: 284 Lbs (422 kg/100m)

P1100HS


$\frac{5}{16}$ " (14.3) Dia. Holes
1 $\frac{1}{8}$ " (47.6) on Center


Wt/100 Ft: 136 Lbs (202 kg/100 m)

P1100T



Slots are
1 $\frac{1}{8}$ " (28.6) x $\frac{9}{16}$ " (14.3)
2" (50.8) on Center

Wt/100 Ft: 136 Lbs (202 kg/100m)

P3000 Series


P3000


Wt/100 Ft: 170 Lbs (253 kg/100m)

P3000HS


$\frac{5}{16}$ " (14.3) Dia. Holes
1 $\frac{1}{8}$ " (47.6) on Center


Wt/100 Ft: 165 Lbs (112 kg/100m)

P3000T



Slots are
1 $\frac{1}{8}$ " (28.6) x $\frac{5}{16}$ " (14.3)
2" (50.8) on Center

Wt/100 Ft: 165 Lbs (112 kg/100m)


P3300 Series

P3300


Wt/100 Ft: 135 Lbs (201 kg/100m)


P3301


Wt/100 Ft: 270 Lbs (402 kg/100m)

P3300HS


$\frac{5}{16}$ " (14.3) Dia. Holes
1 $\frac{1}{8}$ " (47.6) on Center


Wt/100 Ft: 130 Lbs (193 kg/100m)

P3300T


Slots are
1 $\frac{1}{8}$ " (28.6) x $\frac{5}{16}$ " (14.3)
2" (50.8) on Center

Wt/100 Ft: 130 Lbs (193 kg/100m)

P4000 Series


P4000


Wt/100 Ft: 82 Lbs (122 kg/100m)

P4000HS



$\frac{5}{16}$ " (14.3) Dia. Holes
1 $\frac{1}{8}$ " (47.6) on Center

Wt/100 Ft: 79 Lbs (110 kg/100m)


P4000T


Slots are
1 $\frac{1}{8}$ " (28.6) x $\frac{9}{16}$ " (14.3)
2" (50.8) on Center

Wt/100 Ft: 79 Lbs (110 kg/100m)

P6000



Wt/100 Ft: 37 Lbs (55 kg/100m)

P7000


Wt/100 Ft: 36 Lbs (54 kg/100m)

P1184

CLOSURE STRIP



Standard length 10 Ft.
Material: Stainless steel type 304.

Part Number	Use With Channel	"W" In (mm)	Wt/100 Ft Lbs (kg/m)
P1000			
P1184 SS		1½	27
P3000		41.3	40.2
P4000			

CHANNEL NUT WITH SPRING – USE WITH 1¼" CHANNEL

	Part number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
	A1006-1420	¼" -20	6 (2.7)	A1000
	A1008	⅜" -16	6 (2.7)	
	A4008	⅜" -16	5 (2.3)	A3300, A4000

All Springs are Pre-Galvanized

CHANNEL NUT WITH SPRING – USE WITH 1½" CHANNEL

	Part number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With 1½" Channel
	P1006-1420*	¼" 20	7 (3.2)	P1000, P1100, P2000, P3000, P4400
	P1008*	⅜" 16	10 (4.5)	
	P1010*	½" 13	12 (5.4)	
	Part number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With 1½" Channel
	P4006-1420*	¼" 20	7 (3.2)	P3300, P4000, P4100, P4520
	P4008*	⅜" 16	9 (4.1)	
	P4010*	½" 13	9 (4.1)	
	Part number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With 1½" Channel
	P5506-1420*	¼" 20	7 (3.2)	P5000, P5500
	P5508*	⅜" 16	10 (4.5)	
	P5510*	½" 13	10 (4.5)	

* Domestic stainless steel nuts are available. To designate a domestic part, insert a "U" as the sixth character in the part number. Ex: P4006U 1420 SS or P1008U SS.

CHANNEL NUT WITHOUT SPRINGS – USE WITH 1½" CHANNEL

	Part number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With 1½" Channel
	P3006-1420 SS	¼" 20	7 (3.2)	Any Channel
	P3008 SS	⅜" 16	10 (4.5)	
	P3010 SS	½" 13	12 (5.4)	P1000, P1100, P2000, P3000

* Domestic stainless steel nuts are available. To designate a domestic part, insert a "U" as the sixth character in the part number. Ex: P3008U SS or P3010U SS

TOP SPRING CHANNEL NUTS – USE WITH 1½" CHANNEL

	Part number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With 1½" Channel
	P4008UT SS*	⅜" 16	12 (5.4)	P3300, P4000, P4100, P4400, P4520
	P1006TU1420SS*	¼" -20	7 (3.2)	
	P1008TU SS*	⅜" -16	10 (4.5)	
	P1010TU SS*	½" -13	12 (5.4)	Any Channel Except P3300, P4000, P4400, P4520, P4100

Top Spring stainless steel channel nuts are domestic

Note

Most fittings, as shown in this catalog are available in stainless steel or aluminum.
It is recommended that stainless steel channel nuts be used with aluminum channels.

1¼" System

Fiberglass System

Special Metals

PrimeAngle



Metal Grating

Roofwalk


Index



P1000 EA






When used
with P3184 EA.






Wt/100 Ft: 76 Lbs (113 kg/100 m)
Aluminum Type 6063-T6
Nominal Thickness .109" (2.8mm)

P1001 EA






Wt/100 Ft: 134 Lbs (199 kg/100 m)
Aluminum Type 6063-T6
12 Gauge Nominal Thickness .109" (2.8mm)

P4000 EA






Wt/100 Ft: 45 Lbs (67 kg/100 m)
Aluminum Type 6063-T6
Nominal Thickness .078" (2.0mm)

P4001 EA






Wt/100 Ft: 66 Lbs (98 kg/100 m)
Aluminum Type 6063-T6
Nominal Thickness .078" (2.0mm)

P5500 EA






Wt/100 Ft: 97 Lbs (144 kg/100 m)
Aluminum Type 6063-T6
Nominal Thickness .109" (2.8mm)

A1000 EA






Wt/100 Ft: 40 Lbs (60 kg/100 m)
Aluminum Type 6063-T6
Nominal Thickness .075" (1.9mm)




A4000 EA






Wt/100 Ft: 25 Lbs (37 kg/100 m)
Aluminum Type 6063-T6
12 Gauge Nominal Thickness .050" (1.3mm)
Standard Length 16 Ft.

A4001 EA




Wt/100 Ft: 40 Lbs (60 kg/100 m)
Aluminum Type 6063-T6
Nominal Thickness .078" (2.0mm)
Standard Length 16 Ft.

P6000 EA




Wt/100 Ft: 12 Lbs (18 kg/100 m)
Aluminum Type 6063-T6
Nominal Thickness .040" (1.0mm)
Standard Length 16 Ft.

P6001 EA



Wt/100 Ft: 20 Lbs (30 kg/100 m)
Aluminum Type 6063-T6
Nominal Thickness .040" (1.0mm)
Standard Length 16 Ft.

P7000 EA

Wt/100 Ft: 9 Lbs (13 kg/100 m)
Aluminum Type 6063-T6
Nominal Thickness .040" (1.0mm)
Standard Length 10 Ft.

P7001 EA

Wt/100 Ft: 17 Lbs (25 kg/100 m)
Aluminum Type 6063-T6
12 Gauge Nominal Thickness .040" (1.0mm)
Standard Length 10 Ft


P3184 EA

Wt/100 Ft: 21 Lbs (31 kg/100 m)
Aluminum Type 6063-T6
Standard Length 10 Ft

CLOSURE STRIP**P1280 EA, P4280 EA, P5580 EA****END CAPS**

Part Number	Use With Channel	Wt/100 Ft Lbs(kg/m)
P1280 EA	P1000 EA	3.5 (1.6)
P4280 EA	P4000 EA	1.5 (0.7)
P5580 EA	P5500 EA	4.9 (2.2)

PrimeAngle™	211
Accessories	212
PrimeAngle™ Technical Data	213 - 215



MATERIAL

STEEL: PLAIN

12 Gauge (.105" 1.0 mm) ASTM 1011 SS GR 33,
14 Gauge (.076) ASTM 1011 SS GR 33

STEEL: PRE-GALVANIZED

12 Gauge (.105" 1.0 mm) ASTM A653 GR 33,
14 Gauge (.076) ASTM A653 GR 33

FINISHES

Available in two durable, long-lasting finishes:

Pre-Galvanized (PG) or

Perma-Green III (GR) conforming to
ASTM B633 Type III SC1.

STANDARD LENGTHS

Standard lengths are 10' and 12'. Slotted angle is shipped in ten-piece bundles complete with 75 pieces of $\frac{3}{8}$ " - 16 x $\frac{3}{4}$ " hex head bolts and $\frac{3}{8}$ " nuts.


ORDERING INFORMATION:

When ordering, add the length or size and finish to the part number.

DIMENSIONS

Imperial dimensions are illustrated in inches. Metric dimensions are shown in parenthesis or as noted. Unless noted, all metric dimensions are in millimeters and rounded to one decimal place.

PA 158


(1 $\frac{5}{8}$ " x 1 $\frac{5}{8}$ " x 14 GA.) LIGHT DUTY EPG

Note: Includes Serrated
Nuts & Bolts

For those jobs where extra strength is not necessary. Ideal for light-duty shelving or racking.

Wt/100 Ft: 66 lbs (29.9 kg)

PA 238


(1 $\frac{5}{8}$ " x 2 $\frac{3}{8}$ " x 14 GA.) MEDIUM DUTY EPG

Note: Includes Serrated
Nuts & Bolts

Perfect for the majority of framing needs, including shelving, racking and electrical or mechanical support jobs.

Wt/100 Ft: 80 lbs (36.3 kg)

PA 318

(1 $\frac{5}{8}$ " x 3 $\frac{1}{8}$ " x 12 GA.) HEAVY DUTY

Note: Includes Serrated
Nuts & Bolts


Suitable for balconies, ramps, large racks and shelving systems, as well as other structures with substantial load requirements.

Wt/100 Ft: 130 lbs (59.0 kg)



PA 1SNB

SERRATED NUTS AND BOLTS



Wt/100 pcs: 7 lbs (3.2 kg)


TRANSVERSE STIFFENERS

When supporting concentrated loads, the capacity of a pair of slotted-angle beams can be increased by the addition of transverse stiffeners. These should be placed immediately under the load bearing point. The slotted-angle segment used as the stiffener is bolted into place using a metal connector at each junction.

Beams that are 6' (182.9 cm) long or less require only one stiffener in the center of the span. Seven-foot beams need two stiffeners placed 2' (61.0 cm) from each end. Eight-foot beams require two stiffeners 2'6" (76.2 cm) from the ends. For beams with a nine-foot span, it is necessary to have three stiffeners at 2'3" (68.6 cm) intervals. Ten-foot beams need three stiffeners with 2'6" spacings.

For maximum effectiveness, transverse stiffeners should never be spaced more than 3'6" (106.7 cm) apart.


Note: All loads based on actual physical testing. Documentation available on request.




BEAM CONFIGURATIONS

(See corresponding letters in table on following page for load data)


G – Two Single Pieces (Up)




H – Two Single Pieces (Level)




I – Two Single Pieces (Down)




J – Two Z-Sections




K – Two Narrow Channels




L – Two Broad Channels




M – Two T-Sections



N – Two I-Sections




O – Two J-Sections


**BEAM CONFIGURATIONS WITH STIFFENERS**

(See corresponding letters in table on following page for load data)


P – Single Pieces w/Stiffener




Q – T-Sections w/Stiffener



R – Z-Sections w/Stiffener




S – I-Sections w/Stiffener

**BEAM LOAD CALCULATIONS**


The beam loading depends on which slotted angle is used and the manner in which the beam is constructed. The diagrams above show how individual slotted angle components can be combined to form a beam. The loading for each beam configuration is shown in the beam loading tables on the next page.

Example - Load "A"

Load "A" is supported by two 48" (121.9 cm) sections of PA-238 (1 $\frac{1}{8}$ " x 2 $\frac{3}{8}$ ") (41.3mm x 60.3mm). The 48" row in the PA 238 table on next page indicates what each beam configuration will support. Since the columns are sorted from lowest to highest load, the first configuration that satisfies the requirement is "J" which will support 1,100 lbs (4.9 kN).

**Example - Load "C"**

Load "C" is supported by all four beam sections. The load is distributed uniformly on two 3' (91.4 cm) and two 4' (121.9 cm) beams which total 14' (426.7 cm) of supporting beam length. Dividing the 1,000 lbs. (4.5 kN) load by 14-feet equals 72 lbs. per foot (106.3 kg per meter). Using the two 4' (121.9 cm) longest (weakest) lengths, calculate the total weight as follows:




$$2 \text{ (beams)} \times 4' \text{ (length)} \times 72 \text{ lbs./ft.} = 576 \text{ lbs. total wt.}$$

$$2 \text{ (beams)} \times 121.9\text{cm (length)} \times 106.3 \text{ kg/M} = 25,915 \text{ kg total wt.}$$

Example - Load "B"

Load "B" is supported by two 36" (91.4 cm) sections of PA-238 (1 $\frac{1}{8}$ " x 2 $\frac{3}{8}$ ") (41.3mm x 60.3mm). The 36" row in the PA 238 table on next page indicates what each beam configuration will support. Since the columns are sorted from lowest to highest load, the first configuration that satisfies the requirement is "J" which will support 830 lbs. (3.7 kN) and is adequate for this requirement. The 3-foot beams configured in the same manner will support the load because they are shorter and stronger.



The 36" (91.4 cm) row in the PA 238 table on next page indicates what each beam configuration will support. Since the columns are sorted from lowest to highest load, the first configuration that satisfies the requirement is "J" which will support 830 lbs. (3.7 kN) and is adequate for this requirement. The 3-foot beams configured in the same manner will support the load because they are shorter and stronger.




BEAM LOADS

(See corresponding letters in table on previous page for configurations)

PA 158


LIGHT DUTY, (1 5/8" x 1 5/8" x 14 GA.)



Span In. (cm)	G Lbs (kN)	H Lbs (kN)	I Lbs (kN)	P Lbs (kN)	L Lbs (kN)	R Lbs (kN)	M Lbs (kN)
24	550	830	830	920	1,600	1,700	1,840
61.0	2.45	3.69	3.69	4.09	7.12	7.56	8.18
36	370	560	560	610	1,070	1,130	1,230
91.4	1.65	2.49	2.49	2.71	4.76	5.03	5.47
48	280	420	420	460	800	850	920
121.9	1.25	1.87	1.87	2.05	3.56	3.78	4.09
60	220	330	330	370	640	680	740
152.4	0.98	1.47	1.47	1.65	2.85	3.02	3.29
72	180	280	280	310	530	570	610
182.9	0.80	1.25	1.25	1.38	2.36	2.54	2.71
84	•	240	240	260	460	490	530
213.4	•	1.07	1.07	1.16	2.05	2.18	2.36
96	•	210	210	230	400	430	460
243.8	•	0.93	0.93	1.02	1.78	1.91	2.05
108	•	•	•	•	360	380	410
274.3	•	•	•	•	1.60	1.69	1.82
120	•	•	•	•	320	340	370
304.8	•	•	•	•	1.42	1.51	1.65

PA 238


MEDIUM DUTY, (1 5/8" x 2 3/8" x 14 GA.)



Span In. (cm)	G Lbs (kN)	H Lbs (kN)	I Lbs (kN)	P Lbs (kN)	J Lbs (kN)	L Lbs (kN)	R Lbs (kN)	M Lbs (kN)	K Lbs (kN)	Q Lbs (kN)	O Lbs (kN)	N Lbs (kN)
24	700	1,020	1,660	1,740	2,220	3,170	3,230	3,490	3,590	3,630	6,060	7,560
61.0	3.11	4.54	7.38	7.74	9.88	14.10	14.37	15.52	15.97	16.15	26.96	33.63
36	460	680	1,100	1,160	1,480	2,110	2,150	2,320	2,390	2,420	4,040	5,040
91.4	2.05	3.02	4.89	5.16	6.58	9.39	9.56	10.32	10.63	10.76	17.97	22.42
48	350	510	830	870	1,110	1,580	1,620	1,740	1,800	1,810	3,030	3,780
121.9	1.56	2.27	3.69	3.87	4.94	7.03	7.21	7.74	8.01	8.05	13.48	16.81
60	280	410	660	700	890	1,270	1,290	1,390	1,440	1,450	2,420	3,020
152.4	1.25	1.82	2.94	3.11	3.96	5.65	5.74	6.18	6.41	6.45	10.76	13.43
72	230	340	550	580	740	1,060	1,080	1,160	1,200	1,210	2,020	2,520
182.9	1.02	1.51	2.45	2.58	3.29	4.72	4.80	5.16	5.34	5.38	8.99	11.21
84	•	290	470	500	630	910	920	1,000	1,030	1,040	1,730	2,160
213.4	•	1.29	2.09	2.22	2.80	4.05	4.09	4.45	4.58	4.63	7.70	9.61
96	•	260	410	440	550	790	810	870	900	910	1,520	1,890
243.8	•	1.16	1.82	1.96	2.45	3.51	3.60	3.87	4.00	4.05	6.76	8.41
108	•	•	•	•	490	700	720	770	800	810	1,350	1,680
274.3	•	•	•	•	2.18	3.11	3.20	3.43	3.56	3.60	6.01	7.47
120	•	•	•	•	440	630	650	700	720	730	1,210	1,510
304.8	•	•	•	•	1.96	2.80	2.89	3.11	3.20	3.25	5.38	6.72

PA 318

HEAVY DUTY, (1 5/8" x 3 1/8" x 12 GA.)



Span In. (cm)	G Lbs (kN)	H Lbs (kN)	I Lbs (kN)	P Lbs (kN)	J Lbs (kN)	L Lbs (kN)	R Lbs (kN)	M Lbs (kN)	K Lbs (kN)	Q Lbs (kN)	O Lbs (kg)	N Lbs (kg)
24	1,790	1,610	4,300	4,960	6,520	7,910	8,070	9,920	9,990	10,170	14,600	16,120
61.0	7.96	7.16	19.13	22.06	29.00	35.19	35.90	44.13	44.44	45.24	64.94	71.71
36	1,200	1,070	2,870	3,310	4,350	5,270	5,380	6,610	6,660	6,780	9,730	10,750
91.4	5.34	4.76	12.77	14.72	19.35	23.44	23.93	29.40	29.63	30.16	43.28	47.82
48	900	810	2,150	2,480	3,260	3,950	4,030	4,960	4,990	5,080	7,300	8,060
121.9	4.00	3.60	9.56	11.03	14.50	17.57	17.93	22.06	22.20	22.60	32.47	35.85
60	720	640	1,720	1,980	2,610	3,160	3,230	3,970	4,000	4,070	5,840	6,450
152.4	3.20	2.85	7.65	8.81	11.61	14.06	14.37	17.66	17.79	18.10	25.98	28.69
72	600	540	1,430	1,650	2,170	2,640	2,690	3,310	3,330	3,390	4,870	5,370
182.9	2.67	2.40	6.36	7.34	9.65	11.74	11.97	14.72	14.81	15.08	21.66	23.89
84	•	460	1,230	1,420	1,860	2,260	2,300	2,830	2,850	2,910	4,170	4,610
213.4	•	2.05	5.47	6.32	8.27	10.05	10.23	12.59	12.68	12.94	18.55	20.51
96	•	400	1,080	1,240	1,630	1,980	2,020	2,480	2,500	2,540	3,650	4,030
243.8	•	1.78	4.80	5.52	7.25	8.81	8.99	11.03	11.12	11.30	16.24	17.93
108	•	•	•	•	1,100	1,450	1,760	1,790	2,200	2,220	2,260	3,240
274.3	•	•	•	•	4.89	6.45	7.83	7.96	9.79	9.88	10.05	14.41
120	•	•	•	•	990	1,300	1,580	1,610	1,980	2,000	2,030	2,920
304.8	•	•	•	•	4.40	5.78	7.03	7.16	8.81	8.90	9.03	12.99
												14.32

COLUMN LOADS

Column sections are calculated as described in the following example:
(Assumes use of PA-238 1 1/8" x 2 3/8"(41.3mm x 60.3mm), material.)


Since all load areas are supported equally by the 4-columns, the calculations are based on a single-column section.

Section MN is one-fourth of "X", or 250 pounds (1.1 kN). Column section NP supports one-fourth of "Y" (250 pounds) plus the load supported by MN, or a total of 500 pounds (2.2 kN). Section PQ supports one-fourth of "Z" (250 pounds) plus the 500 pound load on section NP, or a total of 750 (3.3kN) pounds.


Column loads are based on free and unbraced column lengths. Since MN, NP and PQ are each 3' long, the load requirement is for a 36" section that will bear 750 pounds safely. A reference to the PA 238 table to the right indicates that all sections designated "A" will support 2,280 lbs. (10.1 kN) and meet the necessary requirements.

Note: To simplify assembly, we recommend using the same size material as for the horizontal members. This would be found in Table 2 to match the 14 gauge 1 1/8" x 2 3/8" (41.3mm x 60.3mm) material selected for the beams of this structure.


A – Single Piece




B – T-Section




B – Broad Channel Section




B – Narrow Channel Section



C – Uneven T-Section



C – Uneven Channel Section




D – Dual Channel Section




D – T-Channel Section





D – T-Channel Section




E – I-Section



F – Uneven I-Section

**PA 158**


(1 1/8" x 1 5/8" x 14 GA.)



Span In. (cm)	A Lbs (kN)	B Lbs (kN)
36	1,450	3,850
91.4	6.45	17.13
48	1,150	3,500
121.9	5.12	15.57
60	950	3,000
152.4	4.23	13.34
72	750	2,500
182.9	3.34	11.12

PA 238


(1 1/8" x 2 3/8" x 14 GA.)



Span In. (cm)	A Lbs (kN)	B Lbs (kN)	C Lbs (kN)	D Lbs (kN)	E Lbs (kN)	F Lbs (kN)
36	2,280	4,760	4,940	7,270	9,520	9,865
91.4	10.14	21.17	21.97	32.34	42.35	43.88
48	1,970	4,490	4,680	6,920	8,970	9,330
121.9	8.76	19.97	20.82	30.78	39.90	41.50
60	1,520	3,995	4,310	6,370	7,990	8,620
152.4	6.76	17.77	19.17	28.34	35.54	38.34
72	1,070	3,140	3,870	5,840	6,280	7,715
182.9	4.76	13.97	17.21	25.98	27.93	34.32
84	660	2,340	3,665	4,930	4,660	6,740
213.4	2.94	10.41	16.30	21.93	20.73	29.98
96	•	1,750	2,700	3,850	3,500	5,365
243.8	•	7.78	12.01	17.13	15.57	23.86
108	•	•	2,060	2,870	•	4,115
274.3	•	•	9.16	12.77	•	18.30
120	•	•	1,610	2,690	•	3,210
304.8	•	•	7.16	11.97	•	14.28

PA 318

(1 1/8" x 3 1/8" x 12 GA.)



Span In. (cm)	A Lbs (kN)	B Lbs (kN)	C Lbs (kN)	D Lbs (kN)	E Lbs (kN)	F Lbs (kN)
36	3,470	7,970	8,770	12,560	15,940	17,550
91.4	15.44	35.45	39.01	55.87	70.90	78.07
48	2,870	7,360	8,580	11,970	14,750	17,150
121.9	12.77	32.74	38.17	53.25	65.61	76.29
60	1,970	6,570	8,180	11,360	13,160	16,360
152.4	8.76	29.22	36.39	50.53	58.54	72.77
72	1,280	5,270	7,690	10,480	10,560	15,360
182.9	5.69	23.44	34.21	46.62	46.97	68.32
84	•	3,670	6,970	9,470	7,370	13,970
213.3	•	16.32	31.00	42.12	32.78	62.14
96	•	2,580	6,260	8,370	5,170	12,570
243.8	•	11.48	27.85	37.23	23.00	55.91
108	•	•	5,460	6,880	•	10,970
274.3	•	•	24.29	30.60	•	48.80
120	•	•	4,460	5,370	•	8,960
304.8	•	•	19.84	23.89	•	39.86

United Interlock Plank Grating System from Unistrut, commonly known as Interlock Grating, fills a multitude of needs including flooring and walkways, mezzanines, stair treads, maintenance and staging platforms, scaffolding

planks, architectural wall coverings and more. United Interlock Grating Systems meets your needs for strength, durability, safety and aesthetics.

Customers choose United Interlock Grating Systems for many reasons:

- Cost-effectiveness
- Easy-to-install product
- Quality assurance that comes from extensive load testing
- Strong design look of our plank grating



United Interlock Grating Applications include:

- Architectural wall coverings
- Catwalks, walkways and pedestrian ramps
- Maintenance and inspection walkways
- Ventilation covers for tanks and wells
- Mining and quarry tower decking
- Pumping and drilling platforms
- Subflooring
- Mezzanines
- Shelving
- Stairs



Ease of Installation	217
Plank Grating	218 - 219
Accessories	220 - 222
Heavy Duty Stair Treads	223
Design and Testing	224
Plank Loads and Deflections	225 - 230
Architectural Specifications.....	231



Architectural Applications

Interlock Grating provides a functional and aesthetically appealing look to architectural applications. Aluminum gratings resist corrosion to give walls, ceilings, ledges, trim, flooring, and specialty projects a clean, lasting, high-tech look. Interlocking plank grating works especially well in intensive-use areas. In addition to its durability, it is easy to clean and does not reflect sound like a solid surface.

Architects have often selected Interlock Grating because it protects lights, insulation support columns, wiring, and other fixtures. And, the panels allow authorized personnel to access the fixtures.

Contractors have reported installed cost savings of up to 75% with Interlock Grating. Many factors combine to make installation quick and easy:

- 1) The lightweight grating is easy to handle. One person can carry a 24' plank.
- 2) Interlock Grating is easy to install with a minimal number of laborers.
- 3) Interlock Grating's light weight reduces shipping costs.
- 4) The planks interlock with positive friction, eliminating costly welding and bolting in some cases.
- 5) Field modifications are easy. Interlock Grating can be cut to size, shape, and angle at the jobsite.
- 6) Interlock Grating requires fewer support structures.





United Interlock Grating strength-to-weight ratio allows it to withstand substantial loads while being easy to handle. The male-female legs of the roll-formed grating interlock securely, and double-male legs provide a safe finished edge for end planks.

Two standard surfaces are available: slotted-smooth and anti-skid. Anti-skid is the ideal choice when safe walking conditions are important. Die-formed teeth in the transverse ribs give you 360° of shoe-gripping traction even when the grating is wet, oily, muddy, or icy.



Interlock Grating Features

Maximizes performance and safety...

- Anti-skid surface provides 360° of slip resistance
- All sections made from structural-grade steel
- Roll-formed design provides superior strength
- Optional heel-toe side and end plates
- Open design prevents build-up of water, grease, oil and small debris

And gives you complete project versatility.

- 6", 9" and 12" plank widths allow design in 3" increments
- Standard lengths of 20' and 24', and special lengths up to 30', provide excellent design flexibility
- Choice of smooth punched, anti-skid punched or solid unpunched surfaces
- Four leg heights, and two material gauges meet a wide range of load, space and budget requirements

Punched Interlock Grating has an open area of 43% for 12" grating, 42% for 9" grating and 35% for 6" grating. This prevents dirt, debris, ice, and snow from building up on the surface and allows light and air to pass through. United Interlock steel grating is made from pre-galvanized steel which conforms to a G-90 thickness designation per ASTM A653. The aluminum grating is made from type 5052 aluminum with a thickness of 0.080".

Unpunched smooth surface grating is also available for special applications.



United Interlock Grating Systems are strong, economical, versatile, and easy to specify.

Variety of choices

- 6" and 9" standard-duty width
- 12" light-duty width
- 14 gauge and 18 gauge
- 1 1/2", 2 1/2", 3"(12" width only) and 4" (6" and 9" width only) leg heights
- 20' and 24' stock lengths
- Anti-skid, slotted-smooth punched surfaces and solid unpunched surface
- Double male and male-female leg shapes
- Steel (6", 9" or 12") and aluminum (6"or 9")



UNITED INTERLOCK® GRATING SYSTEMS—6" AND 9"




6" Wide Planks (14 Ga, 18 Ga, 0.080 Aluminum)							
Leg Height	Leg Shape	Finish Material	Slotted, Smooth	Anti-Skid	Un-punched	Wt. Lbs./Ft	Wt. Lbs./Ft ²
1 1/2"	DM	PG 14 Ga.	G61141 G62141	G61142 G62142	G61143 G62143	2.7	5.4
	MF					2.7	5.4
2 1/2"	DM	PG 14 Ga.	G61241 G62241	G61242 G62242	G61243 G62243	3.4	6.8
	MF					3.4	6.8
	DM	PG 18 Ga.	G61281 G62281	G61282 G62282	G61283 G62283	2.2	4.4
	MF					2.2	4.4
4"	DM	AL 0.080"	G61221 G62221	G61222 G62222	G61223 G62223	1.2	2.3
	MF					1.2	2.3
	DM	PG 14 Ga.	G61341 G62341	G61342 G62342	G61343 G62343	4.2	8.4

9" Wide Planks (14 Ga, 18 Ga, 0.080 Aluminum)							
Leg Height	Leg Shape	Finish Material	Slotted, Smooth	Anti-Skid	Un-punched	Wt. Lbs./Ft	Wt. Lbs./Ft ²
1 1/2"	DM	PG 14 Ga.	G91141 G92141	G91142 G92142	G91143 G92143	3.5	4.7
	MF					3.5	4.7
2 1/2"	DM	PG 18 Ga.	G91241 G92241	G91242 G92242	G91243 G92243	4.0	5.3
	MF					4.0	5.3
	DM	PG 18 Ga.	G91281 G92281	G91282 G92282	G91283 G92283	2.7	3.6
	MF					2.7	3.6
4"	DM	AL 0.080"	G91221 G92221	G91222 G92222	G91223 G92223	1.5	2.0
	MF					1.5	2.0

Note: Standard grating lengths are 20' or 24'; DM—Double Male, MF—Male-Female

Unpunched smooth surface grating is also available for special applications. Contact Unistrut for more information.

UNITED INTERLOCK® GRATING SYSTEMS—12"



12" Wide Planks, 18 Gauge				
Leg Height	Leg Shape	Finish Material	Slotted, Smooth	Anti-Skid
2 1/2"	DM	PG 18 Gauge	G 11281	G 11282
3"	DM	PG 18 Gauge	G 11583	Contact Factory

For Light Traffic Applications

Ideal for mezzanines and other large-area applications, extra-wide 12" interlocking plank grating is designed to simplify installation and reduce the cost of mezzanines, flooring, decking, staging platforms, Roofwalks® and similar applications. With a 43% open area, it allows water, light and air to pass through.

With its extra width, Unistrut 12" wide plank grating covers more area with fewer planks, lowering installation costs. Its high strength-to-weight ratio—18 gauge, 2 1/2" and 3" leg height—makes it ideal for covering large, light-traffic areas. Its snap-together friction fit make it easy to install, with no welding or bolting required.


Made of pre-galvanized steel, it's maintenance-free and long lasting. Specifiers can choose a smooth or anti-skid surface to meet a wide variety of application needs.



FILLER PANEL



Part No.*	Description
G31183 PG	3" Wide x 1 1/2" Leg Height
G31283 PG	3" Wide x 2 1/2" Leg Height
G31383 PG	3" Wide x 4" Leg Height




Provided in standard lengths of 10' and 12'.

CARRIER PLATE




Part No.*	Description
G603 PG	10 ga.- for 9" wide heavy duty stair treads (1/16" hole and 1 1/2" x 9/16" slot)
G618 PG	10 ga. for 10 1/2" wide stair treads (1/16" hole and 1 1/2" x 9/16" slot)
G642 PG	10 ga. for 11" wide stair treads (1/16" hole and 1 1/2" x 9/16" slot)



Provides easy attachment of stair treads to support structures and stringers.



HEEL/TOE SIDE PLATES – 6 1/2" AND 8" HEIGHTS



Part No.*	Description
G631 PG*	14 ga. x 6 1/2" high x 24' long
G621 PG	14 ga. x 8" high x 12' long

Forms a curb along grating length that defines a structure's side edge, and helps contain loose objects.

*Part numbers shown are for galvanized. Most accessories are also available in aluminum.

HEEL/TOE END PLATES – 6½" AND 8" HEIGHTS


Part No.*	Description
G622 PG	14 ga. x 6½" high x 12' long
G623 PG	14 ga. x 8" high x 12' long

Forms a curb along grating ends that defines a structure's edge, and helps contains loose objects.

HOLD DOWN CLIP


Part No.	Description
G639 PG	1½" leg height
G607 PG*	2½" leg height
G620 PG	4" leg height

A 16 gauge attachment for fastening grating to support structure below. Attaches through top side of grating.

"J" BOLT/NUT LOCK WASHER

Part No.*	Description
G600 EG	½" x 2½"

Attachment for fastening panels to supporting members from underside of grating.



*Part numbers shown are for galvanized. Most accessories are also available in aluminum.




GRATING BEAM CLAMP



Part No.*	Description
G640 EG	Beam clamp

Attaches grating to structural I-beams.
Requires no welding or drilling.




LIGHT GAUGE BEAM CLIP



Part No.*	Description
G124 EG	Light Gauge Beam Clip

Quickly attaches grating to rack or shelving beams.
Requires self-drilling, self-tapping screw—GHTS 012075 EG
(not included).




RECESSED WASHER



Part No.*	Description
G714 EG	1 1/8" x 1 1/8" 12 gauge square washer

Holds down grating from above. Eliminates trip points.




*Part numbers shown are for galvanized. Most accessories are also available in aluminum.

Anyone who has slipped on a stairway can appreciate the safety of the anti-skid stair treads. Those who have tried to clean solid-surface stairs can appreciate our maintenance-free slotted design, which is both rust-resistant and self-cleaning. United's stair treads make it easy for you to meet OSHA regulations. Factors to consider when selecting stair treads include loads, impact, frequency of



use, and future use. Our 10½" and 11" tread features a checker-plate nosing that strengthens the tread and increases the width of the basic 9" tread.

The failure loading data shown below indicates ultimate failure in pounds at various spans. A 3½" diameter load was applied to the outer edge of a 9" wide stair tread at the center of the span. 6" wide stair treads are also available.




The stair treads can also be used with Unistrut Metal Framing as shown here to create a stair with guide rail

9" Stair Tread

14 gauge x 2½" x 9"
Completely galvanized,
welded 10 gauge
end plates



Part No.*	Length (in.)
G 900-24 PG	24
G 900-36 PG	36
G 900-48 PG	48




10½" Stair Tread

14 gauge x 2½" x 10½",
Completely galvanized,
welded 10 gauge end plates




Part No.*	Len. (in.)
G 901-24 PG	24
G 901-36 PG	36
G 901-48 PG	48



11" Stair Treads

14 gauge x 2½" x 11" Completely galvanized, welded 10-gauge end plates

Part No.*	Len. (in.)
G 904-24 PG	24
G 904-36 PG	36
G 904-48 PG	48



Allowable Loads: Interlock Grating Stair Treads—Galvanized Steel—3 Widths			
Width	Distance Between Supports (feet)		
	2	3	4
9"	880	760	640
10½"	1,730	1,360	1,020
11"	1,730	1,360	1,020

Note: Values shown provide a Safety Factor of 2.5



Design Considerations

Designers must consider both uniform and concentrated loads. Design considerations are most critical where loads are concentrated on a small area. As the area of the application gets larger, the reactions approach those of uniform loads.

Point (Concentrated) Loads


Point loads should be distributed over a minimum of two transverse ribs, regardless of what size or gauge plank grating is utilized.

Good design practice for point loading plank grating employs a "foot" plate at the load point with a minimum dimension of 3" x 3". This plate will assure that the point load has been distributed over the two transverse-rib minimum.

Maximum point load per rib on 12" x 18 ga. steel plank grating is 185 lbs.

As a result, through the use of the required 3" x 3" "foot" plate, a maximum design load for the minimum-dimension foot plate is 370 lbs.

Higher loads can be supported by the transverse ribs. However, larger "foot" plates will then be required to distribute the higher loads over additional ribs.



Testing

Unistrut is dedicated to the research, development and testing of all our manufactured products. The United Interlock Grating System has been tested in accordance with section 6 of the American Iron and Steel Institute's (AISI) Specifications for the Design of Cold Formed Steel Structural Members.

Tests for allowable loads were performed on product randomly selected from stock. These tests were run on simple spans with no end restrictions, over a 2" end bearing. Concentrated loads were applied across the plank with a 3" bearing, while uniform loads were applied by stacking narrow strips of sheet steel uniformly over the plank surface. Concentrated load tests for galvanized steel grating were run on all strength combinations for spans of 2', 3', 4', 5', 6', 7', 8', 10', 12', 14', 16' and 18'. Uniform load tests for galvanized steel were run on spans of 2', 3', 4', 6', 8' and 10'.





Concentrated load results are the same for 6" and 9" wide planks.

6" x 14 Gauge	Leg Height	Codes	Distance Between Supports (Feet)														
			2	2.5	3	3.5	4	4.5	5	5.5	6	6.5	7	8	9	10	12
1½"	UL	1,232	788	548	402	293	204	150	113	86	68	54	—	—	—	—	—
	UD	0.05	0.08	0.12	0.16	0.20	0.22	0.25	0.27	0.30	0.32	0.35	—	—	—	—	—
	CL	616	493	411	352	308	274	234	193	162	138	119	—	—	—	—	—
	CD	0.04	0.06	0.10	0.13	0.17	0.21	0.25	0.27	0.30	0.32	0.35	—	—	—	—	—
2½"	UL	4,886	3,296	2,150	1,601	1,257	924	734	597	501	431	369	263	204	150	84	47
	UD	0.15	0.17	0.18	0.22	0.26	0.36	0.41	0.45	0.47	0.52	0.61	0.81	0.89	1.13	1.33	1.42
	CL	2,443	2,060	1,612	1,400	1,257	1,040	917	820	752	700	647	525	460	374	250	165
	CD	0.17	0.17	0.17	0.20	0.22	0.25	0.29	0.34	0.40	0.46	0.55	0.66	0.79	0.90	1.07	1.18
4"	UL	5,261	4,016	3,147	2,321	1,755	1,520	1,307	1,019	858	738	648	548	420	342	215	165
	UD	0.08	0.10	0.11	0.13	0.16	0.16	0.17	0.23	0.27	0.33	0.40	0.52	0.65	0.82	1.07	1.18
	CL	2,630	2,510	2,360	2,080	1,755	1,710	1,633	1,400	1,288	1,200	1,134	1,094	980	854	643	577
	CD	0.13	0.14	0.15	0.17	0.18	0.19	0.20	0.23	0.26	0.30	0.33	0.45	0.57	0.69	0.91	1.26

6" x 18 Gauge	Leg Height	Codes	Distance Between Supports (Feet)														
			2	2.5	3	3.5	4	4.5	5	5.5	6	6.5	7	8	9	10	12
2½"	UL	2,472	1,664	1,220	881	663	516	414	342	284	237	197	164	134	102	66	41
	UD	0.14	0.15	0.16	0.21	0.26	0.31	0.36	0.38	0.44	0.47	0.49	0.79	0.89	1.12	1.37	1.58
	CL	1,236	1,040	915	770	663	580	518	470	426	385	344	327	300	255	200	140
	CD	0.12	0.14	0.16	0.18	0.21	0.24	0.28	0.29	0.30	0.37	0.46	0.61	0.74	0.91	1.20	1.50

6" Aluminum (0.080)	Height	Codes	Distance Between Supports (Feet)													
			2	2.5	3	3.5	4	4.5	5	5.5	6	6.5	7	7.5	8	9
2½"	UL	2,676	1,590	1,065	840	706	600	517	412	313	277	255	210	177	—	—
	UD	0.20	0.30	0.35	0.40	0.47	0.55	0.63	0.78	1.01	1.09	1.20	1.4	1.66	—	—
	CL	1,338	925	825	755	706	630	575	515	469	435	410	385	355	—	—
	CD	0.16	0.20	0.25	0.31	0.36	0.45	0.54	0.67	0.81	0.90	0.99	1.12	1.27	—	—

Code Key: UL = Uniform Load (pounds per square foot)
 UD = Deflection under uniform load (Inches)
 CL = Concentrated Load (pounds)
 CD = Deflection under concentrated load (Inches)



9" x 14 Gauge	Leg Height	Codes	Distance Between Supports (Feet)													
			2	2.5	3	3.5	4	4.5	5	5.5	6	6.5	7	8	9	10
1½"	UL	821	525	365	268	195	136	100	75	57	45	36	—	—	—	—
	UD	0.05	0.08	0.12	0.16	0.2	0.22	0.25	0.27	0.3	0.32	0.35	—	—	—	—
	CL	612	488	405	346	286	222	179	145	118	98	82	—	—	—	—
	CD	0.04	0.06	0.10	0.13	0.16	0.18	0.20	0.22	0.24	0.26	0.28	—	—	—	—
2½"	UL	3257	2197	1433	1067	838	616	489	398	334	287	246	175	136	100	56
	UD	0.15	0.17	0.18	0.22	0.26	0.36	0.41	0.45	0.47	0.52	0.61	0.81	0.89	1.13	1.33
	CL	2439	2055	1606	1393	1249	1031	907	810	740	687	632	509	441	355	228
	CD	0.12	0.14	0.14	0.18	0.21	0.29	0.33	0.36	0.38	0.42	0.49	0.65	0.71	0.90	1.06
4"	UL	3507	2667	2098	1547	1170	1013	871	679	572	492	432	365	280	228	143
	UD	0.08	0.1	0.11	0.13	0.16	0.16	0.17	0.23	0.27	0.33	0.4	0.52	0.65	0.82	1.07
	CL	2625	2494	2353	2022	1745	1699	1621	1387	1273	1184	1117	1076	923	831	615
	CD	0.06	0.08	0.09	0.10	0.13	0.13	0.14	0.18	0.22	0.26	0.32	0.42	0.52	0.66	0.86

9" x 18 Gauge	Leg Height	Codes	Distance Between Supports (Feet)													
			2	2.5	3	3.5	4	4.5	5	5.5	6	6.5	7	8	9	10
2½"	UL	1,648	1,109	813	587	442	344	276	228	189	158	131	109	89	68	44
	UD	0.14	0.15	0.16	0.21	0.26	0.31	0.36	0.38	0.44	0.47	0.49	0.79	0.89	1.12	1.37
	CL	1,236	1,040	915	770	663	580	518	470	426	385	344	327	300	255	200
	CD	0.12	0.14	0.16	0.18	0.21	0.24	0.28	0.29	0.30	0.37	0.46	0.61	0.74	0.91	1.2







9" Aluminum (0.080)	Leg Height	Codes	Distance Between Supports (Feet)													
			2	2.5	3	3.5	4	4.5	5	5.5	6	6.5	7	7.5	8	
2½"	UL	1784	1060	710	560	471	400	345	275	209	185	170	140	118		
	UD	0.20	0.30	0.35	0.40	0.47	0.55	0.63	0.78	1.01	1.09	1.20	1.40	1.66		
	CL	1337	992	797	732	704	672	643	563	466	446	441	388	348		
	CD	0.16	0.24	0.28	0.32	0.38	0.44	0.50	0.62	0.81	0.87	0.96	1.12	1.33		







Code Key: UL = Uniform Load (pounds per square foot)

UD = Deflection under uniform load (Inches)

CL = Concentrated Load (pounds)

CD = Deflection under concentrated load (Inches)









12" x 18 Gauge	Leg Height	Codes	Distance Between Supports (Feet)										
			2	2.5	3	3.5	4	4.5	5	5.5	6	6.5	7
2½"	UL	750	600	500	370	285	225	180	150	127	—	—	—
	UD	0.04	0.07	0.11	0.16	0.20	0.25	0.31	0.37	0.44	—	—	—
	CL	559	559	558	480	421	372	330	301	276	—	—	—
	CD	0.03	0.06	0.09	0.13	0.16	0.20	0.25	0.30	0.35	—	—	—

Code Key: UL = Uniform Load (pounds per square foot)

UD = Deflection under uniform load (Inches)

CL = Concentrated Load (pounds)

CD = Deflection under concentrated load (Inches)



1. GENERAL

1.1 Scope of Work

- A. Provide all material and labor required for the interlocking plank grating as indicated in the contract documents.

1.2 Related Work Specified Elsewhere

- A. Structural Steel
- B. Cold Formed Metal Framing
- C. Metal Fabrications

1.3 Quality Assurance

- A. Material shall be provided by a qualified contractor with at least five (5) years experience in the manufacture of interlock grating. Contractor shall demonstrate experience in projects of similar scope.
- B. Anti-Skid surfaced grating shall conform to Federal Specification RR-G-1602A.
- C. The Grating shall be designed to withstand the following load criteria:
 - 1. Uniform Live Load _____ psf.
 - 2. Concentrated Load _____ lbs.
- D. Contractor shall certify that grating has been tested, indicating maximum allowable uniform and concentrated loads, with a factor of safety of 2, per AISC, Section 6.
- E. If product is required in nuclear and/or safety related application, it shall be supplied under the requirements of nuclear specification 10CFR 50 appendix B.

1.4 Submittals

- A. Contractor shall submit shop drawings showing grating layout, support structure and detailed sections depicting assembly.

2. PRODUCTS

2.1 Acceptable Manufacturer

- A. In order to define the requirements for quality, function, sizes, gauges, surfaces, etc., these material specifications designate manufacturers, brands and other pertinent data that describe the minimum product standards of the products that conform to the project's requirements.
- B. Products of other manufacturers may also be acceptable, provided that such products are equivalent to, or better than, those specified and, further, that use of such substitute products will not involve additional cost to owner due to possible required changes to accommodate them.

C. The alternate (substitute) product must be a proven equivalent to that specified by submitting technical data, test reports, samples, typical details, comparative layout and engineering calculations for evaluation.

D. The acceptance of an alternate (substitute) product is at the discretion of the owner or his agents, whose decision shall be final.

2.2 Products

- A. Grating shall be United Interlock Plank Grating System, as manufactured by Unistrut, 16100 S. Lathrop Ave., Harvey, IL 60426 (U.S.A.), Phone (800) 468-9510.
- B. Materials shall conform to ASTM A653, Grade A with a Class G-90 coating.
- C. Material shall be _____ gauge. With a leg height of _____ inches.
- D. The surface pattern shall provide a minimum of 35% but not more than 42% open area. Openings shall be a minimum of 4" long and a maximum of $\frac{3}{4}$ " width. The surface shall be _____.
 - 1. Anti-Skid surface shall provide 360° positive traction and be made of tapered self-cleaning teeth, approximately $\frac{1}{8}$ " high.
 - 2. Anti-Skid surface teeth shall have slots approximately $\frac{1}{16}$ " wide by $\frac{3}{8}$ " long, uniformly spaced with a minimum of 60 and a maximum of 80 teeth per square foot.

3. INSTALLATION

3.1 Site Examination

- A. Contractor shall examine the support structure, work area and conditions for the grating installation. If the supports, area or conditions are not satisfactory, installation shall not commence until satisfactory conditions are present.

3.2 Erection

- A. Grating shall be installed as detailed on the approved shop drawings.
- B. Grating shall be installed in single, unspliced sections for all requirements to 20' lengths.
- C. Grating shall interlock, with male-female legs providing a lock prohibiting horizontal movement. The outside leg of all members shall be male.
- D. Connections of grating to support elements shall be by bolting, clamping, screwing, welding or use of a manufacturers approved hold-down clip.

Roofwalks® Planks	233
Hardware for Membrane, Foam or Coated Roof.....	233
Standing Seam Installation	233



PROTECT ROOFS FROM BIGFOOT WITH ROOFWALKS® ROOFTOP WALKWAYS

Roofwalk walkways are your low-cost solution to damage caused by rooftop foot traffic. On membrane, built-up, foam and coated roofs, they protect against puncture, abrasion and wear. On standing-seam metal roofs, workers of all sizes – even the Bigfoots of the world – can walk safely on the anti-skid surface without causing seam distortion, “dishing” or harmful stress to roof panels. Steel planks are strong yet lightweight, making installation quick and easy. Thanks to special system hardware, no roof penetration is required for anchoring. Roofwalks are versatile and adapt to any roofing system.




ROOFWALKS® SYSTEMS WILL...

- Provide a safe walkway for rooftop traffic
- Protect the roof from foot traffic
- Resist weather in either galvanized steel or aluminum finish
- Attach to all metal standing-seam roofs (including metric)

ROOFWALKS® SYSTEMS WILL NOT...


- Penetrate rooftop surface (except on rib roofs)
- Trap water ...like rubber pads will
- Curl causing trip hazards ...like rubber pads will
- Disappear in snow ...like rubber pads will
- Rot or disintegrate ...like wood or patio blocks will

ROOFWALK GRATING PLANKS




Interlocking Planks 20' or 24' planks in 6", 9" or 12" widths roll formed from 18 gauge galvanized steel (G-90 coating). Planks available with double-male or male-female leg shapes. Anti-Skid surface and 2 1/2" leg height, standard.

Roofwalk Grating (20' & 24' Stock Lengths)			
Leg Height: 2 1/2"; Finish: PG; Surface: Anti-Skid			
Part No.	Plank Width	Leg Shape	Weight Lbs./Ft.
G 91282	9"	DM	2.7
G 92282		MF	2.7
G 61281	6"	DM	2.3
G 62281		MF	2.3
G 11282	12"	DM	3.2
G 12282		MF	3.2




MEMBRANE / COMPOSITE INSTALLATION



Installation on a membrane roof uses the support stands or the Unipier® sleeper support as a mounting platform.

Refer to our website (www.unistrut.com) for detailed installation instructions and a description of the mounting hardware used.

STANDING SEAM INSTALLATION



Installation on a standing seam roof uses a custom support plate specifically designed for each manufacturers standing seam roof to form a mounting platform.

The mounting hardware also depends on the specific standing seam roof. Refer to our website (www.unistrut.com) for detailed installation instructions and a description of the mounting hardware used.



UNISTRUT

PRODUCT INDEX

004M007 thru 034M040	114	20P-1100, 20V-1100	191	625E-999	19
004T008 thru 098N106, 009N012 thru 106N114	113	20P-1200, 20V-1200	191	625PU	193
1.5 Pipe Strap	158	20P-1300, 20V-1300	191	625PU-000 thru F625PU-350	194
1.5 Pipe Support	158	20P-2000 SST, 20V-2000 SST	190	625PU-125	194
1.5 Spacer	160	20P-2000, 20V-2000	190	625PU-FN-000	194
100	199	20P-2100 SST, 20V-2100 SST	192	750E-999	194
1000E	194	20P-2100, 20V-2100	190	750PU	194
10-DS	163	20P-2200 SST, 20V-2200 SST	192	750PU-FN-000	194
10-H	163	20P-2200, 20V-2200	190	AIC-EC	195
10PU	193	20P-2300 SST, 20V-2300 SST	192	CVHPU	199
12-BS	158	20P-2300, 20V-2300	190	PCR	198
12PU	193	20P-2500, 20V-2500	196	PS	198
16-BS	157	20P-2502, 20V-2502	196	RGBC	200
16-BS	158	20P-2504, 20V-2504	196	UB	195
16-H	163	20P-2506, 20V-2506	196	A1000	171
16-H Base	161	20P-2508, 20V-2508	196	A1000 EA	208
16-H-DB	163	20P-2510, 20V-2510	196	A1001	171
2.5-CS	157	20P-2512, 20V-2512	196	A1001A	172
2.5-CS-7	157	20P-2514, 20V-2514	196	A1001B	172
2.5-SB-H	162	20P-2516, 20V-2516	196	A1001C	172
3-R Spacer	160	20P-2518, 20V-2518	196	A1006	175
3-R-2	158	20P-2520, 20V-2520	196	A1007	175
3-R-2 Pipe Strap	158	20P-2522, 20V-2522	196	A1008	175
3-R-4	158	20P-2524, 20V-2524	196	A1026	176
3-R-4 Pipe Strap	158	20P-2526, 20V-2526	197	A1031	176
3-RAH	159	20P-2528, 20V-2528	197	A1036	176
3-RAH	160	20P-2530, 20V-2530	197	A1047	177
3-RAH Pipe Strap	159	20P-2534, 20V-2534	197	A1063	175
4-RAH-7	160	20P-2540, 20V-2540	197	A1065	175
5-R	158	20PU	193	A1066	176
5-RAH	159	20PU	197	A1068	176
5-SB-H	162	24-BS-4	157	A1184	175
6-DS, 6-DSA	163	200-4101	199	A1184P	175
6-H	163	200-4217 thru F200-4343	193	A1191	175
6-H Base	161	250E	194	A1280	175
6-RAH	159	250PU	194	A1325	176
6-RAH Pipe Strap	159	312PU	193	A1326	176
8-DS, 8-DS-DB, 8-DSA	163	375E	194	A1458	176
8-H	163	375PU	200	A2084	176
8-H Base	161	375PU-000 thru F375PU-300	194	A2110	176
8-H-DB	163	375PU-CN	193	A2126	176
8-RAH	159	375PU-CNHD	193	A2223	176
8-RAH Pipe Strap	159	375PU-FN-000	194	A2227	176
8-SB-H, 8-SB-HD	162	500E-999	194	A2324	176
200-3843	195	500PU	193	A2345	176
20-BS	157	500PU	200	A2472	176
20-BS-7	157	500PU-000	194	A2492	177
20E-5000	195	500PU-FN-000	194	A2494	177
20N	200	50PU	197	A2608 thru A2617	177
20P-1000, 20V-1000	191	50PU-500SP	194	A3006	175
				A3007	175

A3008175	G92141 thru G92143.....	.219	P1001 EA.....	.208
A3016175	G92181 thru G92183.....	.219	P1001 SS206
A3300173	G92221 thru G92223.....	.219	P1001 T27
A3301173	G92241 thru G92243.....	.219	P100327
A3347177	G92281 thru G92283.....	.219	P1004 A27
A4000 EA.....	.208	G92341 thru G92343.....	.219	P1006-083273
A4001 EA.....	.209	G92381 thru G92383.....	.219	P1006-102473
A4006175	HCSS.....	.74	P1006-142073
A4007175	HFLW.....	.75	P1006T142073
A4008175	HFMS74	P100773
A4280175	HHCS74	P100873
A5007175	HHXN75	P1008T73
A5008175	HLKW75	P100973
CG-10 thru CG-40116	HOCW76	P101073
CL04 thru CL18114	HRCN75	P1010T73
CN04 thru CN34115	HRMS74	P101273
Deck Plates 12 SS.....	.160	HSHS74	P1012S73
Deck Plates 18 SS.....	.160	HSQN75	P101673
G 11282233	HSQN050144	P102373
G 12282233	HTHR75	P1023S73
G 61281233	HT04 thru HT34115	P102473
G 62281233	J1205 thru J1280117	P1024S73
G 91282233	K106276	P102682
G 92282233	K106376	P102882
G11281219	K106476	P102984
G12281219	LS 410106	P103182
G124222	LS 500106	P103383
G31183 thru G31383220	M2037133	P103483
G600 thru G639221	M2050133	P103584
G603 thru G642220	M2137133	P103681
G61141 thru G61143219	M2150133	P103783
G61181 thru G61183219	M2250133	P103883
G61221 thru G61223219	M2350133	P1043A88
G61241 thru G61243219	M24144	P104488
G61281 thru G61283219	M2506144	P104586
G61341 thru G61343219	M2508144	P1046A88
G61381 thru G61383219	M2510144	P104787
G62141 thru G62143219	M2512144	P1048, P1049, P105088
G62181 thru G62183219	M2523144	P106281
G62221 thru G62223219	M2524144	P106381
G62241 thru G62243219	MU025 thru MU400111	P106481
G62281 thru G62283219	P100024	P106581
G62341 thru G62343219	P1000 DS24	P106681
G640222	P1000 EA208	P106781
G714222	P1000 H3, P1000 HS, P1000 KO, P1000 SL24	P106882
G900 thru G904223	P1000 SS206	P107591
G91141 thru G91143219	P1000 T, P1000 WT24	P110030
G91181 thru G91183219	P1000HS SS206	P1100 HS, P1100 KO, P1100 SL30
G91221 thru G91223219	P1000T SS206	P1100 SS206
G91241 thru G91243219	P100124	P1100 T30
G91281 thru G91283219	P1001 327	P1100 WT30
G91341 thru G91343219	P1001 A, P1001 A3, P1001 B, P1001 B327	P1100HS SS206
G91381 thru G91383219	P1001 C, P1001 C3, P1001 C41, P1001 D327	P1100T SS206



P1101	30	P1454	86	P1956	84
P1101 A, P1101 B, P1101 C	30	P1455	87	P1957	84
P1101 SS.....	206	P1458	82	P1959	81
P1109 thru P1126	108	P1479A thru P1479E.....	86	P1960	81
P1130	85	P1498	83	P1961	81
P1131	85	P1499	83	P1962	82
P1180	61	P1538A thru P1538D.....	83	P1964	81
P1180W.....	132	P1546, P2094 thru P2100	85	P1973	88
P1184 P	60	P1563 thru P1573.....	109	P1985S.....	100
P1186, P2105 thru P2110.....	85	P1579	84	P1986S.....	100
P1201	103	P1593	91	P2000	33
P1202	103	P1640	97	P2000 HS, P2000 KO, P2000 SL, P2000 T,	
P1203	103	P1648S thru P1653S.....	97	P2000 WT.....	33
P1204 thru P1208.....	103	P1654A thru P1661A.....	97	P2001	33
P1211 thru P1217.....	109	P1690 thru P1697.....	129	P2001 A	33
P1271S.....	98	P16F	134	P2001 B	33
P1272S.....	100	P1703	145	P2001 C	33
P1280	61	P1704	145	P2008 thru P2020.....	109
P1280 EA.....	209	P1713	84	P2024 thru P2070-84	110
P1280A.....	61	P1723	82	P2070	110
P1280W.....	132	P1726	82	P2072 SQ	90
P1281	82	P1727	84	P2072,	90
P1282	82	P1728	84	P2072A SQ	90
P1283	82	P1730	86	P2072A,	90
P1290	84	P1732	88	P2073 SQ	90
P1291	84	P1734	86	P2073,	90
P1315	82	P1736	86	P2073A SQ	90
P1320	87	P1737	88	P2073A,	90
P1325	83	P1747	83	P2079	81
P1326	83	P1750	83	P2101 thru P2104.....	85
P1334	81	P1753, P1754.....	128	P21H.....	134
P1346	83	P1769	90	P2223	89
P1347	86	P1771	90	P2224	89
P1354	104	P1773	91	P2225	89
P1354A.....	104	P1775	91	P2226	89
P1356	82	P1777	91	P2227	89
P1357	84	P1787 thru P1795.....	130	P2228	89
P1358	82	P1796S.....	98	P2229	89
P1359	84	P1821	83	P2230	89
P1363A thru P1363E.....	87	P1822	83	P2231, P2232	93
P1376	87	P1823	83	P2231A, P2232A	93
P1376A.....	87	P1834	102	P2233, P2234	93
P1377	87	P1834A.....	102	P2233A, P2234A	93
P1379S.....	100	P1843	104	P2235	84
P1380	81	P1873	82	P2237	88
P1380 A.....	81	P1887	90	P2243	119
P1381	84	P1924	81	P2245	89
P1382	84	P1925	81	P2260 thru P2270.....	85
P1383	88	P1934	84	P2280	61
P1386	100	P1941	81	P2280A	61
P1425 thru P1431.....	109	P1944	103	P2280W	132
P1430	110	P1950	82	P2324	81
P1453	86	P1953	82	P2325	81

P2326	88	P2535	130	P2859	61
P2328	88	P2536	130	P2860	61
P2329	88	P2537	131	P2862	81
P2341 R-L	89	P2539	131	P2863	81
P2343 R-L	89	P2540	132	P2864	81
P2344 R-L	89	P2540A	132	P2865	144
P2345	89	P2541	132	P2867	98
P2346	89	P2542 thru P254692	P2867A, P2867B	98
P2347	89	P2547 thru P255191	P2868	99
P2348	90	P2552	133	P2868A, P2868B	99
P2354 R-L	103	P2558	110	P2893	99
P2355 R-L	103	P2558	110	P2894	99
P2360	86	P2600	112	P2895	99
P2378	74	P2602	131	P2896	99
P2379	74	P262682	P289795
P2380	74	P2645A thru P2645H129	P289896
P2381	74	P2645H129	P289996
P2382	74	P2647A thru P2647F129	P2900133
P2398S	97	P2649A thru P2649H128	P2901133
P2401S	97	P2655103	P2902133
P2403S	97	P267497	P2903133
P2405S	97	P267595	P2904133
P2407	61	P267696	P2920136
P2407	145	P267796	P2921136
P2452	94	P2679-4, -6 & -896	P2922136
P2453	90	P268296	P2923136
P2454	103	P2749102	P2924136
P2458-18 thru P2458-36	94	P2749N102	P2928136
P2459-36 thru P2459-96	94	P2750102	P2929136
P2469	86	P2750N102	P2930136
P2471	81	P2751102	P2932136
P2472 R-L	89	P2751N102	P2940136
P2473	88	P2755131	P2941, P294290
P2474-1 thru P2474-4	118	P2756131	P2944, P2945, P2946, P294792
P2475	118	P2757131	P2949102
P2476	119	P278495	P2950102
P2481	119	P278598	P300036
P2482	119	P278698	P3000 SS206
P248485	P278798	P3000 HS, P3000 KO, P3000 SL, P3000 T	
P2484W85	P280087	P3000 WT36
P248576	P2801132	P3000HS SS206
P2485K76	P2802132	P3000T SS206
P248676	P2803132	P300136
P249081	P281594	P300673
P2491 R-L thru P2493 R-L91	P2815D94	P300773
P2494 R-L thru P2499 R-L92	P2820136	P300873
P2500 R-L thru P2503 R-L92	P2821136	P300973
P2513 thru P251693	P2822136	P301073
P2513A thru P2516A93	P2823136	P301373
P2521131	P2824-6, -9, -1298	P301673
P2521132	P2855131	P304586
P2522130	P2856131	P304787
P2534-50, P2534-75129	P2857131	P3087100



P3088	100	P3356	143	P4100 SL	45
P3116	133	P3357	143	P4100 T, P4100 WT	45
P3165	144	P3357A	143	P4101	45
P3170	144	P3358	143	P4101 T	45
P3184	60	P3359	143	P4280	61
P3184 EA	209	P3360	143	P4280 EA	209
P3184 F	60	P3361	143	P4280W	132
P3184 P	60	P3362	143	P4376	87
P3245	144	P3363	143	P4376A	87
P3246	141	P3364	143	P4377	87
P3249	142	P3365	143	P4400	48
P3250	142	P3366	143	P4400 HS	48
P3251	142	P3367	143	P4400 SL	48
P3252	142	P3368	143	P4400 T, P4400 WT	48
P3253	142	P3369	143	P4401	48
P3254	142	P3370	143	P4520, P4520 HS, P4520 SL, P4520 T,	
P3255	142	P3380	61	P4520 WT	51
P3256	142	P3380	145	P4521	51
P3257	142	P3409 thru P3417	111	P4663	145
P3257A	142	P3521	131	P4703	145
P3258	142	P3539	131	P4908	73
P3259	142	P3663	145	P5000	54
P3260	142	P3700	145	P5000 HS, P5000 KO, P5000 SL, P5000 T,	
P3261	142	P3703	145	P5000 WT	54
P3262	142	P3704	145	P5001	54
P3263	142	P3712 P	60	P5021	132
P3264	142	P3754	141	P5077	87
P3265	142	P3922 thru P3926	131	P5280	61
P3266	142	P4000	42	P5280W	132
P3267	142	P4000 SS	206	P5500	57
P3268	142	P4000 EA	211	P5500 EA	208
P3269	142	P4000 HS	42	P5500 HS, P5500 KO, P5500 SL, P5500 T,	
P3270	142	P4000 SL	42	P5500 WT	57
P3280	61	P4000 T, P4000 WT	42	P5501	57
P3280	145	P4000HS SS	206	P5506	73
P3280W	132	P4000T SS	206	P5506-1420	73
P3300	39	P4001	42	P5507	73
P3300 HS	39	P4001 EA	208	P5508	73
P3300 SL	39	P4003	42	P5509	73
P3300 SS	206	P4004	42	P5510	73
P3300 T, P3300 WT	39	P4006	73	P5521	131
P3300HS SS	206	P4007	73	P5521 thru P5580	132
P3300T SS	206	P4008	73	P5537	131
P3301	39	P4009	73	P5539	131
P3301 SS	206	P4010	73	P5543	88
P3345	86	P4010T	73	P5545	86
P3349	143	P4012	73	P5547	87
P3350	143	P4023	73	P5560	86
P3351	143	P4043	88	P5577	87
P3352	143	P4045	86	P5580	61
P3353	143	P4047	87	P5580 EA	209
P3354	143	P4100	45	P5580W	132
P3355	143	P4100 HS	45	P6000	180

P6000 EA.....	209	P6887	185	WEEB - WMC	149
P6000 SS	206	P6924	184		
P6001	180	P6925	184		
P6001 EA.....	209	P6962	184		
P6001A, P6001B, P6001C	181	P6973	187		
P6006	184	P7000	182		
P6013	184	P7000 EA.....	209		
P6026	185	P7000 SS	206		
P6028	185	P7001	182		
P6031	185	P7001 EA.....	209		
P6036	185	P7006	184		
P6045	186	P7008 thru P7020.....	187		
P6047	186	P7045	186		
P6048	186	P7047	186		
P6062	184	P7108 thru P7110.....	186		
P6065	184	P7235	185		
P6066	184	P7280	184		
P6067	184	P7324	184		
P6068	185	P7325	184		
P6069	185	P7376	187		
P612	86	P7376A	187		
P6127 thru P6129.....	187	P7377	187		
P6184 P	184	P8000	95		
P6186	186	P8001	95		
P6280	184	P9000	65		
P6281 thru P6283.....	185	P9010	68		
P6325	185	P9011	68		
P6326	185	P9012	68		
P6331	186	P9013	69		
P6332	187	P9014	69		
P6334	185	P9200	65		
P6346	185	P9207	68		
P6347	187	P9209	68		
P6353	187	P9324	68		
P6356A, P6358A.....	184	P97687		
P6357	185	PA 158	215		
P6359	185	PA 1SNB	212		
P6376	186	PA 238	215		
P6376A	186	PA 318	215		
P6377	186	PFL050T	101		
P6379 S	187	PLF9037 thru PLF9100	101		
P6380	185	PUX1234 thru PUX41810.....	116		
P6380A	185	RSS4	153		
P6386	187	SLR100.....	149		
P6453	186	SLR200.....	149		
P6454	186	SPF® 100.....	104		
P6455	187	SPF® 200.....	104		
P6458	185	SPF® 300.....	105		
P6546	186	SPF® 400.....	105		
P6579	185	UB1/2PA thru UB12PA.....	115		
P6726A	184	UP-BK.....	155		
P6737	186	UP-MPDS	155		
P6805 thru P6810.....	187	UP-SPSS	155		



LIMITED WARRANTY

Unistrut® warrants for a period of one year from the date of shipment or completion of installed work, as applicable, that the products or services will be free from defects in workmanship and materials at the time of delivery to the carrier. No warranty is given for products or components that have been (i) manufactured by companies other than Unistrut; (ii) subject to misuse, improper installation, corrosion, or negligence; (iii) disassembled, modified or repaired by unauthorized persons; (iv) used in any manner contrary to Unistrut's instructions or recommendations; or (v) subject to (1) corrosion beyond normal weathering; (2) corrosion caused by disruption of any product coating after production; (3) corrosion occurring at points in the product that have been drilled, cut or welded; or (4) corrosion occurring in unusual or highly corrosive soil, environmental or industrial conditions (in case of corrosion under this subsection (v)(4), Unistrut's limited obligation is to ensure that the product complies with its published specifications).

UNISTRUT DISCLAIMS ALL OTHER WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ANY WARRANTY THAT THE PRODUCTS WILL CONFORM TO ANY SAMPLES, ANY WARRANTY THAT THE PRODUCTS WILL NOT DISCOLOR OR THE TEXTURE OR FINISH WILL NOT CORRODE OR DETERIORATE, AND ANY WARRANTY REGARDING ANY ANCILLARY SERVICES RENDERED.

REMEDY AND LIMITATION OR LIABILITY

If the products do not comply with the warranties set forth in these Terms, Buyer must provide prompt written notice to Unistrut of the non-conformance in reasonably sufficient detail (and such other detail as Unistrut requests) and must comply with Unistrut's instructions and policies regarding the nonconforming product. Buyer must provide such notice within the warranty period. Unistrut's liability will terminate upon expiration of the warranty period. Unistrut's sole liability for non-conforming products will be to repair or replace the non-conforming product or return the purchase price paid therefore, at Unistrut's sole option. Buyer will bear all disassembly, shipment and reinstallation costs of repaired or replaced products. IN NO EVENT WILL UNISTRUT BE LIABLE IN CONTRACT, TORT, STRICT LIABILITY OR OTHERWISE FOR INCIDENTAL, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES, REGARDLESS OF WHETHER UNISTRUT WAS INFORMED OF THE POSSIBILITY OF SUCH DAMAGES, AND IN NO EVENT WILL UNISTRUT'S LIABILITY EXCEED AN AMOUNT EQUAL TO THE SALES PRICE OF THE PRODUCTS.

UNISTRUT[®] DEFENDER™

NEW

CORROSION-RESISTANT PRODUCT LINE

UNISTRUT DEFENDER

VS.

HOT-DIP GALVANIZED



1,000 HOURS CONTINUOUS SALT SPRAY TEST RESULTS

*Unistrut Defender has 3X the performance of traditional
Hot-Dip Galvanized products**

A breakthrough in corrosion resistance for the metal framing industry. Unistrut is proud to introduce a new, corrosion-resistant patent pending product line called Unistrut Defender. Scan the QR code below to watch a quick video showing Unistrut Defender's revolutionary self-healing properties, salt spray test, and more. For more information contact your local sales rep or visit unistrut.us.



[View video](#)



unistrut.us



A PART OF  Atkore
INTERNATIONAL

* Based on average ASTM B117 salt spray test results from an independent, accredited test laboratory.



Unistrut Buffalo Supports

Unistrut Buffalo Supports
a division of Eberl Iron Works, Inc.

Ph: (716) 854-7633
Toll Free: (800) 285-3056
Fax: (716) 854-1184
sales@eberliron.com

eberliron.com



UNISTRUT®



RAZOR RIBBON®

**FLEXHEAD®
INDUSTRIES**

Heritage Plastics™

Konkore FITTINGS

Columbia-MBF™

cope®

**RidgeLine™
Pipe Manufacturing**

**UNISTRUT®
Construction**

**EASTERN
wire + conduit**

POWER-STRUT®

TECTRONTube®



SprinkFLEX®



KAF-TECH®

**SCI
STEEL COMPONENTS INC.**