NHID-Clinical

TECHNICAL REFERENCE

# NHID-Clinical v1.3 Core Specification

Behavioral Baseline for AI Voice Agents in B2B Healthcare Payer–Provider Calls

Version 1.3 · June 2026 · CC BY 4.0
Author: Brianna Baynard · Independent, practitioner-led
NIST Public Comment: NIST-2025-0035-0026

**OPEN PROPOSAL — NOT A STANDARD OR REGULATORY REQUIREMENT**

NHID-Clinical is an early-stage open proposal by Brianna Baynard. It is a voluntary open proposal — not an accredited standard, not a certification program, and not a regulatory requirement. No HIPAA compliance, security guarantees, or liability protection are implied.

## Overview

NHID-Clinical v1.3 defines four deterministic behavioral controls for AI voice agents in B2B healthcare administrative calls. The conformance test suite (CTS) and pytest harness produce identical pass/fail output for the same input — no ambiguity, no interpretation.

NHID-Clinical standardizes **observable disclosure and trace behaviors** only. It does not verify caller identity or certify vendors.

| 5 | 18 | 1222 | 6 |
|---|---|---|---|
| Controls | CTS Cases | Unit Tests | Adapters |

## The Five Controls

Each control maps to RFC 2119 keywords in the full specification. Illustrated cards below summarize the v1.3 behavioral gates.

### IDG-01

Identity Disclosure Gate

Agent MUST identify itself as automated before any PHI exchange. Disclosure in the first substantive utterance.

### PDX-01

Pre-Data Exchange Gate

No PHI (member ID, NPI, DOB, claim number) until IDG-01 disclosure is confirmed.

### DBC-01

Deceptive Behavior Check

No claim of human identity; no deceptive artifacts designed to imply human presence.

### EIT-01

Escalation Implementation Test

Human escalation path communicated; transfer executes immediately on request.

**ATR-01 · Audit Trail (fifth canonical control)**

Machine-readable JSON event trace for every call: disclosure timestamps, state transitions, escalation events, and execution context. Maps to HL7 FHIR R4 AuditEvent (base v4.0.1) — no named Implementation Guide conformance (e.g. IHE BALP) is claimed.

## Conformance Test Suite — 18 Cases

tests/nhid_conformance_test_suite_v1.yaml — representative cases shown; full suite in repository.

| Test ID | What It Verifies | Severity |
|---|---|---|
| CTS-IDG-01 | Disclosure present before any data exchange | critical |

| | | |
|---|---|---|
| CTS-PDX-01 | No PHI before disclosure + consent | critical |
| CTS-DBC-01 | No deceptive audio artifacts in transcript | critical |
| CTS-EIT-01 | Escalation path declared and accessible | critical |
| CTS-ATR-01 | Audit log fields present and well-formed | critical |

## Live Conformance API

Reference implementation on AWS Lambda. Demo routes require no API key; production check uses x-api-key.

| Method | Endpoint | Auth | Purpose |
|---|---|---|---|
| POST | /v1/demo/check | none | Raw NHID event → result |
| POST | /v1/adapters/vapi/check | none | Native VAPI payload → result |
| POST | /v1/adapters/twilio/check | none | Native Twilio payload → result |
| POST | /v1/conformance/check | x-api-key | Production conformance check |
| GET | /health | none | Liveness probe |

**Base URL**
https://gfvq4swdtf.execute-api.us-east-1.amazonaws.com/prod

## NHID-Auth v2 — Cryptographic Agent Identity

Separate reference layer for when behavioral controls alone are insufficient. Public reference code — not deployed trust infrastructure.

**Released June 2026 · CC BY 4.0**
Ed25519 provider-signed agent passports with NPI binding. Scoped delegation chains (max 3 hops). Per-agent and per-delegation revocation. Call-SID nonce binding. Reference: src/agent_identity.py (26 dedicated tests).