UUT REPORT

STATION ID	INRD-PCHINNAR
SERIAL NUMBER	NONE
DATE	Tuesday, July 1, 2025
TIME	4:06:50 PM
OPERATOR	
EXECUTION TIME	37.8584 seconds
NUMBER OF RESULTS	380
UUT RESULT	Passed

Expand / Collapse MainSequence

Begin Sequence: MainSequence
C:\projects\repo\pmic-labview\source\measurements\single point efficiency and load regulation\InstrumentStudio Project\PMIC Simulation\PMIC.seq

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Start - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Sweep LoopRecord 0:2	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Sweep LoopRecord 0:0.001	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						

Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	2
Load Current	0.001
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.001
Efficiency	5
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0047434165						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 1:0.012	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						

Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	2
Load Current	0.012
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.012
Efficiency	60
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 2:0.023	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						

Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	2
Load Current	0.023
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.023
Efficiency	115
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0028460499						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 3:0.034	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						

DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	2
Load Current	0.034
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.034
Efficiency	170
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0056920998						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 4:0.045	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							

Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	2
Load Current	0.045
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.045
Efficiency	225
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0075894664						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 5:0.056	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE

Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	2						
Load Current	0.056						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.056						
Efficiency	280						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0066407831						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 6:0.067	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	2						
Load Current	0.067						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.067						
Efficiency	335						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0009486833						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

Sweep LoopRecord 7:0.078	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	2						
Load Current	0.078						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.078						
Efficiency	390						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0047434165						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			

				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 8:0.089	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	2						
Load Current	0.089						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.089						
Efficiency	445						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0009486833						

measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 9:0.1	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	2						
Load Current	0.1						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.1						
Efficiency	500						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						

range	300 V
reading	150.0047434165
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 1:3	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Sweep LoopRecord 0:0.001	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	3						
Load Current	0.001						

Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.001						
Efficiency	3.333333333333						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0028460499						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 1:0.012	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						

Source Voltage	3						
Load Current	0.012						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.012						
Efficiency	40						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0056920998						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 2:0.023	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						

Load sense	1009
Load voltage limit range	6
Source Voltage	3
Load Current	0.023
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.023
Efficiency	76.66666666667
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 3:0.034	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum	50

power	
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	3
Load Current	0.034
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.034
Efficiency	113.3333333333
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0056920998						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 4:0.045	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						

Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	3
Load Current	0.045
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.045
Efficiency	150
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 5:0.056	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						

Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	3
Load Current	0.056
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.056
Efficiency	186.6666666667
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0018973666						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 6:0.067	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						

Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	3
Load Current	0.067
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.067
Efficiency	223.3333333333
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0047434165						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 7:0.078	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						

DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	3
Load Current	0.078
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.078
Efficiency	260
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0085381497						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 8:0.089	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							

Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	3
Load Current	0.089
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.089
Efficiency	296.6666666667
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0018973666						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 9:0.1	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE

Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	3						
Load Current	0.1						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.1						
Efficiency	333.3333333333						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0066407831						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL	LOW	HIGH	COMPARISON TYPE

				VALUE	LIMIT	LIMIT	
End(Sweep Loop)	Done						
Sweep LoopRecord 2:4	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Sweep LoopRecord 0:0.001	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	4						
Load Current	0.001						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.001						
Efficiency	2.5						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						

channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0066407831
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 1:0.012	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	4						
Load Current	0.012						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.012						
Efficiency	30						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0047434165
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 2:0.023	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	4
Load Current	0.023
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.023
Efficiency	57.5
Load voltages	0.1

Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0066407831						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 3:0.034	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	4						
Load Current	0.034						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.034						

Efficiency	85						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 4:0.045	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	4						
Load Current	0.045						
Outputs							

Status	The measurement is performed successfully
Voltage values	0
Load currents	0.045
Efficiency	112.5
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0037947332						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 5:0.056	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	4						

Load Current	0.056
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.056
Efficiency	140
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0085381497						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 6:0.067	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						

Load voltage limit range	6
Source Voltage	4
Load Current	0.067
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.067
Efficiency	167.5
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0018973666						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 7:0.078	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						

Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	4
Load Current	0.078
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.078
Efficiency	195
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0066407831						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 8:0.089	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current	0.1						

limit	
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	4
Load Current	0.089
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.089
Efficiency	222.5
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0066407831						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 9:0.1	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource	DCPower1						

name	
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	4
Load Current	0.1
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.1
Efficiency	250
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0018973666						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 3:5	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Sweep LoopRecord 0:0.001	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL	LOW	HIGH	COMPARISON TYPE

				VALUE	LIMIT	LIMIT	
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	5						
Load Current	0.001						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.001						
Efficiency	2						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0037947332						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 1:0.012	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	5						
Load Current	0.012						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.012						
Efficiency	24						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0066407831						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE

End(Sweep Loop)	Done						
Sweep LoopRecord 2:0.023	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	5						
Load Current	0.023						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.023						
Efficiency	46						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0009486833						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 3:0.034	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	5						
Load Current	0.034						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.034						
Efficiency	68						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						

reading	150
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 4:0.045	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	5						
Load Current	0.045						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.045						
Efficiency	90						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						

measurement_name	DC voltage
range	300 V
reading	150.0028460499
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 5:0.056	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	5						
Load Current	0.056						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.056						
Efficiency	112						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0028460499
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
⊟ Sweep LoopRecord 6:0.067	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
⊟ Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	5						
Load Current	0.067						
⊟ Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.067						
Efficiency	134						
Load voltages	0.1						

Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0056920998						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 7:0.078	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	5						
Load Current	0.078						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.078						

Efficiency	156						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0056920998						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 8:0.089	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	5						
Load Current	0.089						
Outputs							

Status	The measurement is performed successfully
Voltage values	0
Load currents	0.089
Efficiency	178
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0047434165						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 9:0.1	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	5						

Load Current	0.1
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.1
Efficiency	200
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0028460499						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 4:6	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Sweep LoopRecord 0:0.001	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						

Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	6
Load Current	0.001
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.001
Efficiency	1.666666666667
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0085381497						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 1:0.012	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						

Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	6
Load Current	0.012
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.012
Efficiency	20
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0028460499						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 2:0.023	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						

Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	6
Load Current	0.023
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.023
Efficiency	38.33333333333
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0037947332						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 3:0.034	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	6
Load Current	0.034
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.034
Efficiency	56.66666666667
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0018973666						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 4:0.045	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			

				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	6						
Load Current	0.045						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.045						
Efficiency	75						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0056920998						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep	Done						

LoopRecord 5:0.056							

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	6						
Load Current	0.056						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.056						
Efficiency	93.33333333333						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0028460499						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL	LOW	HIGH	COMPARISON TYPE

				VALUE	LIMIT	LIMIT	
End(Sweep Loop)	Done						
Sweep LoopRecord 6:0.067	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	6						
Load Current	0.067						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.067						
Efficiency	111.6666666667						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0066407831						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 7:0.078	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	6						
Load Current	0.078						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.078						
Efficiency	130						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						

range	300 V
reading	150.0085381497
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 8:0.089	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	6						
Load Current	0.089						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.089						
Efficiency	148.3333333333						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						

channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 9:0.1	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	6						
Load Current	0.1						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.1						
Efficiency	166.6666666667						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0037947332						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 5:7	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Sweep LoopRecord 0:0.001	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						

Load sense	1009
Load voltage limit range	6
Source Voltage	7
Load Current	0.001
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.001
Efficiency	1.428571428571
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 1:0.012	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum	50						

power	
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	7
Load Current	0.012
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.012
Efficiency	17.14285714286
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0066407831						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 2:0.023	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						

Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	7
Load Current	0.023
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.023
Efficiency	32.85714285714
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 3:0.034	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						

Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	7
Load Current	0.034
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.034
Efficiency	48.57142857143
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0047434165						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 4:0.045	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						

Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	7
Load Current	0.045
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.045
Efficiency	64.28571428571
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0085381497						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 5:0.056	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						

DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	7
Load Current	0.056
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.056
Efficiency	80
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0085381497						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 6:0.067	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							

Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	7
Load Current	0.067
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.067
Efficiency	95.71428571429
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0037947332						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 7:0.078	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE

Single Point Efficiency And Load Regulation	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	7
Load Current	0.078
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.078
Efficiency	111.4285714286
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0028460499
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 8:0.089	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	7						
Load Current	0.089						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.089						
Efficiency	127.1428571429						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0028460499						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

Sweep LoopRecord 9:0.1	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	7						
Load Current	0.1						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.1						
Efficiency	142.8571428571						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0056920998						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			

				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 6:8	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Sweep LoopRecord 0:0.001	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	8						
Load Current	0.001						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.001						
Efficiency	1.25						
Load voltages	0.1						

Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0037947332						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 1:0.012	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	8						
Load Current	0.012						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						

Load currents	0.012
Efficiency	15
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0075894664
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 2:0.023	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	8
Load Current	0.023
Outputs	

Status	The measurement is performed successfully
Voltage values	0
Load currents	0.023
Efficiency	28.75
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0009486833
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 3:0.034	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6

Source Voltage	8						
Load Current	0.034						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.034						
Efficiency	42.5						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 4:0.045	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						

Load sense	1009
Load voltage limit range	6
Source Voltage	8
Load Current	0.045
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.045
Efficiency	56.25
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0047434165						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 5:0.056	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum	50

power	
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	8
Load Current	0.056
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.056
Efficiency	70
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0056920998						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 6:0.067	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						

Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	8
Load Current	0.067
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.067
Efficiency	83.75
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0009486833						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 7:0.078	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						

Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	8
Load Current	0.078
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.078
Efficiency	97.5
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0075894664						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 8:0.089	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						

Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	8
Load Current	0.089
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.089
Efficiency	111.25
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 9:0.1	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						

DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	8
Load Current	0.1
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.1
Efficiency	125
Load voltages	0.1
Load voltage deviation	-91.66666666667
Read - DMM	Done
TestResults/Data	
Soft Front Panel	Instrument.sfp
channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 7:9	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS

				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Sweep LoopRecord 0:0.001	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	9						
Load Current	0.001						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.001						
Efficiency	1.111111111111						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0085381497						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 1:0.012	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	9						
Load Current	0.012						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.012						
Efficiency	13.33333333333						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						

range	300 V
reading	150.0075894664
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 2:0.023	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	9						
Load Current	0.023						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.023						
Efficiency	25.55555555556						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						

channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0009486833
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 3:0.034	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	9						
Load Current	0.034						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.034						
Efficiency	37.77777777778						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						

Read - DMM	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0028460499
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 4:0.045	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	9
Load Current	0.045
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.045
Efficiency	50

Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0037947332
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
⊟ Sweep LoopRecord 5:0.056	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
⊟ Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	9
Load Current	0.056
⊟ Outputs	
Status	The measurement is performed successfully
Voltage values	0

Load currents	0.056						
Efficiency	62.22222222222						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0047434165						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 6:0.067	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	9						
Load Current	0.067						

Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.067						
Efficiency	74.44444444444						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0085381497						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 7:0.078	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						

Source Voltage	9
Load Current	0.078
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.078
Efficiency	86.66666666667
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 8:0.089	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						

Load sense	1009						
Load voltage limit range	6						
Source Voltage	9						
Load Current	0.089						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.089						
Efficiency	98.88888888889						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 9:0.1	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum	50						

power	
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	9
Load Current	0.1
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.1
Efficiency	111.1111111111
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0056920998						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 8:10	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Sweep LoopRecord 0:0.001	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						

Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	10
Load Current	0.001
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.001
Efficiency	1
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0075894664						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 1:0.012	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency	Done						

And Load Regulation							

TestResults/Data	
Soft Front Panel	Instrument.sfp
Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	10
Load Current	0.012
Outputs	
Status	The measurement is performed successfully
Voltage values	0
Load currents	0.012
Efficiency	12
Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0037947332
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 2:0.023	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS

				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	10						
Load Current	0.023						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.023						
Efficiency	23						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0018973666						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep	Done						

LoopRecord 3:0.034							

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	10						
Load Current	0.034						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.034						
Efficiency	34						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0085381497						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL	LOW	HIGH	COMPARISON TYPE

				VALUE	LIMIT	LIMIT	
End(Sweep Loop)	Done						
Sweep LoopRecord 4:0.045	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	10						
Load Current	0.045						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.045						
Efficiency	45						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0075894664						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 5:0.056	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	10						
Load Current	0.056						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.056						
Efficiency	56						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						

range	300 V
reading	150.0009486833
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 6:0.067	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	10						
Load Current	0.067						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.067						
Efficiency	67						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						

channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 7:0.078	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	10						
Load Current	0.078						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.078						
Efficiency	78						
Load voltages	0.1						
Load voltage deviation	-91.66666666667						

Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	300 V						
reading	150.0018973666						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 8:0.089	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						
Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	1						
Aperture time	0.005						
Nominal output voltage	1.2						
Source resource name	DCPower1						
Source sense	1009						
Source current limit	0.1						
Source maximum power	50						
Load resource name	DCPower3						
Load sense	1009						
Load voltage limit range	6						
Source Voltage	10						
Load Current	0.089						
Outputs							
Status	The measurement is performed successfully						
Voltage values	0						
Load currents	0.089						
Efficiency	89						

Load voltages	0.1
Load voltage deviation	-91.66666666667

Read - DMM	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0085381497
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
⊟ Sweep LoopRecord 9:0.1	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Point Efficiency And Load Regulation	Done						

TestResults/Data	
Soft Front Panel	Instrument.sfp
⊟ Inputs	
Mode of operation	1
DUT setup time	1
Source delay	1
Aperture time	0.005
Nominal output voltage	1.2
Source resource name	DCPower1
Source sense	1009
Source current limit	0.1
Source maximum power	50
Load resource name	DCPower3
Load sense	1009
Load voltage limit range	6
Source Voltage	10
Load Current	0.1
⊟ Outputs	
Status	The measurement is performed successfully
Voltage values	0

Load currents	0.1
Efficiency	100
Load voltages	0.1
Load voltage deviation	-91.66666666667
Read - DMM	Done
TestResults/Data	
Soft Front Panel	Instrument.sfp
channel_name	Channel 0
measurement_name	DC voltage
range	300 V
reading	150.0018973666
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Stop - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument.sfp						

End Sequence: MainSequence

END UUT REPORT