



# UUT REPORT


STATION ID	DESKTOP-EO1DT2Q
SERIAL NUMBER	NONE
DATE	Wednesday, July 2, 2025
TIME	8:56:10 AM
OPERATOR	
EXECUTION TIME	20.0552 seconds
NUMBER OF RESULTS	254
UUT RESULT	Passed


Expand / Collapse MainSequence


Begin Sequence: MainSequence  
C:\Users\nitest\Desktop\pmic-python\source\single point efficiency and load\InstrumentStudio Project\PMIC  
Simulation\PMIC.seq


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Start - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
 Sweep LoopRecord 0:5	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
 Sweep LoopRecord 0:0.1	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource	PXI1Slot14						

name							
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	-2.480972391343e-06						
measurement_units	Volt (V)						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 1:0.64444444444444	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						


Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	6.753105240721e-05						
measurement_units	Volt (V)						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 2:1.188888888889	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
📁 Inputs							
Mode of operation	1						
DUT setup time	1						

Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	7.46841744499e-06						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 3:1.733333333333	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
 Inputs							
Mode of	1						

operation							
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	-3.630159388529e-06						
measurement_units	Volt (V)						



STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 4:2.277777777778	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						

Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	-5.061120981669e-06						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
<div>Sweep</div> LoopRecord 5:2.822222222222	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						

TestResults/Data							
Soft Front Panel		Instrument_2.sfp					
 Inputs							
Mode of operation		1					
DUT setup time		1					
Source delay		0.005					
Aperture time		0.005					
Nominal output voltage		1.3					
Source resource name		PXI1Slot14					
Source current limit		1					
Source maximum power		300					
Load resource name		PXI1Slot15					
Load voltage limit range		5					
Source Voltage		10					
Load Current		5					
 Outputs							
Status		The measurement is performed successfully					
Load currents		5					
Efficiency		30					
Load voltages		0.06					
Load voltage deviation		-95.38461538462					
Read - DMM		Done					
TestResults/Data							
Soft Front Panel		Instrument_3.sfp					
channel_name		Channel 0					
measurement_name		DC voltage					
range		100 mV					
reading		4.889193037485e-05					
measurement_units		Volt (V)					

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 6:3.366666666667	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE

Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
☒ Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
☒ Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	1.610958778317e-05						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 7:3.911111111111	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS
------	--------	-------------	-------	--------





				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
[-] Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
[-] Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	2.754886975791e-05						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
<div> <div></div> Sweep LoopRecord 8:4.455555555556 </div>	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
☰ Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
☰ Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	1.571722846997e-06						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

 Sweep LoopRecord 9:5	Done						
--	------	--	--	--	--	--	--

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	5.583215329673e-07						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL	LOW	HIGH	COMPARISON TYPE




















Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	9.125146176229e-06						
measurement_units	Volt (V)						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 7:3.911111111111	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
📁 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						



Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
<div>🔌 Outputs</div>							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	3.645890898537e-05						
measurement_units	Volt (V)						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 9:5	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						

Mode of operation	1
DUT setup time	1
Source delay	0.005
Aperture time	0.005
Nominal output voltage	1.3

Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
<div><div></div>Outputs</div>							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	-5.722814212238e-06						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 2:11	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
 Sweep LoopRecord 0:0.1	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE

Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
☒ Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
☒ Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	8.234145388007e-05						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
<div> <div></div> Sweep LoopRecord 1:0.6444444444444444 </div>	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS
------	--------	-------------	-------	--------

				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
📁 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
📁 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	6.855741458052e-05						
measurement_units	Volt (V)						



STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 2:1.188888888889	Done						



STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
☰ Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
☰ Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	-4.870072400658e-06						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

 Sweep LoopRecord 3:1.733333333333	Done						
---	------	--	--	--	--	--	--

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	3.254704589241e-05						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL	LOW	HIGH	COMPARISON TYPE










channel_name	Channel 0
measurement_name	DC voltage
range	100 mV
reading	5.408598094222e-05
measurement_units	Volt (V)


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 8:4.455555555556	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
<div>Inputs</div>							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
<div>Outputs</div>							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						









Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	-2.62916740785e-06						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 1:0.64444444444444	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
📁 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						


Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	9.978439513735e-06						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 2:1.188888888889	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
🔍 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						


Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
<div>📄 Outputs</div>							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	6.549575251094e-06						
measurement_units	Volt (V)						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 3:1.733333333333	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						


Mode of operation	1
DUT setup time	1
Source delay	0.005
Aperture time	0.005
Nominal output voltage	1.3

Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
🔌 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	-3.479289471278e-06						
measurement_units	Volt (V)						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 4:2.27777777778	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						


Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	6.508067786744e-05						
measurement_units	Volt (V)						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 5:2.822222222222	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
<div> <input type="checkbox"/> Inputs         </div>							
Mode of operation	1						
DUT setup time	1						

Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	-3.600818209228e-06						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 6:3.366666666667	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
 Inputs							
Mode of	1						

operation							
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	5.427231397656e-05						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 7:3.911111111111	Done						



STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						




Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	6.331780797161e-05						
measurement_units	Volt (V)						



STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Sweep LoopRecord 8:4.455555555556	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						

TestResults/Data							
Soft Front Panel		Instrument_2.sfp					
 Inputs							
Mode of operation		1					
DUT setup time		1					
Source delay		0.005					
Aperture time		0.005					
Nominal output voltage		1.3					
Source resource name		PXI1Slot14					
Source current limit		1					
Source maximum power		300					
Load resource name		PXI1Slot15					
Load voltage limit range		5					
Source Voltage		10					
Load Current		5					
 Outputs							
Status		The measurement is performed successfully					
Load currents		5					
Efficiency		30					
Load voltages		0.06					
Load voltage deviation		-95.38461538462					
Read - DMM		Done					
TestResults/Data							
Soft Front Panel		Instrument_3.sfp					
channel_name		Channel 0					
measurement_name		DC voltage					
range		100 mV					
reading		-4.351720758441e-06					
measurement_units		Volt (V)					


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 9:5	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE

Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	1.38334539779e-07						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE


End(Sweep Loop)	Done						
 Sweep LoopRecord 4:17	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
 Sweep LoopRecord 0:0.1	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
<div><div></div>Inputs</div>							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
<div><div></div>Outputs</div>							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						



channel_name	Channel 0
measurement_name	DC voltage
range	100 mV
reading	-7.448152768759e-06
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 2:1.188888888889	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
<div>Inputs</div>							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
<div>Outputs</div>							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						





















Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	9.302323880184e-06						
measurement_units	Volt (V)						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 5:20	Done						



STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
 Sweep LoopRecord 0:0.1	Done						


STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
Inputs							

Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	4.365659809187e-05						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 1:0.64444444444444	Done						



STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							


Soft Front Panel		Instrument_2.sfp					
 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel		Instrument_3.sfp					
channel_name		Channel 0					
measurement_name		DC voltage					
range		100 mV					
reading		-3.292073995457e-06					
measurement_units		Volt (V)					

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 2:1.188888888889	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And	Done						



Load Regulation (Py)							
TestResults/Data							
Soft Front Panel		Instrument_2.sfp					
 Inputs							
Mode of operation		1					
DUT setup time		1					
Source delay		0.005					
Aperture time		0.005					
Nominal output voltage		1.3					
Source resource name		PXI1Slot14					
Source current limit		1					
Source maximum power		300					
Load resource name		PXI1Slot15					
Load voltage limit range		5					
Source Voltage		10					
Load Current		5					
 Outputs							
Status		The measurement is performed successfully					
Load currents		5					
Efficiency		30					
Load voltages		0.06					
Load voltage deviation		-95.38461538462					
Read - DMM		Done					
TestResults/Data							
Soft Front Panel		Instrument_3.sfp					
channel_name		Channel 0					
measurement_name		DC voltage					
range		100 mV					
reading		-1.290728057854e-07					
measurement_units		Volt (V)					

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
 Sweep LoopRecord 3:1.733333333333	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS
------	--------	-------------	-------	--------



				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
[-] Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
[-] Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	1.951503600128e-06						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
<div> <div></div> Sweep LoopRecord 4:2.277777777778 </div>	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
☰ Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
☰ Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	2.363198777903e-05						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

 Sweep LoopRecord 5:2.822222222222	Done						
---	------	--	--	--	--	--	--

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
Single Efficiency And Load Regulation (Py)	Done						
TestResults/Data							
Soft Front Panel	Instrument_2.sfp						
 Inputs							
Mode of operation	1						
DUT setup time	1						
Source delay	0.005						
Aperture time	0.005						
Nominal output voltage	1.3						
Source resource name	PXI1Slot14						
Source current limit	1						
Source maximum power	300						
Load resource name	PXI1Slot15						
Load voltage limit range	5						
Source Voltage	10						
Load Current	5						
 Outputs							
Status	The measurement is performed successfully						
Load currents	5						
Efficiency	30						
Load voltages	0.06						
Load voltage deviation	-95.38461538462						
Read - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						
channel_name	Channel 0						
measurement_name	DC voltage						
range	100 mV						
reading	-1.077128951125e-05						
measurement_units	Volt (V)						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL	LOW	HIGH	COMPARISON TYPE











channel_name	Channel 0
measurement_name	DC voltage
range	100 mV
reading	-7.491226943635e-06
measurement_units	Volt (V)

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						

STEP	STATUS	MEASUREMENT	UNITS	LIMITS			
				NOMINAL VALUE	LOW LIMIT	HIGH LIMIT	COMPARISON TYPE
End(Sweep Loop)	Done						
Stop - DMM	Done						
TestResults/Data							
Soft Front Panel	Instrument_3.sfp						

End Sequence: MainSequence

# END UUT REPORT

---