

Package ‘seekr’

August 11, 2021

Type Package

Title seekr: R interface for SEEK API (connection to FAIRDOMHub)

Version 0.1.0.9000

Description The package provides several functions for upload/download of data organized in pISA-tree to SEEK based cloud platform (specifically FAIRDOMHub).

License GPL-3

URL <https://github.com/NIB-SI/seekr>

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Imports knitr,

rio,
tools,
RCurl,
httr,
jsonlite,
pisar

VignetteBuilder knitr

Suggests rmarkdown

R topics documented:

| | |
|--------------------------|----|
| contentType | 2 |
| print.seek_api | 2 |
| skCreate | 3 |
| skData | 5 |
| skDelete | 7 |
| skFindId | 8 |
| skFindTitle | 9 |
| skGet | 10 |
| skLog | 11 |
| skOptions | 12 |
| skParse | 13 |
| skSetOption | 14 |
| skSkeleton | 14 |
| skUpload | 16 |

Index**17**

| | |
|-------------|--------------------------------------|
| contentType | <i>Determine MIME type for file.</i> |
|-------------|--------------------------------------|

Description

Determine MIME type for file.

Usage

```
contentType(file)
```

Arguments

| | |
|------|------------|
| file | file name. |
|------|------------|

Value

MIME type string.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

Examples

```
contentType("bla.txt")
contentType("bla.pdf")
contentType("bla.tar.gz")
contentType("bla.bla")
contentType("bla")
contentType("bla.")
```

| | |
|----------------|---|
| print.seek_api | <i>Print method for seek_api object</i> |
|----------------|---|

Description

Print method for seek_api object

Usage

```
## S3 method for class 'seek_api'
print(x, content = FALSE, ...)
```

Arguments

| | |
|---------|--|
| x | object of class seek_api. |
| content | If FALSE (default), content is no printed. |
| ... | further arguments passed to or from other methods. |

Value

An object (list) of class seek_api.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[skParse](#)

Examples

```
## Not run:
options(.sk$test)
options("sk.myid")
r <- skGet("people",options("sk.myid"))
# Print contents
print( r, TRUE)
# Short version, default
r
r$response$status_code
status_code(r$response)
r$status

## End(Not run)
```

skCreate

Create pISA layer or *sk* component.

Description

Create pISA layer or *sk* component.

Usage

```
skCreate(type = "assays", meta = list(), class = "EXP", file = "NA.TXT")
```

Arguments

| | |
|-------|--|
| type | Component name (e.g. 'people', 'projets', ...). |
| meta | Data frame with pISA metadata or a list with minimal information (Title, Description, *ToDo: add fields*). |
| class | Assay class key string. Possible values are 'EXP' and 'MODEL'. |
| file | File name with path, relative to layer. |

Value

FAIRDOMhub created component.

Note

Upon success (status code 200) details of newly created component can be used. Check status code.
Created component id is set in options.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[skGet](#)

Examples

```
## Not run:
if(FALSE)
{
  options(.sk$test)
  options(sk.prid = 26)
  skOptions("id")
  meta= list(
    Title=paste("Test project", Sys.time())
    , Description="Testing upload")
  meta
  rm(sp)
  sp <- skCreate( type = "projects"
    , meta = meta
    )
  (r <- skFindId("projects",meta$Title))
  sp
  str(skData(sp))
  # Call to API does not set the 'member' field
  # Add member manually in the project page on the web site:
  # /Actions/Administer project members
  #
  options(sk.prid=26, sk.pid=sp$id)
  skOptions("id")
  meta= list(
    Title=paste("Test investigation", Sys.time())
    , Description="Testing upload")
  meta
  rm(si)
  si <- skCreate( type = "investigations"
    , meta=meta
    )
  si
  skData(si)$id
  skFindId("investigations",meta$Title)
  options(sk.iid=si$id)
  skOptions("id")
  #'
  iid=skData(si)$id
  options(sk.prid=26, sk.pid=sp$id, sk.iid=si$id)
  skOptions("id")
  ss <- skCreate( type = "studies"
    , meta= list(
```

```

        Title=paste("Test study", Sys.time())
        , Description="Testing upload")
    )
    ss
    skData(ss)$id
    #'
    options(sk.prid = 26
            , sk.pid=skData(sp)$id
            , sk.iid=skData(si)$id
            , sk.sid=skData(ss)$id
            )
    skOptions()
    sa <- skCreate( type = "assays"
    , meta= list(
        Title=paste("Test assay", Sys.time())
        , Description="Testing upload")
        , class="EXP"
        )
    str(sa)
    skData(sa)$relationships$submitter
    skData(sa)$links
}

# Type: data_file
astring <- "_p_Demo/_I_Test/_S_Show/_A_Work-R/"
oldwd <- setwd(system.file("extdata",astring,package="seekr"))
oldwd
.aname <- getLayer("A")
.aroot <- getRoot("A")
.ameta <- readMeta()
file <- "input/README.MD"
options(sk.prid = 26, sk.pid=sp$id, sk.iid=si$id , sk.sid=ss$id , sk.aid=sa$id)
skOptions()
type <- "data_files"
type <- "documents"
sdat <- skCreate( type = type
    , meta= list(
        Title=paste("Test assay", Sys.time())
        , Description="Testing of upload")
        , file=file
        )
    #str(sdat)
    sdat
    skData(sdat)$id
    if(interactive()) setwd(oldwd)
    getwd()
    res <- sdat$content
    item_link <- file.path(res$meta$base_url,res$links$self)
    if(interactive()) shell.exec(item_link)

## End(Not run)

```

Description

Get content from an **sk** object.

Usage

```
skData(r, node, ...)
```

Arguments

| | |
|-------------------|---|
| <code>r</code> | object retrieved by <code>skGet</code> . |
| <code>node</code> | name of the required element. If missing, a list with all relevant objects is returned. |
| <code>...</code> | further arguments. |

Value

File name (string).

Note

Parameter `...` is ignored at this time.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[get](#)

Examples

```
## Not run:
options(.sk$test)
options("sk.myid")
r <- skGet("people",options("sk.myid"))
d <- skData(r,"attributes")
names(d)
d$last_name
skData(r)$attributes$tools
# Get list of people
r <- skGet("people")
d <- skData(r)
length(d)
names(d)
names(d[[1]])
titles <- sapply(d,function(x) x$attributes$title)
head(titles)
# Get FAIRDOMhub user id
myname <- titles[1]
myname
d[[pmatch(myname,titles)]]
id <- d[[pmatch(myname,titles)]]$id
id
```

```
## End(Not run)
```

| | |
|----------|--------------------------|
| skDelete | <i>Delete component.</i> |
|----------|--------------------------|

Description

Delete component.

Usage

```
skDelete(type, id, uri = options("sk.url"), ...)
```

Arguments

| | |
|------|--------------------------------|
| type | Component type (e.g. "assay"). |
| id | Repository id of component. |
| uri | Repository base address (URI). |
| ... | further arguments. |

Value

Deleted object (list) of class seek_api.

Note

Parameter ... is ignored at this time.
Component id in options is set to NULL.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[skCreate](#)

Examples

```
## Not run:
options(.sk$test)
options("sk.myid")
r <- skDelete("assay", options("sk.aid"))
names(r)
r$response$status_code
status_code(r$response)
r

## End(Not run)
```

`skFindId`*Get details of component with id from an *sk* object.*

Description

Get details of component with id from an *sk* object.

Usage

```
skFindId(type, title)
```

Arguments

| | |
|--------------------|---|
| <code>type</code> | Components name (e.g. 'people', 'projects', ...). |
| <code>title</code> | Character string with the identifier of the component (title part). |

Value

FAIRDOMhub component identifier: id, type and title. If argument title is missing, a data frame with identifiers for all items is returned.

Note

If item is not found, value 0 is returned as id.

Touched component id is set in options.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[skFindTitle](#)

Examples

```
## Not run:
options(.sk$test)
id <- skFindId("people", "Guest")
id
skFindTitle("people", id)
# does not exist
skFindId("people", "No User")
# List of projects
projects <- skFindId("projects")
head(projects)
tail(projects)

## End(Not run)
```

| | |
|-------------|--|
| skFindTitle | <i>Get details of component with id from an *sk* object.</i> |
|-------------|--|

Description

Get details of component with id from an *sk* object.

Usage

```
skFindTitle(type, id)
```

Arguments

| | |
|------|--|
| type | Components name (e.g. 'people', 'projects', ...). |
| id | Character string with the identifier of the component (id part). |

Value

FAIRDOMhub component identifier: id, type and title. If argument title is missing, a data frame with identifiers for all items is returned. See note.

Note

If item is not found, empty string is returned as title.

Touched component id is set in options.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[skFindTitle](#)

Examples

```
## Not run:  
skFindTitle("people",0)  
  
## End(Not run)
```

| | |
|-------|---|
| skGet | <i>Get information from repository.</i> |
|-------|---|

Description

Get information from repository.

Usage

```
skGet(type, id, uri = options("sk.url"), ...)
```

Arguments

| | |
|------|--------------------------------------|
| type | Type of information (e.g. "person"). |
| id | Repository id of an item. |
| uri | Repository base address (URI). |
| ... | further arguments. |

Value

An object (list) of class seek_api.

Note

Parameter ... is ignored at this time.

Touched component id is set in options.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[get](#)

Examples

```
## Not run:
options(.sk$test)
options("sk.myid")
r <- skGet("people", options("sk.myid"))
names(r)
r$response$status_code
status_code(r$response)
r
# Non existent user
skGet("people", 0)

## End(Not run)
```

| | |
|-------|-------------------------------------|
| skLog | <i>Writes a note to a log file.</i> |
|-------|-------------------------------------|

Description

Writes a note to a log file.

Usage

```
skLog(..., file = "FAIRDOM.log", append = TRUE)
```

Arguments

| | |
|--------|------------------------------|
| ... | Objects to form a line. |
| file | Log file name. |
| append | Control append/rewrite mode. |

Value

System time of invoking..

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[skGet](#)

Examples

```
tst <- function(){
  skLog("Test", "writing to logfile", file="")
  fht <- system.time(Sys.sleep(1))
  skLog( "Time:", round(fht["elapsed"],2))
}
tst()
rm(tst)
```

skOptions

Show all seekr related options

Description

Lists selected seekr related options that are set in via the options function. Selection is based on the start and end of the name. All seekr options start with prefix 'sk.'. Argument end give the required suffix for the option to be listed. Typical use would be to list identifiers, when end = "id".

Usage

```
skOptions(end = "", start = "sk.", hide = "sk.pwd")
```

Arguments

| | |
|-------|---|
| end | character string defining the end of the string. By default all names are valid (empty string). |
| start | character string defining the start of the name, default is "sk.", which is typical for seekr options. |
| hide | vector of names, that should not be listed. Default is "sk.pwd" which prevents password to be revealed. |

Value

A list of seekr related options.

Note

At the moment two locations are available: main FAIRDOMHub (<https://www.fairdomhub.org/>) and testing site (<https://testing.sysmo-db.org>).

Function options() is used to store server location, user credentials and pISA layer identifications. Options that can be declared: sk.url (server location), sk.usr (username), sk.pwd (password), sk.myid (user id on server), sk.instid (user's institution id), sk.prid (program id), sk.pid (project id), sk.iid (investigation id), sk.sid (study id), sk.aid (assay id).

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[startsWith](#), [endsWith](#)

Examples

```
## Not run:
options(sk.myid=368)
skOptions()
skOptions("id")
skOptions(hide=NULL)

## End(Not run)
```

`skParse`*Parse the response from SEEK API and convert to a list.*

Description

Parse the response from SEEK API and convert to a list.

Usage

```
skParse(resp, ...)
```

Arguments

| | |
|-------------------|-------------------------|
| <code>resp</code> | response from SEEK API. |
| <code>...</code> | further arguments. |

Value

An object (list) of class `seek_api`.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[skGet](#)

Examples

```
## Not run:
options(.sk$test)
options("sk.myid")
r <- skGet("people",options("sk.myid"))
names(r)
r$response$status_code
status_code(r$response)
names(r$content)
r
r <- skGet("people")
length(r$content)
names(r$content)
r$content[[1]]
names(r)
r

## End(Not run)
```

| | |
|-------------|---|
| skSetOption | <i>Sets seekr option according to the type.</i> |
|-------------|---|

Description

Sets seekr option according to the type.

Usage

```
skSetOption(type, id)
```

Arguments

| | |
|------|--|
| type | Components name (e.g. 'people', 'projects', ...). |
| id | Character string with the identifier of the component (id part). |

Value

A list with the set option or NA if the type is not registered.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[skFindTitle](#)

Examples

```
## Not run:
skSetOption("people",111)
skSetOption("myid", 368)
skOptions()
skSetOption("bla",1)

## End(Not run)
```

| | |
|------------|------------------------------|
| skSkeleton | <i>Create *sk* skeleton.</i> |
|------------|------------------------------|

Description

Creates *sk* object with required structure.

Usage

```
skSkeleton(type = "assay", meta)
```

Arguments

| | |
|------|--|
| type | component name (e.g. 'people', 'projects', ...). |
| meta | a data frame with pISA metadata or a list with minimal information (Title, Description, *ToDo: add fields*). |

Value

A list with the minimal information structure.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[skCreate](#)

Examples

```
## Not run:
require(jsonlite)
meta <- list(Title = "Test layer", Description = "Some description")
type <- "projects"
sp <- skSkeleton( type = type
  , meta= meta
)
str(sp)
type = "investigations"
si <- skSkeleton( type = type
  , meta= meta
)
str(si)
type = "studies"
ss <- skSkeleton( type = type
  , meta= meta
)
str(ss)
type = "assays"
sa <- skSkeleton( type = type
  , meta= meta
)
str(sa)

type = "data_files"
file =
sdata <- skSkeleton( type = type
  , meta= meta
)
str(sdata)

## End(Not run)
```

skUpload

Upload file.

Description

Upload file to a created object of type 'documents' or 'data_files'.

Usage

```
skUpload(object, file)
```

Arguments

| | |
|--------|--|
| object | A previously created SEEK component. Must be one of 'documents' or 'data_files'. |
| file | File name with path, relative to layer. |

Value

FAIRDOMhub created component.

Note

Upon success (status code 200) details of newly created component can be used. Check status code.

Author(s)

Andrej Blejec <andrej.blejec@nib.si>

See Also

[skCreate](#)

Examples

```
## Not run:
file <- dir()[1]
file
fhd <- skCreate("documents",meta,file=file)
fhd
sd <- skUpload(fhd, file)

## End(Not run)
```


Index

* **file**

skData, [5](#)

skGet, [10](#)

* **pisa**

contentType, [2](#)

skCreate, [3](#)

skFindId, [8](#)

skFindTitle, [9](#)

skLog, [11](#)

skSkeleton, [14](#)

skUpload, [16](#)

contentType, [2](#)

endsWith, [12](#)

get, [6](#), [10](#)

print.seek_api, [2](#)

skCreate, [3](#), [7](#), [15](#), [16](#)

skData, [5](#)

skDelete, [7](#)

skFindId, [8](#)

skFindTitle, [8](#), [9](#), [9](#), [14](#)

skGet, [4](#), [10](#), [11](#), [13](#)

skLog, [11](#)

skOptions, [12](#)

skParse, [3](#), [13](#)

skSetOption, [14](#)

skSkeleton, [14](#)

skUpload, [16](#)

startsWith, [12](#)