

ENROLL NO: 202300819010082

NAME:Modi Nirmeet

Q: 1

```
import java.io.IOException;
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.Mapper;
import org.apache.hadoop.mapreduce.Reducer;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;

public class WordCount {

    public static class TokenizerMapper extends Mapper<Object, Text, Text, IntWritable>
    {
        private final static IntWritable one = new IntWritable(1);
        private Text word = new Text();
```

```

    public void map(Object key, Text value, Context context) throws IOException,
        InterruptedException {
        String[] tokens = value.toString().split("\\s+");
        for (String token : tokens) {
            word.set(token);
            context.write(word, one);
        }
    }
}

```

```

    public static class IntSumReducer extends Reducer<Text, IntWritable, Text,
        IntWritable> {
        public void reduce(Text key, Iterable<IntWritable> values, Context context) throws
            IOException, InterruptedException {
            int sum = 0;
            for (IntWritable val : values) {
                sum += val.get();
            }
            context.write(key, new IntWritable(sum));
        }
    }
}

```

```

    public static void main(String[] args) throws Exception {
        Configuration conf = new Configuration();
        Job job = Job.getInstance(conf, "word count");
        job.setJarByClass(WordCount.class);
        job.setMapperClass(TokenizerMapper.class);
    }
}

```

```
    job.setCombinerClass(IntSumReducer.class);
    job.setReducerClass(IntSumReducer.class);
    job.setOutputKeyClass(Text.class);
    job.setOutputValueClass(IntWritable.class);

    FileInputFormat.addInputPath(job, new Path(args[0]));
    FileOutputFormat.setOutputPath(job, new Path(args[1]));

    System.exit(job.waitForCompletion(true) ? 0 : 1);
}
}
```

## Q: 2

```
import java.io.IOException;
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.Mapper;
import org.apache.hadoop.mapreduce.Reducer;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;
```

```

public class MinTemperature {

    public static class TempMapper extends Mapper<Object, Text, Text, IntWritable> {
        private Text year = new Text();
        private IntWritable temperature = new IntWritable();

        public void map(Object key, Text value, Context context) throws IOException,
        InterruptedException {
            String[] fields = value.toString().split("\\s+");
            if (fields.length == 2) {
                year.set(fields[0]);
                temperature.set(Integer.parseInt(fields[1]));
                context.write(year, temperature);
            }
        }
    }

    public static class MinTempReducer extends Reducer<Text, IntWritable, Text,
    IntWritable> {
        public void reduce(Text key, Iterable<IntWritable> values, Context context) throws
        IOException, InterruptedException {
            int minTemp = Integer.MAX_VALUE;
            for (IntWritable val : values) {
                minTemp = Math.min(minTemp, val.get());
            }
            context.write(key, new IntWritable(minTemp));
        }
    }
}

```

```
}
```

```
public static void main(String[] args) throws Exception {  
    Configuration conf = new Configuration();  
    Job job = Job.getInstance(conf, "minimum temperature");  
    job.setJarByClass(MinTemperature.class);  
    job.setMapperClass(TempMapper.class);  
    job.setReducerClass(MinTempReducer.class);  
    job.setOutputKeyClass(Text.class);  
    job.setOutputValueClass(IntWritable.class);  
  
    FileInputFormat.addInputPath(job, new Path(args[0]));  
    FileOutputFormat.setOutputPath(job, new Path(args[1]));  
  
    System.exit(job.waitForCompletion(true) ? 0 : 1);  
}  
}
```

Q: 3

```
import java.io.IOException;  
import org.apache.hadoop.conf.Configuration;  
import org.apache.hadoop.fs.Path;  
import org.apache.hadoop.io.IntWritable;
```

```

import org.apache.hadoop.io.LongWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.Mapper;
import org.apache.hadoop.mapreduce.Reducer;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;

public class AverageTokenCount {

    public static class TokenizerMapper extends Mapper<Object, Text, Text, IntWritable>
    {
        private final static IntWritable one = new IntWritable(1);
        private Text word = new Text();

        public void map(Object key, Text value, Context context) throws IOException,
        InterruptedException {
            String[] tokens = value.toString().split("\\s+");
            for (String token : tokens) {
                word.set(token);
                context.write(word, one);
            }
            context.write(new Text("***LINE_COUNT***"), new IntWritable(tokens.length));
        }
    }

    public static class WordCountReducer extends Reducer<Text, IntWritable, Text,
    IntWritable> {

```

```
private IntWritable result = new IntWritable();
```

```
public void reduce(Text key, Iterable<IntWritable> values, Context context) throws  
IOException, InterruptedException {  
    int sum = 0;  
    for (IntWritable val : values) {  
        sum += val.get();  
    }  
    if (!key.toString().equals("***LINE_COUNT**")) {  
        result.set(sum);  
        context.write(key, result);  
    } else {  
        context.write(new Text("TOTAL_TOKENS"), new IntWritable(sum));  
    }  
}  
}
```

```
public static class AverageReducer extends Reducer<Text, IntWritable, Text, Text> {  
    private int totalTokens = 0;  
    private int wordCount = 0;
```

```
public void reduce(Text key, Iterable<IntWritable> values, Context context) throws  
IOException, InterruptedException {  
    if (key.toString().equals("TOTAL_TOKENS")) {  
        for (IntWritable val : values) {  
            totalTokens = val.get();  
        }  
    } else {
```

```

        for (IntWritable val : values) {
            wordCount++;
        }
    }
}

```

```

@Override
protected void cleanup(Context context) throws IOException, InterruptedException
{
    float averageCount = (float) totalTokens / wordCount;
    context.write(new Text("AverageCount"), new Text("=" + averageCount));
}
}

```

```

public static void main(String[] args) throws Exception {
    Configuration conf = new Configuration();
    Job job = Job.getInstance(conf, "average token count");
    job.setJarByClass(AverageTokenCount.class);
    job.setMapperClass(TokenizerMapper.class);
    job.setCombinerClass(WordCountReducer.class);
    job.setReducerClass(AverageReducer.class);
    job.setOutputKeyClass(Text.class);
    job.setOutputValueClass(IntWritable.class);

    FileInputFormat.addInputPath(job, new Path(args[0]));
    FileOutputFormat.setOutputPath(job, new Path(args[1]));

    System.exit(job.waitForCompletion(true) ? 0 : 1);
}

```



```
}  
}
```

Q: 4

```
import java.io.IOException;  
import org.apache.hadoop.conf.Configuration;  
import org.apache.hadoop.fs.Path;  
import org.apache.hadoop.io.IntWritable;  
import org.apache.hadoop.io.Text;  
import org.apache.hadoop.mapreduce.Job;  
import org.apache.hadoop.mapreduce.Mapper;  
import org.apache.hadoop.mapreduce.Reducer;  
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;  
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;  
  
public class TokenCount {  
  
    public static class TokenMapper extends Mapper<Object, Text, Text, IntWritable> {  
        private final static IntWritable one = new IntWritable(1);  
        private Text token = new Text("TOKEN_COUNT");  
  
        public void map(Object key, Text value, Context context) throws IOException,  
            InterruptedException {  
            String[] tokens = value.toString().split("\\s+");  
            for (String word : tokens) {
```

```

        if (word.length() >= 4) {
            context.write(token, one);
        }
    }
}

```

```

public static class TokenReducer extends Reducer<Text, IntWritable, Text,
IntWritable> {

    public void reduce(Text key, Iterable<IntWritable> values, Context context) throws
IOException, InterruptedException {

        int sum = 0;

        for (IntWritable val : values) {
            sum += val.get();
        }

        context.write(new Text("Total count for token"), new IntWritable(sum));
    }
}

```

```

public static void main(String[] args) throws Exception {

    Configuration conf = new Configuration();
    Job job = Job.getInstance(conf, "token count");
    job.setJarByClass(TokenCount.class);
    job.setMapperClass(TokenMapper.class);
    job.setReducerClass(TokenReducer.class);
    job.setOutputKeyClass(Text.class);
    job.setOutputValueClass(IntWritable.class);
}

```

```

FileInputFormat.addInputPath(job, new Path(args[0]));
FileOutputFormat.setOutputPath(job, new Path(args[1]));

System.exit(job.waitForCompletion(true) ? 0 : 1);
}
}

```

Q: 5

```

import java.io.IOException;
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.Mapper;
import org.apache.hadoop.mapreduce.Reducer;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;

public class FemaleVoterSimple {

    public static class VoterMapper extends Mapper<Object, Text, Text, IntWritable> {

```

```

private final static IntWritable one = new IntWritable(1);
private Text femaleKey = new Text("FemaleVoterCount");

public void map(Object key, Text value, Context context) throws IOException,
InterruptedException {
    String[] fields = value.toString().split(",");
    if (fields.length == 4 && fields[2].equalsIgnoreCase("Female")) {
        context.write(femaleKey, one);
    }
}

public static class VoterReducer extends Reducer<Text, IntWritable, Text,
IntWritable> {

    public void reduce(Text key, Iterable<IntWritable> values, Context context) throws
IOException, InterruptedException {
        int totalFemales = 0;
        for (IntWritable val : values) {
            totalFemales += val.get();
        }
        context.write(new Text("No. of female voters are: "), new
IntWritable(totalFemales));
    }
}

```

```

public static void main(String[] args) throws Exception {
    Configuration conf = new Configuration();
    Job job = Job.getInstance(conf, "female voter count");
}

```

```
    job.setJarByClass(FemaleVoterSimple.class);
    job.setMapperClass(VoterMapper.class);
    job.setReducerClass(VoterReducer.class);
    job.setOutputKeyClass(Text.class);
    job.setOutputValueClass(IntWritable.class);

    FileInputFormat.addInputPath(job, new Path(args[0]));
    FileOutputFormat.setOutputPath(job, new Path(args[1]));

    System.exit(job.waitForCompletion(true) ? 0 : 1);
}
}
```

## Q: 6

```
import java.io.IOException;
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.Mapper;
import org.apache.hadoop.mapreduce.Reducer;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;
```

```

public class UserReviewCount {

    public static class ReviewMapper extends Mapper<Object, Text, Text, IntWritable> {
        private final static IntWritable one = new IntWritable(1);
        private Text userId = new Text();

        public void map(Object key, Text value, Context context) throws IOException,
        InterruptedException {
            String[] fields = value.toString().split(",");
            if (fields.length > 0) {
                userId.set(fields[0].trim());
                context.write(userId, one);
            }
        }
    }

    public static class ReviewReducer extends Reducer<Text, IntWritable, Text,
    IntWritable> {

        public void reduce(Text key, Iterable<IntWritable> values, Context context) throws
        IOException, InterruptedException {
            int totalReviews = 0;
            for (IntWritable val : values) {
                totalReviews += val.get();
            }
            context.write(key, new IntWritable(totalReviews));
        }
    }
}

```

```

    }
}

public static void main(String[] args) throws Exception {
    Configuration conf = new Configuration();
    Job job = Job.getInstance(conf, "user review count");
    job.setJarByClass(UserReviewCount.class);
    job.setMapperClass(ReviewMapper.class);
    job.setReducerClass(ReviewReducer.class);
    job.setOutputKeyClass(Text.class);
    job.setOutputValueClass(IntWritable.class);

    FileInputFormat.addInputPath(job, new Path(args[0]));
    FileOutputFormat.setOutputPath(job, new Path(args[1]));

    System.exit(job.waitForCompletion(true) ? 0 : 1);
}
}

```

**Q: 7**

**7.1**

```

import java.io.IOException;
import org.apache.hadoop.conf.Configuration;

```

```

import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.Mapper;
import org.apache.hadoop.mapreduce.Reducer;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;

public class ComedyMovies {

    public static class ComedyMapper extends Mapper<Object, Text, Text, Text> {

        public void map(Object key, Text value, Context context) throws IOException,
        InterruptedException {
            String[] fields = value.toString().split(",");
            if (fields.length > 2 && fields[2].contains("Comedy")) {
                context.write(new Text(fields[1]), value);
            }
        }
    }

    public static class IdentityReducer extends Reducer<Text, Text, Text, Text> {

        public void reduce(Text key, Iterable<Text> values, Context context) throws
        IOException, InterruptedException {
            for (Text val : values) {
                context.write(key, val);
            }
        }
    }
}

```



```

public static void main(String[] args) throws Exception {
    Configuration conf = new Configuration();
    Job job = Job.getInstance(conf, "comedy movies");
    job.setJarByClass(ComedyMovies.class);
    job.setMapperClass(ComedyMapper.class);
    job.setReducerClass(IdentityReducer.class);
    job.setOutputKeyClass(Text.class);
    job.setOutputValueClass(Text.class);

    FileInputFormat.addInputPath(job, new Path(args[0]));
    FileOutputFormat.setOutputPath(job, new Path(args[1]));
    System.exit(job.waitForCompletion(true) ? 0 : 1);
}
}

```

## 7.2

```

import java.io.IOException;
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.Mapper;
import org.apache.hadoop.mapreduce.Reducer;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;

```

```

import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;

public class DocumentaryMovies1995 {

    public static class DocumentaryMapper extends Mapper<Object, Text, Text,
IntWritable> {

        private final static IntWritable one = new IntWritable(1);
        private Text word = new Text("Documentary_1995");

        public void map(Object key, Text value, Context context) throws IOException,
InterruptedException {
            String[] fields = value.toString().split(",");
            if (fields.length > 2 && fields[2].contains("Documentary") &&
fields[1].contains("(1995)")) {
                context.write(word, one);
            }
        }
    }

    public static class SumReducer extends Reducer<Text, IntWritable, Text, IntWritable>
    {

        public void reduce(Text key, Iterable<IntWritable> values, Context context) throws
IOException, InterruptedException {
            int sum = 0;
            for (IntWritable val : values) {
                sum += val.get();
            }
            context.write(key, new IntWritable(sum));
        }
    }
}

```

```

public static void main(String[] args) throws Exception {
    Configuration conf = new Configuration();
    Job job = Job.getInstance(conf, "documentary count 1995");
    job.setJarByClass(DocumentaryMovies1995.class);
    job.setMapperClass(DocumentaryMapper.class);
    job.setReducerClass(SumReducer.class);
    job.setOutputKeyClass(Text.class);
    job.setOutputValueClass(IntWritable.class);

    FileInputFormat.addInputPath(job, new Path(args[0]));
    FileOutputFormat.setOutputPath(job, new Path(args[1]));
    System.exit(job.waitForCompletion(true) ? 0 : 1);
}
}

```

## 7.3

```

import java.io.IOException;
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.Mapper;
import org.apache.hadoop.mapreduce.Reducer;

```

```

import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;

public class MissingGenresCount {

    public static class MissingGenresMapper extends Mapper<Object, Text, Text,
    IntWritable> {

        private final static IntWritable one = new IntWritable(1);
        private Text word = new Text("Missing_Genres");

        public void map(Object key, Text value, Context context) throws IOException,
        InterruptedException {
            String[] fields = value.toString().split(",");
            if (fields.length < 3 || fields[2].trim().isEmpty()) {
                context.write(word, one);
            }
        }
    }

    public static class SumReducer extends Reducer<Text, IntWritable, Text, IntWritable>
    {

        public void reduce(Text key, Iterable<IntWritable> values, Context context) throws
        IOException, InterruptedException {
            int sum = 0;
            for (IntWritable val : values) {
                sum += val.get();
            }
            context.write(key, new IntWritable(sum));
        }
    }
}

```

```

public static void main(String[] args) throws Exception {
    Configuration conf = new Configuration();
    Job job = Job.getInstance(conf, "missing genres count");
    job.setJarByClass(MissingGenresCount.class);
    job.setMapperClass(MissingGenresMapper.class);
    job.setReducerClass(SumReducer.class);
    job.setOutputKeyClass(Text.class);
    job.setOutputValueClass(IntWritable.class);

    FileInputFormat.addInputPath(job, new Path(args[0]));
    FileOutputFormat.setOutputPath(job, new Path(args[1]));
    System.exit(job.waitForCompletion(true) ? 0 : 1);
}
}

```

## 7.4

```

import java.io.IOException;
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.Mapper;
import org.apache.hadoop.mapreduce.Reducer;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;

```

```

import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;

public class GoldMovies {

    public static class GoldMapper extends Mapper<Object, Text, Text, Text> {
        public void map(Object key, Text value, Context context) throws IOException,
        InterruptedException {
            String[] fields = value.toString().split(",");
            if (fields.length > 1 && fields[1].contains("Gold")) {
                context.write(new Text(fields[1]), value);
            }
        }
    }

    public static class IdentityReducer extends Reducer<Text, Text, Text, Text> {
        public void reduce(Text key, Iterable<Text> values, Context context) throws
        IOException, InterruptedException {
            for (Text val : values) {
                context.write(key, val);
            }
        }
    }

    public static void main(String[] args) throws Exception {
        Configuration conf = new Configuration();
        Job job = Job.getInstance(conf, "gold movies");
        job.setJarByClass(GoldMovies.class);
        job.setMapperClass(GoldMapper.class);
        job.setReducerClass(IdentityReducer.class);
    }
}

```

```

        job.setOutputKeyClass(Text.class);
        job.setOutputValueClass(Text.class);

        FileInputFormat.addInputPath(job, new Path(args[0]));
        FileOutputFormat.setOutputPath(job, new Path(args[1]));
        System.exit(job.waitForCompletion(true) ? 0 : 1);
    }
}

```

## 7.5

```

import java.io.IOException;
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.Mapper;
import org.apache.hadoop.mapreduce.Reducer;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;

public class DramaRomanceMovies {

    public static class DramaRomanceMapper extends Mapper<Object, Text, Text,
IntWritable> {

```

```

private final static IntWritable one = new IntWritable(1);
private Text word = new Text("Drama_Romance");

    public void map(Object key, Text value, Context context) throws IOException,
InterruptedException {
        String[] fields = value.toString().split(",");
        if (fields.length > 2 && fields[2].contains("Drama") &&
fields[2].contains("Romance")) {
            context.write(word, one);
        }
    }
}

public static class SumReducer extends Reducer<Text, IntWritable, Text, IntWritable>
{
    public void reduce(Text key, Iterable<IntWritable> values, Context context) throws
IOException, InterruptedException {
        int sum = 0;
        for (IntWritable val : values) {
            sum += val.get();
        }
        context.write(key, new IntWritable(sum));
    }
}

public static void main(String[] args) throws Exception {
    Configuration conf = new Configuration();
    Job job = Job.getInstance(conf, "drama romance movies count");
    job.setJarByClass(DramaRomanceMovies.class);
    job.setMapperClass(DramaRomanceMapper.class);

```



```
    job.setReducerClass(SumReducer.class);  
    job.setOutputKeyClass(Text.class);  
    job.setOutputValueClass(IntWritable.class);  
  
    FileInputFormat.addInputPath(job, new Path(args[0]));  
    FileOutputFormat.setOutputPath(job, new Path(args[1]));  
    System.exit(job.waitForCompletion(true) ? 0 : 1);  
}  
}
```