

Linux Basic commands

Class no:10

1. To create a folder also called directory: **mkdir directoryname**

```
[ec2-user@ip-172-31-46-226 ~]$ pwd
/home/ec2-user
[ec2-user@ip-172-31-46-226 ~]$ mkdir file1.txt
[ec2-user@ip-172-31-46-226 ~]$ ls
file1.txt
[ec2-user@ip-172-31-46-226 ~]$ mkdir file2.txt file3.txt
[ec2-user@ip-172-31-46-226 ~]$ ls
file1.txt file2.txt file3.txt
```

2. To create an empty file: **touch filename**

```
[ec2-user@ip-172-31-46-226 ~]$ touch data.txt
[ec2-user@ip-172-31-46-226 ~]$ touch log.txt data2.txt
[ec2-user@ip-172-31-46-226 ~]$ ls
data.txt data2.txt file1.txt file2.txt file3.txt log.txt
```

3. To get inside of the folder using change directory,

- (i) absolute path: **cd /home/folder-name/file-name**

```
[ec2-user@ip-172-31-46-226 ~]$ cd /home/ec2-user/file1.txt
[ec2-user@ip-172-31-46-226 file1.txt]$ pwd
/home/ec2-user/file1.txt
```

(ii) relative path (when we don't know the exact path we will check and proceed with opening the folders and files one by one using cd command).

```
[ec2-user@ip-172-31-46-226 home]$ cd ec2-user
[ec2-user@ip-172-31-46-226 ~]$ ls
data.txt data2.txt file1.txt file2.txt file3.txt log.txt
[ec2-user@ip-172-31-46-226 ~]$ cd file1.txt
```

4. To go one step back from our folder/file: **cd ..**

```
[ec2-user@ip-172-31-46-226 file1.txt]$ pwd
/home/ec2-user/file1.txt
[ec2-user@ip-172-31-46-226 file1.txt]$ cd ..
[ec2-user@ip-172-31-46-226 ~]$ pwd
/home/ec2-user
```

5. Remove an empty directory: **rmdir foldername**

```
[ec2-user@ip-172-31-46-226 ~]$ rmdir file1.txt
[ec2-user@ip-172-31-46-226 ~]$ ls
data.txt data2.txt file2.txt file3.txt log.txt
[ec2-user@ip-172-31-46-226 ~]$
```

6. To remove a folder with files: **rm -rf foldername**

```
[ec2-user@ip-172-31-46-226 ~]$ cd file2.txt
[ec2-user@ip-172-31-46-226 file2.txt]$ touch write.txt read.txt show.txt
[ec2-user@ip-172-31-46-226 file2.txt]$ ls
read.txt  show.txt  write.txt
[ec2-user@ip-172-31-46-226 file2.txt]$ cd ..
[ec2-user@ip-172-31-46-226 ~]$ ls
data.txt  data2.txt  file2.txt  file3.txt  log.txt
[ec2-user@ip-172-31-46-226 ~]$ rm -rf file2.txt
[ec2-user@ip-172-31-46-226 ~]$ ls
data.txt  data2.txt  file3.txt  log.txt
```

7. To remove a file: **rm filename**

```
[ec2-user@ip-172-31-46-226 home]$ cd /home/ec2-user
[ec2-user@ip-172-31-46-226 ~]$ ls
data.txt  data2.txt  file3.txt  log.txt
[ec2-user@ip-172-31-46-226 ~]$ rm data.txt
[ec2-user@ip-172-31-46-226 ~]$ ls
data2.txt  file3.txt  log.txt
[ec2-user@ip-172-31-46-226 ~]$
```

8. Copy contents of one file to another: **cp source_filename destination_filename**

```
[ec2-user@ip-172-31-46-226 ~]$ ls
data2.txt  file3.txt  log.txt
[ec2-user@ip-172-31-46-226 ~]$ cp data2.txt log.txt
```

9. Text editor to edit a existing file or create new file then edit it: **vim existing_filename/new_filename**

```
[ec2-user@ip-172-31-46-226 ~]$ vim data2.txt
```

Press enter -> press **I**(insert mode) -> write content-> press **escape** ->enter **:wq!**(w-save, q->quit) press enter.

```
Hi and welcome to liux
```

```
:wq!
```

10. Another text editor to edit a file: **nano filename**

```
[ec2-user@ip-172-31-46-226 ~]$ nano data3.txt
```

Enter the contents -> **ctrl+x** followed by **ctrl+y** to save the file.

11. To see the contents of the file without opening it: **cat filename**

```
data2.txt  data3.txt  log.txt  file3.txt  log.txt
[ec2-user@ip-172-31-46-226 ~]$ cat data2.txt
Hi and welcome to liux
```

12. To list all the commands used by us: **history**

```
[ec2-user@ip-172-31-46-226 ~]$ history
1  pwd
2  mkdir file1.txt
3  ls
4  mkdir file2.txt file3.txt
5  ls
6  pwd
7  touch data.txt
8  touch log.txt data2.txt
9  ls
10 cd /home/ec2-user/file1.txt
```

13. To append the contents of one file to another without overwriting it and to see the resultant content:
>> called as the append operator.

cat source_file >> destination_file

```
[ec2-user@ip-172-31-46-226 ~]$ vim happy.txt
[ec2-user@ip-172-31-46-226 ~]$ vim sad.txt
[ec2-user@ip-172-31-46-226 ~]$ cat happy.txt
i am happy and healthy
[ec2-user@ip-172-31-46-226 ~]$ cat sad.txt
i am sad and pittty.
[ec2-user@ip-172-31-46-226 ~]$ cat happy.txt >> sad.txt
[ec2-user@ip-172-31-46-226 ~]$ cat sad.txt
i am sad and pittty.
i am happy and healthy
```

14. To overwrite the contents of one file to another: **cat source_file > destination_file**

```
[ec2-user@ip-172-31-46-226 ~]$ cat happy.txt > sad.txt
[ec2-user@ip-172-31-46-226 ~]$ cat sad.txt
i am happy and healthy
```