

Package ‘CASAL2’

June 19, 2017

Title CASAL2 extract package

Version 1.0

Date 2017-03-20

Author D. Fu and C. Marsh

Description A set of R functions for extracting and plotting from CASAL2 output files.

Maintainer Casal2 development team <casal2@niwa.co.nz>

License CPL v1.0. See the CASAL2 User Manual for license details.

URL <http://www.niwa.co.nz>

Copyright National Institute of Water & Atmospheric Research (NIWA),
New Zealand Ministry for Primary Industries.

RoxygenNote 6.0.1

R topics documented:

check_short_hand	2
convert.to.lines	3
DoubleExponential	3
DoubleNormal	4
evalit	4
extract	5
extract.cs12.file	5
extract.parameters	6
get.casal2_list	6
get.line.label	7
get.line.type	7
get.lines	7
Increasing	8
InverseLogistic	8
is.all.numeric	9
is.even	9
is.in	10
is.odd	10
KnifeEdge	10
Logistic	11
LogisticProducing	12
make.complete_vector	12

make.data.frame	13
make.list	13
make.list_element	13
make.matrix	14
make.named_complete_vector	14
make.vector	14
param.profile	15
param.profile.by.cohort	15
Paste	16
pos	17
pos.match	17
pow	17
ReadSimulatedData	18
reformat.compositional.data	18
regexp.in	19
Regexpr	19
remove.first.words	19
string.to.vector.of.numbers	20
string.to.vector.of.words	20
strip	20
Sum	21
unpaste	21
write.csl2.file	21
Index	23

check_short_hand	<i>Utility extract function</i>
------------------	---------------------------------

Description

Utility extract function

Usage

check_short_hand(x)

Author(s)

Craig Marsh

convert.to.lines	<i>Utility extract function</i>
------------------	---------------------------------

Description

Utility extract function

Usage

```
convert.to.lines(filename)
```

Author(s)

Dan Fu

DoubleExponential	<i>Calculate the Double-Exponential Selectivity used in Casal2</i>
-------------------	--

Description

This function calculates the Double-Exponential selectivity and should be used to plot up the form of the selectivity when estimating the parameters in the model.

Usage

```
DoubleExponential(age_or_length, x0, x1, x2, y0, y1, y2, alpha = 1)
```

Arguments

age_or_length	"vector<numeric>" A vector of ages and or lengths to calculate the selectivity over.
x0	"numeric" See manual for formal definition of these parameters
x1	"numeric"
x2	"numeric"
y0	"numeric"
y1	"numeric"
y2	"numeric"
alpha	"numeric" The capping parameter of the selectivity, to move the max away from one

Value

"vector<numeric>" selectivity values over the age/length range and parameters supplied

Author(s)

Craig Marsh

DoubleNormal*Calculate the Double-Normal Selectivity used in Casal2*

Description

This function calculates the Double-Normal selectivity and should be used to plot up the form of the selectivity when estimating the parameters in the model.

Usage

```
DoubleNormal(age_or_length, alpha = 1, mu, sigma_l, sigma_r)
```

Arguments

age_or_length	"vector<numeric>" A vector of ages and or lengths to calculate the selectivity over.
alpha	"numeric" The capping parameter of the selectivity, to move the max away from one
mu	"numeric" Mean of the selectivity
sigma_l	"numeric" left hand standard deviation of the selectivity
sigma_r	"numeric" Right hand standard deviation of the selectivity

Value

"vector<numeric>" selectivity values over the age/length range and parameters supplied

Author(s)

Craig Marsh

evalit*Utility plot function*

Description

Utility plot function

Usage

```
evalit(x)
```

Author(s)

Craig Marsh

extract	<i>Utility extract function</i>
---------	---------------------------------

Description

Utility extract function

Usage

```
extract(file, path = "")
```

Arguments

file	the name of the input file containing model output to extract
path	Optionally, the path to the file
validate	Optionally, validate the structure of each element in the report section
conversion	Optionally, where possible, convert elements from list_element and data.frame into numeric

Author(s)

Dan Fu

extract.csl2.file	<i>Model configuration write function</i>
-------------------	---

Description

This function reads a Casal2 configuration file and returns a list object in R. Where each element is a command and subcommand from the configuration file

Usage

```
extract.csl2.file(file, path = "")
```

Arguments

file	the name of the input file containing model configuration
path	Optionally, the path to the file

Author(s)

Craig Marsh

extract.parameters	<i>Utility extract.parameters function</i>
--------------------	--

Description

This function reads in a parameter file that would be generated using the -o syntax.

Usage

```
extract.parameters(file, path = "")
```

Arguments

file	the name of the input file containing model output to extract
path	Optionally, the path to the file

Value

Data <"data.frame"> of parameters that are from a -i format.

Author(s)

Craig Marsh

get.casal2_list	<i>Utility function</i>
-----------------	-------------------------

Description

Utility function

Usage

```
get.casal2_list()
```

Author(s)

Craig Marsh

get.line.label	<i>Utility extract function</i>
----------------	---------------------------------

Description

Utility extract function

Usage

```
get.line.label(line)
```

Author(s)

Dan Fu

get.line.type	<i>Utility extract function</i>
---------------	---------------------------------

Description

Utility extract function

Usage

```
get.line.type(line)
```

Author(s)

Dan Fu

get.lines	<i>Utility extract function</i>
-----------	---------------------------------

Description

Utility extract function

Usage

```
get.lines(lines, from = -1, to = -1, contains = "", starts.with = "",  
clip.to = "", clip.from = "", clip.to.match = "",  
clip.from.match = "", ...)
```

Author(s)

Dan Fu

Increasing	<i>Calculate the Increasing Selectivity used in Casal2</i>
------------	--

Description

This function calculates the Increasing selectivity and should be used to plot up the form of the selectivity when estimating the parameters in the model.

Usage

```
Increasing(age_or_length, alpha = 1, v, low, high)
```

Arguments

age_or_length	"vector<numeric>" A vector of ages and or lengths to calculate the selectivity over.
alpha	"numeric" The capping parameter of the selectivity, to move the max away from one
v	"vector<numeric>" A vector of selectivities, must have a one for one relationship with age_or_length.
low	"numeric" age or length at which selectivity is set = 0 below
high	"numeric" age or length at which selectivity is set = alpha above

Value

"vector<numeric>" selectivity values over the age/length range and parameters supplied

Author(s)

Craig Marsh

InverseLogistic	<i>Calculate the Inverse-Logistic Selectivity used in Casal2</i>
-----------------	--

Description

This function calculates the Inverse-Logistic selectivity and should be used to plot up the form of the selectivity when estimating the parameters in the model.

Usage

```
InverseLogistic(age_or_length, alpha = 1, a50, ato95)
```


Arguments

age_or_length	"vector<numeric>" A vector of ages and or lengths to calculate the selectivity over.
alpha	"numeric" The capping parameter of the selectivity, to move the max away from one
a50	"numeric" age or length where selectivity 50%
ato95	"numeric" age or length difference where selectivity goes from 50% - 95% selective

Value

"vector<numeric>" selectivity values over the age/length range and parameters supplied

Author(s)

Craig Marsh

is.all.numeric	<i>Utility extract function</i>
----------------	---------------------------------

Description

Utility extract function

Usage

```
is.all.numeric(x, what = c("test", "vector"), extras = c(".", "NA", "na",  
  "null", "NULL"))
```

Author(s)

Dan Fu (not really)

is.even	<i>Utility extract function</i>
---------	---------------------------------

Description

Utility extract function

Usage

```
is.even(x)
```

Author(s)

Dan Fu

is.in	<i>Utility extract function</i>
-------	---------------------------------

Description

Utility extract function

Usage

```
is.in(x, y)
```

Author(s)

Dan Fu

is.odd	<i>Utility extract function</i>
--------	---------------------------------

Description

Utility extract function

Usage

```
is.odd(x)
```

Author(s)

Dan Fu

KnifeEdge	<i>Calculate the KnifeEdge Selectivity used in Casal2</i>
-----------	---

Description

This function calculates the KnifeEdge selectivity and should be used to plot up the form of the selectivity when estimating the parameters in the model.

Usage

```
KnifeEdge(age_or_length, alpha = 1, Edge)
```

Arguments

age_or_length	"vector<numeric>" A vector of ages and or lengths to calculate the selectivity over.
alpha	"numeric" The capping parameter of the selectivity, to move the max away from one
edge	"numeric" age or length at which selectivity is 0 to the left or alpha to the right

Value

"vector<numeric>" selectivity values over the age/length range and parameters supplied

Author(s)

Craig Marsh

Logistic	<i>Calculate the Logistic Selectivity used in Casal2</i>
----------	--

Description

This function calculates the Logistic selectivity and should be used to plot up the form of the selectivity when estimating the parameters in the model.

Usage

```
Logistic(age_or_length, alpha = 1, a50, ato95)
```

Arguments

age_or_length	"vector<numeric>" A vector of ages and or lengths to calculate the selectivity over.
alpha	"numeric" The capping parameter of the selectivity, to move the max away from one
a50	"numeric" age or length where selectivity 50%
ato95	"numeric" age or length difference where selectivity goes from 50% - 95% selective

Value

"vector<numeric>" selectivity values over the age/length range and parameters supplied

Author(s)

Craig Marsh

LogisticProducing	<i>Calculate the Logistic-Producing Selectivity used in Casal2</i>
-------------------	--

Description

This function calculates the Logistic-Producing selectivity and should be used to plot up the form of the selectivity when estimating the parameters in the model.

Usage

```
LogisticProducing(age_or_length, alpha = 1, a50, ato95, high, low)
```

Arguments

age_or_length	"vector<numeric>" A vector of ages and or lengths to calculate the selectivity over.
alpha	"numeric" The capping parameter of the selectivity, to move the max away from one
a50	"numeric" age or length where selectivity 50%
ato95	"numeric" age or length difference where selectivity goes from 50% - 95% selective
high	"numeric" age or length at which selectivity is set = alpha above
low	"numeric" age or length at which selectivity is set = 0 below

Value

"vector<numeric>" selectivity values over the age/length range and parameters supplied

Author(s)

Craig Marsh

make.complete_vector	<i>Utility extract function</i>
----------------------	---------------------------------

Description

Utility extract function

Usage

```
make.complete_vector(lines)
```

Author(s)

Dan Fu

make.data.frame	<i>Utility extract function</i>
-----------------	---------------------------------

Description

Utility extract function

Usage

```
make.data.frame(lines)
```

Author(s)

Dan Fu

make.list	<i>Utility extract function</i>
-----------	---------------------------------

Description

Utility extract function

Usage

```
make.list(lines)
```

Author(s)

Dan Fu

make.list_element	<i>Utility extract function</i>
-------------------	---------------------------------

Description

Utility extract function

Usage

```
make.list_element(lines)
```

Author(s)

Dan Fu

make.matrix	<i>Utility extract function</i>
-------------	---------------------------------

Description

Utility extract function

Usage

```
make.matrix(lines)
```

Author(s)

Dan Fu

make.named_complete_vector	<i>Utility extract function</i>
----------------------------	---------------------------------

Description

Utility extract function

Usage

```
make.named_complete_vector(lines)
```

Author(s)

Dan Fu

make.vector	<i>Utility extract function</i>
-------------	---------------------------------

Description

Utility extract function

Usage

```
make.vector(lines)
```

Author(s)

Dan Fu

param.profile	<i>Generate an objective score profile plot for a particular parameter as a consequence from a casal2 -p run</i>
---------------	--

Description

This function reads an extracted list from Casal2 and plots the likelihood/objective profile for one or many observations over the specified parameters range. This range is defined in the profile block of the Casal2 configuration file. Casal2 calculates the profile steps as even intervals between the upper and lower bound by $= (\text{upper_bound} - \text{lower_bound}) / (\text{steps} + 1)$

Usage

```
param.profile(obs, param, extract_list, Rescale = F,
  ylab = "Objective contribution", xlab = "Parameter", y_min = -0.5)
```

Arguments

obs	"vector<string>" A vector of report labels that correspond to observations that you would like to plot the profile for. Can be many observations
param	"string" The parameter label that the profile was run for. It should follow the syntax that is used in Casal2 that is, "block[label].parameter" e.g. process[Recruitment].b0
extract_list	"string" The name of the R object that was extracted into R using the extract() function.
Rescale	"bool/logical" If true it will rescale the likelihoods to have a minimum on 0. This is done by subtracting off the minimum value of the likelihood series.
ylab	"string" optional, y-axis label
xlab	"string" optional, x-axis label
ymin	"numeric" optional, minimum value parsed to the ylim parameter in plot()

Author(s)

Craig Marsh

param.profile.by.cohort	<i>Generate an objective score profile plot for a particular parameter and age compositional dataset as a consequence from a casal2 -p run.</i>
-------------------------	---

Description

This function reads an extracted list from Casal2 and plots the likelihood/objective profile for an age compositional observation over the specified parameters range. This range is defined in the profile block of the Casal2 configuration file. Casal2 calculates the profile steps as even intervals between the upper and lower bound by $= (\text{upper_bound} - \text{lower_bound}) / (\text{steps} + 1)$. The plot will generate a line for each cohort and category. The reason I made this function was for the specific investigation of the natural mortality parameter M. Sometimes running a profile of aggregated compositional data on a parameter is not that informative. The aim of this plot is to show which cohorts are suggestive of certain parameters values, this will either create more confusion (most likely) or at least give the user something interesting to think about (perhaps cohort based processes).

Usage

```
param.profile.by.cohort(obs, param, extract_list, Rescale = F,
  ylab = "Objective contribution", xlab = "Parameter", y_min = -0.5,
  threshold = 10)
```

Arguments

obs	"string" A report label that correspond to the age compositional observation that you would like to plot the profile for. Can be many observations
param	"string" The parameter label that the profile was run for. It should follow the syntax that is used in Casal2 that is, "block[label].parameter" e.g. process[Recruitment].b0
extract_list	"string" The name of the R object that was extracted into R using the extract() function.
Rescale	"bool/logical" If true it will rescale the likelihoods to have a minimum on 0. This is done by subtracting off the minimum value of the likelihood series.
ylab	"string" optional, y-axis label
xlab	"string" optional, x-axis label
threshold	"numeric" the minimum number of years a cohort is seen in the observation, for being used in the plot. if threshold = 5 then any cohort that has been sampled for a minimum of 5 years will be automatically plotted.
ymin	"numeric" optional, minimum value parsed to the ylim parameter in plot()

Author(s)

Craig Marsh

Paste

Utility plot function

Description

Utility plot function

Usage

```
Paste(..., sep = "")
```

Author(s)

Craig Marsh

pos	<i>Utility extract function</i>
-----	---------------------------------

Description

Utility extract function

Usage

```
pos(vector, x)
```

Author(s)

Dan Fu

pos.match	<i>Utility extract function</i>
-----------	---------------------------------

Description

Utility extract function

Usage

```
pos.match(vector, regexp)
```

Author(s)

Dan Fu

pow	<i>Utility extract function</i>
-----	---------------------------------

Description

Utility extract function

Usage

```
pow(x, exponent)
```

Author(s)

Craig Marsh

ReadSimulatedData	<i>Read in multiple sets of Simualted data for a single observation</i>
-------------------	---

Description

This function reads in a set of simulated observations generated from Casal2 in simulation mode. These functions read in all the simulated obs as a list, for visualising and summarising in R

Usage

```
ReadSimulatedData(filename, path = "")
```

Arguments

filename	the name of simulated obs for an observation. For example if you generated 100 sets of simulated observations named "SubAntarticObs". Casal2 will generate 100 of these with the following extensions SubAntarticObs.001, SubAntarticObs.002, SubAntarticObs.003,,, SubAntarticObs.100. filename = SubAntarticObs.
path	Optionally, the path to the file, default is current working directory.

Author(s)

Craig Marsh

reformat.compositional.data	<i>Reformat Casal2 compositional observations so they are in the same format as the legacy Casal observations.</i>
-----------------------------	--

Description

This function will take a compositional observation that has been generated by Casal2 and re-format it so that it has the same structure as a CASAL reported compositional observation. The purpose for this function is to reformat the Casal2 observations so we can then feed them into packages that have been tailored for Casal observations, such as Chris Francis's DataWeighting library.

Usage

```
reformat.compositional.data(extract_list, comp_label)
```

Arguments

extract_list	the r object that has been extracted using the extract() function.
comp_label	<string> the label of the report for the observation you want converted

Author(s)

Craig Marsh

regex.in	<i>Utility extract function</i>
----------	---------------------------------

Description

Utility extract function

Usage

```
regex.in(vector, regex)
```

Author(s)

Dan Fu

Regexpr	<i>Utility extract function</i>
---------	---------------------------------

Description

Utility extract function

Usage

```
Regexpr(x, y, fixed = T)
```

Author(s)

Dan Fu

remove.first.words	<i>Utility extract function</i>
--------------------	---------------------------------

Description

Utility extract function

Usage

```
remove.first.words(string, words = 1)
```

Author(s)

Dan Fu

string.to.vector.of.numbers
Utility extract function

Description

Utility extract function

Usage

string.to.vector.of.numbers(string)

Author(s)

Dan Fu

string.to.vector.of.words
Utility extract function

Description

Utility extract function

Usage

string.to.vector.of.words(string)

Author(s)

Dan Fu

strip
Utility for extract function

Description

Utility for extract function

Usage

strip(x)

Author(s)

Craig Marsh

Sum	<i>Utility plot function</i>
-----	------------------------------

Description

Utility plot function

Usage

```
Sum(..., na.rm = T)
```

Author(s)

Craig Marsh

unpaste	<i>Utility extract function</i>
---------	---------------------------------

Description

Utility extract function

Usage

```
unpaste(string, sep)
```

Author(s)

Dan Fu

write.csl2.file	<i>Model configuration write function</i>
-----------------	---

Description

This function will write a Casal2 configuration file based on a list object in R. Ususally this function will be used once a model has been read into R using `extract.csl2.file` and modified. This function will then print our the configuration to a new file where it can be re run into Casal2

Usage

```
write.csl2.file(object, file, path = "")
```

Arguments

object	An R list object that follows the same structure that <code>extract.csl2.file</code> would produce
file	Optionally, the file name
path	Optionally, the path to ouput the file

Author(s)

Craig Marsh

Index

`check_short_hand`, [2](#)
`convert.to.lines`, [3](#)

`DoubleExponential`, [3](#)
`DoubleNormal`, [4](#)

`evalit`, [4](#)
`extract`, [5](#)
`extract.csl2.file`, [5](#)
`extract.parameters`, [6](#)

`get.casal2_list`, [6](#)
`get.line.label`, [7](#)
`get.line.type`, [7](#)
`get.lines`, [7](#)

`Increasing`, [8](#)
`InverseLogistic`, [8](#)
`is.all.numeric`, [9](#)
`is.even`, [9](#)
`is.in`, [10](#)
`is.odd`, [10](#)

`KnifeEdge`, [10](#)

`Logistic`, [11](#)
`LogisticProducing`, [12](#)

`make.complete_vector`, [12](#)
`make.data.frame`, [13](#)
`make.list`, [13](#)
`make.list_element`, [13](#)
`make.matrix`, [14](#)
`make.named_complete_vector`, [14](#)
`make.vector`, [14](#)

`param.profile`, [15](#)
`param.profile.by.cohort`, [15](#)
`Paste`, [16](#)
`pos`, [17](#)
`pos.match`, [17](#)
`pow`, [17](#)

`ReadSimulatedData`, [18](#)
`reformat.compositional.data`, [18](#)

`regex.in`, [19](#)
`Regexpr`, [19](#)
`remove.first.words`, [19](#)

`string.to.vector.of.numbers`, [20](#)
`string.to.vector.of.words`, [20](#)
`strip`, [20](#)
`Sum`, [21](#)

`unpaste`, [21](#)

`write.csl2.file`, [21](#)