

Todo API

GET Root

https://todo-api-is14.onrender.com

Hits the homepage of the API

Example Request

Default

```
GET / HTTP/1.1
Host: todo-api-is14.onrender.com
```

Example Response

200 OK

Body

Header (16)

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Todo API</title>
  </head>
  <body>
    <h1>Todo API</h1>
```

View More

POST Sign Up

https://todo-api-is14.onrender.com/signup

Signs up a user

HEADERS

Content-Type

application/json

BODY raw

```
{
  "username": "bob",
  "email": "bob@mail.com",
  "password": "hobnass"
```



Example Request

User Already Exists ▾

```
POST /signup HTTP/1.1
Host: todo-api-is14.onrender.com
Content-Type: application/json
Content-Length: 69

{
  "username": "bob",
  "email": "bob@mail.com",
  "password": "bobpass"
}
```

Example Response

200 OK

Body Header (12)

```
{
  "error": "username or email already exists"
}
```

POST Login

https://todo-api-is14.onrender.com/login

Logs in the user

HEADERS

Content-Type

application/json

BODY raw

```
{
  "username": "bob",
  "password": "bobpass"
}
```

Example Request

Successful login ▾

```
POST /login HTTP/1.1
Host: todo-api-is14.onrender.com
Content-Type: application/json
Content-Length: 44

{
  "username": "bob",
  "password": "bobpass"
}
```



200 OK

Header (12)

◀ ▶

`https://todo-api-is14.onrender.com/identify`

Identifies the currently signed in user (from the JWT token sent)

AUTHORIZATION

API Key

Key

Authorization

Value

<value>

Success ▼

```
GET /identify HTTP/1.1
Host: todo-api-is14.onrender.com
```

200 OK

Header (12)

<https://todo-api-is14.onrender.com/todos>

Lets an authed user create a todo

Key

Authorization

Value

<value>

HEADERS

Content-Type

application/json

BODY raw

```
{
  "text": "go grocery"
}
```

Example Request

Todo Created ▾

```
POST /todos HTTP/1.1
Host: todo-api-is14.onrender.com
Content-Type: application/json
Content-Length: 25
```

```
{
  "text": "go grocery"
}
```

Example Response

201 Created

Body

Header (11)

```
{
  "id": 1
}
```

GET (User) GET Todos 🔒

https://todo-api-is14.onrender.com/todos

Get all the todos of an authed user

AUTHORIZATION


API Key




Key

Authorization

Value

<value>





Example Request

Success

```
GET /todos HTTP/1.1
Host: todo-api-is14.onrender.com
```

Example Response

200 OK

Body

Header (12)

```
[
  {
    "done": false,
    "id": 1,
    "text": "go grocery",
    "userid": 1
  }
]
```

GET (User) GET Todo 🔒

https://todo-api-is14.onrender.com/todos/:todold

Get an authed user's todo by id

AUTHORIZATION

API Key

Key

Authorization


Value




<value>

PATH VARIABLES

todold

1





Example Request

Success

```
GET /todos/1 HTTP/1.1
Host: todo-api-is14.onrender.com
```

Example Response

200 OK

Body

Header (12)

```
{
  "done": false,
  "id": 1,
  "text": "go grocery",
  "userid": 1
}
```

```
{
  "userid": 1
}
```

GET (User) Get Todo Stats 🔒

https://todo-api-is14.onrender.com/stats/todos

Gets statistics on an authed user's todos

AUTHORIZATION

API Key

Key

Authorization

Value

<value>

Example Request

Success

```
GET /stats/todos HTTP/1.1
Host: todo-api-is14.onrender.com
```

Example Response

200 OK

Body Header (12)

```
{
  "num_done": 0,
  "num_todos": 1
}
```

PUT (User) Update Todo 🔒

https://todo-api-is14.onrender.com/todos/:todoId

AUTHORIZATION

API Key

Key

Authorization

Value

<value>

HEADERS



PATH VARIABLES

todold

1

BODY raw

```
{
  "done": true
}
```

Example Request

Success ▾

```
PUT /todos/1 HTTP/1.1
Host: todo-api-is14.onrender.com
Content-Type: application/json
Content-Length: 17

{
  "done": true
}
```

Example Response

201 Created

Body

Header (11)

```
{
  "message": "Updated"
}
```

DEL (User) Delete Todo

https://todo-api-is14.onrender.com/todos/todold

AUTHORIZATION

API Key

Key

Authorization

Value

<value>

HEADERS

Content-Type

application/json

PATH VARIABLES

todold

1



Example Request

Bad ID ▾

```
DELETE /todos/5 HTTP/1.1
Host: todo-api-is14.onrender.com
Content-Type: application/json
```

Example Response

200 OK

Body Header (5)

```
{
  "message": "Invalid id or unauthorized"
```