Simplex quadrature nodal DG method for wave equations on sphere

April 21, 2026

---

1. $2n-1$ and $2n$ Quadrature points in 2-simplex

1.1. Barycentric Coordinates

Consider the two-dimensional plane with coordinates $\boldsymbol{\xi} = (\xi, \eta)$. Let T be the triangle with vertices

$$\boldsymbol{\xi}_{v_1} = (0,1), \quad \boldsymbol{\xi}_{v_2} = (0,0), \quad \boldsymbol{\xi}_{v_3} = (1,0)$$

Any point within the triangle can be expressed as

$$(\xi, \eta) = \boldsymbol{\xi} = \sum_{i=0}^{3} b_i \boldsymbol{\xi}_{v_i}, \quad \sum_{i=1}^{3} b_i = 1, \quad b_i \geq 0 \tag{1}$$

where b_i for $i = 1, 2, 3$ are known as the barycentric coordinates.

Numerical integration is often encounter in computations. To conduct numerical integration over T, numerical quadrature points and weights are introduced in []. Below we quote the barycentric coordinates of the quadrature points and the associated weights for conducting integration of polynomials of degree at most degree $2n-1$ and $2n$, in Table 1 and Table 2.

n	Sym	b_1	b_2	w_i	w_i^b
1	S_6	0.2113248654051871	0.0000000000000000	0.16666666666666667	0.5000000000000000
2	S_6	0.1127016653792583	0.0000000000000000	0.04166666666666666	0.2777777777777777
2	S_3	0.5000000000000000	0.0000000000000000	0.09999999999999999	0.4444444444444444
2	S_1	0.3333333333333333	0.3333333333333333	0.45000000000000000	–
3	S_6	0.06943184420297367	0.0000000000000000	0.01509901487256561	0.1739274225687269
3	S_6	0.3300094782075718	0.0000000000000000	0.04045654068298990	0.3260725774312731
3	S_6	0.5841571139756568	0.1870738791912763	0.11111111111111111	–
4	S_6	0.04691007703066797	0.0000000000000000	0.006601315081001592	0.1184634425280944
4	S_6	0.2307653449471584	0.0000000000000000	0.02053045968042892	0.2393143352496833
4	S_3	0.5000000000000000	0.0000000000000000	0.01853708483394990	0.2844444444444446
4	S_3	0.1394337314154536	0.1394337314154536	0.10542932962084440	–
4	S_3	0.4384239524408185	0.4384239524408185	0.12473673228977350	–
4	S_1	0.3333333333333333	0.3333333333333333	0.09109991119771331	–

Table 1: Barycentric coordinates of quadrature integration points for integrating polynomials of degree at most $2n-1$ in a triangle. w_i are surface integration associated quadrature weights. w_i^b are line integration quadrature weights associated with edge points.

n	Sym	b_1	b_2	w_i^s
1	S_3	0.1666666666666666	0.1666666666666666	0.3333333333333333
2	S_3	0.09157621350977067	0.09157621350977067	0.1099517436553218
2	S_3	0.4459484909159648	0.4459484909159648	0.2233815896780115
3	S_3	0.219429982549783	0.219429982549783	0.1713331241529809
3	S_3	0.480137964112215	0.480137964112215	0.08073108959303095
3	S_6	0.1416190159239682	0.0193717243612408	0.04063455979366068
4	S_6	0.7284923929554044	0.2631128296346379	0.02723031417443505
4	S_3	0.4592925882927232	0.4592925882927232	0.09509163426728455
4	S_3	0.1705693077517602	0.1705693077517602	0.1032173705347182
4	S_3	0.05054722831703096	0.05054722831703096	0.03245849762319804
4	S_1	0.3333333333333333	0.3333333333333333	0.1443156076777874

Table 2: Barycentric coordinates of quadrature integration points for integrating polynomials of degree at most $2n$ in a triangle. w_i^s are surface integration associated quadrature weights.

Based on these points we evaluate surface integration over a triangle, with $|T|$ being the area of the triangle, by a discrete summation as follows,

$$\int_T f(\boldsymbol{\xi})\, d\boldsymbol{\xi} = |T| \sum_{i=1}^{N} f(\boldsymbol{\xi}_i) w_i^s, \tag{2}$$

provided that f is a polynomial of degree at most $2n-1$ and $2n$. For evaluating line integrals on an edge of a triangle, we adopt the following quadrature formula:

$$\int_{\partial T^\gamma} f(\boldsymbol{\xi})\, d\boldsymbol{\xi} = |\partial T^\gamma| \sum_{i=1}^{n+1} f(\boldsymbol{\xi}_i^\gamma) w_i^e \tag{3}$$

where $|\partial T^\gamma|$ denotes the length of the edge γ, $\boldsymbol{\xi}_i^\gamma$ are the quadrature points on the edge, and w_i^e are the associated quadrature weights.

2. Orthogonal Polynomials on Simplex

We denote the triangle with vertices $(-1,1)$, $(-1,-1)$, and $(1,-1)$ by

$$\mathsf{T}^2 = \{(r,s) \,|\, r,s \geq -1,\ r+s \leq 1\}.$$

Let $n \in \{1,2,3,4\}$. On T^2, let us introduce the orthogonal polynomials $\phi_{i,j}$ defined by

$$\phi_m(r,s) = \Phi_{ij}(r,s) = \sqrt{2} P_i(a) P_j^{(2i+1,j)}(b)(1-b)^j, \quad 0 \leq i,j \leq n, \quad i+j \leq n,$$
$$m = j + (n+1)i + 1 - \frac{i}{2}(i-1), \quad a = 2 \cdot \frac{1+r}{1-s} - 1, \quad b = s$$

where P_i is the Legendre polynomial of degree i and $P_j^{(2i+1,j)}$ is the Jacobi polynomials of degree j. Applying these basis functions we span the function space as

$$\mathcal{V} = \text{span}\{\Phi_{ij}(r,s)\,|\,0 \le i,j \le n, \quad i+j \le n\}$$

Thus, for $n = 1$, we have the basis functions

$$\begin{aligned}
\frac{\phi_1(r,s)}{\sqrt{2}} &= \frac{\Phi_{00}}{\sqrt{2}} = P_0\left(\frac{2(1+r)}{1-s}\right) P_0^{(1,0)}(s)(1-s)^0 = 1 \\
\frac{\phi_2(r,s)}{\sqrt{2}} &= \frac{\Phi_{01}}{\sqrt{2}} = P_0\left(\frac{2(1+r)}{1-s}\right) P_1^{(1,1)}(s)(1-s)^1 = 2 + 4\frac{s-1}{2}(1-s)^1 = 2 - 2(1-s)^2 \\
\frac{\phi_3(r,s)}{\sqrt{2}} &= \frac{\Phi_{10}}{\sqrt{2}} = P_1\left(\frac{2(1+r)}{1-s}\right) P_0^{(3,0)}(s)(1-s)^0 = 1 + \left(\frac{2(1+r)}{1-s} - 1\right) = 2\frac{1+r}{1-s}
\end{aligned}$$

For $n = 2$, we have six functions,

$$\begin{aligned}
\frac{\phi_1(r,s)}{\sqrt{2}} &= \frac{\Phi_{00}}{\sqrt{2}} = P_0\left(\frac{2(1+r)}{1-s}\right) P_0^{(1,0)}(s)(1-s)^0 = 1 \\
\frac{\phi_2(r,s)}{\sqrt{2}} &= \frac{\Phi_{01}}{\sqrt{2}} = P_0\left(\frac{2(1+r)}{1-s}\right) P_1^{(1,1)}(s)(1-s)^1 = 2 - 2(1-s)^2 \\
\frac{\phi_3(r,s)}{\sqrt{2}} &= \frac{\Phi_{02}}{\sqrt{2}} = P_0\left(\frac{2(1+r)}{1-s}\right) P_2^{(1,0)}(s)(1-s)^2 = \left(3 + 6\left(\frac{2(1+r)}{1-s} - 1\right) + \frac{5}{2}\left(\frac{2(1+r)}{1-s} - 1\right)^2\right)(1-s)^2 \\
\frac{\phi_4(r,s)}{\sqrt{2}} &= \frac{\Phi_{10}}{\sqrt{2}} = P_1\left(\frac{2(1+r)}{1-s}\right) P_0^{(3,0)}(s)(1-s)^0 = 2\frac{1+r}{1-s} \\
\frac{\phi_5(r,s)}{\sqrt{2}} &= \frac{\Phi_{11}}{\sqrt{2}} = P_1\left(\frac{2(1+r)}{1-s}\right) P_1^{(3,1)}(s)(1-s)^1 = 2\frac{1+r}{1-s}\left(4 + 3\left(\frac{2(1+r)}{1-s} - 1\right)\right)(1-s)^1 \\
\frac{\phi_6(r,s)}{\sqrt{2}} &= \frac{\Phi_{20}}{\sqrt{2}} = P_2\left(\frac{2(1+r)}{1-s}\right) P_0^{(5,0)}(s)(1-s)^0 = 1 + 3\left(\frac{2(1+r)}{1-s} - 1\right) + \frac{3}{2}\left(\frac{2(1+r)}{1-s} - 1\right)^2
\end{aligned}$$

3. Approximation, Integration, and Differentiation

3.1. Modal and nodal approximation

Based on these grid points, we may seek numerical approximations to a function u defined on T.

Let $\boldsymbol{\xi} = (\xi, \eta)$. Consider a function space $\mathcal{V}$ spanned by a set of linearly independent basis functions $\phi_k(\boldsymbol{\xi})$ for $i = 1, 2, \cdots, n$, i.e.,

$$\mathcal{V} = \text{span}\{\phi_i(\boldsymbol{\xi}) | i = 1, 2, ..., n\}.$$

Thus, a function $u(\boldsymbol{\xi}) \in \mathcal{V}$ can be approximated as follows,

$$u(\boldsymbol{\xi}) = \sum_{i=1}^{N} a_i \phi_i(\boldsymbol{\xi}), \tag{4}$$

where a_i are coefficients. Applying the quadrature points $\boldsymbol{\xi}_m = (\xi_m, \eta_m)$ for $m = 1, 2, \cdots, M$ and denoting $u(\boldsymbol{\xi}_m) = u_m$ for simplicity, we have

$$\boldsymbol{u} = \boldsymbol{V}\boldsymbol{a}, \tag{5}$$

where

$$\boldsymbol{u} = \begin{bmatrix} u_1 \\ u_2 \\ \vdots \\ u_M \end{bmatrix}, \quad \boldsymbol{V} = \begin{bmatrix} \phi_1(\boldsymbol{\xi}_1) & \phi_2(\boldsymbol{\xi}_1) & \cdots & \phi_N(\boldsymbol{\xi}_1) \\ \phi_1(\boldsymbol{\xi}_2) & \phi_2(\boldsymbol{\xi}_2) & \cdots & \phi_N(\boldsymbol{\xi}_2) \\ \vdots & \vdots & \ddots & \vdots \\ \phi_1(\boldsymbol{\xi}_M) & \phi_2(\boldsymbol{\xi}_M) & \cdots & \phi_N(\boldsymbol{\xi}_M) \end{bmatrix}, \quad \boldsymbol{a} = \begin{bmatrix} a_1 \\ a_2 \\ \vdots \\ a_N \end{bmatrix}. \tag{6}$$

Let

$$\boldsymbol{W} = \mathrm{diag}(w_1, w_2, \cdots, w_M) \tag{7}$$

Define the mass matrix over the triangle T as

$$\boldsymbol{M} = |T|\boldsymbol{V}^T\boldsymbol{W}\boldsymbol{V}. \tag{8}$$

Since $\boldsymbol{W}$ is diagonal, we have from Eq. (8)

$$\boldsymbol{M}^T = |T|(\boldsymbol{V}^T\boldsymbol{W}\boldsymbol{V})^T = |T|\boldsymbol{V}^T\boldsymbol{W}\boldsymbol{V} = \boldsymbol{M} \tag{9}$$

Furthermore, for $\boldsymbol{a}$ being a non-zero vector and $\boldsymbol{W}$ being positive definite, we have

$$\boldsymbol{a}^T\boldsymbol{M}\boldsymbol{a} = |T|(\boldsymbol{V}\boldsymbol{a})^T\boldsymbol{W}(\boldsymbol{V}\boldsymbol{a}) > 0. \tag{10}$$

indicating that $\boldsymbol{M}$ is not only symmetric but also positive definite. Thus, its inverse exists, denoted by $\boldsymbol{M}^{-1}$.

Then, multiplying $|T|\boldsymbol{V}^T\boldsymbol{W}$ to Eq. (5), we have the vector $\boldsymbol{a}$ as follows,

$$|T|\boldsymbol{V}^T\boldsymbol{W}\boldsymbol{u} = |T|\boldsymbol{V}^T\boldsymbol{W}\boldsymbol{V}\boldsymbol{a} = \boldsymbol{M}\boldsymbol{a} \implies \boldsymbol{a} = |T|\boldsymbol{M}^{-1}\boldsymbol{V}^T\boldsymbol{W}\boldsymbol{u} \tag{11}$$

3.2. Numerical differentiation

To perform numerical differentiation on the vector $\boldsymbol{u}$, we need to construct the differentiation matrices for differentiating functions in the ξ and η directions. Differentiating Eq. (4) with respect to ξ, we have

$$\partial_\xi u(\boldsymbol{\xi}) = \sum_{i=1}^{N} a_i \partial_\xi \phi_i(\boldsymbol{\xi}) \tag{12}$$

Hence, the grid vector version of the above expression is

$$\boldsymbol{u}_\xi = \boldsymbol{V}_\xi \boldsymbol{a}, \quad \boldsymbol{u}_\xi = \begin{bmatrix} \partial_\xi u_1 \\ \partial_\xi u_2 \\ \vdots \\ \partial_\xi u_M \end{bmatrix}, \quad \boldsymbol{V}_\xi = \begin{bmatrix} \partial_\xi \phi_1(\boldsymbol{\xi}_1) & \partial_\xi \phi_2(\boldsymbol{\xi}_1) & \cdots & \partial_\xi \phi_N(\boldsymbol{\xi}_1) \\ \partial_\xi \phi_1(\boldsymbol{\xi}_2) & \partial_\xi \phi_2(\boldsymbol{\xi}_2) & \cdots & \partial_\xi \phi_N(\boldsymbol{\xi}_2) \\ \vdots & \vdots & \ddots & \vdots \\ \partial_\xi \phi_1(\boldsymbol{\xi}_M) & \partial_\xi \phi_2(\boldsymbol{\xi}_M) & \cdots & \partial_\xi \phi_N(\boldsymbol{\xi}_M) \end{bmatrix} \tag{13}$$

Applying the relationship Eq. (11) we have

$$\boldsymbol{u}_\xi = \boldsymbol{V}_\xi \boldsymbol{a} = |T| \boldsymbol{V}_\xi \boldsymbol{M}^{-1} \boldsymbol{V}^T \boldsymbol{W} \boldsymbol{u} = \boldsymbol{D}_\xi \boldsymbol{u} \tag{14}$$

where $\boldsymbol{D}_\xi$ is the differentiation matrix in the ξ direction. Likewise, we construct the differentiation matrix in the η direction and perform the associated numerical differentiation as follows,

$$\boldsymbol{V}_\eta = \begin{bmatrix} \partial_\eta \phi_1(\boldsymbol{\xi}_1) & \partial_\eta \phi_2(\boldsymbol{\xi}_1) & \cdots & \partial_\eta \phi_N(\boldsymbol{\xi}_1) \\ \partial_\eta \phi_1(\boldsymbol{\xi}_2) & \partial_\eta \phi_2(\boldsymbol{\xi}_2) & \cdots & \partial_\eta \phi_N(\boldsymbol{\xi}_2) \\ \vdots & \vdots & \ddots & \vdots \\ \partial_\eta \phi_1(\boldsymbol{\xi}_M) & \partial_\eta \phi_2(\boldsymbol{\xi}_M) & \cdots & \partial_\eta \phi_N(\boldsymbol{\xi}_M) \end{bmatrix}, \quad \boldsymbol{D}_\eta = |T| \boldsymbol{V}_\eta \boldsymbol{M}^{-1} \boldsymbol{V}^T \boldsymbol{W}, \quad \boldsymbol{u}_\eta = \boldsymbol{D}_\eta \boldsymbol{u}. \tag{15}$$

3.3. Numerical Integration

Here we briefly summarize the extension of the quadrature rule.

Let $q(\boldsymbol{\xi})$ be a scalar function and $\boldsymbol{V}(\boldsymbol{\xi}) = (u(\boldsymbol{\xi}), v(\boldsymbol{\xi}))$ be a vector-valued function. From the divergence theorem, we have

$$\oint_{\partial \mathcal{T}} \boldsymbol{n} \cdot (q\boldsymbol{F})\, d\boldsymbol{\xi} = \int_{\mathcal{T}} \nabla \cdot (q\boldsymbol{F})\, d\boldsymbol{\xi} = \int_{\mathcal{T}} q \nabla \cdot \boldsymbol{F}\, d\boldsymbol{\xi} + \int_{\mathcal{T}} \boldsymbol{F} \cdot \nabla q\, d\boldsymbol{\xi} \tag{16}$$

If both q and $\boldsymbol{F}$ are polynomials of degree at most n then we can apply the simplex quadrature rule to establish discrete version of the equation as follows,

$$\boldsymbol{q}_b^T \boldsymbol{W}_b \boldsymbol{f}_b = |T| \boldsymbol{1}^T \boldsymbol{W} \left(\boldsymbol{D}_\xi (\boldsymbol{q} \odot \boldsymbol{u}) + \boldsymbol{D}_\eta (\boldsymbol{q} \odot \boldsymbol{v}) \right) \tag{17}$$

$$= |T| \boldsymbol{q}^T \boldsymbol{W} (\boldsymbol{D}_\xi \boldsymbol{u} + \boldsymbol{D}_\eta \boldsymbol{v}) + |T| (\boldsymbol{u}^T \boldsymbol{W} \boldsymbol{D}_\xi \boldsymbol{q} + \boldsymbol{v}^T \boldsymbol{W} \boldsymbol{D}_\eta \boldsymbol{q}) \tag{18}$$

where $\boldsymbol{q}_b$ and $\boldsymbol{f}_b$ are grid vector representations of the functions q and $\boldsymbol{n} \cdot F$ at the three edges, and $\boldsymbol{W}_b$ is the quadrature weight matrix with diagonal entries being w_i^b for $i = 1, 2, \ldots, n+1$,

$$\boldsymbol{W}_b = \begin{bmatrix} |\partial T^1| & 0 & 0 \\ 0 & |\partial T^2| & 0 \\ 0 & 0 & |\partial T^3| \end{bmatrix} \otimes \mathrm{diag}(w_1^b, w_2^b, \ldots, w_{n+1}^b)$$

3.4. Well-posed analysis for model wave equations

Let us consider applying discontinuous Galerkin method to solve the model wave equation:

$$\partial_t q(\boldsymbol{\xi}, t) + \nabla \cdot (\boldsymbol{V} q(\boldsymbol{\xi}, t)) = 0, \quad \boldsymbol{\xi} \in \mathcal{T} \tag{19}$$

$$q(\boldsymbol{\xi}, 0) = q_0(\boldsymbol{\xi}), \quad \boldsymbol{\xi} \in \mathcal{T} \tag{20}$$

$$q(\boldsymbol{\xi}, t) = g(\boldsymbol{\xi}, t), \quad \text{if } \boldsymbol{n} \cdot \boldsymbol{V} < 0 \text{ for } \boldsymbol{\xi} \in \gamma \subset \partial \mathcal{T}, \quad t \geq 0 \tag{21}$$

We now conduct an energy estimate of the problem. The governing equation can be expressed in the following split form:

$$\partial_t q = -\frac{1}{2}\nabla\cdot(\boldsymbol{V}q) - \frac{1}{2}\boldsymbol{V}\cdot\nabla q - \frac{1}{2}(\nabla\cdot\boldsymbol{V})q \tag{22}$$

Multiplying $2q$ to the equation, integrating over the domain $\mathcal{T}$, and invoking the identity $\nabla\cdot(\boldsymbol{V}q^2) = q\nabla\cdot(\boldsymbol{V}q) + q\boldsymbol{V}\cdot\nabla q$ as well the divergence theorem, we have

$$\begin{aligned}\frac{d}{dt}\int_{\mathcal{T}} q^2(\boldsymbol{\xi},t)\,d\boldsymbol{\xi} &= -\int_{\mathcal{T}} q\nabla\cdot(\boldsymbol{V}q) + q\boldsymbol{V}\cdot\nabla q + (\nabla\cdot\boldsymbol{V})q^2\,d\boldsymbol{\xi}\\ &= -\int \nabla\cdot(\boldsymbol{V}q^2) + (\nabla\cdot\boldsymbol{V})q^2\,d\boldsymbol{\xi}\\ &= -\oint_{\partial\mathcal{T}}(n\cdot\boldsymbol{V})q^2 d\boldsymbol{\xi} - \int_{\mathcal{T}}(\nabla\cdot\boldsymbol{V})q^2\,d\boldsymbol{\xi}\end{aligned} \tag{23}$$

Let $\alpha = \max_{\boldsymbol{\xi}\in\mathcal{T}}|\nabla\cdot\boldsymbol{V}|$.

$$\frac{d}{dt}\int_{\mathcal{T}} q^2(\boldsymbol{\xi},t)\,d\boldsymbol{\xi} - \alpha\int_{\mathcal{T}} q^2\,d\boldsymbol{\xi} \le \int_{\gamma}(-n\cdot\boldsymbol{V})g^2\,d\boldsymbol{\xi} \tag{24}$$

Multiplying $e^{-\alpha t}$ to the equation and integrating with respect to t, we have

$$e^{-\alpha t}\int_{\mathcal{T}} q^2(\boldsymbol{\xi},t)\,d\boldsymbol{\xi} - \int_{\mathcal{T}} q^2(\boldsymbol{\xi},0)\,d\boldsymbol{\xi} \le \int_0^t e^{-\alpha t'}\int_{\gamma}(-n\cdot\boldsymbol{V})g^2\,d\boldsymbol{\xi}\,dt \tag{25}$$

leading to

$$\int_{\mathcal{T}} q^2(\boldsymbol{\xi},t)\,d\boldsymbol{\xi} \le e^{\alpha t}\int_{\mathcal{T}} q_0^2(\boldsymbol{\xi})\,d\boldsymbol{\xi} + \int_0^t e^{\alpha(t-t')}\int_{\gamma}(-n\cdot\boldsymbol{V})g^2(t')\,d\boldsymbol{\xi}\,dt' \tag{26}$$

3.5. DG scheme for advection equation

We now proceed constructing a DG scheme for solving advection equation.

We consider the following discretization:

$$\begin{aligned}\partial_t\boldsymbol{q} = &-\frac{1}{2}\left(\boldsymbol{D}_\xi(\boldsymbol{u}\odot\boldsymbol{q}) + \boldsymbol{D}_\eta(\boldsymbol{v}\odot\boldsymbol{q})\right) - \frac{1}{2}(\boldsymbol{u}\odot\boldsymbol{D}_\xi\boldsymbol{q} + \boldsymbol{v}\odot\boldsymbol{D}_\eta\boldsymbol{q}) - \frac{1}{2}(\boldsymbol{D}_\xi\boldsymbol{u} + \boldsymbol{D}_\eta\boldsymbol{v})\odot\boldsymbol{q}\\ &+ \boldsymbol{V}\boldsymbol{M}^{-1}\boldsymbol{V}^T\boldsymbol{E}^T\boldsymbol{W}_b\boldsymbol{p}\end{aligned} \tag{27}$$

where

$$\boldsymbol{E} = \left[\boldsymbol{I}_{3(n+1)\times 3(n+1)}|\boldsymbol{0}_{3(n+1)\times(M-3(n+1))}\right] \tag{28}$$

and $\boldsymbol{p}$ is the penalized boundary condition vector, and it is form is to be determined later.

Multiplying $2|T|\boldsymbol{q}^T\boldsymbol{W}$ from the left to the scheme and invoking the discrete divergence theorem, we have

$$\begin{aligned}\frac{d}{dt}(|T|\boldsymbol{q}^T\boldsymbol{W}\boldsymbol{q}) = &-|T|\boldsymbol{q}^T\boldsymbol{W}\left(\boldsymbol{D}_\xi(\boldsymbol{u}\odot\boldsymbol{q}) + \boldsymbol{D}_\eta(\boldsymbol{v}\odot\boldsymbol{q})\right) - |T|\boldsymbol{q}^T\boldsymbol{W}(\boldsymbol{u}\odot\boldsymbol{D}_\xi\boldsymbol{q} + \boldsymbol{v}\odot\boldsymbol{D}_\eta\boldsymbol{q})\\ &- |T|\boldsymbol{q}^T\boldsymbol{W}\left((\boldsymbol{D}_\xi\boldsymbol{u} + \boldsymbol{D}_\eta\boldsymbol{v})\odot\boldsymbol{q}\right) + 2|T|\boldsymbol{q}^T\boldsymbol{W}\boldsymbol{V}\boldsymbol{M}^{-1}\boldsymbol{V}^T\boldsymbol{E}^T\boldsymbol{W}_b\boldsymbol{p}\end{aligned} \tag{29}$$

Apply the relationships $\boldsymbol{M}^{-1} = |T|^{-1}(\boldsymbol{V}\boldsymbol{W}\boldsymbol{V}^T)^{-1}$ and $\boldsymbol{q} = \boldsymbol{V}\hat{\boldsymbol{q}}$, the penalized term becomes

$$\begin{aligned}2|T|\boldsymbol{q}^T\boldsymbol{W}\boldsymbol{V}\boldsymbol{M}^{-1}\boldsymbol{V}^T\boldsymbol{E}^T\boldsymbol{W}_b\boldsymbol{p} =& 2|T|(|T|)^{-1}\widehat{\boldsymbol{q}}^T\boldsymbol{V}^T\boldsymbol{W}\boldsymbol{V}(\boldsymbol{V}\boldsymbol{W}\boldsymbol{V}^T)^{-1}\boldsymbol{V}^T\boldsymbol{E}^T\boldsymbol{W}_b\boldsymbol{p}\\ =& 2\widehat{\boldsymbol{q}}^T\boldsymbol{V}^T\boldsymbol{E}^T\boldsymbol{W}_b\boldsymbol{p} = 2\boldsymbol{q}^T\boldsymbol{E}^T\boldsymbol{W}_b\boldsymbol{p} = 2\boldsymbol{q}_b^T\boldsymbol{W}_b\boldsymbol{p}\end{aligned} \tag{30}$$

Then, the energy rate becomes

$$\begin{aligned}\frac{d}{dt}(|T|\boldsymbol{q}^T\boldsymbol{W}\boldsymbol{q}) =& -\oint_{\partial\mathcal{T}}(\boldsymbol{n}\cdot\boldsymbol{V})q^2\,d\boldsymbol{x} + |T|(\boldsymbol{u}\odot\boldsymbol{q})^T\boldsymbol{W}\boldsymbol{D}_\xi\boldsymbol{q} + |T|(\boldsymbol{v}\odot\boldsymbol{q})^T\boldsymbol{W}\boldsymbol{D}_\eta\boldsymbol{q}\\ &- |T|\boldsymbol{q}^T\boldsymbol{W}(\boldsymbol{u}\odot\boldsymbol{D}_\xi\boldsymbol{q} + \boldsymbol{v}\odot\boldsymbol{D}_\eta\boldsymbol{q}) - |T|\boldsymbol{q}^T\boldsymbol{W}\left((\boldsymbol{D}_\xi\boldsymbol{u} + \boldsymbol{D}_\eta\boldsymbol{v})\odot\boldsymbol{q}\right) + 2\boldsymbol{q}_b^T\boldsymbol{W}_b\boldsymbol{p}\end{aligned} \tag{31}$$

Note that

$$(\boldsymbol{u}\odot\boldsymbol{q})^T\boldsymbol{W}\boldsymbol{D}_\xi\boldsymbol{q} = \sum_{i=0}^{M} u_i q_i (\boldsymbol{D}_\xi\boldsymbol{q})_i w_i = \boldsymbol{q}^T\boldsymbol{W}(\boldsymbol{u}\odot\boldsymbol{D}_\xi\boldsymbol{q}), \tag{32}$$

$$(\boldsymbol{v}\odot\boldsymbol{q})^T\boldsymbol{W}\boldsymbol{D}_\eta\boldsymbol{q} = \sum_{i=0}^{M} v_i q_i (\boldsymbol{D}_\eta\boldsymbol{q})_i w_i = \boldsymbol{q}^T\boldsymbol{W}(\boldsymbol{v}\odot\boldsymbol{D}_\xi\boldsymbol{q}), \tag{33}$$

Hence,

$$\frac{d}{dt}(|T|\boldsymbol{q}^T\boldsymbol{W}\boldsymbol{q}) = -\oint_{\partial\mathcal{T}}(\boldsymbol{n}\cdot\boldsymbol{V})q^2\,d\boldsymbol{x} - |T|\boldsymbol{q}^T\boldsymbol{W}((\boldsymbol{D}_\xi\boldsymbol{u} + \boldsymbol{D}_\eta\boldsymbol{v})\odot\boldsymbol{q}) + 2\boldsymbol{q}_b^T\boldsymbol{W}_b\boldsymbol{p} \tag{34}$$

Consider the boundary term as

$$2\boldsymbol{q}_b^T\boldsymbol{W}_b\boldsymbol{p} = \oint_{\partial\mathcal{T}} 2q\left(\boldsymbol{n}\cdot(\boldsymbol{f} - \boldsymbol{f}^*)\right)\,d\boldsymbol{\xi} \tag{35}$$

where

$$\boldsymbol{f}(q^-) = \boldsymbol{V}q^-, \quad \boldsymbol{f}^*(q^-, q^+) = \frac{\boldsymbol{V}q^- + \boldsymbol{V}q^+}{2} + (1-\tau)\frac{|\boldsymbol{n}^-\cdot\boldsymbol{V}|}{2}(\boldsymbol{n}^-q^- + \boldsymbol{n}^+q^+) \tag{36}$$

where $0 \le \tau \le 1$.

3.6. Numerical boundary and interface conditions

3.6.1. Boundary condition by upwind flux ($\tau = 0$, $q^- = q$ and $q^+ = g$)

To enforce boundary condition, we have, for $q^- = q$, $q^+ = g$, $\boldsymbol{n}^- = \boldsymbol{n}$, $\boldsymbol{n}^+ = -\boldsymbol{n}$,

$$\boldsymbol{f}(q) = \boldsymbol{V}q, \quad \boldsymbol{f}^*(q, g) = \frac{\boldsymbol{V}q + \boldsymbol{V}g}{2} + \frac{|\boldsymbol{n}\cdot\boldsymbol{V}|}{2}(\boldsymbol{n}q - \boldsymbol{n}g)$$

We now discuss the impact of the numerical flux f^*.

Case 1: out flow: $\boldsymbol{n}\cdot\boldsymbol{V} \ge 0$.

we have

$$q\boldsymbol{n}\cdot\boldsymbol{f}^* = \frac{\boldsymbol{n}\cdot\boldsymbol{V}q^2 + \boldsymbol{n}\cdot\boldsymbol{V}qg}{2} + \frac{\boldsymbol{n}\cdot\boldsymbol{V}}{2}(q^2 - qg) = \boldsymbol{n}\cdot\boldsymbol{V}q^2, \tag{37}$$

$$2q\boldsymbol{n}\cdot(\boldsymbol{f} - \boldsymbol{f}^*) = 2q\boldsymbol{n}\cdot\boldsymbol{f} - 2q\boldsymbol{n}\cdot\boldsymbol{f}^* = 2(\boldsymbol{n}\cdot\boldsymbol{V})q^2 - 2(\boldsymbol{n}\cdot\boldsymbol{V})q^2 = 0 \tag{38}$$

Case 2: inflow: $\boldsymbol{n}\cdot\boldsymbol{V}<0$, $\boldsymbol{n}^-=\boldsymbol{n}$, $\boldsymbol{n}^+=-\boldsymbol{n}$.

$$q\boldsymbol{n}\cdot\boldsymbol{f}^* = \frac{\boldsymbol{n}\cdot\boldsymbol{V}q^2+\boldsymbol{n}\cdot\boldsymbol{V}qg}{2}-\frac{\boldsymbol{n}\cdot\boldsymbol{V}}{2}(q^2-qg)=\boldsymbol{n}\cdot\boldsymbol{V}qg$$

and

$$2q\boldsymbol{n}\cdot(\boldsymbol{f}-\boldsymbol{f}^*)=2q\boldsymbol{n}\cdot\boldsymbol{f}-2q\boldsymbol{n}\cdot\boldsymbol{f}^*=2(\boldsymbol{n}\cdot\boldsymbol{V})(q^2-qg)$$

Thus, the boundary term becomes

$$\oint_{\partial\mathcal{T}}\overbrace{(-\boldsymbol{n}\cdot\boldsymbol{V})q^2+2q\boldsymbol{n}\cdot(\boldsymbol{f}-\boldsymbol{f}^*)}^{\rho}\,d\boldsymbol{x}\le\int_\gamma(-\boldsymbol{n}\cdot\boldsymbol{V})g^2\,d\boldsymbol{\xi} \tag{39}$$

since

$$\boldsymbol{\rho}=\begin{cases}(-\boldsymbol{n}\cdot\boldsymbol{V})q^2\le 0 & \text{for out flowing } (\boldsymbol{n}\cdot\boldsymbol{V}>0)\\ (\boldsymbol{n}\cdot\boldsymbol{V})(q-g)^2-\boldsymbol{n}\cdot\boldsymbol{V}g^2\le(-\boldsymbol{n}\cdot\boldsymbol{V})g^2 & \text{for in flowing } (\boldsymbol{n}\cdot\boldsymbol{V}<0)\end{cases} \tag{40}$$

If $\max_{\boldsymbol{\xi}\in\mathcal{T}}||-\boldsymbol{D}_\xi\boldsymbol{u}-\boldsymbol{D}_\eta\boldsymbol{v}||=\alpha$ then we have the energy rate as

$$|T|\frac{d}{dt}(|T|\boldsymbol{q}^T\boldsymbol{W}\boldsymbol{q})-\alpha|T|(\boldsymbol{q}^T\boldsymbol{W}\boldsymbol{q})\le-\oint_\gamma(\boldsymbol{n}\cdot\boldsymbol{V})g^2\,d\boldsymbol{\xi} \tag{41}$$

Multiplying the above expression with respect to time and applying initial condition, we have

$$(|T|\boldsymbol{q}^T\boldsymbol{W}\boldsymbol{q})(t)\le e^{\alpha t}|T|\boldsymbol{q}_0^T\boldsymbol{W}\boldsymbol{q}_0+\int_0^t e^{\alpha(t-t')}\int_{\partial T}(-\boldsymbol{n}\cdot\boldsymbol{V})g^2(\boldsymbol{\xi},t')\,d\boldsymbol{\xi}\,dt' \tag{42}$$

We are left with the exact form of $\boldsymbol{p}$. Let

$$\boldsymbol{q}=[\overbrace{q_1,q_2,\ldots,q_{3(n+1)}}^{\text{boundary points}},\overbrace{q_{3(n+1)+1},\ldots,q_M}^{\text{interior points}}]^T,\quad \boldsymbol{p}=[\overbrace{p_1,p_2,\ldots,p_{3(n+1)}}^{\text{boundary points}}]^T. \tag{43}$$

We require that

$$\begin{aligned}2\boldsymbol{q}_b^T\boldsymbol{W}_b\boldsymbol{p}&=\sum_{i=1}^{n+1}2|\partial T^1|q_iw_i^bp_i+\sum_{i=1}^{n+1}2|\partial T^2|q_{n+1+i}w_i^bp_{n+1+i}+\sum_{i=1}^{n+1}2|\partial T^2|q_{2(n+1)+i}w_i^bp_{2(n+1)+i}\\&=\oint_{\partial T}2q\boldsymbol{n}\cdot(\boldsymbol{f}-\boldsymbol{f}^*)\,d\boldsymbol{x}\\&=\sum_{j=0}^{2}\sum_{i=1}^{n+1}2|\partial T^{j+1}|\,q_{j(n+1)+i}\,(\boldsymbol{n}\cdot(\boldsymbol{f}-\boldsymbol{f}^*))\Big|_{j(n+1)+i}w_i^b\end{aligned} \tag{44}$$

Thus,

$$p_i=(\boldsymbol{n}\cdot(\boldsymbol{f}-\boldsymbol{f}^*))\Big|_i \tag{45}$$

where $f_i=f(\boldsymbol{\xi}_i)$ and $f_i^*=f^*(\boldsymbol{\xi}_i)$.

3.6.2. interface condition by central flux ($\tau = 1$, $q^- = q$ and $q^+ = g$)

The energy rate equations are

$$\forall k = 1, 2, \quad \frac{d}{dt}(|T|(\boldsymbol{q}^{(k)})^T \boldsymbol{W} \boldsymbol{q}^{(k)}) = -\oint_{\partial\mathcal{T}} (\boldsymbol{n}^{(k)} \cdot \boldsymbol{V})(q^{(k)})^2 \, d\boldsymbol{x} + 2(\boldsymbol{q}_b^{(k)})^T \boldsymbol{W}_b \boldsymbol{p}^{(k)} - |T|(\boldsymbol{q}^{(k)})^T \boldsymbol{W}((\boldsymbol{D}_\xi \boldsymbol{u} + \boldsymbol{D}_\eta \boldsymbol{v}) \odot \boldsymbol{q}^{(k)}) \tag{46}$$

To enforce interface condition, we introduce the following flux and numerical flux functions:

$$\boldsymbol{f}(\boldsymbol{q}^-) = \boldsymbol{V}\boldsymbol{q}^-, \quad \boldsymbol{f}^*(\boldsymbol{q}^-, \boldsymbol{q}^+) = \frac{\boldsymbol{V}q^- + \boldsymbol{V}q^+}{2} + \frac{C}{2}(\boldsymbol{n}^- q^- + \boldsymbol{n}^+ q^+) \tag{47}$$

Note that if $C = 0$ then $\boldsymbol{f}^*$ is the central flux function. If $\boldsymbol{n}^- = \boldsymbol{n} = -\boldsymbol{n}^+$ and $C = |\boldsymbol{n} \cdot \boldsymbol{V}|$ then we recover the upwind flux function.

To enforce interface condition from the domain (1) side, we have, for $q^- = q^{(1)}$, $q^+ = q^{(2)}$, $\boldsymbol{n}^- = \boldsymbol{n}^{(1)}$, $\boldsymbol{n}^+ = \boldsymbol{n}^{(2)} = -\boldsymbol{n}^{(1)}$,

$$\boldsymbol{f}(q^{(1)}) = \boldsymbol{V}q^{(1)}, \quad \boldsymbol{f}^*(q^{(1)}, q^{(2)}) = \frac{\boldsymbol{V}q^{(1)} + \boldsymbol{V}q^{(2)}}{2} + \frac{C}{2}\boldsymbol{n}^{(1)}(q^{(1)} - q^{(2)})$$

and to enforce interface condition from the domain (2) side, we have, for $q^- = q^{(2)}$, $q^+ = q^{(1)}$, $\boldsymbol{n}^- = \boldsymbol{n}^{(2)}$, $\boldsymbol{n}^+ = \boldsymbol{n}^{(1)} = -\boldsymbol{n}^{(2)}$,

$$\boldsymbol{f}(q^{(2)}) = \boldsymbol{V}q^{(2)}, \quad \boldsymbol{f}^*(q^{(2)}, q^{(1)}) = \frac{\boldsymbol{V}q^{(2)} + \boldsymbol{V}q^{(1)}}{2} + \frac{C}{2}\boldsymbol{n}^{(2)}(q^{(2)} - q^{(1)})$$

For domain (1), we have

$$\begin{aligned}
2(\boldsymbol{q}_b^{(1)})^T \boldsymbol{W}_b \boldsymbol{p}^{(1)} &= \oint_{\partial\mathcal{T}} 2q^{(1)} \left(\boldsymbol{n}^{(1)} \cdot (\boldsymbol{f}(q^{(1)}) - \boldsymbol{f}^*(q^{(1)}, q^{(2)}))\right) d\boldsymbol{\xi} \\
&= \oint_{\partial\mathcal{T}} 2\left(\boldsymbol{n}^{(1)} \cdot \boldsymbol{V}(q^{(1)})^2 - \boldsymbol{n}^{(1)} \cdot \boldsymbol{V}\frac{(q^{(1)})^2 + q^{(1)}q^{(2)}}{2} - \frac{C}{2}((q^{(1)})^2 - q^{(1)}q^{(2)})\right) d\boldsymbol{\xi} \\
&= \oint_{\partial\mathcal{T}} \left(\boldsymbol{n}^{(1)} \cdot \boldsymbol{V}\right)(q^{(1)})^2 \, d\boldsymbol{\xi} - \oint_{\partial\mathcal{T}} \left(\boldsymbol{n}^{(1)} \cdot \boldsymbol{V}\right) q^{(1)}q^{(2)} \, d\boldsymbol{\xi} \\
&\quad - \oint_{\partial\mathcal{T}} C\left((q^{(1)})^2 - q^{(1)}q^{(2)}\right) d\boldsymbol{\xi}
\end{aligned} \tag{48}$$

For domain (2), we have

$$\begin{aligned}
2(\boldsymbol{q}_b^{(2)})^T \boldsymbol{W}^b \boldsymbol{p}^{(2)} &= \oint_{\partial\mathcal{T}} 2q^{(2)} \left(\boldsymbol{n}^{(2)} \cdot \left(\boldsymbol{f}(q^{(2)}) - \boldsymbol{f}^*(q^{(2)}, q^{(1)})\right)\right) d\boldsymbol{\xi} \\
&= \oint_{\partial\mathcal{T}} 2\left(\boldsymbol{n}^{(2)} \cdot \boldsymbol{V}(q^{(2)})^2 - \boldsymbol{n}^{(2)} \cdot \boldsymbol{V}\frac{(q^{(2)})^2 + q^{(2)}q^{(1)}}{2} - \frac{C}{2}\left((q^{(2)})^2 - q^{(2)}q^{(1)}\right)\right) d\boldsymbol{\xi} \\
&= \oint_{\partial\mathcal{T}} \left(\boldsymbol{n}^{(2)} \cdot \boldsymbol{V}\right)(q^{(2)})^2 \, d\boldsymbol{\xi} - \oint_{\partial\mathcal{T}} \left(\boldsymbol{n}^{(2)} \cdot \boldsymbol{V}\right) q^{(2)}q^{(1)} \, d\boldsymbol{\xi} \\
&\quad - \oint_{\partial\mathcal{T}} C\left((q^{(2)})^2 - q^{(2)}q^{(1)}\right) d\boldsymbol{\xi}
\end{aligned} \tag{49}$$

The total energy rate equation s

$$\frac{d}{dt}\sum_{k=1}^{2}(|T|(\boldsymbol{q}^{(k)})^T\boldsymbol{W}\boldsymbol{q}^{(k)}) = -\sum_{k=1}^{2}\oint_{\partial\mathcal{T}}(\boldsymbol{n}^{(k)}\cdot\boldsymbol{V})(q^{(k)})^2\,d\boldsymbol{x} + \sum_{k=1}^{2}2(\boldsymbol{q}_b^{(k)})^T\boldsymbol{W}_b\boldsymbol{p}^{(k)}$$
$$-\sum_{k=1}^{2}|T|(\boldsymbol{q}^{(k)})^T\boldsymbol{W}((\boldsymbol{D}_\xi\boldsymbol{u}+\boldsymbol{D}_\eta\boldsymbol{v})\odot\boldsymbol{q}^{(k)}) \tag{50}$$

Thus, at an interface point the energy is

$$-C\left((q^{(1)})^2 - q^{(1)}q^{(2)}\right) - C\left((q^{(2)})^2 - q^{(2)}q^{(1)}\right) = -C\left(q^{(1)} - q^{(2)}\right)^2$$

Thus, to ensure dissipation at the interface, we may choose C as follows,

$$C = \begin{cases} |\boldsymbol{n}\cdot\boldsymbol{V}| & \text{upwind flux} \\ \alpha\max_T|\boldsymbol{V}|, \quad \alpha\geq 1 & \text{Lax-Friedrichs flux} \end{cases} \tag{51}$$

We shown that if $C > 0$ the scheme is stable in the semi-discrete level. However, at the fully-discrete level, the scheme may not be stable, due to the amount of dissipation is not enough. Hence, we may adjust the value of α so that the scheme can be made stable. However, the larger the value of α, the smaller time step is required.

Octahedron Sphere

We now discuss the mapping from a box $(x, y) \in [-1, 1]^2$ to a octahedron sphere.

3.7. T_1 to O_1

Let T_1 (triangle), O_1 (octahedron) and S_1 (sphere) be defined as

$$T_1 = \{(x,y)\,|\,x+y\leq 1, \quad 0\leq x,y\leq 1\},$$
$$O_1 = \{(X,Y,Z)\,|\,X+Y+Z=R, \quad 0\leq X,Y,Z\leq R\}$$
$$S_1 = \{(\rho=R,\lambda,\theta)\,|\,0\leq\lambda\leq\frac{\pi}{2}, \quad 0\leq\theta\leq\frac{\pi}{2}\}$$
$$(X,Y,Z) = R(x,y,1-x-y).$$

Then the mapping from (x, y) to (λ, θ) is as follows,

$$\lambda = \frac{\pi}{2}\frac{y}{x+y}, \quad \sin\theta = 1-(x+y)^2, \quad (x,y)\in T_1,$$

or

$$x = \left(1-\frac{2\lambda}{\pi}\right)\sqrt{1-\sin\theta}, \quad y = \frac{2\lambda}{\pi}\sqrt{1-\sin\theta}$$

Then

$$(X, Y, Z) = R(x, y, 1 - x - y), \quad (\bar{X}, \bar{Y}, \bar{Z}) = R(\cos\lambda\cos\theta, \sin\lambda\cos\theta, \sin\theta)$$

Compute

$$\frac{\partial(x,y)}{\partial(\lambda,\theta)} = \begin{bmatrix} \frac{\partial x}{\partial \lambda} & \frac{\partial x}{\partial \theta} \\ \frac{\partial y}{\partial \lambda} & \frac{\partial y}{\partial \theta} \end{bmatrix} = \begin{bmatrix} -\frac{\pi}{2}\sqrt{1-\sin\theta} & -\frac{(\pi-2\lambda)\cos\theta}{2\pi\sqrt{1-\sin\theta}} \\ \frac{\pi}{2}\sqrt{1-\sin\theta} & -\frac{2\lambda\cos\theta}{2\pi\sqrt{1-\sin\theta}} \end{bmatrix} \quad \det\left(\frac{\partial(x,y)}{\partial(\lambda,\theta)}\right) = \frac{\pi}{4}\cos\theta$$

Then

$$\frac{\partial(x,y)}{\partial(\lambda,\theta)} = \begin{bmatrix} \frac{\partial \lambda}{\partial x} & \frac{\partial \lambda}{\partial y} \\ \frac{\partial \theta}{\partial x} & \frac{\partial \theta}{\partial y} \end{bmatrix} = \frac{4}{\pi\cos\theta} \begin{bmatrix} -\frac{2\lambda\cos\theta}{2\pi\sqrt{1-\sin\theta}} & \frac{(\pi-2\lambda)\cos\theta}{2\pi\sqrt{1-\sin\theta}} \\ -\frac{\pi}{2}\sqrt{1-\sin\theta} & -\frac{\pi}{2}\sqrt{1-\sin\theta} \end{bmatrix}$$

Transformation matrix $\boldsymbol{A}$ and $\boldsymbol{A}^{-1}$:

$$\boldsymbol{A} = \begin{bmatrix} R\cos\theta\lambda_x & R\cos\theta\lambda_y \\ R\theta_x & R\theta_y \end{bmatrix}, \quad \det(\boldsymbol{A}) = R^2\cos\theta(\lambda_x\theta_y - \lambda_y\theta_x)$$

$$\boldsymbol{A}^{-1} = \frac{1}{\det(\boldsymbol{A})} \begin{bmatrix} R\theta_y & -R\cos\theta\lambda_y \\ -R\theta_x & R\cos\theta\lambda_x \end{bmatrix}$$

$\boldsymbol{G}$ and $\boldsymbol{G}^{-1}$ matrices and $\sqrt{G}$:

$$\boldsymbol{G} = \boldsymbol{A}^T\boldsymbol{A}, \quad J = \sqrt{\det(\boldsymbol{G})}$$

Transformation of vector on the sphere: Let

$$\boldsymbol{V} = (u, v) = u\boldsymbol{e}_\lambda + v\boldsymbol{e}_\theta$$

Then

$$\begin{bmatrix} u \\ v \end{bmatrix} = \boldsymbol{A}\begin{bmatrix} u^1 \\ u^2 \end{bmatrix}, \quad \begin{bmatrix} u^1 \\ u^2 \end{bmatrix} = \boldsymbol{A}^{-1}\begin{bmatrix} u \\ v \end{bmatrix}$$

4. Advection equation on the sphere

Advection equation:

$$\frac{\partial}{\partial t}q(\lambda,\theta,t) + \nabla\cdot(\boldsymbol{V}q) = 0$$

where $\nabla\cdot(\boldsymbol{V}q)$ is the surface divergence of $\boldsymbol{V}q$

$$\boldsymbol{V} = (u, v), \quad u = u_0(\cos\alpha_0\cos\theta + \sin\alpha_0\cos\lambda\sin\theta), \quad v = -u_0\sin\alpha_0\sin\lambda$$

Based on the transformation, the advection equation on the triangle domain is

$$\frac{\partial}{\partial t}(\sqrt{G}q) + \frac{\partial}{\partial x}(\sqrt{G}u^1 q) + \frac{\partial}{\partial y}(\sqrt{G}u^2 q) = 0$$

Note that $\sqrt{G}$ is a constant for the current transformation. Hence, the equation can be simplified as

$$\frac{\partial q}{\partial t} + \frac{\partial}{\partial x}(u^1 q) + \frac{\partial}{\partial y}(u^2 q) = 0$$

Hence, we can solve the problem based on the scheme developed in the previous section.