

Dynamic Intelligence Hub

DCS Baggage Open Api Specification

Table of Contents

Dynamic Intelligence Hub API and Data Models - DCS Baggage	1
Overview	2
Version information	2
URI scheme	2
Consumes	2
Produces	2
Paths	3
DCS Baggage Data Push	3
DCS Baggage Correlations Data Push	8
Retrieve DCS Baggage Entities using a Baggage Group Identifier	10
Definitions	12
Bag	12
BagLegDelivery	12
BagTag	13
BagsGroup	14
ChargeableServiceDocument	15
CorrelatedBagsGroupDcsPassengerLegData	15
CorrelatedBagsGroupPnrLegData	16
CorrelatedDataBagsGroupDcsPassenger	16
CorrelatedDataBagsGroupPnr	16
CorrelationBagsGroupDcsPassenger	17
CorrelationBagsGroupPnr	17
CorrelationData	17
DcsBaggageApiData	18
DcsBaggageApiResponse	19
DcsBaggageCorrelationsPush	19
DcsBaggagePush	19
Dictionaries	20
Error	20
ErrorSource	21
Errors	21
EventLog	21
Events	22
ExcessBaggageCalculation	23
ExcessBaggageCharge	23
ExcessBaggageItem	24
FlightDesignator	25
FlightEndPoint	25

IncludedResources	25
InfrastructureLocation	26
Meta	26
PatchOperation	27
Price	27
QualifiedFreeText	27
Relationship	28
Relationships	28
Service	28
SpecialBagHandling	29
TimeLocationTrackingLog	30
User	31
Warning	31
Weight	32
Workstation	32
Security	33
basicAuth	33

Dynamic Intelligence Hub API and Data Models - DCS Baggage

Overview

This document describes the API Specifications used to query DCS Baggage data. DCSBaggage record consists of - BagsGroup entity - attributes for group of bags travelling together - Bag entities - attributes for each Bag in the BagsGroup - ExcessBaggageCharge entities - attributes for any excess baggage charges associated The API returns Bags Group, Bags and Excess Baggage information along with Bag Pool information and Relationships of Responsible Passengers if any. The default language is "en" for string formatting like monetary amount.

Version information

Version : 2.1.0

URI scheme

Host : airlines.api.amadeus.com

BasePath : /v2

Schemes : HTTPS

Consumes

- `application/json`

Produces

- `application/vnd.amadeus+json`

Paths

DCS Baggage Data Push

POST /departure-control/dcs-baggage-feed

Description

Model for the DCS Baggage data push feed. Please be aware this is NOT a POST API, rather this explains the format of the data pushed out by Amadeus.

Responses

HTTP Code	Schema
200	DcsBaggagePush

Tags

- Data Push Models

Example HTTP response

Response 200

```
{
  "meta" : {
    "triggerEventLog" : {
      "id" : "46541dsfsSDRWFS54"
    },
    "version" : "2.1.0"
  },
  "lastModification" : {
    "dateTime" : "2015-10-05T10:00:00.043Z",
    "triggerEventName" : "BBTGPQ-Print Baggage Tag",
    "user" : {
      "id" : "USR0001",
      "officeId" : "NCE6X08AA",
      "workstation" : {
        "id" : "A/LHR/T/2/CKI/1/1",
        "fullLocation" : {
          "airportCode" : "LHR",
          "cityCode" : "LON",
          "terminalId" : "2E",
          "buildingId" : "1",
          "areaCode" : "CKI",
          "identifier" : "1",

```

```

        "description" : "LHR TERM-2E"
    }
}
},
"processedBagsGroup" : {
    "type" : "bags-group",
    "id" : "10FBC42026758291",
    "eTag" : 1602876919851,
    "checkedBagsCount" : 1,
    "checkedBagsWeight" : {
        "value" : 125,
        "unit" : "KILOGRAMS"
    },
    "handBagsCount" : 1,
    "handBagsWeight" : {
        "value" : 125,
        "unit" : "KILOGRAMS"
    },
    "responsiblePassenger" : {
        "id" : 1200000000000001,
        "type" : "dcs-passenger",
        "href" : "https://airlines.api.amadeus.com/v2/departure-control/processed-dcs-passengers/1200000000000001",
        "methods" : [ "GET" ]
    },
    "checkedBags" : {
        "collection" : [ {
            "id" : "1101CA1100003431",
            "type" : "bag",
            "ref" : "processedBags"
        } ]
    },
    "pooledPassengers" : {
        "collection" : [ {
            "id" : 1200000000000001,
            "type" : "dcs-passenger",
            "href" : "https://airlines.api.amadeus.com/v2/departure-control/processed-dcs-passengers/1200000000000001",
            "methods" : [ "GET" ]
        } ]
    },
    "itinerary" : [ {
        "id" : "JFK",
        "boardPoint" : {
            "iataCode" : "JFK"
        },
        "offPoint" : {
            "iataCode" : "LHR"
        }
    } ]
} ]

```

```

},
"processedBags" : [ {
  "id" : "1101CA1100003431",
  "bagType" : "STANDARD",
  "bagTag" : {
    "licensePlate" : 5.7483945E7,
    "issuingCarrier" : "6X",
    "finalDestination" : "JFK",
    "systemSource" : "AUTOMATIC"
  },
  "linkedBagTag" : {
    "licensePlate" : 5.7483946E7,
    "issuingCarrier" : "6X",
    "finalDestination" : "JFK",
    "issuanceDay" : 2
  },
  "lastSeenLocation" : {
    "deviceId" : "AF5FA7A4",
    "deviceUser" : 116554,
    "localDateTime" : "2018-10-30T16:43",
    "logSource" : "BAGGAGE_RECONCILIATION_SYSTEM"
  },
  "systemSource" : "AUTOMATIC",
  "weight" : {
    "value" : 125,
    "unit" : "KILOGRAMS"
  },
  "owner" : {
    "id" : 1200000000000001,
    "type" : "dcs-passenger",
    "href" : "https://airlines.api.amadeus.com/v2/departure-control/processed-dcs-passengers/1200000000000001",
    "methods" : [ "GET" ]
  },
  "legs" : [ {
    "id" : "JFK",
    "boardPoint" : {
      "iataCode" : "JFK",
      "localDateTime" : "2018-11-29"
    },
    "offPoint" : {
      "iataCode" : "LHR"
    },
    "operatingFlight" : {
      "carrierCode" : "6X",
      "flightNumber" : 1011,
      "operationalSuffix" : "A"
    },
    "acceptanceStatus" : "FULLY_ACCEPTED",
    "activationStatus" : "ACTIVE",
    "travelClassCode" : "Y",

```



```

    "authorityToLoad" : true,
    "authorityToTransport" : true,
    "offloaded" : false,
    "checkinLocation" : {
      "trackedLocation" : {
        "identifier" : "CKIN"
      }
    },
    "specialBagHandlingItems" : [ {
      "id" : "GOLF",
      "service" : {
        "code" : "GOLF",
        "subType" : "SPECIAL_SERVICE_REQUEST",
        "description" : "Golf Bag",
        "statusCode" : "HK"
      }
    } ]
  } ],
  "processedExcessBaggageCharges" : [ {
    "id" : 1000000000000001,
    "paymentStatus" : "PAID",
    "waiverReason" : {
      "text" : "Excess Waived by Admin"
    },
    "responsiblePassenger" : {
      "id" : 1200000000000001,
      "type" : "dcs-passenger",
      "href" : "https://airlines.api.amadeus.com/v2/departure-control/processed-dcs-passengers/1200000000000001",
      "methods" : [ "GET" ]
    },
    "segments" : {
      "collection" : [ {
        "id" : "2401CA5500003431",
        "type" : "segment-delivery"
      } ]
    },
    "totalCharge" : {
      "total" : "150.50",
      "currency" : "GBP"
    },
    "calculations" : [ {
      "id" : "10DF2D0000BD64F4",
      "boardPoint" : {
        "iataCode" : "JFK"
      },
      "offPoint" : {
        "iataCode" : "LHR"
      }
    },
    "items" : [ {

```

```

    "id" : "1000000000A21C1B",
    "itemType" : "WEIGHT",
    "quantity" : 1,
    "weight" : {
      "value" : 125,
      "unit" : "KILOGRAMS"
    },
    "boardPoint" : {
      "iataCode" : "JFK"
    },
    "offPoint" : {
      "iataCode" : "LHR"
    },
    "rate" : {
      "total" : "15.50",
      "currency" : "GBP"
    },
    "charge" : {
      "total" : "150.50",
      "currency" : "GBP"
    },
    "bag" : {
      "id" : "1101CA1100003431",
      "type" : "bag",
      "ref" : "processedBags"
    },
    "paymentDocument" : {
      "documentType" : "EMD",
      "number" : "1728200002469"
    },
    "waiverReason" : {
      "text" : "Excess Waived by Admin"
    }
  } ]
} ],
"previousRecord" : [ {
  "op" : "replace",
  "path" : "/processedBagsGroup/responsiblePassenger/id",
  "value" : "2501ADE000000000"
} ],
"events" : {
  "recordDomain" : "DCSBAGGAGE",
  "recordId" : "2501ADE0000000001",
  "originFeedTimeStamp" : "2018-10-24T14:19:00Z",
  "events" : [ {
    "origin" : "COMPARISON",
    "eventType" : "UPDATED",
    "currentPath" : "/processedBagsGroup/responsiblePassenger/id",
    "previousPath" : "/processedBagsGroup/responsiblePassenger/id"
  } ]
} ]

```

```
}  
}
```

DCS Baggage Correlations Data Push

POST /departure-control/dcs-baggages-correlations-feed

Description

Model for the DCS Baggage correlations data push feed. Please be aware this is NOT a POST API, rather this explains the format of the data pushed out by Amadeus.

Responses

HTTP Code	Schema
200	DcsBaggageCorrelationsPush

Tags

- Data Push Models

Example HTTP response

Response 200

```
{  
  "meta" : {  
    "triggerEventLog" : {  
      "id" : "46541dsfsSDRWFS54"  
    },  
    "version" : "2.1.0"  
  },  
  "dcsBaggageCorrelations" : {  
    "correlationBagsGroupDcsPassenger" : {  
      "bagsGroupId" : "AA42BA1395020102",  
      "dcsPassengerIds" : [ "2401CA5500003431" ],  
      "correlatedData" : {  
        "2401CA5500003431" : [ {  
          "bagId" : "1101CA1100003431",  
          "bagLegCorrelations" : [ {  
            "bagLegDeliveryId" : "LHR",  
            "dcsPassengerLegDeliveryId" : "LHR",  
            "dcsPassengerSegmentDeliveryId" : "2202DA1200003432"  
          } ], {  
            "bagLegDeliveryId" : "BKK",  
            "dcsPassengerLegDeliveryId" : "BKK",  

```

```

        "dcsPassengerSegmentDeliveryId" : "2202DA1200003432"
      } ]
    } ]
  },
  "correlationBagsGroupPnr" : {
    "bagsGroupId" : "AA42BA1395020102",
    "pnrIds" : [ "ORY4NY-2018-10-19" ],
    "correlatedData" : {
      "ORY4NY-2018-10-19" : [ {
        "bagId" : "1101CA1100003431",
        "pnrTravelerId" : "ORY4NY-2018-10-19-PT-1",
        "bagLegCorrelations" : [ {
          "bagLegDeliveryId" : "ORY",
          "pnrAirSegmentId" : "ORY4NY-2018-10-19-ST-1"
        } ]
      } ]
    } ]
  },
  "dictionaries" : {
    "bagsGroups" : {
      "AA42BA1395020102" : {
        "type" : "bags-group",
        "id" : "AA42BA1395020102",
        "version" : "1",
        "href" : "https://airlines.api.amadeus.com/v2/departure-control/processed-bags-groups/AA42BA1395020102"
      }
    },
    "dcsPassengers" : {
      "2401CA5500003431" : {
        "type" : "dcs-passenger",
        "id" : "2401CA5500003431",
        "version" : "1",
        "href" : "https://airlines.api.amadeus.com/v2/departure-control/processed-dcs-passengers/2401CA5500003431"
      }
    },
    "pnrs" : {
      "ORY4NY-2018-10-19" : {
        "type" : "pnr",
        "id" : "ORY4NY-2018-10-19",
        "version" : "1",
        "href" : "https://airlines.api.amadeus.com/v1/reservation/processed-pnrs/ORY4NY-2018-10-19"
      }
    }
  },
  "events" : {
    "recordDomain" : "DCSBAGGAGE_DCSPASSENGER",

```

```

"recordId" : "AA42BA1395020102",
"originFeedTimeStamp" : "2018-10-24T14:19:00Z",
"events" : [ {
  "origin" : "COMPARISON",
  "eventType" : "UPDATED",
  "currentPath" :
"/dcsBaggageCorrelations/correlationBagsGroupDcsPassenger/correlatedData/bagsGroupId/A
A42BA1395020102",
  "previousPath" :
"/dcsBaggageCorrelations/correlationBagsGroupDcsPassenger/correlatedData/bagsGroupId/A
A42BA1395020102"
} ]
}
}

```

Retrieve DCS Baggage Entities using a Baggage Group Identifier

```
GET /departure-control/processed-bags-groups/{id}
```

Description

Returns the DCS Baggage Entities inside the Baggage Group whose identifier is passed as parameter.

Parameters

Type	Name	Description	Schema
Path	id <i>required</i>	Identifier of a DCS Baggage Record	string

Responses

HTTP Code	Description	Schema
200	Successful operation	DcsBaggageApiResponse
401	Unauthorized. Missing credentials in header request.	Errors
403	Forbidden. Authorization refused for the credentials provided.	Errors
404	Baggage Group or Baggage with the requested id was not found.	Errors
500	Internal server error / Technical	Errors

Tags

- BaggageAPIs

Security

Type	Name
basic	basicAuth

Definitions

Bag

Main entity providing core information on a Baggage Entity. A passenger (Pax) in DCS can own one or more bags, i.e. Bag entities. (ID – UBI)

Name	Description	Schema
bagTag <i>optional</i>		BagTag
bagType <i>optional</i>	The type of the baggage Example : "STANDARD"	enum (EARLY, RUSH, STANDARD, CREW)
id <i>optional</i>	The UBI (Unique Baggage Identifier) of the bag item Example : "1101CA1100003431"	string
lastSeenLocation <i>optional</i>		TimeLocationTrackingLog
legs <i>optional</i>	Flight-leg information associated with the baggage item	< BagLegDelivery > array
linkedBagTag <i>optional</i>		BagTag
owner <i>optional</i>	Relationship to the DCS passenger that owns this baggage	Relationship
systemSource <i>optional</i>	The system process that created the Baggage Example : "AUTOMATIC"	enum (AUTOMATIC, BTM, CRYPTIC, AUTO_BAG_DROP, IATCI, FRONTEND, KIOSK, OTHERS, BPM, SMS, TELEPHONE, WEB)
weight <i>optional</i>		Weight

BagLegDelivery

Stores all the itinerary related information of the bag or bag group corresponding to a flight-leg. operatingFlight is not populated for itinerary in BagsGroup.

Name	Description	Schema
acceptanceStatus <i>optional</i>	The acceptance status of the bag item for the current flight leg Example : "FULLY_ACCEPTED"	enum (FULLY_ACCEPTED, NOT_ACCEPTED, PROVISIONALLY_ACCEPTED, NOT_TRAVELLING)
activationStatus <i>optional</i>	The activation status of the bag item for the current flight leg Example : "ACTIVE"	enum (ACTIVE, INACTIVE, VALIDATED)
authorityToLoad <i>optional</i>	Indicates if the Bag is authorised to be loaded onto the flight Example : true	boolean
authorityToTransport <i>optional</i>	Indicates if the Bag is authorised to be transported by the flight Example : true	boolean
boardPoint <i>optional</i>		FlightEndPoint
checkinLocation <i>optional</i>		TimeLocationTrackingLog
id <i>optional</i>	Bag Leg Identifier Example : "JFK"	string
offPoint <i>optional</i>		FlightEndPoint
offloaded <i>optional</i>	Indicates if the Bag was offloaded from the flight Example : false	boolean
operatingFlight <i>optional</i>		FlightDesignator
specialBagHandlingItems <i>optional</i>		< SpecialBagHandling > array
travelClassCode <i>optional</i>	The cabin class code associated with the bag item Example : "Y"	string

BagTag

A document issued by carrier solely for identification of checked baggage, the baggage (strap) tag portion of which is attached by carrier to a particular article of checked baggage and the baggage (identification) tag portion of which is given to the passenger.

Name	Description	Schema
finalDestination <i>optional</i>	The final destination of the bag as issued on the bag tag, given as the three letter IATA airport code Example : "JFK"	string
issuanceDay <i>optional</i>	The day of the bag tag issuance (0-366), typically empty if not a linked bag tag Example : 2	integer
issuingCarrier <i>optional</i>	The bag tag's issuing carrier code Example : "6X"	string
licensePlate <i>optional</i>	The bag's 10 digit licence plate comprising of leading digit, company code and tag number Example : "5.7483945E7"	string
systemSource <i>optional</i>	Which system process was the bag tag created Example : "AUTOMATIC"	enum (AUTOMATIC, BTM, BPM, IATCI, MANUAL)

BagsGroup

The BagsGroup serves to group and aggregate properties of bags travelling together, including weight, number of bags, the common itinerary and pooling. Each BagsGroup has a responsible passenger, which in the case of pooling is the head of the pool. Every individual bag (baggage entity) forms part of at least one BagsGroup. An individual bag is part of multiple BagsGroups when a passenger is travelling with multiple bags on a multi-legged flight, with some bags not travelling on all the legs. In this case a BagsGroup is formed for every subset of bags on the legs they are travelling together. Therefore, the Bag and BagsGroup entities form a many-to-many relation.

Name	Description	Schema
checkedBags <i>optional</i>	A collection of links to the individual bags comprising this bags group	Relationships
checkedBagsCount <i>optional</i>	The number of checked bags comprising this bags group Example : 5	integer
checkedBagsWeight <i>optional</i>	The total weight of all checked bags	Weight
etag <i>optional</i>	Sequence number for comparison between two baggage images and to know which one is the latest. Example : "1602876919851"	string
handBagsCount <i>optional</i>	The number of hand baggage items comprising this bags group Example : 1	integer

Name	Description	Schema
handBagsWeight <i>optional</i>	The total weight of hand baggage items comprising this bags group.	Weight
id <i>optional</i>	The baggage group reference Example : "10FBC42026758291"	string
itinerary <i>optional</i>	The itinerary where the bags comprising the bags group are travelling	< BagLegDelivery > array
pooledPassengers <i>optional</i>	A one-to-many relationship between the BagsGroup and the DCS-Passengers that are pooled in the group (not including the head of pool)	Relationships
responsiblePassenger <i>optional</i>	The DCS Passenger responsible for the BagsGroup and the head of pool	Relationship
type <i>optional</i>	resource name Example : "bags-group"	enum (bags-group)

ChargeableServiceDocument

A reference to either MCO or EMD document by number and type. A chargeable service document represents the document issued as a result of the chargeable service payment. The document status stores the state of the document as either refunded, voided, or flown (used).

Name	Description	Schema
documentType <i>optional</i>	the type of document for the chargeable service. Either MCO for Miscellaneous Charge Order or EMD for Electronic Miscellaneous Document Example : "EMD"	enum (EMD, MCO)
number <i>optional</i>	the document number Example : "1728200002469"	string

CorrelatedBagsGroupDcsPassengerLegData

Name	Description	Schema
bagLegDeliveryId <i>optional</i>	Example : "LHR"	string
dcsPassengerLegDeliveryId <i>optional</i>	Example : "LHR"	string

Name	Description	Schema
dcsPassengerSegmentDeliveryId <i>optional</i>	Example : "2202DA1200003432"	string

CorrelatedBagsGroupPnrLegData

Set of data field identifiers defining the correlation between DCS Baggage Group and Pnr Air Segments

Name	Description	Schema
bagLegDeliveryId <i>optional</i>	Example : "LHR"	string
pnrAirSegmentId <i>optional</i>	Example : "ORY4NY-2018-10-19-ST-1"	string

CorrelatedDataBagsGroupDcsPassenger

Set of data field identifiers defining the correlation between a DCS Baggage record and a DCS Passenger

Name	Description	Schema
bagId <i>optional</i>	Example : "1101CA1100003431"	string
bagLegCorrelations <i>optional</i>		< CorrelatedBagsGroupDcsPassengerLegData > array

CorrelatedDataBagsGroupPnr

Set of data field identifiers defining the correlation between DCS Baggage Group and Pnr Segments

Name	Description	Schema
bagId <i>optional</i>	Example : "1101CA1100003431"	string
bagLegCorrelations <i>optional</i>		< CorrelatedBagsGroupPnrLegData > array

Name	Description	Schema
pnrTravelerId <i>optional</i>	Example : "ORY4NY-2018-10-19-PT-1"	string

CorrelationBagsGroupDcsPassenger

Structure of correlation between a DCS Baggage Group and DCS Passenger(s).

Name	Description	Schema
bagsGroupId <i>optional</i>	Current DCS Baggage Group Identifier Example : "AA42BA1395020102"	string
correlatedData <i>optional</i>		< string, < CorrelatedDataBagsGroupDcsPassenger > array > map
dcsPassengerIds <i>optional</i>	Identifying DCS Passenger(s) correlated with the DCS Baggage record Example : "2501ADE000000001"	< string > array

CorrelationBagsGroupPnr

Structure of correlation between a DCS Baggage Group and Passenger Name Records.

Name	Description	Schema
bagsGroupId <i>optional</i>	Current DCS Baggage Group Identifier Example : "AA42BA1395020102"	string
correlatedData <i>optional</i>		< string, < CorrelatedDataBagsGroupPnr > array > map
pnrIds <i>optional</i>	Identifying the PNR correlated with the current DCS Baggage Group - item format is record locator + creation date Example : ["ORY4NY-2018-10-19", "KBR849-2018-09-17"]	< string > array

CorrelationData

Name	Schema
correlationBagsGroupDcsPassenger <i>optional</i>	CorrelationBagsGroupDcsPassenger
correlationBagsGroupPnr <i>optional</i>	CorrelationBagsGroupPnr

Name	Schema
dictionaries <i>optional</i>	Dictionaries

DcsBaggageApiData

Polymorphism : Composition

Name	Description	Schema
bags <i>optional</i>		Relationships
checkedBags <i>optional</i>	A collection of links to the individual bags comprising this bags group	Relationships
checkedBags Count <i>optional</i>	The number of checked bags comprising this bags group Example : 5	integer
checkedBags Weight <i>optional</i>	The total weight of all checked bags	Weight
correlations <i>optional</i>	Correlation structures are defined in the included section. This section provides links for all the correlation structures pertaining to the current Baggage Group. Following are correlation link examples.	correlations
etag <i>optional</i>	Sequence number for comparison between two baggage images and to know which one is the latest. Example : "1602876919851"	string
excessBaggageCharges <i>optional</i>		Relationships
handBagsCount <i>optional</i>	The number of hand baggage items comprising this bags group Example : 1	integer
handBagsWeight <i>optional</i>	The total weight of hand baggage items comprising this bags group.	Weight
id <i>optional</i>	The baggage group reference Example : "10FBC42026758291"	string
itinerary <i>optional</i>	The itinerary where the bags comprising the bags group are travelling	< BagLegDelivery > array
pooledPassengers <i>optional</i>	A one-to-many relationship between the BagsGroup and the DCS-Passengers that are pooled in the group (not including the head of pool)	Relationships

Name	Description	Schema
responsiblePassenger <i>optional</i>	The DCS Passenger responsible for the BagsGroup and the head of pool	Relationship
type <i>optional</i>	resource name Example : "bags-group"	enum (bags-group)

correlations

Name	Schema
bagsGroupDcsPassenger <i>optional</i>	Relationship
bagsGroupPnr <i>optional</i>	Relationship

DcsBaggageApiResponse

Name	Schema
data <i>optional</i>	DcsBaggageApiData
dictionaries <i>optional</i>	Dictionaries
included <i>optional</i>	IncludedResources

DcsBaggageCorrelationsPush

Name	Schema
dcsBaggageCorrelations <i>optional</i>	CorrelationData
events <i>optional</i>	Events
meta <i>optional</i>	Meta

DcsBaggagePush

The Online data push schema to be referenced in the main Swagger spec.

Name	Description	Schema
events <i>optional</i>		Events
lastModification <i>optional</i>		EventLog
meta <i>optional</i>		Meta
previousRecord <i>optional</i>	List of JSON Patches as defined by RFC 6902 (see https://tools.ietf.org/html/rfc6902) to apply to processedBagsGroup, processedBags, processedExcessBaggageCharges [latest BagsGroup, Bag and ExcessBaggageCharge version] in order to obtain the actual JSON of the previous BagsGroup, Bag and ExcessBaggageCharge version.	< PatchOperation > array
processedBags <i>optional</i>		< Bag > array
processedBagsGroup <i>optional</i>		BagsGroup
processedExcessBaggageCharges <i>optional</i>		< ExcessBaggageCharge > array

Dictionaries

Name	Description	Schema
bagsGroups <i>optional</i>	Set of key/value pairs with Baggage Group Identifier as key	< string, Relationship > map
dcsPassengers <i>optional</i>	Set of key/value pairs with UCI as key example '2401CA5500003431'	< string, Relationship > map
pnrs <i>optional</i>	Set of key/value pairs with pnrId as key i.e. record locator + creation date - key example 'ABCDEF-2018-05-15'	< string, Relationship > map

Error

Name	Description	Schema
code <i>required</i>	A machine-readable error code from the Amadeus Canned Messages table, that will enable the API Consumers code to handle this type of error	integer
detail <i>optional</i>	An easy-to-read explanation specific to this occurrence of the problem. It should give the API consumer an idea of what went wrong and how to recover from it. Like the title, this field's value can be localized.	string
documentation <i>optional</i>	A link to a web page or file with further documentation to help the API consumer resolve this error	string (url)
source <i>optional</i>		ErrorSource
status <i>required</i>	The HTTP status code of this response. This is present only in terminal errors which cause an unsuccessful response. In the case of multiple errors, they must all have the same status.	integer
title <i>required</i>	An error title from the Canned Messages table with a 1:1 correspondence to the error code. This may be localized	string

ErrorSource

Name	Description	Schema
example <i>optional</i>	A sample input to guide the user when resolving this issue	string
parameter <i>optional</i>	The key of the URI path or query parameter that caused the error	string
pointer <i>optional</i>	A JSON Pointer [RFC6901] to the associated entity in the request body that caused this error	string

Errors

Name	Schema
errors <i>optional</i>	< Error > array

EventLog

Details about the original event triggering the current datapush feed Used by Meta.triggerEventLog and DcsBaggagePush.lastModification

Name	Description	Schema
dateTime <i>optional</i>	GMT date & time Example : "2015-10-05T10:00:00Z"	string (date-time)
id <i>optional</i>	Identifier of the change Example : "46541dsfsSDRWF554"	string
triggerEventName <i>optional</i>	The name of the trigger event. Set to 'DATA_INIT' for initialization messages Example : "DATA_INIT"	string
user <i>optional</i>		User

Events

Structure of Dynamic Intelligence Hub functional events. It has information about what exactly changed in the current payload as compared to the previous version.

Name	Description	Schema
events <i>optional</i>	List of events that have been detected on the DCS Baggage document	< events > array
originFeedTimeStamp <i>optional</i>	Incoming PSS feed time stamp	string (date-time)
recordDomain <i>optional</i>	Functional domain of the record Example : "DCSBAGGAGE"	string
recordId <i>optional</i>	Record identifier e.g. Baggage Group Identifier Example : "AA42BA1395020102"	string

events

Name	Description	Schema
currentPath <i>optional</i>	String containing the JSON Pointer (see IETF RFC6901) that points to the data referenced by the Event in the latest version of the entity. It is only applicable for CREATED and UPDATED events. Example : ""	string
eventType <i>optional</i>	In case of comparison events, type of operation notified by the event Example : "CREATED"	enum (CREATED, UPDATED, DELETED)
origin <i>optional</i>	Type of event e.g. 'COMPARISON' / 'TIME_INITIATED_EVENT' Example : "COMPARISON"	string

Name	Description	Schema
previousPath <i>optional</i>	String containing the JSON Pointer (see IETF RFC6901) that points to the data referenced by the Event in the previous version of the entity. It is only applicable for DELETED and UPDATED events. Example : " "	string

ExcessBaggageCalculation

The airline can decide whether it considers customer's baggage per piece or per weight, so the allowed limit will be set in weight units (Kg) or number of pieces. Additionally, if the airline uses a piece policy, it can also define a maximum weight per piece. Any bags over this weight will also be considered as excess baggage, and more specifically as heavy bags. Therefore, the calculation of the charges to pay by the passenger in case of excess baggage will depend on the airline's policy/scheme.

Name	Description	Schema
boardPoint <i>optional</i>		FlightEndPoint
id <i>optional</i>	The identifier of excess baggage calculation Example : "10DF2D0000BD64F4"	string
items <i>optional</i>		< ExcessBaggageItem > array
offPoint <i>optional</i>		FlightEndPoint

ExcessBaggageCharge

The ExcessBaggageCharge entity maps the core information related to baggage in excess. The entity intends to capture the following information- - The total charges incurred to a passenger and their payment status - The part of the passenger's journey for which excess is calculated - The passenger's baggage allowance on that journey - A breakdown of the calculation per item in excess There is not one single way of calculating excess in DCS. There are different flavors of excess used by different airlines. These differences are mainly observable in the way the baggage allowance and excess rates and charges are determined.

Name	Description	Schema
calculations <i>optional</i>		< ExcessBaggageCalculation > array
id <i>optional</i>	Unique Identifier of Excess Baggage Charge XCI Example : "1000000000000001"	string

Name	Description	Schema
paymentStatus <i>optional</i>	Denotes if the payment has be made or waived etc Example : "PAID"	enum (PAID, UNPAID, WAIVED, EXEMPTED)
responsiblePassenger <i>optional</i>		Relationship
segments <i>optional</i>	Links to the products of the responsible passenger to which this charge applies.	Relationships
totalCharge <i>optional</i>	A breakdown of the total charge	Price
waiverReason <i>optional</i>	Waiver reason associated with the Excess Baggage Charge	QualifiedFreeText

ExcessBaggageItem

A breakdown of the calculation per item in excess.

Name	Description	Schema
bag <i>optional</i>	The relationship to the bag item this charge is applied on	Relationship
boardPoint <i>optional</i>		FlightEndPoint
charge <i>optional</i>		Price
id <i>optional</i>	The identifier of excess baggage item Example : "1000000000A21C1B"	string
itemType <i>optional</i>		enum (PIECE, WEIGHT, HEAVY_CHARGE)
offPoint <i>optional</i>		FlightEndPoint
paymentDocument <i>optional</i>		ChargeableServiceDocument
quantity <i>optional</i>		integer
rate <i>optional</i>		Price

Name	Description	Schema
waiverReason <i>optional</i>	Waiver reason associated with the Excess Baggage Item	QualifiedFreeText
weight <i>optional</i>	only used with itemType "WEIGHT"	Weight

FlightDesignator

This is an identifier that consists of airline code, the flight number and optional operational suffix.

Name	Description	Schema
carrierCode <i>optional</i>	Example : "6X"	string
flightNumber <i>optional</i>	Example : "1011"	string
operationalSuffix <i>optional</i>	Example : "A"	string

FlightEndPoint

Departure or arrival information. `localDateTime` property is only applicable to `BagLegDelivery` structure.

Name	Description	Schema
iataCode <i>optional</i>	IATA Airport code Example : "JFK"	string
localDateTime <i>optional</i>	Local date and time in ISO 8601 format Example : "2018-09-14"	string

IncludedResources

Name	Description	Schema
bags <i>optional</i>	Map of Bag resources with Baggage Entity Identifier (Unique Bag Identifier) as key	< string, Bag > map
correlationBagsGroupDcsPassenger <i>optional</i>	Map of CorrelationBagsGroupDcsPassenger with Baggage Group Identifier as key	< string, CorrelationBagsGroupDcsPassenger > map

Name	Description	Schema
correlationBagsGroupPnr <i>optional</i>	Map of CorrelationBagsGroupPnr with Baggage Group Identifier as key	< string, CorrelationBagsGroupPnr > map
excessBaggageCharges <i>optional</i>	Map of Excess Baggage Charge resources with Excess Baggage Charge Identifier as key	< string, ExcessBaggageCharge > map

InfrastructureLocation

Full location details of the DCS agent/device.

Name	Description	Schema
airportCode <i>optional</i>	IATA three-digit airport code (exclusive with cityCode) Example : "LHR"	string
areaCode <i>optional</i>	Category of the location Example : "CKI"	string
buildingId <i>optional</i>	Building identifier - non verified or regulated (exclusive with terminalId) Example : "1"	string
cityCode <i>optional</i>	IATA three-digit metro area code (exclusive with airportCode) Example : "LON"	string
description <i>optional</i>	Admin user defined non structured free-flow text Example : "LHR TERM-2E"	string
identifier <i>optional</i>	Identifier of the closer location / zone Example : "1"	string
terminalId <i>optional</i>	Terminal identifier as in appendix of the SSM manual (exclusive with buildingId) Example : "2E"	string

Meta

Technical information related to the feed

Name	Description	Schema
triggerEventLog <i>optional</i>	Information related to the initial event that triggered the process	EventLog
version <i>optional</i>	Version of the JSON feed produced Example : "2.1.0"	enum (2.1.0)

PatchOperation

A single JSON Patch operation as defined by RFC 6902 (see <https://tools.ietf.org/html/rfc6902>)

Name	Description	Schema
from <i>optional</i>	A JSON Pointer as defined by RFC 6901 (see https://tools.ietf.org/html/rfc6901)	string
op <i>required</i>	The operation to be performed	enum (add, remove, replace, move, copy, test)
path <i>required</i>	A JSON Pointer as defined by RFC 6901 (see https://tools.ietf.org/html/rfc6901)	string
value <i>optional</i>	The value to be used within the operations	object

Price

This structure provides price details related to a product or a services during quotation for offers or selling transaction. The amount can be represented as a string or as numeric value for computation and detailed currency decimal position to prevent issue with rounding methods.

Name	Description	Schema
currency <i>optional</i>	the currency code of the price calculated Example : "EUR"	string
total <i>optional</i>	the monetary value calculated Example : "75.0"	string

QualifiedFreeText

Specific type to convey a list of string for specific information type

Name	Description	Schema
lang <i>optional</i>	The language of this free text. See RFC 5646. Note that this field is currently not populated. It is reserved for future use. Example : "fr-FR"	string
status <i>optional</i>	The status of the free text. Note that this field is currently not populated. It is reserved for future use. Example : "ACTIVE"	string
text <i>optional</i>	Free Text Example : "Authorised by Admin"	string

Relationship

Name	Description	Schema
href <i>optional</i>	The URI of the related resource Example : "https://airlines.api.amadeus.com/v2/departure-control/processed-dcs-passengers/2401CA5500003431"	string (uri)
id <i>optional</i>		string
methods <i>optional</i>	Accepted Methods	< enum (GET) > array
ref <i>optional</i>	The reference to the related resource if this latter exists in the same document Example : "included/correlationBagsGroupDcsPassenger/AA42BA1395020102"	string
type <i>optional</i>	The type of the related resource Example : "dcs-passenger"	string
version <i>optional</i>	Only populated for correlated resources defined in Dictionaries Example : "1"	string

Relationships

Name	Schema
collection <i>optional</i>	< Relationship > array

Service

Service representation. Can be used for SSR/SK/OSI elements within PNR.

Name	Description	Schema
code <i>optional</i>	This code is used to identify the service type Maximal length : 4 Example : "GOLF"	string
description <i>optional</i>	This field is used to describe the service free text Example : "Golf Bag"	string
id <i>optional</i>	Service Item identifier Example : "1000000000BC2107"	string

Name	Description	Schema
statusCode <i>optional</i>	Information about the status of the service HK - Confirmed HL - Waitlist UN - Unable to confirm not operating UC - Unable to confirm HX - Have Cancelled NO - No action taken Example : "HK"	string
subType <i>optional</i>	This field is used to indicate if we are dealing with an SSR/SK/OSI element Example : "SPECIAL_SERVICE_REQUEST"	enum (SPECIAL_SERVICE_R EQUEST, SPECIAL_KEYWORD, OTHER_SERVICE_INF ORMATION, MANUAL_AUXILIARY _SEGMENT)

SpecialBagHandling

Support bag handling information that can change from one leg to another (should the baggage be delivered at aircraft, ...) and the kind of good that is transported.

Name	Description	Schema
freeText <i>optional</i>	Holds any details for the attribute Example : "Broken Handle"	string
id <i>optional</i>	Special Bag Handling Identifier Example : "GOLF"	string

Name	Description	Schema
label <i>optional</i>	Example : "COURIER"	enum (GROUP, GROUND_TRANSPORT, FRAGILE, DUPLICATE_TAG, DIPLOMATIC_COURIER, DANGEROUS_GOODS, DELIVERED_AT_AIRCRAFT, CREW, COURIER, ROUTING_UPDATE, TOUR, UNACCOMPANIED, VIP, REROUTED, RUSH, SHORT_CONNECTION, JUMP, MISHANDLED, PRIORITY, RELOAD, HAJJ, HOTEL_VOUCHER, HEAVY, IRREGULAR_OPERATION, WEIGHT_REJECT)
service <i>optional</i>		Service

TimeLocationTrackingLog

Details about the last location where the Bag was tracked by DCS system.

Name	Description	Schema
deviceId <i>optional</i>	tracking device Example : "AF5FA7A4"	string
deviceUser <i>optional</i>	the agent's sign in who last tracked Example : "116554"	string
localDateTime <i>optional</i>	Last tracked date and time in ISO 8601 format Example : "2018-10-30T16:43"	string

Name	Description	Schema
logSource <i>optional</i>	channel how last tracked Example : "KIOSK"	enum (EXTERNAL_DCS, CRYPTIC, JFE, KIOSK, MOBILE_PHONE, SMS, TELEPHONE, WEB, AIRLINE_AGENT, GROUND_HANDLING _AGENT, AUTO_CHECK_IN, AUTO_BAG_DROP, LOUNGE_ACCESS, BRS_SCANNER, WIRELESS_HANDHE LD_BOARDING, EXTERNAL_FRONTEN D, BAGGAGE_SORTATIO N_SYSTEM, BAGGAGE_RECONCIL IATION_SYSTEM)
trackedLocation <i>optional</i>		InfrastructureLocation

User

The user that initiated/performed the change in case of user initiated events

Name	Description	Schema
id <i>optional</i>	Identifier of the User Example : "3355KJ"	string
officeId <i>optional</i>	Office Id of the User. Defaulted to "LON1A0955" in case of DCS system initiated actions Example : "FRALH04SS"	string
workstation <i>optional</i>		Workstation

Warning

Name	Description	Schema
code <i>required</i>	A machine-readable error code from the Canned Messages table, that will enable the API Consumers code to handle this type of error	integer

Name	Description	Schema
detail <i>optional</i>	An easy-to-read explanation specific to this occurrence of the problem. It should give the API consumer an idea of what went wrong and how to recover from it. Like the title, this field's value can be localized.	string
documentation <i>optional</i>	A link to a web page or file with further documentation to help the API consumer resolve this error	string (url)
source <i>optional</i>		ErrorSource
title <i>required</i>	An error title from the Canned Messages table with a 1:1 correspondence to the error code. This may be localized	string

Weight

An object representing weight and unit.

Name	Description	Schema
unit <i>optional</i>	The unit of measurement used for the weight value. Example : "KILOGRAMS"	enum (KILOGRAMS, POUNDS)
value <i>optional</i>	Defines the weight value without decimal position. Example : 125	integer

Workstation

Workstation details from where the change was done

Name	Description	Schema
fullLocation <i>optional</i>		InfrastructureLocation
id <i>optional</i>	Identifier of the Workstation in format 'qualifier - address' Example : "J-04SS"	string

Security

basicAuth

HTTP Basic Authentication. Works over **HTTP** and **HTTPS**

Type : basic