

Dynamic Intelligence Hub

DCS Passenger Open Api Specification

Table of Contents

Dynamic Intelligence Hub API and Data Models - DCS Passenger	1
Overview	2
Version information	2
URI scheme	2
Consumes	2
Produces	2
Paths	3
DCS Passenger Data Push	3
DCS Passenger Correlations Data Push	16
Retrieve DCS Passenger by ID (UCI)	21
Definitions	23
AcceptanceDelivery	23
Address	25
AirTravelDocument	25
AssociatedPassengerSegments	26
BoardingDelivery	27
BoardingPassPrint	27
ChargeableServiceDocument	28
Comment	28
CommentDelivery	29
Compensation	29
CompensationAuthorization	30
CompensationReason	30
CompensationVoucher	31
Contact	31
CorrelatedDataDcsPassengerBagsGroup	32
CorrelatedDataDcsPassengerEmd	32
CorrelatedDataDcsPassengerInventory	33
CorrelatedDataDcsPassengerPnr	33
CorrelatedDataDcsPassengerSchedule	34
CorrelatedDataDcsPassengerTicket	34
CorrelatedDcsPassengerBagsGroupLegData	34
CorrelatedDcsPassengerLegInventoryData	35
CorrelatedDcsPassengerLegScheduleData	35
CorrelationData	35
CorrelationDcsPassengerBagsGroup	36
CorrelationDcsPassengerEmd	36
CorrelationDcsPassengerInventory	37

CorrelationDcsPassengerPnr	37
CorrelationDcsPassengerSchedule	38
CorrelationDcsPassengerTicket	38
CorrelationReferences	38
Coupon	39
DcsPassenger	41
DcsPassengerApiData	42
DcsPassengerApiResponse	45
DcsPassengerCorrelationsPush	45
DcsPassengerPush	45
Dictionaries	46
DisruptionState	47
Error	47
ErrorSource	48
Errors	48
EventLog	48
Events	49
FlightEndPoint	50
FlightSegment	50
FlightTransfer	51
FrequentFlyer	53
IdentityDocument	53
IncludedResources	55
InfrastructureLocation	56
InputSource	57
LegDelivery	57
Meta	58
Methods	59
Name	59
Onload	59
OnloadEdit	59
OperatingFlight	60
PassengerSegmentDisruption	60
PatchOperation	60
Phone	61
PriceCategory	61
Regrade	61
RegulatoryChecks	64
RegulatoryComment	64
RegulatoryDocument	65
RegulatoryProgram	66

RegulatoryStatus	66
Relationship	67
Relationships	68
RevenueIntegrityAssessment	68
RevenueIntegrityCheck	69
RevenueIntegrityComment	69
Seat	70
SeatingDelivery	70
SegmentDelivery	71
Service	73
ServiceDescription	75
ServiceProvider	75
Staff	75
Stakeholder	76
Tier	77
TimeLocationTrackingLog	77
Traveler	78
User	79
Waiver	80
Warning	80
WorkStation	80
Security	82
basicAuth	82

Dynamic Intelligence Hub API and Data Models - DCS Passenger

Overview

This document describes the OpenAPI for: 1. GET for DCS Passenger data 2. Data models for the information pushed out by Amadeus for DCS Passenger

Version information

Version : 2.2.0

URI scheme

Host : airlines.api.amadeus.com

BasePath : /v2

Schemes : HTTPS

Consumes

- `application/json`

Produces

- `application/vnd.amadeus+json`

Paths

DCS Passenger Data Push

POST /departure-control/dcs-passenger-feed

Description

Model for the DCS Passenger data push feed. Please be aware this is NOT a POST API, rather this explains the format of the data pushed out by Amadeus.

Responses

HTTP Code	Schema
200	DcsPassengerPush

Tags

- Data Push Models

Example HTTP response

Response 200

```
{
  "meta" : {
    "triggerEventLog" : {
      "id" : "46541dsfsSDRWFS54"
    },
    "version" : "2.2.0"
  },
  "lastModification" : {
    "dateTime" : "2015-10-05T10:00:00.000Z",
    "triggerEventName" : "Customer Acceptance",
    "user" : {
      "id" : "USR0001",
      "officeID" : "NCE6X08AA",
      "workStation" : {
        "id" : "A/LHR/T/2/CKI/1/1",
        "fullLocation" : {
          "airportCode" : "LHR",
          "cityCode" : "LON",
          "terminalId" : "2E",
          "buildingId" : "1",
          "areaCode" : "CKI",
          "identifier" : "1",
```

```

        "description" : "LHR TERM-2E"
    }
}
},
"processedDcsPassenger" : {
    "type" : "dcs-passenger",
    "id" : "2501ADE000000001",
    "etag" : 1602876919851,
    "segmentDeliveries" : [ {
        "id" : "2401CA55000030ID",
        "type" : "segment-delivery",
        "uniqueCustomerIdentifier" : "2501ADE000000001",
        "segment" : {
            "departure" : {
                "iataCode" : "LHR",
                "at" : "2018-01-11"
            },
            "arrival" : {
                "iataCode" : "SIN"
            },
            "number" : "1234",
            "carrierCode" : "7X",
            "suffix" : "B",
            "class" : "Q",
            "cabin" : "M",
            "statusCode" : "HK",
            "operating" : {
                "carrierCode" : "6X",
                "number" : "17"
            }
        },
    },
    "recordLocator" : "PC3XYV",
    "dcsProductType" : "ACTIVE_SYNCHRONISED",
    "legDeliveries" : [ {
        "id" : "LHR",
        "departure" : {
            "iataCode" : "LHR",
            "at" : "2018-09-14T10:10:00"
        },
        "arrival" : {
            "iataCode" : "SIN",
            "at" : "2018-09-14T10:10:00"
        },
        "operatingFlight" : {
            "carrierCode" : "6X",
            "number" : "741",
            "suffix" : "A"
        },
        "travelCabinCode" : "C",
        "acceptance" : {

```



```

    "securityNumber" : "098",
    "status" : "CAC",
    "acceptanceType" : "PRM",
    "isAdvanceAccepted" : false,
    "isForceAccepted" : true,
    "forceAcceptanceReason" : "emergency travel request",
    "isFrozen" : false,
    "channel" : "JFE",
    "physicalAcceptanceLocation" : "BMD",
    "standbyReason" : "CSAX",
    "cancellationReason" : "Customer Unwell"
  },
  "seating" : {
    "seatStatus" : "NOT_GUARANTEED",
    "seatProductStatus" : "HL",
    "isChargeableSeat" : true,
    "seat" : {
      "number" : "12A",
      "characteristicsCodes" : [ "CH", "W" ]
    },
    "chargeableSeat" : {
      "chargeableServiceId" : "10000007896346C1",
      "priceCategory" : {
        "code" : "C",
        "subCode" : "99Y"
      },
      "chargeableServiceDocument" : {
        "documentType" : "EMD",
        "number" : "1728200002469",
        "status" : "REFUNDED"
      },
      "paymentStatus" : "WAIVED",
      "isIssuanceRequired" : true,
      "waiver" : {
        "authoriser" : "Check-in agent",
        "reasonCode" : "Technical",
        "reasonText" : "A technical issue occurred at check-in. Agent had to
waive the chargeable service"
      }
    },
    "seatPreferences" : {
      "number" : "12A",
      "characteristicsCodes" : [ "CH", "W" ]
    }
  },
  "boarding" : {
    "error" : "Unpaid excess exists",
    "warning" : "Customer is CBBG",
    "boardingStatus" : "NBD",
    "boardingPassPrint" : {
      "status" : "PPT",

```

```

    "channel" : "JFE"
  },
  "boardingZone" : "B",
  "trackingLog" : {
    "deviceId" : "AF5FA7A4",
    "referenceDeviceType" : "SELF_BOARDING_DEVICE",
    "deviceUser" : 116554,
    "utcDateTime" : "2018-10-23T22:00:00.000+0000",
    "localDateTime" : "2018-10-23T22:00:00.000+0000",
    "logSource" : "MOBILE_PHONE",
    "trackedLocation" : {
      "airportCode" : "LHR",
      "cityCode" : "LON",
      "terminalId" : "2E",
      "buildingId" : 1,
      "areaCode" : "CKI",
      "identifier" : 1,
      "description" : "CDG TERM-2F LGE TRCK2 Lounge 2F2"
    }
  },
  "onload" : {
    "status" : "OK",
    "priority" : "W31",
    "cabinCode" : "C",
    "edit" : {
      "reasonCode" : "TO_REMAIN",
      "reasonFreeText" : "Keep in same cabin",
      "cabinCode" : "Y"
    }
  },
  "regradeDelivered" : {
    "status" : "ACTIONED",
    "priority" : "W31",
    "cabinCode" : "C",
    "reason" : "OVER_SOLD_CURRENT_FLIGHT",
    "reasonFreeText" : "Oversold current flight",
    "authoriserReference" : "AU0123",
    "regradeType" : "REMAIN_FORCE"
  },
  "regradeProposed" : {
    "status" : "ACTIONED",
    "priority" : "W31",
    "cabinCode" : "C",
    "reason" : "OVER_SOLD_CURRENT_FLIGHT",
    "reasonFreeText" : "Oversold current flight",
    "authoriserReference" : "AU0123",
    "direction" : "RGH",
    "regradeType" : "REMAIN_FORCE"
  },
  "regulatoryChecks" : [ {

```

```

    "id" : 1255477819
  }, {
    "regulatoryProgram" : {
      "name" : "AQQ",
      "countryCode" : "USA"
    },
    "statuses" : [ {
      "id" : 1255477820
    }, {
      "statusType" : "SECURITY",
      "statusCode" : "S",
      "override" : {
        "commentType" : "OVERRIDE_AUTHORIZER",
        "description" : "Authorized by Mr. John Smith"
      },
      "message" : {
        "commentType" : "SPECIAL_INSTRUCTIONS",
        "code" : 8517,
        "description" : "TIMEOUT"
      },
      "isVerifiedId" : false
    } ],
    "assesmentTime" : "2018-07-31T11:23:20Z"
  } ],
  "comments" : [ {
    "id" : "1000000000810D86",
    "text" : "One cabin bag to be taken on the hold",
    "priority" : "HIGH",
    "usage" : "AT_BP_REPRINT",
    "delivery" : {
      "status" : "DELIVERED"
    }
  } ],
  "compensations" : [ {
    "id" : null,
    "categoryDescription" : "ACCOMODATION",
    "reason" : {
      "code" : "FDD",
      "label" : "Flight Delayed on Departure"
    },
    "authorisation" : {
      "authorizer" : "1100AC",
      "status" : "AUTHORIZED",
      "date" : "2018-08-19T00:00:00.000+0000",
      "quantity" : 2
    },
    "vouchers" : [ {
      "id" : 9423690240,
      "voucherType" : "GTP",
      "form" : "Cash",
      "description" : "Meal Voucher",

```

```

        "comment" : "Creating meal voucher for customer John SMITH on AC123",
        "status" : "ACTIVE",
        "printStatus" : "PRINTED",
        "isReprintable" : true,
        "providerCode" : "AC"
    } ]
} ]
},
"associatedPassengerSegments" : {
    "onwardId" : "2401CA55000030ID",
    "infantId" : "2401CA5500003JID",
    "cbbgId" : "2401CA5500003CID",
    "exstId" : "2401CA5500003EID",
    "informativeOnwardId" : "2401CA5500003CID",
    "acceptedOnwardId" : "2401CA5500003CID",
    "alternateOnwardId" : "2401CA5500003CID",
    "misconnectedOnwardId" : "2401CA5500003CID",
    "tciOnwardId" : "2401CA5500003CID",
    "disruptedOnwardId" : "2401CA5500003CID"
},
"staff" : {
    "idType" : "N2",
    "transfersDuringDay" : 2,
    "transferDays" : 3
},
"frequentFlyer" : [ {
    "id" : "FF0001",
    "frequentFlyerNumber" : "6X090807061234",
    "serviceCode" : "FQTU",
    "applicableAirlineCode" : "6X",
    "confirmationStatus" : "K",
    "airlineLevel" : {
        "name" : "Gold",
        "code" : "G",
        "priorityCode" : 1,
        "companyCode" : "6X"
    },
    "allianceLevel" : {
        "name" : "Gold",
        "code" : "G",
        "priorityCode" : 1,
        "companyCode" : "6X"
    },
    "isValidationOverriden" : false
} ],
"associatedAirTravelDocuments" : [ {
    "id" : "1234556677812",
    "documentType" : "ETICKET",
    "primaryDocumentNumber" : "1234556677812",
    "conjunctiveDocumentNumbers" : [ "1234556677812", "1234556677813" ],
    "validatingCarrierCode" : "6X",

```

```

    "associationStatus" : "ASSOCIATED",
    "blacklistCategory" : "Fraud",
    "airCoupons" : [ {
      "id" : "1",
      "number" : 1,
      "documentNumber" : "1234556677812"
    } ]
  }, {
    "id" : "1234556677567",
    "documentType" : "EMD",
    "primaryDocumentNumber" : "1234556677567",
    "conjunctiveDocumentNumbers" : [ "1234556677567" ],
    "airCoupons" : [ {
      "id" : "1",
      "number" : 1,
      "documentNumber" : "1234556677567"
    } ],
    "status" : "CHECKED_IN",
    "associatedDocuments" : [ {
      "id" : "1234556677812",
      "documentType" : "EMD",
      "primaryDocumentNumber" : "1234556677812",
      "conjunctiveDocumentNumbers" : [ "1234556677812" ],
      "airCoupons" : [ {
        "id" : "1",
        "number" : 1,
        "documentNumber" : "1234556677812"
      } ]
    } ],
    "reasonForIssuance" : {
      "code" : "C",
      "subCode" : "99Y",
      "rfiscDescription" : "BAG- EXCESS PC ALLOWANCE"
    }
  } ],
  "previousTicket" : {
    "id" : "1234556677568",
    "documentType" : "ETICKET",
    "primaryDocumentNumber" : "1234556677568"
  },
  "services" : [ {
    "code" : "DOCA",
    "address" : {
      "category" : "DESTINATION",
      "lines" : [ "101, JENYA" ],
      "postalCode" : "560068",
      "countryCode" : "IN",
      "cityName" : "BLR",
      "stateCode" : "KAR"
    }
  }
], {

```

```

    "id" : "1000000000BC2107",
    "chargeableServiceId" : "10000007896346C1",
    "code" : "BIKE",
    "subType" : "SSR",
    "priceCategory" : {
      "code" : "C",
      "subCode" : "99Y"
    },
    "status" : "MCF",
    "NIP" : 1,
    "isSubjectToQuota" : true,
    "quotaCode" : "SSRQ123",
    "chargeableServiceDocument" : {
      "documentType" : "EMD",
      "number" : "1728200002469",
      "status" : "REFUNDED"
    },
    "paymentStatus" : "WAIVED",
    "isIssuanceRequired" : true,
    "waiver" : {
      "authoriser" : "Check-in agent",
      "reasonCode" : "Technical",
      "reasonText" : "A technical issue occurred at check-in. Agent had to waive
the chargeable service"
    }
  } ],
  "contacts" : [ {
    "id" : "762636429911",
    "addresseeName" : {
      "firstName" : "John",
      "lastName" : "SMITH"
    },
    "phone" : {
      "text" : "001461415588511"
    },
    "purpose" : [ "EMERGENCY" ],
    "isDeclined" : false
  } ],
  "regulatoryDocuments" : [ {
    "id" : "100000001AFC111A",
    "document" : {
      "documentType" : "PASSPORT",
      "number" : "GB12345",
      "issuanceDate" : "2018-08-15",
      "expiryDate" : "2025-08-15",
      "effectiveDate" : "2018-09-15",
      "issuanceCountry" : "GB",
      "issuanceLocation" : "LONDON",
      "gender" : "MALE",
      "name" : {
        "firstName" : "John",

```

```

        "lastName" : "SMITH",
        "title" : "Mr"
    },
    "validToDate" : "2019-08-14",
    "validity" : {
        "numberOfDays" : 100,
        "numberOfDaysUsed" : 15,
        "numberOfDaysPerEntry" : 60,
        "numberOfEntriesPermitted" : 10,
        "numberOfEntriesUsed" : 9
    }
},
"recordedDocumentType" : "VVV",
"countryOfRegistration" : "USA",
"countryOfPortOfEntry" : "PRI",
"presentedAtPort" : "SJU",
"isCarried" : false,
"isBearer" : true,
"inputSource" : {
    "entryMethod" : "SWIPED",
    "isSwipeOverriden" : false,
    "isOCR" : false,
    "isHistorical" : false,
    "scannedMethod" : "MACHINE_READABLE"
},
"usedFor" : "ARRIVAL"
} ],
"segmentLinks" : [ {
    "id" : "127317712391918",
    "collection" : [ {
        "id" : "2112C1E05536001D",
        "type" : "segment-delivery"
    } ]
} ],
"revenueIntegrity" : {
    "checks" : [ {
        "id" : "6521372834902",
        "checkType" : "CUSTOMER_TYPE_CHECK",
        "status" : "PASSED"
    } ],
    "comments" : [ {
        "id" : "1255477819",
        "commentType" : "PASSED_CUSTOMER_TYPES",
        "description" : "STUDENT1"
    } ]
},
"passengerDisruption" : {
    "originalDestination" : "LHR",
    "productState" : {
        "status" : "DISRUPTED",
        "reason" : "Disrupted From Flight"
    }
}

```

```

    }
  },
  "nationality" : "GRC",
  "volunteerDowngrade" : "NOT_ASKED",
  "volunteerDeniedBoarding" : "VOLUNTEERED"
} ],
"passenger" : {
  "name" : {
    "firstName" : "John",
    "lastName" : "Smith",
    "title" : "Mr"
  },
  "age" : "45",
  "dateOfBirth" : "1980-01-30",
  "gender" : "MALE",
  "flightPassengerType" : "ADULT",
  "contacts" : [ {
    "id" : "762636429911",
    "email" : {
      "address" : "contact@contactstandard.xyz"
    },
    "language" : "EN",
    "purpose" : [ "STANDARD" ],
    "carrierCode" : "6X"
  }, {
    "id" : "126511237759",
    "phone" : {
      "text" : "00446716216622"
    },
    "language" : "FR",
    "purpose" : [ "STANDARD" ],
    "carrierCode" : "6X"
  }, {
    "id" : "992873466222",
    "addresseeName" : {
      "firstName" : "John",
      "lastName" : "SMITH"
    },
    "phone" : {
      "text" : "001461415588511"
    },
    "purpose" : [ "EMERGENCY" ],
    "carrierCode" : "6X",
    "isDeclined" : false
  } ]
},
"recordLocator" : "PXT607",
"cprFeedType" : "MARKETING_SBR",
"isSamePhysicalCustomer" : false,
"isSystemMarkedSPC" : false,
"isMasterRecord" : true,

```



```

"groupName" : "Star Travels",
"staff" : {
  "id" : "ST0793",
  "companyCode" : "WT",
  "companyName" : "World Travellers",
  "relationshipType" : "Self",
  "category" : "BOOKABLE",
  "joiningDate" : "2011-02-28",
  "retirementDate" : "2011-02-28"
},
"flightTransfers" : [ {
  "id" : 12385310,
  "subType" : "TRAVEL_READY_REACCOMODATION",
  "disruptionTransferReason" : "FLIGHT_DIVERTED",
  "dcsTransferStatus" : "COMPLETED",
  "dataTransferStatus" : "SUCCESS",
  "fromSegments" : {
    "departure" : {
      "iataCode" : "LHR",
      "at" : "2018-01-11"
    },
    "arrival" : {
      "iataCode" : "SIN"
    },
    "number" : "1567",
    "carrierCode" : "7X",
    "suffix" : "B",
    "operating" : {
      "carrierCode" : "6X",
      "number" : "17"
    }
  },
  "toSegments" : {
    "departure" : {
      "iataCode" : "LHR",
      "at" : "2018-01-11"
    },
    "arrival" : {
      "iataCode" : "SIN"
    },
    "number" : "3234",
    "carrierCode" : "7X",
    "suffix" : "B",
    "operating" : {
      "carrierCode" : "6X",
      "number" : "18"
    }
  }
} ],
"frequentFlyer" : [ {
  "id" : "FF0001",

```

```

    "frequentFlyerNumber" : "6X090807061234",
    "serviceCode" : "FQTU",
    "applicableAirlineCode" : "6X",
    "confirmationStatus" : "K",
    "airlineLevel" : {
      "name" : "Gold",
      "code" : "G",
      "priorityCode" : 1,
      "companyCode" : "6X"
    },
    "allianceLevel" : {
      "name" : "Gold",
      "code" : "G",
      "priorityCode" : 1,
      "companyCode" : "6X"
    },
    "isValidationOverriden" : false
  } ],
  "services" : [ {
    "code" : "DOCA",
    "address" : {
      "category" : "DESTINATION",
      "lines" : [ "203, LAA APARTMENTS" ],
      "postalCode" : "560068",
      "countryCode" : "IN",
      "cityName" : "BLR",
      "stateCode" : "KAR"
    },
    "serviceProvider" : {
      "code" : "6X"
    }
  } ],
  "passengerLinks" : [ {
    "id" : "176126316661283",
    "collection" : [ {
      "id" : "2002CAE00036002D",
      "type" : "dcs-passenger",
      "href" : "https://airlines.api.amadeus.com/v2/departure-control/processed-dcs-passengers/2721234567890726",
      "methods" : [ "GET" ]
    } ]
  } ],
  "regulatoryDocuments" : [ {
    "id" : "100000001AFC111B",
    "document" : {
      "documentType" : "PASSPORT",
      "number" : "GB12345",
      "issuanceDate" : "2018-08-15",
      "expiryDate" : "2025-08-15",
      "effectiveDate" : "2018-09-15",
      "issuanceCountry" : "GB",

```

```

        "issuanceLocation" : "GBR",
        "gender" : "MALE",
        "name" : {
            "firstName" : "John",
            "lastName" : "SMITH",
            "title" : "Mr"
        },
        "validToDate" : "2019-08-14",
        "validity" : {
            "numberOfDays" : 100,
            "numberOfDaysUsed" : 15,
            "numberOfDaysPerEntry" : 60,
            "numberOfEntriesPermitted" : 10,
            "numberOfEntriesUsed" : 9
        }
    },
    "recordedDocumentType" : "VVV",
    "countryOfRegistration" : "USA",
    "countryOfPortOfEntry" : "PRI",
    "presentedAtPort" : "SJU",
    "isCarried" : false,
    "isBearer" : true,
    "inputSource" : {
        "entryMethod" : "SWIPED",
        "isSwipeOverriden" : false,
        "isOCR" : false,
        "isHistorical" : false,
        "scannedMethod" : "MACHINE_READABLE"
    },
    "validForCarrier" : "6X",
    "usedFor" : "ARRIVAL"
} ]
},
"previousRecord" : [ {
    "op" : "replace",
    "path" : "/segmentDeliveries/0/dcsProductType",
    "value" : "ACTIVE_NOT_SYNCHRONISED"
} ],
"events" : {
    "recordDomain" : "DCSPASSENGER",
    "recordId" : "2501ADE000000001",
    "originFeedTimeStamp" : "2018-10-24T14:19:00Z",
    "events" : [ {
        "origin" : "COMPARISON",
        "eventType" : "UPDATED",
        "currentPath" : "/segmentDeliveries/0/dcsProductType",
        "previousPath" : "/segmentDeliveries/0/dcsProductType"
    } ]
}
}

```

DCS Passenger Correlations Data Push

POST /departure-control/dcs-passengers-correlations-feed

Description

Model for the DCS Passenger correlations data push feed. Please be aware this is NOT a POST API, rather this explains the format of the data pushed out by Amadeus.

Responses

HTTP Code	Schema
200	DcsPassengerCorrelationsPush

Tags

- Data Push Models

Example HTTP response

Response 200

```
{
  "meta" : {
    "triggerEventLog" : {
      "id" : "46541dsfsSDRWFS54"
    },
    "version" : "2.2.0"
  },
  "dcsPassengerCorrelations" : {
    "correlationDcsPassengerTicket" : {
      "dcsPassengerId" : "2501ADE000000001",
      "ticketIds" : [ "1258767935960-2018-08-21", "1258767935961-2018-08-21" ],
      "correlatedData" : {
        "1258767935960-2018-08-21" : [ {
          "dcsPassengerSegmentDeliveryId" : "2101CA1100003431",
          "ticketCouponId" : "1258767935960-2018-08-21-1"
        }, {
          "dcsPassengerSegmentDeliveryId" : "2202DA1200003432",
          "ticketCouponId" : "1258767935960-2018-08-21-2"
        } ],
        "1258767935961-2018-08-21" : [ {
          "dcsPassengerSegmentDeliveryId" : "2303BA1300003433",
          "ticketCouponId" : "1258767935961-2018-08-21-1"
        } ]
      }
    }
  }
},
```

```

"correlationDcsPassengerPnr" : {
  "dcsPassengerId" : "2501ADE000000001",
  "pnrIds" : [ "ORY4NY-2018-10-19", "KBR849-2018-09-17" ],
  "correlatedData" : {
    "ORY4NY-2018-10-19" : [ {
      "dcsPassengerSegmentDeliveryId" : "2404CA5500003411",
      "pnrTravelerId" : "ORY4NY-2018-10-19-PT-1",
      "pnrAirSegmentId" : "ORY4NY-2018-10-19-ST-1"
    }, {
      "dcsPassengerSegmentDeliveryId" : "2504CA5500003422",
      "pnrTravelerId" : "ORY4NY-2018-10-19-PT-1",
      "pnrAirSegmentId" : "ORY4NY-2018-10-19-ST-2"
    } ],
    "KBR849-2018-09-17" : [ {
      "dcsPassengerSegmentDeliveryId" : "2604CA5500003433",
      "pnrTravelerId" : "KBR849-2018-09-17-PT-2",
      "pnrAirSegmentId" : "KBR849-2018-09-17-ST-1"
    } ]
  }
},
"correlationDcsPassengerSchedule" : {
  "dcsPassengerId" : "2501ADE000000001",
  "scheduleIds" : [ "6X-5641-2018-10-05", "6X-7861-2018-10-06" ],
  "correlatedData" : {
    "6X-5641-2018-10-05" : [ {
      "dcsPassengerSegmentDeliveryId" : "2404CA5500003411",
      "scheduleSegmentId" : "2018-10-05-LHR-MAD",
      "schedulePartnershipFlightId" : "7X-9623-2018-10-05",
      "correlatedLegs" : [ {
        "dcsPassengerLegDeliveryId" : "LHR",
        "scheduleLegId" : "LHR-CDG"
      }, {
        "dcsPassengerLegDeliveryId" : "CDG",
        "scheduleLegId" : "CDG-MAD"
      } ]
    } ],
    "6X-7861-2018-10-06" : [ {
      "dcsPassengerSegmentDeliveryId" : "2504CA5500003422",
      "scheduleSegmentId" : "2018-10-06-MAD-LHR",
      "correlatedLegs" : [ {
        "dcsPassengerLegDeliveryId" : "MAD",
        "scheduleLegId" : "MAD-LHR"
      } ]
    } ]
  }
},
"correlationDcsPassengerEmd" : {
  "dcsPassengerId" : "2501ADE000000001",
  "emdIds" : [ "1721234567891-2018-05-15", "1721234567892-2018-05-15" ],
  "correlatedData" : {
    "1721234567891-2018-05-15" : [ {

```

```

      "dcsPassengerSegmentDeliveryId" : "2404CA5500003411",
      "dcsPassengerServiceId" : "1111000000BC2107",
      "emdCouponId" : "1721234567891-2018-05-15-1"
    }, {
      "dcsPassengerSegmentDeliveryId" : "2505CA5500003422",
      "dcsPassengerServiceId" : "1222000000BC2107",
      "emdCouponId" : "1721234567891-2018-05-15-2"
    } ],
    "1721234567892-2018-05-15" : [ {
      "dcsPassengerSegmentDeliveryId" : "2505CA5500003422",
      "dcsPassengerServiceId" : "1333000000BC2107",
      "emdCouponId" : "1721234567892-2018-05-15-1"
    } ]
  }
},
"correlationDcsPassengerInventory" : {
  "dcsPassengerId" : "2501ADE000000001",
  "inventoryIds" : [ "6X-5641-2018-10-05", "6X-7861-2018-10-06" ],
  "correlatedData" : {
    "6X-5641-2018-10-05" : [ {
      "dcsPassengerSegmentDeliveryId" : "2101ADE000000001",
      "inventorySegmentId" : "2018-10-05-LHR-MAD",
      "inventoryPartnershipFlightId" : "7X-9623-2018-10-05",
      "correlatedLegs" : [ {
        "dcsPassengerLegDeliveryId" : "LHR",
        "inventoryLegId" : "LHR-CDG"
      }, {
        "dcsPassengerLegDeliveryId" : "CDG",
        "inventoryLegId" : "CDG-MAD"
      } ]
    } ],
    "6X-7861-2018-10-06" : [ {
      "dcsPassengerSegmentDeliveryId" : "2201ADE000000002",
      "inventorySegmentId" : "2018-10-06-MAD-LHR",
      "correlatedLegs" : [ {
        "dcsPassengerLegDeliveryId" : "MAD",
        "inventoryLegId" : "MAD-LHR"
      } ]
    } ]
  }
},
"correlationDcsPassengerBagsGroup" : {
  "dcsPassengerId" : "2501ADE000000001",
  "bagsGroupIds" : [ "AA42BA1395020102", "AA41BA1395020413" ],
  "correlatedData" : {
    "AA42BA1395020102" : [ {
      "dcsPassengerSegmentDeliveryId" : "2202DA1200003432",
      "correlatedLegs" : [ {
        "dcsPassengerLegDeliveryId" : "LHR",
        "bagId" : "1101CA1100003431",
        "bagLegDeliveryId" : "LHR"
      } ]
    } ]
  }
}

```

```

    } ]
  } ],
  "AA41BA1395020413" : [ {
    "dcsPassengerSegmentDeliveryId" : "2202DA1200003433",
    "correlatedLegs" : [ {
      "dcsPassengerLegDeliveryId" : "LHR",
      "bagId" : "1101CA1100003432",
      "bagLegDeliveryId" : "LHR"
    } ]
  } ]
},
"dictionary" : {
  "dcsPassengers" : {
    "2501ADE000000001" : {
      "type" : "dcs-passenger",
      "id" : "2501ADE000000001",
      "version" : "1",
      "href" : "https://airlines.api.amadeus.com/v2/departure-control/processed-dcs-passengers/2501ADE000000001"
    }
  },
  "tickets" : {
    "1258767935960-2018-08-21" : {
      "type" : "ticket",
      "id" : "1258767935960-2018-08-21",
      "version" : "1",
      "href" : "https://airlines.api.amadeus.com/v2/ticketing/processed-tickets/1258767935960-2018-08-21"
    },
    "1258767935961-2018-08-21" : {
      "type" : "ticket",
      "id" : "1258767935961-2018-08-21",
      "version" : "1",
      "href" : "https://airlines.api.amadeus.com/v2/ticketing/processed-tickets/1258767935961-2018-08-21"
    }
  },
  "emds" : {
    "1721234567891-2018-05-15" : {
      "type" : "emd",
      "id" : "1721234567891-2018-05-15",
      "version" : "1",
      "href" : "https://airlines.api.amadeus.com/v2/ticketing/processed-emds/1721234567891-2018-05-15"
    },
    "1721234567892-2018-05-15" : {
      "type" : "emd",
      "id" : "1721234567892-2018-05-15",
      "version" : "1",
      "href" : "https://airlines.api.amadeus.com/v2/ticketing/processed-

```

```

emds/1721234567892-2018-05-15"
    },
    "pnrs" : {
      "ORY4NY-2018-10-19" : {
        "type" : "pnr",
        "id" : "ORY4NY-2018-10-19",
        "version" : "1",
        "href" : "https://airlines.api.amadeus.com/v2/reservation/processed-
pnrs/ORY4NY-2018-10-19"
      },
      "KBR849-2018-09-17" : {
        "type" : "pnr",
        "id" : "KBR849-2018-09-17",
        "version" : "1",
        "href" : "https://airlines.api.amadeus.com/v2/reservation/processed-
pnrs/KBR849-2018-09-17"
      }
    },
    "scheduleDatedFlights" : {
      "6X-5641-2018-10-05" : {
        "type" : "dated-flight",
        "id" : "6X-5641-2018-10-05",
        "version" : "1536835243",
        "href" : "https://airlines.api.amadeus.com/v2/schedule/processed-flights/6X-
5641-2018-10-05"
      },
      "6X-7861-2018-10-06" : {
        "type" : "dated-flight",
        "id" : "6X-7861-2018-10-06",
        "version" : "1536835243",
        "href" : "https://airlines.api.amadeus.com/v2/schedule/processed-flights/6X-
7861-2018-10-06"
      }
    },
    "inventoryDatedFlights" : {
      "6X-5641-2018-10-05" : {
        "type" : "dated-flight",
        "id" : "6X-5641-2018-10-05",
        "version" : "1536835243",
        "href" : "https://airlines.api.amadeus.com/v2/inventory/processed-
flights/6X-5641-2018-10-05"
      },
      "6X-7861-2018-10-06" : {
        "type" : "dated-flight",
        "id" : "6X-7861-2018-10-06",
        "version" : "1536835243",
        "href" : "https://airlines.api.amadeus.com/v2/inventory/processed-
flights/6X-7861-2018-10-06"
      }
    }
  },

```



```

    "bagsGroups" : {
      "AA42BA1395020102" : {
        "type" : "bags-group",
        "id" : "AA42BA1395020102",
        "version" : "1",
        "href" : "https://airlines.api.amadeus.com/v2/departure-control/processed-bags-groups/AA42BA1395020102"
      },
      "AA41BA1395020413" : {
        "type" : "bags-group",
        "id" : "AA41BA1395020413",
        "version" : "1",
        "href" : "https://airlines.api.amadeus.com/v2/departure-control/processed-bags-groups/AA41BA1395020413"
      }
    }
  },
  "events" : {
    "recordDomain" : "DCSPASSENGER_TICKET",
    "recordId" : "2501ADE000000001",
    "originFeedTimeStamp" : "2018-10-24T14:19:00Z",
    "events" : [ {
      "origin" : "COMPARISON",
      "eventType" : "UPDATED",
      "currentPath" : "/correlationDcsPassengerTicket/correlatedData/0142345676472-2018-09-20/1/ticketCouponId",
      "previousPath" : "/correlationDcsPassengerTicket/correlatedData/0142345676472-2018-09-20/1/ticketCouponId"
    } ]
  }
}

```

Retrieve DCS Passenger by ID (UCI)

GET /departure-control/processed-dcs-passengers/{id}

Description

Returns the DCS Passenger Record for the ID provided

Parameters

Type	Name	Description	Schema
Path	id <i>required</i>	Identifier of a DCS Passenger Record	string

Responses

HTTP Code	Description	Schema
200	Successful operation	DcsPassengerApiResponse
401	Unauthorized. Missing credentials in header request.	Errors
403	Forbidden. Authorization refused for the credentials provided.	Errors
404	Passenger with the requested id was not found.	Errors
500	Internal server error / Technical	Errors

Tags

- [DcsPassengerAPIs](#)

Security

Type	Name
basic	basicAuth

Definitions

AcceptanceDelivery

Information related to passenger acceptance (checkin) for a flight leg at the departure control system

Name	Description	Schema
acceptanceType <i>optional</i>	Acceptance Type Example : "PRIMARY"	enum (PRIMARY, OUTBOUND_EXTERNAL_TCI, INBOUND_EXTERNAL_TCI, INTERNAL_TCI, PENDING_IATCI_PROCESS)
cancellationReason <i>optional</i>	Reason provided by agent when an acceptance is cancelled Example : "Customer Unwell"	string
channel <i>optional</i>	Acceptance Channel indicator Example : "JFE"	enum (EXTERNAL_DCS, CRYPTIC, JFE, KIOSK, MOBILE_PHONE, SMS, TELEPHONE, WEB, EXTERNAL_FRONTEND)
forceAcceptanceReason <i>optional</i>	Acceptance Reason - given by the DCS agent Example : "emergency travel request"	string
isAdvanceAccepted <i>optional</i>	Advance acceptance indicator - set when passenger is accepted without being present (this can happen for group bookings) Example : false	boolean
isForceAccepted <i>optional</i>	Force Acceptance indicator - indicator set when the agents override some checks like suitability check Example : true	boolean
isFrozen <i>optional</i>	Freeze indicator - set by the agent to prevent acceptance status to be reassessed during onload Example : false	boolean

Name	Description	Schema
physicalAcceptanceLocation <i>optional</i>	Physical Acceptance location(ADM - Airline Administration, ATO - Airport Travel Office, BAG - Baggage, BDP - Bag Drop Podium, BMD - Boarding Monitor Desk, BOF - Airport Back Office, CAR - Cargo, CAT - Catering, CID - Check In Desk, CKI - Airport Check In, CRW - Crew, CSD - CustomerServiceDesk, CTO - CityTravelOffice, ENG - Engineering, GTE - Gate, LCO - Load Control, LGE - Lounge, MVC - Movement Control, OFF - Off Airport, PSF - Passenger Services Facilities, RAM - RAM, REG - Regulatory Authorities, RMP - Ramp, SEC - Security, SSH - Self Service Helpdesk, SSK - Self Service Kiosk, TAG - Travel Agency, TBD - Test Bed, TKT - Ticket Desk, TRA - Transfer Desk, TRN - Training, ROM - RoamingAgent) Example : "BMD"	string
securityNumber <i>optional</i>	Passenger security number Example : "098"	string
standbyReason <i>optional</i>	Standby Reason - given by the DCS agent or by the system Example : "FULL_BLOCKED_SPACE"	enum (FULL_BLOCKED_SPACE, NO_ADJACENT_SEAT_FOR_EXTRA_SEAT_OR_CABIN_BAG, AIRCRAFT_CHANGE, OFFLOADED_BY_ONLOAD, PET_IN_CABIN_QUOTA_EXCEEDED, MANUAL_OFFLOAD, CAPACITY_EXCEEDED, UNSUITABLE_SEAT, CAPACITY_NOT_AVAILABLE, CHECKIN_CAPACITY_NOT_AVAILABLE, WEIGHT_RESTRICTION, ACCEPTANCE_LIMITS_REACHED, ANIMAL_IN_HOLD_QUOTA_EXCEEDED, OTHER)
status <i>optional</i>	Passenger acceptance status Example : "ACCEPTED"	enum (ACCEPTED, STANDBY, NOT_ACCEPTED, NOT_TRAVELLING)

Address

Address information

Name	Description	Schema
category <i>optional</i>	Category of the address element Example : "BUSINESS"	enum (BUSINESS, PERSONAL, DESTINATION, HOME, OTHER)
cityName <i>optional</i>	Full city name Example : "Dublin"	string
countryCode <i>optional</i>	ISO 3166-1 country code Example : "GRC"	string
lines <i>optional</i>	Line 1 = Street address, Line 2 = Apartment, suite, unit, building, floor, etc Example : ["2203 Brooklyn", "Floor 2"]	< string > array
postalCode <i>optional</i>	The postal code Example : "74130"	string
stateCode <i>optional</i>	State code (two character standard IATA state code) Example : "VA"	string

AirTravelDocument

Air travel document details like ETKT, EMD

Name	Description	Schema
airCoupons <i>optional</i>	List of coupons	< Coupon > array
associatedDocuments <i>optional</i>		< AirTravelDocument > array
associationStatus <i>optional</i>	Association status Example : "ASSOCIATED"	enum (ASSOCIATED, MULTIPLE_ASSOCIATED, E_STAPLE, DISASSOCIATED, ETS_UNAVAILABLE, ETICKET_NOT_FOUND, UNMATCHED, UNASSOCIATED)
blacklistCategory <i>optional</i>	Blacklist category Example : "Fraud"	string

Name	Description	Schema
conjunctiveDocumentNumbers <i>optional</i>		< string > array
documentType <i>optional</i>	Document type Example : "ETICKET"	enum (ETICKET, EMD, EMD_STANDALONE, EMD_ASSOCIATED, PAPER_TICKET, PAPER_MD, VIRTUAL_TICKET, VIRTUAL_MD, TICKETLESS_DOCUMENT, TICKET, MD)
id <i>optional</i>	Unique identifier for Air Travel Document Example : "1234556677812"	string
primaryDocumentNumber <i>optional</i>	ticket primary number or emd primary number Example : "1234556677812"	string
validatingCarrierCode <i>optional</i>	ticket validating carrier code Example : "6X"	string

AssociatedPassengerSegments

Other segment identifiers associated with the current one via relationship like CBBG, EXST, infant, in/outbound journey

Name	Description	Schema
acceptedOnwardId <i>optional</i>	Recorded at time of acceptance Example : "2401CA5500003CID"	string
alternateOnwardId <i>optional</i>	Other possible onward Segment Example : "2401CA5500003CID"	string
cbbgId <i>optional</i>	The CBBG passenger segment identifier Example : "2401CA5500003CID"	string
disruptedOnwardId <i>optional</i>	Created when an informativeOnwardId is removed Example : "2401CA5500003CID"	string
exstId <i>optional</i>	The EXST passenger segment identifier Example : "2401CA5500003EID"	string

Name	Description	Schema
infantId <i>optional</i>	The infant passenger segment identifier Example : "2401CA5500003JID"	string
informativeOnwardId <i>optional</i>	Basic computation at time of CPR creation Example : "2401CA5500003CID"	string
misconnectedOnwardId <i>optional</i>	Similar to disruptedOnwardId but also includes misconnections Example : "2401CA5500003CID"	string
onwardId <i>optional</i>	The onward passenger segment identifier Example : "2401CA5500003OID"	string
tciOnwardId <i>optional</i>	IATCI SegmentDelivery id Example : "2401CA5500003CID"	string

BoardingDelivery

Boarding details at leg level

Name	Description	Schema
boardingPassPrint <i>optional</i>		BoardingPassPrint
boardingStatus <i>optional</i>	Passenger boarding status Example : "BOARDED"	enum (NOT_BOARDED, BOARDED, BOARDED_BY_SWIPE)
boardingZone <i>optional</i>	The group in which the passenger is meant to board Example : "B"	string
error <i>optional</i>	Error that is communicated to an agent during boarding Example : "Unpaid excess exists."	string
trackingLog <i>optional</i>	All information related to track the boarding process of a passenger	TimeLocationTrackingLog
warning <i>optional</i>	Warning that is communicated to an agent during boarding Example : "Customer is CBBG."	string

BoardingPassPrint

Boarding pass print details at leg level

Name	Description	Schema
channel <i>optional</i>	Boardingpass Print Channel Example : "JFE"	enum (AIRLINE_AGENT, AUTO_BAG_DROP, AUTO_CHECK_IN, BRS_SCANNER, CRYPTIC, CUSTOMER_PORTAL, EMAIL, EXTERNAL_DCS, EXTERNAL_FRONTEND, GROUND_HANDLING_AGENT, JFE, KIOSK, LOUNGE_ACCESS, MOBILE_PHONE, SMS, TELEPHONE, WEB, WIRELESS_HANDHELD_BOARDING, NONE)
status <i>optional</i>	Boarding pass print status Example : "NEEDS_PRINTING"	enum (NEEDS_PRINTING, PRINTED, NOT_PRINTED, RE_PRINTED)

ChargeableServiceDocument

A reference to either MCO or EMD document by number and type. A chargeable service document represents the document issued as a result of the chargeable service payment. The document status stores the state of the document as either refunded, voided, or flown (used).

Name	Description	Schema
documentType <i>optional</i>	The type of document for the chargeable service. Either MCO for Miscellaneous Charge Order or EMD for Electronic Miscellaneous Document Example : "EMD"	enum (EMD, MCO)
number <i>optional</i>	The document number Example : "1728200002469"	string
status <i>optional</i>	The status of the document Example : "REFUNDED"	enum (VOIDED, REFUNDED, FLOWN)

Comment

Comment as added by DCS agent and details like priority, usage etc.

Name	Description	Schema
delivery <i>optional</i>		CommentDelivery
id <i>optional</i>	the identifier of the comment Example : "1000000000810D86"	string
priority <i>optional</i>	the priority of the comment - HIGH : comment priority is high - MEDIUM: comment priority is medium - NORMAL : comment priority is normal - NOT_APPLICABLE : no priority applicable Example : "HIGH"	enum (HIGH, MEDIUM, NORMAL, NOT_APPLICABLE)
text <i>optional</i>	the text of the comment (ASCII) Example : "One cabin bag to be taken on the hold"	string
usage <i>optional</i>	when to action on the comment - AT_BP_REPRINT : At boarding pass re-print - AT_CHECKIN : At check-in - AT_GATE : At the gate - LIST_ONLY : List only - NEXT_TIME : Next time - PRINT_ON_BP : Print on boarding pass - PRINT_ON_ONBOARD_SERVICE_LIST : Print on onboard service list - PRINT_ON_ONBOARD_SERVICE_LIST_AND_BP : Print on onboard service list and boarding pass - BAGGAGE: Baggage - NORMAL: Normal - CABIN: Cabin Example : "AT_BP_REPRINT"	enum (AT_BP_REPRINT, AT_CHECKIN, AT_GATE, LIST_ONLY, NEXT_TIME, PRINT_ON_BP, PRINT_ON_ONBOARD_SERVICE_LIST, PRINT_ON_ONBOARD_SERVICE_LIST_AND_BP, BAGGAGE, NORMAL, CABIN)

CommentDelivery

Comment delivery status details

Name	Description	Schema
status <i>optional</i>	delivery status of the comment - DELIVERED : comment is delivered - NOT_DELIVERED : comment is not delivered - UNABLE_TO_DELIVER: delivery attempted, but unsuccessful Example : "DELIVERED"	enum (DELIVERED, NOT_DELIVERED, UNABLE_TO_DELIVER)

Compensation

Compensations information

Name	Description	Schema
authorisation <i>optional</i>	All the information related to the authorization for this compensation	CompensationAuthorization

Name	Description	Schema
categoryDescription <i>optional</i>	Compensation category description (as defined by airlines in BZR) Example : "CATERING"	enum (CATERING, ACCOMMODATION, AIRLINE_CASH_CREDIT, GENERAL_SERVICE_VOUCHER, PHYSICAL_TOKENS, MONETARY_COMPENSATION, TRANSPORTATION)
id <i>optional</i>	Unique identifier for this compensation - contains unique product identifier, departure port and compensation reason code Example : "2002EAE0001C08B4-LAX-MCT"	string
reason <i>optional</i>	Reason or event that caused this compensation	CompensationReason
vouchers <i>optional</i>	List of vouchers issued for this compensation	< CompensationVoucher > array

CompensationAuthorization

All the information related to the authorization for this compensation

Name	Description	Schema
authorizer <i>optional</i>	User id of the agent who authorized the compensation before issuance Example : "1100AC"	string
date <i>optional</i>	Date on which the compensation has been authorized Example : "2018-08-19"	string
quantity <i>optional</i>	Count of vouchers authorized for compensation. The default value is 1 Example : "2"	string
status <i>optional</i>	Authorization status	enum (AUTHORIZED, NOT_AUTHORIZED, ISSUED, NOT_NEEDED, PENDING_PRINT, SUITABLE)

CompensationReason

Reason or event that caused this compensation

Name	Description	Schema
code <i>optional</i>	Compensation reason code ((as defined by airlines in BZR) Example : "FDD"	string
label <i>optional</i>	Provides a brief description of the reason which caused the compensation (as defined by airlines in BZR) Example : "Flight Delayed on Departure"	string

CompensationVoucher

Voucher related information for a compensation

Name	Description	Schema
comment <i>optional</i>	free text entered by agent during issuance of this voucher Example : "Creating meal voucher for customer John SMITH on AC123"	string
description <i>optional</i>	Provides a short description of the compensation Example : "Meal Voucher"	string
id <i>optional</i>	Unique identifier of the voucher Example : "9423690240"	string
isReprintable <i>optional</i>	Denotes if the voucher can be printed more than once	boolean
printStatus <i>optional</i>	Denotes voucher printing status	enum (PRINTED, NOT_PRINTED, NEEDS_PRINTING, NOT_PRINTABLE)
providerCode <i>optional</i>	Code for the airline which provided this voucher Example : "AC"	string
status <i>optional</i>	Status of the voucher	enum (ACTIVE, EXPIRED, USED, CANCELLED, ISSUED, PENDING_FOR_PRINTING, ELIGIBLE, PENDING, REQUESTED)
voucherType <i>optional</i>	This field provides the type of voucher e.g. GTP, MCO Example : "GTP"	string

Contact

Represents Contact information like Phone or Email for a Passenger. Also used to represent an Emergency Contact for the Passenger.

Name	Description	Schema
address <i>optional</i>		Address
addresseeName <i>optional</i>		Name
carrierCode <i>optional</i>	The airline code to which the Contact is associated Example : "6X"	string
id <i>optional</i>	the identifier of the contact Example : "126511237759"	string
isDeclined <i>optional</i>	Whether the Passenger declined to provide Contact information Example : false	boolean
phone <i>optional</i>		Phone
purpose <i>optional</i>	The purpose for which this contact is to be used Example : ["STANDARD", "NOTIFICATION"]	< enum (STANDARD, NOTIFICATION, EMERGENCY) > array

CorrelatedDataDcsPassengerBagsGroup

Set of data field identifiers defining the correlation between DCS Baggage and DCS Passenger

Name	Description	Schema
correlatedLegs <i>optional</i>		< CorrelatedDcsPassengerBagsGroupLegData > array
dcsPassengerSegmentDeliveryId <i>optional</i>	Example : "2401CA5500003431"	string

CorrelatedDataDcsPassengerEmd

Set of data field identifiers defining the correlation between DCS Passenger Service, SegmentDeliveryId (populated only for segment level services) and EMD Coupon

Name	Description	Schema
dcsPassengerSegmentDeliveryId <i>optional</i>	Example : "2401CA5500003431"	string

Name	Description	Schema
dcsPassengerServiceId <i>optional</i>	Example : "1000000000BC2107"	string
emdCouponId <i>optional</i>	Example : "1721234567891-2018-05-15-1"	string

CorrelatedDataDcsPassengerInventory

Set of data field identifiers defining the correlation between a DCS Passenger Segment Delivery (UPI) and a Inventory Dated Flight record (inventoryPartnershipFlightId represents codeshare)

Name	Description	Schema
correlatedLegs <i>optional</i>		< CorrelatedDcsPassengerLegInventoryData > array
dcsPassengerSegmentDeliveryId <i>optional</i>	Example : "2401CA5500003431"	string
inventoryPartnershipFlightId <i>optional</i>	codeshare details Example : "7X-9623-2018-10-05"	string
inventorySegmentId <i>optional</i>	Example : "2018-10-05-LHR-CDG"	string

CorrelatedDataDcsPassengerPnr

Set of data field identifiers defining the correlation between a DCS Passenger Segment Delivery (UPI) and a PNR Traveler, Air Segment pair.

Name	Description	Schema
dcsPassengerSegmentDeliveryId <i>optional</i>	Example : "2401CA5500003431"	string
pnrAirSegmentId <i>optional</i>	Example : "KBR849-2018-09-17-ST-6"	string

Name	Description	Schema
pnrTravelerId <i>optional</i>	Example : "KBR849-2018-09-17-PT-1"	string

CorrelatedDataDcsPassengerSchedule

Set of data field identifiers defining the correlation between a DCS Passenger Segment Delivery (UPI) and a Schedule Dated Flight record (schedulePartnershipFlightId represents codeshare)

Name	Description	Schema
correlatedLegs <i>optional</i>		< CorrelatedDcsPassengerLegScheduleData > array
dcsPassengerSegmentDeliveryId <i>optional</i>	Example : "2401CA5500003431"	string
schedulePartnershipFlightId <i>optional</i>	Example : "7X-9623-2018-10-05"	string
scheduleSegmentId <i>optional</i>	Example : "2018-10-05-LHR-CDG"	string

CorrelatedDataDcsPassengerTicket

Set of data field identifiers defining the correlation between DCS Passenger Segment and Ticket Coupon

Name	Description	Schema
dcsPassengerSegmentDeliveryId <i>optional</i>	Example : "2401CA5500003431"	string
ticketCouponId <i>optional</i>	Example : "1258767935960-2018-08-21-3"	string

CorrelatedDcsPassengerBagsGroupLegData

Set of data field identifiers defining "leg level" correlation between DcsBaggage and DcsPassenger

Name	Description	Schema
bagId <i>optional</i>	Example : "1101CA1100003431"	string
bagLegDeliveryId <i>optional</i>	Example : "LHR"	string
dcsPassengerLegDeliveryId <i>optional</i>	Example : "LHR"	string

CorrelatedDcsPassengerLegInventoryData

Set of data field identifiers defining the correlation between a DCS Passenger Leg Delivery and a Inventory Dated Flight Leg

Name	Description	Schema
dcsPassengerLegDeliveryId <i>optional</i>	Example : "LHR"	string
inventoryLegId <i>optional</i>	Example : "LHR-CDG"	string

CorrelatedDcsPassengerLegScheduleData

Set of data field identifiers defining the correlation between a DCS Passenger Leg Delivery and a Schedule Dated Flight Leg

Name	Description	Schema
dcsPassengerLegDeliveryId <i>optional</i>	Example : "LHR"	string
scheduleLegId <i>optional</i>	Example : "LHR-CDG"	string

CorrelationData

The Correlation structures have information about how the DCS Passenger correlates with other domains: Schedule, Inventory, PNR, Ticket, EMD, Bag.

Name	Schema
correlationDcsPassengerBagsGroup <i>optional</i>	CorrelationDcsPassengerBagsGroup
correlationDcsPassengerEmd <i>optional</i>	CorrelationDcsPassengerEmd
correlationDcsPassengerInventory <i>optional</i>	CorrelationDcsPassengerInventory
correlationDcsPassengerPnr <i>optional</i>	CorrelationDcsPassengerPnr
correlationDcsPassengerSchedule <i>optional</i>	CorrelationDcsPassengerSchedule
correlationDcsPassengerTicket <i>optional</i>	CorrelationDcsPassengerTicket
dictionaries <i>optional</i>	Dictionaries

CorrelationDcsPassengerBagsGroup

Structure of correlation between a DCS Passenger and DCS Bag Group.

Name	Description	Schema
bagsGroupIds <i>optional</i>	DCS Bag groups correlated with the DCS Passenger Example : ["AA42BA1395020102", "AA41BA1395020413"]	< string > array
correlatedData <i>optional</i>		< string, < CorrelatedDataDcsPassengerBagsGroup > array > map
dcsPassengerId <i>optional</i>	DCS Passenger identifier Example : "2501ADE000000001"	string

CorrelationDcsPassengerEmd

Structure of correlation between a DCS Passenger and an Electronic Miscellaneous Document. Only associated EMDs (EMD-A's) are considered for correlation.

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataDcsPassengerEmd > array > map

Name	Description	Schema
dcsPassengerId <i>optional</i>	current DCS Passenger - UCI Example : "2501ADE000000001"	string
emdIds <i>optional</i>	Identifying EMD(s) correlated with the DCS Passenger - item format is EMD number + issuance date Example : ["1721234567891-2018-05-15", "1721234567892-2018-05-15"]	< string > array

CorrelationDcsPassengerInventory

Structure of correlation between a DCS Passenger and a Inventory Dated Flight record.

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataDcsPassengerInventory > array > map
dcsPassengerId <i>optional</i>	current DCS Passenger - UCI Example : "2501ADE000000001"	string
inventoryIds <i>optional</i>	Identifying the inventory flight(s) correlated with the current DCS Passenger - item is dated flight ID i.e. carrier code + flight number + flight date + operational suffix Example : ["6X-5641-2018-10-05", "6X-7861-2018-10-06"]	< string > array

CorrelationDcsPassengerPnr

Structure of correlation between a DCS Passenger and a Passenger Name Record.

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataDcsPassengerPnr > array > map
dcsPassengerId <i>optional</i>	current DCS Passenger - UCI Example : "2501ADE000000001"	string
pnrIds <i>optional</i>	Identifying the PNR(s) correlated with the current DCS Passenger - item format is record locator + creation date Example : ["ORY4NY-2018-10-19", "KBR849-2018-09-17"]	< string > array

CorrelationDcsPassengerSchedule

Structure of correlation between a DCS Passenger and a Schedule Dated Flight record.

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataDcsPassengerSchedule > array > map
dcsPassengerId <i>optional</i>	current DCS Passenger - UCI Example : "2501ADE000000001"	string
scheduleIds <i>optional</i>	Identifying the schedule flight(s) correlated with the current DCS Passenger - item is dated flight ID i.e. carrier code + flight number + flight date + operational suffix Example : ["6X-5641-2018-10-05", "6X-7861-2018-10-06"]	< string > array

CorrelationDcsPassengerTicket

Structure of correlation between a DCS Passenger and a Ticket. Only associated tickets are considered for correlation.

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataDcsPassengerTicket > array > map
dcsPassengerId <i>optional</i>	current DCS Passenger - UCI Example : "2501ADE000000001"	string
ticketIds <i>optional</i>	Identifying ticket(s) correlated with the DCS Passenger - item format is primary ticket number + issuance date Example : ["1258767935960-2018-08-21", "1258767935961-2018-08-21"]	< string > array

CorrelationReferences

Name	Description	Schema
correlations <i>optional</i>	Correlation structures are defined in the included section. This section provides links for all the correlation structures pertaining to the current DCS Passenger. Example : { "dcsPassengerTicket" : { "type" : "correlationDcsPassengerTicket", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerTicket/2501ADE000000001" }, "dcsPassengerEmd" : { "type" : "correlationDcsPassengerEmd", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerEmd/2501ADE000000001" }, "dcsPassengerPnr" : { "type" : "correlationDcsPassengerPnr", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerPnr/2501ADE000000001" }, "dcsPassengerSchedule" : { "type" : "correlationDcsPassengerSchedule", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerSchedule/2501ADE000000001" }, "dcsPassengerInventory" : { "type" : "correlationDcsPassengerInventory", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerInventory/2501ADE000000001" }, "dcsPassengerBagsGroup" : { "type" : "correlationDcsPassengerBagsGroup", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerBagsGroup/2501ADE000000001" } }	correlations

correlations

Name	Schema
dcsPassengerBagsGroup <i>optional</i>	Relationship
dcsPassengerEmd <i>optional</i>	Relationship
dcsPassengerInventory <i>optional</i>	Relationship
dcsPassengerPnr <i>optional</i>	Relationship
dcsPassengerSchedule <i>optional</i>	Relationship
dcsPassengerTicket <i>optional</i>	Relationship

Coupon

A coupon refers to a product that has been issued in the current travel document. In tickets, a coupon refers to a flight segment. An airline ticket portion that bears the notion "good for passage", or in the case of an electronic ticket, the electronic coupon indicates the particular places a

passenger is entitled to be carried. A single ticket/document number may contain up to 4 segments. For tickets/documents with more than 4 segments of travel, a conjunction ticket is required to continue the itinerary. In EMDs, a coupon can refer to an ancillary service, an upgrade, a fee or a residual value. * soldSegment - Original image of the coupon at first issuance of the document. * currentSegment - Latest image of the coupon in case it has been subject to modification[s] such as revalidation e.g. change of flight number. * usedSegment - Image of the coupon when its status is considered as used i.e. either flown [B] or exchanged [E], refunded [RF], printed [PR], print exchange [PE], converted to Flight Interruption Manifest [G], closed [CLO], voided [V].

Name	Description	Schema
associatedDocuments <i>optional</i>		< AirTravelDocument > array
documentNumber <i>optional</i>	Document number for the Segment Example : "1234556677813"	string
id <i>optional</i>	identifier of the coupon Example : "1"	string
number <i>optional</i>	The coupon number inside this conjunctive ticket should be the same as the coupon number in case of non conjunctive tickets (from 1 to 4). Example : 1	integer
reasonForIssuance <i>optional</i>		PriceCategory
status <i>optional</i>	coupon operational status. It follows IATA PADIS Code List for data element 4405 Example : "CHECKED_IN"	enum (EXCHANGED, FLOWN, EXCHANGED_TO_FIM, COUPON_NOTIFICATION, OPEN_FOR_USE, REFUNDED, SUSPENDED, VOID, CLOSED, REVOKED, PRINTED, PRINT_EXCHANGE, NOT_AVAILABLE, BOARDED, IRREGULAR_OPERATIONS, ORIGINAL_ISSUE, CHECKED_IN, AIRPORT_CONTROL, UNAVAILABLE, REFUND_TAXES_AND_FEES, PAPER_TICKET)

DcsPassenger

The DcsPassenger data comprises of hierarchical structure: - Passenger level data like name, services etc. - Segment level data array for all the flights the passenger has booked containing flight details, tickets, services, regulatory documents etc. - Leg level data array for all the flight legs for a booked flight segment containing details for acceptance, seating, boarding etc.

Name	Description	Schema
cprFeedType <i>optional</i>	RES-DCS Synchronisation Feed type as setup on DCS business rule Example : "MARKETING_SBR"	enum (MARKETING_SBR, MARKETING_PNL, OPERATING_SBR, OPERATING_PNL, BLOCKSPACE, NO_FEED, DUAL)
etag <i>optional</i>	Sequence number for comparison between two passenger images and to know which one is the latest. Example : "1602876919851"	string
flightTransfers <i>optional</i>	All activities related to flight transfer for a particular passenger	< FlightTransfer > array
frequentFlyer <i>optional</i>	Passenger associated Frequent flyer information	< FrequentFlyer > array
groupName <i>optional</i>	Name of the group booking Example : "Star Travels"	string
id <i>optional</i>	Unique Customer Identifier (UCI) Example : "2501ADE000000001"	string
isMasterRecord <i>optional</i>	Indicates whether this record is the master of the merged records ("id" has UCI of the master CPR) Example : true	boolean
isSamePhysicalCustomer <i>optional</i>	Same Physical Customer(passenger) Indicator - indicates if the records are merged on DCS side manually by DCS agent. This can happen when passenger books flights in separate PNRs and requests DCS agent to through-checkin on all flights. Agent has to manually merge the CPRs. Please note that "segmentDeliveries" contains data for all merged records. "id" has UCI of the master CPR and the individual UCI for child CPR is within corresponding segmentDelivery. Example : false	boolean
isSystemMarkedSPC <i>optional</i>	Indicates if the merge of the record was done by the DCS system automatically (not manually by agent) This typically happens in codeshare scenarios. Example : false	boolean
passenger <i>optional</i>		Traveler

Name	Description	Schema
passengerLinks <i>optional</i>	References to other passengers linked (travelling together) with this one	< Relationships > array
recordLocator <i>optional</i>	Record Locator (Unique booking reference number) Example : "PXT607"	string
regulatoryDocuments <i>optional</i>	Passenger associated Regulatory documents	< RegulatoryDocument > array
segmentDeliveries <i>optional</i>	Booked Segment level details	< SegmentDelivery > array
services <i>optional</i>	Passenger associated services Example : [{ "code" : "DOCA", "address" : { "category" : "DESTINATION", "lines" : ["203, LAA APARTMENTS"], "postalCode" : "560068", "countryCode" : "IN", "cityName" : "BLR", "stateCode" : "KAR" }, "serviceProvider": { "code" : "6X" } }]	< Service > array
staff <i>optional</i>		Staff
type <i>optional</i>	resource name Example : "dcs-passenger"	enum (dcs-passenger)

DcsPassengerApiData

Polymorphism : Composition

Name	Description	Schema
correlations <i>optional</i>	Correlation structures are defined in the included section. This section provides links for all the correlation structures pertaining to the current DCS Passenger. Example : { "dcsPassengerTicket" : { "type" : "correlationDcsPassengerTicket", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerTicket/2501ADE000000001" }, "dcsPassengerEmd" : { "type" : "correlationDcsPassengerEmd", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerEmd/2501ADE000000001" }, "dcsPassengerPnr" : { "type" : "correlationDcsPassengerPnr", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerPnr/2501ADE000000001" }, "dcsPassengerSchedule" : { "type" : "correlationDcsPassengerSchedule", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerSchedule/2501ADE000000001" }, "dcsPassengerInventory" : { "type" : "correlationDcsPassengerInventory", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerInventory/2501ADE000000001" }, "dcsPassengerBagsGroup" : { "type" : "correlationDcsPassengerBagsGroup", "id" : "2501ADE000000001", "ref" : "included/correlationDcsPassengerBagsGroup/2501ADE000000001" } }	correlations
cprFeedType <i>optional</i>	RES-DCS Synchronisation Feed type as setup on DCS business rule Example : "MARKETING_SBR"	enum (MARKETING_SBR, MARKETING_PNL, OPERATING_SBR, OPERATING_PNL, BLOCKSPACE, NO_FEED, DUAL)
etag <i>optional</i>	Sequence number for comparison between two passenger images and to know which one is the latest. Example : "1602876919851"	string
flightTransfers <i>optional</i>	All activities related to flight transfer for a particular passenger	< FlightTransfer > array
frequentFlyer <i>optional</i>	Passenger associated Frequent flyer information	< FrequentFlyer > array
groupName <i>optional</i>	Name of the group booking Example : "Star Travels"	string
id <i>optional</i>	Unique Customer Identifier (UCI) Example : "2501ADE000000001"	string
isMasterRecord <i>optional</i>	Indicates whether this record is the master of the merged records ("id" has UCI of the master CPR) Example : true	boolean

Name	Description	Schema
isSamePhysicalCustomer <i>optional</i>	Same Physical Customer(passenger) Indicator - indicates if the records are merged on DCS side manually by DCS agent. This can happen when passenger books flights in separate PNRs and requests DCS agent to through-checkin on all flights. Agent has to manually merge the CPRs. Please note that "segmentDeliveries" contains data for all merged records. "id" has UCI of the master CPR and the individual UCI for child CPR is within corresponding segmentDelivery. Example : false	boolean
isSystemMarkedSPC <i>optional</i>	Indicates if the merge of the record was done by the DCS system automatically (not manually by agent) This typically happens in codeshare scenarios. Example : false	boolean
passenger <i>optional</i>		Traveler
passengerLinks <i>optional</i>	References to other passengers linked (travelling together) with this one	< Relationships > array
recordLocator <i>optional</i>	Record Locator (Unique booking reference number) Example : "PXT607"	string
regulatoryDocuments <i>optional</i>	Passenger associated Regulatory documents	< RegulatoryDocument > array
segmentDeliveries <i>optional</i>	Booked Segment level details	< SegmentDelivery > array
services <i>optional</i>	Passenger associated services Example : [{ "code" : "DOCA", "address" : { "category" : "DESTINATION", "lines" : ["203, LAA APARTMENTS"], "postalCode" : "560068", "countryCode" : "IN", "cityName" : "BLR", "stateCode" : "KAR" }, "serviceProvider" : { "code" : "6X" } }]	< Service > array
staff <i>optional</i>		Staff
type <i>optional</i>	resource name Example : "dcs-passenger"	enum (dcs-passenger)

correlations

Name	Schema
dcsPassengerBagsGroup <i>optional</i>	Relationship

Name	Schema
dcsPassengerEmd <i>optional</i>	Relationship
dcsPassengerInventory <i>optional</i>	Relationship
dcsPassengerPnr <i>optional</i>	Relationship
dcsPassengerSchedule <i>optional</i>	Relationship
dcsPassengerTicket <i>optional</i>	Relationship

DcsPassengerApiResponse

Response of the API "Get DcsPassenger by ID" along with correlations data as included resources. The dictionaries structure has links to get various entities referenced via correlations.

Name	Schema
data <i>optional</i>	DcsPassengerApiData
dictionaries <i>optional</i>	Dictionaries
included <i>optional</i>	IncludedResources

DcsPassengerCorrelationsPush

The Online data push schema for DcsPassenger correlations with other domains and correlation events. It also contains meta data (technical details like version)

Name	Schema
dcsPassengerCorrelations <i>optional</i>	CorrelationData
events <i>optional</i>	Events
meta <i>optional</i>	Meta

DcsPassengerPush

The Online data push schema for DcsPassenger and events. The structure also contains: - meta data (technical details like version) - lastModification (information about originating DCS transaction) -

previousRecord (JSON patches to get to the previous version of DcsPassenger with respect to the current one)

Name	Description	Schema
events <i>optional</i>		Events
lastModification <i>optional</i>		EventLog
meta <i>optional</i>		Meta
previousRecord <i>optional</i>	List of JSON Patches as defined by RFC 6902 (see https://tools.ietf.org/html/rfc6902) to apply to processedDcsPassenger [latest DcsPassenger version] in order to obtain the actual JSON of the previous DcsPassenger version.	< PatchOperation > array
processedDcsPassenger <i>optional</i>		DcsPassenger

Dictionaries

Links to various entities referenced via correlations

Name	Description	Schema
bagsGroups <i>optional</i>	Set of key/value pairs with baggage group Id as key	< string, Relationship > map
dcsPassengers <i>optional</i>	Set of key/value pairs with dcsPassenger Id as key.	< string, Relationship > map
emds <i>optional</i>	Set of key/value pairs with emdId as key i.e. primary EMD number + issuance date - key example '1721234567891-2018-05-15'	< string, Relationship > map
inventoryDatedFlights <i>optional</i>	Set of key/value pairs with inventoryDatedFlightId as key i.e. carrier code + flight number + flight date + operational suffix - key example '6X-123-2018-10-05-A'	< string, Relationship > map
pnrs <i>optional</i>	Set of key/value pairs with pnrId as key i.e. record locator + creation date - key example 'ABCDEF-2018-05-15'	< string, Relationship > map
scheduleDatedFlights <i>optional</i>	Set of key/value pairs with scheduleDatedFlightId as key i.e. carrier code + flight number + flight date + operational suffix - key example '6X-123-2018-10-05-A'	< string, Relationship > map

Name	Description	Schema
tickets <i>optional</i>	Set of key/value pairs with ticketId as key i.e. primary ticket number + issuance date - key example '1721234567890-2018-05-15'	< string, Relationship > map

DisruptionState

Name	Description	Schema
reason <i>optional</i>	Process/Product disruption reason Example : "FLIGHT_CANCELLATION"	< enum (FLIGHT_CANCELLATION, FLIGHT_SUSPENDED, LEG_SUSPENDED, FLIGHT_DIVERSION, MANUAL_DISRUPTION, FLIGHT_DELAY, MISCONNECTION_INBOUND_DISRUPTION, MISCONNECTION_OUTBOUND_DISRUPTION, DISRUPTION_TRANSFER, DISRUPTED_FROM_FLIGHT) > array
status <i>optional</i>	Process/Product disruption status. - The Product Disruption state refers to the disruption state on this product. If the flight is cancelled, it will be 'DISRUPTED'. - When a passenger is transferred, the FROM and TO flights are linked; for example the passenger was transferred from 6X101/FRA/MUC to 6X103/FRA/MUC. 6X101 will have a Product Disruption state of 'DISRUPTED' before the transfer. After the transfer, the Product Disruption state of 6X103 will be 'NOT_DISRUPTED', and the Product disruption state of 6X101 will be 'WAS_DISRUPTED' (as 6X101 and 6X103 have the same offpoint the passenger is no longer disrupted). The Process Disruption state for 6X103 is the highest of the Product Disruption state of the 6X101 and the Product Disruption state of 6X103, which is 'WAS_DISRUPTED'. Example : "DISRUPTED"	enum (NOT_DISRUPTED, DISRUPTED, WAS_DISRUPTED)

Error

Name	Description	Schema
code <i>required</i>	A machine-readable error code from the Amadeus Canned Messages table, that will enable the API Consumers code to handle this type of error	integer
detail <i>optional</i>	An easy-to-read explanation specific to this occurrence of the problem. It should give the API consumer an idea of what went wrong and how to recover from it. Like the title, this field's value can be localized.	string
documentation <i>optional</i>	A link to a web page or file with further documentation to help the API consumer resolve this error	string (url)
source <i>optional</i>		ErrorSource
status <i>required</i>	The HTTP status code of this response. This is present only in terminal errors which cause an unsuccessful response. In the case of multiple errors, they must all have the same status.	integer
title <i>required</i>	An error title from the Canned Messages table with a 1:1 correspondence to the error code. This may be localized.	string

ErrorSource

Name	Description	Schema
example <i>optional</i>	A sample input to guide the user when resolving this issue	string
parameter <i>optional</i>	The key of the URI path or query parameter that caused the error	string
pointer <i>optional</i>	A JSON Pointer [RFC6901] to the associated entity in the request body that caused this error	string

Errors

Name	Schema
errors <i>optional</i>	< Error > array

EventLog

Details about the original event triggering the current datapush feed Used by Meta.triggerEventLog and DcsPassengerPush.lastModification

Name	Description	Schema
dateTime <i>optional</i>	UTC date & time Example : "2015-10-05T10:00:00Z"	string (date-time)
id <i>optional</i>	Identifier of the change Example : "46541dsfsSDRWF54"	string
triggerEventName <i>optional</i>	The name of the trigger event. - Meta.triggerEventLog Set to 'DATA_INIT' for initialization messages - DcsPassengerPush.lastModification Set in format "CCKXUQ - Cancel Acceptance" for DCS agent initiated actions and set to "1AINTERNAL" for DCS system initiated actions Example : "DATA_INIT"	string
user <i>optional</i>		User

Events

Structure of Dynamic Intelligence Hub functional events. It has information about what exactly changed in the current payload as compared to the previous version.

Name	Description	Schema
events <i>optional</i>	List of events that have been detected on the DCS Passenger document	< events > array
originFeedTimeStamp <i>optional</i>	Incoming DCS feed time stamp	string (datetime)
recordDomain <i>optional</i>	Functional domain of the record Example : "DCSPASSENGER"	string
recordId <i>optional</i>	Record identifier e.g. UCI Example : "2501ADE000000001"	string

events

Name	Description	Schema
currentPath <i>optional</i>	String containing the JSON Pointer (see IETF RFC6901) that points to the data referenced by the Event in the latest version of the entity. It is only applicable for CREATED and UPDATED events. Example : ""	string
eventType <i>optional</i>	In case of comparison events, type of operation notified by the event Example : "CREATED"	enum (CREATED, UPDATED, DELETED)

Name	Description	Schema
origin <i>optional</i>	Type of event e.g. 'COMPARISON' / 'TIME_INITIATED_EVENT' Example : "COMPARISON"	string
previousPath <i>optional</i>	String containing the JSON Pointer (see IETF RFC6901) that points to the data referenced by the Event in the previous version of the entity. It is only applicable for DELETED and UPDATED events. Example : ""	string

FlightEndPoint

Departure or arrival information

Name	Description	Schema
at <i>optional</i>	Local date and time in ISO 8601 format "yyyy-MM-dd'T'HH:mm:ss" or "yyyy-MM-dd"(e.g. 2017-02-10T20:40:00, 2017-02-14). Example : "2018-09-14T10:10:00"	string
iataCode <i>optional</i>	IATA Airport code Example : "JFK"	string

FlightSegment

Booked marketing flight segment details like flight number, cabin, class etc

Name	Description	Schema
arrival <i>optional</i>		FlightEndPoint
cabin <i>optional</i>	Booked cabin code Example : "M"	string
carrierCode <i>optional</i>	Carrier code Example : "6X"	string
class <i>optional</i>	Booking class Example : "Y"	string
departure <i>optional</i>		FlightEndPoint
duration <i>optional</i>	Flight duration Example : "9"	string
number <i>optional</i>	Flight number of the segment Example : "807"	string

Name	Description	Schema
operating <i>optional</i>		OperatingFlight
statusCode <i>optional</i>	Booking status of the segment Example : "HK"	string
suffix <i>optional</i>	Suffix Example : "A"	string

FlightTransfer

All activities related to flight transfer for a particular passenger

Name	Description	Schema
dataTransfer Status <i>optional</i>		enum (PENDING, ONGOING, SUCCESS, ERROR, REQUIRED, IGNORED, NOT_REQUIRED)
dcsTransferStatus <i>optional</i>		enum (REBOOKED_TO_EXT_SYSTEM, COMPLETED, FLIGHT_NOT_ACTIVE, CUSTOMER_DATA_TRANSFER_FAILED, VALIDATION_FAILED, REBOOKING_FAILED, IN_PROGRESS, REBOOKED, CUSTOMER_DATA_TRANSFER_ACCEPTANCE_FAILED, PNL_NOT_RECEIVED)

Name	Description	Schema
disruptionTransferReason <i>optional</i>		enum (FLIGHT_CANCELLED, FLIGHT_DELAYED, MISSED_CONNECTION, DENIED_BOARDING_OVERSALES, DENIED_BOARDING_CONFIGURATION_CHANGE, DENIED_BOARDING_PAYLOAD, FLIGHT_DIVERTED, OTHER)
fromSegments <i>optional</i>	Details of all the segments, from which the passenger have been disrupted/re-accommodated.	< FlightSegment > array
id <i>optional</i>	unique Reaccommodation id Example : "1000000001437D6D"	string
subType <i>optional</i>		enum (STANDBY_TRANSFER, BLOCKSPACE_PARTNER_MOVE, CUSTOMER_TRANSFER_PROCESS, FLOW_FORWARD, UPGRADE_BY_MILES, CUSTOMER_DATA_TRANSFER, CUSTOMER_OPERATIONAL_PROTECTION, STANDBY_UPGRADE_TRANSFER, PAYMENT_TRANSFER, AIRLINE Ancillary Services Upgrade, TRANSFER_REMAINING_CUSTOMERS, TRAVEL_READY_REACCOMMODATION)
toSegments <i>optional</i>	Details of all the segments, to which the passenger have been disrupted/re-accommodated.	< FlightSegment > array

FrequentFlyer

Frequent flyer details

Name	Description	Schema
airlineLevel <i>optional</i>		Tier
allianceLevel <i>optional</i>		Tier
applicableAirlineCode <i>optional</i>	Code of the airline for which frequent traveller data has been added Example : "6X"	string
confirmationStatus <i>optional</i>	Frequent flyer profile status K - validated (implies passenger can claim mileage) Example : "K"	string
customerValue <i>optional</i>	Passenger(customer) value (ACV) coming from loyalty system Example : 2	integer
frequentFlyerNumber <i>optional</i>	Loyalty card number Example : "6X090807061234"	string
id <i>optional</i>	Unique identifier for frequent flyer in the context of the loyalty program Example : "FF0001"	string
serviceCode <i>optional</i>	Service code (FQTV = Mileage program accrual, FQTU = Upgrade and accrual, FQTR = Mileage program redemption, FQTS = Service request) Example : "FQTU"	string

IdentityDocument

The information that are found on an ID document.

Name	Description	Schema
age <i>optional</i>	Age (in years for adult and in months for infant) Example : 33	integer
birthDate <i>optional</i>	Birth date in ISO 8601 format (yyyy-mm-dd) Example : "2000-10-20"	string (date)

Name	Description	Schema
documentType optional	The nature/type of the document. Example : "PASSPORT"	enum (VISA, PASSPORT, DRIVER_LICENSE, IDENTITY_CARD, RESIDENCE_PERMIT, VOTER_ID_CARD, WORK_PERMIT, MILITARY_ID_CARD, AIR_ATTENDANCE_LI CENCE, FLIGHT_MECHANICA L_LICENCE, OPERATIONAL_DISP ATCHER_LICENCE, LOYAL_ATTORNEY_I DENTIFICATION, FOREIGN_NATIONAL _REGISTRATION, KNOWN_TRAVELER, PILOT_LICENCE, NEXUS_CARD, APPROVED_NON_STA NDARD_ID, TWN_RESIDENTS_TR AVEL_PERMIT_TO_FR OM_CHN, CHN_RESIDENTS_TR AVEL_PERMIT_TO_FR OM_TWN_AND_CHN, EXIT_AND_ENTRY_PE RMIT_TWN, TRAVEL_PERMIT_TO_ FROM_HKG_MAC_PU BLIC_AFFAIRS, HOME_RE_ENTRY_PE RMIT_HUI_XIANG_ZH ENG, BORDER_CROSSING_ CARD, BIRTH_CERTIFICATE, ALIEN_PERMIT, CHN_RESIDENT_TRA VEL_PERMIT_TO_FRO M_HKG_AND_MAC, REFUGEE_OR_RE_EN TRY_PERMIT, SEAFARERS_PASSPO RT_SEAMEN, REDRESS, CHN_RESIDENT_TRA VEL_PERMIT_TO_HK G_AND_MAC, CHN_TRAVEL_PERMI

Name	Description	Schema
effectiveDate <i>optional</i>	Date at which the document starts to be valid. It may be different from the issuance date ("issuanceDate"), in ISO 8601 format (yyyy-mm-dd). Example : "2018-09-15"	string (date)
expiryDate <i>optional</i>	Date after which the document is not valid anymore in ISO 8601 format (yyyy-mm-dd) Example : "2025-08-15"	string (date)
gender <i>optional</i>	Gender as it appears on the document Example : "MALE"	enum (MALE, FEMALE, UNKNOWN, OTHER)
issuanceCountry <i>optional</i>	ISO code (2-letters) of the country that issued the document. Example : "GB"	string
issuanceDate <i>optional</i>	Date at which the document has been issued in ISO 8601 format (yyyy-mm-dd) Example : "2018-08-15"	string (date)
issuanceLocation <i>optional</i>	A more precise information concerning the place where the document has been issued, when available. It may be a country, a state, a city or any other type of location. e.g. New-York Example : "GBR"	string
name <i>optional</i>		Name
number <i>optional</i>	The document number (shown on the document) . E.g. QFU514563221J Example : "GB12345"	string
remarks <i>optional</i>	Any kind of special conditions/remarks that can be found on the document. E.g. "Valid during 1 month after arrival in the country", "Not valid to go to United states" Example : ["Valid for entries - 10"]	< string > array
validToDate <i>optional</i>	Document is valid until this date in ISO 8601 format (yyyy-mm-dd) Example : "2019-08-14"	string (date)

IncludedResources

Correlation data sent as included resources with the "Get DCS Passenger by ID" API response

Name	Description	Schema
correlationDcsPassengerBagsGroup <i>optional</i>	map of CorrelationDcsPassengerBagsGroup with DCSPassenger Id as key	< string, CorrelationDcsPassengerBagsGroup > map

Name	Description	Schema
correlationDcsPassengerEmd <i>optional</i>	map of CorrelationDcsPassengerEmd with DCSPassenger Id as key	< string, CorrelationDcsPassengerEmd > map
correlationDcsPassengerInventory <i>optional</i>	map of CorrelationDcsPassengerInventory with DCSPassenger Id as key	< string, CorrelationDcsPassengerInventory > map
correlationDcsPassengerPnr <i>optional</i>	map of CorrelationDcsPassengerPnr with DCSPassenger Id as key	< string, CorrelationDcsPassengerPnr > map
correlationDcsPassengerSchedule <i>optional</i>	map of CorrelationDcsPassengerSchedule with DCSPassenger Id as key	< string, CorrelationDcsPassengerSchedule > map
correlationDcsPassengerTicket <i>optional</i>	map of CorrelationDcsPassengerTicket with DCSPassenger Id as key	< string, CorrelationDcsPassengerTicket > map

InfrastructureLocation

Full location details of the DCS agent/device

Name	Description	Schema
airportCode <i>optional</i>	IATA three-digit airport code (exclusive with cityCode) Example : "LHR"	string
areaCode <i>optional</i>	Category of the location Example : "CKI"	string
buildingId <i>optional</i>	Building identifier - non verified or regulated (exclusive with terminalId) Example : "1"	string
cityCode <i>optional</i>	IATA three-digit metro area code (exclusive with airportCode) Example : "LON"	string
description <i>optional</i>	Admin user defined non structured free-flow text Example : "LHR TERM-2E"	string
identifier <i>optional</i>	Identifier of the closer location / zone Example : "1"	string

Name	Description	Schema
terminalId <i>optional</i>	Terminal identifier as in appendix of the SSM manual (exclusive with buildingId) Example : "2E"	string

InputSource

Means of adding a Regulatory Document for a given flight segment

Name	Description	Schema
entryMethod <i>optional</i>	Indicates whether the document was swiped or manually entered or historical Example : "SWIPED"	enum (SWIPED, MANUAL, HISTORICAL)
isHistorical <i>optional</i>	Indicates whether the document is historical Example : false	boolean
isOCR <i>optional</i>	Indicates whether the document information was populated using Optical Character Recognition technology Example : false	boolean
isSwipeOverriden <i>optional</i>	Indicates whether the document swipe was overridden Example : false	boolean
scannedMethod <i>optional</i>	Indicates the document scanning method Example : "MACHINE_READABLE"	enum (BIOMETRIC_DOCUMENT_OR_EPASSPORT, DIGITAL_PHOTO_DOCUMENT, MACHINE_READABLE)

LegDelivery

A leg delivery corresponds to all the information related to a passenger in the departure control system at a leg level. It represents the level of service that has been delivered to the passenger (check in status, seat delivered, cabin delivered in case of upgrade, etc)

Name	Description	Schema
acceptance <i>optional</i>		AcceptanceDelivery
arrival <i>optional</i>		FlightEndPoint
boarding <i>optional</i>		BoardingDelivery

Name	Description	Schema
comments <i>optional</i>	Comments created by either an agent or the dcs system and intended for the passenger	< Comment > array
compensations <i>optional</i>	Compensations information	< Compensation > array
departure <i>optional</i>		FlightEndPoint
id <i>optional</i>	Leg Delivery Identifier Example : "LHR"	string
onload <i>optional</i>		Onload
operatingFlight <i>optional</i>		OperatingFlight
regradeDelivered <i>optional</i>		Regrade
regradeProposed <i>optional</i>		Regrade
regulatoryChecks <i>optional</i>	Regulatory Checks information for each Regulatory program	< RegulatoryChecks > array
seating <i>optional</i>		SeatingDelivery
travelCabinCode <i>optional</i>	Travel cabin code for that leg Example : "C"	string

Meta

Technical information related to the feed

Name	Description	Schema
triggerEventLog <i>optional</i>	Information related to the initial event that triggered the process	EventLog
version <i>optional</i>	Version of the JSON feed produced Example : "2.2.0"	enum (2.2.0)

Methods

Accepted Methods

Type : < enum (GET) > array

Name

Full name details

Name	Description	Schema
firstName <i>optional</i>	First name Example : "John"	string
lastName <i>optional</i>	Last name Example : "SMITH"	string
title <i>optional</i>	Title Example : "Mr"	string

Onload

Onload details (DCS process of accepting standby passengers as per priority as defined by the airline)

Name	Description	Schema
cabinCode <i>optional</i>	Target cabin code post onload recommendation Example : "C"	string
edit <i>optional</i>		OnloadEdit
priority <i>optional</i>	Priority Example : "W31"	string
status <i>optional</i>	the status of this onload Example : "OK"	string

OnloadEdit

Details like reason, cabin that are set and used by DCS to compute the Onload recommendation

Name	Description	Schema
cabinCode <i>optional</i>	If Onload Edit is Remain, then this is the cabin to keep passenger in Example : "Y"	string

Name	Description	Schema
reasonCode <i>optional</i>	the reason code for this onload edit Example : "IGNORE"	enum (IGNORE, TO_STANDBY, TO_REMAIN, CLEAR)
reasonFreeText <i>optional</i>	Onload edit reason text Example : "Keep in same cabin"	string

OperatingFlight

Operating flight number details

Name	Description	Schema
carrierCode <i>optional</i>	Carrier code Example : "6X"	string
number <i>optional</i>	Airline number Example : "741"	string
suffix <i>optional</i>	Operational suffix Example : "A"	string

PassengerSegmentDisruption

This structure is to hold passenger disruption information. In case of events like flight cancellation/delay/diversion/etc., when a passenger is transferred to an alternative one - then disruption status/reason are added to the products involved in transfer (also called disruption marking). Additionally, the transferred FROM and TO products are linked.

Name	Description	Schema
originalDestination <i>optional</i>	Original destination. Contains IATA location code Example : "LHR"	string
productState <i>optional</i>		DisruptionState

PatchOperation

A single JSON Patch operation as defined by RFC 6902 (see <https://tools.ietf.org/html/rfc6902>)

Name	Description	Schema
from <i>optional</i>	A JSON Pointer as defined by RFC 6901 (see https://tools.ietf.org/html/rfc6901)	string

Name	Description	Schema
op <i>required</i>	The operation to be performed	enum (ADD, REMOVE, REPLACE, MOVE, COPY, TEST)
path <i>required</i>	A JSON Pointer as defined by RFC 6901 (see https://tools.ietf.org/html/rfc6901)	string
value <i>optional</i>	The value to be used within the operations	object

Phone

Phone information

Name	Description	Schema
text <i>optional</i>	Phone number Example : "61415588511"	string

PriceCategory

An EMD is categorised based on its reason for issuance code (RFIC), which defines the group of services it belongs to. There can only be one RFIC code per EMD. Some codes are defined by IATA, however, others can be defined by individual airlines. An EMD, and each RFIC, can have multiple reason for issuance sub-codes (RFISC). There is one RFISC in each EMD coupon and they are airline-specific.

Name	Description	Schema
code <i>optional</i>	The reason for issuance code (RFIC) chargeability indicator defined for the sellable object Example : "C"	string
rfiscDescription <i>optional</i>	description of reason for issuance sub code Example : "BAG- EXCESS PC ALLOWANCE"	string
subCode <i>optional</i>	The reason for issuance sub code (RFISC) chargeability indicator defined for the sellable object Example : "99Y"	string

Regrade

DCS Passengers can be regraded for operational reasons or as a gesture of good will. The regrade depending on the case can be an upper cabin or lower cabin. Amongst the Regrade properties - priority, cabinCode and regradeType will not be populated for regradeDelivered.

Name	Description	Schema
authoriserReference <i>optional</i>	Regrade authoriser reference Example : "AU0123"	string
cabinCode <i>optional</i>	Regrade cabin code - has value only in case of Regrade Proposed Example : "C"	string
priority <i>optional</i>	Regrade priority Example : "W31"	string

Name	Description	Schema
reason <i>optional</i>	The reason code for this regrade Example : "OVER_SOLD_CURRENT_FLIGHT"	enum (OVER_SOLD_CURRENT_FLIGHT, OVER_SOLD_OTHER_FLIGHT, MISIDENTIFICATION_AT_CHECKIN, PREVIOUS_MISHANDLE, BOOKED_MARKETING_UPGRADE, INVOLUNTARY_DOWNGRADE, TICKETED_IN_HIGHER_CLASS, COURTESY, CUSTOMER_DOWNGRADE_REQUESTED, SPECIAL_OCCASION, AIRCRAFT_CHANGE, CABIN_CONFIG_CHANGE, SPECIAL_REQUESTOR, COMPASSIONATE, AUTHORIZED_BY, MARKETING_INITIATIVE, DISRUPTION_CURRENT_FLIGHT, FREQUENT_FLYER_UPGRADE, DISRUPTION_OTHER_FLIGHT, CREW_CHANGE, TECHNICAL_REASON, CATERING_SHORTFALL, CHECKIN_ERROR, INADMISSIBLE, UNSUITABLE, STAFF, SERVICE_RECOVERY, ONLOAD, CANCEL_ACCEPTANCE, DUPE_PRODUCT, MANAGEMENT_AUTHORIZED, CUSTOMER_DOWNGRADE_REQUIREMENT)

Name	Description	Schema
reasonFreeText <i>optional</i>	Regrade reason in free text Example : "Oversold current flight"	string
regradeType <i>optional</i>	Regrade type Example : "VOLUNTARY"	enum (REMAIN_FORCE, INVOLUNTARY, VOLUNTARY, PURCHASED)
status <i>optional</i>	the status of this regrade Example : "PENDING"	enum (PENDING, ACTIONED, CANCELED, FAILED)

RegulatoryChecks

Details about the regulatory checks done for a given flight segment leg

Name	Description	Schema
assessmentTime <i>optional</i>	Time at which Regulatory Transaction was performed Example : "2018-07-31T11:23:20Z"	string
id <i>optional</i>	Regulatory Checks Identifier Example : "1255477819"	string
regulatoryProgram <i>optional</i>		RegulatoryProgram
statuses <i>optional</i>	Regulatory statuses	< RegulatoryStatus > array

RegulatoryComment

Details about any override comments (e.g. for manual selectee) added by DCS agent or message received from regulatory authority

Name	Description	Schema
code <i>optional</i>	4 digit code for directive type comment or G=Government, A=Airline for APP authorizer Example : "8517"	string
commentType <i>optional</i>	Indicates the type of comment from Regulatory System ("DIRECTIVE" in case of APP, "OVERRIDE_AUTHORIZER" for APP and iAPP, "SPECIAL_INSTRUCTIONS" for iAPP, "REASON" for ADC) Example : "REASON"	enum (DIRECTIVE, OVERRIDE_AUTHORIZER, SPECIAL_INSTRUCTIONS, REASON)

Name	Description	Schema
description <i>optional</i>	The comment or override authoriser Example : "TIMEOUT"	string

RegulatoryDocument

Document for booked flight segment used for regulatory purpose E.g. Visas, Passports, Resident Cards, etc, along with information like source of entry and usage of the document.

Name	Description	Schema
countryOfPortOfEntry <i>optional</i>	Country the port of entry is part of Example : "PRI"	string
countryOfRegistration <i>optional</i>	Country of registration Example : "USA"	string
document <i>optional</i>		IdentityDocument
id <i>optional</i>	unique ID of the document image Example : "100000001AFC111A"	string
inputSource <i>optional</i>		InputSource
isBearer <i>optional</i>	Indicates whether it is the bearer's or dependent's the document Example : true	boolean
isCarried <i>optional</i>	Indicates whether the passenger is carrying the document Example : false	boolean
presentedAtPort <i>optional</i>	Port where the document was shown Example : "SJU"	string
recordedDocumentType <i>optional</i>	Free text Qualifier or sub type for the document E.g. VVV is default for Visa and PPP for passport Example : "VVV"	string
usedFor <i>optional</i>	Document is only used for arrival, departure or transit Example : "ARRIVAL"	enum (ARRIVAL, DEPARTURE, TRANSIT)
validForCarrier <i>optional</i>	Document is valid for this carrier. This is required when there are multiple documents to be used in a passenger journey. Example : "6X"	string

RegulatoryProgram

Regulatory program defines the requirements issued by the governments regarding travel to and from their countries. Using this information they indicate from a security and vetting perspective, if they are happy to allow the travel for the passenger in question.

Name	Description	Schema
countryCode <i>optional</i>	Code of the country the program applies to in the ISO 3166-1 alpha-3 format Example : "CAN"	string
name <i>optional</i>	Name of the regulatory program (AQQ, IAPP, APP, ADC, CANADIAN_PPP, PRIVATE_LIST, MANUAL_SELECTEE) Example : "APP"	string

RegulatoryStatus

Regulatory statuses along with any override details

Name	Description	Schema
id <i>optional</i>	Regulatory Status Identifier Example : "1255477820"	string
isVerifiedId <i>optional</i>	Verified Id indicator applicable only for AQQ and IAPP programs Example : false	boolean
message <i>optional</i>		RegulatoryComment
override <i>optional</i>		RegulatoryComment

Name	Description	Schema
statusCode <i>optional</i>	Code of the Status, the value and meaning is based on program Codeset Description ——— ————— I AQQ Inhibited To Board/ADC Perfomed Not OK/iAPP Not Cleared/CAS Do not Board N False/APP Not Required/Not Performed (ADC/iAPP)/Preflight Screening Not Screened Override/SSCI Visa Check Not Performed/CAS Not Performed NI Not processed - Insufficient Information (TSA/Airline Blacklist Status) D ADC performed Conditional Not OK/ESTA Document not on File B ESTA Not Present/Bypassed (ADC/Preflight Screening)/CAI Document not on file C ESTA Denied/ADC performed Conditional OK E Data Error (AQQ/ADC/iAPP/Preflight Screening/CAS)/EVUS not on file F APP Failed 1 True 0 False AIY APIS Data - Complete AIR APIS Data - Agent Reval Required AIQ APIS Data - Not Required AIP APIS Data - Not Performed AIN APIS Data - Not Complete A ESTA Valid/CAI Valid document on file 3 AQQ PreChecked Z ESTA Not Required / ADC Not Applicable/CAI Document not required SM Soft Match U Preflight Screening Not Screened T ESTA Time-out/CAI Time out Y True/ESTA Bypassed/CAI Bypassed X ESTA Insufficient Information/Not Required (ADC/iAPP)/Preflight Screening Revised/SSCI Visa Check Not Required/CAI Insufficient information/CAS Not Required NS Not Supported O AQQ Ok To Board/ADC Performed OK/iAPP Cleared/Preflight Screening Screened/CAS Ok to Board NL Not Processed - Link Down (TSA/Airline Blacklist Status) NP Not Performed (ABL) Q Preflight Screening Not Required P Preflight Screening Not responded/SSCI Visa Check Performed/iAPP Bypassed/ESTA Pending Review/CAS Bypassed R APP Required/Preflight Screening Selectee Override/ESTA Do not Board/CAI Do not board S Selectee (AQQ/TSA/iAPP/Preflight Screening/ABL) / APP Successful/CAS Selectee RR Restricted (TSA/Airline Blacklist Status and Override/AQQ/iAPP) APC ClearToBoard (APP) APX Cancelled (APP) APN NotFound (APP) APT Timeout (APP) APE ErrorCondition (APP) APD DuplicateName (APP) API InsufficientData (APP) APF DoNotBoard (APP) Example : "S"	string
statusType <i>optional</i>	Types of Status Example : "SECURITY"	enum (SECURITY, IMMIGRATION, DIRECTIVE)

Relationship

Details of a relationship

Name	Description	Schema
href <i>optional</i>	The URI of the related resource Example : "https://airlines.api.amadeus.com/v2/departure-control/processed-dcs-passengers/2721234567890726"	string
id <i>optional</i>	Identifier of the related resource Example : "2002CAE00036002D"	string
methods <i>optional</i>		Methods
ref <i>optional</i>	The reference to the related resource if this latter exists in the same document Example : "included/correlationDcsPassengerTicket/2002CAE00036002D"	string
type <i>optional</i>	The type of the related resource Example : "dcs-passenger"	string
version <i>optional</i>	Only populated for correlated resources defined in Dictionaries Example : "1"	string

Relationships

Indicate relationships from one Passenger or one Segment to many Passengers or Segments

Name	Description	Schema
collection <i>optional</i>	The details of the related items	< Relationship > array
id <i>optional</i>	identifier of the relationship collection Example : "17236616612311"	string

RevenueIntegrityAssessment

This object provides information about Revenue Integrity Checks performed for a passenger

Name	Description	Schema
checks <i>optional</i>	List of Revenue Integrity checks performed	< RevenueIntegrityCheck > array
comments <i>optional</i>	List of Passenger(customer) Check Comments	< RevenueIntegrityComment > array

RevenueIntegrityCheck

Provides information Revenue Integrity checks and its status

Name	Description	Schema
checkType <i>optional</i>	Types of check Example : "CUSTOMER_TYPE_CHECK"	enum (BOARD_OFF_POINTS_CHECK, CLASS_CHECK, EXACT_FLIGHT_CHECK, FULL_FIRST_NAME_CHECK, FLIGHT_NUMBER_CHECK, GO_SHOW_CHECK, NO_SHOW_CHECK, STOPOVER_CHECK, SEQUENCE_CHECK, TRAVEL_DATE_CHECK, CUSTOMER_TYPE_CHECK, VALIDITY_DATE_CHECK, TICKET_CHECKS, CARRIER_CHECK, FARE_BASIS_CHECK)
id <i>optional</i>	Revenue Integrity Check identifier Example : "1231432422234"	string
status <i>optional</i>	Status of Revenue Integrity Check Example : "PASSED"	enum (IGNORED, NON_PRIME, NOT_REQUIRED, OVERRIDDEN, BYPASSED, DISRUPTED, FAILED, PASSED, REQUIRED, UNDEFINED)

RevenueIntegrityComment

Comments on Revenue Integrity Checks

Name	Description	Schema
commentType <i>optional</i>	Type of comment Example : "PASSED_CUSTOMER_TYPES"	enum (OVERRIDE_TICKET_CHECKS_REASON, OVERRIDE_STOPOVER_CHECK_REASON, OVERRIDE_SEQUENCE_CHECK_REASON, OUTSTANDING_CUSTOMER_TYPE, PASSED_CUSTOMER_TYPES)
description <i>optional</i>	Contains actual comment Example : "STUDENT1"	string
id <i>optional</i>	Revenue Integrity Comment identifier Example : "1255477819"	string

Seat

Seat details like seat number and characteristics

Name	Description	Schema
characteristicsCodes <i>optional</i>	List of seat characteristics codes defined by IATA like CH - chargeable, W - Window etc Example : ["CH", "W"]	< string > array
number <i>optional</i>	the seat number Example : "12A"	string

SeatingDelivery

Seating details at leg level

Name	Description	Schema
chargeableSeat <i>optional</i>		Service
emergencyExitSuitability <i>optional</i>	suitability of the passenger to seat in emergency exit row	enum (UNABLE_TO_DETERMINE, SUITABLE, NOT_SUITABLE)
isChargeableSeat <i>optional</i>	Chargeable Seat indicator - true if assigned seat is chargeable Example : true	boolean

Name	Description	Schema
seat <i>optional</i>		Seat
seatPreferences <i>optional</i>		Seat
seatProductStatus <i>optional</i>	Seat confirmation status Example : "HL"	string
seatStatus <i>optional</i>	Seat status Example : "CONFIRMED"	enum (CONFIRMED, REJECTED, GUARANTEED, NOT_GUARANTEED)

SegmentDelivery

Booked flight segment details

Name	Description	Schema
associatedAirTravelDocuments <i>optional</i>	Segment associated/matched E-Ticket/EMDs	< AirTravelDocument > array
associatedPassengerSegments <i>optional</i>		AssociatedPassengerSegments
contacts <i>optional</i>	Segment associated contact information Example : [{ "id" : "126511237759", "addresseeName" : { "firstName" : "John", "lastName" : "SMITH" }, "phone" : { "text" : "001461415588511" }, "purpose" : ["EMERGENCY"], "isDeclined" : false }]	< Contact > array

Name	Description	Schema
dcProductType <i>optional</i>	Product Type in DCS record (CPR) as explained below at higher level: - ACTIVE_SYNCHRONISED Fully operational in DCS with interactions with RES on PSS side - ACTIVE_NOT_SYNCHRONISED Fully operational in DCS without any interactions with RES on PSS side - PASSIVE_SYNCHRONISED Future "ACTIVE_SYNCHRONISED" segment which is not yet in DCS window - PASSIVE Flown or cancelled segment - PASSIVE_IATCI Segment is candidate for Inter-Airline-Through-Check-In (IATCI) - PASSIVE_DCS Segment either not handled by DCS originating feed (Informational segment) or has a corresponding another active segment as part of another CPR (The two CPRs would be usually automatically merged by DCS system) - NON_OPERATIONAL Segment is not operational in DCS system anymore due to disruption Example : "ACTIVE_SYNCHRONISED"	enum (ACTIVE_SYNCHRONISED, ACTIVE_NOT_SYNCHRONISED, PASSIVE_SYNCHRONISED, PASSIVE, PASSIVE_IATCI, PASSIVE_DCS, NON_OPERATIONAL)
frequentFlyer <i>optional</i>	Frequent flyer information at segment level	< FrequentFlyer > array
id <i>optional</i>	Unique Product Identifier Example : "2401CA55000030ID"	string
legDeliveries <i>optional</i>	Booked flight segment leg level details	< LegDelivery > array
nationality <i>optional</i>	Nationality of the passenger applied/used for the current segment Example : "GRC"	string
passengerDisruption <i>optional</i>		PassengerSegmentDisruption
previousTicket <i>optional</i>		AirTravelDocument
recordLocator <i>optional</i>	Record locator of the PNR linked to that segment only in case it is different from the main one. Applicable when the DCS passenger record consists of two merged reservation bookings Example : "PC3XYV"	string
regulatoryDocuments <i>optional</i>	Segment associated Regulatory documents	< RegulatoryDocument > array
revenueIntegrity <i>optional</i>		RevenueIntegrityAssessment

Name	Description	Schema
segment <i>optional</i>		FlightSegment
segmentLinks <i>optional</i>	References to other Segment deliveries in other DCS passengers linked to this one. These refers to passengers travelling together for part of their journey.	< Relationships > array
services <i>optional</i>	Segment delivery associated services (SSR/OSI/SK) Example : [{ "code" : "DOCA", "address" : { "category" : "DESTINATION", "lines" : ["101, JENYA"], "postalCode" : "560068", "countryCode" : "IN", "cityName" : "BLR", "stateCode" : "KAR" } }, { "id" : "1000000000BC2107", "chargeableServiceId" : "10000007896346C1", "code" : "BIKE", "subType" : "SSR", "priceCategory" : { "code" : "C", "subCode" : "99Y" }, "status" : "MCF", "NIP" : 1, "isSubjectToQuota" : true, "quotaCode" : "SSRQ123", "chargeableServiceDocument" : { "documentType" : "EMD", "number" : "1728200002469", "status" : "REFUNDED" }, "paymentStatus" : "WAIVED", "isIssuanceRequired" : true, "waiver" : { "authoriser" : "Check-in agent", "reasonCode" : "Technical", "reasonText" : "A technical issue occurred at check-in. Agent had to waive the chargeable service" } }]	< Service > array
staff <i>optional</i>		Staff
type <i>optional</i>	resource name Example : "segment-delivery"	enum (segment-delivery)
uniqueCustomerIdentifier <i>optional</i>	The Unique Customer Identifier (UCI) corresponding to the actual RES booking for this Segment. It could be different from DcsPassenger.id in case DCS has merged multiple passenger records for the same physical passenger (customer). Example : "2501ADE000000001"	string
volunteerDeniedBoarding <i>optional</i>	Volunteer Denied Boarding is a qualifier to the state if passenger have volunteered to be deny boarding the flight.	enum (NOT_ASKED, VOLUNTEERED, DECLINED)
volunteerDowngrade <i>optional</i>	Volunteer Downgrade is a qualifier to the state if passenger have volunteered to be downgraded.	enum (NOT_ASKED, VOLUNTEERED, DECLINED)

Service

Service representation (SSR/SK/OSI/SVC)

Name	Description	Schema
address <i>optional</i>		Address

Name	Description	Schema
chargeableServiceDocument <i>optional</i>		ChargeableServiceDocument
chargeableServiceId <i>optional</i>	The unique identifier of the chargeable service. Example : "10000007896346C1"	string
code <i>optional</i>	This code is used to identify the type of the services Maximal length : 4 Example : "VGML"	string
description <i>optional</i>	This field is used to describe the service free text Example : "Passenger/Crew primary travel document information"	string
document <i>optional</i>		IdentityDocument
id <i>optional</i>	Service Item unique identifier Example : "1000000000BC2107"	string
isIssuanceRequired <i>optional</i>	Whether issuance is required for this chargeable service Example : true	boolean
isSubjectToQuota <i>optional</i>	Whether the service is subject to quota Example : true	boolean
numberInParty <i>optional</i>	Number in party Example : 1	integer
paymentStatus <i>optional</i>	Status of payment made for this service Example : "WAIVED"	enum (PAID, UNPAID, WAIVED, EXEMPTED)
priceCategory <i>optional</i>		PriceCategory
products <i>optional</i>		Relationship
quotaCode <i>optional</i>	The quota code of the service subject to quota as defined in Inventory Example : "SSRQ"	string
serviceProvider <i>optional</i>		ServiceProvider
stakeholders <i>optional</i>		Relationship

Name	Description	Schema
statusCode <i>optional</i>	Service Status Example : "HK"	string
subType <i>optional</i>	This field is used to indicate if we are dealing with an SSR/SK/OSI element Example : "SPECIAL_SERVICE_REQUEST"	enum (SPECIAL_SERVICE_REQUEST, SPECIAL_KEYWORD, OTHER_SERVICE_INFORMATION, MANUAL_AUXILIARY_SEGMENT)
text <i>optional</i>		ServiceDescription
waiver <i>optional</i>		Waiver

ServiceDescription

Name	Description	Schema
label <i>optional</i>	Description Label Example : "A description label"	string
value <i>optional</i>	This field is used for Service level description Example : "P/GBR/012345678/GBR/30JUN73/M/14APR09/JOHNSON/SIMON/JEAN PAUL/H"	string

ServiceProvider

Name	Description	Schema
code <i>optional</i>	This field is used to represent carrier for pax level service. Can be YY meaning applies to all products in PNR Example : "YY"	string

Staff

Airline Staff details like ID type, category, joining date etc

Name	Description	Schema
category <i>optional</i>	Staff Category Example : "BOOKABLE"	enum (BOOKABLE, STANDBY)
companyCode <i>optional</i>	IATA code of the airline/company the staff belong to Example : "WT"	string

Name	Description	Schema
companyName <i>optional</i>	Company Name Example : "World Travellers"	string
id <i>optional</i>	Staff Number Example : "ST0793"	string
idType <i>optional</i>	Staff ID type (e.g. N2, S1) Example : "N2"	string
joiningDate <i>optional</i>	Date of joining in ISO 8601 format (yyyy-mm-dd) Example : "2011-02-28"	string (date)
relationshipType <i>optional</i>	Relationship type (Self, Spouse,...) Example : "Self"	string
retirementDate <i>optional</i>	Date of retirement in ISO 8601 format (yyyy-mm-dd) Example : "2011-02-28"	string (date)
transferDays <i>optional</i>	Number of days the staff has been transferred to the next day flight Example : 3	integer
transfersDuringDay <i>optional</i>	Number of time the staff was transferred during the current day Example : 2	integer

Stakeholder

Person details who may or may not be a traveler (the structure can be used for representing a non-traveler)

Name	Description	Schema
age <i>optional</i>	Age (in years for Adult and in months for Infant - refer flightPassengerType) Example : 32	integer
contacts <i>optional</i>	Passenger associated contact information Example : [{ "id" : "126511237759", "email" : { "address" : "contact@contactstandard.xyz" }, "language" : "EN", "purpose" : ["STANDARD"], "carrierCode" : "6X" }, { "id" : "762636429911", "phone" : { "text" : "00446716216622", "countryCode" : "GB" }, "language" : "FR", "purpose" : ["STANDARD"], "carrierCode" : "6X" }]	< Contact > array
countryOfResidence <i>optional</i>	Country of residence Example : "Portugal"	string

Name	Description	Schema
dateOfBirth <i>optional</i>	The date of birth in ISO 8601 format (yyyy-mm-dd) Example : "2010-10-10"	string (date)
flightPassengerType <i>optional</i>	Specifies passenger type Example : "ADULT"	enum (ADULT, CHILD, INFANT, INFANT_WITH_SEAT)
gender <i>optional</i>	The gender Example : "FEMALE"	enum (MALE, FEMALE, UNKNOWN, OTHER)
id <i>optional</i>	The identifier Example : "DDD78FG"	string
name <i>optional</i>		Name
nationality <i>optional</i>	Nationality Example : "GRC"	string
placeOfBirth <i>optional</i>	Place of birth Example : "London"	string

Tier

Description of a Tier in the context of the loyalty program

Name	Description	Schema
code <i>optional</i>	Code associated to the tier (e.g. <G> for Gold) Example : "G"	string
companyCode <i>optional</i>	Alliance code or airline code of the loyalty program Example : "6X"	string
name <i>optional</i>	Provides the name or description of the tier such as Gold, Silver or Platinum Example : "Gold"	string
priorityCode <i>optional</i>	Priority code used to synchronize with external systems. Should have a clear correspondence to the code. Example : "1"	string

TimeLocationTrackingLog

All information related to track the boarding process of a passenger

Name	Description	Schema
deviceId <i>optional</i>	tracking device Example : "AF5FA7A4"	string

Name	Description	Schema
deviceUser <i>optional</i>	the agent's sign in who last tracked Example : "116554"	string
localDateTime <i>optional</i>	date (dd-mmm-yyy) and time (hh:mm:ss) when last tracked Example : "11-OCT-2018 16:43:59"	string
logSource <i>optional</i>	channel how last tracked	enum (EXTERNAL_DCS, CRYPTIC, JFE, KIOSK, MOBILE_PHONE, SMS, TELEPHONE, WEB, AIRLINE_AGENT, GROUND_HANDLING_AGENT, AUTO_CHECKIN, AUTO_BAGDROP, LOUNGE_ACCESS, BRS_SCANNER, WIRELESS_HANDHELD_BOARDING, EXTERNAL_FRONTEND, BAGGAGE RECONCILIATION SYSTEM, BAGGAGE SORTATION SYSTEM)
referenceDeviceType <i>optional</i>	the type of the device name	enum (CRT, DUMD_GATE_READER, SELF_BOARDING_DEVICE, JFE)
trackedLocation <i>optional</i>		InfrastructureLocation
utcDateTime <i>optional</i>	date (dd-mmm-yyy) and time (hh:mm:ss) when last tracked Example : "11-OCT-2018 14:43:59"	string

Traveler

Traveler details (passenger possibly with CBBG/EXST)

Polymorphism : Composition

Name	Description	Schema
age <i>optional</i>	Age (in years for Adult and in months for Infant - refer flightPassengerType) Example : 32	integer
contacts <i>optional</i>	Passenger associated contact information Example : [{ "id" : "126511237759", "email" : { "address" : "contact@contactstandard.xyz" }, "language" : "EN", "purpose" : ["STANDARD"], "carrierCode" : "6X" }, { "id" : "762636429911", "phone" : { "text" : "00446716216622", "countryCode" : "GB" }, "language" : "FR", "purpose" : ["STANDARD"], "carrierCode" : "6X" }]	< Contact > array
countryOfResidence <i>optional</i>	Country of residence Example : "Portugal"	string
dateOfBirth <i>optional</i>	The date of birth in ISO 8601 format (yyyy-mm-dd) Example : "2010-10-10"	string (date)
flightPassengerType <i>optional</i>	Specifies passenger type Example : "ADULT"	enum (ADULT, CHILD, INFANT, INFANT_WITH_SEAT)
gender <i>optional</i>	The gender Example : "FEMALE"	enum (MALE, FEMALE, UNKNOWN, OTHER)
id <i>optional</i>	The identifier Example : "DDD78FG"	string
name <i>optional</i>		Name
nationality <i>optional</i>	Nationality Example : "GRC"	string
placeOfBirth <i>optional</i>	Place of birth Example : "London"	string
specialSeat <i>optional</i>	CBBG (Cabin Baggage) or EXST (Extra Seat) Example : "CBBG"	enum (CBBG, EXST)

User

The user that initiated/performed the change in case of user initiated events

Name	Description	Schema
id <i>optional</i>	Identifier of the User Example : "3355KJ"	string
officeID <i>optional</i>	Office Id of the User. Defaulted to "LON1A0955" in case of DCS system initiated actions Example : "FRALH04SS"	string

Name	Description	Schema
workStation <i>optional</i>		WorkStation

Waiver

Holds details of payment waiver. A waiver represents the airlines approval for dropping the requirement to pay for a service.

Name	Description	Schema
authoriser <i>optional</i>	The authoriser of the waiver Example : "Check-in agent"	string
reasonCode <i>optional</i>	The reason code of the waiver Example : "Passenger had to wait for check-in due to malfunction of the system"	string
reasonText <i>optional</i>	The reason text of the waiver Example : "A situation at the check-in agent and had to waive the chargeable service"	string

Warning

Name	Description	Schema
code <i>required</i>	A machine-readable error code from the Canned Messages table, that will enable the API Consumers code to handle this type of error	integer
detail <i>optional</i>	An easy-to-read explanation specific to this occurrence of the problem. It should give the API consumer an idea of what went wrong and how to recover from it. Like the title, this field's value can be localized.	string
documentation <i>optional</i>	A link to a web page or file with further documentation to help the API consumer resolve this error	string (url)
source <i>optional</i>		ErrorSource
title <i>required</i>	An error title from the Canned Messages table with a 1:1 correspondence to the error code. This may be localized	string

WorkStation

Workstation details from where the change was done

Name	Description	Schema
fullLocation <i>optional</i>		InfrastructureLocation
id <i>optional</i>	Identifier of the Workstation in format 'qualifier - address' Example : "J-04SS"	string

Security

basicAuth

HTTP Basic Authentication. Works over **HTTP** and **HTTPS**

Type : basic