

# Dynamic Intelligence Hub

Membership Open Api Specification

# Table of Contents

|                                                                                                                                                                          |    |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Amadeus Dynamic Intelligence Hub API .....                                                                                                                               | 1  |
| Overview .....                                                                                                                                                           | 2  |
| Version information .....                                                                                                                                                | 2  |
| License information .....                                                                                                                                                | 2  |
| URI scheme .....                                                                                                                                                         | 2  |
| Consumes .....                                                                                                                                                           | 2  |
| Produces .....                                                                                                                                                           | 2  |
| Paths .....                                                                                                                                                              | 3  |
| EMD Data Push .....                                                                                                                                                      | 3  |
| Get the DIH processed-travel-document resource corresponding to the requested fid It can<br>either be an electronic ticket or an Electronic Miscellaneous Document (EMD) | 3  |
| Ticket Data Push .....                                                                                                                                                   | 4  |
| Ticket Correlation Data Push .....                                                                                                                                       | 5  |
| Definitions .....                                                                                                                                                        | 6  |
| 400Errors.....                                                                                                                                                           | 6  |
| 401Errors.....                                                                                                                                                           | 6  |
| 404Errors.....                                                                                                                                                           | 7  |
| 500Errors.....                                                                                                                                                           | 7  |
| AirTravelDocument .....                                                                                                                                                  | 8  |
| AssociatedPnr .....                                                                                                                                                      | 10 |
| Authorization.....                                                                                                                                                       | 10 |
| BaggageAllowance .....                                                                                                                                                   | 11 |
| BookingClass .....                                                                                                                                                       | 11 |
| Commission .....                                                                                                                                                         | 11 |
| Contact.....                                                                                                                                                             | 12 |
| CorrelatedDataEmdDcsPassenger.....                                                                                                                                       | 12 |
| CorrelatedDataEmdMembership .....                                                                                                                                        | 12 |
| CorrelatedDataEmdPnr .....                                                                                                                                               | 12 |
| CorrelatedDataTicketDcsPassenger .....                                                                                                                                   | 13 |
| CorrelatedDataTicketInventory.....                                                                                                                                       | 13 |
| CorrelatedDataTicketMembership .....                                                                                                                                     | 14 |
| CorrelatedDataTicketPnr .....                                                                                                                                            | 14 |
| CorrelatedDataTicketSchedule .....                                                                                                                                       | 14 |
| CorrelationEmdDcsPassenger .....                                                                                                                                         | 15 |
| CorrelationEmdMembership .....                                                                                                                                           | 15 |
| CorrelationEmdPnr .....                                                                                                                                                  | 15 |
| CorrelationReferences.....                                                                                                                                               | 16 |
| CorrelationTicketDcsPassenger.....                                                                                                                                       | 17 |

|                                     |    |
|-------------------------------------|----|
| CorrelationTicketInventory .....    | 17 |
| CorrelationTicketMembership.....    | 17 |
| CorrelationTicketPnr .....          | 18 |
| CorrelationTicketSchedule .....     | 18 |
| Coupon.....                         | 19 |
| CurrencyConversionLookupRates ..... | 22 |
| Dictionaries .....                  | 22 |
| Discount.....                       | 23 |
| DisplayedFormOfPayment .....        | 23 |
| ElementaryPrice .....               | 24 |
| Email .....                         | 24 |
| EventLog .....                      | 25 |
| EventLogOverride.....               | 25 |
| Events.....                         | 26 |
| FareBasis .....                     | 27 |
| FareCalculation .....               | 27 |
| FareComponent .....                 | 28 |
| FareFamily .....                    | 29 |
| Fee.....                            | 29 |
| FlightDesignator .....              | 30 |
| FlightEndPoint.....                 | 30 |
| FlightSegment .....                 | 30 |
| FormOfIdentification .....          | 31 |
| FrequentFlyer .....                 | 31 |
| Included .....                      | 31 |
| IssueSource.....                    | 32 |
| Location.....                       | 32 |
| Membership.....                     | 33 |
| Meta .....                          | 33 |
| Name .....                          | 33 |
| NegoFareContract .....              | 33 |
| OperatingFlight .....               | 34 |
| PatchOperation .....                | 34 |
| PaymentCard .....                   | 34 |
| PaymentLoyalty.....                 | 35 |
| Phone .....                         | 35 |
| PointOfSale .....                   | 35 |
| Price .....                         | 36 |
| PriceCategory.....                  | 37 |
| PricingConditions .....             | 37 |
| Relationship .....                  | 38 |

|                                  |    |
|----------------------------------|----|
| Stakeholder.....                 | 39 |
| Tax .....                        | 39 |
| TicketRefund .....               | 39 |
| Tier .....                       | 40 |
| TravelDocumentResponseData ..... | 41 |
| Weight .....                     | 44 |
| emdDataPush.....                 | 45 |
| ticketDataPush.....              | 45 |
| ticketingCorrelationsPush.....   | 45 |
| travelDocumentApiResponse.....   | 46 |
| Security .....                   | 47 |
| basicAuth .....                  | 47 |

# **Amadeus Dynamic Intelligence Hub API**

# Overview

This document describes DIH output for 1. Amadeus REST/JSON API endpoint to retrieve a ticket or EMD from Dynamic Intelligence Hub 2. Travel Document Data Push Feed

## Version information

*Version* : 4.3.0

## License information

*License* : Proprietary

*License URL* : <http://amadeus.com/todo/licenses/LICENSE-1.0.html>

*Terms of service* : <http://amadeus.com/todo/terms>

## URI scheme

*Host* : pulse-api-tkt-pulse-qa.router.openshift.int-a.pulse-tst1.172.30.16.120.nip.io

*BasePath* : /

*Schemes* : HTTPS

## Consumes

- `application/json`

## Produces

- `application/vnd.amadeus+json`

# Paths

## EMD Data Push

POST //ticketing/emd-feed

### Description

EMD feed generated by the Online Data Push Micro-Service of Agility Platform

### Responses

| HTTP Code | Description                                                                                                                                                                                                           | Schema                      |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| default   | Payload identical to the API GET /ticketing/tickets output except that it includes the 'events' structure. Please be aware this is NOT a POST API, rather this explains the format of the data pushed out by Amadeus. | <a href="#">emdDataPush</a> |

### Tags

- FEED

## Get the DIH processed-travel-document resource corresponding to the requested fid It can either be an electronic ticket or an Electronic Miscellaneous Document (EMD)

GET //ticketing/processed-travel-documents/{fid}

### Description

Returns the DIH TKT/EMD payload matching the requested fid, as well as its correlations with other domains

### Parameters

| Type        | Name                          | Description                                                                                                                                          | Schema |
|-------------|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>Path</b> | <b>fid</b><br><i>required</i> | Contains the TKT/EMD suffixed by its creation date, which enable to uniquely identify a TravelDocument on DIH. Format is "TICKET_NUMBER-YYYY-MM-DD". | string |

## Responses

| HTTP Code  | Description                                                   | Schema                                    |
|------------|---------------------------------------------------------------|-------------------------------------------|
| <b>200</b> | Successful response, processed-travel-document resource found | <a href="#">travelDocumentApiResponse</a> |
| <b>400</b> | Bad request                                                   | <a href="#">400Errors</a>                 |
| <b>401</b> | Unauthorized                                                  | <a href="#">401Errors</a>                 |
| <b>404</b> | Not found                                                     | <a href="#">404Errors</a>                 |
| <b>500</b> | Internal error                                                | <a href="#">500Errors</a>                 |

## Tags

- TravelDocumentAPI

## Security

| Type         | Name                      |
|--------------|---------------------------|
| <b>basic</b> | <a href="#">basicAuth</a> |

# Ticket Data Push

POST //ticketing/ticket-feed

## Description

Ticket feed generated by the Online Data Push Micro-Service of Agility Platform

## Responses

| HTTP Code      | Description                                                                                                                                                                                                           | Schema                         |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|
| <b>default</b> | Payload identical to the API GET /ticketing/tickets output except that it includes the 'events' structure. Please be aware this is NOT a POST API, rather this explains the format of the data pushed out by Amadeus. | <a href="#">ticketDataPush</a> |

## Tags

- FEED

# Ticket Correlation Data Push

POST //ticketing/ticketing-correlations-feed

## Description

Ticket & EMD correlation feed generated by the Online Data Push Micro-Service of Agility Platform

## Responses

| HTTP Code      | Description                                                                                                                                                          | Schema                                    |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| <b>default</b> | Model for the Ticket and EMD correlations data push feed. Please be aware this is NOT a POST API, rather this explains the format of the data pushed out by Amadeus. | <a href="#">ticketingCorrelationsPush</a> |

## Tags

- FEED

# Definitions

## 400Errors

| Name                            | Schema                          |
|---------------------------------|---------------------------------|
| <b>error</b><br><i>optional</i> | < <a href="#">error</a> > array |

### error

| Name                             | Description                                    | Schema                      |
|----------------------------------|------------------------------------------------|-----------------------------|
| <b>code</b><br><i>optional</i>   | an application-specific error code.            | number                      |
| <b>detail</b><br><i>optional</i> | explanation of the error.                      | string                      |
| <b>source</b><br><i>optional</i> |                                                | <a href="#">IssueSource</a> |
| <b>status</b><br><i>optional</i> | the HTTP status code applicable to this error. | string                      |
| <b>title</b><br><i>optional</i>  | a short summary of the error.                  | string                      |

## 401Errors

| Name                            | Schema                          |
|---------------------------------|---------------------------------|
| <b>error</b><br><i>optional</i> | < <a href="#">error</a> > array |

### error

| Name                             | Description                                    | Schema                      |
|----------------------------------|------------------------------------------------|-----------------------------|
| <b>code</b><br><i>optional</i>   | an application-specific error code.            | number                      |
| <b>detail</b><br><i>optional</i> | explanation of the error.                      | string                      |
| <b>source</b><br><i>optional</i> |                                                | <a href="#">IssueSource</a> |
| <b>status</b><br><i>optional</i> | the HTTP status code applicable to this error. | string                      |
| <b>title</b><br><i>optional</i>  | a short summary of the error.                  | string                      |

## 404Errors

| Name                            | Schema                          |
|---------------------------------|---------------------------------|
| <b>error</b><br><i>optional</i> | < <a href="#">error</a> > array |

### error

| Name                             | Description                                    | Schema                      |
|----------------------------------|------------------------------------------------|-----------------------------|
| <b>code</b><br><i>optional</i>   | an application-specific error code.            | number                      |
| <b>detail</b><br><i>optional</i> | explanation of the error.                      | string                      |
| <b>source</b><br><i>optional</i> |                                                | <a href="#">IssueSource</a> |
| <b>status</b><br><i>optional</i> | the HTTP status code applicable to this error. | string                      |
| <b>title</b><br><i>optional</i>  | a short summary of the error.                  | string                      |

## 500Errors

| Name                            | Schema                          |
|---------------------------------|---------------------------------|
| <b>error</b><br><i>optional</i> | < <a href="#">error</a> > array |

### error

| Name                             | Description                                    | Schema                      |
|----------------------------------|------------------------------------------------|-----------------------------|
| <b>code</b><br><i>optional</i>   | an application-specific error code.            | number                      |
| <b>detail</b><br><i>optional</i> | explanation of the error.                      | string                      |
| <b>source</b><br><i>optional</i> |                                                | <a href="#">IssueSource</a> |
| <b>status</b><br><i>optional</i> | the HTTP status code applicable to this error. | string                      |
| <b>title</b><br><i>optional</i>  | a short summary of the error.                  | string                      |

# AirTravelDocument

| Name                                                 | Description                                                                                                                                            | Schema                                                 |
|------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|
| <b>associatedDocuments</b><br><i>optional</i>        | List of Associated Ticket or Associated EMD for the current document,e.g. EMD-A associated to an ETKT.                                                 | <<br><a href="#">associatedDocuments</a><br>> array    |
| <b>associatedPnr</b><br><i>optional</i>              |                                                                                                                                                        | < <a href="#">AssociatedPnr</a> ><br>array             |
| <b>conjunctiveDocumentNumbers</b><br><i>optional</i> | <b>Example :</b> "0142100147468"                                                                                                                       | < string > array                                       |
| <b>coupons</b><br><i>optional</i>                    |                                                                                                                                                        | < <a href="#">Coupon</a> > array                       |
| <b>creation</b><br><i>optional</i>                   | Indicates the creation DateTime and the point of sale of the entity.                                                                                   | <a href="#">EventLog</a>                               |
| <b>destinationCityIataCode</b><br><i>optional</i>    | destination city code<br><b>Example :</b> "LON"                                                                                                        | string                                                 |
| <b>dictionaries</b><br><i>optional</i>               |                                                                                                                                                        | <a href="#">Dictionaries</a>                           |
| <b>documentRefund</b><br><i>optional</i>             |                                                                                                                                                        | <a href="#">TicketRefund</a>                           |
| <b>documentType</b><br><i>optional</i>               | Type of document<br><b>Example :</b> "TICKET"                                                                                                          | enum (TICKET, EMD_ASSOCIATED, EMD_STANDALONE)          |
| <b>endorsementFreeFlow</b><br><i>optional</i>        | Used to identify any restrictions, airline comments, or rules that may apply to the ticket/EMD<br><b>Example :</b> "FARE RESTRICTION MAY APPLY -BG 6X" | string                                                 |
| <b>formsOfIdentification</b><br><i>optional</i>      |                                                                                                                                                        | <<br><a href="#">FormOfIdentification</a><br>> array   |
| <b>formsOfPayment</b><br><i>optional</i>             |                                                                                                                                                        | <<br><a href="#">DisplayedFormOfPayment</a><br>> array |
| <b>id</b><br><i>optional</i>                         | id of ticket or EMD.<br><b>Example :</b> "0142100147468-2018-10-18"                                                                                    | string                                                 |
| <b>issuanceType</b><br><i>optional</i>               | Indicates the type of transaction.<br><b>Example :</b> "FIRST_ISSUE"                                                                                   | enum (FIRST_ISSUE, REISSUE)                            |

| Name                                            | Description                                                                                                                                                                                                                                                                                                                                                                                            | Schema                                         |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| <b>latestEvent</b><br><i>optional</i>           | Indicates the last updated DateTime. Indicate the last point of sale of the entity. Indicate code to depict message function.                                                                                                                                                                                                                                                                          | <a href="#">EventLog</a>                       |
| <b>numberOfBooklets</b><br><i>optional</i>      | Number of conjunctive tickets/EMDs in the document.<br><b>Example :</b> <b>1.0</b>                                                                                                                                                                                                                                                                                                                     | number                                         |
| <b>originCityIataCode</b><br><i>optional</i>    | origin city code<br><b>Example :</b> <b>"PAR"</b>                                                                                                                                                                                                                                                                                                                                                      | string                                         |
| <b>originalDocuments</b><br><i>optional</i>     | The ticket(s) against which this ticket was exchanged and the original local DateTime of the document issuance.                                                                                                                                                                                                                                                                                        | < <a href="#">originalDocuments</a> ><br>array |
| <b>originalIssueFreeFlow</b><br><i>optional</i> | Original issue information in free text. Not formatted on ETS.<br><b>Example :</b> <b>"Freetext"</b>                                                                                                                                                                                                                                                                                                   | string                                         |
| <b>price</b><br><i>optional</i>                 |                                                                                                                                                                                                                                                                                                                                                                                                        | <a href="#">Price</a>                          |
| <b>pricingConditions</b><br><i>optional</i>     |                                                                                                                                                                                                                                                                                                                                                                                                        | <a href="#">PricingConditions</a>              |
| <b>primaryDocumentNumber</b><br><i>optional</i> | Ticket primary number or EMD primary number<br><b>Example :</b> <b>"0142100147468"</b>                                                                                                                                                                                                                                                                                                                 | string                                         |
| <b>quotationOverrides</b><br><i>optional</i>    | The aim of the override element is to enable an agent to override quotation data and to keep track of all the changes along with the reason for the changes. Overrides are applied on quotation documents [TST] and are automatically populated into the travel document at issuance. To create an override element, an agent needs to provide one override type and one reason code at the same time. | < <a href="#">EventLogOverride</a> ><br>array  |
| <b>traveler</b><br><i>optional</i>              | Traveler information.                                                                                                                                                                                                                                                                                                                                                                                  | <a href="#">Stakeholder</a>                    |
| <b>validatingCarrierCode</b><br><i>optional</i> | Ticket validating carrier code<br><b>Example :</b> <b>"6X"</b>                                                                                                                                                                                                                                                                                                                                         | string                                         |
| <b>validatingCarrierPnr</b><br><i>optional</i>  | Validating carrier record locator and owner of the record locator (Validating carrier code/Ticketing Online Feed user code if not validating/booking GDS code)                                                                                                                                                                                                                                         | <a href="#">AssociatedPnr</a>                  |
| <b>version</b><br><i>optional</i>               | An identifier to track the sequential flow of messages. Epoch format.<br><b>Example :</b> <b>"1586867381"</b>                                                                                                                                                                                                                                                                                          | string                                         |

| Name                           | Description                                                                               | Schema                   |
|--------------------------------|-------------------------------------------------------------------------------------------|--------------------------|
| <b>void</b><br><i>optional</i> | Is only filled when a ticket status becomes void (DateTime information in ISO6081 format) | <a href="#">EventLog</a> |

#### associatedDocuments

| Name                                     | Description                                                                                                                                                                   | Schema                                        |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <b>documentNumber</b><br><i>optional</i> | Identifier of the travel document prefixed by its owner code [NALC - 3 digits]. Can either be a primary or a conjunctive document number.<br><b>Example :</b> "0142100147468" | string                                        |
| <b>documentType</b><br><i>optional</i>   | Type of document<br><b>Example :</b> "EMD_ASSOCIATED"                                                                                                                         | enum (TICKET, EMD_ASSOCIATED, EMD_STANDALONE) |

#### originalDocuments

| Name                                     | Description                                                                                                                                                                   | Schema                                        |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <b>creation</b><br><i>optional</i>       | Indicates the creation DateTime of the entity.                                                                                                                                | <a href="#">EventLog</a>                      |
| <b>documentNumber</b><br><i>optional</i> | Identifier of the travel document prefixed by its owner code [NALC - 3 digits]. Can either be a primary or a conjunctive document number.<br><b>Example :</b> "0142100147468" | string                                        |
| <b>documentType</b><br><i>optional</i>   | Type of document<br><b>Example :</b> "TICKET"                                                                                                                                 | enum (TICKET, EMD_ASSOCIATED, EMD_STANDALONE) |

## AssociatedPnr

Describes the association between the current reservation and another one.

| Name                                | Description                                                                                                                                                                                 | Schema                   |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| <b>creation</b><br><i>optional</i>  | Creation date and system code [GDS/CRS] from which originates the associated reference                                                                                                      | <a href="#">EventLog</a> |
| <b>reference</b><br><i>optional</i> | Record locator [Amadeus or OA] with which the current reservation is associated - in case of a codeshare association, it enables to identify the operating PNR<br><b>Example :</b> "JKL789" | string                   |

## Authorization

| Name                                           | Description                                                                                                                                                                                                                                                                                                  | Schema |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>approvalCode</b><br><i>optional</i>         | A series of characters assigned by the applicable credit card company's authorization system to confirm the approval of a credit sale transaction, with a maximum of 8 digits<br><b>Example :</b> "38562"                                                                                                    | string |
| <b>extendedPaymentCode</b><br><i>optional</i>  | A code to indicate the number of months over which the customer wishes to pay where the credit card issuer permits.<br><b>Example :</b> "11"                                                                                                                                                                 | string |
| <b>sourceOfApprovalCode</b><br><i>optional</i> | Approval source of the authorization when the FOP is a credit card. Can be seen in the corresponding FP elements of the order. Possible values are A - Automatic Approval Code M - Manual Approval Code F - Automatic Capture and Approval Code B - Manual Capture and Approval Code<br><b>Example :</b> "A" | string |

## BaggageAllowance

| Name                                 | Description           | Schema                          |
|--------------------------------------|-----------------------|---------------------------------|
| <b>excessRate</b><br><i>optional</i> |                       | <a href="#">ElementaryPrice</a> |
| <b>quantity</b><br><i>optional</i>   | Total number of units | integer                         |
| <b>weight</b><br><i>optional</i>     |                       | <a href="#">Weight</a>          |

## BookingClass

Booking class description

| Name                           | Description                                                | Schema |
|--------------------------------|------------------------------------------------------------|--------|
| <b>code</b><br><i>optional</i> | code identifying the booking class<br><b>Example :</b> "Y" | string |

## Commission

| Name                                 | Description                                               | Schema                          |
|--------------------------------------|-----------------------------------------------------------|---------------------------------|
| <b>amount</b><br><i>optional</i>     |                                                           | <a href="#">ElementaryPrice</a> |
| <b>percentage</b><br><i>optional</i> | Percentage in case of a rate commission - can be decimal. | number                          |

## Contact

Represents a contact

| Name                            | Schema                |
|---------------------------------|-----------------------|
| <b>email</b><br><i>optional</i> | <a href="#">Email</a> |
| <b>phone</b><br><i>optional</i> | <a href="#">Phone</a> |

## CorrelatedDataEmdDcsPassenger

Set of data field identifiers defining the correlation between an EMD and a CPR

| Name                                                    | Description                            | Schema |
|---------------------------------------------------------|----------------------------------------|--------|
| <b>dcsPassengerSegmentDeliveryId</b><br><i>optional</i> | Example : "2401CA55000030ID"           | string |
| <b>dcsPassengerServiceId</b><br><i>optional</i>         | Example : "1000000000B54A31"           | string |
| <b>emdCouponId</b><br><i>optional</i>                   | Example : "1722500003207-2018-06-15-1" | string |

## CorrelatedDataEmdMembership

Set of data field identifiers defining the correlation between an EMD and a Loyalty Membership

| Name                                      | Description                            | Schema |
|-------------------------------------------|----------------------------------------|--------|
| <b>emdCouponId</b><br><i>optional</i>     | Example : "1722500003207-2018-06-15-1" | string |
| <b>emdCouponStatus</b><br><i>optional</i> | Example : "READY_FOR_USE"              | string |

## CorrelatedDataEmdPnr

Set of data field identifiers defining the correlation between an EMD and a PNR

| Name                                  | Description                            | Schema |
|---------------------------------------|----------------------------------------|--------|
| <b>emdCouponId</b><br><i>optional</i> | Example : "1722500003207-2018-06-15-1" | string |

| Name                                              | Description                         | Schema |
|---------------------------------------------------|-------------------------------------|--------|
| <b>pnrAirSegmentId</b><br><i>optional</i>         | Example : "ABCDEF-2018-06-15-ST-4"  | string |
| <b>pnrServiceId</b><br><i>optional</i>            | Example : "ABCDEF-2018-06-15-OT-10" | string |
| <b>pnrTicketingReferenceId</b><br><i>optional</i> | Example : "ABCDEF-2018-06-15-OT-10" | string |
| <b>pnrTravelerId</b><br><i>optional</i>           | Example : "ABCDEF-2018-06-15-PT-1"  | string |

## CorrelatedDataTicketDcsPassenger

Set of data field identifiers defining the correlation between a ticket and a CPR

| Name                                                    | Description                            | Schema |
|---------------------------------------------------------|----------------------------------------|--------|
| <b>dcsPassengerSegmentDeliveryId</b><br><i>optional</i> | Example : "2401CA55000030ID"           | string |
| <b>ticketCouponId</b><br><i>optional</i>                | Example : "1722500003153-2018-06-15-1" | string |

## CorrelatedDataTicketInventory

Set of data field identifiers defining the correlation between a ticket and an Inventory flight record

| Name                                             | Description                                | Schema |
|--------------------------------------------------|--------------------------------------------|--------|
| <b>inventoryPartnershipId</b><br><i>optional</i> | Example : "6X78955515101900000NULL"        | string |
| <b>inventorySegmentId</b><br><i>optional</i>     | Example : "6X56755525101900000NULLYULCDGO" | string |
| <b>ticketCouponId</b><br><i>optional</i>         | Example : "1722500003153-2018-06-15-1"     | string |

## CorrelatedDataTicketMembership

Set of data field identifiers defining the correlation between a ticket and a Loyalty Membership

| Name                                         | Description                                   | Schema |
|----------------------------------------------|-----------------------------------------------|--------|
| <b>ticketCouponId</b><br><i>optional</i>     | <b>Example :</b> "1722500003153-2018-06-15-1" | string |
| <b>ticketCouponStatus</b><br><i>optional</i> | <b>Example :</b> "READY_FOR_USE"              | string |

## CorrelatedDataTicketPnr

Set of data field identifiers defining the correlation between a ticket and a PNR

| Name                                              | Description                                   | Schema |
|---------------------------------------------------|-----------------------------------------------|--------|
| <b>pnrAirSegmentId</b><br><i>optional</i>         | <b>Example :</b> "ABCDEF-2018-06-15-ST-4"     | string |
| <b>pnrTicketingReferenceId</b><br><i>optional</i> | <b>Example :</b> "ABCDEF-2018-06-15-OT-10"    | string |
| <b>pnrTravelerId</b><br><i>optional</i>           | <b>Example :</b> "ABCDEF-2018-06-15-PT-1"     | string |
| <b>ticketCouponId</b><br><i>optional</i>          | <b>Example :</b> "1722500003153-2018-06-15-1" | string |

## CorrelatedDataTicketSchedule

Set of data field identifiers defining the correlation between a ticket and a Schedule flight record

| Name                                            | Description                                  | Schema |
|-------------------------------------------------|----------------------------------------------|--------|
| <b>schedulePartnershipId</b><br><i>optional</i> | <b>Example :</b> "BA-435-2018-05-25"         | string |
| <b>scheduleSegmentId</b><br><i>optional</i>     | <b>Example :</b> "6X-123-2018-10-05-CDGYUL " | string |

| Name                                     | Description                                   | Schema |
|------------------------------------------|-----------------------------------------------|--------|
| <b>ticketCouponId</b><br><i>optional</i> | <b>Example :</b> "1722500003153-2018-06-15-1" | string |

## CorrelationEmdDcsPassenger

Structure of correlation between an Electronic Miscellaneous Document and a Customer Product Record.

| Name                                      | Description                                                                                                               | Schema                                                                  |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|
| <b>correlatedData</b><br><i>optional</i>  |                                                                                                                           | < string, < <a href="#">CorrelatedDataEmdDcsPassenger</a> > array > map |
| <b>dcsPassengerIds</b><br><i>optional</i> | Identifying the CPR(s) correlated with the current EMD - item corresponds to CPR UCI<br><b>Example :</b> "2501ADE0000001" | < string > array                                                        |
| <b>emdId</b><br><i>optional</i>           | Current EMD number + issuance date<br><b>Example :</b> "1722500003207-2018-06-15"                                         | string                                                                  |

## CorrelationEmdMembership

Structure of correlation between an Electronic Miscellaneous Document and a Loyalty Membership.

| Name                                     | Description                                                                                                                                                                                  | Schema                                                                |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| <b>correlatedData</b><br><i>optional</i> |                                                                                                                                                                                              | < string, < <a href="#">CorrelatedDataEmdMembership</a> > array > map |
| <b>emdId</b><br><i>optional</i>          | Current EMD number + issuance date<br><b>Example :</b> "1722500003207-2018-06-15"                                                                                                            | string                                                                |
| <b>membershipId</b><br><i>optional</i>   | Identifying the Loyalty Membership correlated with the current ticket. Format is carrier code (owner of the program) + frequent flyer id (within the loyalty program)<br><b>Example :</b> "" | string                                                                |

## CorrelationEmdPnr

Structure of correlation between an Electronic Miscellaneous Document and a Passenger Name Record.

| Name                                     | Description                                                                                                                                        | Schema                                                         |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| <b>correlatedData</b><br><i>optional</i> |                                                                                                                                                    | < string, < <a href="#">CorrelatedDataEmdPnr</a> > array > map |
| <b>emdId</b><br><i>optional</i>          | current EMD number + issuance date<br><b>Example</b> : "1722500003207-2018-06-15"                                                                  | string                                                         |
| <b>pnrIds</b><br><i>optional</i>         | Identifying the PNR(s) correlated with the current EMD - item format is record locator + creation date<br><b>Example</b> : [ "ABCDEF-2018-06-15" ] | < string > array                                               |

## CorrelationReferences

| Name                                   | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Schema                       |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| <b>correlations</b><br><i>optional</i> | <p>Correlation resources are defined in the "included" node. This node provides links to all correlations resources associated with the current processed-travel-document resource [TKT/EMD].</p> <p><b>Example</b> : { "ticketPnr" : { "ref" : "included/correlationTicketPnr/1722500003153-2018-10-18" }, "ticketDcsPassenger" : { "ref" : "included/correlationTicketDcsPassenger/1722500003153-2018-10-18" }, "ticketSchedule" : { "ref" : "included/correlationTicketSchedule/1722500003153-2018-10-18" }, "ticketInventory" : { "ref" : "included/correlationTicketInventory/1722500003153-2018-10-18" }, "ticketMembership" : { "ref" : "included/correlationTicketMembership/1722500003153-2018-10-18" }, "emdPnr" : { "ref" : "included/correlationEmdPnr/1722500009467-2019-10-11" }, "emdDcsPassenger" : { "ref" : "included/correlationEmdDcsPassenger/1722500009467-2019-10-11" }, "emdMembership" : { "ref" : "included/correlationEmdMembership/1722500009467-2019-10-11" } }</p> | <a href="#">correlations</a> |

### correlations

| Name                                         | Schema                       |
|----------------------------------------------|------------------------------|
| <b>emdDcsPassenger</b><br><i>optional</i>    | <a href="#">Relationship</a> |
| <b>emdMembership</b><br><i>optional</i>      | <a href="#">Relationship</a> |
| <b>emdPnr</b><br><i>optional</i>             | <a href="#">Relationship</a> |
| <b>ticketDcsPassenger</b><br><i>optional</i> | <a href="#">Relationship</a> |
| <b>ticketInventory</b><br><i>optional</i>    | <a href="#">Relationship</a> |

| Name                                       | Schema                       |
|--------------------------------------------|------------------------------|
| <b>ticketMembership</b><br><i>optional</i> | <a href="#">Relationship</a> |
| <b>ticketPnr</b><br><i>optional</i>        | <a href="#">Relationship</a> |
| <b>ticketSchedule</b><br><i>optional</i>   | <a href="#">Relationship</a> |

## CorrelationTicketDcsPassenger

Structure of correlation between a ticket and a Customer Product Record.

| Name                                      | Description                                                                                                                      | Schema                                                                     |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|
| <b>correlatedData</b><br><i>optional</i>  |                                                                                                                                  | < string, < <a href="#">CorrelatedDataTicketDcsPassenger</a> > array > map |
| <b>dcsPassengerIds</b><br><i>optional</i> | Identifying the CPR(s) correlated with the current ticket - item corresponds to CPR UCI<br><b>Example :</b> [ "2501ADE0000001" ] | < string > array                                                           |
| <b>ticketId</b><br><i>optional</i>        | current ticket number + issuance date<br><b>Example :</b> "172250003153-2018-06-15"                                              | string                                                                     |

## CorrelationTicketInventory

Structure of correlation between a ticket and an Inventory Dated Flight record.

| Name                                     | Description                                                                                                                                                                                                              | Schema                                                                  |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|
| <b>correlatedData</b><br><i>optional</i> |                                                                                                                                                                                                                          | < string, < <a href="#">CorrelatedDataTicketInventory</a> > array > map |
| <b>inventoryIds</b><br><i>optional</i>   | Identifying the inventory flight(s) correlated with the current ticket - item is dated flight ID i.e. carrier code + flight number + flight date + operational suffix.<br><b>Example :</b> [ "6X12355515101900000NULL" ] | < string > array                                                        |
| <b>ticketId</b><br><i>optional</i>       | current ticket number + issuance date<br><b>Example :</b> "172250003153-2018-06-15"                                                                                                                                      | string                                                                  |

## CorrelationTicketMembership

Structure of correlation between a ticket and a Loyalty Membership.

| Name                                     | Description                                                                                                                                                                                  | Schema                                                                   |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| <b>correlatedData</b><br><i>optional</i> |                                                                                                                                                                                              | < string, < <a href="#">CorrelatedDataTicketMembership</a> > array > map |
| <b>membershipId</b><br><i>optional</i>   | Identifying the Loyalty Membership correlated with the current ticket. Format is carrier code (owner of the program) + frequent flyer id (within the loyalty program)<br><b>Example :</b> "" | string                                                                   |
| <b>ticketId</b><br><i>optional</i>       | current ticket number + issuance date<br><b>Example :</b> "1722500003153-2018-06-15"                                                                                                         | string                                                                   |

## CorrelationTicketPnr

Structure of correlation between a ticket and a Passenger Name Record.

| Name                                     | Description                                                                                                                                       | Schema                                                            |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| <b>correlatedData</b><br><i>optional</i> |                                                                                                                                                   | < string, < <a href="#">CorrelatedDataTicketPnr</a> > array > map |
| <b>pnrIds</b><br><i>optional</i>         | Identifying the PNR(s) correlated with the current ticket - item format is record locator + creation date<br><b>Example :</b> "ABCDEF-2018-06-15" | < string > array                                                  |
| <b>ticketId</b><br><i>optional</i>       | current ticket number + issuance date<br><b>Example :</b> "1722500003153-2018-06-15"                                                              | string                                                            |

## CorrelationTicketSchedule

Structure of correlation between a ticket and a Schedule Dated Flight record.

| Name                                     | Description                                                                                                                                                                                                      | Schema                                                                 |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------|
| <b>correlatedData</b><br><i>optional</i> |                                                                                                                                                                                                                  | < string, < <a href="#">CorrelatedDataTicketSchedule</a> > array > map |
| <b>scheduleIds</b><br><i>optional</i>    | Identifying the schedule flight(s) correlated with the current ticket - item is dated flight ID i.e. carrier code + flight number + flight date + operational suffix<br><b>Example :</b> [ "6X-123-2018-10-05" ] | < string > array                                                       |
| <b>ticketId</b><br><i>optional</i>       | current ticket number + issuance date<br><b>Example :</b> "1722500003153-2018-06-15"                                                                                                                             | string                                                                 |

# Coupon

A coupon refers to a product that has been issued in the current travel document. In tickets, a coupon refers to a flight segment. An airline ticket portion that bears the notion "good for passage", or in the case of an electronic ticket, the electronic coupon indicates the particular places a passenger is entitled to be carried. A single ticket/document number may contain up to 4 segments. For tickets/documents with more than 4 segments of travel, a conjunction ticket is required to continue the itinerary. In EMDs, a coupon can refer to an ancillary service, an upgrade, a fee or a residual value. \* soldSegment - Original image of the coupon at first issuance of the document. \* currentSegment - Latest image of the coupon in case it has been subject to modification[s] such as revalidation e.g. change of flight number. \* usedSegment - Image of the coupon when its status is considered as used i.e. either flown [B] or exchanged [E], refunded [RF], printed [PR], print exchange [PE], converted to Flight Interruption Manifest [G], closed [CLO], voided [V].

| Name                                          | Description                                                                                                                                                                                                                                                                                                                                  | Schema                                              |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| <b>associatedDocuments</b><br><i>optional</i> |                                                                                                                                                                                                                                                                                                                                              | <<br><a href="#">associatedDocuments</a><br>> array |
| <b>baggageAllowance</b><br><i>optional</i>    |                                                                                                                                                                                                                                                                                                                                              | <a href="#">BaggageAllowance</a>                    |
| <b>currentSegment</b><br><i>optional</i>      |                                                                                                                                                                                                                                                                                                                                              | <a href="#">FlightSegment</a>                       |
| <b>documentNumber</b><br><i>optional</i>      | A single ticket/document number may contain up to 4 segments. For tickets/documents with more than 4 segments of travel, a conjunction ticket is required to continue the itinerary. Conjunctive tickets/EMDs (i.e. for an ETKT, a conjunctive ticket is issued when the ticket has more than 4 coupons)<br><b>Example :</b> "0142100147468" | string                                              |
| <b>fareBasis</b><br><i>optional</i>           |                                                                                                                                                                                                                                                                                                                                              | <a href="#">FareBasis</a>                           |
| <b>fareFamily</b><br><i>optional</i>          |                                                                                                                                                                                                                                                                                                                                              | <a href="#">FareFamily</a>                          |
| <b>frequentFlyer</b><br><i>optional</i>       |                                                                                                                                                                                                                                                                                                                                              | <a href="#">FrequentFlyer</a>                       |
| <b>id</b><br><i>optional</i>                  | Coupon id<br><b>Example :</b> "0142100147468-2018-10-18-1"                                                                                                                                                                                                                                                                                   | string                                              |
| <b>isCodeshare</b><br><i>optional</i>         | Depicts whether the coupon has codeshare flight or not.<br>Default value is false<br><b>Example :</b> true                                                                                                                                                                                                                                   | boolean                                             |

| Name                                                  | Description                                                                                                                                                                                                                                                          | Schema                                                                     |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|
| <b>isFromConnection</b><br><i>optional</i>            | Indicates whether the flight segment priced is departing from a connection with the previous flight<br><b>Example :</b> <i>false</i>                                                                                                                                 | boolean                                                                    |
| <b>isNonExchangeable</b><br><i>optional</i>           | Non exchangeable indicator signifying that the document being exchanged is exchangeable or not.ex:You can only exchange an EMD if none of the EMD coupons have the coupon indicator set to non-exchangeable. Default value is false<br><b>Example :</b> <i>false</i> | boolean                                                                    |
| <b>isNonRefundable</b><br><i>optional</i>             | Non refundable indicator signifying that the document being refundable or not. Default value is false<br><b>Example :</b> <i>false</i>                                                                                                                               | boolean                                                                    |
| <b>monetaryValue</b><br><i>optional</i>               |                                                                                                                                                                                                                                                                      | <a href="#">ElementaryPrice</a>                                            |
| <b>number</b><br><i>optional</i>                      | The coupon number inside this conjunctive ticket should be the same as "Coupon Number" in case of non conjunctive tickets (from1 to 4).<br><b>Example :</b> <i>1.0</i>                                                                                               | number                                                                     |
| <b>reasonForIssuance</b><br><i>optional</i>           |                                                                                                                                                                                                                                                                      | <a href="#">PriceCategory</a>                                              |
| <b>reservationStatus</b><br><i>optional</i>           | Reservation status.<br><b>Example :</b> <i>"REQUESTED"</i>                                                                                                                                                                                                           | enum (REQUESTED, STANDBY, NO_SEAT, CONFIRMED, WAITLISTED, SPACE_AVAILABLE) |
| <b>revalidation</b><br><i>optional</i>                | Revalidating originator and date at which the coupon was revalidated                                                                                                                                                                                                 | <a href="#">EventLog</a>                                                   |
| <b>sequenceNumber</b><br><i>optional</i>              | The coupon sequence number over ticket(s). In the case of conjunctive tickets it defines the coupon sequence number over all conjunctive tickets and in this case it can be greater than four.<br><b>Example :</b> <i>1.0</i>                                        | number                                                                     |
| <b>serviceRemark</b><br><i>optional</i>               | EMD related service remarks (free text information)<br><b>Example :</b> <i>"Service remark freetext"</i>                                                                                                                                                             | string                                                                     |
| <b>settlementAuthorizationCode</b><br><i>optional</i> | Contains the code present in the coupon that authenticates the settlement of all monetary charges of the coupon.<br><b>Example :</b> <i>"1326459788"</i>                                                                                                             | string                                                                     |
| <b>soldSegment</b><br><i>optional</i>                 |                                                                                                                                                                                                                                                                      | <a href="#">FlightSegment</a>                                              |

| Name                                         | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Schema                                                                                                                                                                                                                                                                                         |
|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>status</b><br><i>optional</i>             | Coupon operational status. It follows IATA PADIS Code List for data element 4405<br><b>Example :</b> "EXCHANGED"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | enum (EXCHANGED, FLOWN, EXCHANGED_TO_FIM, COUPON_NOTIFICATION, OPEN_FOR_USE, REFUNDED, SUSPENDED, VOID, CLOSED, REVOKED, PRINTED, PRINT_EXCHANGE, NOT_AVAILABLE, BOARDED, IRREGULAR_OPERATIONS, ORIGINAL_ISSUE, CHECKED_IN, AIRPORT_CONTROL, UNAVAILABLE, REFUND_TAXES_AND_FEES, PAPER_TICKET) |
| <b>usedSegment</b><br><i>optional</i>        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <a href="#">FlightSegment</a>                                                                                                                                                                                                                                                                  |
| <b>validityDates</b><br><i>optional</i>      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <a href="#">validityDates</a>                                                                                                                                                                                                                                                                  |
| <b>voluntaryIndicator</b><br><i>optional</i> | Coupon Involuntary Indicator indicates if any manual operations have been performed on the coupon. When an Involuntary change is performed on a coupon IATA Ticketing handbook requires one to enter an endorsement in the FE field. * 'W' - Weather/ATC delay * 'U' - Involuntary upgrade * 'D' - Diversion * 'F' - Strike/labor * 'IG' - Involuntary Grade Change * 'I' - Involuntary (no reason given) * 'O' - Oversale * 'S' - Schedule change * 'V' - Voluntary (customer requested) * 'SO' - Flight cancelled * '727' - Involuntary downgrade - passenger compensated * '728' - Involuntary downgrade - passenger not compensated<br><b>Example :</b> "S" | string                                                                                                                                                                                                                                                                                         |

#### associatedDocuments

| Name                                    | Description        | Schema            |
|-----------------------------------------|--------------------|-------------------|
| <b>couponNumbers</b><br><i>optional</i> | <b>Example :</b> 1 | < integer > array |

| Name                                     | Description                                                                   | Schema                                        |
|------------------------------------------|-------------------------------------------------------------------------------|-----------------------------------------------|
| <b>documentNumber</b><br><i>optional</i> | Defines the number of the travel document<br><b>Example</b> : "1724546546479" | string                                        |
| <b>documentType</b><br><i>optional</i>   | Type of document                                                              | enum (TICKET, EMD_STANDALONE, EMD_ASSOCIATED) |

#### validityDates

| Name                                         | Description                                                                                             | Schema        |
|----------------------------------------------|---------------------------------------------------------------------------------------------------------|---------------|
| <b>notValidAfterDate</b><br><i>optional</i>  | Not valid after date(GMT) in ISO 8601format,YYYY-MM-DD<br><b>Example</b> : "2018-10-29T09:35:42.000Z"   | string (date) |
| <b>notValidBeforeDate</b><br><i>optional</i> | Not valid before date(GMT) in format ISO 8601 YYYY-MM-DD<br><b>Example</b> : "2018-10-03T09:35:42.000Z" | string (date) |

## CurrencyConversionLookupRates

Conversion from provider's currency to requested currency

| Name                             | Description                                                                                 | Schema |
|----------------------------------|---------------------------------------------------------------------------------------------|--------|
| <b>rate</b><br><i>optional</i>   | The conversion factor to apply against the source currency to obtain the requested currency | string |
| <b>target</b><br><i>optional</i> | Requested currency code<br><b>Pattern</b> : "[A-Z]{3}"                                      | string |

## Dictionaries

| Name                                                    | Description                                                                                                                                                                                                                                                                                                        | Schema                                                        |
|---------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|
| <b>currencyConversionLookupRates</b><br><i>optional</i> | * Multiple base (many to one) * Used to define rate conversion when multiple currency possible *<br>origin_amount = reverse_rate x target_amount *<br>target_amount = rate x origin_amount * Example:<br>currencyConversionLookupRates: { USD: { rate: "0.80", target: EUR }, GBP: { rate: "1.14", target: EUR } } | < string, <a href="#">CurrencyConversionLookupRates</a> > map |
| <b>dcsPassengers</b><br><i>optional</i>                 | Set of key/value pairs with dcsPassengerId as key i.e. CPR UCI - key example '2501ADE0000001'                                                                                                                                                                                                                      | < string, <a href="#">Relationship</a> > map                  |
| <b>emds</b><br><i>optional</i>                          | Set of key/value pairs with emdId as key i.e. primary EMD number + issuance date - key example '1721234567891-2018-05-15'                                                                                                                                                                                          | < string, <a href="#">Relationship</a> > map                  |

| Name                                  | Description                                                                                                                                            | Schema                                          |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| <b>inventories</b><br><i>optional</i> | Set of key/value pairs with inventoryId as key [generated] - key example 6X12355515101900000NULL'                                                      | < string, <a href="#">Relationship</a><br>> map |
| <b>memberships</b><br><i>optional</i> | Set of key/value pairs with membershipId as key i.e. carrier code + frequent flyer id - key example '6X-1234567890'                                    | < string, <a href="#">Relationship</a><br>> map |
| <b>pnrs</b><br><i>optional</i>        | Set of key/value pairs with pnrId as key i.e. record locator + creation date - key example 'ABCDEF-2018-05-15'                                         | < string, <a href="#">Relationship</a><br>> map |
| <b>schedules</b><br><i>optional</i>   | Set of key/value pairs with scheduleId as key i.e. carrier code + flight number + flight date + operational suffix - key example '6X-123-2018-10-05-A' | < string, <a href="#">Relationship</a><br>> map |
| <b>tickets</b><br><i>optional</i>     | Set of key/value pairs with ticketId as key i.e. primary ticket number + issuance date - key example '1721234567890-2018-05-15'                        | < string, <a href="#">Relationship</a><br>> map |

## Discount

Deduction from the price amount, made in advance of its payment.

| Name                                    | Description                                                                                                                                                                                                                                    | Schema                                          |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| <b>code</b><br><i>optional</i>          | In case of promocode override - Identifier provided by the customer to obtain the discount<br><b>Example :</b> "87TVEFN1"                                                                                                                      | string                                          |
| <b>id</b><br><i>optional</i>            | In case of promocode override - Corporate code used to access the 'discounted' private fare within Fare Quote process<br><b>Example :</b> "OWNTPM20"                                                                                           | string                                          |
| <b>voucherStatus</b><br><i>optional</i> | APPLIED Voucher has been issued / re-issued<br>READY_TO_REFUND Voucher is released following a refund / exchange without benefit re-applied FULLY_CONSUMED<br>Voucher has been consumed following a flown coupon<br><b>Example :</b> "APPLIED" | enum (APPLIED, READY_TO_REFUND, FULLY_CONSUMED) |

## DisplayedFormOfPayment

Contains the Forms Of Payment that have been used to pay for the products issued in the current travel document [flights for tickets, ancillary services/upgrade services/fees for EMDs].

| Name                                    | Description | Schema                        |
|-----------------------------------------|-------------|-------------------------------|
| <b>authorization</b><br><i>optional</i> |             | <a href="#">Authorization</a> |

| Name                                      | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Schema                          |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| <b>code</b><br><i>optional</i>            | Form Of Payment category as defined in IATA PADIS code list for data element 9888. Examples - CA for Cash, CC for Credit Card, CK for Check, MS for Miscellaneous, EF for Electronic Funds transfer.<br><b>Example :</b> "CC"                                                                                                                                                                                                                                                                                                                                                                  | string                          |
| <b>displayedAmount</b><br><i>optional</i> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <a href="#">ElementaryPrice</a> |
| <b>fopIndicator</b><br><i>optional</i>    | Used to specify what the FOP has been used for, in case of exchanges. In case of a first-issue document, it takes the value [NEW]. In case of a single exchange, the FOP used to settle the original document takes the value [ORIGINAL], while the FOP used to settle the additional collection of the exchange i.e. the new ticket, takes the value [NEW]. In case of multiple exchanges, the same principle applies, and the FOP used to settle the last ticket to exchange takes the value [OLD]. This field follows IATA PADIS Code List for data element 9988.<br><b>Example :</b> "NEW" | enum (NEW, OLD, ORIGINAL)       |
| <b>freeText</b><br><i>optional</i>        | Free text as entered in the order via the FP element<br><b>Example :</b> "Form of payment free text"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | string                          |
| <b>paymentCard</b><br><i>optional</i>     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <a href="#">PaymentCard</a>     |
| <b>paymentLoyalty</b><br><i>optional</i>  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <a href="#">PaymentLoyalty</a>  |

## ElementaryPrice

| Name                                          | Description                                                                                                                           | Schema |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>amount</b><br><i>optional</i>              | Amount of the fare. could be alpha numeric. Ex- 500.20 or 514.13A, 'A' signifies additional collection.<br><b>Example :</b> "4871.81" | string |
| <b>currency</b><br><i>optional</i>            | Currency type of the fare.<br><b>Example :</b> "CAD"                                                                                  | string |
| <b>elementaryPriceType</b><br><i>optional</i> | Defines the price type, e.g. for base fare, total...<br><b>Example :</b> ""                                                           | string |

## Email

Email information.

| Name                              | Description                                                | Schema |
|-----------------------------------|------------------------------------------------------------|--------|
| <b>address</b><br><i>optional</i> | Email address<br><b>Example</b> : "james.carter@gmail.com" | string |

## EventLog

Contains the when/how/who of a particular change.

| Name                                       | Description                                                                                                                                                                                                              | Schema                      |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| <b>dateTime</b><br><i>optional</i>         | Date/Time in UTC of the change.<br><b>Example</b> : "2018-10-03T09:35:42.000Z"                                                                                                                                           | string                      |
| <b>id</b><br><i>optional</i>               | Identifier of the change<br><b>Example</b> : "64GqpZfbcAW61PtL"                                                                                                                                                          | string                      |
| <b>pointOfSale</b><br><i>optional</i>      |                                                                                                                                                                                                                          | <a href="#">PointOfSale</a> |
| <b>triggerEventName</b><br><i>optional</i> | Trigger of the message - set to 'DATA_INIT' for initialization messages Description of the overriding use case (promo-code discount, merchandising discounts, manual agent overrides...)<br><b>Example</b> : "DATA_INIT" | string                      |

## EventLogOverride

*Polymorphism* : Composition

| Name                                       | Description                                                                                                                                                                                                              | Schema                              |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| <b>changeLog</b><br><i>optional</i>        | Contains the old/new quotations values following an Override (promo / discount) change.                                                                                                                                  | < <a href="#">changeLog</a> > array |
| <b>dateTime</b><br><i>optional</i>         | Date/Time in UTC of the change.<br><b>Example</b> : "2018-10-03T09:35:42.000Z"                                                                                                                                           | string                              |
| <b>id</b><br><i>optional</i>               | Identifier of the change<br><b>Example</b> : "64GqpZfbcAW61PtL"                                                                                                                                                          | string                              |
| <b>pointOfSale</b><br><i>optional</i>      |                                                                                                                                                                                                                          | <a href="#">PointOfSale</a>         |
| <b>triggerEventName</b><br><i>optional</i> | Trigger of the message - set to 'DATA_INIT' for initialization messages Description of the overriding use case (promo-code discount, merchandising discounts, manual agent overrides...)<br><b>Example</b> : "DATA_INIT" | string                              |

**changeLog**

| Name                                | Description                                                    | Schema |
|-------------------------------------|----------------------------------------------------------------|--------|
| <b>logType</b><br><i>optional</i>   | Defines the type of log.<br><b>Example :</b> "EntityChangeLog" | string |
| <b>newEntity</b><br><i>optional</i> | Current quotations valueq after override.                      | Price  |
| <b>oldEntity</b><br><i>optional</i> | Quotations values before override.                             | Price  |

## Events

Structure of Dynamic Intelligence Hub functional events

| Name                                          | Description                                                               | Schema                  |
|-----------------------------------------------|---------------------------------------------------------------------------|-------------------------|
| <b>events</b><br><i>optional</i>              | List of events that have been detected on the DCS Passenger document      | < <b>events</b> > array |
| <b>originFeedTimeStamp</b><br><i>optional</i> | Incoming PSS feed time stamp - only populated for ticket & emd feeds      | string                  |
| <b>recordDomain</b><br><i>optional</i>        | Functional domain of the record<br><b>Example :</b> "TICKET_DCSPASSENGER" | string                  |
| <b>recordId</b><br><i>optional</i>            | Ticket ID or EMD ID<br><b>Example :</b> "0142100147468-2018-10-18"        | string                  |

### events

| Name                                   | Description                                                                                                                                                                                                               | Schema                           |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| <b>currentPath</b><br><i>optional</i>  | String containing the JSON Pointer (see IETF RFC6901) that points to the data referenced by the Event in the latest version of the entity. It is only applicable for CREATED and UPDATED events.<br><b>Example :</b> ""   | string                           |
| <b>eventType</b><br><i>optional</i>    | In case of comparison events, type of operation notified by the event<br><b>Example :</b> "CREATED"                                                                                                                       | enum (CREATED, UPDATED, DELETED) |
| <b>origin</b><br><i>optional</i>       | Type of event e.g. 'COMPARISON' / 'TIME_INITIATED_EVENT'<br><b>Example :</b> "COMPARISON"                                                                                                                                 | string                           |
| <b>previousPath</b><br><i>optional</i> | String containing the JSON Pointer (see IETF RFC6901) that points to the data referenced by the Event in the previous version of the entity. It is only applicable for DELETED and UPDATED events.<br><b>Example :</b> "" | string                           |

## FareBasis

Composed of codes used by airlines to identify the type of a fare proposed to the booker and to allow airline staff and travel agents to find the rules applicable to that fare.

| Name                                    | Description                                                                                                   | Schema |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------|--------|
| <b>fareBasisCode</b><br><i>optional</i> | Defines the code of the fare delivered to the booker - up to 6 alphanumerical chars<br><b>Example :</b> "TTI" | string |

## FareCalculation

Provides details on the type of pricing applied to the product.

| Name                                       | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Schema |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>pricingIndicator</b><br><i>optional</i> | <p>The Fare Calculation Pricing Indicator provides a granular view of the pricing mode that has been used during the pricing. Thanks to the FCPI, the travel agency, the airline or any user can know what pricing combinations have been used at pricing time. 0: Automatically priced 1: Manually created or updated TST. 2: No fare: free or charter entered in the TST. 3: Pricing by fare basis. 4: Manual manipulation of taxes and/or fees at pricing or issuance time. 5: The system did not price according to the entered passenger type. 6: For US only: Exchange ticket request 7: Bulk fare ticket request 8: Fare price override at issuance time 9: Inclusive tour ticket request A: SATA fare used. B: Amount discount override applied to fare base at pricing time. C: Amount or percent discount override applied to total fare combined with segment selection at pricing time. D: Amount or percent discount override applied to base fare combined with segment selection at pricing time. E: Percentage discount override at pricing time. F: Private fares have been used at pricing time. G: Dynamic discounted fare used at pricing time. H: HIP may apply. The system has priced but is unable to check a higher intermediate point. I: Override Fare Calculation by M/IT at pricing time. J: Override fare diagnostic entry at pricing time. K: Override Fare Calculation by M/BT at pricing time L: Booking date override M: Negotiated rates have been used at pricing time. Agent/consolidator is a fare updater. N: Negotiated rates have been used at pricing time. Airline is a fare updater. O: Past date TST override at issuance time. P: Lowest possible fare override at pricing time. Q: Depends on TSTIndicator. Either Manually stored endorsement before pricing or Manually added a tour code (FT element) on a private or public fare R: Validating carrier override at issuance time. S: Booking class override used on negotiated fares. T: Amount discount override applied to Total fare at pricing time. U: Stopover/transfer override is used in the pricing entry. V: Pricing override used with a pricing past date. W: Booking class override used on non-negotiated fares. Z: Net fare field manually updated (not used in US market)</p> <p><b>Example :</b> "0"</p> | string |
| <b>text</b><br><i>optional</i>             | <p>Content of the fare calculation.</p> <p><b>Example :</b> "PAR 6X YTO289.85SKWI5LGT 6X PAR289.85SKWI5LGT NUC579.70END ROE0.862490"</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | string |

## FareComponent

Fare Component is a basic item that composes Fare Calculation of the base fare on a Fare quote.

| Name                                    | Description                                           | Schema                                 |
|-----------------------------------------|-------------------------------------------------------|----------------------------------------|
| <b>couponRefs</b><br><i>optional</i>    | used to identify the Coupons related to the component | < <a href="#">Relationship</a> > array |
| <b>endCityCode</b><br><i>optional</i>   | Defines the ending city of the Fare Component         | <a href="#">Location</a>               |
| <b>id</b><br><i>optional</i>            | Indicates the identifier of the FareComponent         | integer                                |
| <b>price</b><br><i>optional</i>         |                                                       | <a href="#">Price</a>                  |
| <b>startCityCode</b><br><i>optional</i> | Defines the starting city of the Fare Component       | <a href="#">Location</a>               |

## FareFamily

A method of identifying multiple fare classes in a single entry.

| Name                            | Description                                                       | Schema |
|---------------------------------|-------------------------------------------------------------------|--------|
| <b>code</b><br><i>optional</i>  | Defines the code of Fare Family<br><b>Example :</b> "ELIGHT"      | string |
| <b>owner</b><br><i>optional</i> | Defines the company owner of Fare Family<br><b>Example :</b> "8X" | string |

## Fee

Structure to describe a Fee applied to provide a service or a product to the client. Each type of fees is assigned a code, a 3-digit subcode and a commercial name.

| Name                               | Description                                                                                                                        | Schema                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| <b>amount</b><br><i>optional</i>   | Defines amount with decimal separator.                                                                                             | string                        |
| <b>code</b><br><i>optional</i>     | Indicates the type of fee. Ex- "OB"                                                                                                | string                        |
| <b>currency</b><br><i>optional</i> | Defines a monetary unit. It is a three alpha code. Example: EUR for Euros, USD for US dollar, etc.                                 | string                        |
| <b>subCode</b><br><i>optional</i>  | Identify uniquely the OB fee associated to the TST- 1. Automated ticketing subcode (Txx) 2. Non-automated ticketing subcodes (Rxx) | string                        |
| <b>taxes</b><br><i>optional</i>    |                                                                                                                                    | < <a href="#">Tax</a> > array |

## FlightDesignator

| Name                                        | Description                                                                                                        | Schema |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------|--------|
| <b>carrierCode</b><br><i>optional</i>       | Two letter IATA standard carrier code<br><b>Length</b> : 1 - 2<br><b>Example</b> : "6X"                            | string |
| <b>flightNumber</b><br><i>optional</i>      | The flight number as assigned by the carrier - 1-4 digit number<br><b>Length</b> : 1 - 4<br><b>Example</b> : "555" | string |
| <b>operationalSuffix</b><br><i>optional</i> | The flight number suffix as assigned by the carrier - 1 char<br><b>Example</b> : "A"                               | string |

## FlightEndPoint

Departure or arrival information

| Name                                    | Description                                                                                                       | Schema |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------|--------|
| <b>iataCode</b><br><i>optional</i>      | IATA Airport code<br><b>Example</b> : "LHR"                                                                       | string |
| <b>localDateTime</b><br><i>optional</i> | Local date and time with the following format \ yyyy-mm-ddThh:mm:ss<br><b>Example</b> : "2018-10-03T09:35:42.000" | string |

## FlightSegment

Defining a flight segment, including both Operating and Marketing details when applicable.

| Name                                   | Description                                                                                      | Schema                         |
|----------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------|
| <b>arrival</b><br><i>optional</i>      |                                                                                                  | <a href="#">FlightEndPoint</a> |
| <b>bookingClass</b><br><i>optional</i> |                                                                                                  | <a href="#">BookingClass</a>   |
| <b>carrierCode</b><br><i>optional</i>  | The airline / carrier code<br><b>Length</b> : 1 - 2<br><b>Example</b> : "6X"                     | string                         |
| <b>departure</b><br><i>optional</i>    |                                                                                                  | <a href="#">FlightEndPoint</a> |
| <b>number</b><br><i>optional</i>       | The flight number as assigned by the carrier.<br><b>Length</b> : 1 - 4<br><b>Example</b> : "123" | string                         |

| Name                                | Description                                                                                           | Schema                          |
|-------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------|
| <b>operating</b><br><i>optional</i> |                                                                                                       | <a href="#">OperatingFlight</a> |
| <b>suffix</b><br><i>optional</i>    | The flight number suffix as assigned by the carrier.<br><b>Length</b> : 1 - 4<br><b>Example</b> : "C" | string                          |

## FormOfIdentification

Alternative means of identifying stakeholders.

| Name                                                    | Description                                                               | Schema                                                                                                                        |
|---------------------------------------------------------|---------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>identification</b><br><b>Type</b><br><i>optional</i> | Indicates type of passenger identification number                         | enum (CREDIT_CARD, DRIVERS_LICENSE, FREQUENT_FLYER, PASSPORT, NATIONAL_IDENTITY_CARD, BOOKING_CONFIRMATION, TICKET, OTHER_ID) |
| <b>number</b><br><i>optional</i>                        | The actual form of identification number.<br><b>Example</b> : "012345678" | string                                                                                                                        |

## FrequentFlyer

| Name                                            | Description                                                                                        | Schema |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------|--------|
| <b>applicableAirlineCode</b><br><i>optional</i> | Code of the airline for which frequent traveller data has been added.<br><b>Example</b> : "6X"     | string |
| <b>frequentFlyerNumber</b><br><i>optional</i>   | A code to identify a frequent traveller - Loyalty card number<br><b>Example</b> : "6X090807061234" | string |

## Included

| Name                                                 | Description                                               | Schema                                                     |
|------------------------------------------------------|-----------------------------------------------------------|------------------------------------------------------------|
| <b>correlationEmdDcsPassenger</b><br><i>optional</i> | Correlation resource - EMD correlation with DCS Passenger | < string, <a href="#">CorrelationEmdDcsPassenger</a> > map |

| Name                                                    | Description                                                       | Schema                                                        |
|---------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------|
| <b>correlationEmdMembership</b><br><i>optional</i>      | Correlation resource - EMD correlation with Loyalty Membership    | < string, <a href="#">CorrelationEmdMembership</a> > map      |
| <b>correlationEmdPnr</b><br><i>optional</i>             | Correlation resource - EMD correlation with Passenger Name Record | < string, <a href="#">CorrelationEmdPnr</a> > map             |
| <b>correlationTicketDcsPassenger</b><br><i>optional</i> | Correlation resource - Ticket correlation with DCS Passenger      | < string, <a href="#">CorrelationTicketDcsPassenger</a> > map |
| <b>correlationTicketInventory</b><br><i>optional</i>    | Correlation resource - Ticket correlation with Inventory          | < string, <a href="#">CorrelationTicketInventory</a> > map    |
| <b>correlationTicketMembership</b><br><i>optional</i>   | Correlation resource - Ticket correlation with Loyalty Membership | < string, <a href="#">CorrelationTicketMembership</a> > map   |
| <b>correlationTicketPnr</b><br><i>optional</i>          | Correlation resource - Ticket correlation with PNR                | < string, <a href="#">CorrelationTicketPnr</a> > map          |
| <b>correlationTicketSchedule</b><br><i>optional</i>     | Correlation resource - Ticket correlation with Schedule           | < string, <a href="#">CorrelationTicketSchedule</a> > map     |

## IssueSource

an object containing references to the source of the error

| Name                                | Description                                                               | Schema |
|-------------------------------------|---------------------------------------------------------------------------|--------|
| <b>parameter</b><br><i>optional</i> | A string indicating which URI query parameter caused the issue            | string |
| <b>pointer</b><br><i>optional</i>   | A JSON Pointer [RFC6901] to the associated entity in the request document | string |

## Location

Description of a particular point or place in physical space

| Name                               | Description        | Schema |
|------------------------------------|--------------------|--------|
| <b>iataCode</b><br><i>optional</i> | IATA location code | string |

## Membership

| Name                                     | Description                                                                                                                        | Schema               |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| <b>activeTier</b><br><i>optional</i>     |                                                                                                                                    | <a href="#">Tier</a> |
| <b>id</b><br><i>optional</i>             | Identifies the customer profile i.e. either Frequent Flyer Number or Corporate Recognition Number<br><b>Example</b> : "1234567890" | string               |
| <b>membershipType</b><br><i>optional</i> | Nature of the membership<br><b>Example</b> : "INDIVIDUAL"                                                                          | enum (INDIVIDUAL)    |

## Meta

Technical information related to the feed

| Name                                      | Description                                                       | Schema                   |
|-------------------------------------------|-------------------------------------------------------------------|--------------------------|
| <b>triggerEventLog</b><br><i>optional</i> | information related to the initial event that trigger the process | <a href="#">EventLog</a> |
| <b>version</b><br><i>optional</i>         | Version of the JSON feed produced<br><b>Example</b> : "4.3.0"     | string                   |

## Name

Description of the name of a physical person.

| Name                                | Description               | Schema |
|-------------------------------------|---------------------------|--------|
| <b>firstName</b><br><i>optional</i> | <b>Example</b> : "JAMES"  | string |
| <b>lastName</b><br><i>optional</i>  | <b>Example</b> : "CARTER" | string |

## NegoFareContract

Nature and reference of the commercial agreement by which the airline provides incentives to the selling travel agency for the quoted negotiated fare. This specific type of fare is used in conjunction with tours, referring to Inclusive Tour fares and Bulk Tour fares. The agent incentive on the IT/BT

fare notably depends on the commission element entered in PNR.

| Name                                      | Description                                                                                                                 | Schema                                                                                                                    |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| <b>incentiveScheme</b><br><i>optional</i> | Nature of the agreement between the airline and the selling travel agency                                                   | enum (NET_REMIT, INCLUSIVE_TOUR, BULK_TOUR, INCLUSIVE_TOUR_WITH_NET_REMIT, BULK_TOUR_WITH_NET_REMIT, FLEXIBLE_COMMISSION) |
| <b>tourCode</b><br><i>optional</i>        | Used when a published tour or a special negotiated fare is sold in conjunction with the ticket<br><b>Example :</b> "TOUR99" | string                                                                                                                    |

## OperatingFlight

Information about the marketing flight

| Name                                       | Schema                           |
|--------------------------------------------|----------------------------------|
| <b>flightDesignator</b><br><i>optional</i> | <a href="#">FlightDesignator</a> |

## PatchOperation

A single JSON Patch operation as defined by RFC 6902 (see <https://tools.ietf.org/html/rfc6902>)

| Name                            | Description                                                                                                                        | Schema                                        |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <b>from</b><br><i>optional</i>  | A JSON Pointer as defined by RFC 6901 (see <a href="https://tools.ietf.org/html/rfc6901">https://tools.ietf.org/html/rfc6901</a> ) | string                                        |
| <b>op</b><br><i>required</i>    | The operation to be performed                                                                                                      | enum (add, remove, replace, move, copy, test) |
| <b>path</b><br><i>required</i>  | A JSON Pointer as defined by RFC 6901 (see <a href="https://tools.ietf.org/html/rfc6901">https://tools.ietf.org/html/rfc6901</a> ) | string                                        |
| <b>value</b><br><i>optional</i> | The value to be used within the operations                                                                                         | object                                        |

## PaymentCard

| Name                                       | Description                                                                                                                                           | Schema |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>expiryDate</b><br><i>optional</i>       | Expiration date of the card - format is month & year - MMY<br><b>Example :</b> "0318"                                                                 | string |
| <b>holderName</b><br><i>optional</i>       | Name of credit card holder.<br><b>Example :</b> "SMITH"                                                                                               | string |
| <b>maskedCardNumber</b><br><i>optional</i> | Masked credit card number<br><b>Example :</b> "444433999991118"                                                                                       | string |
| <b>vendorCode</b><br><i>optional</i>       | Vendor code in case the FOP is a credit card - designates the card brand. For instance, VI for Visa, CA for MasterCard, etc.<br><b>Example :</b> "CA" | string |

## PaymentLoyalty

| Name                                        | Description                                                                                                                                                            | Schema                     |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| <b>certificateNumber</b><br><i>optional</i> | Identifies an optional pool of miles provided by the airline owning the loyalty program that can be requested as input to the redemption request [FQTR/FQTU insertion] | string                     |
| <b>membership</b><br><i>optional</i>        | Loyalty profile used for award payment i.e. miles redemption/upgrade [for FOP codes 'FFP'/'FFU']                                                                       | <a href="#">Membership</a> |

## Phone

Phone information.

| Name                             | Description                                                                                                                                               | Schema |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>number</b><br><i>optional</i> | Phone number. Composed of digits only. The number of digits depends on the country.<br><b>Pattern :</b> "[0-9]{1,15}"<br><b>Example :</b> "0033612345678" | string |

## PointOfSale

| Name                             | Schema                 |
|----------------------------------|------------------------|
| <b>login</b><br><i>optional</i>  | <a href="#">login</a>  |
| <b>office</b><br><i>optional</i> | <a href="#">office</a> |

**login**

| Name                                   | Description                                                     | Schema |
|----------------------------------------|-----------------------------------------------------------------|--------|
| <b>cityCode</b><br><i>optional</i>     | city code of the issuing agent/system<br><b>Example :</b> "YUL" | string |
| <b>countryCode</b><br><i>optional</i>  | ISO country code of the agent<br><b>Example :</b> "CA"          | string |
| <b>currencyCode</b><br><i>optional</i> | ISO currency code of the agent<br><b>Example :</b> "CAD"        | string |
| <b>dutyCode</b><br><i>optional</i>     | duty code of the agent<br><b>Example :</b> "SU"                 | string |
| <b>initials</b><br><i>optional</i>     | agent initials<br><b>Example :</b> "JS"                         | string |
| <b>numericSign</b><br><i>optional</i>  | Authorization code of the agent<br><b>Example :</b> "2416"      | string |

## office

| Name                                            | Description                                                                                                                                                                            | Schema |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>agentType</b><br><i>optional</i>             | The issuing channel. AIRLINE_AGENT, TRAVEL_AGENT, WEB, NON_IATA_AGENT<br><b>Example :</b> "AIRLINE_AGENT"                                                                              | string |
| <b>iataNumber</b><br><i>optional</i>            | IATA assigned agency number<br><b>Example :</b> "00106137"                                                                                                                             | string |
| <b>id</b><br><i>optional</i>                    | An identifier for a corporate user of a computer reservation system or global distribution system, typically a travel agency, also known as office ID.<br><b>Example :</b> "NCE1A0980" | string |
| <b>inHouseIdentification</b><br><i>optional</i> | AMID- office id in Amadeus<br><b>Example :</b> "000000"                                                                                                                                | string |
| <b>systemCode</b><br><i>optional</i>            | 2-3 character airline/CRS code of the system that originates the current transaction or the issuance.<br><b>Example :</b> "1A"                                                         | string |

## Price

### Price valuation information

| Name                                  | Description                                      | Schema                               |
|---------------------------------------|--------------------------------------------------|--------------------------------------|
| <b>commissions</b><br><i>optional</i> | Commissions details                              | < <a href="#">Commission</a> > array |
| <b>currency</b><br><i>optional</i>    | currency Code apply to all elements of the price | string                               |

| Name                                     | Description                                                    | Schema                                    |
|------------------------------------------|----------------------------------------------------------------|-------------------------------------------|
| <b>detailedPrices</b><br><i>optional</i> |                                                                | < <a href="#">ElementaryPrice</a> > array |
| <b>discounts</b><br><i>optional</i>      | Exhaustive list of applied discounts                           | < <a href="#">Discount</a> > array        |
| <b>taxes</b><br><i>optional</i>          | Additional charge for external actors (government, airport...) | < <a href="#">Tax</a> > array             |
| <b>total</b><br><i>optional</i>          | Total = base + totalTaxes                                      | string                                    |
| <b>totalTaxes</b><br><i>optional</i>     |                                                                | string                                    |

## PriceCategory

AN EMD IS CATEGORISED BASED ON ITS REASON FOR ISSUANCE CODE (RFIC), WHICH DEFINES THE GROUP OF SERVICES IT BELONGS TO. THERE CAN ONLY BE ONE RFIC CODE PER EMD. SOME CODES ARE DEFINED BY IATA, HOWEVER, OTHERS CAN BE DEFINED BY INDIVIDUAL AIRLINES. AN EMD, AND EACH RFIC, CAN HAVE MULTIPLE REASON FOR ISSUANCE SUB-CODES (RFISC). THERE IS ONE RFISC IN EACH EMD COUPON AND THEY ARE AIRLINE-SPECIFIC.

| Name                                  | Description                                                                                                                | Schema |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------|--------|
| <b>code</b><br><i>optional</i>        | The reason for issuance code (RFIC) chargeability indicator defined for the sellable object<br><b>Example</b> : "E"        | string |
| <b>description</b><br><i>optional</i> | description of reason for issuance sub code<br><b>Example</b> : "Lounge Access"                                            | string |
| <b>subCode</b><br><i>optional</i>     | The reason for issuance sub code (RFISC) chargeability indicator defined for the sellable object<br><b>Example</b> : "0BX" | string |

## PricingConditions

Provides the context under which a product has been priced. Those conditions are dictated at pricing and can affect the subsequent issuance behaviour in terms of eligibility and processing.

| Name                                      | Description | Schema                                  |
|-------------------------------------------|-------------|-----------------------------------------|
| <b>fareCalculation</b><br><i>optional</i> |             | <a href="#">FareCalculation</a>         |
| <b>fareComponents</b><br><i>optional</i>  |             | < <a href="#">FareComponent</a> > array |

| Name                                           | Description                                                                                                                                                        | Schema                                     |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|
| <b>flightBounds</b><br><i>optional</i>         |                                                                                                                                                                    | < <a href="#">FareComponent</a> ><br>array |
| <b>isDomesticSale</b><br><i>optional</i>       | Domestic fare applied for the given itinerary                                                                                                                      | boolean                                    |
| <b>isInternationalSale</b><br><i>optional</i>  | International fare applied for the given itinerary                                                                                                                 | boolean                                    |
| <b>isNonEndorsable</b><br><i>optional</i>      | Indicates that the fare cannot be endorsed - false as default value<br><b>Example</b> : <b>false</b>                                                               | boolean                                    |
| <b>isNonExchangeable</b><br><i>optional</i>    | Indicates that the fare does not permit exchange operation - false as default value<br><b>Example</b> : <b>false</b>                                               | boolean                                    |
| <b>isNonRefundable</b><br><i>optional</i>      | Indicates that the fare does not permit refund operation - false as default value<br><b>Example</b> : <b>true</b>                                                  | boolean                                    |
| <b>isPenaltyRestriction</b><br><i>optional</i> | Penalty restriction indicator signifies if any penalty applies or not for example in case of cancellation. Default value is false<br><b>Example</b> : <b>false</b> | boolean                                    |
| <b>negoFareContract</b><br><i>optional</i>     |                                                                                                                                                                    | <a href="#">NegoFareContract</a>           |

## Relationship

| Name                              | Description                                                     | Schema |
|-----------------------------------|-----------------------------------------------------------------|--------|
| <b>href</b><br><i>optional</i>    | Only populated for correlated resources defined in Dictionaries | string |
| <b>id</b><br><i>optional</i>      |                                                                 | string |
| <b>ref</b><br><i>optional</i>     |                                                                 | string |
| <b>type</b><br><i>optional</i>    |                                                                 | string |
| <b>version</b><br><i>optional</i> | Only populated for correlated resources defined in Dictionaries | string |

# Stakeholder

Definition of the traveler.

| Name                                        | Description                                                                                                                                     | Schema                  |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| <b>contact</b><br><i>optional</i>           | Contact associated with the traveler.                                                                                                           | <a href="#">Contact</a> |
| <b>name</b><br><i>optional</i>              | Names of the stakeholder.                                                                                                                       | <a href="#">Name</a>    |
| <b>passengerTypeCode</b><br><i>optional</i> | 3-characters code defining the passenger type - possible values: ADT, CHD, INS, INF, UNA<br><b>Maximal length</b> : 3<br><b>Example</b> : "ADT" | string                  |

# Tax

| Name                                             | Description                                                                                                                                                                                                                                                                                                                                              | Schema                                                          |
|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|
| <b>amount</b><br><i>optional</i>                 | Defines amount with decimal separator.                                                                                                                                                                                                                                                                                                                   | string                                                          |
| <b>category</b><br><i>optional</i>               | Used to specify if the tax is New, Old or Refundable.                                                                                                                                                                                                                                                                                                    | enum (NEW, OLD, REFUNDABLE)                                     |
| <b>code</b><br><i>optional</i>                   | International Standards Organization (ISO) Tax code.                                                                                                                                                                                                                                                                                                     | string                                                          |
| <b>currency</b><br><i>optional</i>               | Defines a monetary unit. It is a three alpha code. Example: EUR for Euros, USD for US dollar, etc.                                                                                                                                                                                                                                                       | string                                                          |
| <b>isPaidInLoyaltyRewards</b><br><i>optional</i> | It is true when tax is paid in frequent flyer points. The Default value is false.                                                                                                                                                                                                                                                                        | boolean                                                         |
| <b>nature</b><br><i>optional</i>                 | Filling on SSP side.                                                                                                                                                                                                                                                                                                                                     | string                                                          |
| <b>ticketReportedStatuses</b><br><i>optional</i> | DISPLAYED Taxes displayed on the ticket according the IATA standard REPORTED Taxes displayed at ticket level with additional business codes specifics to AMADEUS EQUIVALENT_MONETARY_VALUE It is applicable only when isPaidInLoyaltyRewards = true, this is the corresponding monetary amount in a specific currency of a tax paid with LoyaltyRewards. | < enum (DISPLAYED, REPORTED, EQUIVALENT_MONETARY_VALUE) > array |

# TicketRefund

A ticket refund contains refund information in case of an eticket or EMD. Field farePaid indicates the amount of the original/equivalent fare issued in the current travel document. Field fareUsed is the non-refundable portion of fare applicable to the used coupons of the current travel document

[for example, flown coupons & exchanged coupons are considered as used]. Field fareRefund is the fare to be refunded for relative document. FARE PAID - FARE USED= FARE REFUND Fields refundTotal indicates the Total Refunded amount for the current travel document - it equals the sum of refunded fare amount and refunded tax amount, minus penalties & fees. Field penalty indicates the amount of the cancellation penalty that has been incurred and deducted from the Total Refund amount. Field noShowFee is the fee amount incurred because the refunded travel document contained at least one coupon flagged with the No Show indicator - this fee has been deducted from the Total Refunded amount.

| Name                                          | Description   | Schema                                           |
|-----------------------------------------------|---------------|--------------------------------------------------|
| <b>cancellationPenalty</b><br><i>optional</i> |               | <a href="#">ElementaryPrice</a>                  |
| <b>farePaid</b><br><i>optional</i>            |               | <a href="#">ElementaryPrice</a>                  |
| <b>fareRefund</b><br><i>optional</i>          |               | <a href="#">ElementaryPrice</a>                  |
| <b>fareUsed</b><br><i>optional</i>            |               | <a href="#">ElementaryPrice</a>                  |
| <b>noShowFee</b><br><i>optional</i>           |               | <a href="#">ElementaryPrice</a>                  |
| <b>obFees</b><br><i>optional</i>              |               | < <a href="#">Fee</a> > array                    |
| <b>paymentDetails</b><br><i>optional</i>      |               | < <a href="#">DisplayedFormOfPayment</a> > array |
| <b>refundRemark</b><br><i>optional</i>        | Refund remark | string                                           |
| <b>refundTotal</b><br><i>optional</i>         |               | <a href="#">ElementaryPrice</a>                  |
| <b>taxes</b><br><i>optional</i>               |               | < <a href="#">Tax</a> > array                    |
| <b>totalObFee</b><br><i>optional</i>          |               | <a href="#">ElementaryPrice</a>                  |
| <b>totalTax</b><br><i>optional</i>            |               | <a href="#">ElementaryPrice</a>                  |

## Tier

Description of a Tier in the context of the loyalty program - applicable to both Frequent Flyer profiles & Corporate profiles.

| Name                                    | Description                                                                                                                                                                                                             | Schema  |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| <b>companyCode</b><br><i>optional</i>   | Alliance code or airline code of the loyalty program<br><b>Example :</b> "6X"                                                                                                                                           | string  |
| <b>customerValue</b><br><i>optional</i> | Ranging from 0 to 9999, it measures the value of the customer [frequent flyer/corporation] for the airline depending on its profile, its travel history, potential and other internal factors.<br><b>Example :</b> 5000 | integer |

## TravelDocumentResponseData

*Polymorphism* : Composition

| Name                                                 | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Schema                                        |
|------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <b>associatedDocuments</b><br><i>optional</i>        | List of Associated Ticket or Associated EMD for the current document,e.g. EMD-A associated to an ETKT.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | < <a href="#">associatedDocuments</a> > array |
| <b>associatedPnr</b><br><i>optional</i>              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | < <a href="#">AssociatedPnr</a> > array       |
| <b>conjunctiveDocumentNumbers</b><br><i>optional</i> | <b>Example :</b> "0142100147468"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | < string > array                              |
| <b>correlations</b><br><i>optional</i>               | Correlation resources are defined in the "included" node. This node provides links to all correlations resources associated with the current processed-travel-document resource [TKT/EMD].<br><b>Example :</b> { "ticketPnr" : { "ref" : "included/correlationTicketPnr/1722500003153-2018-10-18" }, "ticketDcsPassenger" : { "ref" : "included/correlationTicketDcsPassenger/1722500003153-2018-10-18" }, "ticketSchedule" : { "ref" : "included/correlationTicketSchedule/1722500003153-2018-10-18" }, "ticketInventory" : { "ref" : "included/correlationTicketInventory/1722500003153-2018-10-18" }, "ticketMembership" : { "ref" : "included/correlationTicketMembership/1722500003153-2018-10-18" }, "emdPnr" : { "ref" : "included/correlationEmdPnr/1722500009467-2019-10-11" }, "emdDcsPassenger" : { "ref" : "included/correlationEmdDcsPassenger/1722500009467-2019-10-11" }, "emdMembership" : { "ref" : "included/correlationEmdMembership/1722500009467-2019-10-11" } } | <a href="#">correlations</a>                  |
| <b>coupons</b><br><i>optional</i>                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | < <a href="#">Coupon</a> > array              |
| <b>creation</b><br><i>optional</i>                   | Indicates the creation DateTime and the point of sale of the entity.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | <a href="#">EventLog</a>                      |

| Name                                              | Description                                                                                                                                            | Schema                                           |
|---------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| <b>destinationCityIataCode</b><br><i>optional</i> | destination city code<br><b>Example :</b> "LON"                                                                                                        | string                                           |
| <b>dictionaries</b><br><i>optional</i>            |                                                                                                                                                        | <a href="#">Dictionaries</a>                     |
| <b>documentRefund</b><br><i>optional</i>          |                                                                                                                                                        | <a href="#">TicketRefund</a>                     |
| <b>documentType</b><br><i>optional</i>            | Type of document<br><b>Example :</b> "TICKET"                                                                                                          | enum (TICKET, EMD_ASSOCIATED, EMD_STANDALONE)    |
| <b>endorsementFreeFlow</b><br><i>optional</i>     | Used to identify any restrictions, airline comments, or rules that may apply to the ticket/EMD<br><b>Example :</b> "FARE RESTRICTION MAY APPLY -BG 6X" | string                                           |
| <b>formsOfIdentification</b><br><i>optional</i>   |                                                                                                                                                        | < <a href="#">FormOfIdentification</a> > array   |
| <b>formsOfPayment</b><br><i>optional</i>          |                                                                                                                                                        | < <a href="#">DisplayedFormOfPayment</a> > array |
| <b>id</b><br><i>optional</i>                      | id of ticket or EMD.<br><b>Example :</b> "0142100147468-2018-10-18"                                                                                    | string                                           |
| <b>issuanceType</b><br><i>optional</i>            | Indicates the type of transaction.<br><b>Example :</b> "FIRST_ISSUE"                                                                                   | enum (FIRST_ISSUE, REISSUE)                      |
| <b>latestEvent</b><br><i>optional</i>             | Indicates the last updated DateTime. Indicate the last point of sale of the entity. Indicate code to depict message function.                          | <a href="#">EventLog</a>                         |
| <b>numberOfBooklets</b><br><i>optional</i>        | Number of conjunctive tickets/EMDs in the document.<br><b>Example :</b> 1.0                                                                            | number                                           |
| <b>originCityIataCode</b><br><i>optional</i>      | origin city code<br><b>Example :</b> "PAR"                                                                                                             | string                                           |
| <b>originalDocuments</b><br><i>optional</i>       | The ticket(s) against which this ticket was exchanged and the original local DateTime of the document issuance.                                        | < <a href="#">originalDocuments</a> > array      |
| <b>originalIssueFreeFlow</b><br><i>optional</i>   | Original issue information in free text. Not formatted on ETS.<br><b>Example :</b> "Freetext"                                                          | string                                           |
| <b>price</b><br><i>optional</i>                   |                                                                                                                                                        | <a href="#">Price</a>                            |

| Name                                            | Description                                                                                                                                                                                                                                                                                                                                                                                            | Schema                                        |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <b>pricingConditions</b><br><i>optional</i>     |                                                                                                                                                                                                                                                                                                                                                                                                        | <a href="#">PricingConditions</a>             |
| <b>primaryDocumentNumber</b><br><i>optional</i> | Ticket primary number or EMD primary number<br><b>Example :</b> "0142100147468"                                                                                                                                                                                                                                                                                                                        | string                                        |
| <b>quotationOverrides</b><br><i>optional</i>    | The aim of the override element is to enable an agent to override quotation data and to keep track of all the changes along with the reason for the changes. Overrides are applied on quotation documents [TST] and are automatically populated into the travel document at issuance. To create an override element, an agent needs to provide one override type and one reason code at the same time. | < <a href="#">EventLogOverride</a> ><br>array |
| <b>traveler</b><br><i>optional</i>              | Traveler information.                                                                                                                                                                                                                                                                                                                                                                                  | <a href="#">Stakeholder</a>                   |
| <b>validatingCarrierCode</b><br><i>optional</i> | Ticket validating carrier code<br><b>Example :</b> "6X"                                                                                                                                                                                                                                                                                                                                                | string                                        |
| <b>validatingCarrierPnr</b><br><i>optional</i>  | Validating carrier record locator and owner of the record locator (Validating carrier code/Ticketing Online Feed user code if not validating/booking GDS code)                                                                                                                                                                                                                                         | <a href="#">AssociatedPnr</a>                 |
| <b>version</b><br><i>optional</i>               | An identifier to track the sequential flow of messages. Epoch format.<br><b>Example :</b> "1586867381"                                                                                                                                                                                                                                                                                                 | string                                        |
| <b>void</b><br><i>optional</i>                  | Is only filled when a ticket status becomes void (DateTime information in ISO6081 format)                                                                                                                                                                                                                                                                                                              | <a href="#">EventLog</a>                      |

#### associatedDocuments

| Name                                     | Description                                                                                                                                                                   | Schema                                        |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <b>documentNumber</b><br><i>optional</i> | Identifier of the travel document prefixed by its owner code [NALC - 3 digits]. Can either be a primary or a conjunctive document number.<br><b>Example :</b> "0142100147468" | string                                        |
| <b>documentType</b><br><i>optional</i>   | Type of document<br><b>Example :</b> "EMD_ASSOCIATED"                                                                                                                         | enum (TICKET, EMD_ASSOCIATED, EMD_STANDALONE) |

#### correlations

| Name                                         | Schema                       |
|----------------------------------------------|------------------------------|
| <b>emdDcsPassenger</b><br><i>optional</i>    | <a href="#">Relationship</a> |
| <b>emdMembership</b><br><i>optional</i>      | <a href="#">Relationship</a> |
| <b>emdPnr</b><br><i>optional</i>             | <a href="#">Relationship</a> |
| <b>ticketDcsPassenger</b><br><i>optional</i> | <a href="#">Relationship</a> |
| <b>ticketInventory</b><br><i>optional</i>    | <a href="#">Relationship</a> |
| <b>ticketMembership</b><br><i>optional</i>   | <a href="#">Relationship</a> |
| <b>ticketPnr</b><br><i>optional</i>          | <a href="#">Relationship</a> |
| <b>ticketSchedule</b><br><i>optional</i>     | <a href="#">Relationship</a> |

### originalDocuments

| Name                                     | Description                                                                                                                                                                   | Schema                                        |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <b>creation</b><br><i>optional</i>       | Indicates the creation DateTime of the entity.                                                                                                                                | <a href="#">EventLog</a>                      |
| <b>documentNumber</b><br><i>optional</i> | Identifier of the travel document prefixed by its owner code [NALC - 3 digits]. Can either be a primary or a conjunctive document number.<br><b>Example :</b> "0142100147468" | string                                        |
| <b>documentType</b><br><i>optional</i>   | Type of document<br><b>Example :</b> "TICKET"                                                                                                                                 | enum (TICKET, EMD_ASSOCIATED, EMD_STANDALONE) |

## Weight

An object representing weight and unit.

| Name                             | Description                                                                                         | Schema                   |
|----------------------------------|-----------------------------------------------------------------------------------------------------|--------------------------|
| <b>amount</b><br><i>optional</i> | Defines the weight value with the specified unit with decimal position.<br><b>Example :</b> "125,5" | string                   |
| <b>unit</b><br><i>optional</i>   | The unit of measurement used for the weight value.                                                  | enum (KILOGRAMS, POUNDS) |

## emdDataPush

| Name                                     | Description                                                                                                                                                                                                                                                                                                         | Schema                                   |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|
| <b>events</b><br><i>optional</i>         |                                                                                                                                                                                                                                                                                                                     | <a href="#">Events</a>                   |
| <b>meta</b><br><i>optional</i>           |                                                                                                                                                                                                                                                                                                                     | <a href="#">Meta</a>                     |
| <b>previousRecord</b><br><i>optional</i> | Representation of the previous version of the record in the form of JSON Patch as defined by RFC 6902 (see <a href="https://tools.ietf.org/html/rfc6902">https://tools.ietf.org/html/rfc6902</a> ). The actual JSON of this previous record needs to be built using the latest version and applying the JSON patch. | < <a href="#">PatchOperation</a> > array |
| <b>processedEmd</b><br><i>optional</i>   |                                                                                                                                                                                                                                                                                                                     | <a href="#">AirTravelDocument</a>        |

## ticketDataPush

| Name                                      | Description                                                                                                                                                                                                                                                                                                         | Schema                                   |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|
| <b>events</b><br><i>optional</i>          |                                                                                                                                                                                                                                                                                                                     | <a href="#">Events</a>                   |
| <b>meta</b><br><i>optional</i>            |                                                                                                                                                                                                                                                                                                                     | <a href="#">Meta</a>                     |
| <b>previousRecord</b><br><i>optional</i>  | Representation of the previous version of the record in the form of JSON Patch as defined by RFC 6902 (see <a href="https://tools.ietf.org/html/rfc6902">https://tools.ietf.org/html/rfc6902</a> ). The actual JSON of this previous record needs to be built using the latest version and applying the JSON patch. | < <a href="#">PatchOperation</a> > array |
| <b>processedTicket</b><br><i>optional</i> |                                                                                                                                                                                                                                                                                                                     | <a href="#">AirTravelDocument</a>        |

## ticketingCorrelationsPush

| Name                                            | Schema                                |
|-------------------------------------------------|---------------------------------------|
| <b>events</b><br><i>optional</i>                | <a href="#">Events</a>                |
| <b>meta</b><br><i>optional</i>                  | <a href="#">Meta</a>                  |
| <b>ticketingCorrelations</b><br><i>optional</i> | <a href="#">ticketingCorrelations</a> |

## ticketingCorrelations

| Name                                                    | Schema                                        |
|---------------------------------------------------------|-----------------------------------------------|
| <b>correlationEmdDcsPassenger</b><br><i>optional</i>    | <a href="#">CorrelationEmdDcsPassenger</a>    |
| <b>correlationEmdMembership</b><br><i>optional</i>      | <a href="#">correlationEmdMembership</a>      |
| <b>correlationEmdPnr</b><br><i>optional</i>             | <a href="#">CorrelationEmdPnr</a>             |
| <b>correlationTicketDcsPassenger</b><br><i>optional</i> | <a href="#">CorrelationTicketDcsPassenger</a> |
| <b>correlationTicketInventory</b><br><i>optional</i>    | <a href="#">CorrelationTicketInventory</a>    |
| <b>correlationTicketMembership</b><br><i>optional</i>   | <a href="#">correlationTicketMembership</a>   |
| <b>correlationTicketPnr</b><br><i>optional</i>          | <a href="#">CorrelationTicketPnr</a>          |
| <b>correlationTicketSchedule</b><br><i>optional</i>     | <a href="#">CorrelationTicketSchedule</a>     |
| <b>dictionaries</b><br><i>optional</i>                  | <a href="#">Dictionaries</a>                  |

## travelDocumentApiResponse

| Name                                   | Schema                                     |
|----------------------------------------|--------------------------------------------|
| <b>data</b><br><i>optional</i>         | <a href="#">TravelDocumentResponseData</a> |
| <b>dictionaries</b><br><i>optional</i> | <a href="#">Dictionaries</a>               |
| <b>included</b><br><i>optional</i>     | <a href="#">Included</a>                   |
| <b>meta</b><br><i>optional</i>         | <a href="#">Meta</a>                       |

# Security

## basicAuth

HTTP Basic Authentication. Works 'HTTPS'.

*Type* : basic