

Dynamic Intelligence Hub

PNR Open Api Specification

Table of Contents

Dynamic Intelligence Hub Data Model - PassengerNameRecord	1
Overview	2
Version information	2
Paths	3
PNR Correlations DataPush Feed	3
PNR DataPush Feed	8
Definitions	28
AcceptanceDelivery	28
AccountingElement	29
Address	30
AirTravelDocument	30
AircraftEquipment	32
AssociatedPnr	32
Authorization	33
AutomatedProcess	33
Bag	34
BagLegDelivery	35
BagTag	35
BagsGroup	36
BoardingDelivery	36
BoardingPassPrint	37
BookingClass	37
Cabin	37
Comment	38
CommentDelivery	38
Commission	38
Commissions	39
Compensation	40
CompensationReason	40
ConnectedFlightSegments	40
Contact	40
CorrelatedDataPnrBagLeg	41
CorrelatedDataPnrBagsGroup	42
CorrelatedDataPnrDcsPassenger	42
CorrelatedDataPnrEmd	42
CorrelatedDataPnrInventory	43
CorrelatedDataPnrMemberships	43
CorrelatedDataPnrSchedule	44

CorrelatedDataPnrTicket	44
CorrelationPnrBagsGroup	44
CorrelationPnrDcsPassenger	45
CorrelationPnrEmd	45
CorrelationPnrInventory	45
CorrelationPnrMembership	46
CorrelationPnrSchedule	46
CorrelationPnrTicket	47
CorrelationReferences	47
Coupon	48
CurrencyConversionLookupRates	50
Dictionaries	50
DisplayedFormOfPayment	51
ElementaryPrice	52
Email	52
EventLog	52
Events	53
FareBasis	54
FareCalculation	54
FareElement	55
Fee	56
FlightBoundItem	57
FlightBounds	57
FlightDesignator	58
FlightEndPoint	59
FlightSegment	59
FlightTransfer	60
IdentityDocument	61
IncludedResources	62
InfrastructureLocation	62
InterAirlineThroughCheckIn	63
InterAirlineThroughCheckIn_FlightSegment	63
IssueSource	63
LegDelivery	64
Login	64
MarketingFlight	65
Membership	65
Meta	66
Name	66
NegoFareContract	67
Office	67

Onload	68
OperatingFlight	68
PassengerDelivery	69
PassengerDelivery_Stakeholder	69
PatchOperation	70
PaymentCard	70
PaymentLoyalty.....	70
Phone	71
PnrCorrelationsFeedData	71
PnrCorrelationsPushFeed	71
PnrFeedData.....	72
PnrHeader	74
PnrPushFeed	75
PointOfSale	76
Price	76
PriceCategory.....	76
PricingConditions	77
Product	78
QuotationRecord	78
Regrade	80
RegulatoryChecks	82
RegulatoryComment	82
RegulatoryProgram	82
RegulatoryStatus	83
Relationship	83
Remark	84
Seat	84
SeatingDelivery	85
SegmentDelivery	85
SegmentDelivery_FlightSegment	86
Service	86
ServiceProvider	88
SpecialBagHandling	88
Stakeholder.....	89
Stakeholder_Passenger	91
SubClass.....	91
Tax	91
TicketingReference	92
Tier	93
TimeLocationTrackingLog	94
TravelersGroup	94

Dynamic Intelligence Hub Data Model - PassengerNameRecord

Overview

This document describes DIH output for PassengerNameRecord Data Push Feed

Version information

Version : 3.2.0

Paths

PNR Correlations DataPush Feed

POST /reservation/pnr-correlations-feed

Description

PNR correlations feed pushed by Amadeus DIH. Please note this is NOT a POST API - this section is only used to specify the data model pushed.

Responses

HTTP Code	Description	Schema
default	PNR Correlations Data Push Feed	PnrCorrelationsPushFeed

Tags

- FEED

Example HTTP response

Response default

```
{
  "meta" : {
    "triggerEventLog" : {
      "id" : "429074ef1bd011e3-e63dfe23f4a0adc",
      "triggerEventName" : "DATA_INIT"
    },
    "version" : "3.2.0"
  },
  "pnrCorrelations" : {
    "correlationPnrTicket" : {
      "pnrId" : "ZAY091-2019-10-05",
      "ticketIds" : [ "1721234567890-2019-10-05", "1721234509876-2019-10-05" ],
      "correlatedData" : [ {
        "1721234567890-2019-10-05" : [ {
          "ticketCouponId" : "1721234567890-2019-10-05-1",
          "pnrTravelerId" : "ZAY091-2019-10-05-PT-1",
          "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-1",
          "pnrTicketingReferenceId" : "ZAY091-2019-10-05-OT-10"
        }, {
          "ticketCouponId" : "1721234567890-2019-10-05-2",
```



```

        "pnrTravelerId" : "ZAY091-2019-10-05-PT-1",
        "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-2",
        "pnrTicketingReferenceId" : "ZAY091-2019-10-05-OT-10"
    } ]
}, {
    "1721234509876-2019-10-05" : [ {
        "ticketCouponId" : "1721234509876-2019-10-05-1",
        "pnrTravelerId" : "ZAY091-2019-10-05-PT-2",
        "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-1",
        "pnrTicketingReferenceId" : "ZAY091-2019-10-05-OT-12"
    }, {
        "ticketCouponId" : "1721234509876-2019-10-05-2",
        "pnrTravelerId" : "ZAY091-2019-10-05-PT-2",
        "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-2",
        "pnrTicketingReferenceId" : "ZAY091-2019-10-05-OT-12"
    } ]
} ]
},
"correlationPnrEmd" : {
    "pnrId" : "ZAY091-2019-10-05",
    "emdIds" : [ "1729999999999-2019-10-05", "1725555555555-2019-10-05" ],
    "correlatedData" : [ {
        "1729999999999-2019-10-05" : [ {
            "emdCouponId" : "1729999999999-2019-10-05-1",
            "pnrTravelerId" : "ZAY091-2019-10-05-PT-1",
            "pnrServiceId" : "ZAY091-2019-10-05-OT-5",
            "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-1",
            "pnrTicketingReferenceId" : "ZAY091-2019-10-05-OT-19"
        } ]
    }, {
        "1725555555555-2019-10-05" : [ {
            "emdCouponId" : "1725555555555-2019-10-05-1",
            "pnrTravelerId" : "ZAY091-2019-10-05-PT-2",
            "pnrServiceId" : "ZAY091-2019-10-05-OT-6",
            "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-1",
            "pnrTicketingReferenceId" : "ZAY091-2019-10-05-OT-19"
        } ]
    } ]
} ]
},
"correlationPnrDcsPassenger" : {
    "pnrId" : "ZAY091-2019-10-05",
    "dcsPassengerIds" : [ "2501ADE0000001", "2501ADE0000005" ],
    "correlatedData" : [ {
        "2501ADE0000001" : [ {
            "pnrTravelerId" : "ZAY091-2019-10-05-PT-1",
            "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-1",
            "dcsPassengerSegmentDeliveryId" : "2401CA10111110ID"
        }, {
            "pnrTravelerId" : "ZAY091-2019-10-05-PT-1",
            "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-2",
            "dcsPassengerSegmentDeliveryId" : "2401CA10333330ID"
        } ]
    } ]
} ]

```

```

    } ]
  }, {
    "2501ADE0000005" : [ {
      "pnrTravelerId" : "ZAY091-2019-10-05-PT-2",
      "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-1",
      "dcsPassengerSegmentDeliveryId" : "2401CA10555550ID"
    }, {
      "pnrTravelerId" : "ZAY091-2019-10-05-PT-2",
      "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-2",
      "dcsPassengerSegmentDeliveryId" : "2401CA10999990ID"
    } ]
  } ]
},
"correlationPnrSchedule" : {
  "pnrId" : "ZAY091-2019-10-05",
  "scheduleIds" : [ "6X-123-2019-10-15", "6X-789-2019-10-25" ],
  "correlatedData" : [ {
    "6X-123-2019-10-15" : [ {
      "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-1",
      "scheduleSegmentId" : "2019-10-15-NCE-CDG"
    } ]
  }, {
    "6X-789-2019-10-25" : [ {
      "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-2",
      "scheduleSegmentId" : "2019-10-25-CDG-NCE",
      "schedulePartnershipId" : "6X-567-2019-10-25"
    } ]
  } ]
},
"correlationPnrInventory" : {
  "pnrId" : "ZAY091-2019-10-05",
  "inventoryIds" : [ "6X-123-2019-10-15", "6X-789-2019-10-25" ],
  "correlatedData" : [ {
    "6X-123-2019-10-15" : [ {
      "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-1",
      "inventorySegmentId" : "2019-10-15-NCE-CDG"
    } ]
  }, {
    "6X-789-2019-10-25" : [ {
      "pnrAirSegmentId" : "ZAY091-2019-10-05-ST-2",
      "inventorySegmentId" : "2019-10-25-CDG-NCE"
    } ]
  } ]
},
"correlationPnrBagsGroup" : {
  "pnrId" : "ZAY091-2018-10-19",
  "bagsGroupIds" : [ "AA42BA1395020102" ],
  "correlatedData" : {
    "AA42BA1395020102" : [ {
      "pnrTravelerId" : "ZAY091-2018-10-19-PT-1",
      "bagId" : "1101CA1100003431",

```

```

    "bagLegCorrelations" : [ {
      "pnrAirSegmentId" : "ZAY091-2018-10-19-ST-1",
      "bagLegDeliveryId" : "1101CA1100003431-ORY"
    } ]
  }, {
    "pnrTravelerId" : "ZAY091-2018-10-19-PT-2",
    "bagId" : "5550CA1100003555",
    "bagLegCorrelations" : [ {
      "pnrAirSegmentId" : "ZAY091-2018-10-19-ST-1",
      "bagLegDeliveryId" : "5550CA1100003555-ORY"
    } ]
  } ]
},
"correlationPnrMembership" : {
  "pnrId" : "ZAY091-2018-10-19",
  "membershipIds" : [ "6X-1234567890", "6X-1234567891" ],
  "correlatedData" : {
    "6X-1234567890" : [ {
      "pnrProductId" : "ZAY091-2018-10-19-OT-7"
    }, {
      "pnrLoyaltyRequestId" : "ZAY091-2018-10-19-OT-9"
    } ],
    "6X-1234567891" : [ {
      "pnrLoyaltyRequestId" : "ZAY091-2018-10-19-OT-15"
    } ]
  }
},
"dictionaries" : {
  "pnrs" : {
    "ZAY091-2019-10-05" : {
      "type" : "pnr",
      "id" : "ZAY091-2019-10-05",
      "version" : "1"
    }
  },
  "tickets" : {
    "1721234567890-2019-10-05" : {
      "type" : "air-travel-document",
      "id" : "1721234567890-2019-10-05",
      "version" : "1"
    }
  },
  "emds" : {
    "1725555555555-2019-10-05" : {
      "type" : "air-travel-document",
      "id" : "1725555555555-2019-10-05",
      "version" : "1"
    }
  },
  "dcsPassengers" : {

```

```

    "2501ADE0000001" : {
      "type" : "dcs-passenger",
      "id" : "2501ADE0000001",
      "version" : "1609937279"
    }
  },
  "schedules" : {
    "6X-123-2019-10-15" : {
      "type" : "dated-flight",
      "id" : "6X-123-2019-10-15",
      "version" : "1536835243"
    }
  },
  "inventories" : {
    "6X-123-2019-10-15" : {
      "type" : "dated-flight",
      "id" : "6X-123-2019-10-15",
      "version" : "1536835243"
    }
  },
  "bagsGroups" : {
    "AA42BA1395020102" : {
      "type" : "bags-group",
      "id" : "AA42BA1395020102",
      "version" : "1609937279"
    }
  },
  "memberships" : {
    "6X-1234567890" : {
      "type" : "membership",
      "id" : "6X-1234567890",
      "version" : "1"
    }
  }
},
"events" : {
  "recordDomain" : "PNR_TICKET",
  "recordId" : "ZAY091-2019-10-05",
  "events" : [ {
    "origin" : "COMPARISON",
    "eventType" : "DELETED",
    "previousPath" : "/correlationPnrTicket/correlatedData/1721111111111-2019-05-10"
  }, {
    "origin" : "COMPARISON",
    "eventType" : "CREATED",
    "currentPath" : "/correlationPnrTicket/correlatedData/1721234567890-2019-10-05"
  } ]
}
}

```

PNR DataPush Feed

POST /reservation/pnr-feed

Description

PNR feed pushed by Amadeus DIH. Please note this is NOT a POST API - this section is only used to specify the data model pushed.

Responses

HTTP Code	Description	Schema
default	PNR Data Push Feed	PnrPushFeed

Tags

- FEED

Example HTTP response

Response default

```
{
  "meta" : {
    "triggerEventLog" : {
      "id" : "429074ef1bd011e3-e63dfe23f4a0adc",
      "triggerEventName" : "DATA_INIT"
    },
    "version" : "3.2.0"
  },
  "processedPnr" : {
    "type" : "pnr",
    "id" : "ZAY091-2019-10-05",
    "reference" : "ZAY091",
    "version" : "1",
    "owner" : {
      "office" : {
        "id" : "NCE6X08AA",
        "iataNumber" : "15398195",
        "systemCode" : "6X",
        "agentType" : "AIRLINE"
      },
      "login" : {
        "numericSign" : "0001",
        "initials" : "JF",
        "dutyCode" : "SU",
```

```

    "currencyCode" : "EUR",
    "countryCode" : "FR",
    "cityCode" : "NCE"
  }
},
"creation" : {
  "dateTime" : "2019-10-05T10:00:00Z",
  "pointOfSale" : {
    "office" : {
      "id" : "NCE6X08AA",
      "iataNumber" : "15398195",
      "systemCode" : "6X",
      "agentType" : "AIRLINE"
    },
    "login" : {
      "numericSign" : "0001",
      "initials" : "JF",
      "dutyCode" : "SU",
      "currencyCode" : "EUR",
      "countryCode" : "FR",
      "cityCode" : "NCE"
    }
  },
  "comment" : "6X ONLINE BOOKING"
},
"lastModification" : {
  "dateTime" : "2019-10-05T10:00:00Z",
  "pointOfSale" : {
    "office" : {
      "id" : "NCE6X08AA",
      "iataNumber" : "15398195",
      "systemCode" : "6X",
      "agentType" : "AIRLINE"
    },
    "login" : {
      "numericSign" : "0001",
      "initials" : "JF",
      "dutyCode" : "SU",
      "currencyCode" : "EUR",
      "countryCode" : "FR",
      "cityCode" : "NCE"
    }
  },
  "comment" : "6X ONLINE BOOKING"
},
"pnrProperties" : [ "CODESHARE_PNR" ],
"queuingOffice" : {
  "id" : "NCE6X08AA",
  "iataNumber" : "15398195",
  "systemCode" : "6X",
  "agentType" : "AIRLINE"
}

```

```

},
"nip" : 1,
"associatedPnrs" : [ {
  "reference" : "JKL789",
  "associationType" : "SPLIT",
  "direction" : "CHILD",
  "creation" : {
    "dateTime" : "2019-10-05T10:00:00Z",
    "pointOfSale" : {
      "office" : {
        "systemCode" : "1A"
      }
    }
  }
} ],
"travelers" : [ {
  "type" : "stakeholder",
  "id" : "ZAY091-2019-10-05-PT-1",
  "reference" : "2501ADE0000001",
  "passengerTypeCode" : "ADT",
  "names" : [ {
    "firstName" : "JAMES",
    "lastName" : "CARTER",
    "title" : "MR"
  } ],
  "dateOfBirth" : "1978-10-05",
  "age" : 40,
  "staffType" : "BOOKABLE",
  "identificationCode" : "ID10152307",
  "identityDocuments" : [ {
    "type" : "service",
    "id" : "ZAY091-2019-05-04-OT-5",
    "code" : "DOCS",
    "subType" : "SPECIAL_SERVICE_REQUEST",
    "serviceProvider" : {
      "code" : "6X"
    }
  },
  "status" : "HK",
  "nip" : 1,
  "creation" : {
    "dateTime" : "2019-10-05T10:00:00Z",
    "pointOfSale" : {
      "office" : {
        "id" : "NCE6X08AA"
      }
    }
  },
  "document" : {
    "documentType" : "PASSPORT",
    "number" : "15FR1234",
    "issuanceDate" : "2019-10-05",

```

```

    "expiryDate" : "2025-10-05",
    "issuanceCountry" : "FRA",
    "issuanceLocation" : "PARIS OFFICE",
    "nationality" : "FRA",
    "gender" : "MALE",
    "name" : {
      "fullName" : "JAMES JUNIOR CARTER",
      "firstName" : "JAMES",
      "lastName" : "CARTER"
    },
    "birthDate" : "1978-10-05",
    "birthPlace" : "PARIS"
  },
  "text" : "P-FRA-15FR1234-FRA-05OCT15-M-05OCT25-CARTER-JAMES-H",
  "products" : [ {
    "type" : "product",
    "id" : "ZAY091-2019-10-05-ST-5",
    "ref" : "processedPnr.products"
  } ]
} ],
"contacts" : [ {
  "type" : "contact",
  "id" : "ZAY091-2019-10-05-OT-47",
  "ref" : "processedPnr.contacts"
} ],
"loyaltyAccruals" : [ {
  "type" : "service",
  "id" : "ZAY091-2019-10-05-OT-7",
  "ref" : "processedPnr.loyaltyRequests"
} ],
"loyaltyServicing" : [ {
  "type" : "service",
  "id" : "ZAY091-2019-10-05-OT-8",
  "ref" : "processedPnr.loyaltyRequests"
} ],
"corporateRecognitions" : [ {
  "type" : "service",
  "id" : "ZAY091-2019-10-05-OT-9",
  "ref" : "processedPnr.loyaltyRequests"
} ],
"infant" : {
  "type" : "stakeholder",
  "id" : "ZAY091-2019-10-05-PT-1-INF",
  "ref" : "processedPnr.travelers"
},
"passenger" : {
  "specialSeat" : "CBBG",
  "uniqueIdentifier" : "2501ADE0000001",
  "exst" : {
    "type" : "stakeholder",
    "id" : "ZAY091-2019-10-05-PT-1",

```



```

    "ref" : "processedPnr.travelers"
  },
  "cbbg" : {
    "type" : "stakeholder",
    "id" : "ZAY091-2019-10-05-PT-1",
    "ref" : "processedPnr.travelers"
  },
  "owner" : {
    "type" : "stakeholder",
    "id" : "ZAY091-2019-10-05-PT-1",
    "ref" : "processedPnr.travelers"
  }
} ],
"products" : [ {
  "type" : "product",
  "subType" : "AIR",
  "id" : "ZAY091-2019-10-05-ST-5",
  "airSegment" : {
    "departure" : {
      "iataCode" : "NCE",
      "terminal" : "1",
      "localDateTime" : "2019-10-25T09:00:00",
      "checkInEndTime" : "07:45"
    },
    "arrival" : {
      "iataCode" : "CDG",
      "terminal" : "2",
      "localDateTime" : "2019-10-25T10:25:00"
    },
    "aircraft" : {
      "aircraftType" : "789"
    },
    "marketing" : {
      "flightDesignator" : {
        "carrierCode" : "6X",
        "flightNumber" : "123",
        "operationalSuffix" : "A"
      },
      "isOpenNumber" : false,
      "bookingClass" : {
        "code" : "I",
        "cabin" : {
          "code" : "F"
        }
      }
    },
    "operating" : {
      "flightDesignator" : {
        "carrierCode" : "8X",
        "flightNumber" : "789",

```

```

    "operationalSuffix" : "A"
  },
  "bookingClass" : {
    "code" : "C",
    "cabin" : {
      "code" : "B",
      "bidPrice" : {
        "amount" : "50",
        "currency" : "CAD",
        "elementaryPriceType" : "BID_PRICE"
      }
    }
  },
  "subClass" : {
    "code" : 1,
    "pointOfSale" : {
      "office" : {
        "systemCode" : "8X"
      },
      "login" : {
        "countryCode" : "FR"
      }
    }
  },
  "yields" : [ {
    "amount" : "55",
    "currency" : "CAD",
    "elementaryPriceType" : "ADJUSTED_YIELD"
  }, {
    "amount" : "5",
    "currency" : "CAD",
    "elementaryPriceType" : "EFFECTIVE_YIELD"
  } ]
},
"overBookingReason" : "FORCE_BOOKING",
"codeshareAgreement" : "FREEFLOW"
},
"creation" : {
  "dateTime" : "2019-10-05T10:00:00Z"
},
"bookingStatusCode" : "HK",
"isInformational" : false,
"isDominantInMarriage" : true
},
"products" : [ {
  "type" : "product",
  "id" : "ZAY091-2019-10-05-0T-5",
  "ref" : "processedPnr.products"
}, {
  "type" : "product",
  "id" : "ZAY091-2019-10-05-0T-10",
  "ref" : "processedPnr.products"
} ]

```

```

    } ],
    "travelers" : [ {
        "type" : "stakeholder",
        "id" : "ZAY091-2019-10-05-PT-1",
        "ref" : "processedPnr.travelers"
    }, {
        "type" : "stakeholder",
        "id" : "ZAY091-2019-10-05-PT-2",
        "ref" : "processedPnr.travelers"
    } ]
}, {
    "type" : "product",
    "subType" : "SERVICE",
    "id" : "ZAY091-2019-10-05-OT-5",
    "service" : {
        "code" : "FQTU",
        "subType" : "SPECIAL_SERVICE_REQUEST",
        "serviceProvider" : {
            "code" : "6X"
        },
        "status" : "HK",
        "nip" : 1,
        "creation" : {
            "dateTime" : "2019-10-05T10:00:00Z",
            "pointOfSale" : {
                "office" : {
                    "id" : "NCE6X08AA"
                }
            }
        }
    },
    "membership" : {
        "id" : "1234567890",
        "membershipType" : "INDIVIDUAL",
        "activeTier" : {
            "code" : "HGOLD",
            "name" : "HONORARY GOLD",
            "priorityCode" : "1",
            "customerValue" : 5000,
            "companyCode" : "6X"
        },
        "allianceTier" : {
            "code" : "G",
            "name" : "GOLD",
            "priorityCode" : "5",
            "companyCode" : "SA"
        }
    },
    "priceCategory" : {
        "code" : "A",
        "subCode" : "A04"
    },
},

```

```

    "text" : "6X1234567890 HGOLD/CN-CCWFXSR0175///Y"
  },
  "products" : [ {
    "type" : "product",
    "id" : "ZAY091-2019-10-05-ST-5",
    "ref" : "processedPnr.products"
  } ],
  "travelers" : [ {
    "type" : "stakeholder",
    "id" : "ZAY091-2019-10-05-PT-1",
    "ref" : "processedPnr.travelers"
  } ]
}, {
  "type" : "product",
  "subType" : "SEATING",
  "id" : "ZAY091-2019-10-05-OT-10",
  "seating" : {
    "code" : "RQST",
    "subType" : "SPECIAL_SERVICE_REQUEST",
    "serviceProvider" : {
      "code" : "6X"
    },
    "status" : "HK",
    "nip" : 1,
    "creation" : {
      "dateTime" : "2019-10-05T10:00:00Z",
      "pointOfSale" : {
        "office" : {
          "id" : "NCE6X08AA"
        }
      }
    }
  },
  "seats" : [ {
    "number" : "05A",
    "characteristicCodes" : [ "CH", "W" ],
    "traveler" : {
      "type" : "stakeholder",
      "id" : "ZAY091-2019-10-05-PT-1",
      "ref" : "processedPnr.travelers"
    }
  }, {
    "number" : "05B",
    "characteristicCodes" : [ "CH" ],
    "traveler" : {
      "type" : "stakeholder",
      "id" : "ZAY091-2019-10-05-PT-2",
      "ref" : "processedPnr.travelers"
    }
  } ],
  "priceCategory" : {
    "code" : "A",

```

```

    "subCode" : "A01"
  },
  "text" : "CDGNCE/05A,P1/05B,P2"
},
"products" : [ {
  "type" : "product",
  "id" : "ZAY091-2019-10-05-ST-5",
  "ref" : "processedPnr.products"
} ],
"travelers" : [ {
  "type" : "stakeholder",
  "id" : "ZAY091-2019-10-05-PT-1",
  "ref" : "processedPnr.travelers"
}, {
  "type" : "stakeholder",
  "id" : "ZAY091-2019-10-05-PT-2",
  "ref" : "processedPnr.travelers"
} ]
} ],
"flightItinerary" : {
  "type" : "CUSTOMER_TRANSACTION_DATA_BOUND",
  "originIataCode" : "NCE",
  "destinationIataCode" : "ORD",
  "yield" : {
    "value" : 60
  },
  "flights" : [ {
    "connectedFlights" : {
      "connectionTimeDuration" : "2h",
      "connectionType" : "MARRIAGE",
      "flightSegments" : [ {
        "type" : "product",
        "id" : "ZAY091-2019-10-05-ST-1",
        "ref" : "processedPnr.products"
      }, {
        "type" : "product",
        "id" : "ZAY091-2019-10-05-ST-2",
        "ref" : "processedPnr.products"
      } ]
    },
    "flightSegment" : {
      "type" : "product",
      "id" : "ZAY091-2019-10-05-ST-1",
      "ref" : "processedPnr.products"
    }
  }, {
    "flightSegment" : null,
    "type" : "product",
    "id" : "ZAY091-2019-10-05-ST-3",
    "ref" : "processedPnr.products"
  } ]
} ]

```

```

    },
    "ticketingReferences" : [ {
      "type" : "ticketing-reference",
      "id" : "ZAY091-2019-10-05-OT-20",
      "referenceTypeCode" : "FA",
      "documents" : [ {
        "documentType" : "ETICKET",
        "documentNumber" : "1721234567891",
        "status" : "ISSUED",
        "numberOfBooklets" : 2,
        "creation" : {
          "dateTime" : "2019-10-05T00:00:00Z",
          "pointOfSale" : {
            "office" : {
              "id" : "NCE6X08AA",
              "iataNumber" : "15398195",
              "systemCode" : "6X"
            }
          }
        }
      }
    ],
    "price" : {
      "total" : "5000.50",
      "currency" : "CAD"
    },
    "coupons" : [ {
      "number" : 1,
      "product" : {
        "type" : "product",
        "id" : "ZAY091-2019-10-05-ST-5",
        "ref" : "processedPnr.products"
      }
    }, {
      "number" : 2,
      "product" : {
        "type" : "product",
        "id" : "ZAY091-2019-10-05-ST-6",
        "ref" : "processedPnr.products"
      }
    }
  ],
  "text" : "172-1234567890/RCI-FDF161000001
MB01/ETAF/EUR3000.00/05OCT19/NCE6X08AA/20494795",
  "isInfant" : false,
  "traveler" : {
    "type" : "stakeholder",
    "id" : "ZAY091-2019-10-05-PT-1",
    "ref" : "processedPnr.travelers"
  },
  "products" : [ {
    "type" : "product",
    "id" : "ZAY091-2019-10-05-ST-5",

```

```

    "ref" : "processedPnr.products"
  }, {
    "type" : "product",
    "id" : "ZAY091-2019-10-05-ST-6",
    "ref" : "processedPnr.products"
  } ]
} ],
"loyaltyRequests" : [ {
  "type" : "service",
  "id" : "ZAY091-2019-05-04-OT-5",
  "code" : "FQTV",
  "subType" : "SPECIAL_SERVICE_REQUEST",
  "serviceProvider" : {
    "code" : "6X"
  },
  "status" : "HK",
  "nip" : 1,
  "creation" : {
    "dateTime" : "2019-10-05T10:00:00Z",
    "pointOfSale" : {
      "office" : {
        "id" : "NCE6X08AA",
        "iataNumber" : "15398195",
        "systemCode" : "6X",
        "agentType" : "AIRLINE"
      },
      "login" : {
        "numericSign" : "0001",
        "initials" : "JF",
        "dutyCode" : "SU",
        "currencyCode" : "EUR",
        "countryCode" : "FR",
        "cityCode" : "NCE"
      }
    }
  },
  "comment" : "6X online BOOKING"
},
"membership" : {
  "id" : "1234567890",
  "membershipType" : "INDIVIDUAL",
  "activeTier" : {
    "code" : "HGOLD",
    "name" : "HONORARY GOLD",
    "priorityCode" : "1",
    "customerValue" : 5000,
    "companyCode" : "6X"
  },
  "allianceTier" : {
    "code" : "HGOLD",
    "name" : "HONORARY GOLD",
    "priorityCode" : "1",

```

```

        "customerValue" : 5000,
        "companyCode" : "6X"
    }
},
"text" : "6X1234567890 GOLD",
"travelers" : [ {
    "type" : "stakeholder",
    "id" : "ZAY091-2019-10-05-PT-1",
    "ref" : "processedPnr.travelers"
} ],
"products" : [ {
    "type" : "product",
    "id" : "ZAY091-2019-10-05-ST-1",
    "ref" : "processedPnr.travelers"
} ]
} ],
"keywords" : [ {
    "type" : "service",
    "id" : "ZAY091-2019-05-04-OT-5",
    "code" : "CKIN",
    "subType" : "SPECIAL_KEYWORD",
    "serviceProvider" : {
        "code" : "6X"
    },
    "status" : "HK",
    "nip" : 1,
    "creation" : {
        "dateTime" : "2019-10-05T10:00:00Z",
        "pointOfSale" : {
            "office" : {
                "id" : "NCE6X08AA"
            }
        }
    },
    "text" : "PLEASE CHECK PASSPORT",
    "travelers" : [ {
        "type" : "stakeholder",
        "id" : "ZAY091-2019-10-05-PT-5",
        "ref" : "processedPnr.travelers"
    } ]
} ],
"remarks" : [ {
    "type" : "remark",
    "id" : "ZAY091-2019-10-05-OT-36",
    "subType" : "RM",
    "category" : "C",
    "content" : "NOTIFY PASSENGER PRIOR TO TICKET PURCHASE & CHECK-IN: FEDERAL LAWS FORBID THE CARRIAGE OF HAZARDOUS MATERIALS - GGAMAUSHAZ",
    "travelers" : [ {
        "type" : "stakeholder",
        "id" : "ZAY091-2019-10-05-PT-1",

```



```

    "ref" : "processedPnr.travelers"
  } ],
  "products" : [ {
    "type" : "product",
    "id" : "ZAY091-2019-10-05-ST-5",
    "ref" : "processedPnr.products"
  } ]
} ],
"contacts" : [ {
  "type" : "contact",
  "id" : "ZAY091-2019-10-05-OT-14",
  "addresseeName" : {
    "fullName" : "JAMES CARTER"
  },
  "phone" : {
    "category" : "PERSONAL",
    "deviceType" : "MOBILE",
    "number" : "0033612345678"
  },
  "address" : {
    "category" : "DESTINATION",
    "lines" : [ "10 RUE DES CANETTES" ],
    "postalCode" : "75006",
    "countryCode" : "FRA",
    "cityName" : "PARIS",
    "stateCode" : "NY",
    "postalBox" : "BP 12345"
  },
  "email" : {
    "address" : "james.carter@gmail.com"
  },
  "language" : "FR",
  "purpose" : "NOTIFICATION",
  "freeFlowFormat" : "D/JAP/10 RUE DES CANETTES/PARIS-ARRONDISSEMENT6/75006",
  "travelerRefs" : [ {
    "type" : "stakeholder",
    "id" : "ZAY091-2019-10-05-PT-1",
    "ref" : "processedPnr.travelers"
  } ]
} ],
"automatedProcesses" : [ {
  "type" : "automated-process",
  "id" : "ZAY091-2019-10-05-OT-37",
  "code" : "TL",
  "dateTime" : "2019-10-10T10:00:00",
  "office" : {
    "id" : "NCE6X08AA"
  },
  "queue" : {
    "number" : 10,
    "category" : 1
  }
} ]

```

```

    },
    "documentDeliveryOptions" : "TTP/TTM/ED/ITR",
    "text" : "25OCT/NCE6X08AA/Q10C1//TTP/INV/ED/ITR",
    "applicableCarrierCode" : "6X",
    "isApplicableToInfants" : false,
    "products" : [ {
        "type" : "product",
        "id" : "ZAY091-2019-10-05-ST-5",
        "ref" : "processedPnr.products"
    } ],
    "travelers" : [ {
        "type" : "stakeholder",
        "id" : "ZAY091-2019-10-05-PT-1",
        "ref" : "processedPnr.travelers"
    } ]
} ],
"paymentMethods" : [ {
    "type" : "payment-method",
    "id" : "ZAY091-2019-10-05-OT-17",
    "code" : "FP",
    "formsOfPayment" : [ {
        "code" : "FFR",
        "fopIndicator" : "NEW",
        "freeText" : "FFR6X1234567890-M50000*A",
        "paymentLoyalty" : {
            "membership" : {
                "id" : "1234567890",
                "membershipType" : "INDIVIDUAL",
                "activeTier" : {
                    "code" : "HGOLD",
                    "name" : "HONORARY GOLD",
                    "priorityCode" : 1,
                    "customerValue" : 5000,
                    "companyCode" : "6X"
                },
                "allianceTier" : {
                    "code" : "G",
                    "name" : "GOLD",
                    "priorityCode" : 5,
                    "companyCode" : "SA"
                }
            },
            "certificateNumber" : "12345"
        },
        "authorization" : {
            "approvalCode" : "12345678"
        }
    }, {
        "code" : "CC",
        "fopIndicator" : "NEW",
        "freeText" : "CCVI*****5555/0523*CVA/CAD1500/AAPS10K/HCARTER JAMES",

```

```

    "paymentCard" : {
      "maskedCardNumber" : "*****5555",
      "vendorCode" : "VI",
      "expiryDate" : 339
    },
    "authorization" : {
      "approvalCode" : "AAPS10K"
    }
  } ],
  "isInfant" : false,
  "travelers" : [ {
    "type" : "stakeholder",
    "id" : "ZAY091-2019-10-05-PT-1",
    "ref" : "processedPnr.travelers"
  } ],
  "products" : [ {
    "type" : "product",
    "id" : "ZAY091-2019-10-05-ST-5",
    "ref" : "processedPnr.products"
  } ]
} ],
"fareElements" : [ {
  "type" : "fare-element",
  "id" : "ZAY091-2019-10-05-OT-37",
  "code" : "FM",
  "commissions" : {
    "controls" : [ "ATO_CTO", "AUTOMATIC" ],
    "values" : [ {
      "commissionType" : "NEW",
      "collectingAgency" : {
        "iataNumber" : "15398195"
      },
      "amount" : {
        "amount" : "90.70",
        "currency" : "CAD"
      }
    }
  ], {
    "commissionType" : "VAT_ON_NEW",
    "percentage" : "19.60"
  }, {
    "commissionType" : "OLD",
    "amount" : {
      "amount" : "50.89",
      "currency" : "CAD"
    }
  }, {
    "commissionType" : "VAT_ON_OLD",
    "percentage" : "19.60"
  }, {
    "commissionType" : "SECONDARY",
    "percentage" : "10.50",

```

```

        "collectingAgency" : {
            "iataNumber" : "15398195"
        },
        "dealNumber" : "1234567"
    } ]
},
"text" : "*AM*90.70V19.60/X0/30.89AV19.60/B10.50/D1234567",
"isInfant" : false,
"travelers" : [ {
    "type" : "stakeholder",
    "id" : "ZAY091-2019-10-05-PT-1",
    "ref" : "processedPnr.travelers"
} ],
"products" : [ {
    "type" : "product",
    "id" : "ZAY091-2019-10-05-ST-5",
    "ref" : "processedPnr.products"
} ]
}, {
    "type" : "fare-element",
    "id" : "ZAY091-2019-10-05-OT-41",
    "code" : "AI",
    "accounting" : {
        "accountNumber" : "123456",
        "costCenter" : "1234567890123456789",
        "iataCompanyCode" : "123ADC01",
        "clientReference" : "123456789"
    },
    "isInfant" : false,
    "travelers" : [ {
        "type" : "stakeholder",
        "id" : "ZAY091-2019-10-05-PT-1",
        "ref" : "processedPnr.travelers"
    } ],
    "products" : [ {
        "type" : "product",
        "id" : "ZAY091-2019-10-05-ST-5",
        "ref" : "processedPnr.products"
    } ]
} ],
"quotations" : [ {
    "type" : "quotation-record",
    "id" : "ZAY091-2019-01-15-QT-1",
    "subType" : "TST",
    "isManual" : false,
    "documentType" : "ETICKET",
    "issuanceType" : "FIRST_ISSUE",
    "flags" : [ "CONFIDENTIAL", "PNR_CHANGED" ],
    "creation" : {
        "dateTime" : "2019-01-15T00:00:00Z",
        "pointOfSale" : {

```

```

    "office" : {
      "id" : "NCE6X0001"
    }
  },
  "lastModification" : {
    "dateTime" : "2019-01-19T00:00:00Z",
    "pointOfSale" : {
      "office" : {
        "id" : "NCE6X0001"
      }
    }
  },
  "lastTicketingDate" : "2019-01-25",
  "originCityIataCode" : "NCE",
  "destinationCityIataCode" : "CDG",
  "pricingConditions" : {
    "flags" : [ "FARE_BASIS_OVERRIDE" ],
    "fareCalculation" : {
      "pricingIndicator" : 3,
      "text" : "PAR 6X YT0289.85SKWI5LGT 6X PAR289.85SKWI5LGT NUC579.70END
ROE0.862490",
      "isManual" : false
    }
  },
  "isInternationalSale" : true,
  "paymentRestriction" : {
    "restriction" : "NO VISA PAYMENT ON INDIAN MARKET"
  }
},
"price" : {
  "detailedPrices" : [ {
    "amount" : "1315",
    "currency" : "CAD",
    "elementaryPriceType" : "GRAND_TOTAL"
  }, {
    "amount" : "500",
    "currency" : "EUR",
    "elementaryPriceType" : "BASE_FARE"
  }, {
    "amount" : "740",
    "currency" : "CAD",
    "elementaryPriceType" : "EQUIVALENT_FARE"
  }, {
    "amount" : "1300",
    "currency" : "CAD",
    "elementaryPriceType" : "TOTAL"
  } ],
  "taxes" : [ {
    "amount" : "300",
    "currency" : "CAD",
    "code" : "YQ",

```

```

    "nature" : "AD",
    "category" : "NEW"
  }, {
    "amount" : "130",
    "currency" : "CAD",
    "code" : "CA",
    "nature" : "AE",
    "category" : "NEW"
  }, {
    "amount" : "130",
    "currency" : "CAD",
    "code" : "FR",
    "nature" : "SE",
    "category" : "NEW"
  } ],
  "fees" : [ {
    "code" : "OB",
    "subCode" : "T01",
    "amount" : "15",
    "currency" : "CAD",
    "exempted" : false,
    "taxIncluded" : true,
    "description" : "MASTERCARD FEE",
    "taxes" : [ {
      "amount" : "3",
      "currency" : "CAD",
      "percentage" : "20",
      "included" : true,
      "exempted" : false,
      "description" : "VAT"
    } ]
  } ]
},
"currencyConversionLookupRates" : {
  "rate" : "1.14",
  "target" : "EUR"
},
"coupons" : [ {
  "fareBasis" : {
    "fareBasisCode" : "BYM3M",
    "primaryCode" : "TTI",
    "ticketDesignatorCode" : "CD10"
  },
  "isNonRefundable" : true,
  "isNonExchangeable" : true,
  "isNonInterlineable" : true,
  "isFromConnection" : false,
  "isFromStopOver" : false,
  "validityDates" : {
    "notValidBeforeDate" : "2019-01-15",
    "notValidAfterDate" : "2019-01-25"
  }
} ]

```

```

    },
    "baggageAllowance" : {
      "weight" : {
        "value" : 10,
        "unit" : "KILOGRAMS"
      },
      "quantity" : 1
    },
    "product" : {
      "type" : "product",
      "id" : "ZAY091-2019-10-05-ST-5",
      "ref" : "processedPnr.products"
    }
  ] ],
  "paymentMethods" : [ {
    "type" : "payment-method",
    "id" : "ZAY091-2019-10-05-OT-17",
    "ref" : "processedPnr.paymentMethods"
  } ],
  "travelers" : [ {
    "type" : "stakeholder",
    "id" : "ZAY091-2019-10-05-PT-1",
    "ref" : "processedPnr.travelers"
  } ]
} ],
"flightTransfer" : {
  "type" : "flight-disruption-transfer",
  "id" : "55555555",
  "subType" : "TRAVEL_READY_REACCOMODATION",
  "travelers" : [ {
    "type" : "stakeholder",
    "id" : "ZAY091-2019-10-05-PT-1",
    "ref" : "processedPnr.travelers"
  } ],
  "fromSegments" : [ {
    "departure" : {
      "iataCode" : "NCE",
      "terminal" : "1",
      "localDateTime" : "2019-10-25T09:00:00",
      "checkInEndTime" : "07:45"
    },
    "arrival" : {
      "iataCode" : "CDG",
      "terminal" : "2",
      "localDateTime" : "2019-10-25T10:25:00"
    },
    "aircraft" : "aircraftType",
    "marketing" : {
      "flightDesignator" : {
        "carrierCode" : "6X",
        "flightNumber" : "123",

```

```

        "operationalSuffix" : "A"
    },
    "bookingClass" : {
        "code" : "I",
        "cabin" : {
            "code" : "F"
        }
    }
} ],
"toSegments" : [ {
    "type" : "product",
    "id" : "ZAY091-2019-10-05-ST-5",
    "ref" : "processedPnr.products"
} ]
}
},
"previousRecord" : [ {
    "op" : "replace",
    "path" : "/products/0/airSegment/bookingStatusCode",
    "value" : "KL"
} ],
"events" : {
    "recordDomain" : "PNR",
    "recordId" : "ZAY091-2019-10-05",
    "originFeedTimeStamp" : "2019-10-25T10:00:00Z",
    "events" : [ {
        "origin" : "COMPARISON",
        "eventType" : "UPDATED",
        "currentPath" : "/products/0/airSegment/bookingStatusCode",
        "previousPath" : "/products/0/airSegment/bookingStatusCode"
    } ]
}
}

```


Definitions

AcceptanceDelivery

Structure containing all the acceptance (check-in) information

Name	Description	Schema
cancellationReasonCode <i>optional</i>	Code for the reason selected by the agent or system when the acceptance of the passenger is cancelled (offload) Example : "false"	string
cancellationReasonLabel <i>optional</i>	Cancellation reason label corresponding to the reason code Example : "NOSHOW"	enum (AIRLINE_STAFF, BAGGAGE_NOT_ACCEPTED, CUSTOMER_FAILED_TO_BOARD, CUSTOMER_REQUEST, , CUSTOMER_UNWELL, , DENIED_BOARDING, FLIGHT_ALTERNATIVE, FLIGHT_DELAYED, FLIGHT_OVERSOLD, FLIGHT_CANCELLED, MISSED_CONNECTION, MEDICAL_REASONS, NOSHOW, OTHER, REGULATORY_REQUIREMENT_NOT_MET, SECURITY_REASONS, TRAVEL_IN_DIFFERENT_CABIN, TRAVEL_DOCUMENTATION_INCOMPLETE, TRAVEL_INDUSTRY_STAFF, USER_ERROR_CORRECTION, VOLUNTARY_DENIED_BOARDING, INVOLUNTARY_DENIED_BOARDING)

Name	Description	Schema
channel <i>optional</i>	Acceptance Channel indicator Example : "JFE"	enum (EXTERNAL_DCS, CRYPTIC, JFE, KIOSK, MOBILE_PHONE, SMS, TELEPHONE, WEB_APPLICATION)
interAirlineThroughCheckIn <i>optional</i>		InterAirlineThroughCheckIn
isForceAccepted <i>optional</i>	Force Acceptance indicator - indicator set when the agents override some checks like suitability check Example : true	boolean
isFrozen <i>optional</i>	Freeze indicator - set by the agent to prevent acceptance status to be reassessed during onload Example : false	boolean
origin <i>optional</i>	the type of channel that originated the acceptance Example : "AIRLINE"	enum (AIRLINE, SELF_SERVICE, DIRECT_CONSUMER, ELECTRONIC_SYSTEM)
reasonFreeText <i>optional</i>	optional free text given by the agent to describe why the passenger was force accepted Example : "VIP passenger"	string
securityNumber <i>optional</i>	Check-in security ID populated by DCS Customer Management Example : "CDG-005"	string
status <i>optional</i>	Passenger acceptance status Example : "ACCEPTED"	enum (ACCEPTED, STANDBY, NOT_ACCEPTED, REJECTED)

AccountingElement

Accounting Information - AI element usually enables an airline to handle accounting information related to the travel agency that has sold the booking. It is also vital to obtain a good calculation of revenues when many companies are involved in the booking. AI is further conveyed in other reporting documents such as the Back Office AIR document.

Name	Description	Schema
accountNumber <i>optional</i>	account identifier for the recipient revenue accounting system Example : "123456"	string

Name	Description	Schema
clientReference <i>optional</i>	Alpha-numerical reference of the client for which accounting information is transmitted - optional use depending on the needs of the travel agency. Example : "123456789"	string
costCenter <i>optional</i>	Cost center number for which the accounting is being registered - optional use depending on the needs of the travel agency Example : "1234567890123456789"	string
iataCompanyCode <i>optional</i>	IATA number of the company for which the accounting is being registered - optional use depending on the needs of the travel agency Example : "123ADC01"	string

Address

Address information

Name	Description	Schema
category <i>optional</i>	Category of the contact element Example : "DESTINATION"	enum (DESTINATION, RESIDENCE, BUSINESS, PERSONAL)
cityName <i>optional</i>	Full city name. Example: Dublin Pattern : "[a-zA-Z -]{1,35}" Example : "PARIS"	string
countryCode <i>optional</i>	ISO 3166-1 country code Pattern : "[a-zA-Z]{2}" Example : "FRA"	string
lines <i>optional</i>	Line 1 = Street address, Line 2 = Apartment, suite, unit, building, floor, etc Example : ["10 RUE DES CANETTES"]	< string > array
postalBox <i>optional</i>	Postal box of the address Example : "BP 12345"	string
postalCode <i>optional</i>	postal/zip code of the address Example : "75006"	string
stateCode <i>optional</i>	State code (two character standard IATA state code) Pattern : "[a-zA-Z0-9]{1,2}" Example : "NY"	string

AirTravelDocument

Name	Description	Schema
associationStatus <i>optional</i>	Designates the nature of the relation between the current travel document and the corresponding segmentDelivery. Example : "ASSOCIATED"	enum (ASSOCIATED, E_STAPLE, MULTIPLE_ASSOCIATED)
blacklistCategory <i>optional</i>	Part of the DCS regulatory checks that have to be carried out before a passenger can be accepted on a flight. Example : "STOLEN"	string
coupons <i>optional</i>	Enables to associate each coupon of the travel document with its corresponding product in PNR. For ORIGINAL & EXCHANGED documents, the product reference is not populated but only 2 coupon numbers, defining the min & max of the coupon numbers range affected by the exchange.	< coupons > array
creation <i>optional</i>		EventLog
documentNumber <i>optional</i>	Identifier of the travel document prefixed by its owner code [NALC - 3 digits]. Can either be a primary or a conjunctive document number. Necessary for TicketingReference definition. Example : "1721234567891"	string
documentType <i>optional</i>	Type of the travel document, which can be an electronic ticket, a paper ticket, an Electronic Miscellaneous Document, or a Miscellaneous Charge Order. Fields associationStatus & blacklistCategory are only populated by segmentDelivery resources. Example : "ETICKET"	enum (ETICKET, EMD, EMD_STANDALONE, EMD_ASSOCIATED, PAPER_TICKET, PAPER_MD, VIRTUAL_TICKET, VIRTUAL_MD, TICKETLESS_DOCUMENT, TICKET, MD)
numberOfBooklets <i>optional</i>	Number of conjunctive documents, for a max of 4 Example : 4	integer
price <i>optional</i>		Price
primaryDocumentNumber <i>optional</i>	Designates the primary document number when documentNumber refers to a conjunctive document. Necessary for SegmentDelivery definition of ticketing data. Example : "1721234567890"	string
status <i>optional</i>	Status of the travel document contained in the fare element Example : "ISSUED"	enum (ISSUED, REFUNDED, VOID, PRINTED, ORIGINAL, EXCHANGED)

coupons

Name	Description	Schema
number <i>optional</i>	Identifies the coupon within the travel document Example : 1	integer
product <i>optional</i>		Relationship
reasonForIssuance <i>optional</i>	Used by TicketingReference items of referenceTypeCode ASVC / SVC	PriceCategory
sequenceNumber <i>optional</i>	Coupon sequence number is used as identifier when primaryDocumentNumber is defined [primary document] Example : 1	integer

AircraftEquipment

Information related to the aircraft

Name	Description	Schema
aircraftType <i>optional</i>	Aircraft type Pattern : "[a-zA-Z0-9]{3}" Example : "319"	string

AssociatedPnr

Describes the relation between the current reservation and another one

Name	Description	Schema
associationType <i>optional</i>	Specifies the directionality of a split between two reservations. Example : "CODESHARE"	enum (CODESHARE, SPLIT, OTHER_AIRLINE, CROSS_REFERENCE)
creation <i>optional</i>	Creation datetime and system code [GDS/CRS] from which originates the associated record.	EventLog
direction <i>optional</i>	In case of a split relation, indicates whether the reference results from a split operation [CHILD] or has originated a split operation [PARENT] leading to the current PNR. Indicates the second reference resulting from the split of the same parent PNR [OTHER]. Example : "CHILD"	enum (CHILD, PARENT, OTHER)
reference <i>optional</i>	Record locator [Amadeus or OA] with which the current reservation is related. In case of a codeshare relation, it enables to identify the operating PNR. Example : "JKL789"	string

Authorization

Details on credit card authorization or award authorization [by Airline Loyalty System] in case of miles redemption/upgrade.

Name	Description	Schema
approvalCode <i>optional</i>	In case of card payment, it consists in a series of characters assigned by the applicable credit card company's authorization system to confirm the approval of a credit sale transaction, with a maximum of 8 digits. In case of award payment, it corresponds to the stock control number returned by the airline loyalty system to indicate the validation of the redemption/upgrade request. Example : "AAPS10K"	string
extendedPaymentCode <i>optional</i>	A code to indicate the number of months over which the customer wishes to pay where the credit card issuer permits. Can also be a code to indicate extended payment with values- - blank or "00" for immediate payment - "03" or "24" for payment over 3 or 24 months (or any other value) - "E" for extended payment, or any other alpha character instructed by the credit card company. Example : "11"	string
sourceOfApprovalCode <i>optional</i>	Approval source of the authorization when the FOP is a credit card. Can be seen in the corresponding FP elements of the order. Possible values are A - Automatic Approval Code M - Manual Approval Code F - Automatic Capture and Approval Code B - Manual Capture and Approval Code Example : "A"	string

AutomatedProcess

Provides information on ticketing arrangements and Amadeus Time Limits

Name	Description	Schema
applicableCarrierCode <i>optional</i>	Identifier of the airline to which the automatic process applies. Example : "6X"	string
code <i>optional</i>	AT: airport ticketing DO: domestic flight IN: international flight MA: mail OK: ticketed OPC: Amadeus Time Limit - auto itinerary cancellation OPW: Amadeus Time Limit - auto queuing & notification PT: prepaid ticket SS: self service ST: satellite ticketing TL: auto queuing TR: revalidation XL: auto itinerary cancellation Example : "TL"	enum (AT, DO, IN, MA, OK, OPC, OPW, PT, SS, ST, TL, TR, XL)

Name	Description	Schema
dateTime <i>optional</i>	Datetime limit at which the process takes action in case issuance is not done. Example : "2019-10-10T10:00:00"	string
documentDeliveryOptions <i>optional</i>	Options as entered by the agent in cryptic, related to the secondary action that can be requested on the following ticketing arrangements [TL/AT/MA/IN/DO]. In addition to the primary action of the given ticketing arrangement, those options enable to issue/print/email documents as a secondary action. Following documents can be printed or emailed - invoices, e-ticket receipts, EMD receipts, insurance certificates. Example : "TTP/TTM/ED/ITR"	string
id <i>optional</i>	item identifier Example : "ZAY091-2019-10-05-OT-37"	string
isApplicableToInfants <i>optional</i>	Indicates that the automated process applies to infant passenger(s) Example : false	boolean
office <i>optional</i>	Office onto which the process must be triggered. Office information limited to office ID.	Office
products <i>optional</i>	Example : [{ "type" : "product", "id" : "ZAY091-2019-10-05-ST-1", "ref" : "processedPnr.products" }]	< Relationship > array
queue <i>optional</i>	Identifies the queue onto which PNR must be automatically placed upon process execution.	queue
text <i>optional</i>	Full PNR element content Example : "25OCT/NCE6X08AA/Q10C1//TTP/INV/ED/ITR"	string
travelers <i>optional</i>	Example : [{ "type" : "stakeholder", "id" : "ZAY091-2019-10-05-PT-1", "ref" : "processedPnr.travelers" }]	< Relationship > array
type <i>optional</i>	resource name Example : "automated-process"	enum (automated-process)

queue

Name	Description	Schema
category <i>optional</i>	Example : "1"	string
number <i>optional</i>	Example : "10"	string

Bag

Structure containing all the information related to an individual checked in bag

Name	Description	Schema
bagTag <i>optional</i>	details of the bag tag	BagTag
bagType <i>optional</i>	The type of the bag Example : "STANDARD"	enum (RUSH, STANDARD, CREW)
id <i>optional</i>	The UBI (Universal Baggage Identifier) of the bag item Example : "100000001"	string
legs <i>optional</i>	Flight-leg information associated with the bag item	< BagLegDelivery > array
owner <i>optional</i>	PNR traveler resource owning the bag	Relationship
systemSource <i>optional</i>	From which channel was this bag created Example : "AUTOMATIC"	enum (AUTOMATIC, BTM, IATCI)
type <i>optional</i>	type of the object Example : "bag"	enum (bag)

BagLegDelivery

Structure to describe the delivery information of a bag at leg level

Name	Description	Schema
acceptanceStatus <i>optional</i>	The acceptance status of the bag item for the current flight leg Example : "NOT_ACCEPTED"	enum (FULLY_ACCEPTED, NOT_ACCEPTED, PROVISIONALLY_ACCEPTED, NOT_TRAVELLING)
boardPoint <i>optional</i>	detail of the boardpoint of the leg	FlightEndPoint
legDelivery <i>optional</i>	link to the corresponding leg delivery	Relationship
offPoint <i>optional</i>	detail of the offpoint of the leg	FlightEndPoint
specialBagHandlingItems <i>optional</i>	special bag handling properties	< SpecialBagHandling > array

BagTag

Structure representing a bag tag in the DCS system

Name	Description	Schema
finalDestination <i>optional</i>	The IATA code of final destination of the bag as issued on the bag tag Example : "JFK"	string
issuingCarrier <i>optional</i>	The bag tag's issuing carrier code Example : "6X"	string
licensePlate <i>optional</i>	The bag tag number Example : "06X1234567"	string

BagsGroup

Structure to describe the data of a bag group

Name	Description	Schema
checkedBags <i>optional</i>	Map of bag resources with id as key	< Bag > array
checkedBagsCount <i>optional</i>	The number of checked bags comprising this bags group Example : 1	integer
checkedBagsWeight <i>optional</i>	The total weight of all checked bags	Weight
handBagsCount <i>optional</i>	The number of hand baggage items comprising this bags group Example : 1	integer
handBagsWeight <i>optional</i>	The total weight of hand baggage items comprising this bags group.	Weight
id <i>optional</i>	The baggage group reference Example : "10FBC42026758291"	string
isPool <i>optional</i>	Indicates if the current group is a pool of baggage Example : false	boolean
type <i>optional</i>	type of the data Example : "bags-group"	enum (bags-group)

BoardingDelivery

Structure containing the boarding information

Name	Description	Schema
boardingPassPrint <i>optional</i>	Boarding pass print	BoardingPassPrint
boardingStatus <i>optional</i>	Passenger boarding status Example : "NOT_BOARDED"	enum (BOARDED, NOT_BOARDED)
trackingLog <i>optional</i>	Provides the local time at which the passenger has actually boarded the plane for the current leg via the field localDateTime	TimeLocationTrackingLog

BoardingPassPrint

Name	Description	Schema
status <i>optional</i>	Boarding pass print status Possible values PRINTED, NEEDS_PRINTING or NOT_PRINTED Example : "PRINTED"	string

BookingClass

booking class description

Name	Description	Schema
cabin <i>optional</i>	inventory cabin the booking class belongs to	Cabin
code <i>optional</i>	code identifying the booking class Example : "C"	string
levelOfService <i>optional</i>	reservation level of service Example : "ECONOMY"	string
subClass <i>optional</i>		SubClass

Cabin

Name	Description	Schema
bidPrice <i>optional</i>	Minimal revenue expected by the airline for a seat sale in the given cabin	ElementaryPrice
code <i>optional</i>	cabin code filed in inventory for the sold seat Example : "F"	string

Comment

Structure to describe a comment given to a customer in DCS

Name	Description	Schema
delivery <i>optional</i>	whether the comment has been delivered to the passenger	CommentDelivery
priority <i>optional</i>	Example : "HIGH"	enum (HIGH, NORMAL)
text <i>optional</i>	the free text of the comment (ASCII) Example : "One cabin bag to be taken on the hold"	string
usage <i>optional</i>	Example : "AT_BP_REPRINT"	enum (BAGGAGE, CABIN, NORMAL, AT_BP_REPRINT, AT_CHECKIN, AT_GATE, NEXT_TIME, PRINT_ON_BP, PRINT_ON_ONBOARD_SERVICE_LIST)

CommentDelivery

Name	Description	Schema
status <i>optional</i>	whether the comment has been delivered to the passenger Example : "DELIVERED"	enum (DELIVERED, NOT_DELIVERED)

Commission

Name	Description	Schema
amount <i>optional</i>		ElementaryPrice
collectingAgency <i>optional</i>	IATA number identifying the travel agency collecting the commission.	collectingAgency

Name	Description	Schema
commissionType <i>optional</i>	Nature of the commission. Example : "NEW"	enum (NEW, NEW_RATE_ON_NET_FARE, CAP_LIMIT_AMOUNT, SECONDARY, SUPPLEMENTARY_AMOUNT, VAT_ON_NEW, VAT_RATE_ON_OLD, CANCELLATION_PENALTY, OLD)
dealNumber <i>optional</i>	Enables the airline to identifies the contract signed by the collecting travel agency. Example : "1234567"	string
percentage <i>optional</i>	Percentage in case of a rate commission - can be decimal. Example : 20.0	number

collectingAgency

Name	Schema
office <i>optional</i>	Office

Commissions

This element is used to record commissions earned from the sale of a ticket, which are either entered as percentage or amount. Structure of the FM fare element stored in PNR.

Name	Description	Schema
controls <i>optional</i>		< enum (ATO_CTO, REUSED, AUTOMATIC, MANUAL, VALIDATED_MANUAL, FILED_FOR_DYNAMIC_DISCOUNTED_FARE, FILED_FOR_NEGOTIATED_FARE, COMPUTED_FOR_NEGOTIATED_FARE) > array
values <i>optional</i>	Details on each commission contained in the FM entry.	< Commission > array

Compensation

Detail of the compensation given to the passenger

Name	Description	Schema
reason <i>optional</i>	Compensation reason code ((as defined by airlines in BZR)	CompensationReason

CompensationReason

Name	Description	Schema
code <i>optional</i>	Compensation reason code ((as defined by airlines in BZR) Example : "FDD"	string

ConnectedFlightSegments

Name	Description	Schema
connectionTimeDuration <i>optional</i>	Only Hours and minutes,Format: [n]H[n]M example: 10H15M;the time duration between the arrival of the inbound flight and the departure of the outbound flight.	string (time)
connectionType <i>optional</i>	Example : "MARRIAGE"	enum (CONNECTION, MARRIAGE, NEGOCIATED_SPACE_MARRIAGE, INTERACTIVE_MARRIAGE, TRAFFIC_RESTRICTIONS_MARRIAGE, LONG_HAUL_MARRIAGE, ONLINE_MARRIAGE)
flightSegments <i>optional</i>		< Relationship > array

Contact

represents a contact

Name	Description	Schema
address <i>optional</i>		Address

Name	Description	Schema
addresseeName <i>optional</i>	the name of the person/company addressed by these contact details	addresseeName
email <i>optional</i>		Email
freeFlowFormat <i>optional</i>	Field containing a full unformatted contact. Example : "D/JAP/10 RUE DES CANETTES/PARIS-ARRONDISSEMENT6/75006"	string
id <i>optional</i>	Contact identifier Example : "ZAY091-2019-10-05-OT-14"	string
language <i>optional</i>	ISO code of the preferred language of communication for notification contacts Example : "FR"	string
phone <i>optional</i>		Phone
purpose <i>optional</i>	the purpose for which this contact is to be used - REGULATORY refers to SSR DOCA element [Advanced Passenger Information]. Example : "NOTIFICATION"	< enum (STANDARD, NOTIFICATION, INFORMATION, REGULATORY, BILLING, MAILING) > array
travelerRefs <i>optional</i>	Example : [{ "type" : "stakeholder", "id" : "ZAY091-2019-10-05-PT-1", "ref" : "processedPnr.travelers" }]	< Relationship > array
type <i>optional</i>	Resource name Example : "contact"	enum (contact)

addresseeName

Name	Description	Schema
fullName <i>optional</i>	Example : "JAMES CARTER"	string

CorrelatedDataPnrBagLeg

Set of data field identifiers defining the correlation between a PNR flight segment and a DCS Baggage leg delivery.

Name	Description	Schema
bagLegDeliveryId <i>optional</i>	Example : "1101CA1100003431-ORY"	string

Name	Description	Schema
pnrAirSegmentId <i>optional</i>	Example : "ZAY091-2018-10-19-ST-1"	string

CorrelatedDataPnrBagsGroup

Set of data field identifiers defining the correlation between a PNR and a DCS Baggage.

Name	Description	Schema
bagId <i>optional</i>	Example : "1101CA1100003431"	string
bagLegCorrelations <i>optional</i>		< CorrelatedDataPnrBagLeg > array
pnrTravelerId <i>optional</i>	Example : "ZAY091-2018-10-19-PT-1"	string

CorrelatedDataPnrDcsPassenger

Set of data field identifiers defining the correlation between a PNR and a DCS Passenger record [CPR].

Name	Description	Schema
dcsPassengerSegmentDeliveryId <i>optional</i>	Example : "2401CA10111110ID"	string
pnrAirSegmentId <i>optional</i>	Example : "ZAY091-2019-10-05-ST-1"	string
pnrTravelerId <i>optional</i>	Example : "ZAY091-2019-10-05-PT-1"	string

CorrelatedDataPnrEmd

Set of data field identifiers defining the correlation between a PNR and an Electronic Miscellaneous Document.

Name	Description	Schema
emdCouponId <i>optional</i>	Example : "172999999999-2019-10-05-1"	string
pnrAirSegmentId <i>optional</i>	Example : "ZAY091-2019-10-05-ST-1"	string
pnrServiceId <i>optional</i>	Example : "ZAY091-2019-10-05-OT-5"	string
pnrTicketingReferenceId <i>optional</i>	Example : "ZAY091-2019-10-05-OT-19"	string
pnrTravelerId <i>optional</i>	Example : "ZAY091-2019-10-05-PT-1"	string

CorrelatedDataPnrInventory

Set of data field identifiers defining the correlation between a PNR and an Inventory Flight record.

Name	Description	Schema
inventoryPartnershipId <i>optional</i>	Example : "6X-567-2019-10-25"	string
inventorySegmentId <i>optional</i>	Example : "2019-10-15-NCE-CDG"	string
pnrAirSegmentId <i>optional</i>	Example : "ZAY091-2019-10-05-ST-1"	string

CorrelatedDataPnrMemberships

Set of data field identifiers defining the correlation between a PNR product/service and a Loyalty Membership.

Name	Description	Schema
pnrLoyaltyRequestId <i>optional</i>	Example : "ZAY091-2018-10-19-OT-9"	string
pnrProductId <i>optional</i>	Example : "ZAY091-2018-10-19-OT-7"	string

CorrelatedDataPnrSchedule

Set of data field identifiers defining the correlation between a PNR and a Schedule Flight record.

Name	Description	Schema
pnrAirSegmentId <i>optional</i>	Example : "ZAY091-2019-10-05-ST-1"	string
schedulePartnershipId <i>optional</i>	Example : "6X-567-2019-10-25"	string
scheduleSegmentId <i>optional</i>	Example : "2019-10-15-NCE-CDG"	string

CorrelatedDataPnrTicket

Set of data field identifiers defining the correlation between a PNR and a ticket.

Name	Description	Schema
pnrAirSegmentId <i>optional</i>	Example : "ZAY091-2019-10-05-ST-1"	string
pnrTicketingReferenceId <i>optional</i>	Example : "ZAY091-2019-10-05-OT-10"	string
pnrTravelerId <i>optional</i>	Example : "ZAY091-2019-10-05-PT-1"	string
ticketCouponId <i>optional</i>	Example : "1721234567890-2019-10-05-1"	string

CorrelationPnrBagsGroup

Structure of correlation between a Passenger Name Record and DCS Baggage.

Name	Description	Schema
bagsGroupIds <i>optional</i>	Identifiers of the DCS Baggage Groups correlated with the current Passenger Name Record. List of Baggage Group Identifiers. Example : ["AA42BA1395020102"]	< string > array

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataPnrBagsGroup > array > map
pnrId <i>optional</i>	Current record locator + its creation date. Example : "AA42BA1395020102"	string

CorrelationPnrDcsPassenger

Structure of correlation between a Passenger Name Record and DCS Passengers.

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataPnrDcsPassenger > array > map
dcsPassengerIds <i>optional</i>	Contains identifiers of the DCS Passengers [UCI] correlated with the current Passenger Name Record. Example : ["2501ADE0000001", "2501ADE0000005"]	< string > array
pnrId <i>optional</i>	Current record locator + its creation date. Example : "ZAY091-2019-10-05"	string

CorrelationPnrEmd

Structure of correlation between a Passenger Name Record and Electronic Miscellaneous Documents.

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataPnrEmd > array > map
emdIds <i>optional</i>	Contains identifiers of the EMDs correlated with the current Passenger Name Record - Format is EMD number + its issuance date. Example : ["1729999999999-2019-10-05", "172555555555-2019-10-05"]	< string > array
pnrId <i>optional</i>	Current record locator + its creation date. Example : "ZAY091-2019-10-05"	string

CorrelationPnrInventory

Structure of correlation between a Passenger Name Record and Inventory Flights.

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataPnrInventory > array > map
inventoryIds <i>optional</i>	Contains identifiers of the Inventory Dated Flights correlated with the current Passenger Name Record. Format is carrier code + flight number + flight date + operational suffix. Example : ["6X-123-2019-10-15", "6X-789-2019-10-25"]	< string > array
pnrId <i>optional</i>	Current record locator + its creation date. Example : "ZAY091-2019-10-05"	string

CorrelationPnrMembership

Structure of correlation between a Passenger Name Record and Loyalty Membership.

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataPnrMemberships > array > map
membershipIds <i>optional</i>	Identifiers of the Loyalty Memberships correlated with the current Passenger Name Record. Format is carrier code (owner of the program) + frequent flyer id (within the loyalty program) Example : ["6X-1234567890", "6X-1234567891"]	< string > array
pnrId <i>optional</i>	Current record locator + its creation date. Example : "ZAY091-2018-10-19"	string

CorrelationPnrSchedule

Structure of correlation between a Passenger Name Record and Schedule Flights.

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataPnrSchedule > array > map
pnrId <i>optional</i>	Current record locator + its creation date. Example : "ZAY091-2019-10-05"	string

Name	Description	Schema
scheduleIds <i>optional</i>	Contains identifiers of the Schedule Dated Flights correlated with the current Passenger Name Record. Format is carrier code + flight number + flight date + operational suffix. Example : ["6X-123-2019-10-15", "6X-789-2019-10-25"]	< string > array

CorrelationPnrTicket

Structure of correlation between a Passenger Name Record and tickets.

Name	Description	Schema
correlatedData <i>optional</i>		< string, < CorrelatedDataPnrTicket > array > map
pnrId <i>optional</i>	Current record locator + its creation date. Example : "ZAY091-2019-10-05"	string
ticketIds <i>optional</i>	Contains identifiers of the tickets correlated with the current Passenger Name Record. Format is ticket number + its issuance date. Example : ["1721234567890-2019-10-05", "1721234509876-2019-10-05"]	< string > array

CorrelationReferences

Name	Description	Schema
correlations <i>optional</i>	Correlation resources are defined in the "IncludedResources" node. This node provides links to all correlations resources associated with the current processed-pnr resource. Example : { "PnrTicket" : { "ref" : "included/correlationPnrTicket/ZAY091-2019-10-05" }, "PnrEmd" : { "ref" : "included/correlationPnrEmd/ZAY091-2019-10-05" }, "PnrDcsPassenger" : { "ref" : "included/correlationPnrDcsPassenger/ZAY091-2019-10-05" }, "PnrSchedule" : { "ref" : "included/correlationPnrSchedule/ZAY091-2019-10-05" }, "PnrInventory" : { "ref" : "included/correlationPnrInventory/ZAY091-2019-10-05" }, "PnrBagsGroup" : { "ref" : "included/correlationPnrBagsGroup/ZAY091-2019-10-05" }, "PnrMembership" : { "ref" : "included/correlationPnrMembership/ZAY091-2019-10-05" } }	correlations

correlations

Name	Schema
PnrBagsGroup <i>optional</i>	Relationship
PnrDcsPassenger <i>optional</i>	Relationship
PnrEmd <i>optional</i>	Relationship
PnrInventory <i>optional</i>	Relationship
PnrMembership <i>optional</i>	Relationship
PnrSchedule <i>optional</i>	Relationship
PnrTicket <i>optional</i>	Relationship

Coupon

Structure providing details on a given TST/TSM-P quotation coupon

Name	Description	Schema
associatedDocuments <i>optional</i>		< associatedDocuments > array
baggageAllowance <i>optional</i>	Define the rule about baggage allowance for this coupon	baggageAllowance
fareBasis <i>optional</i>		FareBasis
isFromConnection <i>optional</i>	Indicates whether the flight segment priced is departing from a connection with the previous flight Example : false	boolean
isFromStopOver <i>optional</i>	Indicates whether the flight segment priced is departing from a stop over relative to the previous flight Example : false	boolean
isNonExchangeable <i>optional</i>	Indicates the coupon's non-eligibility for the exchange operation. You can only exchange an EMD if none of the EMD coupons have this indicator set to true. Default value is false.	boolean
isNonInterlineable <i>optional</i>	Indicates that the coupon cannot be part of an interline itinerary. Default value is false.	boolean

Name	Description	Schema
isNonRefundable <i>optional</i>	Indicates the coupon's non-eligibility for the refund operation. Default value is false.	boolean
monetaryValue <i>optional</i>		ElementaryPrice
product <i>optional</i>		Relationship
reasonForIssuance <i>optional</i>		PriceCategory
servicePresentation <i>optional</i>		servicePresentation
serviceRemark <i>optional</i>	Service remark populated in EMD coupons (free text)	string
validityDates <i>optional</i>		validityDates

associatedDocuments

Name	Description	Schema
couponNumbers <i>optional</i>	Example : [1]	< integer > array
documentNumber <i>optional</i>	defines the number of the document Example : "1724546546479"	string
documentType <i>optional</i>	it defines if it's an electronic or a paper coupon Example : "ELECTRONIC"	enum (ETICKET, PAPER_TICKET)

baggageAllowance

Name	Description	Schema
quantity <i>optional</i>	Total number of units Example : 1	integer
weight <i>optional</i>		Weight

servicePresentation

Name	Description	Schema
atAirportIataCode <i>optional</i>	Location where the service document must be presented. Equals departure airport of associated flight e.g. 'LHR'	string
toCarrierIataCode <i>optional</i>	Carrier to which document must be presented. Equals marketing company code of associated SSR e.g. 6X	string

validityDates

Name	Description	Schema
notValidAfterDate <i>optional</i>	Not valid after date(GMT) in ISO 8601format,YYYY-MM-DD	string (date)
notValidBeforeDate <i>optional</i>	Not valid before date(GMT) in format ISO 8601 YYYY-MM-DD	string (date)

CurrencyConversionLookupRates

Conversion from provider's currency to requested currency

Name	Description	Schema
rate <i>optional</i>	The conversion factor to apply against the source currency to obtain the requested currency Example : "1.14"	string
target <i>optional</i>	Requested currency code Example : "EUR"	string

Dictionaries

Name	Description	Schema
bagsGroups <i>optional</i>	Set of key/value pairs with bagsGroupId as key i.e. DCS Baggage Group Identifier - key example 'AA42BA1395020102'	< string, Relationship > map
currencyConversionLookupRates <i>optional</i>	* Multiple base (many to one) * Used to define rate conversion when multiple currency possible * origin_amount = reverse_rate x target_amount * target_amount = rate x origin_amount * Example: currencyConversionLookupRates: { USD: { rate: "0.80", target: EUR }, GBP: { rate: "1.14", target: EUR } }	< string, CurrencyConversionLookupRates > map

Name	Description	Schema
dcsPassengers <i>optional</i>	Set of key/value pairs with dcsPassengerId as key i.e. CPR UCI - key example '2501ADE0000001'	< string, Relationship > map
emds <i>optional</i>	Set of key/value pairs with emdId as key i.e. primary EMD number + issuance date - key example '1721234567891-2018-05-15'	< string, Relationship > map
inventories <i>optional</i>	Set of key/value pairs with inventoryId as key [generated] - key example '6X12355515101900000NULL'	< string, Relationship > map
memberships <i>optional</i>	Set of key/value pairs with membershipId as key i.e. carrier code + frequent flyer id - key example '6X-1234567890'	< string, Relationship > map
pnrs <i>optional</i>	Set of key/value pairs with pnrId as key i.e. record locator + PNR creation date - key example 'ZAY091-2019-10-05'	< string, Relationship > map
schedules <i>optional</i>	Set of key/value pairs with scheduleId as key i.e. carrier code + flight number + flight date + operational suffix - key example '6X-123-2018-10-05-A'	< string, Relationship > map
tickets <i>optional</i>	Set of key/value pairs with ticketId as key i.e. primary ticket number + issuance date - key example '1721234567890-2018-05-15'	< string, Relationship > map

DisplayedFormOfPayment

Name	Description	Schema
authorization <i>optional</i>	Details on credit card authorization or award authorization [by Airline Loyalty System] in case of miles redemption/upgrade	Authorization
code <i>optional</i>	Form Of Payment category as defined in IATA PADIS code list for data element 9888. Examples - CC for Credit Card, CA for Cash, FFR for award redemption, FFR for award upgrade, CK for Check, MS for Miscellaneous, EF for Electronic Funds transfer. Example : "CC"	string
fopIndicator <i>optional</i>	Used to specify what the FOP has been used for, in case of exchanges. In case the PNR has been subject to first-issues only, fopIndicator is NEW. In case of exchanges, the FOPs used to settle the last documents show a fopIndicator set to NEW. For the other FOPs contained in the FP element, fopIndicator is set to OLD. Example : "NEW"	enum (NEW, OLD)
freeText <i>optional</i>	Free text as entered in FP element Example : "CCVI**9999/0523*CVA/CAD1500/AAPS10K"	string
paymentCard <i>optional</i>		PaymentCard

Name	Description	Schema
paymentLoyalty <i>optional</i>	Loyalty profile used for miles redemption/upgrade when code equals 'FFP'/'FFU'	PaymentLoyalty

ElementaryPrice

Structure representing any kind of monetary value

Name	Description	Schema
amount <i>optional</i>	Defines the monetary value with decimal position. It can be in cash or miles. Example : "5000.50"	string
currency <i>optional</i>	Defines a specific monetary unit using ISO4217 currency code Example : "CND"	string
elementaryPriceType <i>optional</i>	Defines the type of price, eg. for base fare, total, grand total Example : "BASE_FARE"	string
issueCurrencyType <i>optional</i>	Used for ATC use cases to specify if the currency code is a ICOS (Issue currency of Selling) or RCOS (Reissue currency of selling) Example : "ICOS"	string

Email

Email information.

Name	Description	Schema
address <i>optional</i>	Email address Example : " james.carter@gmail.com "	string

EventLog

Name	Description	Schema
comment <i>optional</i>	ReceiveFrom content [RF line] Example : "6X online BOOKING"	string
dateTime <i>optional</i>	GMT date & time Example : "2019-10-05T10:00:00Z"	string (date-time)
id <i>optional</i>	Unique identifier of a JSON message Example : "429074ef1bd011e3-e63dfe23f4a0adc"	string

Name	Description	Schema
pointOfSale <i>optional</i>		PointOfSale
triggerEventName <i>optional</i>	Trigger of the message - set to 'DATA_INIT' for initialization messages Example : "DATA_INIT"	string

Events

Structure of Dynamic Intelligence Hub functional events

Name	Description	Schema
events <i>optional</i>	List of events that have been detected on the record	< events > array
originFeedTimeStamp <i>optional</i>	Incoming PSS feed time stamp - not populated in correlation feeds Example : "2019-10-25T10:00:00Z"	string (date-time)
recordDomain <i>optional</i>	Functional domain of the record i.e. either functional PNR or PNR correlation. Possible values - PNR, PNR_TICKET, PNR_EMD, PNR_DCSPASSENGER, PNR_SCHEDULE, PNR_INVENTORY, PNR_MEMBERSHIP. Example : "PNR"	string
recordId <i>optional</i>	Record identifier e.g. record locator Example : "ZAY091-2019-10-05"	string

events

Name	Description	Schema
currentPath <i>optional</i>	String containing the JSON Pointer (see IETF RFC6901) that points to the data referenced by the event in the latest version of the entity. It is only applicable for CREATED and UPDATED events. Example : "/products/0/airSegment/bookingStatusCode"	string
eventType <i>optional</i>	In case of comparison events, type of operation notified by the event Example : "UPDATED"	enum (CREATED, UPDATED, DELETED)
origin <i>optional</i>	Type of event e.g. 'COMPARISON' / 'TIME_INITIATED_EVENT' Example : "COMPARISON"	string
previousPath <i>optional</i>	String containing the JSON Pointer (see IETF RFC6901) that points to the data referenced by the event in the previous version of the entity. It is only applicable for DELETED and UPDATED events. Example : "/products/0/airSegment/bookingStatusCode"	string

FareBasis

Composed of codes used by airlines to identify the type of a fare proposed to the booker and to allow airline staff and travel agents to find the rules applicable to that fare.

Name	Description	Schema
fareBasisCode <i>optional</i>	Defines the code of the fare delivered to the booker - up to 6 alphanumerical chars Example : "TTI"	string
primaryCode <i>optional</i>	Defines the category of the fare delivered to the booker - up to 3 letters Example : "BYM3M"	string
ticketDesignatorCode <i>optional</i>	Indicates a type of discount that has been applied to this fare - up to 6 alphanumerical chars Example : "CD10"	string

FareCalculation

Name	Description	Schema
isManual <i>optional</i>	Indicates whether the fare calculation stored in the quotation record has been inserted/updated by an agent or auto-generated as a result of a fare quote automated pricing transaction Example : false	boolean

Name	Description	Schema
pricingIndicator <i>optional</i>	The Fare Calculation Pricing Indicator provides a granular view of the pricing mode that has been used during the pricing. Thanks to the FCPI, the travel agency, the airline or any user can know what pricing combinations have been used at pricing time. 0: Automatically priced 1: Manually created or updated TST. 2: No fare: free or charter entered in the TST. 3: Pricing by fare basis. 4: Manual manipulation of taxes and/or fees at pricing or issuance time. 5: The system did not price according to the entered passenger type. 6: For US only: Exchange ticket request 7: Bulk fare ticket request 8: Fare price override at issuance time 9: Inclusive tour ticket request A: SATA fare used. B: Amount discount override applied to fare base at pricing time. C: Amount or percent discount override applied to total fare combined with segment selection at pricing time. D: Amount or percent discount override applied to base fare combined with segment selection at pricing time. E: Percentage discount override at pricing time. F: Private fares have been used at pricing time. G: Dynamic discounted fare used at pricing time. H: HIP may apply. The system has priced but is unable to check a higher intermediate point. I: Override Fare Calculation by M/IT at pricing time. J: Override fare diagnostic entry at pricing time. K: Override Fare Calculation by M/BT at pricing time L: Booking date override M: Negotiated rates have been used at pricing time. Agent/consolidator is a fare updater. N: Negotiated rates have been used at pricing time. Airline is a fare updater. O: Past date TST override at issuance time. P: Lowest possible fare override at pricing time. Q: Depends on TSTIndicator. Either Manually stored endorsement before pricing or Manually added a tour code (FT element) on a private or public fare R: Validating carrier override at issuance time. S: Booking class override used on negotiated fares. T: Amount discount override applied to Total fare at pricing time. U: Stopover/transfer override is used in the pricing entry. V: Pricing override used with a pricing past date. W: Booking class override used on non-negotiated fares. Z: Net fare field manually updated (not used in US market) Example : "0"	string
text <i>optional</i>	Content of the fare calculation Example : "PAR 6X YTO289.85SKWI5LGT 6X PAR289.85SKWI5LGT NUC579.70END ROE0.862490"	string

FareElement

used to describe fare elements contained in PNR

Name	Description	Schema
accounting <i>optional</i>		AccountingElement
code <i>optional</i>	Fare element code FM - Commissions AI - Accounting Information FP - Forms of Payment FD - Fare Discount FT - Tour Code FE - Endorsement FS - Miscellaneous Ticketing Information on TST FZ - Miscellaneous Information FB - Automatic Amadeus Interface Record Sequence Number FG - Automatic Shadow Amadeus Interface Record Sequence Number FI - Automatic Invoice Number FK - Amadeus Extended Ownership Agreement, FK element Provides List Of Offices For Amadeus Interface Records Sent By The Mirroring Process For Back Office Systems FN - Transmission Control Number FV - Validating Airline FY - Fare Price Override Example : "FM"	enum (FM, AI, FP, FD, FE, FS, FZ, FT, FB, FG, FI, FK, FN, FV, FY)
commissions <i>optional</i>		Commissions
formsOfPayment <i>optional</i>		< DisplayedFormOfPayment > array
id <i>optional</i>	Item identifier Example : "ZAY091-2019-10-05-OT-25"	string
isInfant <i>optional</i>	Indicates that the fare element applies to an infant passenger Example : false	boolean
products <i>optional</i>	Links to associated products Example : [{ "type" : "product", "id" : "ZAY091-2019-10-05-ST-1", "ref" : "processedPnr.products" }]	< Relationship > array
text <i>optional</i>	Used to specify the full content of the fare element - not applicable for Accounting Information Example : "*AM*10.12V12.12/C1234567.12/X0/1234567.12AV10.12/XP/1234567.12A/SC1234567.12/B124567A/D1234567/I12345675"	string
travelers <i>optional</i>	Links to associated stakeholders Example : [{ "type" : "stakeholder", "id" : "ZAY091-2019-10-05-PT-1", "ref" : "processedPnr.travelers" }]	< Relationship > array
type <i>optional</i>	Resource name Example : "fare-element"	enum (fare-element, payment-method)

Fee

Structure to describe a ticketing Fee

Name	Description	Schema
amount <i>optional</i>	Defines the monetary value with decimal position. It can be in cash or miles. Example : "5000.50"	string
code <i>optional</i>	Indicates the type of fee. Example : "OB"	string
currency <i>optional</i>	Defines a specific monetary unit using ISO4217 currency code Example : "CND"	string
description <i>optional</i>	Indicates the commercial name. Describes the fee	string
exempted <i>optional</i>	Indicates if fee is exempted or not Example : false	boolean
requested <i>optional</i>	Indicates if fee is Requested or not Example : true	boolean
subCode <i>optional</i>	Identify uniquely the OB fee associated to the TST - 1.Automated ticketing subcode (Txx) 2. Non-automated ticketing subcodes (Rxx) Example : "TX003"	string
taxIncluded <i>optional</i>	Indicates if fee the tax is included or not Example : true	boolean
taxes <i>optional</i>		< Tax > array

FlightBoundItem

Name	Schema
connectedFlights <i>optional</i>	ConnectedFlightSegments
flightSegment <i>optional</i>	Relationship

FlightBounds

Convey the Origin & Destination items determined by Inventory Journey Server at availability process - each O & D pointing to a collection of flight segments i.e. product resources.

Type : < [FlightBounds](#) > array

FlightBounds

Name	Description	Schema
destinationIataCode <i>optional</i>	Destination location code - IATA airport/city code Pattern : "[A-Z]{3}" Example : "JFK"	string
flights <i>optional</i>		< FlightBoundItem > array
originIataCode <i>optional</i>	Origin location code - IATA airport/city code Pattern : "[A-Z]{3}" Example : "JFK"	string
pointOfCommencement <i>optional</i>		pointOfCommencement
type <i>optional</i>	Conveys type of flight bound Example : "CUSTOMER_TRANSACTION_DATA_BOUND"	string
yield <i>optional</i>	Yield defined by Revenue Management System at geographical Origin & Destination level elementaryPriceType set to "ORIGIN_AND_DESTINATION_YIELD"	ElementaryPrice

pointOfCommencement

Name	Description	Schema
address <i>optional</i>		Address
iataCode <i>optional</i>	IATA location code Example : "CDG"	string
name <i>optional</i>	Label associated to the location (e.g. Eiffel Tower, Madison Square) Example : "Charles De Gaulle"	string
subType <i>optional</i>	Location sub-type (e.g. airport, port, rail-station, restaurant, atm...) Example : "airport"	string
timeZoneName <i>optional</i>	Olson format name (TZ) of the location time zone (https://en.wikipedia.org/wiki/List_of_tz_database_time_zones) Example : "Europe/Paris"	string

FlightDesignator

Name	Description	Schema
carrierCode <i>optional</i>	Two letter IATA standard carrier code Example : "6X"	string

Name	Description	Schema
flightNumber <i>optional</i>	1-4 digit number Example : "555"	string
operationalSuffix <i>optional</i>	1 char as flight number suffix Example : "A"	string

FlightEndPoint

Departure or arrival information

Name	Description	Schema
checkInEndTime <i>optional</i>	Time at which the check-in closes for the current flight Example : "10:50"	string
iataCode <i>optional</i>	IATA Airport code Example : "JFK"	string
localDateTime <i>optional</i>	Local date and time with the following format "YYYY-MM-DD'T'HH:mm:ss" Example : "2019-10-25T10:00:00"	string
terminal <i>optional</i>	Terminal name / number Example : "1"	string

FlightSegment

Defining a flight segment, including both Operating and Marketing details when applicable - seats refer to SEATING product(s) & services refer to AIR_SERVICE product(s).

Name	Description	Schema
aircraft <i>optional</i>		AircraftEquipment
arrival <i>optional</i>		FlightEndPoint
bookingStatusCode <i>optional</i>	Status code of the flight sale. For example - HK = confirmed, HL = waitlist, UN = unable to confirm not operating, UC = unable to confirm, HX = have cancelled, NO = no action taken. Example : "HK"	string
creation <i>optional</i>	Date and time at which the flight segment has been originally sold in PNR	EventLog
deliveries <i>optional</i>		< SegmentDelivery > array

Name	Description	Schema
departure <i>optional</i>		FlightEndPoint
isDominantInMarriage <i>optional</i>	In case the flight segment is part of a marriage, it indicates whether it has been used to determine the O & D yield. In most cases, the long haul flight of the O & D is dominant. Example : false	boolean
isInformational <i>optional</i>	Indicates an informational flight segment i.e. already booked on another system. Example : false	boolean
marketing <i>optional</i>		MarketingFlight
operating <i>optional</i>		OperatingFlight
product <i>optional</i>	Used by FlightTransfer attributes fromSegments & toSegments	Relationship
seats <i>optional</i>		< Relationship > array
services <i>optional</i>		< Relationship > array

FlightTransfer

Name	Description	Schema
associatedOrder <i>optional</i>		AssociatedPnr
fromSegments <i>optional</i>	All the segments from which the passengers have been disrupted/reaccommodated.	< FlightSegment > array
id <i>optional</i>	Unique Disruption Transfer (COP) or Enhanced Reaccommodation (TRR) id Example : "10121277"	string
subType <i>optional</i>	Example : "CUSTOMER_OPERATIONAL_PROTECTION"	enum (CUSTOMER_OPERATIONAL_PROTECTION, TRAVEL_READY_REACCOMMODATION)
toSegments <i>optional</i>	All the segments to which the passengers have been disrupted/reaccommodated.	< FlightSegment > array
travelers <i>optional</i>	Definition of PNR travelers impacted by Disruption Transfer.	< Stakeholder > array

Name	Description	Schema
type <i>optional</i>	Example : "hard-coded as 'flight-disruption-transfer'"	string

IdentityDocument

The information that are found on an ID document.

Name	Description	Schema
birthDate <i>optional</i>	Birth date in ISO8601 format. Example : "1978-10-05"	string (date)
birthPlace <i>optional</i>	Birth place as indicated on the document Example : "PARIS"	string
documentType <i>optional</i>	The nature/type of the document. Example : "PASSPORT"	enum (PASSPORT, APPROVED_DOCUMENT, CREW_MEMBER_CERTIFICATE, PASSPORT_CARD, VISA, IDENTITY_CARD, REDRESS, OTHER_DOCUMENT)
expiryDate <i>optional</i>	Date after which the document is not valid anymore. Example : "2025-10-05"	string (date)
gender <i>optional</i>	Gender as it appears on the document Example : "MALE"	enum (MALE, FEMALE, UNKNOWN)
issuanceCountry <i>optional</i>	ISO code (2-letters) of the country that issued the document. Pattern : "[a-zA-Z]{2,3}" Example : "FRA"	string
issuanceDate <i>optional</i>	Date at which the document has been issued. Example : "2019-10-05"	string (date)
issuanceLocation <i>optional</i>	A more precise information concerning the place where the document has been issued, when available. It may be a country, a state, a city or any other type of location. example: 'PARIS OFFICE'	string
name <i>optional</i>	Only fullName, firstName and lastName	Name
nationality <i>optional</i>	ISO code (2-letters) of the nationality appearing on the document Pattern : "[a-zA-Z]{2,3}" Example : "FRA"	string

Name	Description	Schema
number <i>optional</i>	The document number (shown on the document) e.g. QFU514563221J Example : "15FR1234"	string

IncludedResources

Name	Description	Schema
correlationPnrBagsGroup <i>optional</i>	Correlation resource - Pnr correlation with DCS Baggage	< string, CorrelationPnrBagsGroup > map
correlationPnrDcsPassenger <i>optional</i>	Correlation resource - Pnr correlation with DCS Passenger	< string, CorrelationPnrDcsPassenger > map
correlationPnrEmd <i>optional</i>	Correlation resource - Pnr correlation with Ticket Electronic Miscellaneous Document	< string, CorrelationPnrEmd > map
correlationPnrInventory <i>optional</i>	Correlation resource - Pnr correlation with Inventory	< string, CorrelationPnrInventory > map
correlationPnrMembership <i>optional</i>	Correlation resource - Pnr correlation with Loyalty Membership	< string, CorrelationPnrMembership > map
correlationPnrSchedule <i>optional</i>	Correlation resource - Pnr correlation with Schedule	< string, CorrelationPnrSchedule > map
correlationPnrTicket <i>optional</i>	Correlation resource - Pnr correlation with Ticket	< string, CorrelationPnrTicket > map

InfrastructureLocation

Name	Description	Schema
areaCode <i>optional</i>	Location type, e.g. CKI for Checkin counter, GTE for gate area Possible values are ADM ATO BCA BDP BMD BOF CAR CAT CKI CSD CTO DUT ECC ENG FIN FOP GTE IMM ITS LCO LGE MVC NOP OTH PSF RAM REG ROM SBD SEC SSH SSK SUP TAG TKT TRA TRN Example : "CKI"	string
description <i>optional</i>	non-structure freeflow description of the location Example : "LHR TERM-4 CKI 101"	string

Name	Description	Schema
identifier <i>optional</i>	location identifier Example : "101"	string

InterAirlineThroughCheckIn

Name	Description	Schema
onwardFlight <i>optional</i>		InterAirlineThroughCheckIn_FlightSegment
originatorCompany <i>optional</i>	In case of Inbound IATCI, this is the code of the company that performed the check in Example : "8X"	string
targetCompany <i>optional</i>	In case of Outbound IATCI, this is the code of the company on which check in is performed Example : "8X"	string
targetDCSCode <i>optional</i>	Code of the DCS system where the IATCI check in is performed Example : "1S"	string

InterAirlineThroughCheckIn_FlightSegment

Flight segment details

Name	Schema
departure <i>optional</i>	FlightEndPoint
marketing <i>optional</i>	MarketingFlight

IssueSource

an object containing references to the source of the error

Name	Description	Schema
parameter <i>optional</i>	A string indicating which URI query parameter caused the issue	string
pointer <i>optional</i>	A JSON Pointer [RFC6901] to the associated entity in the request document	string

LegDelivery

Product Delivery Information related to legs

Name	Description	Schema
acceptance <i>optional</i>		AcceptanceDelivery
arrival <i>optional</i>	arrival information of the leg, limited to iataCode	FlightEndPoint
boarding <i>optional</i>	Boarding delivery for that leg	BoardingDelivery
comments <i>optional</i>	list of comments assigned to the passenger in the DCS system	< Comment > array
compensation <i>s</i> <i>optional</i>		< Compensation > array
departure <i>optional</i>	departure information of the leg, limited to iataCode	FlightEndPoint
handlingCarrier <i>optional</i>	the 2 or 3 characters code of the handling carrier. Note that this can also refer to a ground handler. Example : "7X"	string
hasBags <i>optional</i>	indicates whether the passenger has bags Example : true	boolean
id <i>optional</i>	identifier of the leg delivery in the PnrApiData Example : "ZAY091-2019-05-04-OT-66"	string
onload <i>optional</i>	Onload information for that leg - populated by onload recommendation.	Onload
regrade <i>optional</i>		Regrade
regulatoryChecks <i>optional</i>		< RegulatoryChecks > array
seating <i>optional</i>		SeatingDelivery
type <i>optional</i>	resource name Example : "leg-delivery"	enum (leg-delivery)

Login

Name	Description	Schema
cityCode <i>optional</i>	city code of the issuing agent/system Example : "NCE"	string
countryCode <i>optional</i>	ISO country code of the agent Example : "FR"	string
currencyCode <i>optional</i>	ISO currency code of the agent Example : "EUR"	string
dutyCode <i>optional</i>	duty code of the agent Example : "SU"	string
initials <i>optional</i>	agent initials Example : "JF"	string
numericSign <i>optional</i>	Authorization code of the agent Example : "0001"	string

MarketingFlight

Name	Description	Schema
bookingClass <i>optional</i>		BookingClass
flightDesignator <i>optional</i>		FlightDesignator
isOpenNumber <i>optional</i>	Indicates an open flight segment, for which there is no specific flight number. Example : false	boolean
overBookingReason <i>optional</i>	Indicates the Inventory origin of overbooking Example : "FORCE_BOOKING"	enum (FORCE_BOOKING, INVENTORY_SYNCHRONIZATION)

Membership

Name	Description	Schema
activeTier <i>optional</i>		Tier
allianceTier <i>optional</i>		Tier
id <i>optional</i>	Identifies the customer profile i.e. either Frequent Flyer Number or Corporate Recognition Number Example : "1234567890"	string

Name	Description	Schema
membershipType <i>optional</i>	Nature of the membership Example : "INDIVIDUAL"	enum (INDIVIDUAL, CORPORATE)

Meta

Technical information related to the feed

Name	Description	Schema
triggerEventLog <i>optional</i>	information related to the initial event that trigger the process	EventLog
version <i>optional</i>	Version of the JSON feed produced	string

Name

Description of the name of a physical person.

Name	Description	Schema
firstName <i>optional</i>	Example : "JAMES"	string
fullName <i>optional</i>	Only populated for passengerDelivery resources Example : "JAMES CARTER"	string
lastName <i>optional</i>	Example : "CARTER"	string
referenceNameType <i>optional</i>	Type of the reference name. When several name entities exist for a given Name element(e.g. Universal name, both Native names, Romanized name), the notion of reference name (i.e. active/main name) exists. It can be either the Universal name or the Native/Phonetic name. Example : "UNIVERSAL"	enum (UNIVERSAL, NATIVE_ROMANIZATION_ASCII, NATIVE_ROMANIZATION_ASCII_EXTENDED, NATIVE_ROMANIZABLE, NATIVE_NON_ROMANIZABLE)
title <i>optional</i>	Contains any suffixes/prefixes that can be appended to a name - e.g. MR, MISS, PR Example : "MR"	string

Name	Description	Schema
transliterationMethod <i>optional</i>	The method (if applicated) that was used to transform the name from universal character (e.g. Korean characters) to Latin characters/phonetic transcription/... Possible values are REVISED_KOREAN_ROMANIZATION or MAC_CUNE_REISHAUER Example : "REVISED_KOREAN_ROMANIZATION"	string

NegoFareContract

Nature and reference of the commercial agreement by which the airline incentivizes the selling travel agency for the quoted negotiated fare. This specific type of fare is used in conjunction with tours, referring to Inclusive Tour fares and Bulk Tour fares. The agent incentive on the IT/BT fare notably depends on the commission element entered in PNR.

Name	Description	Schema
contractReference <i>optional</i>	Exclusive with netRemitSchemeReference Example : "SKYTOUR007"	string
incentiveScheme <i>optional</i>	Nature of the agreement between the airline and the selling travel agency Example : "NET_REMIT"	enum (NET_REMIT, INCLUSIVE_TOUR, BULK_TOUR, INCLUSIVE_TOUR_WITH_NET_REMIT, BULK_TOUR_WITH_NET_REMIT, FLEXIBLE_COMMISSION)
netRemitReference <i>optional</i>	Exclusive with commercialAgreementReference Example : "SKYAIRLINE"	string
tourCode <i>optional</i>	Tour code stored in TST NEGO Example : "SKYWORLDTOUR"	string

Office

Name	Description	Schema
agentType <i>optional</i>	The issuing channel. Example : "AIRLINE"	enum (AIRLINE, TRAVEL_AGENT)
iataNumber <i>optional</i>	IATA assigned office number Example : "15398195"	string
id <i>optional</i>	AMID - office id in Amadeus Example : "NCE6X08AA"	string

Name	Description	Schema
systemCode <i>optional</i>	Identifier of the airline/CRS that originated the transaction [2-3 characters]. Length : 2 - 3 Example : "6X"	string

Onload

Structure containing the onload information

Name	Description	Schema
cabinCode <i>optional</i>	Target cabin code post onload recommendation Example : "C"	string
status <i>optional</i>	Status of the onload of the passenger(OLD = OK, NOL = NOK, OLR = OK Regrade, RGD = Regrade, OFL = Offload, NA = Not Applicable) Example : "OLD"	string

OperatingFlight

Name	Description	Schema
bookingClass <i>optional</i>		BookingClass
codeshareAgreement <i>optional</i>	Nature of agreement between the operating & marketing carriers on the given codeshare flight. BLOCKSPACE - Operating carrier has allotted specific seats on its flight for the carrier marketing the codeshare. FREEFLOW - Marketing carrier can sell seats on the codeshare flight as much as wanted, and only stops doing so when the Operating carrier sends a recap to close the class. CAPPED_FREEFLOW - Marketing carrier has been attributed a seating cap for the given codeshare flight, above which it must stop sales. Example : "BLOCKSPACE"	enum (BLOCKSPACE, FREEFLOW, CAPPED_FREEFLOW)
flightDesignator <i>optional</i>		FlightDesignator
overBookingReason <i>optional</i>	Indicates the Inventory origin of overbooking Example : "FORCE_BOOKING"	enum (FORCE_BOOKING, INVENTORY_SYNCHRONIZATION)

PassengerDelivery

Product Delivery Information related to passengers

Name	Description	Schema
bagsGroupDeliveries <i>optional</i>		< BagsGroup > array
deliveryAirlineCode <i>optional</i>	Airline responsible for the passenger delivery data Example : "6X"	string
excessBaggageStatus <i>optional</i>	if the passenger has excess baggage this indicates the status related to pricing and payment Example : "PAID"	enum (PAID, UNPAID, WAIVED, CALCULATED, TICKETS_ISSUED)
id <i>optional</i>	item identifier Example : "ZAY091-2019-05-04-0T-64"	string
lastTrackedTimeLocation <i>optional</i>	last recorded location of the passenger at the airport (e.g. at checkin, gate,...)	TimeLocationTrackingLog
passengerDetails <i>optional</i>	personalDetails recorded in DCS at passenger level	PassengerDelivery_Stakeholder
type <i>optional</i>	resource name Example : "passenger-delivery"	enum (passenger-delivery)

PassengerDelivery_Stakeholder

PersonalDetails recorded in DCS at passenger level

Name	Description	Schema
age <i>optional</i>	Age of the stakeholder Example : 40	integer
dateOfBirth <i>optional</i>	The stakeholder's date of birth Example : "1978-10-05"	string (date)
gender <i>optional</i>	Gender of the stakeholder Example : "MALE"	enum (MALE, FEMALE, UNKNOWN)
passengerTypeCode <i>optional</i>	3-characters code defining the passenger type - possible values: ADT, CHD, INS, INF, UNA Maximal length : 3 Example : "ADT"	string

PatchOperation

A single JSON Patch operation as defined by RFC 6902 (see <https://tools.ietf.org/html/rfc6902>)

Name	Description	Schema
from <i>optional</i>	A JSON Pointer as defined by RFC 6901 (see https://tools.ietf.org/html/rfc6901)	string
op <i>required</i>	The operation to be performed	enum (add, remove, replace, move, copy, test)
path <i>required</i>	A JSON Pointer as defined by RFC 6901 (see https://tools.ietf.org/html/rfc6901)	string
value <i>optional</i>	The value to be used within the operations	object

PaymentCard

Payment card information

Name	Description	Schema
expiryDate <i>optional</i>	Expiration date of the card - format is month & year - MMY Example : "0318"	string
holderName <i>optional</i>	Name of credit card holder. Example : "SMITH"	string
maskedCardNumber <i>optional</i>	Masked credit card number Example : "**9999"	string
vendorCode <i>optional</i>	Vendor code in case the FOP is a credit card - designates the card brand. For instance, VI for Visa, CA for MasterCard, etc. Example : "CA"	string

PaymentLoyalty

Name	Description	Schema
certificateNumber <i>optional</i>	Identifies an optional pool of miles provided by the airline owning the loyalty program that can be requested as input to the redemption request [FQTR/FQTU insertion]	string
membership <i>optional</i>	Loyalty profile used for award payment i.e. miles redemption/upgrade [for FOP codes 'FFP'/'FFU']	Membership

Phone

Phone information.

Name	Description	Schema
category <i>optional</i>	Category of the contact element Example : "PERSONAL"	enum (PERSONAL, BUSINESS, AGENCY)
deviceType <i>optional</i>	Type of the device (Landline, Mobile or Fax) Example : "MOBILE"	enum (MOBILE, LANDLINE, FAX)
number <i>optional</i>	Phone number. Composed of digits only. The number of digits depends on the country. Pattern : "[0-9]{1,15}" Example : "0033612345678"	string

PnrCorrelationsFeedData

Name	Schema
correlationPnrBagsGroup <i>optional</i>	CorrelationPnrBagsGroup
correlationPnrDcsPassenger <i>optional</i>	CorrelationPnrDcsPassenger
correlationPnrEmd <i>optional</i>	CorrelationPnrEmd
correlationPnrInventory <i>optional</i>	CorrelationPnrInventory
correlationPnrMembership <i>optional</i>	CorrelationPnrMembership
correlationPnrSchedule <i>optional</i>	CorrelationPnrSchedule
correlationPnrTicket <i>optional</i>	CorrelationPnrTicket
dictionaries <i>optional</i>	Dictionaries

PnrCorrelationsPushFeed

Name	Schema
events <i>optional</i>	Events
meta <i>optional</i>	Meta

Name	Schema
pnrCorrelations <i>optional</i>	PnrCorrelationsFeedData

PnrFeedData

Polymorphism : Composition

Name	Description	Schema
associatedPnr <i>optional</i>		< AssociatedPnr > array
automatedProcesses <i>optional</i>	Ticketing arrangements & Amadeus Time Limit	< AutomatedProcess > array
contacts <i>optional</i>	global contacts i.e. non-related to a particular traveler	< Contact > array
creation <i>optional</i>		EventLog
fareElements <i>optional</i>	Elements in reservation related to pricing	< FareElement > array
flightItinerary <i>optional</i>		FlightBounds
flightTransfer <i>optional</i>		FlightTransfer
group <i>optional</i>		TravelersGroup
id <i>optional</i>	id of Passenger name record Example : "ZAY091-2019-10-05"	string
keywords <i>optional</i>	Special Keywords, Other Service Information	< Service > array
lastModification <i>optional</i>		EventLog
loyaltyRequests <i>optional</i>	Loyalty elements for Frequent Flyers & Corporate Program users	< Service > array
nip <i>optional</i>	Order Number In Party - number of passengers in the order Example : 5	integer

Name	Description	Schema
owner <i>optional</i>		PointOfSale
paymentMethods <i>optional</i>	FOPs i.e. FP lines contained in reservation.	< FareElement > array
pnrProperties <i>optional</i>	PNR header flags	< enum (CODESHARE, STANDBY_STAFF, BOOKABLE_STAFF, NON_COMMERCIAL, GROUP, OTHER_AIRLINE, HAS_HYBRID, HAS_FEDERAL_AIR_ MARSHAL, HAS_CORPORATE, HAS_PREPAID_TICKE T_ADVICE, TTY_END_OF_TRANS ACTION, EDIFACT_CLAIM, TERMINAL_EMULAT OR_CLAIM, OPERATING_DCS, THIRD_PARTY_MIGR ATION, HAS_GROUND_HAND LING, MASS_MIGRATED, INTERNATIONAL, DOMESTIC) > array
products <i>optional</i>	A product is either a flight segment or a service booked in reservation	< Product > array
queuingOffice <i>optional</i>	Default office onto which PNR is queued - limited to office ID.	Office
quotations <i>optional</i>	Pricing records stored in reservation	< QuotationRecord > array
reference <i>optional</i>	Unique identifier for the order Example : "ZAY091"	string
remarks <i>optional</i>		< Remark > array
ticketingReferences <i>optional</i>	Travel document references contained in reservation	< TicketingReference > array

Name	Description	Schema
travelers <i>optional</i>		< Stakeholder > array
type <i>optional</i>	resource name Example : "pnr"	enum (pnr)
version <i>optional</i>	Current envelope number Example : "1"	string

PnrHeader

Name	Description	Schema
associatedPnr <i>optional</i>		< AssociatedPnr > array
creation <i>optional</i>		EventLog
group <i>optional</i>		TravelersGroup
id <i>optional</i>	id of Passenger name record Example : "ZAY091-2019-10-05"	string
lastModification <i>optional</i>		EventLog
nip <i>optional</i>	Order Number In Party - number of passengers in the order Example : 5	integer
owner <i>optional</i>		PointOfSale

Name	Description	Schema
pnrProperties <i>optional</i>	PNR header flags	< enum (CODESHARE, STANDBY_STAFF, BOOKABLE_STAFF, NON_COMMERCIAL, GROUP, OTHER_AIRLINE, HAS_HYBRID, HAS_FEDERAL_AIR_ MARSHAL, HAS_CORPORATE, HAS_PREPAID_TICKE T_ADVICE, TTY_END_OF_TRANS ACTION, EDIFACT_CLAIM, TERMINAL_EMULAT OR_CLAIM, OPERATING_DCS, THIRD_PARTY_MIGR ATION, HAS_GROUND_HAND LING, MASS_MIGRATED, INTERNATIONAL, DOMESTIC) > array
queuingOffice <i>optional</i>	Default office onto which PNR is queued - limited to office ID.	Office
reference <i>optional</i>	Unique identifier for the order Example : "ZAY091"	string
type <i>optional</i>	resource name Example : "pnr"	enum (pnr)
version <i>optional</i>	Current envelope number Example : "1"	string

PnrPushFeed

Name	Description	Schema
events <i>optional</i>		Events
meta <i>optional</i>		Meta

Name	Description	Schema
previousRecord <i>optional</i>	List of JSON Patches as defined by RFC 6902 (see https://tools.ietf.org/html/rfc6902) to apply to processedPnr [latest PNR version] in order to obtain the actual JSON of the previous PNR version.	< PatchOperation > array
processedPnr <i>optional</i>		PnrFeedData

PointOfSale

Name	Schema
login <i>optional</i>	Login
office <i>optional</i>	Office

Price

Name	Description	Schema
currency <i>optional</i>	currency	string
detailedPrices <i>optional</i>		< ElementaryPrice > array
fees <i>optional</i>		< Fee > array
taxes <i>optional</i>		< Tax > array
total <i>optional</i>	total amount	string

PriceCategory

AN EMD IS CATEGORISED BASED ON ITS REASON FOR ISSUANCE CODE (RFIC), WHICH DEFINES THE GROUP OF SERVICES IT BELONGS TO. THERE CAN ONLY BE ONE RFIC CODE PER EMD. SOME CODES ARE DEFINED BY IATA, HOWEVER, OTHERS CAN BE DEFINED BY INDIVIDUAL AIRLINES. AN EMD, AND EACH RFIC, CAN HAVE MULTIPLE REASON FOR ISSUANCE SUB-CODES (RFISC). THERE IS ONE RFISC IN EACH EMD COUPON AND THEY ARE AIRLINE-SPECIFIC.

Name	Description	Schema
code <i>optional</i>	The reason for issuance code (RFIC) chargeability indicator defined for the sellable object Example : "C"	string
description <i>optional</i>	description of reason for issuance sub code Example : "PET IN CABIN - CAT"	string
subCode <i>optional</i>	The reason for issuance sub code (RFISC) chargeability indicator defined for the sellable object Example : "0BT"	string

PricingConditions

Name	Description	Schema
fareCalculati on <i>optional</i>		FareCalculation
fareType <i>optional</i>	Nature of the fare obtained as a result of the pricing transaction. While public fares are accessible from any Point Of Sales, private fares are restricted to some POS set up in a security table. Negotiated fares are a special type of private fare that is backed up by a contractual distribution agreement whereby the airline is expected to provide agents with incentives for the fare sold.	enum (PRIVATE, NEGOTIATED)
flags <i>optional</i>	Flags pertaining to the pricing transaction involved in the current quotation/document Example : ["BOOKING_CLASS_OVERRIDE", "ZAP_OFF"]	< enum (FARE_BASIS_OVERRIDE, MILEAGE_OVERRIDE, BOOKING_CLASS_OVERRIDE, ZAP_OFF) > array
isDomesticSale <i>optional</i>	Domestic fare applied for the given itinerary	boolean
isInternationalSale <i>optional</i>	International fare applied for the given itinerary	boolean
negoFareContract <i>optional</i>		NegoFareContract
paymentRestriction <i>optional</i>	Indicates if the fare provides any restrictions related to payment methods that will be used at issuance Example : "NO VISA PAYMENT ON INDIAN MARKET"	string

Name	Description	Schema
waiverReason <i>optional</i>	Defines the reason for the fare to be waived Example : "PASSENGER DISRUPTED"	string

Product

A product can either be a flight segment, a standalone service, an air service i.e. related to flight segment(s), or a seat request made on a given flight segment. A service can be auxiliary [SVC] or ancillary service i.e. a Special Service Request [SSR].

Name	Description	Schema
airSegment <i>optional</i>		FlightSegment
id <i>optional</i>	item identifier Example : "ZAY091-2019-10-05-ST-1"	string
products <i>optional</i>		< Relationship > array
seating <i>optional</i>		Service
service <i>optional</i>		Service
subType <i>optional</i>	Example : "SERVICE"	enum (AIR, SERVICE, SEATING)
travelers <i>optional</i>		< Relationship > array
type <i>optional</i>	resource name Example : "product"	enum (product)

QuotationRecord

Structure to describe a given pricing

Name	Description	Schema
coupons <i>optional</i>	Defines the price information related to the coupons stored in the current pricing record	< Coupon > array
creation <i>optional</i>	Date & office of pricing record creation	EventLog
currencyConversionLookupRates <i>optional</i>	Conveys currency conversion information from provider's currency to requested currency	< CurrencyConversionLookupRates > array

Name	Description	Schema
destinationCityIataCode <i>optional</i>	Defines the destination city of the quotation itinerary	string
documentType <i>optional</i>	Document type indicator indicates if the TST must be issued as a paper ticket or electronic ticket, or if the TSM-P must be issued as an associated EMD or standalone EMD. Example : "ETICKET"	enum (TICKET, ETICKET, PAPER_TICKET, EMD_STANDALONE, EMD_ASSOCIATED)
fareElements <i>optional</i>	Example : [{ "type" : "fare-element", "id" : "ZAY091-2019-05-04-OT-45", "ref" : "processedPnr.fareElements" }]	< Relationship > array
flags <i>optional</i>	Flags attributed to the current quotation record Example : ["CONFIDENTIAL", "PNR_CHANGED"]	< enum (CONFIDENTIAL, PNR_CHANGED, TSM_ISSUED, ISSUANCE_REQUIRED) > array
id <i>optional</i>	Defines the identifier of Pricing Record. Example : "ZAY091-2019-01-15-QT-1"	string
isManual <i>optional</i>	Indicates whether the pricing record has been created/updated by an agent or auto-generated as a result of a fare quote automated pricing transaction Example : false	boolean
issuanceType <i>optional</i>	This indicator defines the Issued indicator of a pricing record Example : "FIRST_ISSUE"	enum (FIRST_ISSUE, REISSUE, FIRST_ISSUE_IT_FARE, FIRST_ISSUE_BT_FARE, REISSUE_IT_FARE, REISSUE_BT_FARE)
lastModification <i>optional</i>	Date & office of the last modification on the pricing record	EventLog
lastTicketingDate <i>optional</i>	Defines the last issuance date of the pricing record Example : "2018-08-10"	string (date)
originCityIataCode <i>optional</i>	Defines the origin city of the quotation itinerary	string
paymentMethods <i>optional</i>	Example : [{ "type" : "payment-method", "id" : "ZAY091-2019-05-04-OT-47", "ref" : "processedPnr.paymentMethods" }]	< Relationship > array
price <i>optional</i>		Price

Name	Description	Schema
pricingConditions <i>optional</i>		PricingConditions
remark <i>optional</i>	Remark free text entered by the agent in TSM quotation record Example : "SPECIAL SERVICE PRICING"	string
subType <i>optional</i>	Defines the type of pricing record - TST quotation record or TSM quotation record Example : "TSM_P"	enum (TST, TSM_P)
travelers <i>optional</i>	Example : [{ "type" : "stakeholder", "id" : "ZAY091-2019-10-05-PT-1", "ref" : "processedPnr.travelers" }]	< Relationship > array
type <i>optional</i>	Resource name Example : "quotation-record"	enum (quotation-record)

Regrade

Structure containing the regrade information

Name	Description	Schema
authoriserReference <i>optional</i>	Regrade authoriser reference Example : "AU0123"	string
cabinCode <i>optional</i>	Regrade cabin code - has value only in case of Regrade Proposed Example : "C"	string
direction <i>optional</i>	Regrade direction Example : "UPGRADE"	enum (UPGRADE, DOWNGRADE, NEUTRAL)
priority <i>optional</i>	Regrade priority Example : "31"	string
reasonCode <i>optional</i>	Regrade reason code Example : "OC"	enum (OC, OO, MC, PM, SO, AC, CF, RQ, CO, AB, MI, DC, DO, CC, TR, CS, CI, IA, US, SR, ST, CR, VO, BM, PD, HC, MM, CA, CD, DP, MA, OL)
reasonFreeText <i>optional</i>	Regrade reason in free text Example : "Oversold current flight"	string

Name	Description	Schema
reasonLabel <i>optional</i>	Regrade reason label corresponding to reason code	enum (OVERSOLD_CURRENT_FLIGHT, OVERSOLD_OTHER_FLIGHT, CUSTOMER_MISIDENTIFICATION_AT_CHECKIN, PREVIOUSLY_MISHANDLED, SPECIAL_OCCASION, AIRCRAFT_CHANGE, CABIN_CONFIGURATION_CHANGE, SPECIAL_REQUESTOR, COMPASSIONATE, AUTHORIZED_BY, MARKETING_INITIATIVE, DISRUPTION_CURRENT_FLIGHT, DISRUPTION_OTHER_FLIGHT, CREW_CHANGE, TECHNICAL_REASON , CATERING_SHORTFALL, CHECKIN_ERROR, INADMISSIBLE, UNSUITABLE, STAFF, SERVICE_RECOVERY_ENTITLEMENT, COURTESY, CUSTOMER_DOWNGRADE_REQUESTED, BOOKED_MARKETING_UPGRADE, INVOLUNTARY_DOWNGRADE, TICKETED_IN_HIGHER_CLASS, FREQUENT_FLYER_UPGRADE, CANCEL_ACCEPTANCE, CUSTOMER_DOWNGRADE_REQUIREMENT, DUPLICATE_PRODUCT, MANAGEMENT_AUTHORIZED, ONLOAD)

Name	Description	Schema
regradeType <i>optional</i>	Regrade type Example : "INVOLUNTARY"	enum (INVOLUNTARY, REMAIN_FORCE, NO_REGRADE)

RegulatoryChecks

Name	Description	Schema
regulatoryProgram <i>optional</i>	details of the regulatory program	RegulatoryProgram
statuses <i>optional</i>	list of regulatory statuses	< RegulatoryStatus > array

RegulatoryComment

Structure to represent a comment received by the authorities in the context of a regulatory check

Name	Description	Schema
code <i>optional</i>	4 digit code for directive type comment or G=Government, A=Airline for APP authorizer Example : "8517"	string
commentType <i>optional</i>	Indicates the type of comment from Regulatory System ("Directive" in case of APP, "Override Authorizer" for APP and iAPP, "Special Instructions" for iAPP, "reason" for ADC) Example : "reason"	string
description <i>optional</i>	The comment or override authoriser Example : "TIMEOUT"	string

RegulatoryProgram

Structure to represent a regulatory program (e.g. APP)

Name	Description	Schema
countryCode <i>optional</i>	Code of the country the program applies to in the ISO 3166-1 alpha-3 format Example : "CAN"	string
name <i>optional</i>	Name of the regulatory program (AQQ, IAPP, APP, ADC) Example : "APP"	string

RegulatoryStatus

Structure to give the details of a given regulatory status along with the associated message from the authorities

Name	Description	Schema
message <i>optional</i>		RegulatoryComment
statusCode <i>optional</i>	Codes for regulatory statuses ARQ status X - APP not required R - APP Required APR status Y - Successful B - Bypassed R - Void X - Not needed N - Failed AQQ status O - OK to board I - Inhibited to board S - Selectee E - Data error N - AQQ not performed X - AQQ not required B - ESTA Bypassed TCS status CTB - Bypassed CTD - Disrupted CTF - Failed CTI - Ignored CTN - Not Required CTO - Overridden CTP - Passed CTR - Required CTU - Undefined CTX - Non-Prime EST status Z - ESTA not required A - Valid ESTA application on file B - ESTA application not present on file C - Additional US Travel Document required (ESTA denied) 1 - ESTA inhibited X - Insufficient Information Y - ESTA Bypassed (Internal Status) APS status Y - Complete N - NotComplete R - AgentRevalidation Q - NotRequired P - NotPerformed MSL status Y - Yes N - No APC status APC - ClearToBoard APX - Cancelled APN - NotFound APT - Timeout APE - ErrorCondition APD - Duplicate Name API - Insufficient Data APF - DoNotBoard TRS status T - DepartureTransit O - ArrivalTransit I - IntermediateTransit OVR status OVG - APP override indicator is Government OVA - APP override indicator is Airline APP status APM - APP query is Manual APA - APP query is Automatic Example : "CTP"	string
statusType <i>optional</i>	Nature of the regulatory status - possible values ARQ - APP processing requirement for the product APR - APP result indicator of the product AQQ - AQQ program status TCS - Customer type check state EST - ESTA program status APS - ApiDataStatus indicator MSL - Missing luggage indicator APC - APP status code [APP] TRS - TransitIndicator True [APP] NRM - TransitIndicator False [APP] OVR - APP override Indicator [APP] APP - APP query type [APP] IAP - APP Inhibition [APP] API - APIS data indicator [APP] VDB - Voluntary denied boarding Example : "TCS"	string

Relationship

Name	Description	Schema
id <i>optional</i>	Example : "ZAY091-2019-10-05-PT-1"	string
ref <i>optional</i>	Example : "processedPnr.travelers"	string
type <i>optional</i>	Example : "stakeholder"	string
version <i>optional</i>	Only populated for correlated resources defined in Dictionaries	string

Remark

Name	Description	Schema
category <i>optional</i>	Applicable to miscellaneous remarks only, the subCategory is a 1-alphaChar suffix to category, enabling to identify the applicability scope of the remark. For example, RMH is used to categorize all remarks related to hotels. Possible values: C H A F R X. Maximal length : 1 Example : "C"	string
content <i>optional</i>	Content of the remark element Example : "NOTIFY PASSENGER PRIOR TO TICKET PURCHASE & CHECK-IN: FEDERAL LAWS FORBID THE CARRIAGE OF HAZARDOUS MATERIALS - GGAMAUSHAZ"	string
id <i>optional</i>	item identifier Example : "ZAY091-2019-10-05-OT-36"	string
products <i>optional</i>	Example : [{ "type" : "product", "id" : "ZAY091-2019-10-05-ST-1", "ref" : "processedPnr.products" }]	< Relationship > array
subType <i>optional</i>	Possible values for remark category RM Miscellaneous remark RC Confidential remarks RQ Quality control remark RI Invoice remark RX Corporate Remarks Example : "RM"	string
travelers <i>optional</i>	Example : [{ "type" : "stakeholder", "id" : "ZAY091-2019-10-05-PT-1", "ref" : "processedPnr.travelers" }]	< Relationship > array
type <i>optional</i>	resource name Example : "remark"	enum (remark)

Seat

Seat information

Name	Description	Schema
characteristicCodes <i>optional</i>	List of seat characteristics codes (the code corresponds to the dictionary key associated to the corresponding textual value). Example: CH = Chargeable Seat, W = Window Seat, A = Aisle Seat, Q = Seat in a quiet zone, E = Exit Row Seat, ... Example : ["CH"]	< string > array
number <i>optional</i>	Seat number corresponding to the concatenation of the seat row and seat column Example : "05A"	string
traveler <i>optional</i>		Relationship

SeatingDelivery

Structure containing all the delivery seating information

Name	Description	Schema
seat <i>optional</i>	Seat number and characteristics of the seat delivered in DCS	Seat

SegmentDelivery

Product Delivery Information related to segments

Name	Description	Schema
activeIdentityDocument <i>optional</i>	passenger details recorded in the DCS at segment level	Stakeholder
associatedTickets <i>optional</i>	Example : [{ "documentNumber" : "172555555555", "documentType" : "ETICKET", "associationStatus" : "ASSOCIATED", "primaryDocumentNumber" : "172111111111", "coupons" : { "number" : 1 } }]	< AirTravelDocument > array
distributionId <i>optional</i>	Unique Product Identifier / Distribution ID Example : "2401CA5500030ID"	string
flightSegment <i>optional</i>		SegmentDelivery_FlightSegment
id <i>optional</i>	identifier of the segmentDelivery in the PNR Example : "ZAY091-2019-05-04-OT-65"	string
isGoShow <i>optional</i>	indicates if the dcs record was created at the airport because the passenger showed up with a flexible ticket but had not yet a reservation for the flight Example : false	boolean

Name	Description	Schema
isNoRec <i>optional</i>	indicates if the dcs record was created at the airport because no reservation was found in the system Example : false	boolean
legDeliveries <i>optional</i>	Information at leg level for each leg	< LegDelivery > array
transferFlag <i>optional</i>		enum (FROM_FLIGHT, TO_FLIGHT)
traveler <i>optional</i>	link to associated stakeholder	Relationship
type <i>optional</i>	resource name Example : "segment-delivery"	enum (segment-delivery)

SegmentDelivery_FlightSegment

Flight segment details

Name	Description	Schema
arrival <i>optional</i>		FlightEndPoint
departure <i>optional</i>		FlightEndPoint
isInformational <i>optional</i>	Indicates an informational flight segment i.e. already booked on another system.	boolean
marketing <i>optional</i>		MarketingFlight

Service

Service representation

Name	Description	Schema
code <i>optional</i>	This code is used to identify the service type Maximal length : 4 Example : "FQTV"	string
creation <i>optional</i>	Original booking datetime & office of the service - office information limited to office ID	EventLog
document <i>optional</i>	This field is used to structure SSR DOCS identification document or the SSR DOCO visa when possible	IdentityDocument

Name	Description	Schema
id <i>optional</i>	Service identifier. In case the Service structure is used for a SERVICE/SEATING product, this field is not applicable i.e. already specified in the product. Example : "ZAY091-2019-05-04-OT-5"	string
membership <i>optional</i>	Information on the loyalty profile referenced in Frequent Flyer PNR elements & corporate recognition PNR elements.	Membership
nip <i>optional</i>	Number in party Example : 1	integer
priceCategory <i>optional</i>	Price category	Service_PriceCategory
products <i>optional</i>	Service association with flight segments [AIR products]. In case the Service structure is used for a SERVICE/SEATING product resource, this field is not applicable i.e. already specified in the product. Example : [{ "type" : "product", "id" : "ZAY091-2019-10-05-ST-1", "ref" : "processedPnr.products" }]	< Relationship > array
seats <i>optional</i>	Used to structure information from seating SSR elements e.g. RQST, NSST	< Seat > array
serviceProvider <i>optional</i>		ServiceProvider
status <i>optional</i>	Status code. For example - HK = confirmed, HL = waitlist, UN = unable to confirm not operating, UC = unable to confirm, HX = have cancelled, NO = no action taken." Example : "HK"	string
subType <i>optional</i>	This field is used to indicate if we are dealing with an SVC/SSR/SK/OSI element Example : "SPECIAL_SERVICE_REQUEST"	enum (SPECIAL_SERVICE_REQUEST, MANUAL_AUXILIARY_SEGMENT, SPECIAL_KEYWORD, OTHER_SERVICE_INFORMATION)
text <i>optional</i>	Service full content Example : "6X1234567890 GOLD"	string
travelers <i>optional</i>	Service association with stakeholder resources. If the Service structure is used for a SERVICE/SEATING product resource, this field is not applicable i.e. already specified in the product. If the Service structure is used for a stakeholder's identity document, this field is not applicable. Example : [{ "type" : "stakeholder", "id" : "ZAY091-2019-10-05-PT-1", "ref" : "processedPnr.travelers" }]	< Relationship > array

Name	Description	Schema
type <i>optional</i>	Resource name. In case the Service structure is used for a SERVICE/SEATING product, this field is not applicable i.e. already specified in the product. Example : "service"	enum (service)

Service_PriceCategory

Name	Description	Schema
code <i>optional</i>	The reason for issuance code (RFIC) chargeability indicator defined for the sellable object Example : "A"	string
subCode <i>optional</i>	The reason for issuance sub code (RFISC) chargeability indicator defined for the sellable object Example : "A04"	string

ServiceProvider

Carrier details

Name	Description	Schema
code <i>optional</i>	IATA code of the carrier Example : "6X"	string

SpecialBagHandling

Structure to convey special bag handling instructions

Name	Description	Schema
freeText <i>optional</i>	Holds any details for the attribute Example : "CONFIDENTIAL CREW BAG"	string

Name	Description	Schema
label <i>optional</i>	special bag label Example : "CREW"	enum (GROUP, GROUND_TRANSPORT, FRAGILE, DUPLICATE_TAG, DIPLOMATIC_COURIER, DANGEROUS_GOODS, DELIVERED_AT_AIRCRAFT, CREW, COURIER, ROUTING_UPDATE, TOUR, UNACCOMPANIED, VIP, REROUTED, RUSH, SHORT_CONNECTION, JUMP, MISHANDLED, PRIORITY, RELOAD, HAJJ, HOTEL_VOUCHER, HEAVY, IRREGULAR_OPERATION, WEIGHT_REJECT)

Stakeholder

Definition of PNR travelers. Fields gender, nationality, placeOfBirth, countryOfResidence are only populated for passengerDelivery resources.

Name	Description	Schema
adult <i>optional</i>	It contains information regarding the adult carrying the infant. This entity will be displayed for a traveler ID representing an infant without seat	Relationship
age <i>optional</i>	Age of the stakeholder Example : 40	integer
contacts <i>optional</i>	Contacts associated with the traveler Example : [{ "type" : "contact", "id" : "ZAY091-2019-10-05-OT-6", "ref" : "processedPnr.contacts" }]	< Relationship > array
corporateRecognitions <i>optional</i>	Corporate recognition programs used by the traveler - CLID elements Example : [{ "type" : "service", "id" : "ZAY091-2019-10-05-OT-19", "ref" : "processedPnr.loyaltyRequests" }]	< Relationship > array

Name	Description	Schema
countryOfResidence <i>optional</i>	The stakeholder's country of residence Example : "Portugal"	string
dateOfBirth <i>optional</i>	The stakeholder's date of birth Example : "1978-10-05"	string (date)
gender <i>optional</i>	Gender of the stakeholder Example : "MALE"	enum (MALE, FEMALE, UNKNOWN)
id <i>optional</i>	item identifier Example : "ZAY091-2019-10-05-PT-1, For Infant ZAY091-2019-10-05-PT-1-INF"	string
identificationCode <i>optional</i>	ID or CR field, must start with ID or CR followed by alphanumeric characters e.g ID10152307, CR1234AA Example : "ID10152307"	string
identityDocuments <i>optional</i>	Advanced Passenger Information - regulatory identity documents - SSR DOCS & DOCO elements	< Service > array
infant <i>optional</i>	It contains information regarding the infant travelling with the adult. This entity will be displayed for a traveler ID representing an adult carrying an infant without seat	Relationship
loyaltyAccruals <i>optional</i>	Frequent Flyer profiles used for miles accrual - SSR FQTV elements Example : [{ "type" : "service", "id" : "ZAY091-2019-10-05-OT-15", "ref" : "processedPnr.loyaltyRequests" }]	< Relationship > array
loyaltyServicing <i>optional</i>	Frequent Flyer profiles used for servicing - SSR FQTS elements Example : [{ "type" : "service", "id" : "ZAY091-2019-10-05-OT-17", "ref" : "processedPnr.loyaltyRequests" }]	< Relationship > array
names <i>optional</i>	Names of the stakeholder. The concatenation of full name + PTC + staffType + dateOfBirth + specialSeat must remain below 59 characters.	< Name > array
nationality <i>optional</i>	Nationality of the Stakeholder	string
passenger <i>optional</i>		Stakeholder_Passenger
passengerTypeCode <i>optional</i>	3-characters code defining the passenger type - possible values: ADT, CHD, INS, INF, UNA Maximal length : 3 Example : "ADT"	string
placeOfBirth <i>optional</i>	The stakeholder's place of birth Example : "London"	string

Name	Description	Schema
staffType <i>optional</i>	The type of staff of the stakeholder e.g BKB or SBY Example : "BOOKABLE"	enum (BOOKABLE, STANDBY)
type <i>optional</i>	resource name Example : "stakeholder"	enum (stakeholder)

Stakeholder_Passenger

Defines attributes related to a Passenger

Name	Description	Schema
cbbg <i>optional</i>	In case the current traveler is associated with a cabin baggage [separate NM element in PNR], this field provides the reference to the corresponding Stakeholder.	Relationship
exst <i>optional</i>	In case the current traveler is associated with an extra seat [separate NM element in PNR], this field provides the reference to the corresponding Stakeholder.	Relationship
owner <i>optional</i>	In case the current traveler has specialSeat set to EXST or CBBG, this field provides the reference to the Stakeholder owning the extra seat or cabin baggage.	Relationship
passengerDeliveries <i>optional</i>	Map of passenger-delivery resources with id as key	< PassengerDelivery > array
specialSeat <i>optional</i>	CBBG (Cabin Baggage) or EXST (Extra Seat) Example : "CBBG"	enum (CBBG, EXST)
uniqueIdentifier <i>optional</i>	Unique Customer Identifier reported by PNR Example : "2501ADE0000001"	string

SubClass

Name	Description	Schema
code <i>optional</i>	inventory identification of the subclass	integer
pointOfSale <i>optional</i>	Used to convey office/systemCode & login/countryCode from where the subClass value determination originates	PointOfSale
yields <i>optional</i>		< ElementaryPrice > array

Tax

Structure to describe a Tax

Name	Description	Schema
amount <i>optional</i>	Defines the monetary value with decimal position. It can be in cash or miles. Example : "5000.50"	string
category <i>optional</i>	Used to specify if the tax is New, Old or Refundable. Example : "NEW"	enum (NEW, OLD, REFUNDABLE)
code <i>optional</i>	International Standards Organization (ISO) tax code which is a two-letter country code Example : "IZ"	string
currency <i>optional</i>	Defines a specific monetary unit using ISO4217 currency code Example : "CND"	string
description <i>optional</i>	text describing the tax Example : "Government tax"	string
exempted <i>optional</i>	Indicates if tax is exempted or not Example : false	boolean
included <i>optional</i>	Indicates if tax is included or not Example : true	boolean
nature <i>optional</i>	Nature of the tax in Fare Quote filing Example : "EB"	string
percentage <i>optional</i>	In the case of a tax on TST value, the percentage of the tax will be indicated in this field. Example : "5.00"	string
taxType <i>optional</i>	Defines the type of Taxes, PFC taxes, Airport Taxes, EquivalentTaxes for TCH. Example : "Airport Taxes"	string

TicketingReference

Describes a travel document referenced in the current reservation

Name	Description	Schema
creation <i>optional</i>	Insertion datetime & origin office ID for SSR ticketing references	EventLog
documents <i>optional</i>		< AirTravelDocument > array
id <i>optional</i>	Identifies the element in reservation which references the document Example : "ZAY091-2019-10-05-OT-20"	string
isInfant <i>optional</i>	Indicates that the referenced document applies to an infant traveler Example : false	boolean

Name	Description	Schema
products <i>optional</i>	Links to associated products Example : [{ "type" : "product", "id" : "ZAY091-2019-10-05-ST-1", "ref" : "processedPnr.products" }]	< Relationship > array
referenceStatusCode <i>optional</i>	Status code of SSR & SVC ticketing references - For example HK [confirmed]	string
referenceTypeCode <i>optional</i>	Categorizes the element in reservation which references the document Example : "FA"	enum (FA, FHE, FHD, FHP, FHA, FHM, FO, TKNE_SSR, TKNE_OSI, TKNA_SSR, TKNA_OSI, TKNM_SSR, TKNM_OSI, TKNO_OSI, ASVC_SSR, SVC)
text <i>optional</i>	Used to specify the full reference content in reservation Example : "172-1234567890/RCI-FDF161000001MB01/ETAF/EUR3000.00/05OCT19/NCE6X08AA/20494795"	string
traveler <i>optional</i>	Links to associated stakeholders	Relationship
type <i>optional</i>	Resource name Example : "ticketing-reference"	enum (ticketing-reference)

Tier

Description of a Tier in the context of the loyalty program - applicable to both Frequent Flyer profiles & Corporate profiles.

Name	Description	Schema
code <i>optional</i>	Tier level code Example : "HGOLD"	string
companyCode <i>optional</i>	Alliance code or airline code of the loyalty program Example : "6X"	string
customerValue <i>optional</i>	Ranging from 0 to 9999, it measures the value of the customer [frequent flyer/corporation] for the airline depending on its profile, its travel history, potential and other internal factors. Example : 5000	integer
name <i>optional</i>	Tier level description Example : "HONORARY GOLD"	string
priorityCode <i>optional</i>	Priority code used to synchronize with external systems Example : "1"	string

TimeLocationTrackingLog

Structure to represent a time and location for which a passenger was recorded

Name	Description	Schema
localDateTime <i>optional</i>	Example : "2018-10-18T12:48:12"	string
trackedLocation <i>optional</i>		InfrastructureLocation

TravelersGroup

Name	Description	Schema
name <i>optional</i>	Name of the group PNR Example : "GROUP/NAME/IN/SEVERAL/PARTS"	string
size <i>optional</i>	Number of name-assigned passengers that can be booked in the group PNR Example : 9	integer
sizeRemaining <i>optional</i>	Number of passengers that is still available for insertion in group PNR according to its size Example : 4	integer
sizeTaken <i>optional</i>	Number of passengers inserted in group PNR Example : 5	integer

Weight

Generic structure to convey a weight

Name	Description	Schema
unit <i>optional</i>	the unit of weight measurement Example : "KILOGRAMS"	enum (KILOGRAMS, POUNDS)
value <i>optional</i>	the weight value in the given unit Example : 10	integer