

Dynamic Intelligence Hub

Flight Date Open Api Specification

Table of Contents

Dynamic Intelligence Hub Data Model - Schedule Flight Date	1
Overview	2
Version information	2
Paths	3
Schedule Flight Date Correlation DataPush Feed	3
Schedule Flight Date DataPush Feed	7
Definitions	15
AircraftConfiguration	15
Arrival	15
CorrelatedDataScheduleDcsPassenger	16
CorrelatedDataScheduleDcsfm	16
CorrelatedDataScheduleInventory	17
CorrelatedDataSchedulePnr	17
CorrelatedDataScheduleTicket	18
CorrelatedScheduleDcsPassengerLegData	18
CorrelatedScheduleInventoryLegData	18
CorrelationReferences	19
CorrelationScheduleDcsPassenger	19
CorrelationScheduleDcsfm	20
CorrelationScheduleInventory	20
CorrelationSchedulePnr	20
CorrelationScheduleTicket	21
DatedFlight	21
Departure	26
Dictionaries	27
EventLog	27
Events	28
FlightDesignator	29
Included	29
LegDCSStatuses	29
Meta	30
PatchOperation	30
Relationship	31
ScheduleCorrelationsFeedData	31
ScheduleFlightCorrelationDataPush	32
ScheduleFlightData	32
ScheduleFlightDataPush	37
issueSource	38

Dynamic Intelligence Hub Data Model - Schedule Flight Date

Overview

This document describes DIH output for Schedule flight date Data Push Feed

Version information

Version : 2.1.0

Paths

Schedule Flight Date Correlation DataPush Feed

POST /schedule/processed-flights-correlation-feed

Description

SKD Flight Date correlations feed pushed by Amadeus DIH. Please note this is NOT a POST API - this section is only used to specify the data model pushed.

Responses

HTTP Code	Description	Schema
default	SKD Flight Date Correlations Data Push Feed	ScheduleFlightCorrelationDataPush

Tags

- FEED

Example HTTP response

Response default

```
{
  "meta" : {
    "triggerEventLog" : {
      "id" : "429074ef1bd011e3-e63dfe23f4a0adc",
      "triggerEventName" : "DATA_INIT"
    },
    "version" : "2.1.0"
  },
  "scheduleCorrelations" : {
    "CorrelationSchedulePnr" : {
      "scheduleId" : "6X-835-B-2018-09-17",
      "pnrIds" : [ "QFBCSR-2018-05-12", "KNGBAD-2018-06-16" ],
      "correlatedData" : [ {
        "QFBCSR-2018-05-12" : [ {
          "pnrAirSegmentId" : "QFBCSR-2018-05-12-ST-1",
          "scheduleSegmentId" : "2018-09-17-LHR-CDG",
          "schedulePartnershipId" : "7X-9623-2018-09-17"
        }, {
          "pnrAirSegmentId" : "QFBCSR-2018-05-12-ST-2",
          "scheduleSegmentId" : "2018-09-17-LHR-CDG",
```

```

    "schedulePartnershipId" : "7X-9623-2018-09-17"
  } ]
}, {
  "KNGBAD-2018-06-16" : [ {
    "pnrAirSegmentId" : "KNGBAD-2018-06-16-ST-5",
    "scheduleSegmentId" : "2018-09-17-CDG-NCE",
    "schedulePartnershipId" : "7X-9623-2018-09-17"
  } ]
} ]
},
"CorrelationScheduleTicket" : {
  "scheduleId" : "6X-835-B-2018-09-17",
  "ticketIds" : [ "1723214567845-2018-05-12", "1722541219542-2018-06-16" ],
  "correlatedData" : [ {
    "1723214567845-2018-05-12" : [ {
      "ticketCouponId" : "1723214567845-2018-05-12-1",
      "scheduleSegmentId" : "2018-09-17-LHR-CDG",
      "schedulePartnershipId" : "7X-9623-2018-09-17"
    } ]
  } ],
  {
    "1722541219542-2018-06-16" : [ {
      "ticketCouponId" : "1722541219542-2018-06-16-1",
      "scheduleSegmentId" : "2018-09-17-CDG-NCE"
    } ]
  } ]
},
"CorrelationScheduleDcsPassenger" : {
  "scheduleId" : "6X-835-B-2018-09-17",
  "dcsPassengerIds" : [ "2501ADE0000001" ],
  "correlatedData" : [ {
    "2501ADE0000001" : [ {
      "scheduleSegmentId" : "2018-09-17-LHR-CDG",
      "dcsPassengerSegmentDeliveryId" : "2401CA55000030ID",
      "schedulePartnershipId" : "7X-9623-2018-09-17",
      "correlatedLegs" : [ {
        "scheduleLegId" : "LHR-CDG",
        "dcsPassengerLegDeliveryId" : "2401DA55000037F3-LHR"
      } ]
    } ]
  } ]
},
"CorrelationScheduleInventory" : {
  "scheduleId" : "6X-835-2018-09-17",
  "inventoryFlightIds" : [ "6X-835-2018-09-17" ],
  "correlatedData" : [ {
    "6X-835-2018-09-17" : [ {
      "scheduleSegmentId" : "2018-09-17-LHR-CDG",
      "inventorySegmentId" : "2018-09-17-LHR-CDG",
      "schedulePartnershipIds" : [ "7X-434-2018-09-17", "8X-876-2018-09-17" ],
      "correlatedLegs" : [ {
        "scheduleLegId" : "LHR-CDG",

```

```

        "inventoryLegId" : "LHR-CDG"
    } ]
}, {
    "scheduleSegmentId" : "2018-09-17-LHR-NCE",
    "inventorySegmentId" : "2018-09-17-LHR-NCE",
    "schedulePartnershipIds" : [ "7X-434-2018-09-17", "8X-876-2018-09-17" ],
    "correlatedLegs" : [ {
        "scheduleLegId" : "LHR-CDG",
        "inventoryLegId" : "LHR-CDG"
    }, {
        "scheduleLegId" : "CDG-NCE",
        "inventoryLegId" : "CDG-NCE"
    } ]
}, {
    "scheduleSegmentId" : "2018-09-17-CDG-NCE",
    "inventorySegmentId" : "2018-09-17-CDG-NCE",
    "schedulePartnershipIds" : [ "7X-434-2018-09-17" ],
    "correlatedLegs" : [ {
        "scheduleLegId" : "CDG-NCE",
        "inventoryLegId" : "CDG-NCE"
    } ]
} ]
} ]
},
"CorrelationScheduleDcsfm" : {
    "scheduleId" : "6X-835-2018-09-17",
    "dcsfmIds" : [ "6X-835-2018-09-17-LHR", "6X-835-2018-09-17-CDG" ],
    "correlatedData" : [ {
        "6X-835-2018-09-17-LHR" : [ {
            "dcsfmLegId" : "LHR-CDG",
            "scheduleLegId" : "LHR-CDG",
            "scheduleSegmentIds" : [ "2018-06-12-LHR-NCE", "2018-06-12-LHR-CDG" ]
        } ]
    }, {
        "6X-835-2018-09-17-CDG" : [ {
            "dcsfmLegId" : "CDG-NCE",
            "scheduleLegId" : "CDG-NCE",
            "scheduleSegmentIds" : [ "2018-06-12-LHR-NCE", "2018-06-12-CDG-NCE" ]
        } ]
    } ]
} ]
},
"ictionaries" : {
    "schedules" : {
        "6X-835-2018-09-17" : {
            "type" : "dated-flight",
            "id" : "6X-835-2018-09-17",
            "version" : "1536835243123456"
        }
    }
},
"pnrs" : {
    "QFBCSR-2018-05-12" : {

```

```

    "type" : "pnr",
    "id" : "QFBCSR-2018-05-12",
    "version" : "2"
  },
  "KNGBAD-2018-06-16" : {
    "type" : "pnr",
    "id" : "KNGBAD-2018-06-16",
    "version" : "1"
  }
},
"tickets" : {
  "1723214567845-2018-05-12" : {
    "type" : "air-travel-document",
    "id" : "1723214567845-2018-05-12",
    "version" : "1"
  },
  "1722541219542-2018-06-16" : {
    "type" : "air-travel-document",
    "id" : "1722541219542-2018-06-16",
    "version" : "1"
  }
},
"dcsPassengers" : {
  "2501ADE0000001" : {
    "type" : "dcs-passenger",
    "id" : "2501ADE0000001",
    "version" : "1609937279"
  }
},
"inventories" : {
  "6X-835-2018-09-17" : {
    "type" : "dated-flight",
    "id" : "6X-835-2018-09-17",
    "version" : "1536835243"
  }
},
"dcsfmFlightLegs" : {
  "6X-835-2018-09-17-LHR" : {
    "type" : "dated-flight",
    "id" : "6X-835-2018-09-17-LHR",
    "version" : "1"
  },
  "6X-835-2018-09-17-CDG" : {
    "type" : "dated-flight",
    "id" : "6X-835-2018-09-17-CDG",
    "version" : "1"
  }
}
},
"events" : {

```



```

"recordDomain" : "SCHEDULE_PNR",
"recordId" : "6X-835-2018-09-17",
"events" : [ {
  "origin" : "COMPARISON",
  "eventType" : "UPDATED",
  "currentPath" : "/correlationSchedulePnr/correlatedData",
  "previousPath" : "/correlationSchedulePnr/correlatedData"
}, {
  "origin" : "COMPARISON",
  "eventType" : "CREATED",
  "currentPath" : "/correlationSchedulePnr/correlatedData/KNGBAD-2018-06-16"
} ]
}

```

Schedule Flight Date DataPush Feed

POST /schedule/processed-flights-feed

Description

SKD Flight Date feed pushed by Amadeus DIH. Please note this is NOT a POST API - this section is only used to specify the data model pushed.

Responses

HTTP Code	Description	Schema
default	SKD Flight Date Data Push Feed	ScheduleFlightDataPush

Tags

- FEED

Example HTTP response

Response default

```

{
  "meta" : {
    "triggerEventLog" : {
      "id" : "429074ef1bd011e3-e63dfe23f4a0adc",
      "triggerEventName" : "DATA_INIT"
    },
    "version" : "2.1.0"
  }
}

```

```

},
"previousRecord" : [ {
  "op" : "replace",
  "path" : "scheduleProcessedFlight/legs/0/aircraftEquipment/aircraftType",
  "value" : 320
}, {
  "op" : "replace",
  "path" : "/version",
  "value" : "1524839045128470"
} ],
"scheduleProcessedFlight" : {
  "type" : "dated-flight",
  "id" : "6X-835-2018-09-17",
  "version" : "1536835243123456",
  "flightDesignator" : {
    "carrierCode" : "6X",
    "flightNumber" : "835",
    "operationalSuffix" : "B"
  },
  "scheduledDepartureDate" : "2018-09-17",
  "dayOfOperation" : "MON",
  "isCancelled" : "false",
  "characteristics" : [ "INTERNATIONAL" ],
  "codeshare" : "OPERATING",
  "flightPoints" : [ {
    "id" : "LHR_1",
    "iataCode" : "LHR",
    "city" : "LON",
    "country" : "GB",
    "region" : "EUROP",
    "continent" : "ITC2",
    "departure" : {
      "timings" : [ {
        "qualifier" : "STD",
        "value" : "2018-09-17T12:40:00"
      } ],
      "terminals" : [ {
        "code" : "1"
      } ]
    }
  } ],
  "id" : "CDG_2",
  "iataCode" : "CDG",
  "city" : "PAR",
  "country" : "FR",
  "region" : "EUROP",
  "continent" : "ITC2",
  "departure" : {
    "timings" : [ {
      "qualifier" : "STD",
      "value" : "2018-09-17T17:00:00"
    } ]
  }
} ],

```

```

    } ]
  },
  "arrival" : {
    "timings" : [ {
      "qualifier" : "STA",
      "value" : "2018-09-17T14:45:00"
    } ]
  }
}, {
  "id" : "NCE_3",
  "iataCode" : "NCE",
  "city" : "NCE",
  "country" : "FR",
  "region" : "EUROP",
  "continent" : "ITC2",
  "arrival" : {
    "timings" : [ {
      "qualifier" : "STA",
      "value" : "2018-09-17T18:19:00"
    } ],
    "terminals" : [ {
      "code" : "1"
    } ]
  }
} ],
"segments" : [ {
  "id" : "2018-09-17-LHR-CDG",
  "boardFlightPointId" : "LHR_1",
  "offFlightPointId" : "CDG_2",
  "boardPointIataCode" : "LHR",
  "offPointIataCode" : "CDG",
  "scheduledDepartureDateTime" : "2018-09-17T12:40:00",
  "scheduledArrivalDateTime" : "2018-09-17T14:45:00",
  "numberOfLegs" : 1,
  "legIds" : [ "LHR-CDG" ],
  "trafficRestrictions" : [ "D", "A" ],
  "partnerships" : {
    "marketingFlights" : [ {
      "id" : "7X-9623-2018-09-17",
      "flightDesignator" : {
        "carrierCode" : "7X",
        "flightNumber" : "9623"
      }
    } ],
    {
      "id" : "8X-6828-2018-09-17",
      "flightDesignator" : {
        "carrierCode" : "8X",
        "flightNumber" : "6828"
      }
    }
  }, {
    "id" : "9X-4551-2018-09-17",

```

```

        "flightDesignator" : {
            "carrierCode" : "9X",
            "flightNumber" : "4551"
        }
    } ]
}
}, {
    "id" : "2018-09-17-LHR-NCE",
    "boardFlightPointId" : "LHR_1",
    "offFlightPointId" : "NCE_3",
    "boardPointIataCode" : "LHR",
    "offPointIataCode" : "NCE",
    "scheduledDepartureDateTime" : "2018-09-17T12:40:00",
    "scheduledArrivalDateTime" : "2018-09-17T18:19:00",
    "numberOfLegs" : 2,
    "legIds" : [ "LHR-CDG", "CDG-NCE" ],
    "partnerships" : {
        "marketingFlights" : [ {
            "id" : "7X-9623-2018-09-17",
            "flightDesignator" : {
                "carrierCode" : "7X",
                "flightNumber" : "9623"
            }
        }, {
            "id" : "8X-6828-2018-09-17",
            "flightDesignator" : {
                "carrierCode" : "8X",
                "flightNumber" : "6828"
            }
        }, {
            "id" : "8X-4642-2018-09-17",
            "flightDesignator" : {
                "carrierCode" : "8X",
                "flightNumber" : "4642"
            }
        }
    ]
}
}, {
    "id" : "2018-09-17-CDG-NCE",
    "boardFlightPointId" : "CDG_2",
    "offFlightPointId" : "NCE_3",
    "boardPointIataCode" : "CDG",
    "offPointIataCode" : "NCE",
    "scheduledDepartureDateTime" : "2018-09-17T17:00:00",
    "scheduledArrivalDateTime" : "2018-09-17T18:19:00",
    "numberOfLegs" : 1,
    "legIds" : [ "CDG-NCE" ],
    "partnerships" : {
        "marketingFlights" : [ {
            "id" : "7X-9623-2018-09-17",
            "flightDesignator" : {

```

```

        "carrierCode" : "7X",
        "flightNumber" : "9623"
    }, {
        "id" : "8X-6828-2018-09-17",
        "flightDesignator" : {
            "carrierCode" : "8X",
            "flightNumber" : "6828"
        }
    }, {
        "id" : "8X-4642-2018-09-17",
        "flightDesignator" : {
            "carrierCode" : "8X",
            "flightNumber" : "4642"
        }
    } ]
} ],
"legs" : [ {
    "id" : "LHR-CDG",
    "boardFlightPointId" : "LHR_1",
    "offFlightPointId" : "CDG_2",
    "boardPointIataCode" : "LHR",
    "offPointIataCode" : "CDG",
    "scheduledDepartureDateTime" : "2018-09-17T12:40:00",
    "scheduledArrivalDateTime" : "2018-09-17T14:45:00",
    "routingOrder" : 1,
    "aircraftEquipment" : {
        "aircraftType" : 320,
        "franchiseeFlight" : {
            "airlineCode" : "8X",
            "disclosure" : "EXPRESS AIRWAYS"
        }
    },
    "scheduledFittedConfiguration" : {
        "code" : "331",
        "configurationContents" : [ {
            "cabin" : "J",
            "capacity" : 27
        }, {
            "cabin" : "W",
            "capacity" : 21
        }, {
            "cabin" : "Y",
            "capacity" : 244
        } ]
    },
    "totalScheduledFittedCapacity" : 292,
    "operationalSaleableConfiguration" : {
        "code" : "001",
        "configurationContents" : [ {
            "cabin" : "J",

```

```

        "capacity" : 27
      }, {
        "cabin" : "0",
        "capacity" : 21
      }, {
        "cabin" : "Y",
        "capacity" : 244
      } ]
    },
    "scheduledSaleableConfiguration" : {
      "code" : "052",
      "configurationContents" : [ {
        "cabin" : "J",
        "capacity" : 27
      }, {
        "cabin" : "0",
        "capacity" : 21
      }, {
        "cabin" : "Y",
        "capacity" : 244
      } ]
    },
    "operationalFittedConfiguration" : {
      "code" : "009",
      "configurationContents" : [ {
        "cabin" : "J",
        "capacity" : 27
      }, {
        "cabin" : "0",
        "capacity" : 21
      }, {
        "cabin" : "Y",
        "capacity" : 244
      } ]
    }
  },
  "legDCSStatuses" : {
    "acceptanceStatus" : "OPEN",
    "generalStatus" : "OPEN",
    "loadControlStatus" : "OPEN",
    "boardingStatus" : "OPEN"
  }
}, {
  "id" : "CDG-NCE",
  "boardFlightPointId" : "CDG_2",
  "offFlightPointId" : "NCE_3",
  "boardPointIataCode" : "CDG",
  "offPointIataCode" : "NCE",
  "scheduledDepartureDateTime" : "2018-09-17T17:00:00",
  "scheduledArrivalDateTime" : "2018-09-17T18:19:00",
  "routingOrder" : 2,

```

```

"serviceType" : "X",
"aircraftEquipment" : {
  "aircraftType" : 320,
  "franchiseeFlight" : {
    "airlineCode" : "8X",
    "disclosure" : "EXPRESS AIRWAYS"
  },
"scheduledFittedConfiguration" : {
  "code" : "331",
  "configurationContents" : [ {
    "cabin" : "J",
    "capacity" : 27
  }, {
    "cabin" : "W",
    "capacity" : 21
  }, {
    "cabin" : "Y",
    "capacity" : 244
  } ]
},
"totalScheduledFittedCapacity" : 292,
"operationalSaleableConfiguration" : {
  "code" : "001",
  "configurationContents" : [ {
    "cabin" : "J",
    "capacity" : 27
  }, {
    "cabin" : "0",
    "capacity" : 21
  }, {
    "cabin" : "Y",
    "capacity" : 244
  } ]
},
"scheduledSaleableConfiguration" : {
  "code" : "052",
  "configurationContents" : [ {
    "cabin" : "J",
    "capacity" : 27
  }, {
    "cabin" : "0",
    "capacity" : 21
  }, {
    "cabin" : "Y",
    "capacity" : 244
  } ]
},
"operationalFittedConfiguration" : {
  "code" : "009",
  "configurationContents" : [ {
    "cabin" : "J",

```

```

        "capacity" : 27
      }, {
        "cabin" : "0",
        "capacity" : 21
      }, {
        "cabin" : "Y",
        "capacity" : 244
      } ]
    }
  },
  "legDCSStatuses" : {
    "acceptanceStatus" : "OPEN",
    "generalStatus" : "OPEN",
    "loadControlStatus" : "OPEN",
    "boardingStatus" : "OPEN"
  }
} ]
},
"events" : {
  "recordDomain" : "SCHEDULE",
  "recordId" : "6X-835-2018-09-17",
  "events" : [ {
    "origin" : "COMPARISON",
    "eventType" : "UPDATED",
    "currentPath" : "/flightPoints/0/departure/timings",
    "previousPath" : "/flightPoints/0/departure/timings"
  } ]
}
}

```


Definitions

AircraftConfiguration

Name	Description	Schema
code <i>optional</i>	Code associated to the configuration. Example : "331"	string
configurationContents <i>optional</i>	Description of the configuration (cabin codes/ capacities)	< configurationContents > array

configurationContents

Name	Description	Schema
cabin <i>optional</i>	Cabin code. Example : "J"	string
capacity <i>optional</i>	Cabin capacity. Example : 27	integer

Arrival

Arrival details

Name	Description	Schema
terminals <i>optional</i>	It is an array to accommodate terminal information from more than 1 source(Ex, if the first terminal information was from schedule source and later DCS system sends a terminal info, both the information will be stored here. However currently there is no source information in this section so you will always receive only the terminal code from schedule source only).	< terminals > array
timings <i>optional</i>		< timings > array

terminals

Name	Description	Schema
code <i>optional</i>	Terminal code. Example : "1"	string

timings

Name	Description	Schema
qualifier <i>optional</i>	Type of timing information. Example : "STA"	enum (STD, STA, ETD_TAKEOFF, ETD_FLIX_FD, ETA_TOUCHDOWN, ETA_ON_BLOCK, ATD_OFF_BLOCK, ATD_TAKEOFF, ATA_TOUCHDOWN, ATA_ON_BLOCK, STANDARD_TIME_OF_DEPARTURE_ZULU, STANDARD_TIME_OF_ARRIVAL_ZULU)
value <i>optional</i>	Value of the timing attached to the related type in ISO format yyyy-mm-ddThh:mm:ss Example : "2018-09-17T14:45:00"	string (datetime)

CorrelatedDataScheduleDcsPassenger

Set of data field identifiers defining the correlation between a dated flight and a CM Pax record

Name	Description	Schema
correlatedLegs <i>optional</i>		< CorrelatedScheduleDcsPassengerLegData > array
dcsPassengerSegmentDeliveryId <i>optional</i>	The Id of the segment delivery of Dcs Passenger that is involved in correlation. Example : "2401CA55000030ID"	string
schedulePartnershipId <i>optional</i>	If the carrier is a codeshare and the booking is linked to one of the codeshare partner, it is Id of that partner flight. Example : "7X-9623-2018-09-17"	string
scheduleSegmentId <i>optional</i>	The Id of the flight segment that is involved in correlation. Example : "2018-09-17-LHR-CDG"	string

CorrelatedDataScheduleDcsfm

Set of data field identifiers defining the correlation between a schedule dated flight and DCS flight management records

Name	Description	Schema
dcsfmLegId <i>optional</i>	The Id of the DCS FM leg that is involved in correlation. Example : "LHR-CDG"	string
scheduleLegId <i>optional</i>	The Id of the schedule flight leg that is invloved in correlation. Example : "LHR-CDG"	string
scheduleSegmentIds <i>optional</i>	Segment Id(s) of the schedule which is correlated with the DCS FM record.	< string > array

CorrelatedDataScheduleInventory

Set of data field identifiers defining the correlation between a schedule dated flight and a inventory dated flight record

Name	Description	Schema
correlatedLegs <i>optional</i>		< CorrelatedScheduleInventoryLegData > array
inventorySegmentId <i>optional</i>	The Id of the inventory flight segment that is involved in correlation. Example : "2018-09-17-LHR-CDG"	string
schedulePartnershipIds <i>optional</i>	Flight Id(s) of the partnership carrier(s).	< string > array
scheduleSegmentId <i>optional</i>	The Id of the schedule flight segment that is invloved in correlation. Example : "2018-09-17-LHR-CDG"	string

CorrelatedDataSchedulePnr

Set of data field identifiers defining the correlation between a flight schedule and a PNR

Name	Description	Schema
pnrAirSegmentId <i>optional</i>	The Id of the PNR air segment that is involved in correlation. Example : "QFBCSR-2018-05-12-ST-1"	string
schedulePartnershipId <i>optional</i>	If the carrier is a codeshare and the booking is linked to one of the codeshare parther, it is Id of that partner flight. Example : "7X-9623-2018-09-17"	string

Name	Description	Schema
scheduleSegmentId <i>optional</i>	The Id of the flight segment that is involved in correlation. Example : "2018-09-17-LHR-CDG"	string

CorrelatedDataScheduleTicket

Set of data field identifiers defining the correlation between skd and tkt

Name	Description	Schema
schedulePartnershipId <i>optional</i>	If the carrier is a codeshare and the booking is linked to one of the codeshare partner, it is Id of that partner flight. Example : "7X-9623-2018-09-17"	string
scheduleSegmentId <i>optional</i>	The Id of the flight segment that is involved in correlation. Example : "2018-09-17-LHR-CDG"	string
ticketCouponId <i>optional</i>	The Id of the coupon that is involved in correlation. Example : "1723214567845-2018-05-12-1"	string

CorrelatedScheduleDcsPassengerLegData

Name	Description	Schema
dcsPassengerLegDeliveryId <i>optional</i>	Id of the leg delivery of Dcs Passenger involved in correlation. Example : "2401DA55000037F3-LHR"	string
scheduleLegId <i>optional</i>	Id of the flight leg which is involved in correlation. Example : "LHR-CDG"	string

CorrelatedScheduleInventoryLegData

Name	Description	Schema
inventoryLegId <i>optional</i>	Id of the inventory flight leg involved in correlation. Example : "LHR-CDG"	string
scheduleLegId <i>optional</i>	Id of the schedule flight leg which is involved in correlation. Example : "LHR-CDG"	string

CorrelationReferences

Name	Description	Schema
correlations <i>optional</i>	Correlation structures are defined in the included section. This section provides links for all the correlation structures pertaining to the current schedule flight record. Example : { "schedulePnr" : { "ref" : "included/correlationSchedulePnr/6X-834-2018-09-17" }, "scheduleTicket" : { "ref" : "included/correlationScheduleTicket/6X-834-2018-09-17" }, "scheduleDcsPassenger" : { "ref" : "included/correlationScheduleDcsPassenger/6X-834-2018-09-17" }, "scheduleInventory" : { "ref" : "included/correlationScheduleInventory/6X-834-2018-09-17" }, "scheduleDcsfm" : { "ref" : "included/correlationScheduleDcsfm/6X-834-2018-09-17" } }	correlations

correlations

Name	Schema
scheduleDcsPassenger <i>optional</i>	Relationship
scheduleDcsfm <i>optional</i>	Relationship
scheduleInventory <i>optional</i>	Relationship
schedulePnr <i>optional</i>	Relationship
scheduleTicket <i>optional</i>	Relationship

CorrelationScheduleDcsPassenger

Structure of correlation between a schedule and a CM record

Name	Description	Schema
correlatedData <i>optional</i>	The sub-entity details which used for correlating the main records	< string, < CorrelatedDataScheduleDcsPassenger > array > map
dcsPassengerIds <i>optional</i>	Ids of the DcsPassenger records correlated with the current schedule flight. Example : "2501ADE0000001"	< string > array

Name	Description	Schema
scheduleId <i>optional</i>	Id of the flight record which is correlating with DcsPassenger. Example : "6X-835-2018-09-17"	string

CorrelationScheduleDcsfm

Structure of correlation between a schedule and DCS Flight management record(s)

Name	Description	Schema
correlatedData <i>optional</i>	The sub-entity details which used for correlating the main records	< string, < CorrelatedDataScheduleDcsfm > array > map
dcsfmIDs <i>optional</i>	Id(s) of the DCS FM flight leg records which are correlating with schedule flight. Example : ["6X-835-2018-09-17-LHR", "6X-835-2018-09-17-CDG"]	< string > array
scheduleId <i>optional</i>	Id of the flight record which is correlating with DcsFM. Example : "6X-835-2018-09-17"	string

CorrelationScheduleInventory

Structure of correlation between a schedule and an inventory record

Name	Description	Schema
correlatedData <i>optional</i>	The sub-entity details which used for correlating the main records	< string, < CorrelatedDataScheduleInventory > array > map
inventoryFlightIds <i>optional</i>	Ids of the inventory flight records correlated with the current schedule flight. Example : "6X-835-2018-09-17"	< string > array
scheduleId <i>optional</i>	Id of the flight record which is correlating with DcsPassenger. Example : "6X-835-2018-09-17"	string

CorrelationSchedulePnr

Structure of correlation between a flight and a Passenger Name Record.

Name	Description	Schema
correlatedData <i>optional</i>	The sub-entity details which used for correlating the main records	< string, < CorrelatedDataSchedulePnr > array > map
pnrIds <i>optional</i>	Identifying the PNR(s) correlated with the current schedule flight - item format is record locator + creation date. Example : "[QFBCSR-2018-05-12,KNGBAD-2018-06-16]"	< string > array
scheduleId <i>optional</i>	Id of the flight record which is correlating with PNRs. Example : "6X-835-2018-09-17"	string

CorrelationScheduleTicket

Structure of correlation between a schedule and a ticket Record.

Name	Description	Schema
correlatedData <i>optional</i>	The sub-entity details which used for correlating the main records	< string, < CorrelatedDataScheduleTicket > array > map
scheduleId <i>optional</i>	Id of the flight record which is correlating with tickets. Example : "6X-835-2018-09-17"	string
ticketIds <i>optional</i>	Ids of the tkts correlated with the current schedule flight, where ticket Id is ticket number + issuance date. Example : "[1723214567845-2018-05-12,1722541219542-2018-06-16]"	< string > array

DatedFlight

Name	Description	Schema
characteristics <i>optional</i>		< enum (PSEUDO, HIDDEN, INTERNATIONAL, DOMESTIC, ADHOC) > array
codeshare <i>optional</i>	Type of codeshare defined on the flight. Example : "OPERATING"	enum (PRIME, MARKETING, OPERATING)
dayOfOperation <i>optional</i>	Day of operation (in LT) of the date. Example : "MON"	enum (MON, TUE, WED, THU, FRI, SAT, SUN)
flightDesignator <i>optional</i>		FlightDesignator

Name	Description	Schema
flightPoints <i>optional</i>		< flightPoints > array
id <i>optional</i>	ID of the flight. Example : "6X-123-2018-12-12"	string
isCancelled <i>optional</i>	Depicts if a flight is cancelled(true) or active(false). Example : false	boolean
legs <i>optional</i>		< legs > array
scheduledDepartureDate <i>optional</i>	The departure date of the flight date (in Local Time) in ISO format yyyy-mm-dd. Example : "2018-09-17"	string (date)
segments <i>optional</i>		< segments > array
type <i>optional</i>	Refers to dated flight. Example : "dated-flight"	string
version <i>optional</i>	Version of the flight message. Timestamp of the message is used as version. Example : "1536835243123456"	string

flightPoints

Name	Description	Schema
arrival <i>optional</i>		Arrival
city <i>optional</i>	city code of the flight point. Example : "LON"	string
continent <i>optional</i>	Continent code of the flight point. Example : "ITC2"	string
country <i>optional</i>	Country code of the flight point. Example : "GB"	string
departure <i>optional</i>		Departure
iataCode <i>optional</i>	IATA code of the airport. Example : "LHR"	string
id <i>optional</i>	Identifier of the flight point. Example : "LHR_1"	string
region <i>optional</i>	Region code of the flight point. Example : "EUROP"	string

legs

Name	Description	Schema
aircraftEquipment <i>optional</i>	Information on the aircraft equipment.	aircraftEquipment
boardFlightPointId <i>optional</i>	ID of the FlightPoint that represents the departure point of the leg. Example : "LHR_1"	string
boardPointIataCode <i>optional</i>	IATA code of the board point of the leg. Example : "LHR"	string
id <i>optional</i>	Identifier of the leg, which comprises of boardPoint + offPoint. Example : "LHR-CDG"	string
legDCSStatuses <i>optional</i>		LegDCSStatuses
offFlightPointId <i>optional</i>	ID of the FlightPoint that represents the arrival point of the leg. Example : "CDG_2"	string
offPointIataCode <i>optional</i>	IATA code of the off point of the leg. Example : "CDG"	string
routingOrder <i>optional</i>	Absolute position of the leg in the whole flight. Example : 1	integer
scheduledArrivalDateTime <i>optional</i>	'Scheduled arrival date and time of the segment(in LT), ISO format yyyy-mm-ddThh:mm:ss'. Example : "2018-09-17T14:45:00"	string (datetime)
scheduledDepartureDateTime <i>optional</i>	'Scheduled departure date and time of the segment(in LT), ISO format yyyy-mm-ddThh:mm:ss'. Example : "2018-09-17T12:40:00"	string (datetime)
serviceType <i>optional</i>	Service type defined for this leg	enum (UNKNOWN_SERVICE_TYPE, J, S, U, F, V, M, Q, G, B, A, R, C, O, H, L, P, T, K, D, E, W, X, I, N, Y, Z)

aircraftEquipment

Name	Description	Schema
aircraftType <i>optional</i>	Type of the aircraft equipment(Airbus 320). Example : "320"	string

Name	Description	Schema
franchiseeFlight <i>optional</i>	Franchisee flight details	franchiseeFlight
operationalFittedConfiguration <i>optional</i>		AircraftConfiguration
operationalSaleableConfiguration <i>optional</i>		AircraftConfiguration
scheduledFittedConfiguration <i>optional</i>		AircraftConfiguration
scheduledSaleableConfiguration <i>optional</i>		AircraftConfiguration
totalScheduledFittedCapacity <i>optional</i>	The total capacity of scheduledFittedConfiguration. Example : 292	integer

franchiseeFlight

Name	Description	Schema
airlineCode <i>optional</i>	Airline code of the franchisee flight. Example : "8X"	string
disclosure <i>optional</i>	Disclosure provided for the franchisee flight. Example : "EXPRESS AIRWAYS"	string

segments

Name	Description	Schema
boardFlightPointId <i>optional</i>	ID of the FlightPoint that represents the departure point of the segment. Example : "LHR_1"	string
boardPointIataCode <i>optional</i>	IATA code of the board point of the segment. Example : "LHR"	string

Name	Description	Schema
id <i>optional</i>	ID of the segment, which comprises of segment departure date + boardPoint + offPoint. Example : "2018-09-17-LHR-CDG"	string
legIds <i>optional</i>	List of the ids of the legs which are contained in this segment. Example : "LHR-CDG"	< string > array
numberOfLegs <i>optional</i>	Number of legs contained in this segment. Example : 1	integer
offFlightPointId <i>optional</i>	ID of the FlightPoint that represents the arrival point of the segment. Example : "CDG_2"	string
offPointIataCode <i>optional</i>	IATA code of the off point of the segment. Example : "CDG"	string
partnerships <i>optional</i>	Provides the information of the partnership flight of the main flight. If the main flight is operating, then marketing flight(s) information is populated. Else if the main flight is marketing, then the operating flight information is populated.	partnerships
scheduledArrivalDateTime <i>optional</i>	'Scheduled arrival date and time of the segment(in LT), ISO format yyyy-mm-ddThh:mm:ss'. Example : "2018-09-17T14:45:00"	string (datetime)
scheduledDepartureDateTime <i>optional</i>	'Scheduled departure date and time of the segment(in LT), ISO format yyyy-mm-ddThh:mm:ss'. Example : "2018-09-17T12:40:00"	string (datetime)
trafficRestrictions <i>optional</i>	List of traffic restriction codes set on this segment. Example : "[D,A]"	< string > array

partnerships

Name	Description	Schema
marketingFlights <i>optional</i>		< marketingFlights > array
operatingFlight <i>optional</i>	This property is populated only when the main flight is a marketing flight.	operatingFlight

marketingFlights

Name	Description	Schema
flightDesignator <i>optional</i>		FlightDesignator
id <i>optional</i>	Marketing flight ID. Example : "8X-9623-2018-09-17"	string

operatingFlight

Name	Description	Schema
flightDesignator <i>optional</i>		FlightDesignator
id <i>optional</i>	Operating flight ID. Example : "7X-346-2018-09-17"	string

Departure

Departure details

Name	Description	Schema
terminals <i>optional</i>	It is an array to accommodate terminal information from more than 1 source(Ex, if the first terminal information was from schedule source and later DCS system sends a terminal info, both the information will be stored here. However currently there is no source information in this section so you will always receive only the terminal code from schedule source only.)	< terminals > array
timings <i>optional</i>		< timings > array

terminals

Name	Description	Schema
code <i>optional</i>	Terminal code. Example : "1"	string

timings

Name	Description	Schema
qualifier <i>optional</i>	Type of timing information. Example : "STD"	enum (STD, STA, ETD_OFF_BLOCK, ETD_TAKEOFF, ETA_TOUCHDOWN, ETA_ON_BLOCK, ATD_OFF_BLOCK, ATD_TAKEOFF, ATA_TOUCHDOWN, ATA_ON_BLOCK, STANDARD_TIME_OF_DEPARTURE_ZULU, STANDARD_TIME_OF_ARRIVAL_ZULU)
value <i>optional</i>	Value of the timing attached to the related type in ISO format yyyy-mm-ddThh:mm:ss Example : "2018-09-17T12:40:00"	string (datetime)

Dictionaries

Name	Description	Schema
dcsPassengers <i>optional</i>	Set of key/value pairs with dcsPassengerId as key	< string, Relationship > map
dcsfmFlightLegs <i>optional</i>	Set of key/value pairs with dcsfmId as key	< string, Relationship > map
inventories <i>optional</i>	Set of key/value pairs with inventoryId as key	< string, Relationship > map
pnrs <i>optional</i>	Set of key/value pairs with pnrId as key	< string, Relationship > map
schedules <i>optional</i>	Set of key/value pairs with scheduleId as key	< string, Relationship > map
tickets <i>optional</i>	Set of key/value pairs with ticketId as key	< string, Relationship > map

EventLog

Information related to the initial event that trigger the process.

Name	Description	Schema
id <i>optional</i>	Unique identifier of a JSON message. Example : "429074ef1bd011e3-e63dfe23f4a0adc"	string

Name	Description	Schema
triggerEventName <i>optional</i>	Trigger of the message - set to 'DATA_INIT' for initialization messages. Example : "DATA_INIT"	string

Events

Structure of Dynamic Intelligence Hub functional events

Name	Description	Schema
events <i>optional</i>	List of events that have been detected on the FlightDate document	< events > array
originFeedTimeStamp <i>optional</i>	Incoming PSS feed time stamp	string (date-time)
recordDomain <i>optional</i>	Functional domain of the record Example : "SCHEDULE"	string
recordId <i>optional</i>	Record identifier e.g. FlightId Example : "6X-123-A-2018-12-12"	string

events

Name	Description	Schema
currentPath <i>optional</i>	String containing the JSON Pointer (see IETF RFC6901) that points to the data referenced by the Event in the latest version of the entity. It is only applicable for CREATED and UPDATED events. Example : "/correlationScheduleTicket/correlatedData/1722345676472-2018-09-20"	string
eventType <i>optional</i>	In case of comparison events, type of operation notified by the Example : "CREATED"	enum (CREATED, UPDATED, DELETED)
origin <i>optional</i>	Type of event e.g. COMPARISON / TIME_INITIATED_EVENT Example : "COMPARISON"	string
previousPath <i>optional</i>	String containing the JSON Pointer (see IETF RFC6901) that points to the data referenced by the Event in the previous version of the entity. It is only applicable for DELETED and UPDATED events. Example : "/correlationScheduleTicket/correlatedData/1722345676472-2018-09-20"	string

FlightDesignator

Provides information of flight number, carrier code and operational suffix.

Name	Description	Schema
carrierCode <i>optional</i>	Two letter IATA standard carrier code Example : "6X"	string
flightNumber <i>optional</i>	1-4 digit number Example : "835"	string
operationalSuffix <i>optional</i>	The operational suffix Example : "B"	string

Included

Name	Description	Schema
correlationScheduleDcsPassenger <i>optional</i>	Map of CorrelationScheduleDcsPassenger with Schedule Id as key	< string, CorrelationScheduleDcsPassenger > map
correlationScheduleDcsfm <i>optional</i>	Map of CorrelationScheduleDcsfm with Schedule Id as key	< string, CorrelationScheduleDcsfm > map
correlationScheduleInventory <i>optional</i>	Map of CorrelationScheduleInventory with Schedule Id as key	< string, CorrelationScheduleInventory > map
correlationSchedulePnr <i>optional</i>	Map of CorrelationSchedulePnr with Schedule Id as key	< string, CorrelationSchedulePnr > map
correlationScheduleTicket <i>optional</i>	Map of CorrelationScheduleTicket with Schedule Id as key	< string, CorrelationScheduleTicket > map

LegDCSStatuses

Name	Description	Schema
acceptanceStatus <i>optional</i>	Acceptance status of the flight * NOT_OPEN - Acceptance is not open * OPEN Acceptance is open * SUSPENDED - Acceptance is suspended * CLOSED - Acceptance is closed * FINALISED - Acceptance is finalised.	enum (NOT_OPEN, OPEN, GATED, SUSPENDED, CLOSED, FINALISED)

Name	Description	Schema
boardingStatus <i>optional</i>	Boarding status of the flight * OPEN - Boarding is open * NOT_OPEN - Boarding is not open * CLOSED - Boarding is closed * SUSPENDED - Boarding is suspended.	enum (OPEN, NOT_OPEN, CLOSED, SUSPENDED)
generalStatus <i>optional</i>	General status of the flight * DEPARTED - Flight is departed * PLAN_INITIALISED - Flight is initialised * LOCKED - Flight is locked * NOT_OPEN - Flight is not open * OPEN - Flight is open * SUSPENDED - Flight is suspended * CANCELLED - Flight is cancelled.	enum (DEPARTED, PLAN_INITIALISED, LOCKED, NOT_OPEN, OPEN, SUSPENDED, CANCELLED)
loadControlStatus <i>optional</i>	Local control status of the flight * CONTROL_IGNORED - Load control is ignored * OPEN - Load control is open * NOT_OPEN - Load control is not open * CLOSED - Load control is closed * SHEET_FINALISED - Load control is sheet finalised * CONTROL_FINALISED - Load control is finalised * CONTROL_SUSPENDED - Load control is suspended * CANCELLED - Load control is cancelled.	enum (CONTROL_IGNORED, OPEN, NOT_OPEN, CLOSED, SHEET_FINALISED, CONTROL_FINALISED, CONTROL_SUSPENDED, CANCELLED)

Meta

Technical information related to the feed.

Name	Description	Schema
triggerEventLog <i>optional</i>		EventLog
version <i>optional</i>	Version of the JSON feed produced. Example : "2.1.0"	string

PatchOperation

A single JSON Patch operation as defined by RFC 6902 (see <https://tools.ietf.org/html/rfc6902>)

Name	Description	Schema
from <i>optional</i>	A JSON Pointer as defined by RFC 6901 (see https://tools.ietf.org/html/rfc6901) Example : "scheduleProcessedFlight/legs/1"	string
op <i>required</i>	The operation to be performed Example : "add"	enum (add, remove, replace, move, copy, test)

Name	Description	Schema
path <i>required</i>	A JSON Pointer as defined by RFC 6901 (see https://tools.ietf.org/html/rfc6901) Example : "scheduleProcessedFlight/legs/0/aircraftEquipment/aircraft_type"	string
value <i>optional</i>	The value to be used within the operations Example : "320"	object

Relationship

Details of a relationship

Name	Description	Schema
id <i>optional</i>	Id of the related resource Example : "6X-234-2019-12-12"	string
ref <i>optional</i>	The reference to the related resource if this latter exists in the same document Example : "included/correlationScheduleTicket/6X-123-A-2018-12-12"	string
type <i>optional</i>	Type of the related resource Example : "dated-flight"	string
version <i>optional</i>	Version of the document. Example : "1536835243123456"	string

ScheduleCorrelationsFeedData

Name	Schema
correlationScheduleDcsPassenger <i>optional</i>	CorrelationScheduleDcsPassenger
correlationScheduleDcsfm <i>optional</i>	CorrelationScheduleDcsfm
correlationScheduleInventory <i>optional</i>	CorrelationScheduleInventory
correlationSchedulePnr <i>optional</i>	CorrelationSchedulePnr
correlationScheduleTicket <i>optional</i>	CorrelationScheduleTicket
dictionaries <i>optional</i>	Dictionaries

ScheduleFlightCorrelationDataPush

Name	Schema
events <i>optional</i>	Events
meta <i>optional</i>	Meta
scheduleCorrelations <i>optional</i>	ScheduleCorrelationsFeedData

ScheduleFlightData

Polymorphism : Composition

Name	Description	Schema
characteristics <i>optional</i>		< enum (PSEUDO, HIDDEN, INTERNATIONAL, DOMESTIC, ADHOC) > array
codeshare <i>optional</i>	Type of codeshare defined on the flight. Example : "OPERATING"	enum (PRIME, MARKETING, OPERATING)
correlations <i>optional</i>	Correlation structures are defined in the included section. This section provides links for all the correlation structures pertaining to the current schedule flight record. Example : { "schedulePnr" : { "ref" : "included/correlationSchedulePnr/6X-834-2018-09-17" }, "scheduleTicket" : { "ref" : "included/correlationScheduleTicket/6X-834-2018-09-17" }, "scheduleDcsPassenger" : { "ref" : "included/correlationScheduleDcsPassenger/6X-834-2018-09-17" }, "scheduleInventory" : { "ref" : "included/correlationScheduleInventory/6X-834-2018-09-17" }, "scheduleDcsfm" : { "ref" : "included/correlationScheduleDcsfm/6X-834-2018-09-17" } }	correlations
dayOfOperation <i>optional</i>	Day of operation (in LT) of the date. Example : "MON"	enum (MON, TUE, WED, THU, FRI, SAT, SUN)
flightDesignator <i>optional</i>		FlightDesignator
flightPoints <i>optional</i>		< flightPoints > array

Name	Description	Schema
id <i>optional</i>	ID of the flight. Example : "6X-123-2018-12-12"	string
isCancelled <i>optional</i>	Depicts if a flight is cancelled(true) or active(false). Example : false	boolean
legs <i>optional</i>		< legs > array
scheduledDepartureDate <i>optional</i>	The departure date of the flight date (in Local Time) in ISO format yyyy-mm-dd. Example : "2018-09-17"	string (date)
segments <i>optional</i>		< segments > array
type <i>optional</i>	Refers to dated flight. Example : "dated-flight"	string
version <i>optional</i>	Version of the flight message. Timestamp of the message is used as version. Example : "1536835243123456"	string

correlations

Name	Schema
scheduleDcsPassenger <i>optional</i>	Relationship
scheduleDcsfm <i>optional</i>	Relationship
scheduleInventory <i>optional</i>	Relationship
schedulePnr <i>optional</i>	Relationship
scheduleTicket <i>optional</i>	Relationship

flightPoints

Name	Description	Schema
arrival <i>optional</i>		Arrival
city <i>optional</i>	city code of the flight point. Example : "LON"	string
continent <i>optional</i>	Continent code of the flight point. Example : "ITC2"	string

Name	Description	Schema
country <i>optional</i>	Country code of the flight point. Example : "GB"	string
departure <i>optional</i>		Departure
iataCode <i>optional</i>	IATA code of the airport. Example : "LHR"	string
id <i>optional</i>	Identifier of the flight point. Example : "LHR_1"	string
region <i>optional</i>	Region code of the flight point. Example : "EUROP"	string

legs

Name	Description	Schema
aircraftEquipment <i>optional</i>	Information on the aircraft equipment.	aircraftEquipment
boardFlightPointId <i>optional</i>	ID of the FlightPoint that represents the departure point of the leg. Example : "LHR_1"	string
boardPointIataCode <i>optional</i>	IATA code of the board point of the leg. Example : "LHR"	string
id <i>optional</i>	Identifier of the leg, which comprises of boardPoint + offPoint. Example : "LHR-CDG"	string
legDCSStatuses <i>optional</i>		LegDCSStatuses
offFlightPointId <i>optional</i>	ID of the FlightPoint that represents the arrival point of the leg. Example : "CDG_2"	string
offPointIataCode <i>optional</i>	IATA code of the off point of the leg. Example : "CDG"	string
routingOrder <i>optional</i>	Absolute position of the leg in the whole flight. Example : 1	integer
scheduledArrivalDateTime <i>optional</i>	'Scheduled arrival date and time of the segment(in LT), ISO format yyyy-mm-ddThh:mm:ss'. Example : "2018-09-17T14:45:00"	string (datetime)

Name	Description	Schema
scheduledDepartureDateTime <i>optional</i>	'Scheduled departure date and time of the segment(in LT), ISO format yyyy-mm-ddThh:mm:ss'. Example : "2018-09-17T12:40:00"	string (datetime)
serviceType <i>optional</i>	Service type defined for this leg	enum (UNKNOWN_SERVICE_TYPE, J, S, U, F, V, M, Q, G, B, A, R, C, O, H, L, P, T, K, D, E, W, X, I, N, Y, Z)

aircraftEquipment

Name	Description	Schema
aircraftType <i>optional</i>	Type of the aircraft equipment(Airbus 320). Example : "320"	string
franchiseeFlight <i>optional</i>	Franchisee flight details	franchiseeFlight
operationalFittedConfiguration <i>optional</i>		AircraftConfiguration
operationalSaleableConfiguration <i>optional</i>		AircraftConfiguration
scheduledFittedConfiguration <i>optional</i>		AircraftConfiguration
scheduledSaleableConfiguration <i>optional</i>		AircraftConfiguration
totalScheduledFittedCapacity <i>optional</i>	The total capacity of scheduledFittedConfiguration. Example : 292	integer

franchiseeFlight

Name	Description	Schema
airlineCode <i>optional</i>	Airline code of the franchisee flight. Example : "8X"	string
disclosure <i>optional</i>	Disclosure provided for the franchisee flight. Example : "EXPRESS AIRWAYS"	string

segments

Name	Description	Schema
boardFlightPointId <i>optional</i>	ID of the FlightPoint that represents the departure point of the segment. Example : "LHR_1"	string
boardPointIataCode <i>optional</i>	IATA code of the board point of the segment. Example : "LHR"	string
id <i>optional</i>	ID of the segment, which comprises of segment departure date + boardPoint + offPoint. Example : "2018-09-17-LHR-CDG"	string
legIds <i>optional</i>	List of the ids of the legs which are contained in this segment. Example : "LHR-CDG"	< string > array
numberOfLegs <i>optional</i>	Number of legs contained in this segment. Example : 1	integer
offFlightPointId <i>optional</i>	ID of the FlightPoint that represents the arrival point of the segment. Example : "CDG_2"	string
offPointIataCode <i>optional</i>	IATA code of the off point of the segment. Example : "CDG"	string
partnerships <i>optional</i>	Provides the information of the partnership flight of the main flight. If the main flight is operating, then marketing flight(s) information is populated. Else if the main flight is marketing, then the operating flight information is populated.	partnerships
scheduledArrivalDateTime <i>optional</i>	'Scheduled arrival date and time of the segment(in LT), ISO format yyyy-mm-ddThh:mm:ss'. Example : "2018-09-17T14:45:00"	string (datetime)
scheduledDepartureDateTime <i>optional</i>	'Scheduled departure date and time of the segment(in LT), ISO format yyyy-mm-ddThh:mm:ss'. Example : "2018-09-17T12:40:00"	string (datetime)

Name	Description	Schema
trafficRestrictions <i>optional</i>	List of traffic restriction codes set on this segment. Example : "[D,A]"	< string > array

partnerships

Name	Description	Schema
marketingFlights <i>optional</i>		< marketingFlights > array
operatingFlight <i>optional</i>	This property is populated only when the main flight is a marketing flight.	operatingFlight

marketingFlights

Name	Description	Schema
flightDesignator <i>optional</i>		FlightDesignator
id <i>optional</i>	Marketing flight ID. Example : "8X-9623-2018-09-17"	string

operatingFlight

Name	Description	Schema
flightDesignator <i>optional</i>		FlightDesignator
id <i>optional</i>	Operating flight ID. Example : "7X-346-2018-09-17"	string

ScheduleFlightDataPush

Name	Description	Schema
events <i>optional</i>		Events
meta <i>optional</i>		Meta

Name	Description	Schema
previousRecord <i>optional</i>	List of JSON Patches as defined by RFC 6902 (see https://tools.ietf.org/html/rfc6902) to apply to DatedFlight [latest version] in order to obtain the actual JSON of the previous DatedFlight version.	< PatchOperation > array
scheduleProcessedFlight <i>optional</i>		DatedFlight

issueSource

an object containing references to the source of the error

Name	Description	Schema
parameters <i>optional</i>	a string indicating which URI query parameter caused the issue	string
pointer <i>optional</i>	a JSON Pointer [RFC6901] to the associated entity in the request document	string