

ยินดีต้อนรับสู่

CYBER SECURITY WORKSHOP



Bangkok
8-9 May 2019


The material in these slides is based on Karst Koymans' CIA course material, see: <https://www.os3.nl/2020-2021/courses/cia/start>

Required!

- RFC2182:
 - “The DNS requires that multiple servers exist for every zone”
- Why?
 - Resilience
 - Spread the Load
- How?


Zone transfers

- Pull
 - When Secondary starts without data
 - Query Type AXFR (Authoritative Transfer)




Zone transfers

- Pull
 - When data changed
 - Slave checks after SOA refresh time
 - Query Type IXFR (Incremental Transfer)
 - Include known SOA in authority section




Zone transfers

- Push
 - Special opcode (4) NOTIFY
- Slave behaves as if SOA refresh timed out




Zone transfers

- Zone transfers are often limited to slave servers
 - DNS data: public or semipublic?
 - IP level ACL... safe enough?




Zone transfers

- Zone transfers are often limited to secondaries
 - DNS data: public or semipublic?
 - IP level ACL... safe enough?



Transaction Signature: TSIG


- TSIG (RFC2845)
- Shared secret




■ Symmetric encryption

Transaction security with TSiG

- Hash based Message Authentication Code (HMAC)



■ Create signature



■ Verify signature

Transaction security with TSIG

- TSIG (RFC2845)
- Shared secret
 - Communicated out of band
 - Secret in configuration, **NOT** in zone data!
- Hash based Message Authentication Code (HMAC)
 - Provides mutual Authenticity & Integrity
 - Does not provide confidentiality

Lab time!



- Hands on: <http://bangkok.lol/>
- 4. Setup a redundant authoritative name server for your domain