

A decorative wavy line in orange and white, running vertically along the left side of the slide.

React

Introducing JSX

Content

1. Why JSX?
2. What JSX?
3. Embedding Expressions in JSX
4. JSX is an Expression
5. Specifying Attributes with JSX
6. JSX Represents Objects
7. Specifying Children with JSX
8. HTML to JSX

1. Why JSX?

- React embraces the fact that rendering logic is inherently coupled with other UI logic:
 - how events are handled.
 - how the state changes over time.
 - how the data is prepared for display.
- Instead of artificially separating *technologies* by putting markup and logic in separate files, React **separates concerns** with loosely coupled units called “**components**” that contain both.
- React doesn't require using JSX, but most people find it helpful as a visual aid when working with UI inside the JavaScript code. It also allows React to show more useful error and warning messages.

2. What JSX?

- Special dialect of JS (its no HTML)
- Browsers don't understand JSX code! We write JSX then run tools to convert it into normal JS
- Very similar in form and function to HTML with a couple differences
- JSX vs HTML
 - Adding custom styling to an element uses different syntax
 - Adding a class to an element uses different syntax
 - JSX can reference JS variables

3. Embedding Expressions in JSX

```
function App() {  
  const name = "Dany";  
  return (  
    <h1>  
      Hello {name}! I'm {2021 - 1981} years old.  
    </h1>  
  );  
}
```

```
function App() {  
  function formatName(user) {  
    return user.lastName + " " + user.firstName;  
  }  
  const user = {  
    firstName: "Danh",  
    lastName: "Lê Thanh",  
  };  
  return <h1>Hello {formatName(user)}!</h1>;  
}
```

4. JSX is an Expression

After compilation, **JSX** expressions become regular JavaScript **function** calls and evaluate to JavaScript objects. This means that you can use **JSX** inside of **if** statements and **for** loops, **assign** it to **variables**, **accept** it as **arguments**, and **return** it from **functions**.

```
function App() {  
  function formatName(user) {  
    return user.lastName + " " + user.firstName;  
  }  
  function getGreeting(user) {  
    if (user) {  
      return <h1>Hello, {formatName(user)}!</h1>;  
    } else {  
      return <h1>Hello, Stranger.</h1>;  
    }  
  }  
  const user = { firstName: "Dan", lastName: "Lê Thanh" };  
  return getGreeting(user);  
}
```

5. Specifying Attributes with JSX

You may use quotes to specify string literals as attributes or curly braces to embed a JavaScript expression in an attribute.

```
function App() {  
  const emailSample = "admin@yahoo.com";  
  return (  
    <div>  
      <label htmlFor="txtEmail">Email: </label>  
      <input id="txtEmail" type="email" placeholder={emailSample} />  
    </div>  
  );  
}  
  
export default App;
```

Note: Don't put quotes around curly braces when embedding a JavaScript expression in an attribute.

6. JSX Represents Objects

Babel compiles JSX down to `React.createElement()` calls

```
const element = (  
  <h1 className="greeting">  
    Hello, world!  
  </h1>  
);
```

```
const element = React.createElement(  
  'h1',  
  {className: 'greeting'},  
  'Hello, world!'  
);
```


7. Specifying Children with JSX

```
function App() {  
  return (  
    <div>  
      <h1>Hello!</h1>  
      <h2>Good to see you here.</h2>  
    </div>  
  );  
}
```

```
import { Fragment } from "react";
```

```
function App() {  
  return (  
    <Fragment>  
      <h1>Hello!</h1>  
      <h2>Good to see you here.</h2>  
    </Fragment>  
  );  
}
```

▼ <div id="root"> event

▼ <div>

```
  <h1>Hello!</h1>  
  <h2>Good to see you here.</h2>  
</div>  
</div>
```

▼ <div id="root"> event

```
  <h1>Hello!</h1>  
  <h2>Good to see you here.</h2>  
</div>
```

```
function App() {  
  return (  
    <>  
      <h1>Hello!</h1>  
      <h2>Good to see you here.</h2>  
    </>  
  );  
}
```

8. HTML to JSX

Enter name:

Submit

■ HTML

```
<body>
  <label class="label" for="name">Enter name:</label>
  <input type="text" id="name">
  <button style="background-color: ■blue; color: □white">Submit</button>
</body>
```

■ JSX

```
return (
  <div>
    <label className="label" htmlFor="name">Enter name:</label>
    <input id="name" type="text" />
    <button style={{backgroundColor: 'blue', color: 'white'}}>Submit</button>
  </div>
);
```

Differences In Attributes

- All DOM properties and attributes (including event handlers) should be **lower camelCased**. Ex: tabIndex, onClick, readOnly, ...
- The exception is **aria-*** and **data-*** attributes, which should be **lowercased**. Ex: aria-label, data-id, ...
- **checked**, **defaultChecked**: for controlled and uncontrolled component.
- **value**, **defaultValue**: for controlled and uncontrolled component.
- **className** ⇔ class in HTML
- **htmlFor** ⇔ for in HTML

- **onChange:**

Realtime change (in HTML, fire when data changed)

- **selected:**

If you want to mark an `<option>` as selected, reference the **value** attribute of that **option** in the **value** of its `<select>` instead. Check out ["The select Tag"](#) for detailed instructions.


- **style**

The style attribute accepts a JavaScript object with **lower camelCased** properties rather than a CSS string. Ex: `backgroundColor`, `fontWeight`, ...

- **Tag validation**

Validate opening & closing tag. Ex: `<input type="text" />`

Exercise: HTML to JSX

 **Sale System**

Logout

Trainer

Trainer List

Create a Trainer

Teams

Team List

Create a Team

Trainees

Trainees

Courses

Courses

Syllabus

Syllabus

CREATE CLASS

Class No.	<input type="text"/>
Class Name	<input type="text"/>
Start Date	<input type="text" value="mm / dd / yyyy"/>
End Date	<input type="text" value="mm / dd / yyyy"/>
Class Is Open	<input type="radio"/> Yes <input checked="" type="radio"/> No
Level	<input type="range" value="5"/>
Note	<div><div></div></div>
<div><div>Save</div><div>Back</div></div>	



THE END