

# Deep Generative Models

## Lecture 9

Roman Isachenko

Moscow Institute of Physics and Technology

Autumn, 2021

# Recap of previous lecture

## Standart ELBO

$$p(\mathbf{x}|\boldsymbol{\theta}) \geq \mathcal{L}(\boldsymbol{\phi}, \boldsymbol{\theta}) = \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \boldsymbol{\phi})} \log \frac{p(\mathbf{x}, \mathbf{z}|\boldsymbol{\theta})}{q(\mathbf{z}|\mathbf{x}, \boldsymbol{\phi})} \rightarrow \max_{\boldsymbol{\phi}, \boldsymbol{\theta}}.$$

## Expressive flow-based VAE posterior

$$\log q(\mathbf{z}^*|\mathbf{x}, \boldsymbol{\phi}, \boldsymbol{\lambda}) = \log q(\mathbf{z}|\mathbf{x}, \boldsymbol{\phi}) + \log \det \left| \frac{\partial f(\mathbf{z}, \boldsymbol{\lambda})}{\partial \mathbf{z}} \right|$$

## ELBO with flow-based posterior

$$\begin{aligned} \mathcal{L}(\boldsymbol{\phi}, \boldsymbol{\theta}, \boldsymbol{\lambda}) &= \mathbb{E}_{q(\mathbf{z}^*|\mathbf{x}, \boldsymbol{\phi}, \boldsymbol{\lambda})} [\log p(\mathbf{x}, \mathbf{z}^*|\boldsymbol{\theta}) - \log q(\mathbf{z}^*|\mathbf{x}, \boldsymbol{\phi}, \boldsymbol{\lambda})] = \\ &= \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \boldsymbol{\phi})} \left[ \log p(\mathbf{x}, \mathbf{z}^*|\boldsymbol{\theta}) - \log q(\mathbf{z}|\mathbf{x}, \boldsymbol{\phi}) + \log \left| \det \left( \frac{\partial f(\mathbf{z}, \boldsymbol{\lambda})}{\partial \mathbf{z}} \right) \right| \right]. \end{aligned}$$

- ▶ Obtain samples  $\mathbf{z}$  from the encoder  $q(\mathbf{z}|\mathbf{x}, \boldsymbol{\phi})$ .
- ▶ Apply flow model  $\mathbf{z}^* = f(\mathbf{z}, \boldsymbol{\lambda})$ .
- ▶ Compute likelihood for  $\mathbf{z}^*$  using the decoder, base distribution for  $\mathbf{z}^*$  and the Jacobian.

# Recap of previous lecture

## Expressive flow-based VAE posterior

$$\log q(\mathbf{z}^*|\mathbf{x}, \phi, \lambda) = \log q(\mathbf{z}|\mathbf{x}, \phi) + \log \det \left| \frac{\partial f(\mathbf{z}, \lambda)}{\partial \mathbf{z}} \right|$$

## Expressive flow-based VAE prior

$$\log p(\mathbf{z}|\lambda) = \log p(\epsilon) + \log \det \left| \frac{d\epsilon}{d\mathbf{z}} \right|; \quad \mathbf{z} = g(\epsilon, \lambda) = f^{-1}(\epsilon, \lambda)$$

## Theorem

VAE with the AF prior for latent code  $\mathbf{z}$  is equivalent to using the IAF posterior for latent code  $\epsilon$ .

$$\begin{aligned} \mathcal{L}(\phi, \theta, \lambda) &= \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \phi)} \log p(\mathbf{x}|\mathbf{z}, \theta) - \underbrace{KL(q(\mathbf{z}|\mathbf{x}, \phi) || p(\mathbf{z}|\lambda))}_{\text{flow-based prior}} \\ &= \mathbb{E}_{q(\mathbf{z}|\mathbf{x}, \phi)} \log p(\mathbf{x}|\mathbf{z}, \theta) - \underbrace{KL(q(\mathbf{z}|\mathbf{x}, \phi, \lambda) || p(\mathbf{z}))}_{\text{flow-based posterior}} \end{aligned}$$

## Recap of previous lecture

Images are discrete data flow is a continuous model. We need to convert a discrete data distribution to a continuous one.

### Uniform dequantization bound

$$\mathbf{x} \sim \text{Categorical}(\boldsymbol{\pi}), \quad \mathbf{u} \sim U[0, 1], \quad \mathbf{y} = \mathbf{x} + \mathbf{u} \sim \text{Continuous}$$


$$\log P(\mathbf{x}|\boldsymbol{\theta}) \geq \int_{U[0,1]} \log p(\mathbf{x} + \mathbf{u}|\boldsymbol{\theta}) d\mathbf{u}.$$

### Variational dequantization bound

Introduce variational dequantization noise distribution  $q(\mathbf{u}|\mathbf{x})$  and treat it as an approximate posterior.

$$\log P(\mathbf{x}|\boldsymbol{\theta}) \geq \int q(\mathbf{u}|\mathbf{x}) \log \frac{p(\mathbf{x} + \mathbf{u}|\boldsymbol{\theta})}{q(\mathbf{u}|\mathbf{x})} d\mathbf{u} = \mathcal{L}(q, \boldsymbol{\theta}).$$

# Recap of previous lecture



## Flow model for dequantization

$$q(\mathbf{u}|\mathbf{x}) = p(h^{-1}(\mathbf{u}, \phi)) \cdot \left| \det \frac{\partial h^{-1}(\mathbf{u}, \phi)}{\partial \mathbf{u}} \right|.$$

## Variational dequantization bound

$$\mathcal{L}(q, \theta) = \int q(\mathbf{u}|\mathbf{x}) \log \frac{p(\mathbf{x} + \mathbf{u}|\theta)}{q(\mathbf{u}|\mathbf{x})} d\mathbf{u}.$$

---

Ho J. et al. Flow++: Improving Flow-Based Generative Models with Variational Dequantization and Architecture Design, 2019

# Recap of previous lecture

## Disentanglement learning

A disentangled representation is a one where single latent units are sensitive to changes in single generative factors, while being invariant to changes in other factors.

## $\beta$ -VAE

$$\mathcal{L}(q, \theta, \beta) = \mathbb{E}_{q(\mathbf{z}|\mathbf{x})} \log p(\mathbf{x}|\mathbf{z}, \theta) - \beta \cdot KL(q(\mathbf{z}|\mathbf{x})||p(\mathbf{z})).$$


Representations becomes disentangled by setting a stronger constraint with  $\beta > 1$ . However, it leads to poorer reconstructions and a loss of high frequency details.

## ELBO surgery

$$\frac{1}{n} \sum_{i=1}^n \mathcal{L}_i(q, \theta, \beta) = \underbrace{\frac{1}{n} \sum_{i=1}^n \mathbb{E}_{q(\mathbf{z}|\mathbf{x}_i)} \log p(\mathbf{x}_i|\mathbf{z}, \theta)}_{\text{Reconstruction loss}} - \underbrace{\beta \cdot \mathbb{I}_q[\mathbf{x}, \mathbf{z}]}_{\text{MI}} - \underbrace{\beta \cdot KL(q(\mathbf{z})||p(\mathbf{z}))}_{\text{Marginal KL}}$$



Higgins I. et al. *beta-VAE: Learning Basic Visual Concepts with a Constrained Variational Framework*, 2017





## ELBO

$$\mathcal{L}(q, \theta, \beta) = \mathbb{E}_{q(\mathbf{z}|\mathbf{x})} \log p(\mathbf{x}|\mathbf{z}, \theta) - \beta \cdot KL(q(\mathbf{z}|\mathbf{x})||p(\mathbf{z})).$$

## ELBO surgery

$$\frac{1}{n} \sum_{i=1}^n \mathcal{L}_i(q, \theta, \beta) = \underbrace{\frac{1}{n} \sum_{i=1}^n \mathbb{E}_{q(\mathbf{z}|\mathbf{x}_i)} \log p(\mathbf{x}_i|\mathbf{z}, \theta)}_{\text{Reconstruction loss}} - \underbrace{\beta \cdot \mathbb{I}_q[\mathbf{x}, \mathbf{z}]}_{\text{MI}} - \underbrace{\beta \cdot KL(q(\mathbf{z})||p(\mathbf{z}))}_{\text{Marginal KL}}$$

## Minimization of MI

- ▶ It is not necessary and not desirable for disentanglement.
- ▶ It hurts reconstruction.

# DIP-VAE

## Disentangled aggregated variational posterior

$$q(\mathbf{z}) = \frac{1}{n} \sum_{i=1}^n q(\mathbf{z}|\mathbf{x}) = \prod_{j=1}^d q(z_j)$$

## DIP-VAE Objective

$$\begin{aligned}\mathcal{L}_{\text{DIP}}(q, \theta) &= \frac{1}{n} \sum_{i=1}^n \mathcal{L}_i(q, \theta) - \lambda \cdot KL(q(\mathbf{z})||p(\mathbf{z})) = \\ &= \frac{1}{n} \sum_{i=1}^n [\mathbb{E}_{q(\mathbf{z}|\mathbf{x}_i)} \log p(\mathbf{x}_i|\mathbf{z}, \theta) - KL(q(\mathbf{z}|\mathbf{x}_i)||p(\mathbf{z}))] - \lambda \cdot KL(q(\mathbf{z})||p(\mathbf{z})) = \\ &= \underbrace{\frac{1}{n} \sum_{i=1}^n [\mathbb{E}_{q(\mathbf{z}|\mathbf{x}_i)} \log p(\mathbf{x}_i|\mathbf{z}, \theta)]}_{\text{Reconstruction loss}} - \underbrace{\mathbb{I}_q[\mathbf{x}, \mathbf{z}]}_{\text{MI}} - \underbrace{(1 + \lambda) \cdot KL(q(\mathbf{z})||p(\mathbf{z}))}_{\text{Marginal KL}}\end{aligned}$$

# DIP-VAE

$$\mathcal{L}_{\text{DIP}}(q, \theta) = \frac{1}{n} \sum_{i=1}^n \mathcal{L}_i(q, \theta) - \lambda \cdot \underbrace{KL(q(\mathbf{z}) || p(\mathbf{z}))}_{\text{intractable}}$$

Let match the moments of  $q(\mathbf{z})$  and  $p(\mathbf{z})$ :

$$\text{cov}_{q(\mathbf{z})}(\mathbf{z}) = \mathbb{E}_{q(\mathbf{z})} \left[ (\mathbf{z} - \mathbb{E}_{q(\mathbf{z})}(\mathbf{z}))(\mathbf{z} - \mathbb{E}_{q(\mathbf{z})}(\mathbf{z}))^T \right]$$


DIP-VAE regularizes  $\text{cov}_{q(\mathbf{z})}(\mathbf{z})$  to be close to the identity matrix.

## Objective

$$\max_{q, \theta} \left[ \frac{1}{n} \sum_{i=1}^n \mathcal{L}_i(q, \theta) - \lambda_1 \sum_{i \neq j} [\text{cov}_{q(\mathbf{z})}(\mathbf{z})]_{ij}^2 - \lambda_2 \sum_i \left( [\text{cov}_{q(\mathbf{z})}(\mathbf{z})]_{ii} - 1 \right)^2 \right]$$

# DIP-VAE

Reconstructions become better.



---

Kumar A., Sattigeri P., Balakrishnan A. *Variational Inference of Disentangled Latent Concepts from Unlabeled Observations*, 2017

# Challenging Disentanglement Assumptions

## Theorem

Let  $\mathbf{z} \sim P$  with a density  $p(\mathbf{z}) = \prod_{i=1}^d p(z_i)$ . Then, there exists an **infinite** family of bijective functions  $f : \text{supp}(\mathbf{z}) \rightarrow \text{supp}(\mathbf{z})$ :

- ▶  $\frac{\partial f_i(\mathbf{z})}{\partial z_j} \neq 0$  for all  $i$  and  $j$  ( $\mathbf{z}$  and  $f(\mathbf{z})$  are completely entangled);
- ▶  $P(\mathbf{z} \leq \mathbf{u}) = P(f(\mathbf{z}) \leq \mathbf{u})$  for all  $\mathbf{u} \in \text{supp}(\mathbf{z})$ .


Consider a generative model with disentangled representation  $\mathbf{z}$ .

- ▶  $\exists \hat{\mathbf{z}} = f(\mathbf{z})$  where  $\hat{\mathbf{z}}$  is completely entangled with respect to  $\mathbf{z}$ .
- ▶ The disentanglement method cannot distinguish between the two equivalent generative models:

$$p(\mathbf{x}) = \int p(\mathbf{x}|\mathbf{z})p(\mathbf{z})d\mathbf{z} = \int p(\mathbf{x}|\hat{\mathbf{z}})p(\hat{\mathbf{z}})d\hat{\mathbf{z}}.$$

Theorem claims that unsupervised disentanglement learning is impossible for arbitrary generative models with a factorized prior.

# Challenging Disentanglement Assumptions




Dataset = Noisy-dSprites

BetaVAE Score (A)	100	80	44	41	46	37
FactorVAE Score (B)	80	100	49	52	25	38
MIG (C)	44	49	100	76	6	42
DCI Disentanglement (D)	41	52	76	100	-8	38
Modularity (E)	46	25	6	-8	100	13
SAP (F)	37	38	42	38	13	100
	(A)	(B)	(C)	(D)	(E)	(F)

Locatello F. et al. *Challenging Common Assumptions in the Unsupervised Learning of Disentangled Representations*, 2018

# Generative models zoo



# Likelihood based models

Is likelihood a good measure of model quality?

Poor likelihood  
Great samples

$$p_1(\mathbf{x}) = \frac{1}{n} \sum_{i=1}^n \mathcal{N}(\mathbf{x} | \mathbf{x}_i, \epsilon \mathbf{I})$$

For small  $\epsilon$  this model will generate samples with great quality, but likelihood will be very poor.

Great likelihood  
Poor samples

$$p_2(\mathbf{x}) = 0.01p(\mathbf{x}) + 0.99p_{\text{noise}}(\mathbf{x})$$

$$\begin{aligned} \log [0.01p(\mathbf{x}) + 0.99p_{\text{noise}}(\mathbf{x})] &\geq \\ &\geq \log [0.01p(\mathbf{x})] = \log p(\mathbf{x}) - \log 100 \end{aligned}$$

Noisy irrelevant samples, but for high dimensions  $\log p(\mathbf{x})$  becomes proportional to  $m$ .



## Likelihood-free learning

- ▶ Likelihood is not a perfect measure quality measure for generative model.
- ▶ Likelihood could be intractable.

### Where did we start

We would like to approximate true data distribution  $\pi(\mathbf{x})$ . Instead of searching true  $\pi(\mathbf{x})$  over all probability distributions, learn function approximation  $p(\mathbf{x}|\theta) \approx \pi(\mathbf{x})$ .

Imagine we have two sets of samples

- ▶  $\mathcal{S}_1 = \{\mathbf{x}_i\}_{i=1}^{n_1} \sim \pi(\mathbf{x})$  – real samples;
- ▶  $\mathcal{S}_2 = \{\mathbf{x}_i\}_{i=1}^{n_2} \sim p(\mathbf{x}|\theta)$  – generated (or fake) samples.

### Two sample test

$$H_0 : \pi(\mathbf{x}) = p(\mathbf{x}|\theta), \quad H_1 : \pi(\mathbf{x}) \neq p(\mathbf{x}|\theta)$$

Define test statistic  $T(\mathcal{S}_1, \mathcal{S}_2)$ . The test statistic is likelihood free. If  $T(\mathcal{S}_1, \mathcal{S}_2) < \alpha$ , then accept  $H_0$ , else reject it.

# Likelihood-free learning

## Two sample test

$$H_0 : \pi(\mathbf{x}) = p(\mathbf{x}|\boldsymbol{\theta}), \quad H_1 : \pi(\mathbf{x}) \neq p(\mathbf{x}|\boldsymbol{\theta})$$

## Desired behaviour

- ▶  $p(\mathbf{x}|\boldsymbol{\theta})$  minimizes the value of test statistic  $T(\mathcal{S}_1, \mathcal{S}_2)$ .
- ▶ It is hard to find an appropriate test statistic in high dimensions.  $T(\mathcal{S}_1, \mathcal{S}_2)$  could be learnable.

## GAN objective

$$\min_G \max_D V(G, D) = \min_G \max_D [\mathbb{E}_{\pi(\mathbf{x})} \log D(\mathbf{x}) + \mathbb{E}_{p(\mathbf{z})} \log(1 - D(G(\mathbf{z})))]$$

- ▶ **Generator:** generative model  $\mathbf{x} = G(\mathbf{z})$ , which makes generated sample more realistic.
- ▶ **Discriminator:** a classifier  $D(\mathbf{x}) \in [0, 1]$ , which distinguishes real samples from generated samples.

# Vanilla GAN optimality

## Theorem

The minimax game

$$\min_G \max_D V(G, D) = \min_G \max_D [\mathbb{E}_{\pi(\mathbf{x})} \log D(\mathbf{x}) + \mathbb{E}_{p(\mathbf{z})} \log(1 - D(G(\mathbf{z})))]$$

has the global optimum  $\pi(\mathbf{x}) = p(\mathbf{x}|\theta)$ , in this case  $D^*(\mathbf{x}) = 0.5$ .

## Proof (fixed $G$ )

$$\begin{aligned} V(G, D) &= \mathbb{E}_{\pi(\mathbf{x})} \log D(\mathbf{x}) + \mathbb{E}_{p(\mathbf{x}|\theta)} \log(1 - D(\mathbf{x})) \\ &= \int \underbrace{[\pi(\mathbf{x}) \log D(\mathbf{x}) + p(\mathbf{x}|\theta) \log(1 - D(\mathbf{x}))]}_{y(D)} d\mathbf{x} \end{aligned}$$

$$\frac{dy(D)}{dD} = \frac{\pi(\mathbf{x})}{D(\mathbf{x})} - \frac{p(\mathbf{x}|\theta)}{1 - D(\mathbf{x})} = 0 \quad \Rightarrow \quad D^*(\mathbf{x}) = \frac{\pi(\mathbf{x})}{\pi(\mathbf{x}) + p(\mathbf{x}|\theta)}$$

# Vanilla GAN optimality

Proof continued (fixed  $D = D^*$ )

$$\begin{aligned} V(G, D^*) &= \mathbb{E}_{\pi(\mathbf{x})} \log \frac{\pi(\mathbf{x})}{\pi(\mathbf{x}) + p(\mathbf{x}|\theta)} + \mathbb{E}_{p(\mathbf{x}|\theta)} \log \frac{p(\mathbf{x}|\theta)}{\pi(\mathbf{x}) + p(\mathbf{x}|\theta)} \\ &= KL\left(\pi(\mathbf{x}) \parallel \frac{\pi(\mathbf{x}) + p(\mathbf{x}|\theta)}{2}\right) + KL\left(p(\mathbf{x}|\theta) \parallel \frac{\pi(\mathbf{x}) + p(\mathbf{x}|\theta)}{2}\right) - 2 \log 2 \\ &= 2JSD(\pi(\mathbf{x}) \parallel p(\mathbf{x}|\theta)) - 2 \log 2. \end{aligned}$$

Jensen-Shannon divergence (symmetric KL divergence)

$$JSD(\pi(\mathbf{x}) \parallel p(\mathbf{x}|\theta)) = \frac{1}{2} \left[ KL\left(\pi(\mathbf{x}) \parallel \frac{\pi(\mathbf{x}) + p(\mathbf{x}|\theta)}{2}\right) + KL\left(p(\mathbf{x}|\theta) \parallel \frac{\pi(\mathbf{x}) + p(\mathbf{x}|\theta)}{2}\right) \right]$$

Could be used as a distance measure!

$$V(G^*, D^*) = -2 \log 2, \quad \pi(\mathbf{x}) = p(\mathbf{x}|\theta).$$

# Vanilla GAN optimality

## Theorem

The minimax game

$$\min_G \max_D V(G, D) = \min_G \max_D [\mathbb{E}_{\pi(\mathbf{x})} \log D(\mathbf{x}) + \mathbb{E}_{p(\mathbf{z})} \log(1 - D(G(\mathbf{z})))]$$

has the global optimum  $\pi(\mathbf{x}) = p(\mathbf{x}|\theta)$ , in this case  $D^*(\mathbf{x}) = 0.5$ .

## Proof

for fixed  $G$ :

$$D^*(\mathbf{x}) = \frac{\pi(\mathbf{x})}{\pi(\mathbf{x}) + p(\mathbf{x}|\theta)}$$

for fixed  $D = D^*$ :


$$\min_G V(G, D^*) = \min_G [2JSD(\pi||p) - \log 4] = -\log 4, \quad \pi(\mathbf{x}) = p(\mathbf{x}|\theta).$$

If the generator could be any function and the discriminator is optimal at every step, then the generator is guaranteed to converge to the data distribution.

# Vanilla GAN

## Objective

$$\min_G \max_D V(G, D) = \min_G \max_D [\mathbb{E}_{\pi(\mathbf{x})} \log D(\mathbf{x}) + \mathbb{E}_{p(\mathbf{z})} \log(1 - D(G(\mathbf{z})))]$$





- ▶ Generator updates are made in parameter space.
- ▶ Discriminator is not optimal at every step.
- ▶ Generator and discriminator loss keeps oscillating during GAN training.

# Vanishing gradients

## Objective

$$\min_G \max_D V(G, D) = \min_G \max_D [\mathbb{E}_{\pi(\mathbf{x})} \log D(\mathbf{x}) + \mathbb{E}_{p(\mathbf{z})} \log(1 - D(G(\mathbf{z})))]$$

Early in learning,  $G$  is poor,  $D$  can reject samples with high confidence. In this case,  $\log(1 - D(G(\mathbf{z})))$  saturates.



Arjovsky M., Bottou L. *Towards Principled Methods for Training Generative Adversarial Networks*, 2017


# Vanishing gradients

## Objective

$$\min_G \max_D V(G, D) = \min_G \max_D [\mathbb{E}_{\pi(\mathbf{x})} \log D(\mathbf{x}) + \mathbb{E}_{p(\mathbf{z})} \log(1 - D(G(\mathbf{z})))]$$

## Non-saturating GAN

- ▶ Maximize  $\log D(G(\mathbf{z}))$  instead of minimizing  $\log(1 - D(G(\mathbf{z})))$ .
- ▶ Gradients are getting much stronger, but the training is unstable (with increasing mean and variance).



Arjovsky M., Bottou L. *Towards Principled Methods for Training Generative Adversarial Networks*, 2017



# Summary

- ▶  $\beta$ -VAE makes the latent components more independent, but the reconstructions get poorer.
- ▶ DIP-VAE does not make the reconstructions worse using ELBO surgery theorem.
- ▶ Majority of disentanglement learning models use heuristic objective or regularizers to achieve the goal, but the task itself could not be solved without good inductive bias.
- ▶ Likelihood is not a perfect criteria to measure quality of generative model.
- ▶ Adversarial learning suggests to solve minimax problem to match the distributions.
- ▶ Vanilla GAN tries to optimize Jensen-Shannon divergence (in theory).