

Deep Generative Models


Lecture 14

Roman Isachenko

Moscow Institute of Physics and Technology

2023, Autumn

Recap of previous lecture



Theorem (implicit score matching)

$$\frac{1}{2} \mathbb{E}_{\pi} \left\| \mathbf{s}_{\theta}(\mathbf{x}) - \nabla_{\mathbf{x}} \log \pi(\mathbf{x}) \right\|_2^2 = \mathbb{E}_{\pi} \left[\frac{1}{2} \left\| \mathbf{s}_{\theta}(\mathbf{x}) \right\|_2^2 + \text{tr}(\nabla_{\mathbf{x}} \mathbf{s}_{\theta}(\mathbf{x})) \right] + \text{const}$$

1. The left hand side is intractable due to unknown $\pi(\mathbf{x})$ – **denoising score matching**.
2. The right hand side is complex due to Hessian matrix – **sliced score matching (Hutchinson's trace estimation)**.

Recap of previous lecture

Let perturb original data by normal noise $p(\mathbf{x}'|\mathbf{x}, \sigma) = \mathcal{N}(\mathbf{x}'|\mathbf{x}, \sigma^2\mathbf{I})$

$$\pi(\mathbf{x}'|\sigma) = \int \pi(\mathbf{x})p(\mathbf{x}'|\mathbf{x}, \sigma)d\mathbf{x}.$$

Then the solution of

$$\frac{1}{2}\mathbb{E}_{\pi(\mathbf{x}'|\sigma)}\|\mathbf{s}_{\theta}(\mathbf{x}', \sigma) - \nabla_{\mathbf{x}'} \log \pi(\mathbf{x}'|\sigma)\|_2^2 \rightarrow \min_{\theta}$$

satisfies $\mathbf{s}_{\theta}(\mathbf{x}', \sigma) \approx \mathbf{s}(\mathbf{x}', \theta, 0) = \mathbf{s}(\mathbf{x}', \theta)$ if σ is small enough.

Theorem (denoising score matching)

$$\begin{aligned}\mathbb{E}_{\pi(\mathbf{x}'|\sigma)}\|\mathbf{s}_{\theta}(\mathbf{x}', \sigma) - \nabla_{\mathbf{x}'} \log \pi(\mathbf{x}'|\sigma)\|_2^2 &= \\ &= \mathbb{E}_{\pi(\mathbf{x})}\mathbb{E}_{p(\mathbf{x}'|\mathbf{x}, \sigma)}\|\mathbf{s}_{\theta}(\mathbf{x}', \sigma) - \nabla_{\mathbf{x}'} \log p(\mathbf{x}'|\mathbf{x}, \sigma)\|_2^2 + \text{const}(\theta)\end{aligned}$$

Here $\nabla_{\mathbf{x}'} \log p(\mathbf{x}'|\mathbf{x}, \sigma) = -\frac{\mathbf{x}' - \mathbf{x}}{\sigma^2}$.

- ▶ The RHS does not need to compute $\nabla_{\mathbf{x}'} \log \pi(\mathbf{x}'|\sigma)$ and even more $\nabla_{\mathbf{x}'} \log \pi(\mathbf{x}')$.
- ▶ $\mathbf{s}_{\theta}(\mathbf{x}', \sigma)$ tries to **denoise** a corrupted sample.
- ▶ Score function $\mathbf{s}_{\theta}(\mathbf{x}', \sigma)$ parametrized by σ .



Recap of previous lecture

Noise conditioned score network

- ▶ Define the sequence of noise levels: $\sigma_1 > \sigma_2 > \dots > \sigma_L$.
- ▶ Train denoised score function $\mathbf{s}_\theta(\mathbf{x}', \sigma)$ for each noise level:

$$\sum_{l=1}^L \sigma_l^2 \mathbb{E}_{\pi(\mathbf{x})} \mathbb{E}_{p(\mathbf{x}'|\mathbf{x}, \sigma_l)} \left\| \mathbf{s}_\theta(\mathbf{x}', \sigma_l) - \nabla'_{\mathbf{x}} \log p(\mathbf{x}'|\mathbf{x}, \sigma_l) \right\|_2^2 \rightarrow \min_{\theta}$$

- ▶ Sample from **annealed** Langevin dynamics (for $l = 1, \dots, L$).




Outline

1. The worst course overview


Outline

1. The worst course overview

The worst course overview :)



The worst course overview :)



Xiao Z., Kreis K., Vahdat A. Tackling the generative learning trilemma with denoising diffusion GANs, 2021

Summary

