

```

/*
=====
=====
    RaceDay System - Database Creation
    & Population Script
    Target: Microsoft SQL Server
    (SSMS)
    Matches ERD in Section A exactly -
    6 entities:
    Roles, Users, Events, Categories,
    Enrolments, Results

=====
===== */

IF DB_ID('RaceDayDB') IS NOT NULL
BEGIN
    ALTER DATABASE RaceDayDB SET
    SINGLE_USER WITH ROLLBACK IMMEDIATE;
    DROP DATABASE RaceDayDB;
END
GO

CREATE DATABASE RaceDayDB;
GO

```

```

USE RaceDayDB;
GO

/*
=====
=====
TABLE CREATION
=====
===== */

CREATE TABLE Roles (
    RoleID      INT IDENTITY(1,1)
PRIMARY KEY,
    RoleName    NVARCHAR(50) NOT NULL
UNIQUE
);
GO

CREATE TABLE Users (
    UserID      INT IDENTITY(1,1)
PRIMARY KEY,
    FullName    NVARCHAR(150) NOT
NULL,
    Email       NVARCHAR(150) NOT
NULL UNIQUE,
    PasswordHash NVARCHAR(256) NOT
NULL,
    RoleID      INT NOT NULL,

```

```
        CreatedAt          DATETIME2 NOT
NULL DEFAULT SYSDATETIME(),
        CONSTRAINT FK_Users_Roles FOREIGN
KEY (RoleID) REFERENCES Roles(RoleID)
);
GO
```

```
CREATE TABLE Events (
        EventID             INT IDENTITY(1,1)
PRIMARY KEY,
        EventName           NVARCHAR(150) NOT
NULL,
        EventDate           DATE NOT NULL,
        Location            NVARCHAR(200) NOT
NULL,
        Description         NVARCHAR(MAX)
NULL,
        CreatedBy           INT NOT NULL,
        CONSTRAINT FK_Events_Users
FOREIGN KEY (CreatedBy) REFERENCES
Users(UserID)
);
GO
```

```
CREATE TABLE Categories (
        CategoryID          INT IDENTITY(1,1)
PRIMARY KEY,
        EventID             INT NOT NULL,
        CategoryName        NVARCHAR(100) NOT
```

```

NULL,
    Distance          DECIMAL(6,2) NOT
NULL,
    MaxParticipants INT NOT NULL,
    CONSTRAINT FK_Categories_Events
FOREIGN KEY (EventID) REFERENCES
Events(EventID)
);
GO

CREATE TABLE Enrolments (
    EnrolmentID      INT IDENTITY(1,1)
PRIMARY KEY,
    UserID           INT NOT NULL,
    CategoryID       INT NOT NULL,
    EnrolmentDate    DATETIME2 NOT
NULL DEFAULT SYSDATETIME(),
    Status           NVARCHAR(20) NOT
NULL DEFAULT 'Pending'
    CHECK (Status IN ('Pending',
'Confirmed', 'Cancelled')),
    CONSTRAINT FK_Enrolments_Users
FOREIGN KEY (UserID) REFERENCES
Users(UserID),
    CONSTRAINT
FK_Enrolments_Categories FOREIGN KEY
(CategoryID) REFERENCES
Categories(CategoryID),
    CONSTRAINT

```

```

UQ_Enrolments_User_Category UNIQUE
(UserID, CategoryID)
);
GO

CREATE TABLE Results (
    ResultID          INT IDENTITY(1,1)
PRIMARY KEY,
    EnrolmentID      INT NOT NULL
UNIQUE,
    FinishTime       TIME NULL,
    Position          INT NULL,
    Status            NVARCHAR(20) NOT
NULL DEFAULT 'Finished'
    CHECK (Status IN ('Finished',
'DNF', 'DQ')),
    CONSTRAINT FK_Results_Enrolments
FOREIGN KEY (EnrolmentID) REFERENCES
Enrolments(EnrolmentID)
);
GO

/*
=====
=====
DATA POPULATION
=====
===== */

```

```
-- Roles
INSERT INTO Roles (RoleName) VALUES
('Admin'), ('Participant');
GO

-- Users (2 Admins, 4 Participants)
INSERT INTO Users (FullName, Email,
PasswordHash, RoleID) VALUES
('Thabo Nkosi',
'thabo.nkosi@raceday.com',
'HASH_PLACEHOLDER_1', 1),
('Lindiwe Dube',
'lindiwe.dube@raceday.com',
'HASH_PLACEHOLDER_2', 1),
('Sarah Johnson',
'sarah.johnson@raceday.com',
'HASH_PLACEHOLDER_3', 2),
('Michael Botha',
'michael.botha@raceday.com',
'HASH_PLACEHOLDER_4', 2),
('Naledi Mokoena',
'naledi.mokoena@raceday.com', 'HASH_PL
ACEHOLDER_5', 2),
('James Reddy',
'james.reddy@raceday.com',
'HASH_PLACEHOLDER_6', 2);
GO
```

```
-- Events (created by Admin users)
INSERT INTO Events (EventName,
EventDate, Location, Description,
CreatedBy) VALUES
('Johannesburg City Marathon', '2026-
10-11', 'Johannesburg CBD', 'Annual
city marathon through the CBD.', 1),
('Cape Town Trail Run', '2026-
11-08', 'Table Mountain', 'Scenic
trail run with multiple distances.',
2);
GO
```

```
-- Categories (linked to Events)
INSERT INTO Categories (EventID,
CategoryName, Distance,
MaxParticipants) VALUES
(1, '5km Fun Run', 5.00, 200),
(1, '21km Half Marathon', 21.10,
150),
(1, '42km Marathon', 42.20, 100),
(2, '10km Trail', 10.00, 120),
(2, '25km Trail', 25.00, 80);
GO
```

```
-- Enrolments (Participants enrolling
in Categories)
INSERT INTO Enrolments (UserID,
CategoryID, Status) VALUES
```

```

(3, 1, 'Confirmed'),
(4, 2, 'Confirmed'),
(5, 3, 'Confirmed'),
(6, 4, 'Confirmed'),
(3, 5, 'Pending');
GO

-- Results (one per completed
Enrolment)
INSERT INTO Results (EnrolmentID,
FinishTime, Position, Status) VALUES
(1, '00:28:45', 1, 'Finished'),
(2, '01:45:12', 3, 'Finished'),
(3, '03:52:30', 5, 'Finished'),
(4, '00:58:20', 2, 'Finished');
GO

/*
=====
=====
    VERIFICATION QUERIES (optional -
comment out before grading if not
required)

=====
===== */

SELECT * FROM Roles;
SELECT * FROM Users;

```



```
SELECT * FROM Events;  
SELECT * FROM Categories;  
SELECT * FROM Enrolments;  
SELECT * FROM Results;  
GO
```