



Sea-Bird Scientific
13431 NE 20th Street
Bellevue, WA 98005
USA

+1 425-643-9866
seabird@seabird.com
www.seabird.com

SENSOR SERIAL NUMBER: 1842
CALIBRATION DATE: 19-Feb-26

SBE 37 PRESSURE CALIBRATION DATA
508 psia S/N 0201

COEFFICIENTS:

PA0 =	1.170814e-01	PTCA0 =	1.884363e+01
PA1 =	2.414063e-02	PTCA1 =	2.775756e-01
PA2 =	2.099687e-09	PTCA2 =	-2.342336e-03
		PTCB0 =	2.497563e+01
		PTCB1 =	-7.500000e-05
		PTCB2 =	0.000000e+00

PRESSURE SPAN CALIBRATION

THERMAL CORRECTION

PRESSURE (PSIA)	INSTRUMENT OUTPUT (counts)	TEMPERATURE (°C)	COMPUTED PRESSURE (PSIA)	RESIDUAL (%FSR)	TEMP (°C)	INSTRUMENT OUTPUT (counts)
14.42	616.3	21.3	14.42	0.00	32.50	652.33
104.68	4352.9	21.3	104.67	-0.00	29.00	652.38
204.71	8489.6	21.3	204.65	-0.01	24.00	651.34
304.70	12625.4	21.3	304.68	-0.00	18.50	650.64
404.71	16758.7	21.3	404.72	0.00	15.00	649.35
504.74	20887.0	21.3	504.72	-0.01	4.50	647.02
404.69	16759.0	21.3	404.73	0.01	1.00	646.50
304.70	12626.6	21.3	304.71	0.00		
204.69	8491.7	21.3	204.70	0.00	TEMPERATURE (°C)	SPAN
104.69	4354.6	21.3	104.71	0.00	-5.00	24.98
14.43	616.5	21.3	14.43	0.00	35.00	24.97

$$x = \text{instrument output} - \text{PTCA0} - \text{PTCA1} * t - \text{PTCA2} * t^2$$

$$n = x * \text{PTCB0} / (\text{PTCB0} + \text{PTCB1} * t + \text{PTCB2} * t^2)$$

$$\text{pressure (PSIA)} = \text{PA0} + \text{PA1} * n + \text{PA2} * n^2$$

$$\text{Residual (\%FSR)} = (\text{computed pressure} - \text{true pressure}) * 100 / \text{Full Scale Range}$$

